# THE CLEAN AIR ACT ASSESSMENT PACKAGE-1988 (CAP-88) A DOSE AND RISK ASSESSMENT METHODOLOGY FOR RADIONUCLIDE EMISSIONS TO AIR

VOLUME 2

APPENDICES A - H

Prepared By:

Deborah A. Beres
SC&A, Inc.
1311 Dolley Madison Blvd.
McLean, VA 22101

Contract No. 68-D9-0170
Work Assignment 1-28

Prepared For:

U.S. Environmental Protection Agency
Office of Radiation Programs
401 M Street, S.W.
Washington, D.C. 20460

Larry Gray
Work Assignment Manager

October 1990

CONTENTS


LIST OF TABLES . . . . . ii

LIST OF FIGURES . . . . . iii

1. INTRODUCTION . . . . . 1-1
   1.1 ENVIRONMENTAL TRANSPORT . . . . . 1-1
   1.2 ESTIMATION OF DOSE AND RISK . . . . . 1-1
   1.3 LIMITATIONS OF THE CAP-88 METHODOLOGY . . . . . 1-2
   1.4 VERIFICATION OF THE CAP-88 METHODOLOGY . . . . . 1-2
   1.5 REFERENCES FOR PROGRAMS INCLUDED IN CAP-88 . . . . . 1-3

2. HARDWARE/SOFTWARE REQUIREMENTS . . . . . 2-1

3. CAP-88 PACKAGE CONTENTS . . . . . 3-1

4. RUNNING THE CAP-88 PACKAGE . . . . . 4-1
   4.1 PREPAR/AIRDOS-EPA INPUT DATA . . . . . 4-1
   4.2 PREDA/DARTAB INPUT DATA . . . . . 4-30
   4.3 IMPORTANT DIFFERENCES BETWEEN CAP-88 AND EARLIER VERSIONS OF AIRDOS-EPA . . . . . 4-39

5. CAP-88 OUTPUT . . . . . 5-1

6. BACKGROUND INFORMATION AND AIDS TO THE USER . . . . . 6-1

   6.1 EPA ENVIRONMENTAL PATHWAY MODELING ASSUMPTIONS . . . . . 6-1
   6.2 CALCULATION OF $Q_H$ FOR PLUME RISE . . . . . 6-11
   6.3 POPULATION CENSUS FILES . . . . . 6-11
   6.4 STABILITY ARRAYS . . . . . 6-12
   6.5 CALCULATION OF DAUGHTER INGROWTH FACTORS . . . . . 6-16

7. REFERENCES . . . . . 7-1

APPENDIX A: AIRDOS-EPA (AIRDOS2.FOR) PROGRAM FILE

APPENDIX B: PREPAR (PREPAR2.FOR) PROGRAM FILE

APPENDIX C: DARTAB (DARTAB2.FOR) PROGRAM FILE

APPENDIX D: PREDA (PREDA.FOR) PROGRAM FILE

APPENDIX E: SAMPLE.JCL FILE

APPENDIX F: ALLRAD88 DATA FILE

APPENDIX G: SAMPLE PREPAR INPUT ARRAY

APPENDIX H: PRDPOP PROGRAM FILE

APPENDIX I: SAMPLE CAP-88 OUTPUT FILES

CONTENTS
(continued)

APPENDIX J: SAMPLE.SYNOPSIS FILES

APPENDIX K: SECPOP PROGRAM FILES

APPENDIX L: AVAILABLE STAR DATA SETS

APPENDIX M: CHAIN PROGRAM FILES

LIST OF TABLES


Table 3-1. Elements of CAP-88 . . . . . 3-2

Table 4-1. Run identification data . . . . . 4-2

Table 4-2. Data type names and associated NAMELIST names used by PREPAR for scalar and vector variables . . . . . 4-4

Table 4-3. Scalar and vector variable names along with default values and associated NAMELIST names . . . . . 4-5

Table 4-4. Definitions of the PREPAR/AIRDOS-EPA options . . . . . 4-12

Table 4-5. Input variables used in PREPAR/AIRDOS-EPA . . . . . 4-14

Table 4-6. Input variables used in PREPAR. . . . . 4-23

Table 4-7. Data type names used by PREPAR for array input . . . . . 4-27

Table 4-8. Definition of arrays input using PREPAR . . . . . 4-28

Table 4-9. NAMELIST STAR variables . . . . . 4-29

Table 4-10. Cattle densities and vegetable crop distributions for use with AIRDOS-EPA . . . . . 4-31

Table 4-11. Valid PREDA NAMELIST and variable names . . . . . 4-33

Table 4-12. Possible table types output by DARTAB . . . . . 4-38

Table 6-1. Presumed sources of food for urban and rural sites . . . . . 6-1

Table 6-2. AIRDOS-EPA parameters used for generic site assessments . . . 6-3

Table 6-3. Default values used for element dependent factors . . . . . 6-5

Table 6-4. Fatal cancer risk factors for selected radionuclides . . . . 6-8

Table 6-5. Sample STAR data file . . . . . 6-13

Table 6-6. JCL for creating STAR file from National Climatic Data Center data tapes . . . . . 6-15

LIST OF FIGURES

Figure 3-1. CAP-88 program flow chart . . . . . 3-4

# APPENDIX C

## DARTAB (DARTAB2.FOR) PROGRAM FILE

```
0       1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123
C=============================================================================
C     DARTAB...  PROGRAM TO CALCULATE AND PRINT DOSE AND RISK TABLES     -
C     FROM AIRDOS-EPA INTERMEDIATE OUTPUT USING DOSE AND RISK FACTORS    -
C     FROM RADRISK.  C.L.BEGOVICH ORNL/CSD JUNE 1980                     -
C                                                                        -
C     CHLOC, LOCTAB, AND RDSTOR CORRECTED 06/22/82.  C.B.NELSON          -
C     LOCTAB, PREPDR, PREPHR, AND PREPRF CORRECTED 11/05/82.  C.B.NELSON-
C     CHLOC CORRECTED 09/19/83.  C.B.NELSON                              -
C     RDSTOR MODIFIED FOR SPECIAL VALUES OF INHAL F1 11/28/83 C.B.NELSON-
C     MAIN AND RDSTOR MODIFIED FOR EXTENDED HEADER 6/12/84               -
C     6/88 MODIFIED TO DECLARE CHARACTERS AS CHARACTERS NOT REAL * 8      -
C                                                                        -
C                                                                        -
C=============================================================================
      CHARACTER*4 RESP, ANG

      CHARACTER*8 NUCLID,ORGN,CANC,TOTBOD,RNLOC,OGLOC,GEN,OREP,CREP,
     +            RREP,PO218,PB214,BI214,PO214,PULMO,LUNGS,NDP,TDP,
     +            PUL,RREPS

      CHARACTER*80 TITLE, FOOD_ARRAY_INFO

      CHARACTER*36 DATE_AND_TIME
      COMMON / HEADERINFO / DATE_AND_TIME
      INTEGER*2   NUMBER_FILES

      REAL*4 CONVRESP(40)
      LOGICAL GENEFF,OUTPUT
      REAL LLET
      INTEGER RTABLE,DTABLE,TABLE(7),FTABLE,PTLOC,HLLOC,FALOC
      INTEGER ICRP,IHEAD
      LOGICAL SEP_DOSE_LET_TABLES, COMB_DOSE_LET_TABLES,
     +        ALL_DOSE_LET_TABLES
      LOGICAL SEP_RISK_LET_TABLES, COMB_RISK_LET_TABLES,
     +        ALL_RISK_LET_TABLES
      LOGICAL RNFLAG
C
      DIMENSION CONC(4),ILET(2),RREPS(4)

      DIMENSION RNLOC(10), OGLOC(10), OREP(20), RREP(20), CREP(20),
     +          NUCLID(40), CANC(20), ORGN(20), GEN(3), RESP(40)

      COMMON /LOCTBL_CHARS/ RNLOC, OGLOC
      COMMON /WORK_LEVEL_CHARS/ OREP, RREP, CREP
      COMMON /NAMES_CHARS/ NUCLID, CANC, ORGN, GEN
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
1234567890123456789012345678901234567890123456789012345678901234567890123456789012
      NAMELIST /INPUT/ILOC,JLOC,PLOC,AGEX,ILET,DTABLE,RTABLE,FTABLE,
     A  OUTPUT,GSCFAC,ICRP,IHEAD
      NAMELIST /ORGAN/ORGN,NORGN,TIME
      NAMELIST /QFACTR/HLET,LLET
      NAMELIST /CANCER/CANC,NCANC,RELABS
      NAMELIST /RNUCLD/NUCLID,NONCLD,PSIZE,RESP,GIABS
      NAMELIST /LOCTBL/NTLOC,RNLOC,OGLOC,PTLOC,FALOC,HLLOC,LTABLE
      NAMELIST/GENTIC/GENEFF,GEN,NGEN,GRFAC,REPPER,GLLET,GHLET
      COMMON/DOSE_LET_TABLES/SEP_DOSE_LET_TABLES, COMB_DOSE_LET_TABLES,
     +        ALL_DOSE_LET_TABLES
      COMMON/RISK_LET_TABLES/SEP_RISK_LET_TABLES, COMB_RISK_LET_TABLES,
     +        ALL_RISK_LET_TABLES


      COMMON/COMEX/EXPP(20,20,40,4),POP(20,20),POPFAC,TOTFAC, NOL,NOU,
     > NRL,NRU,IDIST(20),ILOC,JLOC
      COMMON/COMOR/NORGN,TIME(20),DOSE(20,40,4,2), DTABLE(7)
      COMMON/LETFAC/HLET(20),LLET(20)
      COMMON/COMCA/NCANC,RELABS(20),RISK(20,40,4,2), RTABLE(7),
     > AGEX,YRLL(20,40,4,2)
      COMMON/COMRF/REF(20,40,4),FTABLE(7)
      COMMON/COMNU/NONCLD,PSIZE(40),GIABS(4,40),
     > INDPOP
         COMMON/COMLOC/PTLOC(10),FALOC(10),
     >   HLLOC(10),LTABLE(10),NTLOC
         COMMON/COMGEN/NGEN,GDOSE(3,40,4,2),GRISK(3,40,4,2),
     >   GENEFF,GRFAC(2),REPPER,GLLET(3),GHLET(3),GREF(3,40,4)
         COMMON/COMRN/WLRN(20,20),
     A   RRISK,RREF(2),RYRLL,NOREP,NRREP,NCREP
         COMMON/COMUS/ARRAY(2010)



         DATA PO218/'PO-218  '/,PB214/'PB-214  '/,BI214/'BI-214  '/,
     A   PO214/'PO-214  '/,PULMO/'PULMNARY'/,LUNGS/'LUNGS    '/,
     B   NDP/'*N-P*    '/,TDP/'*T-B*    '/,PUL/'*PUL*    '/
         DATA TOTBOD/'TOT BODY'/
         DATA RNFLAG/.FALSE./
         DATA ANG /'    '/

          EQUIVALENCE (RESP,CONVRESP)


         DATE_AND_TIME = '                                          '
C***     READ DATA AND TIME PASSED BY PREPAR
         READ (11,1000) DATE_AND_TIME
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

1000    FORMAT (A)

C***    SUPPRESS UNDERFLOW MESSAGES (ERROR CODE 208).
        CALL ERRSET(208,256,-1,1)
C***    SET DEFAULT VALUES.
        OUTPUT=.TRUE.
      ILOC=0
      JLOC=0
      PLOC=100.
      AGEX=70.7565
        REPPER=1.41330E-2
        GSCFAC=.5
      ICRP=1
      IHEAD=1
      NORGN=0
      NCANC=1
      CANC(1)=TOTBOD
      DO 10 J=1,7
      DTABLE(J)=0
      RTABLE(J)=0
      FTABLE(J)=0
   10 CONTINUE
      RTABLE(6)=4
      SEP_DOSE_LET_TABLES  = .FALSE.
      COMB_DOSE_LET_TABLES = .FALSE.
      ALL_DOSE_LET_TABLES  = .FALSE.
      SEP_RISK_LET_TABLES  = .FALSE.
      COMB_RISK_LET_TABLES = .FALSE.
      ALL_RISK_LET_TABLES  = .FALSE.
      ILET(1)=1
      ILET(2)=1
      DO 20 J=1,20
      TIME(J)=70.
      HLET(J)=20.
      LLET(J)=1.
      RELABS(J)=1.
   20 CONTINUE
        NGEN=0
        NOREP=4
        NCREP=1
        NRREP=0
        RREPS(1)=PO218
        RREPS(2)=PB214
        RREPS(3)=BI214
        RREPS(4)=PO214
        CREP(1)=PULMO
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        OREP(1)=LUNGS
        OREP(2)=NDP
        OREP(3)=TDP
        OREP(4)=PUL
      READ(5,11700) TITLE
      READ(5,INPUT)
      IF (IHEAD.EQ.0) ICRP=0
      WRITE(6,11950) IHEAD,ICRP
      WRITE(6,10600) DTABLE,RTABLE,FTABLE
      IF (PLOC.NE.0) WRITE(6,10100)PLOC
      IF (ILET(1).EQ.0.OR.ILET(1).EQ.2) WRITE(6,10200)
      IF (ILET(1).EQ.1.OR.ILET(1).EQ.2) WRITE(6,10300)
      IF (ILET(2).EQ.0.OR.ILET(2).EQ.2) WRITE(6,10400)
      IF (ILET(2).EQ.1.OR.ILET(2).EQ.2) WRITE(6,10500)
C***    ILET = 0 MEANS ONLY TABLES FOR LOW AND HIGH LET SEPARATELY
C***    ILET = 1 MEANS ONLY A TABLE FOR LOW AND HIGH LET COMBINED
C***    ILET = 2 MEANS BOTH SETS OF TABLES
      IF ( ILET(1) .EQ. 0 ) THEN
         SEP_DOSE_LET_TABLES  = .TRUE.
      ELSE IF ( ILET(1) .EQ. 2 ) THEN
         ALL_DOSE_LET_TABLES = .TRUE.
      ELSE
         COMB_DOSE_LET_TABLES  = .TRUE.
      ENDIF
      IF ( ILET(2) .EQ. 0 ) THEN
         SEP_RISK_LET_TABLES  = .TRUE.
      ELSE IF ( ILET(2) .EQ. 2 ) THEN
         ALL_RISK_LET_TABLES  = .TRUE.
      ELSE
         COMB_RISK_LET_TABLES = .TRUE.
      ENDIF
        WRITE(6,11900) GSCFAC
C***    READ IN ORGAN PARAMETERS
   40 READ(5,ORGAN)
      WRITE(6,10700) NORGN
      WRITE(6,10800) (ORGN(I),TIME(I),I=1,NORGN)
      IF (ILET(1).GT.0) READ(5,QFACTR)
      IF (ILET(1).GT.0) WRITE(6,10900) (ORGN(I),LLET(I),HLET(I), I=1,
     > NORGN)
C***    READ IN CANCER PARAMETERS
   50 READ(5,CANCER)
      WRITE(6,11000) NCANC
      WRITE(6,11100) (CANC(I),RELABS(I),I=1,NCANC)
C***    READ IN GENETIC PARAMETERS
        READ(5,GENTIC)
        IF(GENEFF) WRITE(6,11800) (GEN(I),I=1,NGEN)
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        IF(GENEFF) WRITE(6,11850) GRFAC,REPPER
11800   FORMAT('0GENETIC DOSES ARE PRINTED FOR:'/
     <    1X,3(1X,A8))
11850   FORMAT(' THE RISK FACTOR (PER RAD/MILLION BIRTHS)',
     < ' FOR GENETIC DOSE ARE :'/
     <    1X,F8.1,' FOR LOW LET, AND'/
     <    1X,F8.1,' FOR HIGH LET,'/
     < ' AND THE REPLACEMENT RATE FOR THE POPULATION IS :'/
     < 1X,E10.4,' YEAR-1')
C***    CONVERT TO /MRAD/BIRTHS
        GRFAC(1)=GRFAC(1)*1.E-9
        GRFAC(2)=GRFAC(2)*1.E-9
C***    READ IN RADIONUCLIDE PARAMETERS
      READ(5,RNUCLD)
      WRITE(6,11200) NONCLD
      WRITE(6,11300)(NUCLID(I),PSIZE(I),RESP(I), (GIABS(J,I),J=1,4),
     >                I=1,NONCLD)
        DO 30 I=1,NONCLD
        DO 25 K=1,4
        IF(NUCLID(I).EQ.RREPS(K)) GO TO 27
25      CONTINUE
        GO TO 30
27      NRREP=NRREP+1
        RREP(NRREP)=RREPS(K)
30      CONTINUE
        NTLOC=0
        READ(5,LOCTBL)
        IF(NTLOC.EQ.0) GO TO 55
        WRITE(6,11305) NTLOC
        WRITE(6,11310) (RNLOC(I),OGLOC(I),PTLOC(I),FALOC(I),HLLOC(I),
     >  I=1,NTLOC)
55      CONTINUE
11305   FORMAT('0',I2,' LOCATION TABLES ARE TO BE OUTPUT FOR:'/
     >  ' NUCLIDE   ORGAN   PATHWAY   QUANTITY  LET'/
     >  '           OR CANCER'/)
11310   FORMAT(1X,A8,1X,A8,4X,I2,7X,I2,7X,I2)
C***    READ IN DOSE RATES AND HEALTH RISKS
      CALL RDSTOR(OUTPUT,CONVRESP,IHEAD,ICRP)

C***    CHOOSE LOCATION AND FIND EXPOSURES
      CALL CHLOC(PLOC,CONC,GSCFAC,NUCLID, RNFLAG, ANG)

      IF(NORGN.NE.0) CALL RDORGF(ORGN)

        CALL SUMMRY(GSCFAC )
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      IF (NORGN.LE.0) GO TO 70
C***    DECIDE IF LOW AND HIGH LET ARE TO BE SEPARATE TABLES
C***    AND THEN OUTPUT TABLES
      IDO=0
      DO 60 J=1,7
      IF (DTABLE(J).NE.0) IDO=1
      TABLE(J)=DTABLE(J)
   60 CONTINUE
        IF(NTLOC.EQ.0 .OR. IDO.EQ.1) GO TO 67
        DO 65 J=1,NTLOC
        IF(FALOC(J).EQ.1)IDO=1
65      CONTINUE
67      CONTINUE
      IF (IDO.EQ.1) CALL PREPDR(TABLE,TITLE,GSCFAC )

   70 IDO=0
      DO 80 J=1,7
      IF (FTABLE(J).NE.0) IDO=1
   80 TABLE(J)=FTABLE(J)
        IF(NTLOC.EQ.0 .OR. IDO.EQ.1) GO TO 87
        DO 85 J=1,NTLOC
        IF(FALOC(J).EQ.3) IDO=1
85      CONTINUE
87      CONTINUE
      IF (IDO.EQ.1) CALL PREPRF(TABLE,TITLE,GSCFAC )

C***    OUTPUT RISK TABLES
      IDO=0
      DO 90 J=1,7
      IF (RTABLE(J).NE.0) IDO=1
   90 TABLE(J)=RTABLE(J)
        IF(NTLOC.EQ.0 .OR. IDO.EQ.1) GO TO 97
        DO 95 J=1,NTLOC
        IF(FALOC(J).EQ.2)IDO=1
95      CONTINUE
97      CONTINUE
      IF (IDO.EQ.1) CALL PREPHR(TABLE,TITLE,GSCFAC)

C*************************************************************************
C*   OUTPUT THE NEW SYNOPSIS REPORT     ADDED 8/88 BY J.MCGUE       *
C*************************************************************************

      CALL READ_INFO_FOR_SYNOPSIS_RPT( FOOD_ARRAY_INFO, NUMBER_FILES)

      CALL WRITE_SYNOPSIS_REPORT( INDPOP, ORGN, NORGN,
     +                            FOOD_ARRAY_INFO,
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

     +                                NUMBER_FILES, ANG)


      STOP


10100 FORMAT(' TABLES FOR THE SELECTED INDIVIDUAL WILL BE DONE FOR',
     >' THE LOCATION HAVING', F8.2,' % OF THE HIGHEST TOTAL RISK.'/)
10200 FORMAT(' DOSE RATE TABLES FOR LOW AND HIGH LET WILL BE ',
     > 'PRINTED SEPARATELY.')
10300 FORMAT(' DOSE RATE TABLES COMBINING LOW AND HIGH LET ',
     > 'WILL BE PRINTED.')
10400 FORMAT(' HEALTH RISK TABLES FOR LOW AND HIGH LET WILL BE ',
     > 'PRINTED SEPARATELY.')
10500 FORMAT(' HEALTH RISK TABLES COMBINING LOW AND HIGH LET ',
     > 'WILL BE PRINTED.')
10600 FORMAT('00 INDICATES THE TABLE WILL NOT BE PRINTED'/
     A' 1 INDICATES INDIVIDUAL VALUES WILL BE PRINTED'/
     B' 2 INDICATES MEAN INDIVIDUAL VALUES WILL BE PRINTED'/
     C' 3 INDICATES COLLECTIVE VALUES WILL BE PRINTED'/
     D' 4 INDICATES ALL OF THE ABOVE WILL BE PRINTED'//
     > '   QUANTITY      TABLE NO.  1  2  3  4  5  6  7'/
     > '+_____________________________________________'/
     > ' 1.DOSE RATES                ',7(I2,1X)/
     > ' 2.HEALTH RISKS              ',7(I2,1X)/
     > ' 3.RISK EQUIVALENT FACTOR  ',7(I2,1X))
10700 FORMAT('0THERE ARE ',I4,' ORGANS TO BE OUTPUT. THEY ARE:'/)
10800 FORMAT(1X,'ORGAN',4X,'TIME',4X,'ORGAN',4X,'TIME',4X,
     1'ORGAN',4X,'TIME'/
     > (3(1X, A8,2X,F4.0,2X)))
10900 FORMAT('0  ORGAN     DOSE EQUIVALENT FACTORS  '/
     A  '                 LOW LET         HIGH LET'/
     A  (2X,A8,F15.5,1X,F15.4))
11000   FORMAT('0THERE ARE ',I4,' CANCERS TO BE OUTPUT.'/
     > ' A 1 INDICATES ABSOLUTE RISK; A 2 IS RELATIVE RISK.')
11100 FORMAT('   CANCER      CANCER      CANCER      CANCER'/ (1X,4(A8,
     > 1X,F2.0,1X)))
11200 FORMAT('0THERE ARE ',I4,' RADIONUCLIDES TO BE OUTPUT.')
11300 FORMAT('  NUCLIDE  PARTICLE SIZE   CLEARANCE CLASS ',
     > 20X,'G.I. ABSORPTION FRACTION'/49X,'STOMACH',8X,'SI',13X,'ULI',
     >  12X,'LLI'/ (1X,A8,1X,F10.5,6X,10X,A1,4X,4F15.5))
11700 FORMAT(A80)
11900   FORMAT('0THE GROUND SURFACE CORRECTION FACTOR IS ',F5.2/)
11950   FORMAT('0IHEAD=',I2/' ICRP=',I3/)
      END
```

```
0         1         2         3         4         5         6         7
1234567890123456789012345678901234567890123456789012345678901234567890123456789012

C*************************************************************************
C                                                                        *
C                                                                        *
C                                                                        *
C                INPUT AND DATA PREPARATION  ROUTINES                    *
C                                                                        *
C                                                                        *
C                                                                        *
C*************************************************************************



C========================================================================
C                                                                       -
C                      SUBROUTINE RDSTOR                                -
C                                                                       -
C========================================================================

      SUBROUTINE RDSTOR(OUTPUT,CONVRESP,IHEAD,ICRP)


C***    THIS SUBROUTINE READS AND STORES DOSE RATES
C***    AND HEALTH RISKS FOR ORGANS AND CANCERS
C***    THIS SUBROUTINE WAS CORRECTED 6/88 BY JOAN MCGUE..GO TO 40
C***    WAS JUMPING INTO THE LOOP DO 50
C***    THE CHARACTER ARRAYS O,C,OG WERE PULLED OUT OF THE COMMON COMUS
C***    AND MADE LOCAL 6/88


      CHARACTER*8 NUC,NUCLID,ORGN,CANC,GEN,OREP,CREP,RREP
        LOGICAL GENEFF,OUTPUT
      CHARACTER*36 DATE_AND_TIME
      COMMON / HEADERINFO / DATE_AND_TIME
      REAL*8 O,C,OG
      REAL*8 CONVORGN(40),CONVCANC(40),CONVGEN(3),CONVCREP(20)
      INTEGER IHEAD,ICRP
      REAL*4 RESPIN,CONVRESP(40)
      DIMENSION OREP(20), RREP(20), CREP(20),
     +          NUCLID(40), CANC(20), ORGN(20), GEN(3)

      COMMON /WORK_LEVEL_CHARS/ OREP, RREP, CREP
      COMMON /NAMES_CHARS/ NUCLID, CANC, ORGN, GEN
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      INTEGER SAVED_INDEX

      COMMON/COMOR/NORGN,TIME(20),DOSE(20,40,4,2), DTABLE(7)
        COMMON/COMRN/WLRN(20,20),RRISK,RREF(2),RYRLL,NOREP,NRREP,NCREP
      COMMON/COMCA/NCANC,RELABS(20),RISK(20,40,4,2), RTABLE(7),
     >  AGEX,YRLL(20,40,4,2)
      COMMON/COMRF/REF(20,40,4),FTABLE(7)
      COMMON/COMNU/NONCLD,PSIZE(40),GIABS (4,40),
     > INDPOP
      COMMON/COMUS/D(2,40),R(2,40),RF(40),YLL(2,40),
     >             G(2,3),DCHK(20,40),RCHK(20,40),GCHK(3,40)
      COMMON/COMGEN/NGEN,GDOSE(3,40,4,2),GRISK(3,40,4,2),
     >  GENEFF,GRFAC(2),REPPER,GLLET(3),GHLET(3),GREF(3,40,4)

      DIMENSION GIIN(4), O(40), C(40), OG(3)

      LOGICAL*1 FAL,TRU,DCHK,RCHK,GCHK,IW
      DATA TRU/.TRUE./,FAL/.FALSE./,ICRPIN/0/
      DATA SAVED_INDEX / 1/

      EQUIVALENCE (ORGN,CONVORGN),(CANC,CONVCANC),(GEN,CONVGEN),
     +            (CREP,CONVCREP)

C***    ZERO OUT ALL ARRAYS
        NDO=NORGN+1
        DO 35 N=1,2
      DO 30 J=1,4
      DO 30 K=1,NONCLD
      DO 10 L=1,NDO
      DOSE(L,K,J,N)=0.0
        IF(L.GT.NGEN) GO TO 10
        GDOSE(L,K,J,N)=0.0
   10 CONTINUE
      NDO=NCANC+1
      DO 20 L=1,NDO
      RISK(L,K,J,N)=0.0
        YRLL(L,K,J,N)=0.0
      REF(L,K,J)=0.0
        IF(L.GT.NGEN) GO TO 20
        GRISK(L,K,J,N)=0.0
        GREF(L,K,J)=0.0
   20 CONTINUE
   30 CONTINUE
35      CONTINUE
        DO 38 L=1,40
        DO 37 K=1,20
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        DCHK(K,L)=TRU
        RCHK(K,L)=TRU
37      CONTINUE
        DO 39 K=1,3
        GCHK(K,L)=TRU
39      CONTINUE
38      CONTINUE
C***    READ FIRST RECORD
   41 IF (IHEAD.EQ.0) READ(25,END=180) NUC,SIZEIN,RESPIN,GIIN,TIMIN,
     >  IND
      IF (IHEAD.EQ.1) READ(25,END=180) NUC,SIZEIN,RESPIN,GIIN,TIMIN,
     >  IND,ICRPIN


      IF (ICRPIN.EQ.1.AND.ICRP.EQ.0) GO TO 125
        IFIND=0
C***    CHECK TO SEE IF THE RADIONUCLIDE IS IN OUTPUT LIST
      SAVED_INDEX = 1
40    CONTINUE
      DO 50 K= SAVED_INDEX,NONCLD
         IF (NUC.EQ.NUCLID(K)) GO TO 60
   50 CONTINUE
      IF(IFIND.EQ.0) GO TO 125
        GO TO 41
C***    FIND OUT WHAT TYPE OF RECORD FOLLOWS
   60 SAVED_INDEX = K+1

      IRA=IND/10
        IF(IRA.GT.2) GO TO 401
      ICHOS=IND-IRA*10
      IF (ICHOS.NE.2) GO TO 75
      IF (ABS(GIIN(2)-GIABS(2,K)).GT.1.E-2*GIABS(2,K)) GO TO 40
   75 IF (ICHOS.NE.3) GO TO 80
      IF (ABS(SIZEIN-PSIZE(K)).GT.1.E-2*PSIZE(K)) GO TO 40


      IF (RESPIN.NE.CONVRESP(K)) GO TO 40
      IF(GIABS(1,K).NE.0..AND.ABS(GIABS(1,K)-GIIN(2)).GT.
     <  1E-2*GIABS(1,K))  GO TO 40
   80 IF (IND.LE.5) GO TO 130
C***    THE NEXT TWO RECORDS CONTAIN CANCERS AND RISKS
        IF(IFIND.NE.0) GO TO 81
      READ(25) NC,ILET,(C(I),I=1,NC)
        READ(25) ((R(L,I),L=1,ILET),I=1,NC)
        READ(25) ((YLL(L,I),L=1,ILET),I=1,NC)
        READ(25)(RF(I),I=1,NC),TRF
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

81       IFIND=1
         REF(NCANC+1,K,ICHOS-1)=TRF+REF(NCANC+1,K,ICHOS-1)
C***     CHECK TO SEE IF THE CANCER IS IN OUTPUT LIST
       DO 110 I=1,NC
       DO 90 J=1,NCANC


       IF (C(I).EQ.CONVCANC(J)) GO TO 100
    90 CONTINUE
       GO TO 110
C***     THE CANCER NAMES MATCH, NOW DO WE HAVE RELATIVE OR ABS RISK
   100 IF (RELABS(J).NE.IRA) GO TO 110
C***       A MATCH, STORE THE RISK
         RCHK(J,K)=FAL
       RISK(J,K,ICHOS-1,1)=R(1,I)
         YRLL(J,K,ICHOS-1,1)=YLL(1,I)
       IF (ILET.LE.1) GO TO 105
         RISK(J,K,ICHOS-1,2)=R(2,I)
         YRLL(J,K,ICHOS-1,2)=YLL(2,I)
105       REF(J,K,ICHOS-1)=RF(I)
       IF(IND.NE.3) GO TO 110
         DO 106 L=1,NRREP
         IF(NUCLID(K).EQ.RREP(L)) GO TO 107
   106   CONTINUE
         GO TO 110
   107   DO 108 L=1,NCREP


         IF(C(I).EQ.CONVCREP(L)) GO TO 109
   108   CONTINUE
         GO TO 110
   109   RISK(J,K,2,2)=0.0
         YRLL(J,K,2,2)=0.0
   110 CONTINUE
C***     THE RISKS HAVE BEEN STORED OR SKIPPED, GO TO NEXT RECORD
       GO TO 40
C***     SKIP THE RECORDS
   125 READ(25)
       READ(25)
         IF(IND.LE.5 .OR. IND.GT.90) GO TO 41
         READ(25)
         READ(25)
       GO TO 41
C***     THE NEXT TWO RECORDS CONTAIN ORGANS AND DOSE RATES
   130 IF(IFIND.NE.0) GO TO 131
         READ(25) NO,ILET,(O(I),I=1,NO)
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      READ(25) ((D(L,I),L=1,ILET),I=1,NO)
131     IFIND=1
C***    FOR INTERNAL DOSES, ALSO CHECK OTHER NUCLIDE PARAMETERS
C***    CHECK TO SEE IF THE ORGANS ARE ON OUTPUT LIST
  140 DO 170 I=1,NO
      DO 150 J=1,NORGN


      IF (O(I).EQ.CONVORGN(J)) GO TO 160
  150 CONTINUE
        GO TO 170
C***    A MATCH SO STORE THE DOSE
  160 IF(IND.GT.3) GO TO 159
        IF(ABS(TIMIN-TIME(J)).GT.1.E-2*TIME(J)) GO TO 40
159     DOSE(J,K,IND-1,1)=D(1,I)
      IF (ILET.GT.1) DOSE(J,K,IND-1,2)=D(2,I)
        DCHK(J,K)=FAL
        IF(IND.NE.3) GO TO 170
        DO 162 L=1,NRREP
        IF(NUCLID(K).EQ.RREP(L)) GO TO 163
162     CONTINUE
        GO TO 170
163     DO 165 L=1,NOREP
        IF(ORGN(J).EQ.OREP(L)) GO TO 167
165     CONTINUE
        GO TO 170
167     DOSE(J,K,2,2)=0.0
  170 CONTINUE
        IF(IND.LT.4) GO TO 40
        DO 172 I=1,NO
        DO 152 J=1,NGEN


        IF(O(I).EQ.CONVGEN(J)) GO TO 161
152     CONTINUE
        GO TO 172
161     GDOSE(J,K,IND-1,1)=D(1,I)*30.
        IF(ILET.GT.1)GDOSE(J,K,IND-1,2)=D(2,I)*30.
172     CONTINUE
        GO TO 40
C***    DOSES HAVE BEEN SKIPPED OR STORED, GO TO NEXT RECORD
  180 CONTINUE
        IW=TRU
        DO 200 K=1,NONCLD
        DO 200 J=1,NORGN
        IF(.NOT.DCHK(J,K)) GO TO 200
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        IF(IW) WRITE(27,900)
        WRITE(27,901) ORGN(J),NUCLID(K)
        IW=FAL
200     CONTINUE
900     FORMAT('0 THE FOLLOWING NUCLIDES AND ',
     <  'ORGAN DOSE FACTORS WERE NOT FOUND',
     >  ' IN THE INPUT DATA SETS:'/
     >  '   ORGAN  NUCLIDE'/)
901     FORMAT(1X,A8,1X,A8)
        IW=TRU
        DO 300 K=1,NONCLD
        DO 300 J=1,NCANC
        IF(.NOT.RCHK(J,K)) GO TO 300
        IF(IW) WRITE(27,902)
        IW=FAL
902     FORMAT('0THE FOLLOWING NUCLIDES AND ',
     <  'CANCER RISK FACTORS WERE NOT FOUND',
     >  ' IN THE INPUT DATA SETS:'/
     >  '  CANCER  NUCLIDE'/)
        WRITE(27,901) CANC(J),NUCLID(K)
300     CONTINUE
        IF(.NOT.GENEFF) GO TO 706
       IW=TRU
        DO 400 K=1,NONCLD
        DO 400 J=1,NGEN
        IF(.NOT.GCHK(J,K)) GO TO 400
        IF(IW) WRITE(27,903)
        IW=FAL
903     FORMAT('0THE FOLLOWING NUCLIDES AND ',
     <  'GENETIC DOSE FACTORS WERE NOT',
     >  ' FOUND IN THE INPUT DATA SETS:'/
     >  ' GEN.DOSE NUCLIDE')
        WRITE(27,901) GEN(J),NUCLID(K)
400     CONTINUE
        DO 625 J=1,NONCLD
        DO 625 K=3,4
        NGN=NGEN-1
        AVG=0.0
        DO 600 I=1,NGN
        AVG=AVG+GDOSE(I,J,K,1)
600     CONTINUE
        GDOSE(NGEN,J,K,1)=AVG/FLOAT(NGN)
625     CONTINUE
        DO 700 L=1,2
        DO 700 I=1,4
        DO 700 K=1,NONCLD
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        GRISK(1,K,I,L)=GDOSE(3,K,I,L)*GRFAC(L)
700     CONTINUE
        DO 705 I=1,4
        DO 705 K=1,NONCLD
        GREF(1,K,I)=(GRISK(1,K,I,1)+GRISK(1,K,I,2))/(30.*GRFAC(1))
705     CONTINUE
706     IF(OUTPUT) CALL FACOUT(DATE_AND_TIME)

        RETURN
401     IF(IRA.NE.9) GO TO 800
        ICHOS=0
        IF(IND.EQ.98) ICHOS=3
        IF(IND.EQ.99) ICHOS=2
        IF(ICHOS.EQ.0) GO TO 125
        IF(.NOT.GENEFF) GO TO 125
        IF(ICHOS.NE.2) GO TO 507
        IF(ABS(GIIN(2)-GIABS(2,K)).GT.1.E-2*GIABS(2,K)) GO TO 40
 507    IF(ICHOS.NE.3) GO TO 510
        IF(ABS(SIZEIN-PSIZE(K)).GT.1.E-2*PSIZE(K)) GO TO 40

        IF(RESPIN.NE.CONVRESP(K)) GO TO 40
      IF(GIABS(1,K).EQ.0..AND.GIIN(2).GT.1..OR.
     &   GIABS(1,K).NE.0..AND.ABS(GIIN(2)-GIABS(1,K)).GT.
     &   1E-3*GIABS(1,K)) GO TO 40
510     IF(IFIND.NE.0) GO TO 511
        READ(25) NG,LET,(OG(I),I=1,NG)
        READ(25) ((G(L,I),L=1,LET),I=1,NG)
511     IFIND=1
520     DO 530 I=1,NG
        DO 525 J=1,NGEN

        IF(OG(I).EQ.CONVGEN(J)) GO TO 540
525     CONTINUE
        GO TO 530
540     GDOSE(J,K,ICHOS-1,1)=G(1,I)
        IF(LET.GT.1) GDOSE(J,K,ICHOS-1,2)=G(2,I)
        GCHK(J,K)=FAL
530     CONTINUE
        GO TO 40
800     IF(IND.NE.33) GO TO 125
        READ(25) NC,ILET,(C(I),I=1,NC)
        READ(25) ((R(L,I),L=1,ILET),I=1,NC)
        READ(25) ((YLL(L,I),L=1,ILET),I=1,NC)
        READ(25) (RF(I),I=1,NC),TRF
        IFIND=1
        CONVCREP(1)=C(1)
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
```

```
        NCREP=NC
        RRISK=R(1,1)
        RYRLL=YLL(1,1)
        RREF(1)=RF(1)
        RREF(2)=TRF
        GO TO 40
      END

C=======================================================================
C                                                                      -
C                        SUBROUTINE CHLOC                              -
C                                                                      -
C=======================================================================

      SUBROUTINE CHLOC(PLOC,CONC,GSCFAC,NUCLID,RNFLAG,ANG)


      CHARACTER*8 NUC,NUCLID,RADON
      CHARACTER*4 ANGLE, ANG
      CHARACTER*36 DATE_AND_TIME
      COMMON / HEADERINFO / DATE_AND_TIME

      DIMENSION NUCLID(40)

      LOGICAL NFLAG(40),RNFLAG
      DIMENSION CONC(4),FAC(4),IOR(4),GI(4)
      COMMON/COMEX/EXPP(20,20,40,4),POP(20,20),POPFAC,TOTFAC, NOL,NOU,
     > NRL,NRU,IDIST(20),ILOC,JLOC
      COMMON/COMCA/NCANC,RELABS(20),RISK(20,40,4,2), RTABLE(7),
     > AGEX,YRLL(20,40,4,2)
        COMMON/COMRF/REF(20,40,4),FTABLE(7)
      COMMON/COMNU/NONCLD,PSIZE(40),GIABS (4,40),IND
      COMMON/COMRN/WLRN(20,20),RRISK,RREF(2),RYRLL,NOREP,NRREP,NCREP

      COMMON/COMUS/TRISK(20,20)


C     RSKLIN AND POPLIN WERE ADDED FOR THE NEW REPORT 2/8/88.  THEY
C     ARE SEQUENTIAL ARRAYS WHICH WILL STORE THE VALUES OF THE POPULATION
C     AND RISKS IN LINEAR ORDER AS THE SORTED RISK ARRAY.  THE VALUES ARE
C     STORED WITH THE DIRECTIONS DISTANCES TOGETHER IE. N 1, N 2, N 3 ETC.

      DIMENSION ANGLE(16)
      REAL      SRISK(400), RSKLIN(400)
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      REAL      OUTPUT(20,20)
      INTEGER   POPLIN(400)
      LOGICAL   USER_SUPPLIED_IJLOC

C***  FOLLOWING VARS AND COMMON ADDED FOR NEW SYNOPSIS REPORT 9/1988


      REAL PCI_PER_LITER_CONC (20,20)
      REAL WLI, MAX_PCI_LITERS, FATAL_CANCER_RISK, ORGAN_DOSES(20),
     +     PATHWAY_DOSES(4), NUC_DOSES(36)
      INTEGER LOC_DIST
      COMMON / IND_RESULTS / WLI, LOC_DIST, MAX_PCI_LITERS,
     +                       FATAL_CANCER_RISK ,ORGAN_DOSES,
     +                       PATHWAY_DOSES,NUC_DOSES

      REAL  EFFECT_PERSON_REM, PERSON_WORKING_LEVEL,POP_ORGAN_DOSES(20)
      INTEGER IO(400), NLOC, NOP

      COMMON / POPU_RESULTS / POPLIN, RSKLIN, SRISK, IO, NLOC, NOP,
     +                        EFFECT_PERSON_REM, PERSON_WORKING_LEVEL,
     +                        POP_ORGAN_DOSES



C***
      DATA USER_SUPPLIED_IJLOC /.FALSE./
      DATA FAC/2*1.E-5,10.,1000./
      DATA BRTHRT/.83E6/
      DATA RADON/'RN-222  '/
      DATA IOR/3,4,1,2/
      DATA NFLAG/40*.FALSE./
      DATA OUTPUT/400*0.0/, PCI_PER_LITER_CONC / 400 * 0.0 /

        DATA ANGLE/'N   ','NNE ','NE  ','ENE ','E   ',
     A  'ESE ','SE  ','SSE ','S   ','SSW ','SW  ','WSW ',
     B  'W   ','WNW ','NW  ','NNW '/

C***  THE FOLLOWING EQUIVALENCE WAS DELETED ... COULD SEE NO REASON FOR IT
C***  EXCEPT TO SAVE SPACE, HOWEVER THE VALUES IN SRISK NEED TO BE SAVED FOR
C***  THE NEW SYNOPSIS REPORT.  9/1988

CC    EQUIVALENCE(TRISK(1,1),SRISK(1))

        FAC(4)=FAC(4)*GSCFAC
        NOP=JLOC+(ILOC-1)*20
        DO 2 K=1,20
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        DO 2 L=1,20
        POP(L,K)=1.0
        WLRN(L,K)=0.0
        TRISK(L,K)=0.0
2       CONTINUE
      DO 10 K=1,40
      DO 10 J=1,20
        DO 5 I=1,4
        DO 5 L=1,20
5       EXPP(L,J,K,I)=0.0
10      CONTINUE
   20 READ(26,END=110) NUC,SIZE,RSP,GI,TIM,IND
      READ(26)NOL,NOU,NRL,NRU,(IDIST(I),I=NRL,NRU)
      DO 30 J=1,NONCLD
      IF(NFLAG(J)) GO TO 30
      IF(NUC.EQ.NUCLID(J)) GO TO 40
   30 CONTINUE
      GO TO 90
   40 NFLAG(J)=.TRUE.
      IF (NUC.EQ.RADON) GO TO 160
      DO 70 ILO=NOL,NOU
      DO 70 JLO=NRL,NRU
      READ(26) CONC
      DO 50 NC=1,NCANC
      DO 50 L=1,4
      DO 50 N=1,2
      TRISK(JLO,ILO)=TRISK(JLO,ILO)+RISK(NC,J,IOR(L),N)*
     A  CONC(L)*FAC(IOR(L))
   50 CONTINUE
      DO 60 I=1,4
      EXPP(JLO,ILO,J,IOR(I))=CONC(I)
   60 CONTINUE
   70 CONTINUE
   80 IF (IND.EQ.1) READ(26) POP
      GO TO 20
   90 DO 100 ILO=NRL,NRU
      DO 100 JLO=NOL,NOU
      READ(26)
  100 CONTINUE
      IF (IND.EQ.1) READ(26)
      GO TO 20

  110 IF (ILOC.NE.0.AND.JLOC.NE.0) THEN
        USER_SUPPLIED_IJLOC = .TRUE.
        GO TO 130
      ENDIF
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
      LENO=NOU-NOL+1
      LENR=NRU-NRL+1
      NLOC=LENO*LENR
      J=0
      IF (IND.EQ.1) THEN
C   CALCULATE NUMBER DEATHS PER YEAR FOR NEW REPORT 2/8/88
C***  IT SHOULD BE NOTED HERE THAT WHEN MORE TIME PERMITS THIS SHOULD BE
C***  MOVED TO SUBROUTINE POP_RESULTS********

         CALL CALC_DEATHS_PER_YEAR(OUTPUT,NOL,NOU,NRL,NRU,NONCLD,
     +                             EXPP,AGEX,RISK,NCANC,RRISK,
     +                             RNFLAG,WLRN)
      ENDIF
      DO 120 ILO=NOL,NOU
      DO 120 JLO=NRL,NRU
         J = J + 1
         IF(IND .EQ. 1)  THEN
            IF ( POP(ILO,JLO) .NE. 0.0 ) TRISK(JLO,ILO) =
     +           TRISK(JLO,ILO)/POP(ILO,JLO)
C     THE POPULATIONS ARRAY STORES THE DIRECTIONS AND DISTANCES IN
C     THE OPPOSITE ORDER OF THE TRISK ARRAY. IE. N 1, NW 1, NNE 3 ETC.
C     SO ILO AND JLO ARE REVERSED IN ORDER FOR POPLIN TO BE CORRECT.
C***  THESE SHOULD BE MOVED ALSO TO SUB. POP_RESULTS.

            POPLIN(J) = POP(ILO,JLO)
            RSKLIN(J) = OUTPUT(JLO,ILO)
         ENDIF

         SRISK(J)  = TRISK(JLO,ILO)
         IO(J) = J
  120 CONTINUE
      CALL VSORTP(SRISK,NLOC,IO)
      NOP=NLOC*PLOC*.01+.5
      IF (NOP.GE.NLOC) NOP=NLOC
      IF (NOP.LE.1) NOP=1
CC       OUTPUT THE NEW REPORT  ***LEAVE IN FOR NOW FOR DEBUG
CC      IF ( IND .EQ. 1 ) THEN
CC            CALL RISK_FREQ_REPORT(SRISK,POPLIN,RSKLIN,IO,NLOC,NOP)
CC      ENDIF


      LOC=IO(NOP)
      ILOC=(LOC-1)/LENR+1
      JLOC=LOC-(ILOC-1)*LENR
      IF (JLOC.EQ.0) JLOC=NRU
      ILOC=ILOC+NOL-1
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
      JLOC=JLOC+NRL-1
  130 POPFAC=1.
        TOTFAC=1.
        IF (IND.NE.1) GO TO 150
      IF (POP(ILOC,JLOC).NE.0.0) POPFAC=1./POP(ILOC,JLOC)
      TOTPOP=0.0
      DO 140 K1=NRL,NRU
      DO 140 K2=NOL,NOU
  140 TOTPOP=TOTPOP+POP(K2,K1)
      TOTFAC=1./TOTPOP
150      ANG=ANGLE(MOD(17-ILOC,16)+1)
      WRITE(27,101)DATE_AND_TIME
 101  FORMAT('1',T10,'DATE',2X,A)

C***   SAVE VALUES FOR SYNOPSIS REPORT

      IF ( USER_SUPPLIED_IJLOC ) THEN
         WRITE(27,10000) IDIST(JLOC),ANG,TRISK(JLOC,ILOC)
         FATAL_CANCER_RISK = TRISK(JLOC,ILOC)
      ELSE
         WRITE(27,10000) IDIST(JLOC),ANG,SRISK(NOP)
         FATAL_CANCER_RISK = SRISK(NOP)
      ENDIF

      LOC_DIST = IDIST(JLOC)
      MAX_PCI_LITERS = PCI_PER_LITER_CONC(ILOC,JLOC)
C***

      RETURN
  160 CONTINUE
C***    SPECIAL SECTION FOR RADON-222
      RNFLAG = .TRUE.
      DO 190 ILO=NOL,NOU
      DO 190 JLO=NRL,NRU
      READ(26) WFRAC,WLEVEL, PCI_PER_LITER_CONC(ILO,JLO)
  170 EXPP(JLO,ILO,J,3)=WLEVEL*1.E-6/(10.*WFRAC)
        EXPP(JLO,ILO,J,2)=WLEVEL*BRTHRT*8760./(10.*WFRAC)
        EXPP(JLO,ILO,J,1)=0.0
        EXPP(JLO,ILO,J,4)=0.0
        DO 180 N=1,2
        DO 180 K=1,4
        DO 180 NC=1,NCANC
        TRISK(JLO,ILO)=TRISK(JLO,ILO)+RISK(NC,J,K,N)*EXPP(JLO,ILO,J,K)*
     A  FAC(K)
180     CONTINUE
        WLRN(JLO,ILO)=WLEVEL
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        TRISK(JLO,ILO)=TRISK(JLO,ILO)+WLEVEL*RRISK
  190 CONTINUE
        WRITE(27,20100)
20100   FORMAT(' THERE ARE NO GROUND SURFACE CONCENTRATION',
     >  ' OR INGESTION RATE EXPOSURES FOR RN-222.')
       GO TO 80
10000   FORMAT(' THE LOCATION USED FOR THE SELECTED INDIVIDUAL',
     > ' EXPOSURE IS ',/' ==>',I7,' METERS ',A4,'FROM THE SOURCE.'/
     >  ' THE  LIFETIME FATAL CANCER RISK IS ',1PE10.2,'.')
       END

C=======================================================================
C                                                                      -
C                        SUBROUTINE PREPDR                             -
C                                                                      -
C=======================================================================


      SUBROUTINE PREPDR(TABLE,TITLE,GSCFAC)

C     CORRECTED FOR LOCTAB ORGAN/CANCER "SUM" OPTION.  CBN 11/05/82
C***    THIS ROUTINE PREPARES DOSE RATES TO BE OUTPUT.

      CHARACTER*8 ORGN,NUCLID,RNLOC,OGLOC,ORC,ORG,LAST,GEN,OREP,RREP,
     +            CREP,GON, CANC

      CHARACTER*80 TITLE, NOTE, NOT2
      CHARACTER*8 TITL2, TLET
      CHARACTER*32 NUN
      CHARACTER*36 DATE_AND_TIME
      COMMON / HEADERINFO / DATE_AND_TIME


      CHARACTER*40 TITLA, TITLB, TITLGA, TITLGB

      DIMENSION RNLOC(10), OGLOC(10), OREP(20), RREP(20), CREP(20),
     +          NUCLID(40), CANC(20), ORGN(20), GEN(3)

      COMMON /LOCTBL_CHARS/ RNLOC, OGLOC
      COMMON /WORK_LEVEL_CHARS/ OREP, RREP, CREP
      COMMON /NAMES_CHARS/ NUCLID, CANC, ORGN, GEN


      LOGICAL SEP_DOSE_LET_TABLES, COMB_DOSE_LET_TABLES,
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
     +        ALL_DOSE_LET_TABLES
      COMMON/DOSE_LET_TABLES/SEP_DOSE_LET_TABLES, COMB_DOSE_LET_TABLES,
     +        ALL_DOSE_LET_TABLES
         COMMON/HEAD/ORG
         COMMON/COMRN/WLRN(20,20),RRISK,RREF(2),RYRLL,NOREP,NRREP,NCREP
         COMMON/COMWOR/FACO(20,4)
         COMMON/COMGEN/NGEN,GDOSE(3,40,4,2),GRISK(3,40,4,2),
     >   GENEFF,GRFAC(2),REPPER,GLLET(3),GHLET(3),GREF(3,40,4)
         COMMON/COMLOC/PTLOC(10),FALOC(10),
     >   HLLOC(10),LTABLE(10),NTLOC
      REAL LLET
      INTEGER TABLE,FALOC,HLLOC,PTLOC
      DIMENSION TABLE(7),TITLA(3), FACD(4,3),TLET(3),
     >          ITAB(7),TITLB(3),TITLGA(3),TITLGB(3),
     >          FACG(4,3),OFAC(20,20),NUN(3)
      LOGICAL IDO,GENEFF
      COMMON/COMOR/NORGN,TIME(20),DOSE(20,40,4,2)
      COMMON/LETFAC/HLET(20),LLET(20)
      COMMON/COMNU/NONCLD,PSIZE(40),GIABS (4,40),
     > INDPOP
      DATA ORG/' ORGAN  '/,LAST/'WT. SUM '/,GON/' GONAD  '/
      DATA NUN/'(WORKING LEVEL)                    ',
     +        '(WORKING LEVEL)                    ',
     +        '(PERSON WORKING LEVEL)             ' /

      DATA NOTE/'RADON DAUGHTER EXPOSURE:
     +                          '/
      DATA NOT2/'
     +                          '/

      DATA TITLA/'INDIVIDUAL DOSE RATE (MRAD/YEAR)         ',
     +           'MEAN INDIVIDUAL DOSE RATE (MRAD/YEAR)    ',
     +           'COLLECTIVE DOSE RATE (PERSON RAD /YEAR) '/


      DATA TITLB/'INDIVIDUAL DOSE EQ. RATE(MREM/YEAR)      ',
     +           'MEAN INDIVIDUAL DOSE EQ. RATE (MREM/YR) ',
     +           'COLLECTIVE DOSE EQ.  (PERSON REM /YEAR) '/


      DATA TITLGA/'INDIVIDUAL GENETIC DOSE (MRAD)           ',
     +            'MEAN INDIVIDUAL GENETIC DOSE (MRAD)      ',
     +            'COLLECTIVE GENETIC DOSE ( PERSON RAD)    '/


      DATA TITLGB/'INDIVIDUAL GENETIC DOSE EQ. (MREM)       ',
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
     +            'MEAN INDIVIDUAL GENETIC DOSE EQ. (MREM) ',
     +            'COLLECTIVE GENETIC DOSE EQ. (PERSON REM)'/

      DATA TLET/'LOW LET ','HIGH LET','        '/

      DATA FACD/1.,1.,1.,100.,1.,1.,1.,100.,.001,.001,.001,.1/
      DATA FACG/1.,1.,1.,100.,1.,1.,1.,100.,.001,.001,.001,.1/
C*****?????????
C***    MULTIPLY DOSES BY EXPOSURES
C***    PREPARE TABLE FOR HIGH AND LOW LET SEPARATELY
        DO 5 J=1,3
        FACD(4,J)=FACD(4,J)*GSCFAC
        FACG(4,J)=FACG(4,J)*GSCFAC
5       CONTINUE
      DO 50 L=1,2
        TITL2 = TLET(L)
      DO 40 IT=1,3
        DO 42 J=1,NOREP
        DO 42 K=1,1
        OFAC(J,K)=1.
42      CONTINUE
      IDO=.FALSE.
        IF(COMB_DOSE_LET_TABLES) GO TO 35
      DO 30 K=1,7
      ITAB(K)=0
      IF (TABLE(K).NE.IT.AND.TABLE(K).NE.4) GO TO 30
      ITAB(K)=1
      IDO=.TRUE.
   30 CONTINUE
35      CONTINUE
      IF (ITAB(6).NE.0) ITAB(6)=0
        ORC=ORG
      IF (IDO) CALL MULT(IT,FACD(1,IT),DOSE(1,1,1,L),NORGN,ORGN,TITLE,
     > TITLA(IT),ITAB,TITL2,NOTE,NUN(IT),OFAC,OREP,NOREP,20,NUCLID,
     + NONCLD )
        ORC=GON
        IF(IDO.AND.GENEFF) CALL MULT(IT,FACG(1,IT),GDOSE(1,1,1,L),NGEN,
     >  GEN,TITLE,TITLGA(IT),ITAB,TITL2,NOT2,NOT2,0.,0.,0,3,NUCLID,
     +  NONCLD )
C       IF(IT.EQ.2) GO TO 38
        IF(NTLOC.EQ.0) GO TO 38
        DO 45 LL=1,NTLOC
        IF(FALOC(LL).NE.1) GO TO 45
        IF(HLLOC(LL).EQ.1) GO TO 45
        IF(LTABLE(LL).NE.IT .AND. LTABLE(LL).NE.4) GO TO 45
        CALL LOCTAB(IT,RNLOC(LL),PTLOC(LL),OGLOC(LL),FACD(1,IT),
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

     A  DOSE(1,1,1,L),TITLA(IT),TITL2,ORGN,NORGN+1,20,1,NUCLID,
     +  DATE_AND_TIME)

        IF(GENEFF) CALL LOCTAB(IT,RNLOC(LL),PTLOC(LL),OGLOC(LL),
     <  FACG(1,IT),GDOSE(1,1,1,L),TITLGA(IT),TITL2,GEN,NGEN,
     <  3,1,NUCLID, DATE_AND_TIME)

45      CONTINUE
38      CONTINUE
      IF (INDPOP.NE.1) GO TO 50
   40 CONTINUE
   50 CONTINUE
C***    COMBINE HIGH AND LOW LET USING INPUT QUALITY FACTORS
      TITL2 = TLET(3)

      DO 80 I=1,4
      DO 80 J=1,NONCLD
      DO 80 K=1,NORGN
      DOSE(K,J,I,1)=(DOSE(K,J,I,1)*LLET(K)+ DOSE(K,J,I,2)*HLET(K))
      DOSE(NORGN+1,J,I,1)=DOSE(NORGN+1,J,I,1)+DOSE(K,J,I,1)*FACO(K,I)
        IF (K.GT.NGEN) GO TO 80
        GDOSE(K,J,I,1)=(GDOSE(K,J,I,1)*GLLET(K)+GDOSE(K,J,I,2)*GHLET(K))
80      CONTINUE
      DO 100 IT=1,3
      IDO=.FALSE.
        IF(SEP_DOSE_LET_TABLES)  GO TO 95
      DO 90 K=1,6
      ITAB(K)=0
      IF (TABLE(K).NE.IT.AND.TABLE(K).NE.4) GO TO 90
      ITAB(K)=1
      IDO=.TRUE.
   90 CONTINUE
95      CONTINUE
        ORGN(NORGN+1)=LAST
        ORC=ORG
      IF (IDO) CALL MULT(IT,FACD(1,IT),DOSE,NORGN+1,ORGN,TITLE,
     <  TITLB(IT),ITAB,TITL2,NOTE,NUN(IT),OFAC,OREP,NOREP,20,NUCLID,
     +  NONCLD )
        ORC=GON
        IF(IDO.AND.GENEFF) CALL MULT(IT,FACG(1,IT),GDOSE,NGEN,GEN,
     <  TITLE,TITLGB(IT),ITAB,TITL2,NOT2,NOT2,0.,0.,0,3,NUCLID,NONCLD)
C       IF(IT.EQ.2) GO TO 138
        IF(NTLOC.EQ.0) GO TO 138
        DO 135 LL=1,NTLOC
        IF(FALOC(LL).NE.1) GO TO 135
        IF(HLLOC(LL).EQ.0) GO TO 135
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        IF(LTABLE(LL).NE.IT .AND. LTABLE(LL).NE.4) GO TO 135
        CALL LOCTAB(IT,RNLOC(LL),PTLOC(LL),OGLOC(LL),FACD(1,IT),
     >  DOSE,TITLB(IT),TITL2,ORGN,NORGN+1,20,1,NUCLID,
     +  DATE_AND_TIME)


        IF(GENEFF) CALL LOCTAB(IT,RNLOC(LL),PTLOC(LL),OGLOC(LL),
     >  FACG(1,IT),GDOSE,TITLGB(IT),TITL2,GEN,NGEN,3,1,NUCLID,
     +  DATE_AND_TIME)

135     CONTINUE
138     CONTINUE
      IF (INDPOP.NE.1) RETURN
  100 CONTINUE
      RETURN
      END

C-------------------------------------------------------------------------
C                                                                        -
C                        SUBROUTINE PREPHR                               -
C                                                                        -
C-------------------------------------------------------------------------

      SUBROUTINE PREPHR(TABLE,TITLE,GSCFAC)

C     CORRECTED FOR LOCTAB ORGAN/CANCER "SUM" OPTION.  CBN 11/05/82
C***    PREPARE HEALTH RISKS TO BE OUTPUT
      CHARACTER*8 CANC,NUCLID,RNLOC,OGLOC,ORG,CAN,LAST,GEN,RREP,OREP,
     +            CREP, GON, ORGN

      CHARACTER*80 NOTE,NOT2, TITLE
      CHARACTER*32 NUN
      CHARACTER*36 DATE_AND_TIME
      COMMON / HEADERINFO / DATE_AND_TIME

      CHARACTER*8 TLET, TITL2
      CHARACTER*40 TITLA, TITLG

      DIMENSION RNLOC(10), OGLOC(10), OREP(20), RREP(20), CREP(20),
     +          NUCLID(40), CANC(20), ORGN(20), GEN(3)

      COMMON /LOCTBL_CHARS/ RNLOC, OGLOC
      COMMON /WORK_LEVEL_CHARS/ OREP, RREP, CREP
      COMMON /NAMES_CHARS/ NUCLID, CANC, ORGN, GEN
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      LOGICAL SEP_RISK_LET_TABLES, COMB_RISK_LET_TABLES,
     +        ALL_RISK_LET_TABLES
      COMMON/RISK_LET_TABLES/SEP_RISK_LET_TABLES, COMB_RISK_LET_TABLES,
     +        ALL_RISK_LET_TABLES
        COMMON/HEAD/ORG
        COMMON/COMRN/WLRN(20,20),
     A  RRISK,RREF(2),RYRLL,NOREP,NRREP,NCREP
      INTEGER TABLE,FALOC,HLLOC,PTLOC
      LOGICAL IDO,GENEFF
        COMMON/COMLOC/PTLOC(10),FALOC(10),
     >  HLLOC(10),LTABLE(10),NTLOC
        COMMON/COMGEN/NGEN,GDOSE(3,40,4,2),GRISK(3,40,4,2),
     >  GENEFF,GRFAC(2),REPPER,GLLET(3),GHLET(3),GREF(3,40,4)
      DIMENSION TABLE(7),TITLA(3), TLET(3),
     > FACD(4,3),ITAB(7),TITLG(3),FACG(4,3),NUN(3),DRISK(2)

      COMMON/COMCA/NCANC,RELABS(20),RISK(20,40,4,2),RTABLE(7),
     > AGEX,YRLL(20,40,4,2)
      COMMON/COMNU/NONCLD,PSIZE(40),GIABS (4,40),
     > INDPOP
      DATA CAN/' CANCER '/,LAST/'TOTAL   '/,GON/' GONAD  '/
      DATA NOTE/'RADON DAUGHTER EXPOSURE RISK:
     +                         '/
      DATA NOT2/'
     +                         '/
      DATA NUN/'                                  ',
     +        '                                   ',
     +        '(DEATH/YR)                         '/
      DATA TITLA/'INDIVIDUAL LIFETIME RISK (DEATHS)       ',
     +           'MEAN INDIVIDUAL LIFETIME RISK (DEATHS)  ',
     +           'FATAL CANCER RATE (DEATH/YR)            '/

      DATA TITLG/'INDIVIDUAL GENETIC EFFECTS PER BIRTH    ',
     +           'MEAN INDIVIDUAL GENETIC EFFECTS /BIRTH  ',
     +           'COLLECTIVE GENETIC EFFECT(EFFECTIVE/YR) '/

      DATA FACD/2*1.E-5,10.,1000.,2*1.E-5,10.,1000.,4*0./
      DATA FACG/1.,1.,1.,100.,1.,1.,1.,100.,.001,.001,.001,.1/
C*****???????
      DATA TLET/'LOW LET ','HIGH LET','COMB.LET'/
C***    MULTIPLY RISKS BY EXPOSURES
C***    PREPARE HIGH AND LOW LET SEPARATELY
        DO 2 J=1,3
        FACD(4,J)=GSCFAC*FACD(4,J)
        FACG(4,J)=GSCFAC*FACG(4,J)
2       CONTINUE
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      DO 5 J=1,4
        FACG(J,3)=FACG(J,2)*REPPER
5     FACD(J,3)=FACD(J,2)/AGEX
      DO 50 L=1,2
       TITL2 = TLET(L)
        DO 25 I=1,4
        DO 25 J=1,NONCLD
        DO 25 K=1,NCANC
        RISK(NCANC+1,J,I,L)=RISK(K,J,I,L)+RISK(NCANC+1,J,I,L)
25      CONTINUE
        CANC(NCANC+1)=LAST
      DO 40 IT=1,3
      IDO=.FALSE.
        IF(COMB_RISK_LET_TABLES) GO TO 35
      DO 30 K=1,7
      ITAB(K)=0
      IF (TABLE(K).NE.IT.AND.TABLE(K).NE.4) GO TO 30
      IDO=.TRUE.
      ITAB(K)=1
   30 CONTINUE
35      CONTINUE
        ORG=CAN
        DRISK(1)=RRISK
        IF(IT.EQ.3) DRISK(1)=RRISK/AGEX
        DRISK(2)=DRISK(1)
       IF (IDO) CALL MULT(IT,FACD(1,IT),RISK(1,1,1,L),NCANC+1,CANC,TITLE,
     > TITLA(IT),ITAB,TITL2,NOTE,NUN(IT),DRISK,CREP,NCREP,20,NUCLID,
     + NONCLD )
        ORG=GON
        IF(IDO.AND. GENEFF) CALL MULT(IT,FACG(1,IT),GRISK(1,1,1,L),
     >  1,GEN(3),TITLE,TITLG(IT),ITAB,TITL2,NOT2,NOT2,0.,0.,0,3,NUCLID,
     +  NONCLD )
C       IF(IT.EQ.2) GO TO 38
        IF(NTLOC.EQ.0) GO TO 38
        DO 45 LL=1,NTLOC
        IF(FALOC(LL).NE.2) GO TO 45
        IF(HLLOC(LL).EQ.1) GO TO 45
        IF(LTABLE(LL).NE.IT .AND. LTABLE(LL).NE.4) GO TO 45
        CALL LOCTAB(IT,RNLOC(LL),PTLOC(LL),OGLOC(LL),FACD(1,IT),
     >  RISK(1,1,1,L),TITLA(IT),TITL2,CANC,NCANC+1,20,3,NUCLID,
     +  DATE_AND_TIME)

        IF(GENEFF) CALL LOCTAB(IT,RNLOC(LL),PTLOC(LL),OGLOC(LL),
     <  FACG(1,IT),GRISK(1,1,1,L),TITLG(IT),TITL2,
     <  GEN(3),1,3,3,NUCLID, DATE_AND_TIME)
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

45       CONTINUE
38       CONTINUE
       IF (INDPOP.NE.1) GO TO 50
   40 CONTINUE
   50 CONTINUE
C***    COMBINE HIGH AND LOW LET USING INPUT QUALITY FACTORS
       DO 70 I=1,4
       DO 70 J=1,NONCLD
         RISK(NCANC+1,J,I,1)=0.0
       DO 70 K=1,NCANC
       RISK(K,J,I,1)=RISK(K,J,I,1)+RISK(K,J,I,2)
         RISK(NCANC+1,J,I,1)=RISK(NCANC+1,J,I,1)+RISK(K,J,I,1)
         IF(K.GT.1) GO TO 70
         GRISK(K,J,I,1)=GRISK(K,J,I,1)+GRISK(K,J,I,2)
70       CONTINUE
       TITL2 = TLET(3)
       DO 100 IT=1,3
       IDO=.FALSE.
         IF(SEP_RISK_LET_TABLES) GO TO 95
       DO 90 K=1,6
       ITAB(K)=0
       IF (TABLE(K).NE.IT.AND.TABLE(K).NE.4) GO TO 90
       IDO=.TRUE.
       ITAB(K)=1
   90 CONTINUE
95       CONTINUE
         DRISK(1)=RRISK
         IF(IT.EQ.3) DRISK(1)=RRISK/AGEX
         DRISK(2)=DRISK(1)
         ORG=CAN
       IF (IDO) CALL MULT(IT,FACD(1,IT),RISK,NCANC+1,CANC,TITLE,
      +                   TITLA(IT),ITAB,TITL2,NOTE,NUN(IT),DRISK,
      +                   CREP,NCREP,20,NUCLID,NONCLD )
         ORG=GON
         IF(IDO.AND.GENEFF) CALL MULT(IT,FACG(1,IT),GRISK,1,GEN(3),
      >  TITLE,TITLG(IT),ITAB,TITL2,NOT2,NOT2,0.,0.,0,3,NUCLID,NONCLD)
C        IF(IT.EQ.2) GO TO 138
         IF(NTLOC.EQ.0) GO TO 138
         DO 135 LL=1,NTLOC
         IF(FALOC(LL).NE.2) GO TO 135
         IF(HLLOC(LL).EQ.0) GO TO 135
         IF(LTABLE(LL).NE.IT .AND. LTABLE(LL).NE.4) GO TO 135
         CALL LOCTAB(IT,RNLOC(LL),PTLOC(LL),OGLOC(LL),FACD(1,IT),
      >  RISK,TITLA(IT),TITL2,CANC,NCANC+1,20,3,NUCLID,
      +  DATE_AND_TIME)
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        IF(GENEFF) CALL LOCTAB(IT,RNLOC(LL),PTLOC(LL),OGLOC(LL),
     >  FACG(1,IT),GRISK,TITLG(IT),TITL2,GEN(3),1,3,3,NUCLID,
     +  DATE_AND_TIME)

135     CONTINUE
138     CONTINUE
      IF (INDPOP.NE.1) RETURN
  100 CONTINUE
      RETURN
      END

C=======================================================================
C                                                                      =
C                          SUBROUTINE PREPRF                           =
C                                                                      =
C=======================================================================

      SUBROUTINE PREPRF(TABLE,TITLE,GSCFAC)

C     CORRECTED FOR LOCTAB ORGAN/CANCER "SUM" OPTION.  CBN 11/05/82
C***    PREPARE HEALTH EQUIVALENT FACTORS TO BE OUTPUT.

      CHARACTER*8 CANC, NUCLID,LAST,RNLOC,OGLOC,ORC,CAN,GEN,OREP,RREP,
     +            CREP,GON, ORGN, TITL2
      CHARACTER*80 TITLE, NOTE, NOTA
      CHARACTER*40 TITLA, TITLG
      CHARACTER*32 NUN
      CHARACTER*36 DATE_AND_TIME
      COMMON / HEADERINFO / DATE_AND_TIME

      DIMENSION RNLOC(10), OGLOC(10), OREP(20), RREP(20), CREP(20),
     +          NUCLID(40), CANC(20), ORGN(20), GEN(3)

      COMMON /LOCTBL_CHARS/ RNLOC, OGLOC
      COMMON /WORK_LEVEL_CHARS/ OREP, RREP, CREP
      COMMON /NAMES_CHARS/ NUCLID, CANC, ORGN, GEN



        COMMON/COMRN/WLRN(20,20),RRISK,RREF(2),RYRLL,NOREP,NRREP,NCREP
        LOGICAL GENEFF
        COMMON/HEAD/ORC
      COMMON/COMCA/NCANC,RELABS(20),RISK(20,40,4,2)
      COMMON/COMRF/REF(20,40,4),FTABLE(7)
      COMMON/COMNU/NONCLD,PSIZE(40),GIABS (4,40),INDPOP
        COMMON/COMLOC/PTLOC(10),FALOC(10),
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
     >  HLLOC(10),LTABLE(10),NTLOC
        COMMON/COMGEN/NGEN,GDOSE(3,40,4,2),GRISK(3,40,4,2),
     >  GENEFF,GRFAC(2),REPPER,GLLET(3),GHLET(3),GREF(3,40,4)
        INTEGER TABLE,FALOC,HLLOC,PTLOC
        LOGICAL IDO
        DIMENSION TABLE(7),TITLA(3),FACD(4,3),
     > ITAB(7),TITLG(3),FACG(4,3),DREF(2),NUN(3)


        DATA NUN/'(MREM/YR)                          ',
     +          '(MREM/YR)                          ',
     +          '(PERSON REM/YR)                    '/
        DATA CAN/' CANCER '/,GON/' GONAD  '/
        DATA LAST/'W BODY  '/
        DATA NOTE/'RADON DAUGHTER EXPOSURE RISK EQIVALENT:
     +                        '/

        DATA NOTA/'
     +                        '/

           DATA FACD/1.,1.,1.E6,1.E8,1.,1.,1.E6,1.E8,.001,
     A     .001,1.E3,1.E5/
           DATA FACG/1.,1.,1.,100.,1.,1.,1.,100.,.001,.001,.001,.1/

        DATA TITLA/'INDIVIDUAL RISK EQ. RATE (MREM/YEAR)    ',
     +           'MEAN INDIVIDUAL RISK EQ. RATE(MREM/YEAR)',
     +           'COLLECTIVE RISK EQ RATE(PERSON REM/YEAR)'/

        DATA TITLG/'INDIVIDUAL GENETIC RISK EQ. (MREM/YEAR) ',
     +           'MEAN INDIVIDUAL GENETIC RISK EQ.(MREM/Y)',
     +           'COLL. GENETIC RISK EQ. (PERSON REM/YEAR)'/

        DATA TITL2/'        '/
        NCANR=NCANC+1
        CANC(NCANR)=LAST
          CREP(NCREP+1)=LAST
          DO 5 J=1,3
          FACD(4,J)=FACD(4,J)*GSCFAC
          FACG(4,J)=FACG(4,J)*GSCFAC
5         CONTINUE
        DO 20 IT=1,3
        IDO=.FALSE.
        DO 10 K=1,7
        ITAB(K)=0
        IF (TABLE(K).NE.IT.AND.TABLE(K).NE.4) GO TO 10
        ITAB(K)=1
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
      IDO=.TRUE.
   10 CONTINUE
        NCRR=NCREP+1
        IF(NCREP.EQ.0) NCRR=0
       ORC=CAN
        FAC=1.
        IF(IT.EQ.3)FAC=.001
        DO 12 J=1,NCRR
 12      DREF(J)=RREF(J)*FAC
      IF (IDO) CALL MULT(IT,FACD(1,IT),REF,NCANR,CANC,TITLE, TITLA(IT)
     > ,ITAB,TITL2,NOTE,NUN(IT),DREF,CREP,NCRR,20,NUCLID, NONCLD)
        ORC=GON
        IF(IDO.AND.GENEFF) CALL MULT(IT,FACG(1,IT),GREF,1,GEN(3),
     >  TITLE,TITLG(IT),ITAB,TITL2,NOTA,NOTA,0.,0.,0,3,NUCLID,NONCLD)
C       IF(IT.EQ.2) GO TO 38
        IF(NTLOC.EQ.0) GO TO 38
        DO 35 LL=1,NTLOC
        IF(FALOC(LL).NE.3) GO TO 35
        IF(LTABLE(LL).NE.IT .AND. LTABLE(LL).NE.4) GO TO 35
        CALL LOCTAB(IT,RNLOC(LL),PTLOC(LL),OGLOC(LL),FACD(1,IT),
     A  REF,TITLA(IT),TITL2,CANC,NCANR,20,2,NUCLID,
     +  DATE_AND_TIME)

        IF(GENEFF) CALL LOCTAB(IT,RNLOC(LL),PTLOC(LL),OGLOC(LL),
     A  FACG(1,IT),GREF,TITLG(IT),TITL2,GEN(3),1,3,2,NUCLID,
     +  DATE_AND_TIME)

35      CONTINUE
38      CONTINUE
      IF (INDPOP.NE.1) RETURN
   20 CONTINUE
      RETURN
      END

C=============================================================================
C                                                                            -
C              SUBROUTINE READ INFO FOR SYNOPSIS RPT                         -
C                                                                            -
C=============================================================================


      SUBROUTINE READ_INFO_FOR_SYNOPSIS_RPT( FOOD_ARRAY_INFO,
     +                                       NUMBER_FILES )
C     ------------------------------------
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
1234567890123456789012345678901234567890123456789012345678901234567890123456789012

C     VARIABLES PASSED
C     ================


      CHARACTER*80 FOOD_ARRAY_INFO

      INTEGER*2    NUMBER_FILES

C     GLOBAL VARIABLES
C     ================

      CHARACTER*80 FILES_USED(10), NAME_OF_PERSON, PHONE_NUMBER

      COMMON / GENERIC_INFO / FILES_USED, NAME_OF_PERSON, PHONE_NUMBER


      CHARACTER*80 COMMENTS(2)
      CHARACTER*72 FACILITY, ADDRESS
      CHARACTER*38 SOURCE_CATEGORY
      CHARACTER*25 CITY
      CHARACTER*10 ZIPCODE
      CHARACTER*4  YEAR
      CHARACTER*2  STATE
      COMMON / FACIL_INFO / COMMENTS, FACILITY, ADDRESS,
     +                      SOURCE_CATEGORY, CITY, ZIPCODE, YEAR, STATE


      REAL         VEG_LOCAL, VEG_REGIONAL, VEG_IMPORTED, MEAT_LOCAL,
     +             MEAT_REGIONAL, MEAT_IMPORTED, MILK_LOCAL,
     +             MILK_REGIONAL, MILK_IMPORTED

      COMMON / FOOD_INFO / VEG_LOCAL, VEG_REGIONAL, VEG_IMPORTED,
     +                     MEAT_LOCAL, MEAT_REGIONAL, MEAT_IMPORTED,
     +                     MILK_LOCAL, MILK_REGIONAL, MILK_IMPORTED

      INTEGER*4    TEMPERATURE, RAINFALL_RATE, LID_HEIGHT
      REAL         LATITUDE, LONGITUDE

      COMMON / SITE_INFO / TEMPERATURE, RAINFALL_RATE, LID_HEIGHT,
     +                     LATITUDE, LONGITUDE

      INTEGER*2    NUMBER_STACKS, SOURCE_TYPE, PLUME_RISE_TYPE
      REAL         HEIGHT(6), AREA(6), AREA_DIAMETER(6),
     +             STACK_DIAMETER(6),BOUYANCY(6), MOMENTUM(6), ENTERED(7)
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
      COMMON / EMMIS_INFO / HEIGHT, AREA, AREA_DIAMETER,
     +                      STACK_DIAMETER, BOUYANCY, MOMENTUM,
     +                      ENTERED,
     +                      NUMBER_STACKS, SOURCE_TYPE, PLUME_RISE_TYPE

      CHARACTER*8  NAME_NUC(36)
      CHARACTER*1  ISOL(36)
      COMMON / NUCCHARINFO / NAME_NUC, ISOL

      INTEGER*2    NUMBER_NUCS, DECAY_CHAIN_FLAG (36), DAUGHTERS
      LOGICAL      RN_RUN
      REAL         AMAD(36), RELEASE_RATE(36,6), ALAMSUR(36)
      COMMON / NUC_INFO / AMAD, RELEASE_RATE, NUMBER_NUCS,
     +                    DAUGHTERS, DECAY_CHAIN_FLAG, ALAMSUR,RN_RUN

      CHARACTER*90 SAVED_TITLE_LINES (20)
      CHARACTER*26 ID_CODE
      COMMON / TITLES / SAVED_TITLE_LINES, ID_CODE


C     LOCAL VARIABLES
C     ===============

      INTEGER*2    I, J, RFLAG

      REAL         TEMP, RAIN_RATE




C************  READ IN THE TITLE PAGE INFO ************************

      READ(11,1000) NAME_OF_PERSON
      READ(11,1000) PHONE_NUMBER

C******  READ IN THE NAMES OF THE INPUT FILES USED FOR THE RUN *******
      I = 0
 10   CONTINUE
      I = I + 1
      READ(11,1000) FILES_USED(I)

C**** READ FILES UNTIL DELIMITER * ENCOUNTERED
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      IF ( FILES_USED(I)(1:1) .EQ. '*' ) THEN
        NUMBER_FILES = I - 1
        GO TO 20
      ELSE
        GO TO 10
      ENDIF

 20   CONTINUE


C**************  READ IN THE INFO ON THE FACILITY **********************

C***      READ(11,1000) ID_CODE
      READ(11,1000) FACILITY
      READ(11,1000) ADDRESS
      READ(11,1000) CITY
      READ(11,1000) STATE
      READ(11,1000) ZIPCODE
      READ(11,1000) SOURCE_CATEGORY
      READ(11,1000) YEAR
      IF ( YEAR .EQ. 'YEAR' ) THEN
         YEAR = '1986'
      ENDIF

      READ(11,1000) COMMENTS(1)
      READ(11,1000) COMMENTS(2)

C***************  READ IN THE SITE SPECIFIC INFO **********************
      READ(11,*) TEMP
      READ(11,*) RAIN_RATE
      READ(11,*) LID_HEIGHT
      READ(11,*) LATITUDE
      READ(11,*) LONGITUDE
      READ(11,1000) FOOD_ARRAY_INFO

      READ(11,*) VEG_LOCAL,  VEG_REGIONAL,  VEG_IMPORTED,
     +              MEAT_LOCAL, MEAT_REGIONAL, MEAT_IMPORTED,
     +              MILK_LOCAL, MILK_REGIONAL, MILK_IMPORTED


C************** READ IN THE INFO ON THE SOURCE TERM ********************
      READ(11,*) RFLAG
      IF ( RFLAG .EQ. 0 ) THEN
         RN_RUN = .FALSE.
      ELSE
         RN_RUN = .TRUE.
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      ENDIF
      IF ( .NOT. RN_RUN ) THEN
        READ(11,*) DAUGHTERS
        READ(11,*) NUMBER_NUCS, NUMBER_STACKS
        DO 30 I = 1, NUMBER_NUCS
           READ(11,1000) NAME_NUC(I)
           READ(11,*) DECAY_CHAIN_FLAG (I)
           READ(11,1030) ISOL(I), AMAD(I), ALAMSUR(I)
           READ(11,*) ( RELEASE_RATE(I,J), J = 1,NUMBER_STACKS )
 30      CONTINUE
      ELSE
        READ(11,*) NUMBER_NUCS, NUMBER_STACKS
        DO 35 I = 1, NUMBER_NUCS
           READ(11,1000) NAME_NUC(I)
           READ(11,1030) ISOL(I), AMAD(I), ALAMSUR(I)
           READ(11,*) ( RELEASE_RATE(I,J), J = 1,NUMBER_STACKS )
 35      CONTINUE
      ENDIF


C**************  READ IN THE EMMISSION INFO  ****************************

      READ(11,1040) SOURCE_TYPE, PLUME_RISE_TYPE

C***            SOURCE TYPE 1 = AREA, 0 = STACK          ***************
C*** PLUME_RISE 0 = BOUYANT, 1 = MOMENTUM, 2 = ENTERED ***************

      READ(11,*) ( HEIGHT(J), J = 1,NUMBER_STACKS )

      IF ( SOURCE_TYPE .EQ. 1 ) THEN
         READ(11,*) ( AREA (J), J = 1, NUMBER_STACKS )
         READ(11,*) ( AREA_DIAMETER (J), J = 1, NUMBER_STACKS )
      ELSE
         READ(11,*) ( STACK_DIAMETER (J) , J = 1, NUMBER_STACKS )
      ENDIF

      IF ( PLUME_RISE_TYPE . EQ. 0 ) THEN
         READ(11,*) ( BOUYANCY(J) , J = 1, NUMBER_STACKS )
      ELSE IF ( PLUME_RISE_TYPE . EQ. 1 ) THEN
         READ(11,*) ( MOMENTUM (J) , J = 1, NUMBER_STACKS )
      ELSE
         READ(11,*) ( ENTERED(J) , J = 1, 7)
      ENDIF

C************** CONVERT TEMPERATURE TO CELIUS
      TEMP = TEMP - 273.0
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

C************** CONVERT RAINFALL RATE AND TEMPERATURE TO NEAREST INTEGER
      RAINFALL_RATE = NINT(RAIN_RATE)
      TEMPERATURE   = NINT(TEMP      )


 1000 FORMAT(A)
 1030 FORMAT( A, 1X, E10.3,1X, E10.3)
 1040 FORMAT( I1, 1X, I1)


      RETURN

      END



C*************************************************************************
C                                                                        *
C                                                                        *
C                                                                        *
C                    OUTPUT ROUTINES AND REPORTS                         *
C                                                                        *
C                                                                        *
C                                                                        *
C*************************************************************************



C========================================================================
C                                                                        =
C                      SUBROUTINE FACOUT                                 =
C                                                                        =
C========================================================================


      SUBROUTINE FACOUT(DATE_AND_TIME)

      CHARACTER*8 NUCLID,ORGN,CANC,GEN,RN222,WBODY
      CHARACTER*36 DATE_AND_TIME

       DIMENSION NUCLID(40), CANC(20), ORGN(20), GEN(3)

       COMMON /NAMES_CHARS/ NUCLID, CANC, ORGN, GEN
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
      DIMENSION ARRAY(20,40,4),ORGN(1),PATH(7),DTABLE(7),WLSUM(4),
     +          RFAC(20), NUCLID(40), CREP(20)

      COMMON/COMNU/NONCLD,PSIZE(40),GIABS (4,40),INDPOP

      COMMON/COMUS/SUMX(40,7),SUMY(40,3),PERX(40),PERY(40),TVAL(40),
     > FACO(20,4)

      DATA RADON/'RN-222  '/
      DATA PATH/'INGESTION       ','INHALATION      ','AIR IMMERSION   '
     +         ,'GROUND SURFACE  ','INTERNAL        ','EXTERNAL        '
     +         ,'                '/

      DATA SUM/'TOTAL   '/
C***    SUM OVER ALL NUCLIDES FOR EACH ORGAN AND PATHWAY
C***    PATHWAY 5 IS INTERNAL, 6 IS EXTERNAL, AND 7 IS ALL PATHWAYS
      DO 10 I=1,7
      DO 10 K=1,NORGN
   10 SUMX(K,I)=0.0
      DO 30 I=1,4
      DO 20 K=1,NORGN
      DO 20 J=1,NONCLD
      SUMX(K,I)=SUMX(K,I)+ARRAY(K,J,I)
      IF (I.LE.2) SUMX(K,5)=SUMX(K,5)+ARRAY(K,J,I)
      IF (I.GE.3) SUMX(K,6)=SUMX(K,6)+ARRAY(K,J,I)
      SUMX(K,7)=SUMX(K,7)+ARRAY(K,J,I)
   20 CONTINUE
   30 CONTINUE
C***    TABLE 1
      IF (DTABLE(1).EQ.0) GO TO 80
      DO 70 I=1,4
      WRITE(27,10000) TITLE,TITL1,TITLA
      WRITE(27,10200) PATH(I)

      WRITE(27,10300) ORC,(ORGN(K),K=1,NORGN)
      WRITE(27,10400)
      DO 60 J=1,NONCLD
      DO 40 K=1,NORGN
      PERX(K)=0.0
   40 IF (SUMX(K,I).NE.0.0) PERX(K)=ARRAY(K,J,I)/SUMX(K,I)*100.
      WRITE(27,10500) NUCLID(J),(ARRAY(K,J,I),K=1,NORGN)
      WRITE(27,10600) PATH(I),(PERX(K),K=1,NORGN)
      DO 50 K=1,NORGN
      II=5
      IF (I.GT.2) II=6
      PERX(K)=0.0
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        WRITE(27,10200) GEN(3),((GRISK(1,K,J,N),N=1,2),J=1,2),
     A  (GRISK(1,K,J,1),J=3,4)
200     CONTINUE
        WRITE(27,10176)
10176   FORMAT('0',28X,'YEARS OF LIFE LOST FACTORS',35X,/
     A  1X,'CANCER',10X,'INGESTION',10X,'INHALATION',
     A  9X,'AIR',5X,'GROUND'/
     B  12X,'LOW LET',3X,'HIGH LET',2X,'LOW LET',
     B  3X,'HIGH LET',2X,'IMMERSION',1X,'SURFACE')
        WRITE(27,10250) (CANC(I),((YRLL(I,K,J,N),N=1,2),J=1,2),
     A  (YRLL(I,K,J,1),J=3,4),I = 1, NCANC)

10250   FORMAT((1X,A8,1X,6(1PE10.1)))
        WRITE(27,10190)
10190   FORMAT('1 RISK EQUIVALENT CONVERSION FACTORS'/
     A  1X,'CANCER',3X,'INGESTION',1X,'INHALATION',
     B  4X,'AIR',4X,'GROUND'/31X,'IMMERSION',2X,'SURFACE')
        NALL=NCANC+1
        CANC(NALL)=WBODY
        WRITE(27,10275) (CANC(I),(REF(I,K,J),J=1,4),I=1,NALL)
10275   FORMAT((1X,A8,1X,4(1PE10.2)))
        IF(.NOT.GENEFF) GO TO 300
        WRITE(27,10600)
10600   FORMAT(' GENETIC EFFECT RISK EQ. CONVERSION FACTOR')
        WRITE(27,10275) GEN(3),(GREF(1,K,I),I=1,4)
300     CONTINUE
1000    CONTINUE
        DO 400 I=1,NONCLD
        IF(NUCLID(I).EQ.RN222) GO TO 450
400     CONTINUE
        RETURN
450     WRITE(27,10700) RRISK,RYRLL,RREF
10700   FORMAT('1FOR RN-222 WORKING LEVEL CALCULATIONS:'/
     A  ' RISK CONVERSION FACTOR = ',1PE10.2/
     B  ' YEARS OF LIFE LOST FACTOR = ',1PE10.2/
     C  ' RISK EQ. CONVERSION FACTOR (PULMNARY) = ',1PE10.2/
     D  ' RISK EQ. CONVERSION FACTOR (W BODY  ) = ',1PE10.2)
        RETURN
      END

C=======================================================================
C                                                                      =
C                        SUBROUTINE RDORGF                             =
C                                                                      =
C=======================================================================
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
      SUBROUTINE RDORGF(ORGN)
      CHARACTER*8 ORGN,ORGB
        COMMON/COMWOR/FACO(20,4)
      DIMENSION ORGN(20),ORGB(20),ORGDAT(20),IPATH(20)
      COMMON/COMOR/NORGN,TIME(20),DOSE(20,40,4,2)
      NAMELIST/ ORGANF/NORGB,ORGB,ORGDAT,IPATH
      READ(5,ORGANF)
      WRITE(27,10000)

      DO 10 J=1,NORGB
        IF (IPATH(J).NE.5) THEN
           WRITE(27,10200) ORGB(J),ORGDAT(J),IPATH(J)
        ELSE IF (IPATH(J).EQ.5) THEN
           WRITE(27,10300) ORGB(J),ORGDAT(J)
        ENDIF
   10 CONTINUE

      DO 80 K=1,NORGN
      DO 30 I=1,4
   30 FACO(K,I)=0.0
      DO 40 J=1,NORGB
      IF (ORGN(K).EQ.ORGB(J)) GO TO 50
   40 CONTINUE
      GO TO 80
   50 IF (IPATH(J).EQ.5) GO TO 60
      FACO(K,IPATH(J))=ORGDAT(J)
      GO TO 80
   60 DO 70 I=1,4
      FACO(K,I)=ORGDAT(J)
   70 CONTINUE
   80 CONTINUE
      RETURN
10000 FORMAT('0ORGAN DOSE WEIGHTING FACTORS'//
     A   ' ORGAN     FACTORS   PATHWAYS'/)
10200 FORMAT(1X,A8,1X,F8.5,2X,I2)
10300 FORMAT(1X,A8,1X,F8.5,2X,' 1 2 3 4')

      END
```

```
C=============================================================================
C                                                                            -
C                          SUBROUTINE SUMMRY                                 =
C                                                                            -
C
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
C=============================================================================

      SUBROUTINE SUMMRY(GSCFAC)


CC** THE OUTPUT OF A TITLE HAS BEEN REMOVED 8/88

      CHARACTER*8 NUCLID,ORGN,GEN,CANC,TOTAL,WTSUM,RN222
      CHARACTER*36 DATE_AND_TIME
      COMMON / HEADERINFO / DATE_AND_TIME

      DIMENSION NUCLID(40), CANC(20), ORGN(20), GEN(3)

      COMMON /NAMES_CHARS/ NUCLID, CANC, ORGN, GEN


      LOGICAL GENEFF,RNWR
      REAL LLET
      LOGICAL SEP_DOSE_LET_TABLES, COMB_DOSE_LET_TABLES,
     +        ALL_DOSE_LET_TABLES
      COMMON/DOSE_LET_TABLES/SEP_DOSE_LET_TABLES, COMB_DOSE_LET_TABLES,
     +        ALL_DOSE_LET_TABLES
C

C***  FOLLOWING VARS AND COMMON ADDED FOR NEW SYNOPSIS REPORT 9/1988

      REAL WLI, MAX_PCI_LITERS, FATAL_CANCER_RISK, ORGAN_DOSES(20),
     +     PATHWAY_DOSES(4), NUC_DOSES(36)
      INTEGER LOC_DIST
      COMMON / IND_RESULTS / WLI, LOC_DIST, MAX_PCI_LITERS,
     +                       FATAL_CANCER_RISK ,ORGAN_DOSES,
     +                       PATHWAY_DOSES,NUC_DOSES



      REAL    SRISK(400), RSKLIN(400), EFFECT_PERSON_REM,
     +        PERSON_WORKING_LEVEL, POP_ORGAN_DOSES(20)

      INTEGER POPLIN(400)
      INTEGER IO(400), NLOC, NOP

      COMMON / POPU_RESULTS / POPLIN, RSKLIN, SRISK, IO, NLOC, NOP,
     +                        EFFECT_PERSON_REM, PERSON_WORKING_LEVEL,
     +                        POP_ORGAN_DOSES

C***
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      COMMON/COMEX/EXPP(20,20,40,4),POP(20,20),POPFAC,TOTFAC, NOL,NOU,
     > NRL,NRU,IDIST(20),ILOC,JLOC
      COMMON/COMOR/NORGN,TIME(20),DOSE(20,40,4,2), DTABLE(7)
      COMMON/COMRN/WLRN(20,20),
     A  RRISK,RREF(2),RYRLL,NOREP,NRREP,NCREP
      COMMON/LETFAC/HLET(20),LLET(20)
      COMMON/COMNU/NONCLD,PSIZE(40),GIABS (4,40),
     >INDPOP
      COMMON/COMGEN/NGEN,GDOSE(3,40,4,2),GRISK(3,40,4,2),
     >  GENEFF,GRFAC(2),REPPER,GLLET(3),GHLET(3),GREF(3,40,4)
      COMMON/COMUS/STLOW(40),STHIG(40),STCOM(40),STGLO(40),
     A  STGHI(40),STGCO(40)
      DIMENSION DOSFAC(4),GENFAC(4)
      DATA RN222/'RN-222  '/
      DATA DOSFAC/1.,1.,1.,100./,
     +  GENFAC/1.,1.,1.,100./,TOTAL/'TOTAL   '/,WTSUM/'WT.SUM  '/
        COMMON/COMWOR/DFAC(20,4)
        DOSFAC(4)=GSCFAC*DOSFAC(4)
        GENFAC(4)=GSCFAC*GENFAC(4)
        RNWR=.FALSE.
        DO 5 J=1,NONCLD
        IF(NUCLID(J).EQ.RN222) RNWR=.TRUE.
5        CONTINUE
         WLC=0.0
         DO 10 II=NOL,NOU
         DO  10 JJ=NRL,NRU
         WLC=WLC+WLRN(JJ,II)
10       CONTINUE
         WLE=WLC*TOTFAC
C****    DOSE RATES BY ORGAN
         DO 50 J=1,40
         STHIG(J)=0.0
         STLOW(J)=0.0
         STCOM(J)=0.0
         STGLO(J)=0.0
         STGHI(J)=0.0
         STGCO(J)=0.0
50       CONTINUE
         SUML=0.0
         SUMH=0.0
         SUMC=0.0
         DO 100 L=1,NORGN
         DO 100 K=1,4
         FACNEW=POPFAC*DOSFAC(K)
         FACNE2=POPFAC*GENFAC(K)
         DO 100 J=1,NONCLD
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        STHIG(L)=STHIG(L)+DOSE(L,J,K,2)*FACNEW*EXPP(JLOC,ILOC,J,K)
        SUMH=SUMH+DOSE(L,J,K,2)*FACNEW*EXPP(JLOC,ILOC,J,K)*DFAC(L,K)
        STLOW(L)=STLOW(L)+DOSE(L,J,K,1)*FACNEW*EXPP(JLOC,ILOC,J,K)
        SUML=SUML+DOSE(L,J,K,1)*FACNEW*EXPP(JLOC,ILOC,J,K)*DFAC(L,K)
        STCOM(L)=STCOM(L)+DOSE(L,J,K,1)*FACNEW*EXPP(JLOC,ILOC,J,K)
    <   *LLET(L)+DOSE(L,J,K,2)*FACNEW*EXPP(JLOC,ILOC,J,K)*HLET(L)
        SUMC=SUMC+DOSE(L,J,K,1)*FACNEW*EXPP(JLOC,ILOC,J,K)*
    <   LLET(L)*DFAC(L,K)+DOSE(L,J,K,2)*FACNEW*EXPP(JLOC,ILOC,J,K)*
    <   HLET(L)*DFAC(L,K)
        IF(L.GT.NGEN) GO TO 100
        STGHI(L)=STGHI(L)+GDOSE(L,J,K,2)*FACNE2*EXPP(JLOC,ILOC,J,K)
        STGLO(L)=STGLO(L)+GDOSE(L,J,K,1)*FACNE2*EXPP(JLOC,ILOC,J,K)
        STGCO(L)=STGCO(L)+GDOSE(L,J,K,1)*FACNE2*EXPP(JLOC,ILOC,J,K)
    <   *GLLET(L)+GDOSE(L,J,K,2)*FACNE2*EXPP(JLOC,ILOC,J,K)*GHLET(L)
100     CONTINUE

C****   SAVE COMBINED DOSES FOR SYNOPSIS REPORT
        DO 15 L = 1, NORGN
          ORGAN_DOSES(L) = STCOM(L)
 15     CONTINUE

        WRITE(27,101)DATE_AND_TIME
101     FORMAT('1',T10,'DATE',2X,A)
        WRITE(27,10100) (ORGN(L),L=1,NORGN),WTSUM
        IF ( (SEP_DOSE_LET_TABLES ) .OR. (ALL_DOSE_LET_TABLES) ) THEN
           WRITE(27,10205) (STLOW(L),L=1,NORGN),SUML
           WRITE(27,10210) (STHIG(L),L=1,NORGN),SUMH
        ENDIF
        IF ( ( COMB_DOSE_LET_TABLES ) .OR. ( ALL_DOSE_LET_TABLES))
    +      WRITE(27,10215) (STCOM(L),L=1,NORGN),SUMC
        WLI=WLRN(JLOC,ILOC)*POPFAC
        IF(RNWR)WRITE(27,20216) WLI
20216   FORMAT('0RADON DAUGHTER EXPOSURE:'/
     A  ' (WORKING LEVEL)',9X,1PE10.2)

10100   FORMAT('0',/30X,'ORGAN DOSE/EXPOSURE SUMMARY'//
     A  '0*** SELECTED INDIVIDUAL ***'/
     B   '0DOSE RATES:'/
     >  17X,' ORGANS:',10(2X,A8)/(26X,10(2X,A8)))
10205   FORMAT(' LOW LET (MRAD/Y)',8X,10(1PE10.2)/
     A  (26X,10(1PE10.2)))
10206   FORMAT(' LOW LET (PERSON RAD/Y)',1X,10(1PE10.2)/
     A  (26X,10(1PE10.2)))
10210   FORMAT(' HIGH LET (MRAD/Y)',7X,10(1PE10.2)/
     A  (26X,10(1PE10.2)))
10211   FORMAT(' HIGH LET (PERSON RAD/Y)',10(1PE10.2)/
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

     A  (26X,10(1PE10.2)))
10215    FORMAT(' DOSE EQUIVALENT (MREM/Y)',10(1PE10.2)/
     A  (26X,10(1PE10.2)))
10216    FORMAT(' DOSE EQ. (PERSON REM/Y)',10(1PE10.2)/
     A  (26X,10(1PE10.2)))
         IF(INDPOP.NE.1) GO TO 1000
         DO 150 J=1,40
         STHIG(J)=0.0
         STLOW(J)=0.0
         STCOM(J)=0.0
         STGHI(J)=0.0
         STGLO(J)=0.0
         STGCO(J)=0.0
150      CONTINUE
         SUML=0.0
         SUMH=0.0
         SUMC=0.0
         DO 200 L=1,NORGN
         DO 200 K=1,4
         FACNEW=TOTFAC*DOSFAC(K)
         FACNE2=TOTFAC*GENFAC(K)
         DO 200 J=1,NONCLD
         DO 200 II=NOL,NOU
         DO 200 JJ=NRL,NRU
         STHIG(L)=STHIG(L)+DOSE(L,J,K,2)*EXPP(JJ,II,J,K)*FACNEW
         SUMH=SUMH+DOSE(L,J,K,2)*EXPP(JJ,II,J,K)*FACNEW*DFAC(L,K)
         STLOW(L)=STLOW(L)+DOSE(L,J,K,1)*EXPP(JJ,II,J,K)*FACNEW
         SUML=SUML+DOSE(L,J,K,1)*EXPP(JJ,II,J,K)*FACNEW*DFAC(L,K)
         STCOM(L)=STCOM(L)+DOSE(L,J,K,1)*EXPP(JJ,II,J,K)*FACNEW
     >   *LLET(L)+DOSE(L,J,K,2)*EXPP(JJ,II,J,K)*FACNEW*HLET(L)
         SUMC=SUMC+DOSE(L,J,K,1)*EXPP(JJ,II,J,K)*FACNEW*
     >   LLET(L)*DFAC(L,K)+DOSE(L,J,K,2)*EXPP(JJ,II,J,K)*FACNEW*
     >   HLET(L)*DFAC(L,K)
         IF(L.GT.NGEN) GO TO 200
         STGHI(L)=STGHI(L)+GDOSE(L,J,K,2)*EXPP(JJ,II,J,K)*FACNE2
         STGLO(L)=STGLO(L)+GDOSE(L,J,K,1)*EXPP(JJ,II,J,K)*FACNE2
         STGCO(L)=STGCO(L)+GDOSE(L,J,K,1)*EXPP(JJ,II,J,K)*FACNE2
     >   *GLLET(L)+GDOSE(L,J,K,2)*EXPP(JJ,II,J,K)*FACNE2*GHLET(L)
200      CONTINUE
         WRITE(27,10400) (ORGN(L),L=1,NORGN),WTSUM
10400    FORMAT(/'0*** MEAN INDIVIDUAL ***'/
     A   '0DOSE RATE:'/
     +   17X,' ORGANS:',10(2X,A8)/(26X,10(2X,A8)))
         IF ( (SEP_DOSE_LET_TABLES ) .OR. (ALL_DOSE_LET_TABLES) ) THEN
           WRITE(27,10205) (STLOW(L),L=1,NORGN),SUML
           WRITE(27,10210) (STHIG(L),L=1,NORGN),SUMH
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        ENDIF
        IF ( ( COMB_DOSE_LET_TABLES ) .OR. ( ALL_DOSE_LET_TABLES) )
     +    WRITE(27,10215) (STCOM(L),L=1,NORGN),SUMC
        IF(RNWR)WRITE(27,20216) WLE
        DO 350 K=1,40
        STLOW(K)=0.0
        STHIG(K)=0.0
        STCOM(K)=0.0
        IF(K.GT.NGEN) GO TO 350
        STGLO(K)=0.0
        STGHI(K)=0.0
        STGCO(K)=0.0
350     CONTINUE
        SUML=0.0
        SUMH=0.0
        SUMC=0.0
        DO 400 K=1,4
        DO 400 J=1,NONCLD
        TEXPP=0.0
        DO 403 II=NOL,NOU
        DO 403 JJ=NRL,NRU
        TEXPP=TEXPP+EXPP(JJ,II,J,K)
403     CONTINUE
        TEXPP=TEXPP*.001
        DO 400 L=1,NORGN
        STLOW(L)=STLOW(L)+DOSE(L,J,K,1)*TEXPP*DOSFAC(K)
        SUML=SUML+DOSE(L,J,K,1)*TEXPP*DOSFAC(K)*DFAC(L,K)
        STHIG(L)=STHIG(L)+DOSE(L,J,K,2)*TEXPP*DOSFAC(K)
        SUMH=SUMH+DOSE(L,J,K,2)*TEXPP*DOSFAC(K)*DFAC(L,K)
        STCOM(L)=STCOM(L)+DOSE(L,J,K,1)*TEXPP*DOSFAC(K)*LLET(L)+
     >  DOSE(L,J,K,2)*TEXPP*DOSFAC(K)*HLET(L)
        SUMC=SUMC+DOSE(L,J,K,1)*TEXPP*DOSFAC(K)*LLET(L)*DFAC(L,K)+
     >  DOSE(L,J,K,2)*TEXPP*DOSFAC(K)*HLET(L)*DFAC(L,K)
        IF(L.GT.NGEN) GO TO 400
        STGLO(L)=STGLO(L)+GDOSE(L,J,K,1)*TEXPP*GENFAC(K)
        STGHI(L)=STGHI(L)+GDOSE(L,J,K,2)*TEXPP*GENFAC(K)
        STGCO(L)=STGCO(L)+GDOSE(L,J,K,1)*TEXPP*GENFAC(K)*GLLET(L)+
     >  GDOSE(L,J,K,2)*TEXPP*GENFAC(K)*GHLET(L)
400     CONTINUE

C***    SAVE EFFECTIVE PERSON-REM/ YEAR FOR SYNOPSIS REPORT

        EFFECT_PERSON_REM = STCOM (NORGN)

C****   SAVE COMBINED DOSES FOR SYNOPSIS REPORT
        DO 16 L = 1, NORGN - 1
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

          POP_ORGAN_DOSES(L) = STCOM(L)
 16     CONTINUE

        WRITE(27,10700) (ORGN(L),L=1,NORGN),WTSUM
10700   FORMAT(/'0*** COLLECTIVE POPULATION ***'/
     A  '0DOSE RATE:'/
     >  17X,' ORGANS:',10(2X,A8)/(26X,10(2X,A8)))
        IF ( (SEP_DOSE_LET_TABLES ) .OR. (ALL_DOSE_LET_TABLES) ) THEN
           WRITE(27,10206) (STLOW(L),L=1,NORGN),SUML
           WRITE(27,10211) (STHIG(L),L=1,NORGN),SUMH
        ENDIF
        IF ( (COMB_DOSE_LET_TABLES ) .OR. (ALL_DOSE_LET_TABLES) )
     +     WRITE(27,10216) (STCOM(L),L=1,NORGN),SUMC

        IF (RNWR) THEN

C***       SAVE PERSON WORKING LEVELS FOR SYNOPSIS REPORT

           PERSON_WORKING_LEVEL = WLC

           WRITE(27,20416) WLC
20416      FORMAT('ORADON DAUGHTER EXPOSURE:'/
     A           ' (PERSON WORKING LEVEL)',2X,1PE10.2)

        ENDIF

C****   DOSE RATES BY PATHWAY
1000    DO 1050 J=1,40
        STHIG(J)=0.0
        STLOW(J)=0.0
        STCOM(J)=0.0
        STGHI(J)=0.0
        STGLO(J)=0.0
        STGCO(J)=0.0
1050    CONTINUE
        DO 1199 K=1,4
        FACNE2=POPFAC*GENFAC(K)
        DO 1100 L=1,NORGN
        FACNEW=POPFAC*DOSFAC(K)*DFAC(L,K)
        DO 1100 J=1,NONCLD
        STHIG(K)=STHIG(K)+DOSE(L,J,K,2)*FACNEW*EXPP(JLOC,ILOC,J,K)
        STLOW(K)=STLOW(K)+DOSE(L,J,K,1)*FACNEW*EXPP(JLOC,ILOC,J,K)
        STCOM(K)=STCOM(K)+DOSE(L,J,K,1)*FACNEW*EXPP(JLOC,ILOC,J,K)
     <  *LLET(L)+DOSE(L,J,K,2)*FACNEW*EXPP(JLOC,ILOC,J,K)*HLET(L)
        IF(L.NE.NGEN) GO TO 1100
        STGHI(K)=STGHI(K)+GDOSE(L,J,K,2)*FACNE2*EXPP(JLOC,ILOC,J,K)
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        STGLO(K)=STGLO(K)+GDOSE(L,J,K,1)*FACNE2*EXPP(JLOC,ILOC,J,K)
        STGCO(K)=STGCO(K)+GDOSE(L,J,K,1)*FACNE2*EXPP(JLOC,ILOC,J,K)
     <  *GLLET(L)+GDOSE(L,J,K,2)*FACNE2*EXPP(JLOC,ILOC,J,K)*GHLET(L)
1100    CONTINUE
        IF(K.GT.2) GO TO 1101
        STHIG(5)=STHIG(5)+STHIG(K)
        STLOW(5)=STLOW(5)+STLOW(K)
        STCOM(5)=STCOM(5)+STCOM(K)
        STGHI(5)=STGHI(5)+STGHI(K)
        STGLO(5)=STGLO(5)+STGLO(K)
        STGCO(5)=STGCO(5)+STGCO(K)
1101    IF(K.LT.3) GO TO 1102
        STHIG(6)=STHIG(6)+STHIG(K)
        STLOW(6)=STLOW(6)+STLOW(K)
        STCOM(6)=STCOM(6)+STCOM(K)
        STGHI(6)=STGHI(6)+STGHI(K)
        STGLO(6)=STGLO(6)+STGLO(K)
        STGCO(6)=STGCO(6)+STGCO(K)
1102    STHIG(7)=STHIG(7)+STHIG(K)
        STLOW(7)=STLOW(7)+STLOW(K)
        STCOM(7)=STCOM(7)+STCOM(K)
        STGHI(7)=STGHI(7)+STGHI(K)
        STGLO(7)=STGLO(7)+STGLO(K)
        STGCO(7)=STGCO(7)+STGCO(K)
1199    CONTINUE
        WRITE(27,101)DATE_AND_TIME
        WRITE(27,11100)
11100   FORMAT('0'/30X,' PATHWAY DOSE/EXPOSURE SUMMARY'/
     A  '0*** SELECTED INDIVIDUAL ***'/
     B  '0DOSE RATES:'/
     <  ' WEIGHTED SUMS OF ORGAN DOSE RATES'/
     <  '                  PATHWAYS:  INGESTION ',
     <  'INHALATION  AIR     GROUND',
     <  '    INTERNAL  EXTERNAL  TOTAL'/
     <  45X,' IMMERSION  SURFACE')
        IF ( (SEP_DOSE_LET_TABLES ) .OR. (ALL_DOSE_LET_TABLES) ) THEN
           WRITE(27,10205) (STLOW(L),L=1,7)
          WRITE(27,10210) (STHIG(L),L=1,7)
        ENDIF
        IF ( ( COMB_DOSE_LET_TABLES ) .OR. ( ALL_DOSE_LET_TABLES) )
     +     WRITE(27,10215) (STCOM(L),L=1,7)

        IF(RNWR) THEN
          WRITE(27,20216) WLI
        ELSE
C****     SAVE DOSES BY PATHWAY FOR DATABASE
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

          DO 20 L = 1, 4
            PATHWAY_DOSES(L) = STCOM(L)
 20       CONTINUE
        ENDIF

        IF(INDPOP.NE.1) GO TO 11000
        DO 1150 J=1,40
        STHIG(J)=0.0
        STLOW(J)=0.0
        STCOM(J)=0.0
        STGHI(J)=0.0
        STGLO(J)=0.0
        STGCO(J)=0.0
1150    CONTINUE
        DO 1299 K=1,4
        FACNE2=TOTFAC*GENFAC(K)
        DO 1200 L=1,NORGN
        FACNEW=TOTFAC*DOSFAC(K)*DFAC(L,K)
        DO 1200 J=1,NONCLD
        DO 1200 II=NOL,NOU
        DO 1200 JJ=NRL,NRU
        STHIG(K)=STHIG(K)+DOSE(L,J,K,2)*EXPP(JJ,II,J,K)*FACNEW
        STLOW(K)=STLOW(K)+DOSE(L,J,K,1)*EXPP(JJ,II,J,K)*FACNEW
        STCOM(K)=STCOM(K)+DOSE(L,J,K,1)*EXPP(JJ,II,J,K)*FACNEW
     >  *LLET(L)+DOSE(L,J,K,2)*EXPP(JJ,II,J,K)*FACNEW*HLET(L)
        IF(L.NE.NGEN) GO TO 1200
        STGHI(K)=STGHI(K)+GDOSE(L,J,K,2)*EXPP(JJ,II,J,K)*FACNE2
        STGLO(K)=STGLO(K)+GDOSE(L,J,K,1)*EXPP(JJ,II,J,K)*FACNE2
        STGCO(K)=STGCO(K)+GDOSE(L,J,K,1)*EXPP(JJ,II,J,K)*FACNE2*
     A  GLLET(L)+GDOSE(L,J,K,2)*EXPP(JJ,II,J,K)*FACNE2*GHLET(L)
1200    CONTINUE
1203    IF(K.GT.2) GO TO 1201
        STHIG(5)=STHIG(5)+STHIG(K)
        STLOW(5)=STLOW(5)+STLOW(K)
        STCOM(5)=STCOM(5)+STCOM(K)
        STGHI(5)=STGHI(5)+STGHI(K)
        STGLO(5)=STGLO(5)+STGLO(K)
        STGCO(5)=STGCO(5)+STGCO(K)
1201    IF(K.LT.3) GO TO 1202
        STHIG(6)=STHIG(6)+STHIG(K)
        STLOW(6)=STLOW(6)+STLOW(K)
        STCOM(6)=STCOM(6)+STCOM(K)
        STGHI(6)=STGHI(6)+STGHI(K)
        STGLO(6)=STGLO(6)+STGLO(K)
        STGCO(6)=STGCO(6)+STGCO(K)
1202    STHIG(7)=STHIG(7)+STHIG(K)
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        STLOW(7)=STLOW(7)+STLOW(K)
        STCOM(7)=STCOM(7)+STCOM(K)
        STGHI(7)=STGHI(7)+STGHI(K)
        STGLO(7)=STGLO(7)+STGLO(K)
        STGCO(7)=STGCO(7)+STGCO(K)
1299    CONTINUE
        WRITE(27,11400)
11400   FORMAT(/'0*** MEAN INDIVIDUAL ***'/
     A  '0DOSE RATES:'/
     <  ' WEIGHTED SUMS OF ORGAN DOSE RATES'/
     <  '                PATHWAYS:  INGESTION ',
     <  'INHALATION  AIR     GROUND',
     <  '    INTERNAL  EXTERNAL  TOTAL'/
     <  45X,' IMMERSION  SURFACE')
        IF ( (SEP_DOSE_LET_TABLES ) .OR. (ALL_DOSE_LET_TABLES) ) THEN
           WRITE(27,10205) (STLOW(L),L=1,7)
           WRITE(27,10210) (STHIG(L),L=1,7)
        ENDIF
        IF ( ( COMB_DOSE_LET_TABLES ) .OR. ( ALL_DOSE_LET_TABLES) )
     +    WRITE(27,10215) (STCOM(L),L=1,7)
        IF(RNWR)WRITE(27,20216) WLE
        DO 1350 K=1,40
        STLOW(K)=0.0
        STHIG(K)=0.0
        STCOM(K)=0.0
        STGLO(K)=0.0
        STGHI(K)=0.0
        STGCO(K)=0.0
1350    CONTINUE
        DO 1499 K=1,4
        DO 1400 J=1,NONCLD
        TEXPP=0.0
        DO 1404 II=NOL,NOU
        DO 1404 JJ=NRL,NRU
        TEXPP=TEXPP+EXPP(JJ,II,J,K)
1404    CONTINUE
        TEXPP=TEXPP*.001
        DO 1400 L=1,NORGN
        STLOW(K)=STLOW(K)+DOSE(L,J,K,1)*TEXPP*DOSFAC(K)*DFAC(L,K)
        STHIG(K)=STHIG(K)+DOSE(L,J,K,2)*TEXPP*DOSFAC(K)*DFAC(L,K)
        STCOM(K)=STCOM(K)+DOSE(L,J,K,1)*TEXPP*DOSFAC(K)*LLET(L)*
     >  DFAC(L,K)+DOSE(L,J,K,2)*TEXPP*DOSFAC(K)*HLET(L)*DFAC(L,K)
        IF(L.NE.NGEN) GO TO 1400
        STGLO(K)=STGLO(K)+GDOSE(L,J,K,1)*TEXPP*GENFAC(K)
        STGHI(K)=STGHI(K)+GDOSE(L,J,K,2)*TEXPP*GENFAC(K)
        STGCO(K)=STGCO(K)+GDOSE(L,J,K,2)*TEXPP*GENFAC(K)*GHLET(L)+
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

     A  GDOSE(L,J,K,1)*TEXPP*GENFAC(K)*GLLET(L)
1400     CONTINUE
1403     IF(K.GT.2) GO TO 1401
         STLOW(5)=STLOW(5)+STLOW(K)
         STHIG(5)=STHIG(5)+STHIG(K)
         STCOM(5)=STCOM(5)+STCOM(K)
         STGLO(5)=STGLO(5)+STGLO(K)
         STGHI(5)=STGHI(5)+STGHI(K)
         STGCO(5)=STGCO(5)+STGCO(K)
         GO TO 1402
1401     STLOW(6)=STLOW(6)+STLOW(K)
         STHIG(6)=STHIG(6)+STHIG(K)
         STCOM(6)=STCOM(6)+STCOM(K)
         STGLO(6)=STGLO(6)+STGLO(K)
         STGHI(6)=STGHI(6)+STGHI(K)
         STGCO(6)=STGCO(6)+STGCO(K)
1402     STLOW(7)=STLOW(7)+STLOW(K)
         STHIG(7)=STHIG(7)+STHIG(K)
         STCOM(7)=STCOM(7)+STCOM(K)
         STGLO(7)=STGLO(7)+STGLO(K)
         STGHI(7)=STGHI(7)+STGHI(K)
         STGCO(7)=STGCO(7)+STGCO(K)
1499     CONTINUE
11700    FORMAT(/'0*** COLLECTIVE POPULATION ***'/
     A   '0DOSE RATES:'/
     <   ' WEIGHTED SUMS OF ORGAN DOSE RATES'/
     <   '                  PATHWAYS:  INGESTION ',
     <   'INHALATION  AIR     GROUND',
     <   '    INTERNAL  EXTERNAL  TOTAL'/
     <   45X,' IMMERSION  SURFACE')
         WRITE(27,11700)
         IF ( (SEP_DOSE_LET_TABLES ) .OR. (ALL_DOSE_LET_TABLES) ) THEN
            WRITE(27,10206) (STLOW(L),L=1,7)
            WRITE(27,10211) (STHIG(L),L=1,7)
         ENDIF
         IF ( ( COMB_DOSE_LET_TABLES ) .OR. ( ALL_DOSE_LET_TABLES) )
     +      WRITE(27,10216) (STCOM(L),L=1,7)
         IF(RNWR)WRITE(27,20416) WLC
C****    DOSE RATES BY NUCLIDE
11000    DO 2050 J=1,40
         STHIG(J)=0.0
         STLOW(J)=0.0
         STCOM(J)=0.0
         STGLO(J)=0.0
         STGHI(J)=0.0
         STGCO(J)=0.0
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

2050     CONTINUE
         SUML=0.0
         SUMH=0.0
         SUMC=0.0
         SUMGL=0.0
         SUMGH=0.0
         SUMGC=0.0
         DO 2109 J=1,NONCLD
         DO 2100 K=1,4
         FACNE2=POPFAC*GENFAC(K)
         DO 2100 L=1,NORGN
         FACNEW=POPFAC*DOSFAC(K)*DFAC(L,K)
         STHIG(J)=STHIG(J)+DOSE(L,J,K,2)*FACNEW*EXPP(JLOC,ILOC,J,K)
         STLOW(J)=STLOW(J)+DOSE(L,J,K,1)*FACNEW*EXPP(JLOC,ILOC,J,K)
         STCOM(J)=STCOM(J)+DOSE(L,J,K,1)*FACNEW*EXPP(JLOC,ILOC,J,K)
     <   *LLET(L)+DOSE(L,J,K,2)*FACNEW*EXPP(JLOC,ILOC,J,K)*HLET(L)
         IF(L.NE.NGEN) GO TO 2100
         STGHI(J)=STGHI(J)+GDOSE(L,J,K,2)*FACNE2*EXPP(JLOC,ILOC,J,K)
         STGLO(J)=STGLO(J)+GDOSE(L,J,K,1)*FACNE2*EXPP(JLOC,ILOC,J,K)
         STGCO(J)=STGCO(J)+GDOSE(L,J,K,1)*FACNE2*EXPP(JLOC,ILOC,J,K)*
     A   GLLET(L)+GDOSE(L,J,K,2)*FACNE2*EXPP(JLOC,ILOC,J,K)*GHLET(L)
2100     CONTINUE
         SUML=SUML+STLOW(J)
         SUMH=SUMH+STHIG(J)
         SUMC=SUMC+STCOM(J)
         SUMGL=SUMGL+STGLO(J)
         SUMGH=SUMGH+STGHI(J)
         SUMGC=SUMGC+STGCO(J)
2109     CONTINUE
         WRITE(27,101)DATE_AND_TIME
         WRITE(27,12100) (NUCLID(L),L=1,NONCLD),TOTAL
12100    FORMAT('0',/30X,'NUCLIDE DOSE/EXPOSURE SUMMARY'//
      A  '0*** SELECTED INDIVIDUAL ***'/
      A  '0DOSE RATES:'/
      A  ' WEIGHTED SUMS OF ORGAN DOSE RATES'/
      A  15X,' NUCLIDES:',10(2X,A8)/(26X,10(2X,A8)))
         IF ( (SEP_DOSE_LET_TABLES ) .OR. (ALL_DOSE_LET_TABLES) ) THEN
            WRITE(27,10205) (STLOW(L),L=1,NONCLD),SUML
            WRITE(27,10210) (STHIG(L),L=1,NONCLD),SUMH
         ENDIF
         IF ( ( COMB_DOSE_LET_TABLES ) .OR. ( ALL_DOSE_LET_TABLES) )
      +     WRITE(27,10215) (STCOM(L),L=1,NONCLD),SUMC

         IF(RNWR) THEN
           WRITE(27,20216) WLI
         ELSE
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

C****     SAVE DOSES BY PATHWAY FOR DATABASE
          DO 30 L = 1, NONCLD
            NUC_DOSES(L) = STCOM(L)
 30       CONTINUE
        ENDIF

        IF(INDPOP.NE.1) GO TO 21000
        DO 2150 J=1,40
        STHIG(J)=0.0
        STLOW(J)=0.0
        STCOM(J)=0.0
        STGLO(J)=0.0
        STGHI(J)=0.0
        STGCO(J)=0.0
2150    CONTINUE
        SUML=0.0
        SUMH=0.0
        SUMC=0.0
        SUMGL=0.0
        SUMGH=0.0
        SUMGC=0.0
        DO 2209 J=1,NONCLD
        DO 2200 K=1,4
        FACNE2=TOTFAC*GENFAC(K)
        DO 2200 L=1,NORGN
        FACNEW=TOTFAC*DOSFAC(K)*DFAC(L,K)
        DO 2200 II=NOL,NOU
        DO 2200 JJ=NRL,NRU
        STHIG(J)=STHIG(J)+DOSE(L,J,K,2)*EXPP(JJ,II,J,K)*FACNEW
        STLOW(J)=STLOW(J)+DOSE(L,J,K,1)*EXPP(JJ,II,J,K)*FACNEW
        STCOM(J)=STCOM(J)+DOSE(L,J,K,1)*EXPP(JJ,II,J,K)*FACNEW
     >  *LLET(L)+DOSE(L,J,K,2)*EXPP(JJ,II,J,K)*FACNEW*HLET(L)
        IF(L.NE.NGEN) GO TO 2200
        STGLO(J)=STGLO(J)+GDOSE(L,J,K,1)*EXPP(JJ,II,J,K)*FACNE2
        STGHI(J)=STGHI(J)+GDOSE(L,J,K,2)*EXPP(JJ,II,J,K)*FACNE2
        STGCO(J)=STGCO(J)+GDOSE(L,J,K,1)*EXPP(JJ,II,J,K)*FACNE2*
     A  GLLET(L)+GDOSE(L,J,K,2)*EXPP(JJ,II,J,K)*FACNE2*GHLET(L)
2200    CONTINUE
        SUML=SUML+STLOW(J)
        SUMH=SUMH+STHIG(J)
        SUMC=SUMC+STCOM(J)
        SUMGL=SUMGL+STGLO(J)
        SUMGH=SUMGH+STGHI(J)
        SUMGC=SUMGC+STGCO(J)
2209    CONTINUE
        WRITE(27,12400) (NUCLID(L),L=1,NONCLD),TOTAL
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

12400    FORMAT(/'0*** MEAN INDIVIDUAL ***'/
     A  '0DOSE RATES:'/
     A  ' WEIGHTED SUMS OF ORGAN DOSE RATES'/
     >  15X,' NUCLIDES:',10(2X,A8)/(26X,10(2X,A8)))
        IF ( (SEP_DOSE_LET_TABLES ) .OR. (ALL_DOSE_LET_TABLES) ) THEN
           WRITE(27,10205) (STLOW(L),L=1,NONCLD),SUML
           WRITE(27,10210) (STHIG(L),L=1,NONCLD),SUMH
        ENDIF
        IF ( ( COMB_DOSE_LET_TABLES ) .OR. ( ALL_DOSE_LET_TABLES) )
     +    WRITE(27,10215) (STCOM(L),L=1,NONCLD),SUMC
        IF(RNWR)WRITE(27,20216) WLE
        DO 2350 K=1,40
        STLOW(K)=0.0
        STHIG(K)=0.0
        STCOM(K)=0.0
        STGLO(K)=0.0
        STGHI(K)=0.0
        STGCO(K)=0.0
2350    CONTINUE
        SUML=0.0
        SUMH=0.0
        SUMC=0.0
        SUMGL=0.0
        SUMGH=0.0
        SUMGC=0.0
        DO 2409 J=1,NONCLD
        DO 2400 K=1,4
        TEXPP=0.0
        DO 2403 II=NOL,NOU
        DO 2403 JJ=NRL,NRU
        TEXPP=TEXPP+EXPP(JJ,II,J,K)
2403    CONTINUE
        TEXPP=TEXPP*.001
        DO 2400 L=1,NORGN
        STLOW(J)=STLOW(J)+DOSE(L,J,K,1)*TEXPP*DOSFAC(K)*DFAC(L,K)
        STHIG(J)=STHIG(J)+DOSE(L,J,K,2)*TEXPP*DOSFAC(K)*DFAC(L,K)
        STCOM(J)=STCOM(J)+DOSE(L,J,K,1)*TEXPP*DOSFAC(K)*LLET(L)*
     >  DFAC(L,K)+DOSE(L,J,K,2)*TEXPP*DOSFAC(K)*HLET(L)*DFAC(L,K)
        IF(L.NE.NGEN) GO TO 2400
        STGLO(J)=STGLO(J)+GDOSE(L,J,K,1)*TEXPP*GENFAC(K)
        STGHI(J)=STGHI(J)+GDOSE(L,J,K,2)*TEXPP*GENFAC(K)
        STGCO(J)=STGCO(J)+GDOSE(L,J,K,1)*TEXPP*GENFAC(K)*GLLET(L)+
     A  GDOSE(L,J,K,2)*TEXPP*GENFAC(K)*GHLET(L)
2400    CONTINUE
        SUML=SUML+STLOW(J)
        SUMH=SUMH+STHIG(J)
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        SUMC=SUMC+STCOM(J)
        SUMGL=SUMGL+STGLO(J)
        SUMGH=SUMGH+STGHI(J)
        SUMGC=SUMGC+STGCO(J)
2409    CONTINUE
        WRITE(27,12700) (NUCLID(L),L=1,NONCLD),TOTAL
12700   FORMAT(/'0*** COLLECTIVE POPULATION ***'/
     A  '0DOSE RATES:'/
     A  ' WEIGHTED SUMS OF ORGAN DOSE RATES'/
     >  15X,' NUCLIDES:',10(2X,A8)/(26X,10(2X,A8)))
        IF ( (SEP_DOSE_LET_TABLES ) .OR. (ALL_DOSE_LET_TABLES) ) THEN
           WRITE(27,10206) (STLOW(L),L=1,NONCLD),SUML
           WRITE(27,10211) (STHIG(L),L=1,NONCLD),SUMH
        ENDIF
        IF ( ( COMB_DOSE_LET_TABLES ) .OR. ( ALL_DOSE_LET_TABLES) )
     +     WRITE(27,10216) (STCOM(L),L=1,NONCLD),SUMC
        IF(RNWR)WRITE(27,20416) WLC
21000   CALL SUMMR2(RNWR,GSCFAC,DATE_AND_TIME)

        RETURN
      END

C=======================================================================
C                                                                      =
C                        SUBROUTINE SUMMR2                             =
C                                                                      =
C=======================================================================

      SUBROUTINE SUMMR2(RNWR,GSCFAC,DATE_AND_TIME)


CC** THE OUTPUT OF A TITLE WAS REMOVED 8/88

      CHARACTER*8 NUCLID, CANC, GEN, ORGN, TOTAL, PUL
      CHARACTER*36 DATE_AND_TIME

      LOGICAL GENEFF,RNWR
      LOGICAL SEP_RISK_LET_TABLES, COMB_RISK_LET_TABLES,
     +        ALL_RISK_LET_TABLES
      COMMON/RISK_LET_TABLES/SEP_RISK_LET_TABLES, COMB_RISK_LET_TABLES,
     +        ALL_RISK_LET_TABLES
C
      DIMENSION NUCLID(40), CANC(20), ORGN(20), GEN(3)

      COMMON /NAMES_CHARS/ NUCLID, CANC, ORGN, GEN
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
      COMMON/COMEX/EXPP(20,20,40,4),POP(20,20),POPFAC,TOTFAC, NOL,NOU,
     > NRL,NRU,IDIST(20),ILOC,JLOC
      COMMON/COMRN/WLRN(20,20),RRISK,RREF(2),RYRLL,NOREP,NRREP,NCREP
      COMMON/COMCA/NCANC,RELABS(20),RISK(20,40,4,2), RTABLE(7),
     > AGEX,YRLL(20,40,4,2)
      COMMON/COMRF/REF(20,40,4),FTABLE(7)
      COMMON/COMNU/NONCLD,PSIZE(40),GIABS (4,40),
     > INDPOP
         COMMON/COMGEN/NGEN,GDOSE(3,40,4,2),GRISK(3,40,4,2),
     >   GENEFF,GRFAC(2),REPPER,GLLET(3),GHLET(3),GREF(3,40,4)
         COMMON/COMUS/STLOW(40),STHIG(40),STCOM(40),STREQ(40),
     A   STGLO(40),STGHI(40),STGCO(40),STLLL(40),STHLL(40),STCLL(40),
     B   STGRQ(40)
         DIMENSION RISFAC(4),REQFAC(4),GENFAC(4)
         DATA PUL/'PULMNARY'/
         DATA RISFAC/2*1.E-5,10.,1000./,
     <   REQFAC/1.,1.,1.E6,1.E8/,
     <   GENFAC/1.,1.,1.,100./,TOTAL/'TOTAL   '/
C****    RISK RATES BY CANCER
         RISFAC(4)=RISFAC(4)*GSCFAC
         REQFAC(4)=REQFAC(4)*GSCFAC
         GENFAC(4)=GENFAC(4)*GSCFAC
         LP=1
         DO 25 K=1,NCANC
         IF(CANC(K).EQ.PUL)LP=K
25       CONTINUE
         DO 50 J=1,40
         STHIG(J)=0.0
         STLOW(J)=0.0
         STCOM(J)=0.0
         STGLO(J)=0.0
         STGHI(J)=0.0
         STGCO(J)=0.0
         STREQ(J)=0.0
         STGRQ(J)=0.0
         STLLL(J)=0.0
         STHLL(J)=0.0
         STCLL(J)=0.0
50       CONTINUE
         SUML=0.0
         SUMH=0.0
         SUMC=0.0
         SUMLLL=0.0
         SUMHLL=0.0
         SUMCLL=0.0
         TBEQ=0.0
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      RLL=0.0
      YRP=RYRLL*WLRN(JLOC,ILOC)*POPFAC
      RR=RRISK*WLRN(JLOC,ILOC)*POPFAC
      IF(WLRN(JLOC,ILOC).NE.0.0)RLL=RYRLL/RRISK
      RP=RR
      DO 109 L=1,NCANC
      DO 100 K=1,4
      FACNEW=POPFAC*RISFAC(K)
      FACNE2=POPFAC*GENFAC(K)
      DO 100 J=1,NONCLD
      STHIG(L)=STHIG(L)+RISK(L,J,K,2)*FACNEW*EXPP(JLOC,ILOC,J,K)
      STHLL(L)=STHLL(L)+YRLL(L,J,K,2)*FACNEW*EXPP(JLOC,ILOC,J,K)
      STLOW(L)=STLOW(L)+RISK(L,J,K,1)*FACNEW*EXPP(JLOC,ILOC,J,K)
      STLLL(L)=STLLL(L)+YRLL(L,J,K,1)*FACNEW*EXPP(JLOC,ILOC,J,K)
      STCOM(L)=STCOM(L)+RISK(L,J,K,1)*FACNEW*EXPP(JLOC,ILOC,J,K)
     <+RISK(L,J,K,2)*FACNEW*EXPP(JLOC,ILOC,J,K)
      STCLL(L)=STCLL(L)+YRLL(L,J,K,1)*FACNEW*EXPP(JLOC,ILOC,J,K)
     <+YRLL(L,J,K,2)*FACNEW*EXPP(JLOC,ILOC,J,K)
      STREQ(L)=STREQ(L)+REF(L,J,K)*POPFAC*REQFAC(K)*EXPP(JLOC,
     <ILOC,J,K)
      IF(L.GT.1) GO TO 100
      TBEQ=TBEQ+REF(NCANC+1,J,K)*POPFAC*REQFAC(K)*EXPP(JLOC,
     <ILOC,J,K)
      STGRQ(L)=STGRQ(L)+GREF(L,J,K)*FACNE2*EXPP(JLOC,ILOC,J,K)
      STGLO(L)=STGLO(L)+GRISK(L,J,K,1)*FACNE2*EXPP(JLOC,ILOC,J,K)
      STGHI(L)=STGHI(L)+GRISK(L,J,K,2)*FACNE2*EXPP(JLOC,ILOC,J,K)
      STGCO(L)=STGCO(L)+GRISK(L,J,K,1)*FACNE2*EXPP(JLOC,ILOC,J,K)+
     A GRISK(L,J,K,2)*FACNE2*EXPP(JLOC,ILOC,J,K)
100   CONTINUE
      SUML=SUML+STLOW(L)
      SUMH=SUMH+STHIG(L)
      SUMLLL=SUMLLL+STLLL(L)
      SUMHLL=SUMHLL+STHLL(L)
      SUMCLL=SUMCLL+STCLL(L)
      SUMC=SUMC+STCOM(L)
      IF(L.EQ.LP) STCPH=STCLL(L)
      IF(L.EQ.LP)STCCH=STCOM(L)
      IF(STLOW(L).NE.0.0)STLLL(L)=STLLL(L)/STLOW(L)
      IF(STHIG(L).NE.0.0)STHLL(L)=STHLL(L)/STHIG(L)
      IF(STCOM(L).NE.0.0)STCLL(L)=STCLL(L)/STCOM(L)
109   CONTINUE
      IF(SUML.NE.0.0)SUMLLL=SUMLLL/SUML
      IF(SUMH.NE.0.0)SUMHLL=SUMHLL/SUMH
      IF(SUMC.NE.0.0) YRT=(RYRLL*WLRN(JLOC,ILOC)*POPFAC+SUMCLL)/
     A (SUMC+RRISK*POPFAC*WLRN(JLOC,ILOC))
      IF(SUMC.NE.0.0)SUMCLL=SUMCLL/SUMC
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        YRP=STCPH+YRP
        RP=RP+STCCH
        IF(RP.NE.0.0) YRP=YRP/RP
        WRITE(27,101)DATE_AND_TIME
101     FORMAT('1',T10,'DATE',2X,A)
        WRITE(27,10100)
        WRITE(27,10102)(CANC(L),L=1,NCANC),TOTAL
10100   FORMAT('0',/30X,'RISK/RISK EQUIVALENT SUMMARY'//
     A  '0*** SELECTED INDIVIDUAL  ***'/
     B  '0LIFETIME FATAL CANCER RISK:'/)
10102   FORMAT(16X,' CANCERS:',10(2X,A8)/(26X,10(2X,A8)))
        IF ( (SEP_RISK_LET_TABLES ) .OR. (ALL_RISK_LET_TABLES) ) THEN
           WRITE(27,10205) (STLOW(L),L=1,NCANC),SUML
           WRITE(27,10210) (STHIG(L),L=1,NCANC),SUMH
        ENDIF
        IF ( ( COMB_RISK_LET_TABLES ) .OR. ( ALL_RISK_LET_TABLES) )
     +     WRITE(27,10215) (STCOM(L),L=1,NCANC),SUMC
        IF(RNWR)WRITE(27,20216) RR
        TT=SUMC+RR
20216   FORMAT('0LUNG CANCER RISK FROM RADON DAUGHTER EXPOSURE ',
     A  8X,1PE10.2)
        IF(RNWR)WRITE(27,20217) TT
20217   FORMAT(' TOTAL FATAL CANCER RISK FROM ALL EXPOSURES',
     A  12X,1PE10.2)
10205   FORMAT(' LOW LET ',16X,10(1PE10.2)/(26X,10(1PE10.2)))
10210   FORMAT(' HIGH LET',16X,10(1PE10.2)/(26X,10(1PE10.2)))
10215   FORMAT('  TOTAL',18X,10(1PE10.2)/(26X,10(1PE10.2)))
        WRITE(27,30100)
30100   FORMAT('0AVERAGE LIFE LOSS PER PREMATURE DEATH:')
        WRITE(27,10102) (CANC(L),L=1,NCANC),TOTAL
        IF ( (SEP_RISK_LET_TABLES ) .OR. (ALL_RISK_LET_TABLES) ) THEN
          WRITE(27,10250) (STLLL(L),L=1,NCANC),SUMLLL
          WRITE(27,10255) (STHLL(L),L=1,NCANC),SUMHLL
        ENDIF
        IF ( ( COMB_RISK_LET_TABLES ) .OR. ( ALL_RISK_LET_TABLES) )
     +    WRITE(27,10260) (STCLL(L),L=1,NCANC),SUMCLL
        IF(RNWR)WRITE(27,20218) RLL
20218   FORMAT('0AVG LIFE LOSS FROM RADON DAUGHTER EXPOSURE ',
     A  'FOR LUNG',3X,1PE10.2)
        IF(RNWR)WRITE(27,20219)YRP
20219   FORMAT(' AVG LIFE LOSS FROM ALL EXPOSURES FOR LUNG',
     A  13X,1PE10.2)
        IF(RNWR)WRITE(27,20220) YRT
20220   FORMAT(' AVG LIFE LOSS FROM ALL EXPOSURES (TOTAL)  ',
     A  12X,1PE10.2)
10250   FORMAT(' LOW LET (YR)',12X,10(1PE10.2)/(26X,10(1PE10.2)))
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

10255    FORMAT(' HIGH LET (YR)',11X,10(1PE10.2)/(26X,10(1PE10.2)))
10260    FORMAT(' COMBINED (YR)',11X,10(1PE10.2)/(26X,10(1PE10.2)))
         RQ=RREF(1)*WLRN(JLOC,ILOC)*POPFAC
         RT=RREF(2)*WLRN(JLOC,ILOC)*POPFAC
         TTP=RQ+STREQ(LP)
         TTQ=RT+TBEQ
         IF(RNWR)WRITE(27,20221) RQ
         IF(RNWR)WRITE(27,20222) RT
         IF(RNWR)WRITE(27,20224) TTP
         IF(RNWR)WRITE(27,20223) TTQ
20221    FORMAT(' LUNG RISK EQUIVALENT(MREM/YR) FROM RADON ',
     A   'DAUGHTER EXPOSURE  ',4X,1PE10.2)
20321    FORMAT(' LUNG RISK EQ. (PERSON REM/YR) FROM RADON ',
     A   'DAUGHTER EXPOSURE',6X,1PE10.2)
20222    FORMAT(' WHOLE BODY RISK EQ (MREM/YR) FROM RADON ',
     A   'DAUGHTER EXPOSURE ',6X,1PE10.2)
20322    FORMAT(' WHOLE BODY RISK EQ (PERSON REM/YR) FROM RADON ',
     A   'DAUGHTER EXPOSURE',1X,1PE10.2)
20223    FORMAT(' WHOLE BODY RISK EQ (MREM/YR) FROM ALL EXPOSURES',
     A17X,1PE10.2)
20224    FORMAT(' PULMNARY RISK EQ (MREM/YR) FOR ALL EXPOSURES',
     A   20X,1PE10.2)
20323    FORMAT(' WHOLE BODY RISK EQ (PERSON REM/YR) FROM ALL EXPOSURES',
     A11X,1PE10.2)
20324    FORMAT(' PULMNARY RISK EQ (PERSON REM/YR) FOR ALL EXPOSURES',
     A   14X,1PE10.2)

10225    FORMAT(' LOW LET (EFFECTS/BIRTH)',1X,10(1PE10.2)/
     >   (26X,10(1PE10.2)))
10230    FORMAT(' HIGH LET (EFFECTS/BIRTH)',10(1PE10.2)/
     >   (26X,10(1PE10.2)))
10235    FORMAT(' COMBINED (EFFECTS/BIRTH)',10(1PE10.2)/
     >   (26X,10(1PE10.2)))
30300    FORMAT('0GENETIC RISK EQUIVALENT:'/
     A   ' (MREM/YR)',15X,10(1PE10.2)/(26X,10(1PE10.2)))
         IF(INDPOP.NE.1) GO TO 1000
         DO 150 J=1,40
         STHIG(J)=0.0
         STLOW(J)=0.0
         STCOM(J)=0.0
         STGLO(J)=0.0
         STGHI(J)=0.0
         STGCO(J)=0.0
         STREQ(J)=0.0
         STLLL(J)=0.0
         STHLL(J)=0.0
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        STCLL(J)=0.0
        STGRQ(J)=0.0
150     CONTINUE
        TBEQ=0.0
        SUML=0.0
        SUMH=0.0
        SUMC=0.0
        SUMLLL=0.0
        SUMHLL=0.0
        SUMCLL=0.0
        RRM=0.0
        RLL=0.0
        RQM=0.0
        RTM=0.0
        YRP=0.0
        DO 206 II=NOL,NOU
        DO 206 JJ=NRL,NRU
        RQM=RQM+RREF(1)*WLRN(JJ,II)*TOTFAC
        RTM=RTM+RREF(2)*WLRN(JJ,II)*TOTFAC
        RRM=RRISK*WLRN(JJ,II)*TOTFAC+RRM
        YRP=RYRLL*WLRN(JJ,II)*TOTFAC+YRP
206     CONTINUE
        IF(RRM.NE.0.0)RLL=YRP/RRM
        RP=YRP
        DO 209 L=1,NCANC
        DO 200 K=1,4
        FACNEW=TOTFAC*RISFAC(K)
        FACNE2=TOTFAC*GENFAC(K)
        DO 200 J=1,NONCLD
        DO 200 II=NOL,NOU
        DO 200 JJ=NRL,NRU
        STHIG(L)=STHIG(L)+RISK(L,J,K,2)*EXPP(JJ,II,J,K)*FACNEW
        STHLL(L)=STHLL(L)+YRLL(L,J,K,2)*EXPP(JJ,II,J,K)*FACNEW
        STLOW(L)=STLOW(L)+RISK(L,J,K,1)*EXPP(JJ,II,J,K)*FACNEW
        STLLL(L)=STLLL(L)+YRLL(L,J,K,1)*EXPP(JJ,II,J,K)*FACNEW
        STCOM(L)=STCOM(L)+RISK(L,J,K,1)*EXPP(JJ,II,J,K)*FACNEW
    >   +RISK(L,J,K,2)*EXPP(JJ,II,J,K)*FACNEW
        STCLL(L)=STCLL(L)+YRLL(L,J,K,1)*EXPP(JJ,II,J,K)*FACNEW
    >   +YRLL(L,J,K,2)*EXPP(JJ,II,J,K)*FACNEW
        STREQ(L)=STREQ(L)+REF(L,J,K)*EXPP(JJ,II,J,K)*TOTFAC
    >   *REQFAC(K)
        IF(L.NE.1) GO TO 200
        TBEQ=TBEQ+REF(NCANC+1,J,K)*EXPP(JJ,II,J,K)*TOTFAC*REQFAC(K)
        STGRQ(L)=STGRQ(L)+GREF(L,J,K)*EXPP(JJ,II,J,K)*TOTFAC*GENFAC(K)
        STGLO(L)=STGLO(L)+GRISK(L,J,K,1)*EXPP(JJ,II,J,K)*FACNE2
        STGHI(L)=STGHI(L)+GRISK(L,J,K,2)*EXPP(JJ,II,J,K)*FACNE2
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        STGCO(L)=STGCO(L)+GRISK(L,J,K,1)*EXPP(JJ,II,J,K)*FACNE2+
     A  GRISK(L,J,K,2)*EXPP(JJ,II,J,K)*FACNE2
200     CONTINUE
        SUML=SUML+STLOW(L)
        SUMH=SUMH+STHIG(L)
        SUMC=SUMC+STCOM(L)
        SUMLLL=SUMLLL+STLLL(L)
        SUMHLL=SUMHLL+STHLL(L)
        SUMCLL=SUMCLL+STCLL(L)
        IF(L.EQ.LP) STCPH=STCLL(LP)
        IF(L.EQ.LP) STCCH=STCOM(LP)
        IF(STLOW(L).NE.0.0)STLLL(L)=STLLL(L)/STLOW(L)
        IF(STHIG(L).NE.0.0)STHLL(L)=STHLL(L)/STHIG(L)
        IF(STCOM(L).NE.0.0)STCLL(L)=STCLL(L)/STCOM(L)
209     CONTINUE
        IF(SUML.NE.0.0)SUMLLL=SUMLLL/SUML
        IF(SUMH.NE.0.0)SUMHLL=SUMHLL/SUMH
        IF(SUMC.NE.0.0) YRT=(YRP+SUMCLL)/(RRM+SUMC)
        YRP=STCPH+YRP
        RP=RRM+STCCH
        IF(RP.NE.0.0)YRP=YRP/RP
        IF(SUMC.NE.0.0)SUMCLL=SUMCLL/SUMC
        WRITE(27,101)DATE_AND_TIME
        WRITE(27,10400)
        WRITE(27,10402)(CANC(L),L=1,NCANC),TOTAL
10400   FORMAT('0'/30X,'RISK/RISK EQUIVALENT SUMMARY'//
     A  '0*** MEAN INDIVIDUAL  ***'/
     B  '0LIFETIME FATAL CANCER RISK:'/)
10402   FORMAT(16X,' CANCERS:',10(2X,A8)/(26X,10(2X,A8)))
        IF ( (SEP_RISK_LET_TABLES ) .OR. (ALL_RISK_LET_TABLES) ) THEN
           WRITE(27,10205) (STLOW(L),L=1,NCANC),SUML
           WRITE(27,10210) (STHIG(L),L=1,NCANC),SUMH
        ENDIF
        IF ( ( COMB_RISK_LET_TABLES ) .OR. ( ALL_RISK_LET_TABLES) )
     +     WRITE(27,10215) (STCOM(L),L=1,NCANC),SUMC

        IF(RNWR)WRITE(27,20216) RRM
        TTM=SUMC+RRM
        IF(RNWR)WRITE(27,20217)TTM
        WRITE(27,30100)
        WRITE(27,10102) (CANC(L),L=1,NCANC),TOTAL
        IF ( (SEP_RISK_LET_TABLES ) .OR. (ALL_RISK_LET_TABLES) ) THEN
          WRITE(27,10250) (STLLL(L),L=1,NCANC),SUMLLL
          WRITE(27,10255) (STHLL(L),L=1,NCANC),SUMHLL
        ENDIF
        IF ( ( COMB_RISK_LET_TABLES ) .OR. ( ALL_RISK_LET_TABLES) )
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

     +    WRITE(27,10260) (STCLL(L),L=1,NCANC),SUMCLL

          IF(RNWR)WRITE(27,20218) RLL
          IF(RNWR)WRITE(27,20219) YRP
          IF(RNWR)WRITE(27,20220) YRT
          IF(RNWR)WRITE(27,20221) RQM
          IF(RNWR)WRITE(27,20222) RTM
          TTP=RQM+STREQ(LP)
          IF(RNWR)WRITE(27,20224) TTP
          TTQM=RTM+TBEQ
          IF(RNWR)WRITE(27,20223) TTQM
          DO 350 K=1,40
          STLOW(K)=0.0
          STHIG(K)=0.0
          STCOM(K)=0.0
          STGLO(K)=0.0
          STGHI(K)=0.0
          STGCO(K)=0.0
          STREQ(K)=0.0
          STLLL(K)=0.0
          STHLL(K)=0.0
          STCLL(K)=0.0
          STGRQ(K)=0.0
350       CONTINUE
          SUML=0.0
          TBEQ=0.0
          SUMH=0.0
          SUMC=0.0
          SUMLLL=0.0
          SUMHLL=0.0
          SUMCLL=0.0
          WLT=0.0
          DO 401 II=NOL,NOU
          DO 401 JJ=NRL,NRU
          WLT=WLT+WLRN(JJ,II)
401       CONTINUE
          RRC=RRISK*WLT/AGEX
          RQC=RREF(1)*WLT*.001
          RTC=RREF(2)*WLT*.001
          DO 400 K=1,4
          DO 400 J=1,NONCLD
          TEXPP=0.0
          DO 403 II=NOL,NOU
          DO 403 JJ=NRL,NRU
          TEXPP=TEXPP+EXPP(JJ,II,J,K)
403       CONTINUE
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
        DO 400 L=1,NCANC
        STLOW(L)=STLOW(L)+RISK(L,J,K,1)*TEXPP*RISFAC(K)/AGEX
        STLLL(L)=STLLL(L)+YRLL(L,J,K,1)*TEXPP*RISFAC(K)/AGEX
        SUML=SUML+RISK(L,J,K,1)*TEXPP*RISFAC(K)/AGEX
        SUMLLL=SUMLLL+YRLL(L,J,K,1)*TEXPP*RISFAC(K)/AGEX
        STHIG(L)=STHIG(L)+RISK(L,J,K,2)*TEXPP*RISFAC(K)/AGEX
        STHLL(L)=STHLL(L)+YRLL(L,J,K,2)*TEXPP*RISFAC(K)/AGEX
        SUMH=SUMH+RISK(L,J,K,2)*TEXPP*RISFAC(K)/AGEX
        SUMHLL=SUMHLL+YRLL(L,J,K,2)*TEXPP*RISFAC(K)/AGEX
        STCOM(L)=STCOM(L)+RISK(L,J,K,1)*TEXPP*RISFAC(K)/AGEX+
     >  RISK(L,J,K,2)*TEXPP*RISFAC(K)/AGEX
        STCLL(L)=STCLL(L)+YRLL(L,J,K,1)*TEXPP*
     >  RISFAC(K)/AGEX+
     >  YRLL(L,J,K,2)*TEXPP*RISFAC(K)/AGEX
        SUMC=SUMC+RISK(L,J,K,1)*TEXPP*RISFAC(K)/AGEX+
     A  RISK(L,J,K,2)*TEXPP*RISFAC(K)/AGEX
        SUMCLL=SUMCLL+YRLL(L,J,K,1)*TEXPP*RISFAC(K)/AGEX+
     A  YRLL(L,J,K,2)*TEXPP*RISFAC(K)/AGEX
        STREQ(L)=STREQ(L)+REF(L,J,K)*TEXPP*REQFAC(K)*.001
        IF(L.NE.1) GO TO 400
        TBEQ=TBEQ+REF(NCANC+1,J,K)*TEXPP*REQFAC(K)*.001
        STGRQ(L)=STGRQ(L)+GREF(L,J,K)*TEXPP*GENFAC(K)*.001
        STGLO(L)=STGLO(L)+GRISK(L,J,K,1)*TEXPP*GENFAC(K)*REPPER
        STGHI(L)=STGHI(L)+GRISK(L,J,K,2)*TEXPP*GENFAC(K)*REPPER
        STGCO(L)=STGCO(L)+GRISK(L,J,K,1)*TEXPP*GENFAC(K)*REPPER+
     A  GRISK(L,J,K,2)*TEXPP*GENFAC(K)*REPPER
400     CONTINUE
        WRITE(27,101)DATE_AND_TIME

        WRITE(27,10700) (CANC(L),L=1,NCANC),TOTAL
10700   FORMAT('0',/29X,'RISK/RISK EQUIVALENT SUMMARY'/
     1  /'0*** COLLECTIVE POPULATION ***'/
     A  '0COLLECTIVE FATAL CANCER RISK:'/
     A  16X,' CANCERS:',10(2X,A8)/(26X,10(2X,A8)))
10705   FORMAT(' LOW LET(DEATHS/YR)',6X,10(1PE10.2)/
     A  (26X,10(1PE10.2)))
10710   FORMAT(' HIGH LET(DEATHS/YR)',5X,10(1PE10.2)/
     A  (26X,10(1PE10.2)))
        IF ( (SEP_RISK_LET_TABLES ) .OR. (ALL_RISK_LET_TABLES) ) THEN
           WRITE(27,10705) (STLOW(L),L=1,NCANC),SUML
           WRITE(27,10710) (STHIG(L),L=1,NCANC),SUMH
        ENDIF
        IF ( ( COMB_RISK_LET_TABLES ) .OR. ( ALL_RISK_LET_TABLES) )
     +     WRITE(27,10715) (STCOM(L),L=1,NCANC),SUMC
        IF(RNWR)WRITE(27,20316) RRC
        TTC=SUMC+RRC
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        IF(RNWR)WRITE(27,20317) TTC
20316   FORMAT('0LUNG CANCER RISK(DEATHS/YR) FROM RADON DAUGHTER',
     > ' EXPOSURE',8X,1PE10.2)
20317   FORMAT(' TOTAL FATAL CANCER RISK(DEATHS/YR) FROM ALL',
     > ' EXPOSURE',12X,1PE10.2)
10750   FORMAT(' LOST LOW LET',12X,10(1PE10.2)/(26X,10(1PE10.2)))
10755   FORMAT(' LIFE LOST HIGH LET',6X,10(1PE10.2)/(26X,10(1PE10.2)))
10760   FORMAT(' LIFE LOST COMBINED',6X,10(1PE10.2)/(26X,10(1PE10.2)))
10715   FORMAT('  TOTAL (DEATHS/YR)',6X,10(1PE10.2)/
     A  (26X,10(1PE10.2)))
        IF(RNWR)WRITE(27,20321) RQC
        IF(RNWR)WRITE(27,20322) RTC
        TTPC=RQC+STREQ(LP)
        IF(RNWR)WRITE(27,20324) TTPC
        TTQC=RTC+TBEQ
        IF(RNWR)WRITE(27,20323) TTQC
10720   FORMAT('0GENETIC RISK EQUIVALENT:'/
     1 ' (PERSON REM/YR)',9X,10(1PE10.2)/
     A  (26X,10(1PE10.2)))

10725   FORMAT(' LOW LET(EFFECTS/YR)',5X,10(1PE10.2)/
     >  (26X,10(1PE10.2)))
10730   FORMAT(' HIGH LET(EFFECTS/YR)',4X,10(1PE10.2)/
     >  (26X,10(1PE10.2)))
10735   FORMAT(' COMBINED(EFFECTS/YR)',4X,10(1PE10.2)/
     >  (26X,10(1PE10.2)))
        WRITE(27,10720) STGRQ(1)
C****   RISK RATES BY PATHWAY
1000    DO 1050 J=1,40
        STHIG(J)=0.0
        STLOW(J)=0.0
        STCOM(J)=0.0
        STREQ(J)=0.0
        STGRQ(J)=0.0
        STGLO(J)=0.0
        STGHI(J)=0.0
        STGCO(J)=0.0
1050    CONTINUE
        DO 1199 K=1,4
        DO 1100 L=1,NCANC
        FACNEW=POPFAC*RISFAC(K)
        FACNE2=POPFAC*GENFAC(K)
        DO 1100 J=1,NONCLD
        STHIG(K)=STHIG(K)+RISK(L,J,K,2)*FACNEW*EXPP(JLOC,ILOC,J,K)
        STLOW(K)=STLOW(K)+RISK(L,J,K,1)*FACNEW*EXPP(JLOC,ILOC,J,K)
        STCOM(K)=STCOM(K)+RISK(L,J,K,1)*FACNEW*EXPP(JLOC,ILOC,J,K)
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

     <  +RISK(L,J,K,2)*FACNEW*EXPP(JLOC,ILOC,J,K)
        IF(L.NE.1) GO TO 1100
        STREQ(K)=STREQ(K)+REF(NCANC+1,J,K)*POPFAC*REQFAC(K)*
     <  EXPP(JLOC,ILOC,J,K)
        STGRQ(K)=STGRQ(K)+GREF(L,J,K)*POPFAC*GENFAC(K)*
     <  EXPP(JLOC,ILOC,J,K)
        STGHI(K)=STGHI(K)+GRISK(L,J,K,2)*FACNE2*EXPP(JLOC,ILOC,J,K)
        STGLO(K)=STGLO(K)+GRISK(L,J,K,1)*FACNE2*EXPP(JLOC,ILOC,J,K)
        STGCO(K)=STGCO(K)+GRISK(L,J,K,1)*FACNE2*EXPP(JLOC,ILOC,J,K)+
     A  GRISK(L,J,K,2)*FACNE2*EXPP(JLOC,ILOC,J,K)
1100    CONTINUE
1103    IF(K.GT.2) GO TO 1101
        STHIG(5)=STHIG(5)+STHIG(K)
        STLOW(5)=STLOW(5)+STLOW(K)
        STCOM(5)=STCOM(5)+STCOM(K)
        STGHI(5)=STGHI(5)+STGHI(K)
        STGLO(5)=STGLO(5)+STGLO(K)
        STGCO(5)=STGCO(5)+STGCO(K)
        STGRQ(5)=STGRQ(5)+STGRQ(K)
        STREQ(5)=STREQ(5)+STREQ(K)
1101    IF(K.LT.3) GO TO 1102
        STHIG(6)=STHIG(6)+STHIG(K)
        STLOW(6)=STLOW(6)+STLOW(K)
        STCOM(6)=STCOM(6)+STCOM(K)
        STGRQ(6)=STGRQ(6)+STGRQ(K)
        STREQ(6)=STREQ(6)+STREQ(K)
        STGHI(6)=STGHI(6)+STGHI(K)
        STGLO(6)=STGLO(6)+STGLO(K)
        STGCO(6)=STGCO(6)+STGCO(K)
1102    STHIG(7)=STHIG(7)+STHIG(K)
        STLOW(7)=STLOW(7)+STLOW(K)
        STCOM(7)=STCOM(7)+STCOM(K)
        STGRQ(7)=STGRQ(7)+STGRQ(K)
        STREQ(7)=STREQ(7)+STREQ(K)
        STGHI(7)=STGHI(7)+STGHI(K)
        STGLO(7)=STGLO(7)+STGLO(K)
        STGCO(7)=STGCO(7)+STGCO(K)
1199    CONTINUE
        WRITE(27,101)DATE_AND_TIME
        WRITE(27,11100)
        WRITE(27,11102)
11100   FORMAT('0',/30X,'PATHWAY RISK/RISK EQUIVALENT SUMMARY'
     A  //'0*** SELECTED INDIVIDUAL ***'/
     A  '0LIFETIME FATAL CANCER RISK:'/)
11102   FORMAT('               PATHWAYS:  INGESTION ',
     <  'INHALATION    AIR     GROUND',
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

     <  '     INTERNAL  EXTERNAL   TOTAL'/
     <  45X,' IMMERSION  SURFACE')
        IF ( (SEP_RISK_LET_TABLES ) .OR. (ALL_RISK_LET_TABLES) ) THEN
           WRITE(27,10205) (STLOW(L),L=1,7)
          WRITE(27,10210) (STHIG(L),L=1,7)
        ENDIF
        IF ( ( COMB_RISK_LET_TABLES ) .OR. ( ALL_RISK_LET_TABLES) )
     +     WRITE(27,10215) (STCOM(L),L=1,7)
        IF(RNWR)WRITE(27,20216) RR
        IF(RNWR)WRITE(27,20217)TT
        IF(RNWR)WRITE(27,20422) RT
20422   FORMAT('0WHOLE BODY RISK EQ(MREM/YR) FROM RADON',
     > ' DAUGHTER  EXPOSURE',7X,1PE10.2)
        IF(RNWR)WRITE(27,20223) TTQ

        IF(INDPOP.NE.1) GO TO 11000
        DO 1150 J=1,40
        STHIG(J)=0.0
        STLOW(J)=0.0
        STCOM(J)=0.0
        STREQ(J)=0.0
        STGRQ(J)=0.0
        STGLO(J)=0.0
        STGHI(J)=0.0
        STGCO(J)=0.0
1150    CONTINUE
        TBEQ=0.0
        DO 1299 K=1,4
        FACNEW=TOTFAC*RISFAC(K)
        FACNE2=TOTFAC*GENFAC(K)
        DO 1200 L=1,NCANC
        DO 1200 J=1,NONCLD
        DO 1200 II=NOL,NOU
        DO 1200 JJ=NRL,NRU
        STHIG(K)=STHIG(K)+RISK(L,J,K,2)*EXPP(JJ,II,J,K)*FACNEW
        STLOW(K)=STLOW(K)+RISK(L,J,K,1)*EXPP(JJ,II,J,K)*FACNEW
        STCOM(K)=STCOM(K)+RISK(L,J,K,1)*EXPP(JJ,II,J,K)*FACNEW
     >  +RISK(L,J,K,2)*EXPP(JJ,II,J,K)*FACNEW
        IF(L.GT.1) GO TO 1200
        STREQ(K)=STREQ(K)+REF(NCANC+1,J,K)*EXPP(JJ,II,J,K)*
     >  TOTFAC*REQFAC(K)
        STGRQ(K)=STGRQ(K)+GREF(L,J,K)*EXPP(JJ,II,J,K)*
     >  TOTFAC*GENFAC(K)
        STGHI(K)=STGHI(K)+GRISK(L,J,K,2)*EXPP(JJ,II,J,K)*FACNE2
        STGLO(K)=STGLO(K)+GRISK(L,J,K,1)*EXPP(JJ,II,J,K)*FACNE2
        STGCO(K)=STGCO(K)+GRISK(L,J,K,1)*EXPP(JJ,II,J,K)*FACNE2+
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

     A  GRISK(L,J,K,2)*EXPP(JJ,II,J,K)*FACNE2
1200     CONTINUE
1203     IF(K.GT.2) GO TO 1201
         STHIG(5)=STHIG(5)+STHIG(K)
         STLOW(5)=STLOW(5)+STLOW(K)
         STCOM(5)=STCOM(5)+STCOM(K)
         STGRQ(5)=STGRQ(5)+STGRQ(K)
         STREQ(5)=STREQ(5)+STREQ(K)
         STGLO(5)=STGLO(5)+STGLO(K)
         STGHI(5)=STGHI(5)+STGHI(K)
         STGCO(5)=STGCO(5)+STGCO(K)
1201     IF(K.LT.3) GO TO 1202
         STHIG(6)=STHIG(6)+STHIG(K)
         STLOW(6)=STLOW(6)+STLOW(K)
         STCOM(6)=STCOM(6)+STCOM(K)
         STGRQ(6)=STGRQ(6)+STGRQ(K)
         STREQ(6)=STREQ(6)+STREQ(K)
         STGLO(6)=STGLO(6)+STGLO(K)
         STGHI(6)=STGHI(6)+STGHI(K)
         STGCO(6)=STGCO(6)+STGCO(K)
1202     STHIG(7)=STHIG(7)+STHIG(K)
         STLOW(7)=STLOW(7)+STLOW(K)
         STCOM(7)=STCOM(7)+STCOM(K)
         STGRQ(7)=STGRQ(7)+STGRQ(K)
         STREQ(7)=STREQ(7)+STREQ(K)
         STGLO(7)=STGLO(7)+STGLO(K)
         STGHI(7)=STGHI(7)+STGHI(K)
         STGCO(7)=STGCO(7)+STGCO(K)
1299     CONTINUE
         WRITE(27,101)DATE_AND_TIME
         WRITE(27,11400)
         WRITE(27,11102)
11400    FORMAT(/'0',/
     >   29X,'PATHWAY RISK/RISK EQUIVALENT SUMMARY'//
     A   '0***MEAN INDIVIDUAL ***'/
     B   'OLIFETIME FATAL CANCER RISK:'/)

         IF ( (SEP_RISK_LET_TABLES ) .OR. (ALL_RISK_LET_TABLES) ) THEN
            WRITE(27,10205) (STLOW(L),L=1,7)
           WRITE(27,10210) (STHIG(L),L=1,7)
         ENDIF
         IF ( ( COMB_RISK_LET_TABLES ) .OR. ( ALL_RISK_LET_TABLES) )
     +      WRITE(27,10215) (STCOM(L),L=1,7)


         IF(RNWR)WRITE(27,20216) RRM
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      IF(RNWR)WRITE(27,20217) TTM
      IF(RNWR)WRITE(27,20422) RTM
      IF(RNWR)WRITE(27,20223) TTQM
      DO 1350 K=1,40
      STLOW(K)=0.0
      STHIG(K)=0.0
      STCOM(K)=0.0
      STGLO(K)=0.0
      STGHI(K)=0.0
      STGCO(K)=0.0
      STREQ(K)=0.0
      STGRQ(K)=0.0
1350  CONTINUE
      DO 1499 K=1,4
      DO 1400 J=1,NONCLD
      TEXPP=0.0
      DO 1404 II=NOL,NOU
      DO 1404 JJ=NRL,NRU
      TEXPP=TEXPP+EXPP(JJ,II,J,K)
1404  CONTINUE
      DO 1400 L=1,NCANC
      STLOW(K)=STLOW(K)+RISK(L,J,K,1)*TEXPP*RISFAC(K)/AGEX
      STHIG(K)=STHIG(K)+RISK(L,J,K,2)*TEXPP*RISFAC(K)/AGEX
      STCOM(K)=STCOM(K)+RISK(L,J,K,1)*TEXPP*RISFAC(K)/AGEX+
     > RISK(L,J,K,2)*TEXPP*RISFAC(K)/AGEX
      IF(L.GT.1) GO TO 1400
      STREQ(K)=STREQ(K)+REF(NCANC+1,J,K)*TEXPP*REQFAC(K)*.001
      STGRQ(K)=STGRQ(K)+GREF(L,J,K)*TEXPP*GENFAC(K)*.001
      STGLO(K)=STGLO(K)+GRISK(L,J,K,1)*TEXPP*GENFAC(K)*REPPER
      STGHI(K)=STGHI(K)+GRISK(L,J,K,2)*TEXPP*GENFAC(K)*REPPER
      STGCO(K)=STGCO(K)+GRISK(L,J,K,1)*TEXPP*GENFAC(K)*REPPER+
     A GRISK(L,J,K,2)*TEXPP*GENFAC(K)*REPPER
1400  CONTINUE
1403  IF(K.GT.2) GO TO 1401
      STLOW(5)=STLOW(5)+STLOW(K)
      STHIG(5)=STHIG(5)+STHIG(K)
      STCOM(5)=STCOM(5)+STCOM(K)
      STGLO(5)=STGLO(5)+STGLO(K)
      STGHI(5)=STGHI(5)+STGHI(K)
      STGCO(5)=STGCO(5)+STGCO(K)
      STGRQ(5)=STGRQ(5)+STGRQ(K)
      STREQ(5)=STREQ(5)+STREQ(K)
      GO TO 1402
1401  STLOW(6)=STLOW(6)+STLOW(K)
      STHIG(6)=STHIG(6)+STHIG(K)
      STCOM(6)=STCOM(6)+STCOM(K)
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
1234567890123456789012345678901234567890123456789012345678901234567890123456789012

        STGLO(6)=STGLO(6)+STGLO(K)
        STGHI(6)=STGHI(6)+STGHI(K)
        STGCO(6)=STGCO(6)+STGCO(K)
        STGRQ(6)=STGRQ(6)+STGRQ(K)
        STREQ(6)=STREQ(6)+STREQ(K)
1402    STLOW(7)=STLOW(7)+STLOW(K)
        STHIG(7)=STHIG(7)+STHIG(K)
        STCOM(7)=STCOM(7)+STCOM(K)
        STGRQ(7)=STGRQ(7)+STGRQ(K)
        STREQ(7)=STREQ(7)+STREQ(K)
        STGLO(7)=STGLO(7)+STGLO(K)
        STGHI(7)=STGHI(7)+STGHI(K)
        STGCO(7)=STGCO(7)+STGCO(K)
1499    CONTINUE
        WRITE(27,101)DATE_AND_TIME
        WRITE(27,11700)
        WRITE(27,11102)
11700   FORMAT(/'0',/
     >  29X,'PATHWAY RISK/RISK EQUIVALENT SUMMARY'//
     A  '0*** COLLECTIVE POPULATION ***'/
     B  '0COLLECTIVE FATAL CANCER RISK:'/)

        IF ( (SEP_RISK_LET_TABLES ) .OR. (ALL_RISK_LET_TABLES) ) THEN
          WRITE(27,10705) (STLOW(L),L=1,7)
          WRITE(27,10710) (STHIG(L),L=1,7)
        ENDIF
        IF ( ( COMB_RISK_LET_TABLES ) .OR. ( ALL_RISK_LET_TABLES) )
     +     WRITE(27,10715) (STCOM(L),L=1,7)

        IF(RNWR)WRITE(27,20316) RRC
        IF(RNWR)WRITE(27,20317) TTC
        IF(RNWR)WRITE(27,20522) RTC
20522   FORMAT('0WHOLE BODY RISK EQ(PERSON REM/YR) FROM RADON ',
     >  'DAUGHTER EXPOSURE',2X,1PE10.2)
        WRITE(27,20323) TTQC
        WRITE(27,10720) (STGRQ(L),L=1,7)
C****   RISK RATES BY NUCLIDE
11000   DO 2050 J=1,40
        STHIG(J)=0.0
        STLOW(J)=0.0
        STCOM(J)=0.0
        STGLO(J)=0.0
        STGHI(J)=0.0
        STGCO(J)=0.0
        STREQ(J)=0.0
        STGRQ(J)=0.0
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
```

```
2050    CONTINUE
        SUML=0.0
        SUMH=0.0
        SUMC=0.0
        SUMGL=0.0
        SUMGH=0.0
        SUMGC=0.0
        SUMRQ=0.0
        SUMGQ=0.0
        DO 2109 J=1,NONCLD
        DO 2100 K=1,4
        FACNEW=POPFAC*RISFAC(K)
        FACNE2=POPFAC*GENFAC(K)
        DO 2100 L=1,NCANC
        STHIG(J)=STHIG(J)+RISK(L,J,K,2)*FACNEW*EXPP(JLOC,ILOC,J,K)
        STLOW(J)=STLOW(J)+RISK(L,J,K,1)*FACNEW*EXPP(JLOC,ILOC,J,K)
        STCOM(J)=STCOM(J)+RISK(L,J,K,1)*FACNEW*EXPP(JLOC,ILOC,J,K)
    <   +RISK(L,J,K,2)*FACNEW*EXPP(JLOC,ILOC,J,K)
        IF(L.GT.1) GO TO 2100
        STREQ(J)=STREQ(J)+REF(NCANC+1,J,K)*POPFAC*REQFAC(K)*
    <   EXPP(JLOC,ILOC,J,K)
        SUMRQ=SUMRQ+REF(NCANC+1,J,K)*POPFAC*REQFAC(K)*
    <   EXPP(JLOC,ILOC,J,K)
        STGRQ(J)=STGRQ(J)+GREF(L,J,K)*POPFAC*GENFAC(K)*
    <   EXPP(JLOC,ILOC,J,K)
        SUMGQ=SUMGQ+GREF(L,J,K)*POPFAC*GENFAC(K)*
    <   EXPP(JLOC,ILOC,J,K)
        STGHI(J)=STGHI(J)+GRISK(L,J,K,2)*EXPP(JLOC,ILOC,J,K)*FACNE2
        STGLO(J)=STGLO(J)+GRISK(L,J,K,1)*EXPP(JLOC,ILOC,J,K)*FACNE2
        STGCO(J)=STGCO(J)+GRISK(L,J,K,1)*EXPP(JLOC,ILOC,J,K)*FACNE2+
    A   GRISK(L,J,K,2)*EXPP(JLOC,ILOC,J,K)*FACNE2
2100    CONTINUE
        SUML=SUML+STLOW(J)
        SUMH=SUMH+STHIG(J)
        SUMC=SUMC+STCOM(J)
        SUMGL=SUMGL+STGLO(J)
        SUMGH=SUMGH+STGHI(J)
        SUMGC=SUMGC+STGCO(J)
2109    CONTINUE
        WRITE(27,101)DATE_AND_TIME
        WRITE(27,12100)
        WRITE(27,12102)(NUCLID(L),L=1,NONCLD),TOTAL
12100   FORMAT('0',/30X,'NUCLIDE RISK/RISK EQUIVALENT SUMMARY'/
     1  /'0*** SELECTED INDIVIDUAL ***'/
     A  '0LIFETIME FATAL CANCER RISK:')
12102   FORMAT(15X,' NUCLIDES:',10(2X,A8)/(26X,10(2X,A8)))
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        IF ( (SEP_RISK_LET_TABLES ) .OR. (ALL_RISK_LET_TABLES) ) THEN
           WRITE(27,10205) (STLOW(L),L=1,NONCLD),SUML
           WRITE(27,10210) (STHIG(L),L=1,NONCLD),SUMH
        ENDIF
        IF ( ( COMB_RISK_LET_TABLES ) .OR. ( ALL_RISK_LET_TABLES) )
     +     WRITE(27,10215) (STCOM(L),L=1,NONCLD),SUMC


        IF(RNWR)WRITE(27,20216) RR
        IF(RNWR)WRITE(27,20217) TT
        IF(RNWR)WRITE(27,20422) RT
        IF(RNWR)WRITE(27,20223) TTQ


        IF(INDPOP.NE.1) GO TO 21000
        DO 2150 J=1,40
        STHIG(J)=0.0
        STLOW(J)=0.0
        STCOM(J)=0.0
        STREQ(J)=0.0
        STGRQ(J)=0.0
        STGLO(J)=0.0
        STGHI(J)=0.0
        STGCO(J)=0.0
2150    CONTINUE
        SUML=0.0
        SUMH=0.0
        SUMC=0.0
        SUMGL=0.0
        SUMGH=0.0
        SUMGC=0.0
        SUMRQ=0.0
        SUMGQ=0.0
        DO 2209 J=1,NONCLD
        DO 2200 L=1,NCANC
        DO 2200 K=1,4
        FACNEW=TOTFAC*RISFAC(K)
        FACNE2=TOTFAC*GENFAC(K)
        DO 2200 II=NOL,NOU
        DO 2200 JJ=NRL,NRU
        STHIG(J)=STHIG(J)+RISK(L,J,K,2)*EXPP(JJ,II,J,K)*FACNEW
        STLOW(J)=STLOW(J)+RISK(L,J,K,1)*EXPP(JJ,II,J,K)*FACNEW
        STCOM(J)=STCOM(J)+RISK(L,J,K,1)*EXPP(JJ,II,J,K)*FACNEW
     >  +RISK(L,J,K,2)*EXPP(JJ,II,J,K)*FACNEW
        IF(L.GT.1) GO TO 2200
        STREQ(J)=STREQ(J)+REF(NCANC+1,J,K)*EXPP(JJ,II,J,K)*TOTFAC*
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

     >  REQFAC(K)
        SUMRQ=SUMRQ+REF(NCANC+1,J,K)*EXPP(JJ,II,J,K)*TOTFAC*
     >  REQFAC(K)
        STGRQ(J)=STGRQ(J)+GREF(L,J,K)*EXPP(JJ,II,J,K)*TOTFAC*
     >  GENFAC(K)
        SUMGQ=SUMGQ+GREF(L,J,K)*EXPP(JJ,II,J,K)*TOTFAC*
     >  GENFAC(K)
        STGHI(J)=STGHI(J)+GRISK(L,J,K,2)*EXPP(JJ,II,J,K)*FACNE2
        STGLO(J)=STGLO(J)+GRISK(L,J,K,1)*EXPP(JJ,II,J,K)*FACNE2
        STGCO(J)=STGCO(J)+GRISK(L,J,K,2)*EXPP(JJ,II,J,K)*FACNE2+
     +  GRISK(L,J,K,1)*EXPP(JJ,II,J,K)*FACNE2
2200    CONTINUE
        SUML=SUML+STLOW(J)
        SUMH=SUMH+STHIG(J)
        SUMC=SUMC+STCOM(J)
        SUMGL=SUMGL+STGLO(J)
        SUMGH=SUMGH+STGHI(J)
        SUMGC=SUMGC+STGCO(J)
2209    CONTINUE
        WRITE(27,101)DATE_AND_TIME
        WRITE(27,12400) (NUCLID(L),L=1,NONCLD),TOTAL
12400   FORMAT('0',/
     >  30X,'NUCLIDE RISK/RISK EQUIVALENT SUMMARY'//
     A  '0*** MEAN INDIVIDUAL ***'/
     B  '0LIFETIME FATAL CANCER RISK:'/
     A  15X,' NUCLIDES:',10(2X,A8)/(26X,10(2X,A8)))

        IF ( (SEP_RISK_LET_TABLES ) .OR. (ALL_RISK_LET_TABLES) ) THEN
           WRITE(27,10205) (STLOW(L),L=1,NONCLD),SUML
           WRITE(27,10210) (STHIG(L),L=1,NONCLD),SUMH
        ENDIF
        IF ( ( COMB_RISK_LET_TABLES ) .OR. ( ALL_RISK_LET_TABLES) )
     +     WRITE(27,10215) (STCOM(L),L=1,NONCLD),SUMC


        IF(RNWR)WRITE(27,20216) RRM
        IF(RNWR)WRITE(27,20217) TTM
        IF(RNWR)WRITE(27,20422) RTM
        IF(RNWR)WRITE(27,20223) TTQM
        DO 2350 K=1,40
        STLOW(K)=0.0
        STHIG(K)=0.0
        STCOM(K)=0.0
        STGLO(K)=0.0
        STGHI(K)=0.0
        STGCO(K)=0.0
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        STREQ(K)=0.0
        STGRQ(K)=0.0
2350    CONTINUE
        SUML=0.0
        SUMH=0.0
        SUMC=0.0
        SUMGL=0.0
        SUMGH=0.0
        SUMGC=0.0
        SUMRQ=0.0
        SUMGQ=0.0
        DO 2409 J=1,NONCLD
        DO 2400 K=1,4
        TEXPP=0.0
        DO 2403 II=NOL,NOU
        DO 2403 JJ=NRL,NRU
        TEXPP=TEXPP+EXPP(JJ,II,J,K)
2403    CONTINUE
        DO 2400 L=1,NCANC
        STLOW(J)=STLOW(J)+RISK(L,J,K,1)*TEXPP*RISFAC(K)/AGEX
        STHIG(J)=STHIG(J)+RISK(L,J,K,2)*TEXPP*RISFAC(K)/AGEX
        STCOM(J)=STCOM(J)+RISK(L,J,K,1)*TEXPP*RISFAC(K)/AGEX+
     >  RISK(L,J,K,2)*TEXPP*RISFAC(K)/AGEX
        IF(L.GT.1) GO TO 2400
        STREQ(J)=STREQ(J)+REF(NCANC+1,J,K)*TEXPP*REQFAC(K)*.001
        SUMRQ=SUMRQ+REF(NCANC+1,J,K)*TEXPP*REQFAC(K)*.001
        STGRQ(J)=STGRQ(J)+GREF(L,J,K)*TEXPP*GENFAC(K)*.001
        SUMGQ=SUMGQ+GREF(L,J,K)*TEXPP*GENFAC(K)*.001
        STGLO(J)=STGLO(J)+GRISK(L,J,K,1)*TEXPP*GENFAC(K)*REPPER
        STGHI(J)=STGHI(J)+GRISK(L,J,K,2)*TEXPP*GENFAC(K)*REPPER
        STGCO(J)=STGCO(J)+GRISK(L,J,K,1)*TEXPP*GENFAC(K)*REPPER
     A  +GRISK(L,J,K,2)*TEXPP*GENFAC(K)*REPPER
2400    CONTINUE
        SUML=SUML+STLOW(J)
        SUMH=SUMH+STHIG(J)
        SUMC=SUMC+STCOM(J)
        SUMGL=SUMGL+STGLO(J)
        SUMGH=SUMGH+STGHI(J)
        SUMGC=SUMGC+STGCO(J)
2409    CONTINUE
        WRITE(27,101)DATE_AND_TIME
        WRITE(27,12700) (NUCLID(L),L=1,NONCLD),TOTAL
12700   FORMAT('0',/
     >  29X,'NUCLIDE RISK/RISK EQUIVALENT SUMMARY'//
     A  '0*** COLLECTIVE POPULATION ***'/
     A  '0COLLECTIVE FATAL CANCER RISK:'/
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

     A  15X,' NUCLIDES:',10(2X,A8)/(26X,10(2X,A8)))

        IF ( (SEP_RISK_LET_TABLES ) .OR. (ALL_RISK_LET_TABLES) ) THEN
           WRITE(27,10705) (STLOW(L),L=1,NONCLD),SUML
           WRITE(27,10710) (STHIG(L),L=1,NONCLD),SUMH
        ENDIF
        IF ( ( COMB_RISK_LET_TABLES ) .OR. ( ALL_RISK_LET_TABLES) )
     +     WRITE(27,10715) (STCOM(L),L=1,NONCLD),SUMC


        IF(RNWR)WRITE(27,20216) RRC
        WRITE(27,20217) TTC
        IF(RNWR)WRITE(27,20522) RTC
        IF(RNWR)WRITE(27,20323) TTQC
21000   RETURN
      END



C=======================================================================
C                                                                      -
C                        SUBROUTINE DRTAB                              -
C                                                                      -
C=======================================================================

      SUBROUTINE DRTAB(ARRAY,NORGN,ORGN,TITLE,TITL1,DTABLE,TITLA,NOTE,
     A  NUN,RFAC,CREP,NCREP, NUCLID)
C***    THIS ROUTINE OUTPUT THE APPROPRIATE TABLES.

      CHARACTER*8 ORGN,NUCLID,ORC,SUM,CREP,RADON

      CHARACTER*80 TITLE,NOTE
      CHARACTER*40 TITL1
      CHARACTER*8  TITLA
      CHARACTER*32 NUN
      CHARACTER*16 PATH



      COMMON/COMRN/WLRN(20,20),RRISK,RREF(2),RYRLL,NOREP,NRREP,NFREP

      COMMON/HEAD/ORC

      INTEGER DTABLE
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
      3         4         5         6         7
3456789012345678901234567890123456789012345678901234567890123456789012

20,40,4),ORGN(1),PATH(7),DTABLE(7),WLSUM(4),
0), NUCLID(40), CREP(20)

CLD,PSIZE(40),GIABS (4,40),INDPOP

X(40,7),SUMY(40,3),PERX(40),PERY(40),TVAL(40),


22  '/
TION       ','INHALATION      ','AIR IMMERSION   '
O SURFACE  ','INTERNAL        ','EXTERNAL        '
           '/

  '/
UCLIDES FOR EACH ORGAN AND PATHWAY
NTERNAL, 6 IS EXTERNAL, AND 7 IS ALL PATHWAYS




,I)+ARRAY(K,J,I)
(K,5)=SUMX(K,5)+ARRAY(K,J,I)
(K,6)=SUMX(K,6)+ARRAY(K,J,I)
,7)+ARRAY(K,J,I)



.0) GO TO 80

TITLE,TITL1,TITLA
PATH(I)

ORC,(ORGN(K),K=1,NORGN)



.0.0) PERX(K)=ARRAY(K,J,I)/SUMX(K,I)*100.
NUCLID(J),(ARRAY(K,J,I),K=1,NORGN)
PATH(I),(PERX(K),K=1,NORGN)
```

```
0         1         2
12345678901234567890123

      DIMENSION ARRAY(2
     +          RFAC(20

      COMMON/COMNU/NONC

      COMMON/COMUS/SUMX
     > FACO(20,4)

      DATA RADON/'RN-22
      DATA PATH/'INGEST
     +         ,'GROUNI
     +         ,'

      DATA SUM/'TOTAL
C***    SUM OVER ALL NU
C***    PATHWAY 5 IS II
      DO 10 I=1,7
      DO 10 K=1,NORGN
   10 SUMX(K,I)=0.0
      DO 30 I=1,4
      DO 20 K=1,NORGN
      DO 20 J=1,NONCLD
      SUMX(K,I)=SUMX(K
      IF (I.LE.2) SUMX
      IF (I.GE.3) SUMX
      SUMX(K,7)=SUMX(K
   20 CONTINUE
   30 CONTINUE
C***    TABLE 1
      IF (DTABLE(1).EQ
      DO 70 I=1,4
      WRITE(27,10000)
      WRITE(27,10200)

      WRITE(27,10300)
      WRITE(27,10400)
      DO 60 J=1,NONCLD
      DO 40 K=1,NORGN
      PERX(K)=0.0
   40 IF (SUMX(K,I).NE
      WRITE(27,10500)
      WRITE(27,10600)
      DO 50 K=1,NORGN
      II=5
      IF (I.GT.2) II=6
      PERX(K)=0.0
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      IF (SUMX(K,II).NE.0.0) PERX(K)=ARRAY(K,J,I)/SUMX(K,II)*100.
      PERY(K)=0.0
   50 IF (SUMX(K,7).NE.0.0) PERY(K)=ARRAY(K,J,I)/SUMX(K,7)*100.
      WRITE(27,10600) PATH(II),(PERX(K),K=1,NORGN)
      WRITE(27,10700) (PERY(K),K=1,NORGN)
      WRITE(27,10100)
   60 CONTINUE
      WRITE(27,11000) (SUMX(K,I),K=1,NORGN)
        IF(I.NE.2) GO TO 70
        DO 75 J=1,NONCLD
        IF(NUCLID(J).NE.RADON) GO TO 75
        WRITE(27,20100) NOTE
        IF(RFAC(1).EQ.0.0) GO TO 75
        WRITE(27,10300)ORC, (CREP(JJ),JJ=1,NCREP)
        WRITE(27,20400)NUN,(RFAC(JJ),JJ=1,NCREP)
75      CONTINUE
70      CONTINUE
C***    TABLE 2
   80 IF (DTABLE(2).EQ.0) GO TO 120
      DO 110 I=1,2
      WRITE(27,10000) TITLE,TITL1,TITLA
      II=I+4
      WRITE(27,10200) PATH(II)
      WRITE(27,10300) ORC,(ORGN(K),K=1,NORGN)
      WRITE(27,10400)
      DO 100 J=1,NONCLD
      DO 90 K=1,NORGN
      L=1
      IF (I.EQ.2) L=3
      TVAL(K)=ARRAY(K,J,L)+ARRAY(K,J,L+1)
      PERY(K)=0.0
      IF (SUMX(K,II).NE.0.0) PERY(K)=TVAL(K)/SUMX(K,II)*100.
      PERX(K)=0.0
   90 IF (SUMX(K,7).NE.0.0) PERX(K)=TVAL(K)/SUMX(K,7)*100.
      WRITE(27,10500) NUCLID(J),(TVAL(K),K=1,NORGN)
      WRITE(27,10600) PATH(II),(PERY(K),K=1,NORGN)
      WRITE(27,10700) (PERX(K),K=1,NORGN)
  100 CONTINUE
      WRITE(27,11000) (SUMX(K,II),K=1,NORGN)
      WRITE(27,10100)
        IF(I.NE.1) GO TO 110
        DO 115 J=1,NONCLD
        IF(NUCLID(J).NE.RADON) GO TO 115
         WRITE(27,20100) NOTE
        IF(RFAC(1).EQ.0.0) GO TO 115
      WRITE(27,10300)ORC,(CREP(JJ),JJ=1,NCREP)
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      WRITE(27,20400)NUN,(RFAC(JJ),JJ=1,NCREP)
115     CONTINUE
110     CONTINUE
C***    TABLE 3
  120 IF (DTABLE(3).EQ.0) GO TO 170
      WRITE(27,10000) TITLE,TITL1,TITLA
      WRITE(27,10900)
      WRITE(27,10300) ORC,(ORGN(K),K=1,NORGN)
      WRITE(27,10400)
      DO 160 J=1,NONCLD
      DO 130 K=1,NORGN
  130 TVAL(K)=0.0
      DO 150 K=1,NORGN
      DO 140 I=1,4
      TVAL(K)=ARRAY(K,J,I)+TVAL(K)
  140 CONTINUE
      PERX(K)=0.0
      IF (SUMX(K,7).NE.0.0) PERX(K)=TVAL(K)/SUMX(K,7)*100.
  150 CONTINUE
      WRITE(27,10500) NUCLID(J),(TVAL(K),K=1,NORGN)
      WRITE(27,10700) (PERX(K),K=1,NORGN)
      WRITE(27,10100)
  160 CONTINUE
      WRITE(27,11000) (SUMX(K,7),K=1,NORGN)
        DO 165 J=1,NONCLD
        IF(NUCLID(J).NE.RADON) GO TO 165
        WRITE(27,20100) NOTE
        IF(RFAC(1).EQ.0.0) GO TO 165
        WRITE(27,10300)ORC, (CREP(K),K=1,NCREP)
        WRITE(27,20400)NUN, (RFAC(JJ),JJ=1,NCREP)
165     CONTINUE
C***    TABLE 4
  170 IF (DTABLE(4).EQ.0) GO TO 260
      DO 250 K=1,NORGN
      WRITE(27,10000) TITLE,TITL1,TITLA
      WRITE(27,11100) ORC,ORGN(K)
      WRITE(27,11200) (NUCLID(J),J=1,NONCLD),SUM
      WRITE(27,11300)
      DO 180 I=1,3
      DO 180 J=1,NONCLD
  180 SUMY(J,I)=0.0
      DO 200 I=1,4
      DO 190 J=1,NONCLD
      IF (I.LE.2) SUMY(J,1)=SUMY(J,1)+ARRAY(K,J,I)
      IF (I.GE.3) SUMY(J,2)=SUMY(J,2)+ARRAY(K,J,I)
      SUMY(J,3)=SUMY(J,3)+ARRAY(K,J,I)
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
  190 CONTINUE
  200 CONTINUE
      DO 220 I=1,4
      WRITE(27,11400) PATH(I),(ARRAY(K,J,I),J=1,NONCLD),
     > SUMX(K,I)
      DO 210 J=1,NONCLD
      II=1
      IF (I.GT.2) II=2
      PERX(J)=0.0
      IF (SUMY(J,II).NE.0.0) PERX(J)=ARRAY(K,J,I)/SUMY(J,II)*100.
      PERY(J)=0.0
      IF (SUMY(J,3).NE.0.0) PERY(J)=ARRAY(K,J,I)/SUMY(J,3)*100.
  210 CONTINUE
      WPP=0.0
      IF (SUMX(K,4+II).NE.0.0) WPP=SUMX(K,I)/SUMX(K,4+II)*100.
      WP=0.0
      IF (SUMX(K,7).NE.0.0) WP=SUMX(K,I)/SUMX(K,7)*100.
      WRITE(27,11500) PATH(4+II),(PERX(J),J=1,NONCLD),WPP
      WRITE(27,11600) (PERY(J),J=1,NONCLD),WP
      WRITE(27,10100)
  220 CONTINUE
      DO 240 I=1,2
      WRITE(27,11400) PATH(I+4),(SUMY(J,I),J=1,NONCLD),SUMX(K,4+I)
      DO 230 J=1,NONCLD
      PERX(J)=0.0
  230 IF (SUMY(J,3).NE.0.0) PERX(J)=SUMY(J,I)/SUMY(J,3)*100.
      WP=0.0
      IF (SUMX(K,7).NE.0.0) WP=SUMX(K,4+I)/SUMX(K,7)*100.
      WRITE(27,11600) (PERX(J),J=1,NONCLD),WP
      WRITE(27,10100)
  240 CONTINUE
      WRITE(27,11700) (SUMY(J,3),J=1,NONCLD),SUMX(K,7)
C****  THIS SECTION OF CODE WAS FIXED TO CONFORM WITH FORTRAN 77
C****  STANDARDS.  IE TO STOP IT FROM JUMPING INTO THE DO LOOP 6/88
C****   J. MCGUE

       DO 245 J = 1,NONCLD

         IF ( NUCLID(J) .EQ. RADON ) THEN
           JJ=NCREP
           IF ( ORGN(K) .EQ. SUM) THEN
              WRITE(27,20100) NOTE
              IF ( RFAC(1) .EQ. 0.0) GO TO 250
              WRITE(27,20400)NUN, RFAC(JJ)
           ELSE
              DO 255 JJ=1,NCREP
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

                IF ( ORGN(K) .EQ. CREP(JJ) ) THEN
                   WRITE(27,20100) NOTE
                   IF(RFAC(1).EQ.0.0) GO TO 250
                   WRITE(27,20400)NUN, RFAC(JJ)
                ENDIF
 255          CONTINUE
            ENDIF
          ENDIF

 245     CONTINUE

 250  CONTINUE
C***    TABLE 5
  260 IF (DTABLE(5).EQ.0) GO TO 350
      DO 340 J=1,NONCLD
      WRITE(27,10000) TITLE,TITL1,TITLA
      WRITE(27,11800) NUCLID(J)
      DO 270 I=1,3
      DO 270 K=1,NORGN
  270 SUMY(K,I)=0.0
      DO 280 I=1,4
      DO 280 K=1,NORGN
      IF (I.LE.2) SUMY(K,1)=SUMY(K,1)+ARRAY(K,J,I)
      IF (I.GE.3) SUMY(K,2)=SUMY(K,2)+ARRAY(K,J,I)
      SUMY(K,3)=SUMY(K,3)+ARRAY(K,J,I)
  280 CONTINUE
      WRITE(27,11900) ORC,(ORGN(K),K=1,NORGN)
      WRITE(27,11300)
      DO 300 I=1,4
      WRITE(27,11400) PATH(I),(ARRAY(K,J,I),K=1,NORGN)
      II=1
      IF (I.GE.3) II=2
      DO 290 K=1,NORGN
      PERX(K)=0.0
      IF (SUMY(K,II).NE.0.0) PERX(K)=ARRAY(K,J,I)/SUMY(K,II)*100.
      PERY(K)=0.0
      IF (SUMY(K,3).NE.0.0) PERY(K)=ARRAY(K,J,I)/SUMY(K,3)*100.
  290 CONTINUE
      WRITE(27,11500) PATH(II+4), (PERX(K),K=1,NORGN)
      WRITE(27,11600) (PERY(K),K=1,NORGN)
      WRITE(27,10100)
  300 CONTINUE
      DO 320 I=1,2
      WRITE(27,11400) PATH(I+4),(SUMY(K,I),K=1,NORGN)
      DO 310 K=1,NORGN
      PERX(K)=0.0
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      IF (SUMY(K,3).NE.0.0) PERX(K)=SUMY(K,I)/SUMY(K,3)*100.
  310 CONTINUE
      WRITE(27,11600) (PERX(K),K=1,NORGN)
      WRITE(27,10100)
  320 CONTINUE
      WRITE(27,11700) (SUMY(K,3),K=1,NORGN)
      DO 330 K=1,NORGN
      PERX(K)=0.0
  330 IF (SUMX(K,7).NE.0.0) PERX(K)=SUMY(K,3)/SUMX(K,7)*100.
      WRITE(27,10700) (PERX(K),K=1,NORGN)
        L=1
        WRITE(27,20100) NOTE
        IF(RFAC(1).EQ.0.0) GO TO 340
        WRITE(27,10300)ORC, (CREP(K),K=1,NCREP)
        WRITE(27,20400)NUN, (RFAC(K),K=1,NCREP)
335     CONTINUE
  340 CONTINUE
C***    TABLE 6
  350 IF (DTABLE(6).EQ.0) GO TO 500
        DO 360 I=1,7
        TVAL(I)=0.0
        DO 360 J=1,NONCLD
        SUMX(J,I)=0.0
360     CONTINUE
  390 DO 400 I=1,4
      DO 400 J=1,NONCLD
      SUMX(J,I)=ARRAY(NORGN,J,I)
        IF(I.GE.3) GO TO 401
      SUMX(J,5)=SUMX(J,5)+ARRAY(NORGN,J,I)
        TVAL(5)=TVAL(5)+ARRAY(NORGN,J,I)
        GO TO 402
401      SUMX(J,6)=SUMX(J,6)+ARRAY(NORGN,J,I)
        TVAL(6)=TVAL(6)+ARRAY(NORGN,J,I)
402      SUMX(J,7)=SUMX(J,7)+ARRAY(NORGN,J,I)
      TVAL(I)=TVAL(I)+ARRAY(NORGN,J,I)
        TVAL(7)=TVAL(7)+ARRAY(NORGN,J,I)
  400 CONTINUE
  410 CONTINUE
      WRITE(27,10000) TITLE,TITL1,TITLA
        WRITE(27,12100) ORC
      WRITE(27,11200) (NUCLID(J),J=1,NONCLD),SUM
      DO 430 I=1,4
      WRITE(27,11400) PATH(I),(SUMX(J,I),J=1,NONCLD),TVAL(I)
      II=5
      IF (I.GE.3) II=6
      DO 420 J=1,NONCLD
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      PERX(J)=0.0
      IF (SUMX(J,II).NE.0.0) PERX(J)=SUMX(J,I)/SUMX(J,II)*100.
      PERY(J)=0.0
      IF (SUMX(J,7).NE.0.0) PERY(J)=SUMX(J,I)/SUMX(J,7)*100.
  420 CONTINUE
      WP=0.0
      IF (TVAL(II).NE.0.0) WP=TVAL(I)/TVAL(II)*100.
      WPP=0.0
      IF (TVAL(7).NE.0.0) WPP=TVAL(I)/TVAL(7)*100.
      WRITE(27,11500) PATH(II), (PERX(J),J=1,NONCLD),WP
      WRITE(27,11600) (PERY(J),J=1,NONCLD),WPP
      WRITE(27,10100)
  430 CONTINUE
      DO 450 I=5,6
      WRITE(27,11400) PATH(I),(SUMX(J,I),J=1,NONCLD),TVAL(I)
      DO 440 J=1,NONCLD
      PERX(J)=0.0
      IF (SUMX(J,7).NE.0.0) PERX(J)=SUMX(J,I)/SUMX(J,7)*100.
  440 CONTINUE
      WRITE(27,11600) (PERX(J),J=1,NONCLD)
      WRITE(27,10100)
  450 CONTINUE
      WRITE(27,11700) (SUMX(J,7),J=1,NONCLD),TVAL(7)
      DO 460 J=1,NONCLD
      PERX(J)=0.0
      IF (TVAL(7).NE.0.0) PERX(J)=SUMX(J,7)/TVAL(7)*100.
  460 CONTINUE
      WRITE(27,12000) (PERX(J),J=1,NONCLD)
        DO 465 J=1,NONCLD
        IF(NUCLID(J).NE.RADON) GO TO 465
        WRITE(27,20100) NOTE
        IF(RFAC(1).EQ.0.0) GO TO 470
        WRITE(27,20400)NUN, RFAC
470     CONTINUE
465     CONTINUE
C***    TABLE 7
500     IF(DTABLE(7).EQ.0) RETURN
        DO 510 I=1,7
        DO 510 J=1,NORGN
        SUMX(J,I)=0.0
510     CONTINUE
        DO 550 I=1,4
        DO 550 J=1,NORGN
        DO 550 K=1,NONCLD
        SUMX(J,I)=SUMX(J,I)+ARRAY(J,K,I)
        IF(I.GE.3) GO TO 501
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        SUMX(J,5)=SUMX(J,5)+ARRAY(J,K,I)
        GO TO 502
501     SUMX(J,6)=SUMX(J,6)+ARRAY(J,K,I)
502     SUMX(J,7)=SUMX(J,7)+ARRAY(J,K,I)
550     CONTINUE
        WRITE(27,10000) TITLE,TITL1,TITLA
        WRITE(27,12200)
        WRITE(27,10300) ORC,(ORGN(K),K=1,NORGN)
        WRITE(27,11300)
        DO 575 I=1,4
        WRITE(27,11400) PATH(I),(SUMX(J,I),J=1,NORGN)
        II=5
        IF(I.GE.3) II=6
        DO 560 J=1,NORGN
        PERX(J)=0.0
        IF(SUMX(J,II).NE.0.0) PERX(J)=SUMX(J,I)/SUMX(J,II)*100.
        PERY(J)=0.0
        IF(SUMX(J,7).NE.0.0) PERY(J)=SUMX(J,I)/SUMX(J,7)*100.
560     CONTINUE
        WRITE(27,11500) PATH(II),(PERX(J),J=1,NORGN)
        WRITE(27,11600) (PERY(J),J=1,NORGN)
        WRITE(27,10100)
575     CONTINUE
        DO 590 I=5,6
        WRITE(27,11400) PATH(I),(SUMX(J,I),J=1,NORGN)
        DO 580 J=1,NORGN
        PERX(J)=0.0
        IF(SUMX(J,7).NE.0.0) PERX(J)=SUMX(J,I)/SUMX(J,7)*100.
580     CONTINUE
        WRITE(27,11600) (PERX(J),J=1,NORGN)
        WRITE(27,10100)
590     CONTINUE
        WRITE(27,11700) (SUMX(J,7),J=1,NORGN)
        DO 600 J=1,NONCLD
        IF(NUCLID(J).NE.RADON) GO TO 600
        WRITE(27,20100) NOTE
        IF(RFAC(1).EQ.0.0) GO TO 600
        DO 610 L=1,NCREP
610     WLSUM(L)=0.0
        DO 612 JJ=1,1
        DO 612 L=1,NCREP
        WLSUM(L)=WLSUM(L)+RFAC(L)
612     CONTINUE
        WRITE(27,10300)ORC, (CREP(L),L=1,NCREP)
        WRITE(27,20400)NUN, (WLSUM(L),L=1,NCREP)
600     CONTINUE
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      RETURN
10000 FORMAT(1H1,20X,A80/21X,A40/21X,A8)
10100 FORMAT(1X)
10200 FORMAT('0*** FOR PATHWAY:',A16//)
10300 FORMAT('0',A8,':',22X,10(2X,A8)/(33X,10(2X,A8)))
10400 FORMAT('0NUCLIDES'/)
10500 FORMAT(1X,A8,23X,10(1PE10.2)/(33X,10(1PE10.2) ) )
10600 FORMAT(' % OF TOTAL',1X,A16,4X,10(1PE10.2)/(33X,10(1PE10.2) ) )
10700 FORMAT(' % OF TOTAL',21X,10(1PE10.2)/ (33X,10(1PE10.2) ) )
10800 FORMAT('0TOTAL     ',21X,10(1PE10.2)/(33X,10(1PE10.2) ) )
10900 FORMAT('0*** FOR ALL PATHWAYS:'//)
11000 FORMAT(' TOTAL',26X,10(1PE10.2)/(33X,10(1PE10.2)))
11100 FORMAT('0***FOR',A8,':',A8//)
11200 FORMAT(' NUCLIDES',23X,10(2X,A8)/(33X,10(2X,A8)))
11300 FORMAT(' PATHWAYS'/)
11400 FORMAT(1X,A16,15X,10(1PE10.2)/(33X,10(1PE10.2) ))
11500 FORMAT(' % OF ',1X,A16,9X,10(1PE10.2)/ (33X,10(1PE10.2)))
11600 FORMAT(' % OF ALL PATHWAYS',14X,10(1PE10.2)/ (33X,10(1PE10.2)))
11700 FORMAT(' TOTAL OVER ALL PATHWAYS',8X,10(1PE10.2)/(33X,
     +       10(1PE10.2)))
11800 FORMAT('0FOR NUCLIDE:',A8)
11900 FORMAT(1X,A8,23X,10(2X,A8)/(33X,10(2X,A8)))
12000 FORMAT(11H % OF TOTAL,21X,10(1PE10.2)/(33X,10(1PE10.2) ))
12100   FORMAT('0***SUMMED OVER ALL',A8)
12200   FORMAT('0***SUMMED OVER ALL NUCLIDES')
20100   FORMAT('0',/////10X,A80)
20400   FORMAT(1X,A32,10(1PE10.2) )
      END


C=======================================================================
C                                                                      =
C                        SUBROUTINE LOCTAB                             =
C                                                                      =
C=======================================================================

      SUBROUTINE LOCTAB(IT,RN,PT,OG,FACD,ARRAY,TITL1,TITLA,
     <  ORGN,NORGN,NDIM,NO, NUCLID,DATE_AND_TIME)

C     CORRECTED FOR ORGAN/CANCER "SUM" OPTION.  CBN 11/05/82

        CHARACTER*8 RN,OG,SUM,NUCLID,ORGN,WLOPT(2),PUL,
     +  TBEQ,OGI

      CHARACTER*80 TITLE
      CHARACTER*8  TITLA
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
      CHARACTER*40 TITL1
      CHARACTER*16 TPATH
      CHARACTER*36 DATE_AND_TIME

        COMMON/COMRN/WLRN(20,20),RRISK,RREF(2),RYRLL,NOREP,NRREP,NCREP
        COMMON/COMCA/DUM(6428),AGEX
        INTEGER PT

        DIMENSION ARRAY(NDIM,40,4), NUCLID(40),
     +  ORGN(1),FACD(1),TPATH(7),IDIR(16),NL(40),SAVG(20)

        COMMON/COMUS/OUTPUT(40,40),HOLDC(40),HOLDR(40)

       DATA TPATH/'INGESTION       ','INHALATION      ',
     +            'AIR IMMERSION   ','GROUND SURFACE  ',
     +            'INTERNAL        ','EXTERNAL        ',
     +            'ALL             '/

       DATA SUM/'SUM     '/,WLOPT/'WORKLEVL','WLSUM   '/,
     +      PUL/'PULMNARY'/,TBEQ/'BODY EQ.'/

       DATA IDIR/1,16,15,14,13,12,11,10,9,8,7,6,5,4,3,2/

      COMMON/COMNU/NONCLD,PSIZE(40),GIABS (4,40),INDPOP

      COMMON/COMEX/EXPP(20,20,40,4),POP(20,20),POPFAC,TOTFAC, NOL,NOU,
     > NRL,NRU,IDIST(20),ILOC,JLOC

10000   FORMAT('0',21X,A40/21X,A8)
        DO 10 K=1,40
        HOLDC(K)=0.0
        HOLDR(K)=0.0
        DO 10 L=1,40
10      OUTPUT(L,K)=0.0
      INB=1
      INE = NONCLD
      DO 11 J=1,NONCLD
   11 NL(J)=J
        TSUM=0.0
        DO 12 J=1,2
        IF(RN.EQ.WLOPT(J)) GO TO 1000
12      CONTINUE
14      CONTINUE
        IF(RN.EQ.SUM.OR.RN.EQ.WLOPT(2)) GO TO 80
        INE=0
        DO 50 J=1,NONCLD
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

        IF(RN.NE.NUCLID(J)) GO TO 50
        INE=INE+1
        NL(INE)=J
   50   CONTINUE
        IF(INE.NE.0) GO TO 80
        WRITE(27,10500) RN
10500   FORMAT(' RADIONUCLIDE ',A8,
     A  ' IS NOT IN LIST. TABLE WILL BE SKIPPED.')
        RETURN
80      CONTINUE
        IF(OG.EQ.SUM) GO TO 175
        DO 150 J=1,NORGN
        IF(OG.EQ.ORGN(J)) GO TO 170
150     CONTINUE
        WRITE(27,10600) OG
10600   FORMAT(' ORGAN ',A8,' IS NOT IN LIST.',
     A  ' TABLE WILL BE SKIPPED.')
        RETURN
170     IO=J
        GO TO 180
175     IO=NORGN
  180   OGI=ORGN(IO)
        IPT=PT
        IPB=IPT
        IPE=IPT
        IF(IPT.LE.4) GO TO 184
177     CONTINUE
        IPT=IPT-4
        GO TO (181,182,183),IPT
181     IPB=1
        IPE=2
        GO TO 184
182     IPB=3
        IPE=4
        GO TO 184
183     IPB=1
        IPE=4
184     CONTINUE
        DO 300 IPT=IPB,IPE
        DO 300 INL=INB,INE
        IN=NL(INL)
        DO 300 II=NOL,NOU
        DO 300 JJ=NRL,NRU
        OUTPUT(JJ,II)=OUTPUT(JJ,II)+ARRAY(IO,IN,IPT)*FACD(IPT)*
     >  EXPP(JJ,II,IN,IPT)
300     CONTINUE
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

305      IF(IT.EQ.3) GO TO 500
         DO 400 JJ=NRL,NRU
         SOUT=0.
         SPOP=0.
         SAVG(JJ)=0.
         DO 390 II=NOL,NOU
         IF(POP(II,JJ).NE.0.) GO TO 360
         OUTPUT(JJ,II)=0.
         GO TO 390
  360    IF(IT.NE.1) GO TO 370
C      IT=1 (INDIVIDUAL)
         SOUT=SOUT+OUTPUT(JJ,II)/POP(II,JJ)
         SPOP=SPOP+1.
         GO TO 380
C      IT=2 (MEAN INDIVIDUAL)
  370    SOUT=SOUT+OUTPUT(JJ,II)
         SPOP=SPOP+POP(II,JJ)
  380    OUTPUT(JJ,II)=OUTPUT(JJ,II)/POP(II,JJ)
  390    CONTINUE
         IF(SPOP.NE.0.) SAVG(JJ)=SOUT/SPOP
  400    CONTINUE
         WRITE(27,100)DATE_AND_TIME
  100    FORMAT('1',T10,'DATE',2X,A)
         WRITE(27,10000) TITL1,TITLA
         WRITE(27,10100) RN,OGI,TPATH(PT)
         DO 600 JJ=NRL,NRU
         WRITE(27,10200) IDIST(JJ),(OUTPUT(JJ,IDIR(II)),II=1,8)
600      CONTINUE
         WRITE(27,10125)
         DO 605 JJ=NRL,NRU
         WRITE(27,10205) IDIST(JJ),(OUTPUT(JJ,IDIR(II)),II=9,16),SAVG(JJ)
605      CONTINUE
         RETURN
500      WRITE(27,100)DATE_AND_TIME
         WRITE(27,10000) TITL1,TITLA
         DO 680 II=1,16
         DO 680 JJ=NRL,NRU
         HOLDC(II)=OUTPUT(JJ,II)+HOLDC(II)
         HOLDR(JJ)=OUTPUT(JJ,II)+HOLDR(JJ)
680      TSUM=OUTPUT(JJ,II)+TSUM
         WRITE(27,10100) RN,OGI,TPATH(PT)
         DO 700 JJ=NRL,NRU
700      WRITE(27,10200) IDIST(JJ),(OUTPUT(JJ,IDIR(II)),II=1,8)
         WRITE(27,10250) (HOLDC(IDIR(II)),II=1,8)
         WRITE(27,10175)
         DO 710 JJ=NRL,NRU
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

710      WRITE(27,10205) IDIST(JJ),(OUTPUT(JJ,IDIR(II)),II=9,16),
     +                   HOLDR(JJ)
         WRITE(27,10250) (HOLDC(IDIR(II)),II=9,16),TSUM
         RETURN
1000     IF(NDIM.NE.20) RETURN
         IF(OG.EQ.SUM) GO TO 1001
         IF(OG.EQ.PUL) GO TO 1001
         IF(OG.EQ.TBEQ) GO TO 1001
         IF(J.EQ.1) GO TO 305
         GO TO 14
1001     CONTINUE
         IF(NO.NE.1) GO TO 1200
1100     DO 1150 II=NOL,NOU
         DO 1150 JJ=NRL,NRU
         OUTPUT(JJ,II)=WLRN(JJ,II)
1150     CONTINUE
         OG=SUM
         PT=7
         GO TO 305
1200     IF(NO.NE.3) GO TO 1300
         FAC=1.
         IF(IT.EQ.3) FAC=1./AGEX
         DO 1250 II=NOL,NOU
         DO 1250 JJ=NRL,NRU
         OUTPUT(JJ,II)=RRISK*WLRN(JJ,II)*FAC
1250     CONTINUE
         IF(J.EQ.1) GO TO 305
         GO TO 14
1300     IF(OG.NE.PUL) GO TO 1400
         FAC=1.
         IF(IT.EQ.3) FAC=.001
         DO 1350 II=NOL,NOU
         DO 1350 JJ=NRL,NRU
         OUTPUT(JJ,II)=RREF(1)*WLRN(JJ,II)*FAC
1350     CONTINUE
         IF(J.EQ.1) GO TO 500
         GO TO 14
1400     IF(OG.NE.TBEQ) RETURN
         FAC=1.
         IF(IT.EQ.3) FAC=.001
         DO 1450 II=NOL,NOU
         DO 1450 JJ=NRL,NRU
         OUTPUT(JJ,II)=RREF(2)*WLRN(JJ,II)*FAC
1450     CONTINUE
         IF(J.EQ.1) GO TO 305
         GO TO 14
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

10100   FORMAT(' FOR RADIONUCLIDE : ',A8/
     >  ' AND ORGAN/CANCER : ',A8/
     >  ' AND PATHWAY : ',A16/
     >  ' DIRECTIONS:',3X,'N',6X,'NNE',5X,'NE',6X,
     >  'ENE',6X,'E',6X,'ESE',5X,'SE',6X,'SSE'/
     >  '  DISTANCE'/'  (METERS):')
10125   FORMAT(////15X,'S',6X,'SSW',5X,'SW',6X,'WSW',6X,'W',
     >  6X,'WNW',5X,'NW',6X,'NNW',5X,'AVG'/
     >  1H ,' DISTANCE'/'  (METERS):')
10175   FORMAT(////,15X,'S',6X,'SSW',5X,'SW',6X,'WSW',6X,'W'
     >  ,6X,'WNW',5X,'NW',6X,'NNW',5X,'SUM'/'  DISTANCE'/
     >  '  (METERS):')
10200   FORMAT(I7,3X,8(1PE7.1,1X) )
10205   FORMAT(I7,3X,9(1PE7.1,1X) )
10250   FORMAT('0 SUM',5X,9(1PE7.1,1X) )
      END


C=======================================================================
C                SUBROUTINE WRITE SYNOPSIS REPORT                      =
C                                                                      =
C   NEW REPORT ADDED 8/88 BY J. MCGUE.  THIS REPORT IS A SUMMARY OF    =
C   THE INPUT USED AND THE RESULTS OF THE RUN.                         =
C                                                                      =
C=======================================================================

C=======================================================================
C  THE FOLLOWING ROUTINES USE THE SUBROUTINE OUTPUT_STRING TO WRITE    =
C  ALL THE INFORMATION ON THE SYNOPSIS REPORT.  THIS WAS DONE TO AID   =
C  IN CHANGES MADE TO THE REPORT.  ALL OUTPUT IS READ INTO THE CHARAC  =
C  STRING LINES BY INTERNAL WRITES, LINES IS THEN PASSED TO            =
C  OUTPUT_STRING.  OUTPUT_STRING KEEPS TRACK OF THE                    =
C  LINE NUMBERS FOR PAGING ETC.  SEE THE SUBROUTINE FOR DOCUMENTATION. =
C  EVERYTHING ELSE IS SELF EXPLANATORY.                                =
C  ALL WRITES TO FILE 13 ARE FOR THE SAS DATA BASE FILE 13 HOLDS ALL   =
C  EXTRANEOUS INFORMATION.  THE SO CALLED 'USELESS' STUFF.             =
C  ALL WRITES TO FILE 14 ARE FOR THE SAS DATA BASE FILE 14, HOLDS ALL  =
C  INFORMATION THAT WILL BE USED IN REPORTS.  THE 'GOODSTUF'.          =
C=======================================================================


      SUBROUTINE WRITE_SYNOPSIS_REPORT( INDPOP, ORGN, NORGN,
     +                                  FOOD_ARRAY_INFO,
     +                                  NUMBER_FILES, ANG)
C     ==================================
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
```

```
C     VARIABLES PASSED
C     ================

      INTEGER       INDPOP, NORGN
      INTEGER*2     NUMBER_FILES
      INTEGER*4     ANG
      CHARACTER*8   ORGN(20)
      CHARACTER*36  DATE_AND_TIME
      COMMON / HEADERINFO / DATE_AND_TIME

      CHARACTER*80 FOOD_ARRAY_INFO



C     GLOBAL VARIABLES
C     ================

      CHARACTER*80 FILES_USED(10), NAME_OF_PERSON, PHONE_NUMBER

      COMMON / GENERIC_INFO / FILES_USED, NAME_OF_PERSON, PHONE_NUMBER


      INTEGER*2   NUMBER_STACKS, SOURCE_TYPE, PLUME_RISE_TYPE
      REAL        HEIGHT(6), AREA(6), AREA_DIAMETER(6),
     +            STACK_DIAMETER(6),BOUYANCY(6), MOMENTUM(6), ENTERED(7)

      COMMON / EMMIS_INFO / HEIGHT, AREA, AREA_DIAMETER,
     +                      STACK_DIAMETER, BOUYANCY, MOMENTUM,
     +                      ENTERED,
     +                      NUMBER_STACKS, SOURCE_TYPE, PLUME_RISE_TYPE

      INTEGER*2   NUMBER_NUCS, DECAY_CHAIN_FLAG (36), DAUGHTERS
      LOGICAL     RN_RUN
      REAL        AMAD(36), RELEASE_RATE(36,6), ALAMSUR(36)
      COMMON / NUC_INFO / AMAD, RELEASE_RATE, NUMBER_NUCS,
     +                    DAUGHTERS, DECAY_CHAIN_FLAG, ALAMSUR, RN_RUN


      COMMON/COMEX/EXPP(20,20,40,4),POP(20,20),POPFAC,TOTFAC, NOL,NOU,
     + NRL,NRU,IDIST(20),ILOC,JLOC


      INTEGER*2  PAGE_NO, LINE_COUNT, NUM_TITLE_LINES
      COMMON / COUNTERS / PAGE_NO, LINE_COUNT, NUM_TITLE_LINES
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      CHARACTER*90 SAVED_TITLE_LINES (20)
      CHARACTER*26 ID_CODE
      COMMON / TITLES / SAVED_TITLE_LINES, ID_CODE


C     LOCAL VARIABLES
C     ---------------

      INTEGER*2    I, REPORT_NUMBER
      CHARACTER*1  STACK_NUMBERS (6)
      CHARACTER*8  STARFILE, POPFILE
      CHARACTER*90 LINES (20)

C      INITILIZATION
C      -------------

      DATA STACK_NUMBERS / '1', '2', '3', '4', '5', '6' /
      DATA STARFILE /'        '/, POPFILE /'        '/



C**   BEGIN

1000  FORMAT ( '1' )
1010  FORMAT ( 1X, A )

C******* GET THE NAMES OF THE FILES USED ...ID CODE, WIND FILE, *********
C*******       POPULATION FILE, AND FOOD FILE NAMES            *********

      ID_CODE = '                              '
      CALL GET_FILE_NAMES (ID_CODE, STARFILE, POPFILE,
     +                     FILES_USED, NUMBER_FILES )



      WRITE(13,1005) RN_RUN
      WRITE(14,1005) RN_RUN
 1005 FORMAT (I1,10X,'RN_FLAG')

C******************** WRITE FILE NAMES TO SAS FILES ********************

      WRITE  (14,1006) STARFILE
      WRITE  (13,1006) STARFILE
      WRITE  (14,1007) POPFILE
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      WRITE  (13,1007) POPFILE

 1006 FORMAT (A,10X,'Star')
 1007 FORMAT (A,10X,'Pop')

C******** WRITE TITLE PAGE & PERSON TO GIVE TO AND PHONE NUMBER *******

      WRITE  (12,1000)
      WRITE  (12,1010) NAME_OF_PERSON
      WRITE  (12,1010) PHONE_NUMBER


C*********************** WRITE HEADING ********************************

      WRITE  (12,1000)
      WRITE  (12,1020)
1020  FORMAT (17X,'SYNOPSIS REPORT - CAP-88 (1.00)'/)

      WRITE  (12,1030) ID_CODE, DATE_AND_TIME
      WRITE  (13,1040) ID_CODE

 1030 FORMAT (1X,'ID Code: ',A,2X,'Date/Time: ',A/)
 1040 FORMAT (A,10X,'ID_Code')

C********************** WRITE FACILITY INFO ***************************

      CALL W_FACILITY_INFO


C*************************************************************************
C***  BEFORE THIS DID NOT NEED WORRY ABOUT PAGING ETC.  FROM ON YOU DO
C***  THEREFORE, FOR EASE IN CHANGING AND MODIFYING THE ORDER OF THE
C***  REPORT, A CALL TO THE OUTPUT_STRING ROUTINE WILL ALWAYS BE MADE
C***  THIS ROUTINE WILL CHECK FOR PAGING AND REPRINTING OF TITLES
C*************************************************************************

      PAGE_NO    = 1
      LINE_COUNT = 15

C*************************************************************************
C***  CHECK TO SEE IF POPULATION OR INDIVIDUAL RUN AND WRITE RESULTS
C***  ACCORDINGLY  ( INDPOP = 1 ==> POPULATION, 0 ==> INDIV RUN )
C*************************************************************************

      IF ( INDPOP .EQ. 0 ) THEN
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

C******************  WRITE INDIVIDUAL RESULTS  ************************

         CALL INDIV_RESULTS ( RN_RUN, NUMBER_NUCS, NORGN, ORGN, ILOC,
     +                        NUMBER_STACKS, ANG)
       ELSE
         REPORT_NUMBER = 1

C******************  WRITE POPULATION RESULTS  ************************

         CALL POP_RESULTS ( RN_RUN, REPORT_NUMBER, ORGN, NORGN )

C******************  WRITE INDIVIDUAL RESULTS  ************************

         CALL INDIV_RESULTS ( RN_RUN, NUMBER_NUCS, NORGN, ORGN, ILOC,
     +                        NUMBER_STACKS, ANG)
       ENDIF

C******************  WRITE RADIONUCLIDE INFORMATION  ******************

       CALL WRITE_NUC_INFO( NUMBER_STACKS, STACK_NUMBERS)


C**********************  WRITE SITE INFORMATION  **********************

       CALL W_SITE_INFO

C******************  WRITE EMMISSION INFORMATION  *********************

       CALL W_EMMISSION_INFO (STACK_NUMBERS)

C*********************  WRITE FOOD SUPPLY INFO  ************************

       CALL W_FOOD_INFO (FOOD_ARRAY_INFO)

C***************************************************************************
C***  DETERMINE IF POPULATION OR INDIVIDUAL AND WRITE EITHER THE
C***  DISTANCES USED IF INDIV, OR THE POPOULATION ARRAY IF POP RUN
C***************************************************************************

       IF ( INDPOP .EQ. 0 ) THEN

C*****************  WRITE INDIV DISTANCES ON SAME PAGE  ***************
C*** MAKE THE NEXT OUTPUT ALL A .TRUE., .TRUE. IE. NEVER SPLIT IT UP

         WRITE  (LINES,1050) ( IDIST(I), I = NRL,NRU )
1050     FORMAT (/ 17X,
```

```
0         1         2         3         4         5         6         7
1234567890123456789012345678901234567890123456789012345678901234567890123456789012

     +         'DISTANCES USED FOR MAXIMUM INDIVIDUAL ASSESSMENT',
     +         /17X,'-----------------------------------------------',
     +         / 1X, 10(I6,1X) )
          IF ( NRU .LE. 10 ) THEN
            CALL OUTPUT_STRING ( LINES, 4 , .TRUE., .FALSE. )
          ELSE
            CALL OUTPUT_STRING ( LINES, 5 , .TRUE., .TRUE. )
          ENDIF

       ELSE
C****************** IF POP RUN OUTPUT POP ARRAY NOW  ******************

          CALL WRITE_POP_ARRAY( POP, IDIST, NOL, NOU, NRL, NRU )

       ENDIF


C**********  WRITE THE NAMES OF FILES REFERENCED FOR THE RUN  *********

          WRITE  (LINES,1060)
 1060     FORMAT (// 23X,'REFERENCE FILE NAMES FOR ASSESSMENT',
     +           /  23X,'---------------------------------' /)

          CALL OUTPUT_STRING ( LINES, 5, .TRUE., .FALSE. )

       DO 10 I = 1, NUMBER_FILES
          WRITE  (LINES,1010) FILES_USED(I)
          CALL OUTPUT_STRING ( LINES, 1, .FALSE., .FALSE. )

  10   CONTINUE


C*************************************************************
C***     IF POP RUN OUTPUT RISK FREQUENCY TABLE
C***     IN FACTORS OF 10 FOR DOE
C*************************************************************

       IF ( INDPOP .EQ. 1 ) THEN
          REPORT_NUMBER = 2
C***      FORCE A NEW PAGE TO BE DONE FOR THIS REPORT
          LINE_COUNT = 66
          CALL NEW_RISK_FREQ_REPORT ( REPORT_NUMBER )

       ENDIF

       RETURN
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      END

C*********************************************************************
C                                                                     *
C                OUTPUT ROUTINES FOR THE SYNOPSIS REPORT              *
C                 CALLED BY WRITE SYNOPSIS REPORT                     *
C                                                                     *
C*********************************************************************

C=====================================================================
C                                                                     -
C                        SUBROUTINE W SITE INFO                       -
C                                                                     -
C=====================================================================

      SUBROUTINE W_SITE_INFO
C     ======================

C     VARIABLES PASSED
C     ================


C     GLOBAL VARIABLES
C     ================

      INTEGER*4   TEMPERATURE, RAINFALL_RATE, LID_HEIGHT
      REAL        LATITUDE, LONGITUDE

      COMMON / SITE_INFO / TEMPERATURE, RAINFALL_RATE, LID_HEIGHT,
     +                     LATITUDE, LONGITUDE

C     LOCAL VARIABLES
C     ===============
      CHARACTER*90 LINES (20)


C**   BEGIN

      WRITE  (LINES,1000)
1000  FORMAT (/ 32X, 'SITE INFORMATION' / 32X, '----------------'/ )

      CALL OUTPUT_STRING ( LINES, 4, .TRUE., .FALSE. )


      WRITE  (LINES,1010) TEMPERATURE
      WRITE  (13,1020) TEMPERATURE
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

1010  FORMAT ( 7X, 'Temperature:', 4X, I3, 2X, 'C' )
1020  FORMAT (I3,10X,'TEMP')

      CALL OUTPUT_STRING ( LINES, 1, .FALSE., .FALSE. )

      WRITE  (LINES,1030) RAINFALL_RATE
      WRITE  (13,1040) RAINFALL_RATE
1030  FORMAT ( 10X, 'Rainfall:', 4X, I3, 2X, 'cm/yr' )
1040  FORMAT (I3,10X,'RAINFALL')

      CALL OUTPUT_STRING ( LINES, 1, .FALSE., .FALSE. )

      WRITE  (LINES,1050) LID_HEIGHT
      WRITE  (13,1060) LID_HEIGHT
1050  FORMAT ( 5X, 'Mixing Height:', 3X, I4, 1X, 'meters' )
1060  FORMAT (I4,10X,'LID_HITE')

      CALL OUTPUT_STRING ( LINES, 1, .FALSE., .FALSE. )

      WRITE  (13,1070) LATITUDE
 1070 FORMAT (F8.4,10X,'LATITUDE')
      WRITE  (13,1080) LONGITUDE
 1080 FORMAT (F8.4,10X,'LONGITUDE')
      RETURN
      END

C=============================================================================
C                                                                            =
C                        SUBROUTINE W FACILITY INFO                          =
C                                                                            =
C=============================================================================

      SUBROUTINE W_FACILITY_INFO
C     ==========================


C     GLOBAL VARIABLES
C     ================

      CHARACTER*80 COMMENTS(2)
      CHARACTER*72 FACILITY, ADDRESS
      CHARACTER*38 SOURCE_CATEGORY
      CHARACTER*25 CITY
      CHARACTER*10 ZIPCODE
      CHARACTER*4  YEAR
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      CHARACTER*2  STATE
      COMMON / FACIL_INFO / COMMENTS, FACILITY, ADDRESS,
     +                      SOURCE_CATEGORY, CITY, ZIPCODE, YEAR, STATE

C     LOCAL VARIABLES
C     ===============


      INTEGER*2 I, NUM_COMMENTS

      CHARACTER*80 BLANK_LINE


      DATA NUM_COMMENTS / 0/
      DATA BLANK_LINE/ '
     +                                '/


C***   BEGIN

      WRITE  (12,1000) FACILITY
      WRITE  (14,1001) FACILITY
      WRITE  (13,1001) FACILITY
 1000 FORMAT (1X,'Facility: ',A)
 1001 FORMAT (A,5X,'Facility')

      WRITE  (12,1010) ADDRESS
 1010 FORMAT (2X,'Address: ',A)
      WRITE  (13,1020) ADDRESS
 1020 FORMAT (A,5X,'Address')

      WRITE  (12,1030) CITY
 1030 FORMAT (5X,'City: ', A)
      WRITE  (13,1040) CITY
 1040 FORMAT (A,10X,'City')

      IF ( ZIPCODE .EQ. 'ZIP CODE' ) THEN
        WRITE (12, 1045) STATE
1045    FORMAT (4X,'State: ', A, 5X, 'Zipcode: ')
      ELSE
        WRITE  (12,1050) STATE, ZIPCODE
1050    FORMAT (4X,'State: ', A, 5X, 'Zipcode: ',A )
      ENDIF
      WRITE  (13,1060) STATE
      WRITE  (14,1060) STATE
      WRITE  (13,1070) ZIPCODE
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

1060  FORMAT (A,10X,'State')
1070  FORMAT (A,10X,'Zipcode')

      WRITE  (12,1080) SOURCE_CATEGORY, YEAR
1080  FORMAT (/1X, 'Source Category:  ',A, 2X, 'Source Term: ',A )
      WRITE  (13,1090) YEAR
      WRITE  (14,1090) YEAR
1090  FORMAT (A,10X,'YEAR')

      WRITE  (12,2000)
2000  FORMAT (/1X, 'Comments: ' )


      DO 10 I = 1,2
         IF ( COMMENTS (I) .EQ. BLANK_LINE ) THEN
           GO TO 20
         ELSE
           NUM_COMMENTS = NUM_COMMENTS + 1
         ENDIF
 10   CONTINUE

 20   WRITE  (13,2005) NUM_COMMENTS
 2005 FORMAT (I2,10X,'NUM_CMTS')

      WRITE  (12,2010) COMMENTS(1)
      WRITE  (12,2010) COMMENTS(2)

C***    OUTPUT TO SAS FILES ONLY THE EXACT NUMBER OF COMMENT LINES

      DO 30 I = 1, NUM_COMMENTS
         WRITE  (13,2020) COMMENTS(I)
 30   CONTINUE

2010  FORMAT (1X,A )
2020  FORMAT (A,10X,'COMMENTS')

      RETURN
      END

C=======================================================================
C                                                                      =
C                      SUBROUTINE WRITE NUC INFO                       =
C                                                                      =
C=======================================================================
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
1234567890123456789012345678901234567890123456789012345678901234567890123456789012

      SUBROUTINE WRITE_NUC_INFO( NUMBER_STACKS, STACK_NUMBERS)

C     VARIABLES PASSED
C     ================

      INTEGER*2   NUMBER_STACKS
      CHARACTER*1 STACK_NUMBERS (6)

C     GLOBAL VARIABLES
C     ================

      CHARACTER*8  NAME_NUC(36)
      CHARACTER*1  ISOL(36)
      COMMON / NUCCHARINFO / NAME_NUC, ISOL

      INTEGER*2    NUMBER_NUCS, DECAY_CHAIN_FLAG (36), DAUGHTERS
      LOGICAL      RN_RUN
      REAL         AMAD(36), RELEASE_RATE(36,6), ALAMSUR(36)
      COMMON / NUC_INFO / AMAD, RELEASE_RATE, NUMBER_NUCS,
     +                    DAUGHTERS, DECAY_CHAIN_FLAG, ALAMSUR, RN_RUN

      CHARACTER*80 COMMENTS(2)
      CHARACTER*72 FACILITY, ADDRESS
      CHARACTER*38 SOURCE_CATEGORY
      CHARACTER*25 CITY
      CHARACTER*10 ZIPCODE
      CHARACTER*4  YEAR
      CHARACTER*2  STATE
      COMMON / FACIL_INFO / COMMENTS, FACILITY, ADDRESS,
     +                      SOURCE_CATEGORY, CITY, ZIPCODE, YEAR, STATE


C     LOCAL VARIABLES
C     ===============

      INTEGER*2  I, J
      CHARACTER*8 DASHES(6)
      CHARACTER*90 LINES (20)
      CHARACTER*5  UNITS (6)
      CHARACTER*7  STKWORD (6)
      CHARACTER*61 FORMAT1, FORMAT2, FORMAT3
      REAL TOTREL

      DATA UNITS / 'Ci/yr','Ci/yr','Ci/yr','Ci/yr','Ci/yr','Ci/yr'/
      DATA STKWORD / 'Stack #', 'Stack #', 'Stack #', 'Stack #',
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
     +               'Stack #', 'Stack #'/
      DATA DASHES /6*'--------'/
      DATA FORMAT1 /
     + '( '' Nuclide   Class  Amad  '',1X,  (A5, 4X), 3X, ''TOTAL'') '/
      DATA FORMAT2 /
     + '( '' -------   -----  ----''  ,2X,  ( A8,1X ),4X, ''-----'')'/
      DATA FORMAT3 /
     + '(1X, A8, 4X, A1, 4X, F4.2, 2X,  (1PE8.2, 1X), 1X, 1PE10.2  )'/

      WRITE  (LINES,1010) YEAR
 1010 FORMAT ( /28X, 'SOURCE TERM (' ,A4, ')'
     +         /28X, '-----------------')
      CALL OUTPUT_STRING ( LINES, 3, .TRUE., .FALSE. )
      WRITE (LINES, 1015) ( STKWORD (I), STACK_NUMBERS (I),
     +                      I = 1,NUMBER_STACKS )
 1015 FORMAT ( 24X, 6( A7, A1, 1X ) )

      FORMAT1 (34:34) = STACK_NUMBERS ( NUMBER_STACKS )
      WRITE  (LINES(2), FORMAT1) ( UNITS (I), I = 1, NUMBER_STACKS )
C 1020 FORMAT ( ' Nuclide   Class  Amad  ',1X, 6(A, 4X), 1X, A6)

      FORMAT2 (34:34) = STACK_NUMBERS ( NUMBER_STACKS )
      WRITE  (LINES(3), FORMAT2) ( DASHES (I) , I = 1,NUMBER_STACKS )
C1030 FORMAt ( ' -------   -----  ----'  , 2X,  ( A8,1X ) A5 )

      CALL OUTPUT_STRING ( LINES, 3, .TRUE., .TRUE. )

      IF ( .NOT. RN_RUN ) THEN
        WRITE (14,1086) DAUGHTERS
      ENDIF
      DO 10 I = 1, NUMBER_NUCS
         TOTREL = 0.0
         DO 5 J = 1,NUMBER_STACKS
            TOTREL = RELEASE_RATE (I,J) + TOTREL
 5       CONTINUE

         FORMAT3 (32:32) = STACK_NUMBERS ( NUMBER_STACKS )
         WRITE  (LINES, FORMAT3) NAME_NUC (I), ISOL (I), AMAD (I),
     +           ( RELEASE_RATE (I,J), J = 1, NUMBER_STACKS ), TOTREL
         CALL OUTPUT_STRING ( LINES, 1, .FALSE., .TRUE. )


C***  OUTPUT THE NUC INFO FOR THE SAS CODE

         WRITE (14,1060) NAME_NUC (I)
         WRITE (14,1070) ISOL (I)
```

```
0         1         2         3         4         5         6         7
1234567890123456789012345678901234567890123456789012345678901234567890123456789012

          WRITE (14,1080) AMAD (I)
          WRITE (14,1085) ALAMSUR(I)
          IF ( .NOT. RN_RUN ) THEN
            WRITE (14,1087) DECAY_CHAIN_FLAG (I)
          ENDIF
          WRITE (14,1090) ( RELEASE_RATE (I,J),
     +                      J = 1, NUMBER_STACKS )
C 1050     FORMAT (1X, A8, 4X, A1, 4X, F4.2, 2X, 6(1PE8.2, 1X), 1PE10.2)
 1060     FORMAT (A8,10X,'NAME_N')
 1070     FORMAT (A1,10X,'ISOL')
 1080     FORMAT (F4.2,10X,'AMAD')
 1085     FORMAT (E10.3,10X,'LAMSUR')
 1086     FORMAT (I1,10X,'DAUGHTERS FLAG')
 1087     FORMAT (I1,10X,'DECAY CHAIN FLAG')
 1090     FORMAT (1(1PE8.2,5X,'RRATE'))

10     CONTINUE

       RETURN
       END

C=======================================================================
C                                                                      -
C                        SUBROUTINE W EMISSION INFO                    -
C                                                                      -
C=======================================================================

       SUBROUTINE W_EMMISSION_INFO (STACK_NUMBERS)
C      ===========================

C      VARIABLES PASSED
C      ================

       CHARACTER*1  STACK_NUMBERS (6)

C      GLOBAL VARIABLES
C      ================

       INTEGER*2    NUMBER_STACKS, SOURCE_TYPE, PLUME_RISE_TYPE
       REAL         HEIGHT(6), AREA(6), AREA_DIAMETER(6),
      +             STACK_DIAMETER(6),BOUYANCY(6), MOMENTUM(6), ENTERED(7)

       COMMON / EMMIS_INFO / HEIGHT, AREA, AREA_DIAMETER,
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
1234567890123456789012345678901234567890123456789012345678901234567890123456789012

     +                     STACK_DIAMETER, BOUYANCY, MOMENTUM,
     +                     ENTERED,
     +                     NUMBER_STACKS, SOURCE_TYPE, PLUME_RISE_TYPE


C     LOCAL VARIABLES
C     ===============

      INTEGER*2    I
      CHARACTER*8  DASHES8 (6)
      CHARACTER*5  PASQUIL_CATS (7)

      CHARACTER*90 LINES (20)

C      INITILIZATION
C      =============

      DATA DASHES8 / 6*'--------'/
      DATA PASQUIL_CATS / '--A--', '--B--', '--C--', '--D--', '--E--',
     +                    '--F--', '--G--'/


C*** BEGIN

      WRITE  (LINES,1000)
1000  FORMAT (/ 29X, 'EMISSION INFORMATION' / 29X,
     +               '---------------------'/ )
      CALL OUTPUT_STRING ( LINES, 4, .TRUE., .FALSE. )


      WRITE  (LINES(1),1010) (STACK_NUMBERS(I), I = 1, NUMBER_STACKS )
1010  FORMAT ( 10X, ' Stack Number:',4X, 6( A , 8X ) )

      WRITE  ( LINES(2),1020) (DASHES8 (I), I = 1, NUMBER_STACKS )
1020  FORMAT ( 25X, 6( A, 1X ) )

      CALL OUTPUT_STRING ( LINES, 2, .TRUE., .TRUE. )


C***   DETERMINE IF STACK OR AREA SOURCE AND WRITE ACCORDINGLY
C***   SOURCE TYPE = 0 ==> STACK, 1 ==> AREA
      WRITE(13,1030)SOURCE_TYPE
1030  FORMAT (I1,10X,'SRC_TYPE')
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
      IF ( SOURCE_TYPE .EQ. 0 ) THEN


         WRITE  (LINES,1040) ( HEIGHT(I), I = 1,NUMBER_STACKS )
         WRITE  (13,1050) ( HEIGHT(I), I = 1,NUMBER_STACKS )

1040     FORMAT ( 2X, 'Stack Height (meters) :', 2X, 6( F6.2, 3X ) )
1050     FORMAT (1(F6.2,10X,'HEIGHT'))
         CALL OUTPUT_STRING ( LINES, 1, .FALSE., .TRUE. )

         WRITE  (LINES,1060) (STACK_DIAMETER (I), I = 1,NUMBER_STACKS)
         WRITE  (13,1070) (STACK_DIAMETER (I), I = 1,NUMBER_STACKS)
1060     FORMAT ( 1X, 'Stack Diameter (meters):', 2X, 6( F6.2, 3X ) )
1070     FORMAT (1(F6.2,10X,'DIAM'))

         CALL OUTPUT_STRING ( LINES, 1, .FALSE., .TRUE. )

C***      DETERMINE PLUME RISE TYPE AND WRITE ACCORDINGLY FOR STACK SOURCE
C***      0 ==> BOUYANT, 1 ==> MOMENTUM , 2 ==> ENTERED

         WRITE  (LINES,1080)
1080     FORMAT ( 2X, 'Plume Rise' )
         CALL OUTPUT_STRING ( LINES, 1, .FALSE., .TRUE. )

         WRITE (13,1090)PLUME_RISE_TYPE
1090     FORMAT (I1,10X,'PR_TYPE')


         IF ( PLUME_RISE_TYPE .EQ. 0 ) THEN

            WRITE  (LINES,2000) ( BOUYANCY (I), I = 1, NUMBER_STACKS )
            WRITE  (13,2010) ( BOUYANCY (I), I = 1, NUMBER_STACKS )
2000        FORMAT ( 6X, 'Bouyant (cal/sec) :', 6( 1PE8.2, 1X ) )
2010        FORMAT (1(1PE8.2,5X,'PL_RISE'))
            CALL OUTPUT_STRING ( LINES, 1, .FALSE., .TRUE. )

         ELSE IF ( PLUME_RISE_TYPE .EQ. 1 ) THEN

            WRITE  (LINES,2020) ( MOMENTUM (I), I = 1, NUMBER_STACKS )
            WRITE  (13,2010) ( MOMENTUM (I), I = 1, NUMBER_STACKS )
2020        FORMAT ( 7X, 'Momentum (m/sec) :', 6( 1PE8.2, 1X ) )
            CALL OUTPUT_STRING ( LINES, 1, .FALSE., .TRUE. )

         ELSE
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

              WRITE  (LINES,2030) ( PASQUIL_CATS(I), I = 1,7 ),
     +                            ( ENTERED (I), I = 1,7  )
              WRITE  (13,2040) (    ENTERED (I), I = 1,7 )
2030          FORMAT ( 26x,7(A5,3X) / 5x, 'Entered (meters) :',
     +                      7(1X,F7.2) )
2040          FORMAT (1(1PE8.2,5X,'PL_RISE'))

              CALL OUTPUT_STRING ( LINES, 2, .TRUE., .FALSE. )


           ENDIF

      ELSE
C***   AREA SOURCE


          WRITE  (LINES,2050) ( HEIGHT(I), I = 1,NUMBER_STACKS )
2050      FORMAT ( 2X, 'Area Height (meters) :', 2X, 6( F6.2, 3X ) )
          CALL OUTPUT_STRING ( LINES, 1, .FALSE., .TRUE. )

          WRITE (13,2060) (HEIGHT(I), I = 1,NUMBER_STACKS)
2060     FORMAT (1(F6.2,5X,'HEIGHT'))

          WRITE (13,2070) (AREA_DIAMETER (I), I=1,NUMBER_STACKS )
2070      FORMAT (1(1PE8.2,5X,'DIAM'))

          WRITE  (LINES,2080) ( AREA (I), I = 1,NUMBER_STACKS )
          WRITE  (13,2090) ( AREA (I), I = 1,NUMBER_STACKS )
2080      FORMAT (9X, 'Area ( sq. m) :', 6( 1X, 1PE8.2 ) )
2090      FORMAT (1(1PE8.2,5X,'AREA'))
          CALL OUTPUT_STRING ( LINES, 1, .FALSE., .TRUE. )

          WRITE  (LINES,3000) ( AREA_DIAMETER (I), I = 1,NUMBER_STACKS )
3000      FORMAT (1X, 'Area Diameter (meters):', 6( 1X, 1PE8.2 ) )
          CALL OUTPUT_STRING ( LINES, 1, .FALSE., .TRUE. )


      ENDIF


      RETURN
      END

C=================================================================
C                                                                -
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

C                          SUBROUTINE W FOOD INFO                              =
C                                                                              =
C==============================================================================

      SUBROUTINE W_FOOD_INFO (FOOD_ARRAY_INFO)
C     ========================

C     VARIABLES PASSED
C     ================

      CHARACTER*80 FOOD_ARRAY_INFO


C     GLOBAL VARIABLES
C     ================

      REAL        VEG_LOCAL, VEG_REGIONAL, VEG_IMPORTED, MEAT_LOCAL,
     +            MEAT_REGIONAL, MEAT_IMPORTED, MILK_LOCAL,
     +            MILK_REGIONAL, MILK_IMPORTED

      COMMON / FOOD_INFO / VEG_LOCAL, VEG_REGIONAL, VEG_IMPORTED,
     +                     MEAT_LOCAL, MEAT_REGIONAL, MEAT_IMPORTED,
     +                     MILK_LOCAL, MILK_REGIONAL, MILK_IMPORTED


C     LOCAL VARIABLES
C     ===============

      CHARACTER*90 LINES (20)


C***    BEGIN

      WRITE  (LINES,1000)
1000  FORMAT (/29X, 'FOOD SUPPLY FRACTIONS'/
     +        29X, '----------------------',/)
      CALL OUTPUT_STRING ( LINES, 4, .TRUE., .FALSE. )


      WRITE  (LINES,1010)
1010  FORMAT ( 24X, 'Local', 5X, 'Regional', 5X, 'Imported' /
     +        24X, '-----', 5X, '--------', 5X, '--------' )
      CALL OUTPUT_STRING ( LINES, 2, .TRUE., .TRUE. )
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
```

```
      WRITE  (LINES,1020) VEG_LOCAL, VEG_REGIONAL, VEG_IMPORTED
      WRITE  (13,1030) VEG_LOCAL
      WRITE  (13,1040) VEG_REGIONAL
      WRITE  (13,1050) VEG_IMPORTED
1020  FORMAT ( 10X, 'Vegetable: ', 2X, F5.3, 6X, F5.3, 8X, F5.3 )
1030  FORMAT ( F5.3,10X,'VEG_LOC')
1040  FORMAT ( F5.3,10X,'VEG_REG')
1050  FORMAT ( F5.3,10X,'VEG_IMP')
      CALL OUTPUT_STRING ( LINES, 1, .FALSE., .TRUE. )

      WRITE  (LINES,1060) MEAT_LOCAL, MEAT_REGIONAL, MEAT_IMPORTED
      WRITE  (13,1070) MEAT_LOCAL
      WRITE  (13,1080) MEAT_REGIONAL
      WRITE  (13,1090) MEAT_IMPORTED
1060  FORMAT ( 15X, 'Meat: ', 2X, F5.3, 6X, F5.3, 8X, F5.3 )
1070  FORMAT ( F5.3,10X,'BEEF_LOC')
1080  FORMAT ( F5.3,10X,'BEEF_REG')
1090  FORMAT ( F5.3,10X,'BEEF_IMP')
      CALL OUTPUT_STRING ( LINES, 1, .FALSE., .TRUE. )

      WRITE  (LINES,2000) MILK_LOCAL, MILK_REGIONAL, MILK_IMPORTED
      WRITE  (13,2010) MILK_LOCAL
      WRITE  (13,2020) MILK_REGIONAL
      WRITE  (13,2030) MILK_IMPORTED
2000  FORMAT ( 15X, 'Milk: ', 2X, F5.3, 6X, F5.3, 8X, F5.3 )
2010  FORMAT (F5.3,10X,'MILK_LOC')
2020  FORMAT (F5.3,10X,'MILK_REG')
2030  FORMAT (F5.3,10X,'MILK_IMP')
      CALL OUTPUT_STRING ( LINES, 1, .FALSE., .TRUE. )

      WRITE  (LINES,2040) FOOD_ARRAY_INFO
2040  FORMAT ( / 1X, A )
      CALL OUTPUT_STRING ( LINES, 2, .FALSE., .FALSE. )


      RETURN
      END
```

```
C=============================================================================
C                                                                            =
C                        SUBROUTINE INDIV RESULTS                            =
C                                                                            =
C=============================================================================
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
      SUBROUTINE INDIV_RESULTS( RN_RUN, NUMBER_NUCS, NORGN, ORGN, ILOC,
     +                          NUMBER_STACKS, ANG)
C     ========================

C     VARIABLES PASSED
C     ================
      LOGICAL   RN_RUN
      INTEGER*2 NUMBER_NUCS,NUMBER_STACKS
      INTEGER*4 ANG
      CHARACTER*8 ORGN(20)
      INTEGER NORGN

C     GLOBAL VARIABLES
C     ================
      REAL WLI, MAX_PCI_LITERS, FATAL_CANCER_RISK, ORGAN_DOSES(20),
     +     PATHWAY_DOSES(4), NUC_DOSES(36)
      INTEGER LOC_DIST

      COMMON / IND_RESULTS / WLI, LOC_DIST, MAX_PCI_LITERS,
     +                       FATAL_CANCER_RISK ,ORGAN_DOSES,
     +                       PATHWAY_DOSES,NUC_DOSES


C     LOCAL VARIABLES
C     ===============

      CHARACTER*15  DIRECTIONS(16)

      CHARACTER*90  LINES(20)

C     INITIALIZATION
C     ==============

      DATA DIRECTIONS /'NORTH          ','NORTH NORTHWEST',
     +                 'NORTHWEST      ','WEST NORTHWEST ',
     +                 'WEST           ','WEST SOUTHWEST ',
     +                 'SOUTHWEST      ','SOUTH SOUTHWEST',
     +                 'SOUTH          ','SOUTH SOUTHEAST',
     +                 'SOUTHEAST      ','EAST  SOUTHEAST',
     +                 'EAST           ','EAST  NORTHEAST',
     +                 'NORTHEAST      ','NORTH NORTHEAST'/


C**** CHECK FOR RADON RUN, IF MORE THAN 1 NUCLIDE AND RADON FLAG IS SET
C**** OUTPUT FOR NON RADON RUN ELSE OUTPUT FOR RADON RUN
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      WRITE(14,1006) LOC_DIST
 1006 FORMAT (I6,10X,'MAX_DIST')

      WRITE(14,1007) ANG
 1007 FORMAT(A4,10X,'MAX_DIR')

      IF ( .NOT. RN_RUN  ) THEN
        WRITE(14,1008) (NORGN-1)
 1008   FORMAT(I2,10x,'NUM_ORG')
      ENDIF

      WRITE (13,1023) NUMBER_STACKS
      WRITE (14,1023) NUMBER_STACKS
 1023 FORMAT (I1,10X,'NUM_STCK')

      IF (.NOT. RN_RUN ) THEN
        WRITE (14,1033) NUMBER_NUCS
        WRITE (13,1033) NUMBER_NUCS
 1033 FORMAT (I2,10X,'NUM_NUCS')
      ENDIF

      IF ( RN_RUN) THEN

         WRITE  (LINES, 1000 )
 1000    FORMAT ( / 10X, 'RN-222 EXPOSURE AND RISK FOR THE INDIVIDUAL',
     +                   ' AT MAXIMUM RISK',
     +           / 10X, '-----------------------------------------',
     +                  '----------------')
         CALL OUTPUT_STRING ( LINES, 3, .TRUE., .FALSE. )

         WRITE  (LINES,1010) LOC_DIST, DIRECTIONS(ILOC)
 1010    FORMAT ( / 1X, 'Location to the individual:',I6,
     +                  ' METERS',1X, A15 )
         CALL OUTPUT_STRING ( LINES, 2, .FALSE., .FALSE. )

         WRITE  (LINES,1020) WLI
         WRITE  (14,1021) WLI
 1020    FORMAT ( / 6X, 'Exposure in Working Levels:', 1PE10.2 )
 1021    FORMAT (1PE10.2,10X,'IND_WL')
         CALL OUTPUT_STRING ( LINES, 2, .FALSE., .FALSE. )

         WRITE  (LINES,1030) MAX_PCI_LITERS
         WRITE  (14,1031) MAX_PCI_LITERS
 1030    FORMAT ( 6X, 'pCi/liter at that location:', 1PE10.2 )
 1031    FORMAT (1PE10.2,10X,'MAX_CONC')
         CALL OUTPUT_STRING ( LINES, 1, .FALSE., .FALSE. )
```

```
0         1         2         3         4         5         6         7
1234567890123456789012345678901234567890123456789012345678901234567890123456789012

        WRITE  (LINES, 1040) FATAL_CANCER_RISK
        WRITE  (14,1041) FATAL_CANCER_RISK
1040    FORMAT ( 6X, 'Lifetime Fatal Cancer Risk:', 1PE10.2 )
1041    FORMAT (1PE10.2,10X,'LIFERISK')
        CALL OUTPUT_STRING ( LINES, 1, .FALSE., .FALSE. )

     ELSE

        WRITE  (LINES, 1050)
1050    FORMAT ( / 25X, 'INDIVIDUAL AT MAXIMUM RISK ASSESSEMENT',
    +           / 31X,        '(RN-222 RISKS EXCLUDED)',
    +           / 31X,        '-----------------------')
        CALL OUTPUT_STRING ( LINES, 4, .TRUE., .FALSE. )

        WRITE  (LINES,1010) LOC_DIST, DIRECTIONS(ILOC)
        CALL OUTPUT_STRING ( LINES, 2, .FALSE., .FALSE. )

        WRITE  (LINES,1060) ( ORGN(J), J = 1, NORGN - 1)
1060    FORMAT ( / 16X, 7( A8,2X ) / 2X, 'Organ dose')
        CALL OUTPUT_STRING ( LINES, 3, .TRUE., .TRUE. )

        WRITE  (LINES,1070) ( ORGAN_DOSES (J), J = 1, NORGN - 1)
        WRITE  (14,1071) ( ORGAN_DOSES (J), J = 1, NORGN - 1)
        WRITE  (14,1072) ( PATHWAY_DOSES (J), J = 1, 4)
        WRITE  (14,1073) ( NUC_DOSES (J), J = 1, NUMBER_NUCS)
1070    FORMAT (3X, '(mrem/yr) : ', 8(1PE8.1,2X) )
1071    FORMAT (1(1PE10.2,5X,'O_DOSE'))
1072    FORMAT (1(1PE10.2,5X,'P_DOSE'))
1073    FORMAT (1(1PE10.2,5X,'N_DOSE'))
        CALL OUTPUT_STRING ( LINES, 1, .TRUE., .FALSE. )

        WRITE  (LINES,1080) ORGAN_DOSES (NORGN)
        WRITE  (14,1081) ORGAN_DOSES (NORGN)
1080    FORMAT ( / 2X, 'ICRP Effective Dose Equivalent (mrem/yr):',
    +          1PE10.2)
1081    FORMAT (1PE10.2, 10X,'I_EFECTIV')
        CALL OUTPUT_STRING ( LINES, 2, .FALSE., .FALSE. )

        WRITE  (LINES, 1090) FATAL_CANCER_RISK
        WRITE  (14,1041) FATAL_CANCER_RISK
1090    FORMAT ( 2X,   'Lifetime Fatal Cancer Risk                :',
    +            1PE10.2 )
        CALL OUTPUT_STRING ( LINES, 1, .FALSE., .FALSE. )

     ENDIF
```

```
0         1         2         3         4         5         6         7
1234567890123456789012345678901234567890123456789012345678901234567890123456789012

      RETURN
      END

C=======================================================================
C                                                                      -
C                        SUBROUTINE POP RESULTS                        -
C                                                                      -
C=======================================================================

      SUBROUTINE POP_RESULTS( RN_RUN, REPORT_NUMBER, ORGN, NORGN )
C     ============================

C     VARIABLES PASSED
C     ================
      LOGICAL   RN_RUN
      INTEGER*2 REPORT_NUMBER
      CHARACTER*8  ORGN (20)
      INTEGER   NORGN
C     GLOBAL VARIABLES
C     ================

      REAL    SRISK(400), RSKLIN(400), EFFECT_PERSON_REM,
     +        PERSON_WORKING_LEVEL, POP_ORGAN_DOSES(20)

      INTEGER POPLIN(400)

      INTEGER IO(400), NLOC, NOP

      COMMON / POPU_RESULTS / POPLIN, RSKLIN, SRISK, IO, NLOC, NOP,
     +                        EFFECT_PERSON_REM, PERSON_WORKING_LEVEL,
     +                        POP_ORGAN_DOSES

C     LOCAL VARIABLES
C     ===============

      CHARACTER*90  LINES(20)

C**** CHECK FOR RADON RUN, IF MORE THAN 1 NUCLIDE AND RADON FLAG IS SET
C**** OUTPUT FOR NON RADON RUN ELSE OUTPUT FOR RADON RUN

      IF ( RN_RUN ) THEN
         WRITE  (LINES, 1000 )
 1000    FORMAT ( / 25X, 'RN-222 POPULATION ASSESSMENT',
     +            / 25X, '----------------------------' /)
         CALL OUTPUT_STRING ( LINES, 4, .TRUE., .FALSE. )
```

```
0         1         2         3         4         5         6         7
1234567890123456789012345678901234567890123456789012345678901234567890123456789012

         WRITE  (LINES, 1020) PERSON_WORKING_LEVEL
         WRITE  (14,1021) PERSON_WORKING_LEVEL
 1020    FORMAT (1X, 'Collective Exposure (Person Working Levels):',
     +                1PE10.2 )
 1021    FORMAT (1PE10.2,10X,'POP_WL')
         CALL OUTPUT_STRING ( LINES, 1, .FALSE., .FALSE. )

      ELSE

         WRITE  (LINES, 1010)
 1010    FORMAT ( / 29X, 'POPULATION ASSESSMENT',
     +            / 26X, '(RN-222 DOSE/RISK EXCLUDED)',
     +            / 26X, '--------------------------' /)
         CALL OUTPUT_STRING ( LINES, 5, .TRUE., .FALSE. )

         WRITE  (LINES, 1030) EFFECT_PERSON_REM
         WRITE  (14,1031) EFFECT_PERSON_REM
 1030    FORMAT (1X, 'ICRP Collective Effective Dose Equivalent',
     +               ' (Person-Rem/Year):', 1PE10.2)
 1031    FORMAT (1PE10.2,10X,'P_EFECTIV')
         CALL OUTPUT_STRING ( LINES, 1, .FALSE., .FALSE. )

         WRITE  (LINES,1060) ( ORGN(J), J = 1, NORGN - 1)
 1060    FORMAT (/ 1X,'Collective Population'/,
     +           / 16X, 7( A8,2X ) / 2X, 'Organ dose')
         CALL OUTPUT_STRING ( LINES, 5, .TRUE., .TRUE. )

         WRITE  (LINES,1070) ( POP_ORGAN_DOSES (J), J = 1, NORGN - 1)
 1070    FORMAT (2X, '(P-REM/YR) : ', 8(1PE8.1,2X) )
         CALL OUTPUT_STRING ( LINES, 1, .TRUE., .FALSE. )

      ENDIF

      CALL NEW_RISK_FREQ_REPORT ( REPORT_NUMBER )

      RETURN
      END

C=============================================================================
C                                                                            =
C                        SUBROUTINE WRITE POP ARRAY                          =
C                                                                            =
C=============================================================================

      SUBROUTINE WRITE_POP_ARRAY( POP, IDIST, NOL, NOU, NRL, NRU)
```

```
0         1         2         3         4         5         6         7
1234567890123456789012345678901234567890123456789012345678901234567890123456789012

C     ========================

C     VARIABLES PASSED
C     ================

      INTEGER   NOL, NOU, NRL, NRU, IDIST(20)
      REAL      POP(20,20)


C     LOCAL VARIABLES
C     ===============

      INTEGER*2 REPEAT_NUMBER, BEG_DIST_PTR, END_DIST_PTR
      INTEGER*2 I, J, K

      CHARACTER*5 DASHES(20)
      CHARACTER*3 DIRECTION(16)
      CHARACTER*90 LINES(20)


      DATA DIRECTION / '  N','NNW',' NW','WNW','  W','WSW',' SW',
     +                 'SSW','  S','SSE',' SE','ESE','  E','ENE',
     +                 ' NE','NNE'/

      DATA DASHES / 20*'-----' /



      WRITE  (LINES, 1010)
 1010 FORMAT ( / 12X, 'POPULATION ARRAY (1980 Census)',
     +         / 12X, '------------------------------'/)
      CALL OUTPUT_STRING ( LINES, 4, .TRUE., .FALSE. )


C***   DETERMINE NUMBER OF TIMES DIRECTIONS PRINTED

      REPEAT_NUMBER = (( NRU-NRL ) / 7) + 1
      DO 20 I = 1, REPEAT_NUMBER

        BEG_DIST_PTR = NRL + ( 7 * ( I - 1 ) )
        END_DIST_PTR = MIN0 (BEG_DIST_PTR+6, NRU )

        WRITE  (LINES, 1020 ) (IDIST(J), J = BEG_DIST_PTR,END_DIST_PTR)
 1020   FORMAT ( /, 5X, 7(I7) )

        WRITE  (LINES(3), 1030 )
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
```

```
     +                          (DASHES(J),J = BEG_DIST_PTR, END_DIST_PTR)
 1030    FORMAT (     5X, 7( 2X,A5 ) )

         CALL OUTPUT_STRING ( LINES, 3, .TRUE., .TRUE. )

          DO 10 K = NOL, NOU

            WRITE  (LINES, 1040 ) DIRECTION(K),
     +                          (POP(K,J), J = BEG_DIST_PTR, END_DIST_PTR)
 1040       FORMAT (1X, A3, 1X, 7F7.0)
            CALL OUTPUT_STRING ( LINES, 1, .FALSE., .TRUE. )

 10         CONTINUE

 20     CONTINUE

        RETURN
        END



C  ****
C    NEW REPORT ADDED 1/88 BY JOAN MCGUE
C ****
C=================================================================

C=================================================================
C                                                                -
C                  SUBROUTINE NEW RISK FREQ REPORT               -
C                                                                -
C=================================================================

        SUBROUTINE NEW_RISK_FREQ_REPORT ( REPORT_NUMBER )


        REAL     SRISK(400), RSKLIN(400), EFFECT_PERSON_REM,
       +         PERSON_WORKING_LEVEL, POP_ORGAN_DOSES(20)

        INTEGER POPLIN(400), IO(400), NLOC, NOP

        COMMON / POPU_RESULTS / POPLIN, RSKLIN, SRISK, IO, NLOC, NOP,
       +                        EFFECT_PERSON_REM, PERSON_WORKING_LEVEL,
       +                        POP_ORGAN_DOSES

        INTEGER*2 NUM_INTERVALS, REPORT_NUMBER
        INTEGER NUMBER_OF_PEOPLE, INDEX, TOTAL_NUMBER_OF_PEOPLE
```

```
0         1         2         3         4         5         6         7
1234567890123456789012345678901234567890123456789012345678901234567890123456789012

      REAL  NUMBER_OF_DEATHS, TOTAL_NUMBER_OF_DEATHS
      REAL RISK_INTERVALS(14,2)

      CHARACTER*18 RISK_FORMATS(15,2)
      CHARACTER*90 LINES (20)

      DATA RISK_INTERVALS /.1,.01,.001,.0001,.00001,.000001,
     +                     .0,.0,.0,.0,.0,.0,.0,.0,
     +                     .3,.1,.03,.01,.003,.001,.0003,.0001,
     +                     .00003,.00001,.000003,.000001,.0000003,
     +                     .0000001 /

      DATA RISK_FORMATS  /'1.0E+00 TO 1.0E-01','1.0E-01 TO 1.0E-02',
     +                    '1.0E-02 TO 1.0E-03','1.0E-03 TO 1.0E-04',
     +                    '1.0E-04 TO 1.0E-05','1.0E-05 TO 1.0E-06',
     +                    ' LESS THAN 1.0E-06','                  ',
     +                    '                  ','                  ',
     +                    '                  ','                  ',
     +                    '                  ','                  ',
     +                    '                  ','1.0E+00 TO 3.0E-01',
     +                    '3.0E-01 TO 1.0E-01','1.0E-01 TO 3.0E-02',
     +                    '3.0E-02 TO 1.0E-02','1.0E-02 TO 3.0E-03',
     +                    '3.0E-03 TO 1.0E-03','1.0E-03 TO 3.0E-04',
     +                    '3.0E-04 TO 1.0E-04','1.0E-04 TO 3.0E-05',
     +                    '3.0E-05 TO 1.0E-05','1.0E-05 TO 3.0E-06',
     +                    '3.0E-06 TO 1.0E-06','1.0E-06 TO 3.0E-07',
     +                    '3.0E-07 TO 1.0E-07',' LESS THAN 1.0E-07'/


C*** SET INITIAL VALUES
      INDEX = 1
      NUMBER_OF_PEOPLE = 0
      TOTAL_NUMBER_OF_PEOPLE = 0
      NUMBER_OF_DEATHS = 0.0
      TOTAL_NUMBER_OF_DEATHS = 0.0

C***  DETERMINE NUMBER OF INTERVALS ACCORDING TO FIRST OR SECOND REPORT
C***  BEING PRINTED .. THE FIRST REPORT IS IN FACTORS OF 10 NUM
C***  INTERVALS = 6, THE SECOND REPORT IS IN FACTORS OF 3,
C***  NUM INTERVALS = 14

      IF ( REPORT_NUMBER .EQ. 1 ) THEN
         NUM_INTERVALS = 6
      ELSE
         NUM_INTERVALS = 14
      ENDIF
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
      WRITE (LINES,90)
   90 FORMAT(/17X,'FREQUENCY DISTRIBUTION OF LIFETIME ',
     +      'FATAL CANCER RISKS')
      CALL OUTPUT_STRING ( LINES, 2, .TRUE., .FALSE. )

      WRITE (LINES,101)
  101 FORMAT(/ 34X,'NUMBER OF PEOPLE',2X,'DEATHS/YEAR',2X,'DEATHS/YEAR'
     +       / 22X,'NUMBER OF',3X,'AT THIS RISK OR',5X,'AT THIS',
     +          4X,'AT THIS RISK'
     +       /  8X,'RISK',12X,'PEOPLE',8X,'HIGHER',11X,'RISK',
     +          7X,'OR HIGHER'
     +       /  8X,'----',12X,'------',8X,'------',11X,'----',
     +          7X,'---------')
      CALL OUTPUT_STRING ( LINES, 5, .TRUE., .TRUE. )



C     THE ARRAY IO IS USED AS A POINTER TO THE UNSORTED ARRAYS.  IT IS
C     USED TO ACCESS THE UNSORTED ARRAYS VALUES IN THE PROPER ORDER.
C     REMEMBER THEY ORGINALLY PARRALLED TRISK (SRISK).

         I = NLOC
   10    CONTINUE
         IF ( ( I .GT. 0 ) .AND. ( INDEX .LE. NUM_INTERVALS ) ) THEN
           IF (SRISK(I) .GE. RISK_INTERVALS(INDEX,REPORT_NUMBER)) THEN
                 NUMBER_OF_PEOPLE = NUMBER_OF_PEOPLE + POPLIN( IO(I) )
                 NUMBER_OF_DEATHS = NUMBER_OF_DEATHS + RSKLIN( IO(I) )
                 I = I - 1
             ELSE
                 TOTAL_NUMBER_OF_PEOPLE = TOTAL_NUMBER_OF_PEOPLE +
     +           NUMBER_OF_PEOPLE
                 TOTAL_NUMBER_OF_DEATHS = TOTAL_NUMBER_OF_DEATHS +
     +           NUMBER_OF_DEATHS
              IF (REPORT_NUMBER .EQ. 1) THEN
                 WRITE(14,102) NUMBER_OF_PEOPLE
                 WRITE(14,105) NUMBER_OF_DEATHS
              ENDIF
                 WRITE (LINES,'(1X,A18,1X,I10,4X,I10,7X,1PE10.2,3X,
     +                     1PE10.2)')
     +              RISK_FORMATS(INDEX,REPORT_NUMBER),NUMBER_OF_PEOPLE,
     +              TOTAL_NUMBER_OF_PEOPLE,NUMBER_OF_DEATHS,
     +              TOTAL_NUMBER_OF_DEATHS
                 CALL OUTPUT_STRING ( LINES, 1, .FALSE., .TRUE. )

                 NUMBER_OF_PEOPLE = 0
                 NUMBER_OF_DEATHS = 0.0
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

                  INDEX = INDEX + 1
               ENDIF
            GOTO 10
            ENDIF

C**** ELSE
  20        CONTINUE

            IF ( I .GT. 0 ) THEN
               NUMBER_OF_PEOPLE = NUMBER_OF_PEOPLE + POPLIN( IO(I) )
               NUMBER_OF_DEATHS = NUMBER_OF_DEATHS + RSKLIN( IO(I) )
               I = I - 1
               GOTO 20
            ENDIF

            TOTAL_NUMBER_OF_PEOPLE = TOTAL_NUMBER_OF_PEOPLE +
     +                               NUMBER_OF_PEOPLE
            TOTAL_NUMBER_OF_DEATHS = TOTAL_NUMBER_OF_DEATHS +
     +                               NUMBER_OF_DEATHS

            WRITE (LINES,'(1X,A18,1X,I10,4X,I10,7X,1PE10.2,3X,1PE10.2)')
     +              RISK_FORMATS(INDEX,REPORT_NUMBER),NUMBER_OF_PEOPLE,
     +              TOTAL_NUMBER_OF_PEOPLE,NUMBER_OF_DEATHS,
     +              TOTAL_NUMBER_OF_DEATHS
       IF(REPORT_NUMBER .EQ.1 )THEN
            WRITE(14,102) NUMBER_OF_PEOPLE
            WRITE(14,105) NUMBER_OF_DEATHS
            WRITE(14,100) TOTAL_NUMBER_OF_DEATHS
            WRITE(14,103) TOTAL_NUMBER_OF_PEOPLE
         ENDIF
  100    FORMAT(1PE10.2,10X,'TOTDEATH')
  102    FORMAT(I8 ,10X,'PEOPLE')
  103    FORMAT(I8 ,10X,'TOTPEOPL')
  105    FORMAT(1PE10.2,10X,'DEATHS')

            CALL OUTPUT_STRING ( LINES, 1, .FALSE., .TRUE. )

C**         WRITE (LINES,104) SRISK(NOP)
C** 104        FORMAT(/ 3X,'RISK TO THE MAXIMUM INDIVIDUAL  ==> ',
C**     +           1PE10.2)
C**            CALL OUTPUT_STRING ( LINES, 2, .FALSE., .FALSE. )

C**            WRITE (LINES,105) TOTAL_NUMBER_OF_DEATHS
C** 105        FORMAT(3X,'THE TOTAL NUMBER OF DEATHS/YEAR ==> ',
C**     +           1PE10.2)
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
```

```
      RETURN

      END

C*************************************************************************
C                                                                        *
C                                                                        *
C                    MATHAMATICAL ROUTINES                               *
C                                                                        *
C                                                                        *
C                                                                        *
C*************************************************************************

C=========================================================================
C                                                                        -
C                         SUBROUTINE MULT                                -
C                                                                        -
C=========================================================================

      SUBROUTINE MULT(IM,CONFAC,ARRAYI,NOC,NAMNOC,TITLE,TITL1,TABLE,
     > TITL2,NOTE,NUN,RFACI,CREP,NCREP,NDIM,NUCLID,noncld)
      INTEGER TABLE

      CHARACTER*8 NAMNOC,CREP,PUL, NUCLID

      DIMENSION NUCLID(40)

      COMMON/COMRN/WLRN(20,20),RRISK,RREF(2),RYRLL,NOREP,NRREP,NFREP

      CHARACTER*80 TITLE, NOTE
      CHARACTER*8 TITL2
      CHARACTER*32 NUN
      CHARACTER*40 TITL1

      COMMON/COMEX/EXPP(20,20,40,4),POP(20,20),POPFAC,TOTFAC, NOL,NOU,
     > NRL,NRU,IDIST(20),ILOC,JLOC
      DIMENSION ARRAYI(NDIM,40,4),ARRAYO(20,40,4),CONFAC(4),
     >          NAMNOC(1),TABLE(7),CREP(20),RFACI(20),
     >          RFACO(20)
      GO TO (10,30,50),IM
   10 DO 20 I=1,4
      DO 20 J=1,NONCLD
      DO 20 K=1,NOC
      ARRAYO(K,J,I)=ARRAYI(K,J,I)*EXPP(JLOC,ILOC,J,I)*CONFAC(I)*POPFAC
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

   20 CONTINUE
        RFACO(1)=0.0
        IF(NCREP.EQ.0) GO TO 80
        DO 25 I=1,NCREP
25      RFACO(I)=RFACI(I)*WLRN(JLOC,ILOC)*POPFAC
      GO TO 80
   30 DO 40 I=1,4
      DO 40 J=1,NONCLD
      DO 40 K=1,NOC
      ARRAYO(K,J,I)=0.0D0
      DO 40 II=NOL,NOU
      DO 40 JJ=NRL,NRU
      ARRAYO(K,J,I)=ARRAYO(K,J,I)+ARRAYI(K,J,I) *EXPP(JJ,II,J,I)*
     > CONFAC(I)*TOTFAC
   40 CONTINUE
        RFACO(1)=0.0
        RFACO(2)=0.0
        IF(NCREP.EQ.0) GO TO 80
        DO 45 I=1,NCREP
        DO 45 II=NOL,NOU
        DO 45 JJ=NRL,NRU
        RFACO(I)=RFACI(I)*WLRN(JJ,II)*TOTFAC+RFACO(I)
45      CONTINUE
      GO TO 80
   50 DO 70 I=1,4
      DO 70 J=1,NONCLD
      TEXPP=0.0
      DO 60 II=NOL,NOU
      DO 60 JJ=NRL,NRU
      TEXPP=TEXPP+EXPP(JJ,II,J,I)
   60 CONTINUE
      DO 70 K=1,NOC
        ARRAYO(K,J,I)=ARRAYI(K,J,I)*TEXPP*CONFAC(I)
   70 CONTINUE
        RFACO(1)=0.0
        IF(NCREP.EQ.0) GO TO 80
        TWLRN=0.0
        DO 65 II=NOL,NOU
        DO 65 JJ=NRL,NRU
        TWLRN=TWLRN+WLRN(JJ,II)
65      CONTINUE
        DO 75 I=1,NCREP
        RFACO(I)=RFACI(I)*TWLRN
75      CONTINUE
   80 CALL DRTAB(ARRAYO,NOC,NAMNOC,TITLE,TITL1,TABLE,TITL2,NOTE,
     A  NUN,RFACO,CREP,NCREP,NUCLID)
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      RETURN
      END


C  ****
C     CALCS FOR NEW REPORT ADDED 1/88 BY JOAN MCGUE
C ****
C=================================================================

C=================================================================
C                                                                 -
C                   SUBROUTINE CALC DEATHS PER YEAR               -
C                                                                 -
C=================================================================

      SUBROUTINE CALC_DEATHS_PER_YEAR(OUTPUT,NOL,NOU,NRL,NRU,NONCLD,
     +                           EXPP,AGEX,RISK,NCANC,RRISK,RNFLAG,WLRN)

C   THIS SUBROUTINE CALCULATES THE NUMBER OF DEATHS PER YEAR FOR THE
C   NEW REPORT.  THE CALUCLATIONS ARE THE SAME AS THOSE USED IN THE
C   SUBROUTINE LOCTAB FOR A POPULATION RUN.  THEY MAY BE REDUNDENT
C   BUT THESE CALCULATIONS AREN'T DONE IN LOCTAB UNLESS THAT REPORT
C   IS REQUESTED FOR OUTPUT.  THEREFORE, IT'S EASIER TO DO THEM HERE
C   FOR THE NEW REPORT.

       INTEGER NOL,NOU,NRL,NRU,NONCLD,NCANC
       REAL RISK(20,40,4,2) ,FACD(4), EXPP(20,20,40,4),AGEX
       REAL OUTPUT(20,20),  CMBRSK(40,4),RRISK,WLRN(20,20)
       INTEGER I,J,DIST,DIRECT
       LOGICAL RNFLAG
C**** NOTE FACD(4) = GSCFAC * FACD(4,2) = 500   SEE PREPHR FOR NUMBERS
       DATA FACD/1.E-5,1.E-5,10.,500./,CMBRSK/160*0.0/

       DO 5 I = 1,4
           FACD(I) = FACD(I) / AGEX
   5   CONTINUE
       DO 10 I = 1,4
        DO 10 J = 1, NONCLD
          DO 10 K = 1,NCANC
C     COMBINE THE RISKS HIGH LET AND LOW LETS.

            CMBRSK(J,I) = CMBRSK(J,I) + RISK(K,J,I,1) +
     -                              RISK(K,J,I,2)
  10   CONTINUE
C   SEE IF RADON NUC FLAG SET..CALCULATE WLSUM ****
C
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      IF (RNFLAG) THEN
         FAC = 1./AGEX
         DO 15 DIRECT = NOL,NOU
            DO 15 DIST = NRL,NRU
               OUTPUT(DIST,DIRECT) = RRISK*WLRN(DIST,DIRECT)*FAC
   15    CONTINUE
      ENDIF

      DO 20 I = 1,4
         DO 20 J = 1,NONCLD
           DO 20 DIRECT = NOL,NOU
              DO 20 DIST = NRL,NRU
                 OUTPUT(DIST,DIRECT) = OUTPUT(DIST,DIRECT) +
     -             CMBRSK(J,I) * FACD(I)* EXPP(DIST,DIRECT,J,I)
   20   CONTINUE

       RETURN
       END


C*************************************************************************
C                                                                        *
C                                                                        *
C                                                                        *
C                      UTILITY ROUTINES                                  *
C                                                                        *
C                                                                        *
C                                                                        *
C*************************************************************************


C========================================================================
C                                                                       =
C                        SUBROUTINE VSORTP                              =
C                                                                       =
C========================================================================

      SUBROUTINE VSORTP(A,LA,IR)
C
      DIMENSION A(1),IU(21),IL(21),IR(1)
C
      M=1
      I=1
      J=LA
      R=.375
   10 IF (I.EQ.J) GO TO 100
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

   20 IF (R.GT..5898437) GO TO 30
      R=R+3.90625E-2
      GO TO 40
   30 R=R-.21875
   40 K=I
C                                    SELECT A CENTRAL ELEMENT OF THE
C                                    ARRAY AND SAVE IT IN LOCATION T
      IJ=I+(J-I)*R
      T=A(IJ)
      IT=IR(IJ)
C                                    IF FIRST ELEMENT OF ARRAY IS GREATER
C                                    THAN T, INTERCHANGE WITH T
      IF (A(I).LE.T) GO TO 50
      A(IJ)=A(I)
      A(I)=T
      T=A(IJ)
      IR(IJ)=IR(I)
      IR(I)=IT
      IT=IR(IJ)
   50 L=J
C                                    IF LAST ELEMENT OF ARRAY IS LESS THAN
C                                    T, INTERCHANGE WITH T
      IF (A(J).GE.T) GO TO 70
      A(IJ)=A(J)
      A(J)=T
      T=A(IJ)
      IR(IJ)=IR(J)
      IR(J)=IT
      IT=IR(IJ)
C                                    IF FIRST ELEMENT OF ARRAY IS GREATER
C                                    THAN T, INTERCHANGE WITH T
      IF (A(I).LE.T) GO TO 70
      A(IJ)=A(I)
      A(I)=T
      T=A(IJ)
      IR(IJ)=IR(I)
      IR(I)=IT
      IT=IR(IJ)
      GO TO 70
   60 TT=A(L)
      A(L)=A(K)
      A(K)=TT
      ITT=IR(L)
      IR(L)=IR(K)
      IR(K)=ITT
C                                    FIND AN ELEMENT IN THE SECOND HALF OF
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
C                                     THE ARRAY WHICH IS SMALLER THAN T
   70 L=L-1
      IF (A(L).GT.T) GO TO 70
C                                     FIND AN ELEMENT IN THE FIRST HALF OF
C                                     THE ARRAY WHICH IS GREATER THAN T
   80 K=K+1
      IF (A(K).LT.T) GO TO 80
C                                     INTERCHANGE THESE ELEMENTS
      IF (K.LE.L) GO TO 60
C                                     SAVE UPPER AND LOWER SUBSCRIPTS OF
C                                     THE ARRAY YET TO BE SORTED
      IF (L-I.LE.J-K) GO TO 90
      IL(M)=I
      IU(M)=L
      I=K
      M=M+1
      GO TO 110
   90 IL(M)=K
      IU(M)=J
      J=L
      M=M+1
      GO TO 110
C                                     BEGIN AGAIN ON ANOTHER PORTION OF
C                                     THE UNSORTED ARRAY
  100 M=M-1
      IF (M.EQ.0) RETURN
      I=IL(M)
      J=IU(M)
  110 IF (M.GT.21) WRITE(27,10000)M
      IF (J-I.GE.1) GO TO 40
      IF (I.EQ.1) GO TO 10
      I=I-1
  120 I=I+1
      IF (I.EQ.J) GO TO 100
      T=A(I+1)
      IT=IR(I+1)
      IF (A(I).LE.T) GO TO 120
      K=I
  130 A(K+1)=A(K)
      IR(K+1)=IR(K)
      K=K-1
      IF (T.LT.A(K)) GO TO 130
      A(K+1)=T
      IR(K+1)=IT
      GO TO 120
C
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

10000 FORMAT(' IN VSORTP, M=',I3)
      END


C=============================================================================
C                                                                            =
C                        SUBROUTINE GET FILE NAMES                           =
C                                                                            =
C=============================================================================


       SUBROUTINE GET_FILE_NAMES (ID_CODE, STARFILE, POPFILE,
     +                           FILES_USED, NUMBER_FILES )


       CHARACTER*8  STARFILE, POPFILE
       CHARACTER*26 ID_CODE
       CHARACTER*80 FILES_USED(10)
       INTEGER*2    NUMBER_FILES

       INTEGER*2 I, K
       LOGICAL JCL_FILE

C*******           LOOK FOR TYPE OF FILE BEING REFERENCE           ********
C******* LOOK FOR THE KEY WORDS 'POP', 'JCL',  'STARFILE'         ********
C*******    THEN PARSE THRU THE FILES USED TO GET THE NAMES       ********

      DO 10 I = 1, NUMBER_FILES

         K = INDEX ( FILES_USED (I) , 'JCL' )
         IF ( K .NE. 0 ) THEN
           JCL_FILE = .TRUE.
           CALL EXTRACT_NAME ( JCL_FILE, ID_CODE, FILES_USED (I) )
         ENDIF
 10    CONTINUE

      DO 20 I = 1, NUMBER_FILES

         K = INDEX ( FILES_USED (I) , 'POP' )
         IF ( K .NE. 0 ) THEN
           JCL_FILE = .FALSE.
           CALL EXTRACT_NAME ( JCL_FILE, POPFILE, FILES_USED (I) )
           IF ( POPFILE .NE. '********' )
     +        GO TO 25
         ENDIF
 20    CONTINUE
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

 25    DO 30 I = 1, NUMBER_FILES

         K = INDEX ( FILES_USED (I) , 'STAR' )
         IF ( K .NE. 0 ) THEN
           JCL_FILE = .FALSE.
           CALL EXTRACT_NAME ( JCL_FILE, STARFILE, FILES_USED (I) )
           IF ( STARFILE .NE. '********' )
     +        GO TO 35
         ENDIF
 30    CONTINUE


 35    RETURN
       END


C=============================================================================
C                                                                            -
C                          FUNCTION LENSTR                                   -
C                                                                            -
C=============================================================================

      INTEGER FUNCTION LENSTR (STRING)
C     ================================

C  DETERMINE THE LENGTH OF THE STRING PASSED

C          VARIABLES PASSED
C          ================

           CHARACTER STRING *(*)

C          LOCAL VARIABLES
C          ===============

           INTEGER*2 N, I


        N = LEN(STRING)
        DO 10 I = N, 1, -1
           IF ( STRING(I:I) .NE. ' ' ) THEN
              LENSTR = I
              RETURN
           ENDIF
 10     CONTINUE
        LENSTR = 0
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

       RETURN
       END

C*************************************************************************
C                                                                        *
C                                                                        *
C                      LOW LEVEL ROUTINTES                               *
C                                                                        *
C                                                                        *
C                                                                        *
C*************************************************************************


C========================================================================
C                                                                       -
C                        SUBROUTINE OUTPUT STRING                       -
C                                                                       -
C========================================================================


C========================================================================
C  OUTPUT STRING WRITES THE INFO FOR THE SYNOPSIS REPORT. THE INFO      =
C  CONTAINED IN LINES IS FORMED BY INTERNAL WRITES.  THIS ROUTINE WAS   =
C  MADE TO AID IN LINE COUNTING AND PAGING                              =
C    LINES ==>  THE CHARACTER STRINGS TO BE WRITTEN FOR THE REPORT      =
C    NUM   ==>  NUMBER OF LINES TO BE OUTPUT AT A TIME                  =
C    TITLE ==>  LOGICAL VAR, IF TRUE THE LINES TO BE OUTPUT ARE A TITLE =
C               THE LINE NUMBER IS CHECKED TO MAKE SURE THE TITLE WILL  =
C               NOT BE SPLIT UP ( IE BOTTOM AND TOP OF A PAGE )         =
C    REPRINT_TITLE ==>  LOGICAL VAR, IF TRUE THE LAST TITLE OUTPUT      =
C                       SAVED IN THE STRING SAVED_TITLE_LINES, IS OUTPUT=
C                       AT THE TOP OF A NEW PAGE.                       =
C                                                                       =
C    BY USING THESE VARS, TITLES CAN BE REPRINTED OR NOT REPRINTED. IT'S=
C    UP TO YOU.                                                         =
C========================================================================

      SUBROUTINE OUTPUT_STRING ( LINES, NUM, TITLE, REPRINT_TITLE )
C     ========================

      LOGICAL TITLE, REPRINT_TITLE

      CHARACTER*90 LINES (20)

      INTEGER*2 I
      INTEGER   NUM
```

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      INTEGER*2  PAGE_NO, LINE_COUNT, NUM_TITLE_LINES
      COMMON / COUNTERS / PAGE_NO, LINE_COUNT, NUM_TITLE_LINES

      CHARACTER*90 SAVED_TITLE_LINES (20)
      CHARACTER*26 ID_CODE
      COMMON / TITLES / SAVED_TITLE_LINES, ID_CODE

      CHARACTER*36 DATE_AND_TIME
      COMMON / HEADERINFO / DATE_AND_TIME


      IF ( TITLE ) THEN

C  SAVE TITLE FOR FUTURE IF PAGE EJECT
        DO  10 I = 1, NUM
          SAVED_TITLE_LINES (I) = LINES (I)
  10    CONTINUE
        NUM_TITLE_LINES = NUM

        I = LINE_COUNT + NUM
C  CHECK FOR TITLE BEING SPLIT UP

        IF ( I .GE. 60 ) THEN
C  NEW PAGE
          PAGE_NO = PAGE_NO + 1
          WRITE  (12, 1000 ) ID_CODE, DATE_AND_TIME, PAGE_NO
1000      FORMAT ('1',/ 1X,'ID CODE: ' ,A, 1X,'DATE/TIME:',A,1X,
     +            'PAGE ', I1 /)
          LINE_COUNT = 3
        ENDIF
      ENDIF


      DO 20 I = 1, NUM


        IF ( LINE_COUNT .GT. 60 ) THEN
C   NEW PAGE

          PAGE_NO = PAGE_NO + 1
          WRITE  (12, 1000 ) ID_CODE, DATE_AND_TIME, PAGE_NO
          LINE_COUNT = 3

          IF ( REPRINT_TITLE ) THEN
C   OUTPUT TITLE ON NEW PAGE
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

            DO 30 J = 1, NUM_TITLE_LINES
              WRITE  (12, 1010 ) SAVED_TITLE_LINES (J)
              LINE_COUNT = LINE_COUNT + 1
   30         CONTINUE

            ENDIF

          ENDIF

          WRITE  (12, 1010 ) LINES (I)
 1010     FORMAT ( A )
          LINE_COUNT = LINE_COUNT + 1

   20 CONTINUE

      RETURN
      END


C=============================================================================
C                                                                            =
C                    SUBROUTINE EXTRACT NAME                                 =
C                                                                            =
C    THE FOLLOWING SUBROUTINE PARSES THRU THE GIVEN LINE TO FIND THE         =
C    MEMBER NAME OF THE POPULATION FILE, THE WIND FILE OR THE JCL FILE       =
C    NAME. **********************   IF ITS THE JCL FILE REFERENCE LINE      =
C    THE ID CODE IS EXTRACTED.  THE ID CODE CONSISTS OF THE UNIQUE           =
C    PARTITIONED DATA SET NAME FOR THE SOURCE CATEGORY FOLLOWED BY AN        =
C    UNDERSCORE '_' FOLLOWED BY THE MEMBER NAME OF THE JCL                   =
C    AN ERROR IS INDICATED BY BOTH THE SOURCE AND MEMBER NAME                =
C    '********'.  FOR INSTANCE IF CAA88 IS NOT FOUND THIS IS AN ERROR.       =
C ***THIS CODE IS BUILT ON THE ASSUMPTION THAT THE FILE NAMES MUST BE        =
C    IN THE FOLLOWING FORMAT 'CAA88.SOURCENAME(MEMBER)'.                     =
C=============================================================================

      SUBROUTINE EXTRACT_NAME ( JCL_FILE, FNAME, LINE )

      CHARACTER FNAME *(*)
      CHARACTER*80 LINE
      LOGICAL JCL_FILE


      INTEGER*2  J, K
      INTEGER*2 LEN_SRCE

      CHARACTER* 17 SOURCE
```

DARTAB (DARTAB2.FOR) Program File
(continued)

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

      CHARACTER* 8  MEMBER

      DATA SOURCE /'                  '/


C** BEGIN

      MEMBER = '        '

      K = INDEX ( LINE, 'CAA88.' )

C**     IF 'CAA88' IS NOT FOUND IT IS AN ERROR
      IF ( K .EQ. 0 ) THEN
        IF ( JCL_FILE ) THEN
           SOURCE = '******************'
        ENDIF
        MEMBER = '********'
      ELSE
C**       FIND END OF SOURCE CATEGORY NAME
        J = INDEX ( LINE , '(' )

C**       NO LEFT PAREN INDICATES ERROR IN MEMBER NAME
        IF ( J .EQ.  0 ) THEN
          IF ( JCL_FILE ) THEN
             SOURCE = '******************'
          ENDIF
          MEMBER = '********'
        ELSE

C****     EXTRACT SOURCE CAT FOR ID CODE IF LINE IS FOR JCL FILE
          IF ( JCL_FILE ) THEN
             K = K + 6
             LENGTH = J - K
             IF  ( LENGTH .GT. 17 ) THEN
               J = K + 17
               LENGTH = 17
             ENDIF
             SOURCE (1: LENGTH) =  LINE ( K : J-1 )
          ENDIF

          K = INDEX ( LINE, ')' )

C**         NO RIGHT PAREN INDICATES ERROR IN MEMBER NAME
          IF ( K .EQ.  0 ) THEN
            MEMBER = '********'
          ELSE
```

```
0         1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012
            LENGTH = K - J - 1
            IF  ( LENGTH .GT. 8 ) THEN
              K = J + 9
              LENGTH = 8
            ENDIF
            MEMBER (1:LENGTH) = LINE ( J+1:K-1 )
          ENDIF

        ENDIF

      ENDIF

C**    IF JCL FILE MAKE THE ID CODE
      IF ( JCL_FILE ) THEN
         LEN_SRCE = LENSTR ( SOURCE )
         FNAME (1:LEN_SRCE) = SOURCE (1:LEN_SRCE)
         FNAME (LEN_SRCE+1:LEN_SRCE+1) = '_'
         FNAME (LEN_SRCE+2:LEN_SRCE+9) = MEMBER
      ELSE
         FNAME ( 1:8 ) = MEMBER
      ENDIF

      RETURN
      END
```