



United States  
Environmental  
Protection  
Agency

Office of Air Quality Planning and Standards  
Information Transfer and Program Integration Division  
Information Management Group  
Research Triangle Park, NC 27711

---

# AQS Data Dictionary

VERSION 2.3

Date Revised: October 8, 2004

# **AQS DATA DICTIONARY**

**VERSION 2.3**

**U.S. ENVIRONMENTAL PROTECTION AGENCY  
OFFICE OF AIR QUALITY PLANNING AND STANDARDS  
INFORMATION TRANSFER AND PROGRAM INTEGRATION DIVISION  
INFORMATION MANAGEMENT GROUP  
RESEARCH TRIANGLE PARK, NC 27711**

# Table of Contents

<b>1</b>	<b>Introduction.....</b>	<b>1-1</b>
1.1	AQS Documentation.....	1-1
1.2	About This Book.....	1-1
1.3	About AQS.....	1-2
<b>2</b>	<b>Description of Terms .....</b>	<b>2-1</b>
2.1	Concepts.....	2-1
2.2	Definitions.....	2-3
2.3	Data Model.....	2-8
<b>3</b>	<b>AQS Views.....</b>	<b>3-1</b>
	<b>AQS Site Views.....</b>	<b>3-1</b>
3.1	Sites.....	3-1
3.2	Tangent Roads .....	3-3
3.3	Open Paths .....	3-4
	<b>AQS Monitor Views .....</b>	<b>3-5</b>
3.4	Monitors.....	3-5
3.5	Monitor Pollutant Areas.....	3-7
3.6	Sample Periods.....	3-8
3.7	Monitor Type Assignments.....	3-9
3.8	Monitor Agency Roles.....	3-10
3.9	Monitor Objectives .....	3-11
3.10	Required Collection Frequencies.....	3-12
3.11	Sample Schedules .....	3-13
3.12	Monitor Tangent Roads .....	3-14
3.13	Probe Obstructions.....	3-15
3.14	Monitor Regulatory Compliances.....	3-16
3.15	Monitor Collocation Periods.....	3-17
3.16	Monitor Protocols .....	3-18
	<b>AQS Pollutant Data Views .....</b>	<b>3-19</b>

3.17	Composite Data.....	3-19
3.18	Composite Qualifier Details .....	3-20
3.19	Raw Data.....	3-21
3.20	Raw Qualifier Details .....	3-22
3.21	Precision Data .....	3-23
3.22	Accuracy Data.....	3-24
3.23	Blank Data .....	3-25
3.24	Blank Qualifier Details .....	3-26
<b>Comments View.....</b>		<b>3-27</b>
3.25	Comments .....	3-27
<b>AQS Pollutant Summary Views.....</b>		<b>3-28</b>
3.26	NAAQS Averages.....	3-28
3.27	Daily Summaries.....	3-29
3.28	Quarterly Summaries .....	3-30
3.29	Annual Summaries.....	3-31
3.30	Summary Maximums.....	3-33
3.31	Summary Percentiles .....	3-34
3.32	Summary Protocols.....	3-35
3.33	Monitor Precision Summaries.....	3-36
3.34	Precision Summary Protocols.....	3-37
3.35	Reporting Organization Precision Summaries.....	3-38
3.36	Monitor Accuracy Summaries .....	3-39
3.37	Accuracy Summary Protocols.....	3-40
3.38	Reporting Organization Accuracy Summaries .....	3-41
<b>4 AQS Data Table Fields.....</b>		<b>4-1</b>
4.1	Accuracy Audit ID Number.....	4-1
4.2	Accuracy Date.....	4-2
4.3	Accuracy Type .....	4-3
4.4	Action Date .....	4-4
4.5	Action Indicator .....	4-5
4.6	Action Reason.....	4-6
4.7	Action Type .....	4-7

4.8	Actual Method .....	4-8
4.9	Actual Value .....	4-9
4.10	Agency Code.....	4-10
4.11	Agency Performing FRM Audit .....	4-11
4.12	Agency Role Begin Date .....	4-12
4.13	Agency Role End Date.....	4-13
4.14	Agency Role Name.....	4-14
4.15	Alternate Method Detectable Limit .....	4-15
4.16	Applicable NAAQS Indicator.....	4-16
4.17	AQCR .....	4-17
4.18	Arithmetic Mean (Annual).....	4-18
4.19	Arithmetic Mean (Daily).....	4-20
4.20	Arithmetic Mean (NAAQS).....	4-21
4.21	Arithmetic Mean (Quarterly) .....	4-27
4.22	Arithmetic Standard Deviation .....	4-28
4.23	Audit Class.....	4-30
4.24	Audit Level .....	4-31
4.25	Audit Sample ID .....	4-32
4.26	Audit Scale.....	4-33
4.27	Audit Scheduled.....	4-34
4.28	Audit Type .....	4-35
4.29	Beam Length.....	4-36
4.30	Blank Date .....	4-37
4.31	Blank Date/Time.....	4-38
4.32	Blank Scale .....	4-39
4.33	Blank Time.....	4-40
4.34	Blank Value .....	4-42
4.35	Block.....	4-43
4.36	Block Group.....	4-44
4.37	Census Tract.....	4-45
4.38	Certification Indicator .....	4-46
4.39	City Code .....	4-47
4.40	Class I Area.....	4-48

4.41	CMSA Represented .....	4-49
4.42	Collection Date .....	4-50
4.43	Collection Frequency Code.....	4-51
4.44	Collocated POC .....	4-52
4.45	Collocation Begin Date.....	4-53
4.46	Collocation End Date.....	4-54
4.47	Comment Text .....	4-55
4.48	Community Monitoring Zone.....	4-56
4.49	Compliance Date.....	4-57
4.50	Compliance Indicator.....	4-58
4.51	Composite Period.....	4-59
4.52	Composite Type.....	4-60
4.53	Composite Year .....	4-61
4.54	Congressional District.....	4-62
4.55	Count of Accuracy Audits (Monitor Accuracy Summary).....	4-63
4.56	Count of Accuracy Audits (Reporting Organization Accuracy Summary) .....	4-64
4.57	Count of Analyzers .....	4-65
4.58	Count of Collocated Sites .....	4-66
4.59	Count of Exceptional Events .....	4-67
4.60	Count of Days Greater Than Alert Level.....	4-68
4.61	Count of Half-MDL Substitutions .....	4-69
4.62	Count of Methods .....	4-70
4.63	Count of Missing Days Assumed Less Than Standard.....	4-71
4.64	Count of Non-Overlapping Exceedances (Annual) .....	4-73
4.65	Count of Non-Overlapping Exceedances (Daily).....	4-74
4.66	Count of Null Data Values.....	4-75
4.67	Count of Observations (Annual).....	4-76
4.68	Count of Observations (Daily).....	4-77
4.69	Count of Observations (Quarterly) .....	4-78
4.70	Count of Precision Checks (Monitor Precision Summary).....	4-79
4.71	Count of Precision Checks (Reporting Organization Precision Summary).....	4-80
4.72	Count of Primary Exceedances (Annual) .....	4-81
4.73	Count of Primary Exceedances (Daily) .....	4-83

4.74	Count of Required Days.....	4-85
4.75	Count of Secondary Exceedances (Annual) .....	4-86
4.76	Count of Secondary Exceedances (Daily) .....	4-88
4.77	Count of Valid Collocated Data Pairs (Monitor Precision Summary) .....	4-90
4.78	Count of Valid Collocated Data Pairs (Reporting Organization Precision Summary)..	4-92
4.79	Count of Valid Days .....	4-94
4.80	County Code .....	4-95
4.81	Created Date.....	4-96
4.82	Created User.....	4-97
4.83	Daily Rank .....	4-98
4.84	Date Sampling Began .....	4-99
4.85	Date Sampling Ended .....	4-100
4.86	Date Site Established .....	4-101
4.87	Date Site Terminated .....	4-102
4.88	Direct Entry Indicator .....	4-103
4.89	Direction from Central Business District to Site .....	4-104
4.90	Direction from Monitor to Probe Obstruction .....	4-105
4.91	Direction from Receiver to Transmitter.....	4-106
4.92	Direction from Site to Street .....	4-107
4.93	Direction to Meteorological Site.....	4-108
4.94	Distance from Central Business District to Site .....	4-109
4.95	Distance from Monitor to Probe Obstruction .....	4-110
4.96	Distance from Monitor to Tangent Road.....	4-111
4.97	Distance from Primary Sampler.....	4-112
4.98	Distance to Meteorological Site.....	4-113
4.99	Dominant Source .....	4-114
4.100	Duration Code.....	4-115
4.101	EPA Region Concurrence Indicator.....	4-116
4.102	EPA Region Evaluation Date.....	4-117
4.103	Estimate of Days Greater Than Standard.....	4-118
4.104	Exceptional Data Type ID .....	4-121
4.105	Exclusion Date .....	4-123
4.106	Exclusion Indicator .....	4-124

4.107	Expiration Date .....	4-125
4.108	Freeze Indicator .....	4-126
4.109	Geometric Mean.....	4-127
4.110	Geometric Standard Deviation.....	4-128
4.111	Geometric Type .....	4-130
4.112	Half MDL Substitution Indicator.....	4-131
4.113	Height of Receiver .....	4-132
4.114	Height of Transmitter.....	4-133
4.115	Horizontal Accuracy .....	4-134
4.116	Horizontal Collection Method .....	4-136
4.117	Horizontal Datum.....	4-137
4.118	Hour of Maximum Value.....	4-138
4.119	HQ Evaluation Date.....	4-139
4.120	Indicated Method .....	4-140
4.121	Indicated Value .....	4-141
4.122	Land Use Type.....	4-142
4.123	Land Use Under Path.....	4-143
4.124	Last Post Date .....	4-144
4.125	Last Sampling Date.....	4-145
4.126	Latitude .....	4-146
4.127	Local Primary Standard .....	4-147
4.128	Local Region.....	4-148
4.129	Local Site ID .....	4-149
4.130	Local Site Name.....	4-150
4.131	Location Setting.....	4-151
4.132	Longitude .....	4-152
4.133	Lower Probability/Confidence Limit (Reporting Organization Accuracy Summary)	4-153
4.134	Lower Probability/Confidence Limit (Reporting Organization Precision Summary)	4-155
4.135	Maximum Beam Height.....	4-157
4.136	Maximum Indicator .....	4-158
4.137	Maximum Level.....	4-159
4.138	Maximum Value (Annual).....	4-160
4.139	Maximum Value (and Second Highest through Fifth Highest).....	4-162

4.140	Maximum Value (Daily).....	4-163
4.141	Maximum Value Date.....	4-164
4.142	Maximum Value Date of Second Highest .....	4-165
4.143	Maximum Value Date/Time .....	4-166
4.144	Maximum Value Time.....	4-167
4.145	Maximum Value Date of Second Highest .....	4-168
4.146	Mean (Monitor Accuracy Summary).....	4-169
4.147	Mean (Monitor Precision Summary) .....	4-170
4.148	Mean (Reporting Organization Accuracy Summary).....	4-172
4.149	Mean (Reporting Organization Precision Summary) .....	4-173
4.150	Measurement Scale.....	4-175
4.151	Meteorological Site ID.....	4-176
4.152	Meteorological Site Type.....	4-177
4.153	Method Code.....	4-178
4.154	Minimum Beam Height .....	4-179
4.155	Minimum Collection Frequency.....	4-180
4.156	Minimum Sample Value.....	4-181
4.157	Modified Date.....	4-182
4.158	Modified User .....	4-183
4.159	Monitor ID .....	4-184
4.160	Monitor Objective Type.....	4-186
4.161	Monitor Protocol ID.....	4-187
4.162	Monitor Protocol ID (Annual) .....	4-188
4.163	Monitor Protocol ID (Monitor Accuracy Summary).....	4-189
4.164	Monitor Protocol ID (Monitor Precision Summary) .....	4-190
4.165	Monitor Type .....	4-191
4.166	Monitor Type Begin Date.....	4-192
4.167	Monitor Type End Date .....	4-193
4.168	Monthly Required Collection Frequency.....	4-194
4.169	MSA Represented.....	4-195
4.170	NAAQS Date/Time.....	4-196
4.171	Number of Samples.....	4-197
4.172	Open Path Number.....	4-198

4.173	Parameter .....	4-199
4.174	Percent Difference .....	4-200
4.175	Percent of Observations (Annual).....	4-202
4.176	Percent of Observations (Daily).....	4-204
4.177	Percent of Observations (Quarterly).....	4-205
4.178	Percentile.....	4-209
4.179	Percentile Sample Value.....	4-210
4.180	POC.....	4-214
4.181	Pollutant Area Code.....	4-215
4.182	Pollutant Area Type .....	4-216
4.183	Precision Class.....	4-217
4.184	Precision Date .....	4-218
4.185	Precision ID .....	4-219
4.186	Precision Sample ID .....	4-220
4.187	Precision Scale .....	4-221
4.188	Primary Qualifier Code.....	4-222
4.189	Primary Qualifier Type.....	4-223
4.190	Primary Sampler Indicator.....	4-224
4.191	Primary Sampler Monitor ID .....	4-225
4.192	Probe Height .....	4-226
4.193	Probe Horizontal Distance .....	4-227
4.194	Probe Location.....	4-228
4.195	Probe Obstruction Height .....	4-229
4.196	Probe Obstruction Type .....	4-230
4.197	Probe Vertical Distance .....	4-231
4.198	Project Class.....	4-232
4.199	Qualifier Code.....	4-233
4.200	Qualifier Code- Null Data.....	4-234
4.201	Quarter Represented.....	4-235
4.202	Recording Mode.....	4-236
4.203	Reference Point.....	4-237
4.204	Regulation Code.....	4-238
4.205	Reported Sample Value .....	4-239

4.206	Reported Scale .....	4-240
4.207	Reported Unit.....	4-241
4.208	Reporting Organization.....	4-242
4.209	Required Collection Frequency Begin Date .....	4-243
4.210	Required Collection Frequency Code.....	4-244
4.211	Required Collection Frequency End Date .....	4-245
4.212	Road Type.....	4-246
4.213	Sample Date.....	4-247
4.214	Sample Date/Time .....	4-248
4.215	Sample Residence Time.....	4-249
4.216	Sample Schedule Month .....	4-250
4.217	Sample Time .....	4-251
4.218	Schedule Exemption Indicator.....	4-252
4.219	Screening Group Number .....	4-253
4.220	Sequence Number .....	4-254
4.221	Session Date.....	4-255
4.222	Session Screening Group.....	4-256
4.223	Session User ID.....	4-257
4.224	Site ID .....	4-258
4.225	Source of Traffic Count .....	4-259
4.226	Source Scale.....	4-260
4.227	Spatial Average Indicator .....	4-261
4.228	Standard Deviation (Monitor Precision Summary) .....	4-262
4.229	Standard Deviation (Reporting Organization Accuracy Summary).....	4-264
4.230	Standard Deviation (Reporting Organization Precision Summary).....	4-265
4.231	Standard Sample Value.....	4-267
4.232	Standard Scale.....	4-269
4.233	Standard Unit .....	4-270
4.234	State Code .....	4-271
4.235	Status Indicator .....	4-272
4.236	Street Address .....	4-273
4.237	Street Name.....	4-274
4.238	Summary Criteria Indicator (Annual).....	4-275

4.239	Summary Criteria Indicator (Daily)	4-277
4.240	Summary Criteria Indicator (Quarterly)	4-278
4.241	Summary Quarter	4-279
4.242	Summary Year	4-280
4.243	Supporting Agency	4-281
4.244	Surrogate Indicator	4-282
4.245	Tangent Street Number	4-283
4.246	Time Period	4-284
4.247	Time Zone	4-285
4.248	Traffic Count	4-286
4.249	Uncertainty Value	4-287
4.250	Unrestricted Air Flow Indicator	4-288
4.251	Upper Probability Limit (Reporting Organization Accuracy Summary)	4-289
4.252	Upper Probability Limit (Reporting Organization Precision Summary)	4-291
4.253	Urban Area Code	4-294
4.254	Urban Area Represented	4-295
4.255	UTM Easting	4-296
4.256	UTM Northing	4-297
4.257	UTM Zone	4-298
4.258	Vertical Accuracy	4-299
4.259	Vertical Collection Method	4-300
4.260	Vertical Datum	4-301
4.261	Vertical Measure	4-302
4.262	Weighted Arithmetic Mean	4-303
4.263	Worst Site Type	4-305
4.264	Year of Traffic Count	4-306
4.265	Year Represented	4-307
4.266	Zero Span	4-308
4.267	Zero Span Scale	4-309
4.268	Zip Code	4-310

# 1 Introduction

## 1.1 AQS Documentation

This is the AQS Data Dictionary, part of the Documentation set for the Air Quality System (AQS)

- AQS Data Dictionary
- AQS Data Input Formats (Summary)
- AQS Data Coding Manual
- AQS User's Guide (in draft)
- AQS Data Reports and Retrieval Manual (in draft)

The AQS Data Dictionary presents detailed information about data in the database. Logical groupings of data (“views”) are documented, to help with effective use of the data. Field attributes and definitions, and calculation algorithms, are provided as appropriate. This document also provides information on transformed, derived or calculated information presented to the user that does not directly reflect data in the form that it is stored in the database.

AQS Data Input Formats, is a small summary document showing the basic requirements for data input. It is intended as a quick reference guide. Detailed information on the various data input formats is contained in the AQS Data Coding Manual.

The AQS Data Coding Manual includes the information a user needs to know to create transactions for loading data into the database. Information in the manual is presented on a transaction by transaction basis. Business rules used by the AQS edit software, as well as the accompanying error messages, are laid out to help build error free transactions, or troubleshoot failed transactions.

The AQS User's Guide, includes information about accessing the system via a web browser, using the on-line interface, and entering data using the on-line data entry screens (Maintenance screens). The process for “loading” the transactions described in AQS Data Coding Manual is explained, including using the “critical review” process, and “posting” the data to the database.

The AQS Data Retrieval Manual, includes information about using the standard report generation software. Information includes the type of reports, the selections available for each report, the data included on the reports, and the on-line report interface. Information about available work file outputs is also included.

## 1.2 About This Book

This volume, AQS Data Dictionary, describes the views, records, and fields used by AQS. The data dictionary is organized by sections.

This introductory section provides a brief overview of the Air Quality System with a discussion of the structure of the AQS data.

Section 2:

1. Presents basic database concepts,
2. Describes the structure of the AQS
3. Presents data model diagrams that show the relationships between the data.
4. Defines terms used throughout the document, and their meaning in AQS.

Section 3 describes the AQS views. Each view description includes:

1. A narrative explaining its purpose, content, and use;
2. A description of the fields contained in the view.

Section 4 describes the AQS fields. The fields are presented in alphabetic order. Field descriptions include:

1. A narrative describing the field, including its uses;
2. Those parts of AQS that are the source of the data;
3. The data type, length, and whether the field is required;
4. The views in which the field is used;
5. Any rules of value assignment, including algorithms and formulas.

### **1.3 About AQS**

The Air Quality System (AQS) is a computer-based information management system for handling the storage and retrieval of information pertaining to ambient outdoor airborne pollutants and related meteorologic data. The AQS database uses Oracle database software; access to the database is provided via web browsers (i.e. Internet Explorer). AQS is administered by the U.S. Environmental Protection Agency (USEPA), Office of Air Quality Planning and Standards (OAQPS) in Research Triangle Park, North Carolina.

The collection and maintenance of air quality data is required to establish and enforce the standards set by the following Federal Acts and Amendments:

1955: Air Pollution Control Act

“An Act to provide research and technical assistance relating to air pollution control“

Reserved for Congress the right to control pollution.

1963: Clean Air Act

Emissions standards for stationary sources

Compliance deadlines for States

1965: Motor Vehicle Air Pollution Control Act

Emissions standards for vehicles

1967: Air Quality Act

Created Air Quality Control Regions (AQCR)

Timetables for State Implementation Plans (SIP)

1970: Amendments to the Clean Air Act

National Ambient Air Quality Standards (NAAQS)

New Source Performance Standards(NSPS)

New motor vehicle standards and compliance timetable

## 1990: Amendments to the Clean Air Act Modification of standards and timetables

The monitoring data in AQS are the result of the various Clean Air Act requirements to provide a national database of ambient air pollution data. Criteria pollutant (SO<sub>2</sub>, NO<sub>2</sub>, O<sub>3</sub>, CO, PM<sub>10</sub>, PM<sub>2.5</sub> and Pb) data, air toxic data, photochemical assessment data, and meteorological data. Individual observations, as well as summarized data are provided. The database contains values from 1957 through the present day. AQS contains hundreds of millions of observations, coming from tens of thousands of monitors.

As regulations broaden to include more pollutants, the AQS system expands. For hazardous air pollutants (HAPS) the USEPA is currently gathering data and has proposed baselines for limiting emissions. There are currently over 1000 pollutants that AQS is prepared to track and additions are made as needed.

In addition to the ambient pollutant concentration data, AQS contains descriptive information about the location of the monitoring site (e.g., address, latitude/longitude, local site name, etc.) where the ambient data are collected as well as information about the types of monitors used to collect the ambient measurements. Quality assurance information is also contained in the AQS.

The air pollution monitoring data residing in the AQS database is submitted directly to the database by many different groups. The State, Tribal and Local air pollution agencies throughout the United States routinely submit monitoring data from the air monitors that they manage. Some Federal agencies, including USEPA, and private companies also supply data directly. The data submitted by these various groups are “owned” by those groups... in other words only the agency responsible for a monitor at a site can maintain that monitor’s data. USEPA’s OAQPS maintains the administrative data in AQS (e.g. reference tables and codes, security tables, and overall software maintenance).

AQS data are not real time, because observation data are quality assured by the submitting agencies before loading into the database. Agencies generally have 3 months to collect, analyze, compute, and quality assure the values prior to loading the data into AQS. Each year, the monitoring agencies certify to USEPA that the criteria pollutant data values for that year are correctly stored in the database. This data serves as the basis for area designations (e.g. non-attainment designations), among many other uses. In addition to providing data for evaluating conformance to Federal regulations, data from the AQS is used to fulfill air quality information requests from the public.

Summary air quality data is available on AQS from 1957 onward. Detailed data reported from individual monitoring devices are available for the past decade. Older detail data are available as download files from the archive database. See the AQS website for these files. If you do not see the files you need, the website also contains a request form to receive those files. The website address is as follows:

<http://www.epa.gov/ttn/airs/airsaqs/detaildata/requestingaqsdta.htm>

## 2 Description of Terms

### 2.1 Concepts

The AQS is both a repository and a tool.

#### 2.1.1 AQS Repository

As a repository of data the AQS stores air quality information in a computer database. Over the years this data has been stored on various computers in various forms. In the last decade the data has been moved from an IBM system in ADATABASE, to a Digital Equipment system in Oracle and will be moving to a faster system in the near future.

The repository contains data from 1957 to the present. In the late 1950s there were a few hundred sites reporting data, that grew to over 5000 sites in the mid 1970s and there are now a little over 3000 sites reporting data today. In 1957 only a few pollutants were monitored at each location. Today there are some sites monitoring over 150 different pollutants so the repository is receiving data from between 50 and 60 thousand data sources each year. Each source reports raw data at different rates, some hour or sub-hourly, some daily, some every few days. There are over 82 million new raw data records added to the repository each year.

With such a large amount of data to work with the repository has been broken into over 100 “tables” of data. This distribution of data is an attempt to improve load and search times and to reduce unnecessary repetition of data values. This distributed data structure is normally concealed. While the repository is perhaps impressive in its complexity, size and scope, the normal user of AQS has no direct contact with it. For users the data is structured into logical “views”.

#### 2.1.2 Views Of The Repository.

While the actual data structure of the repository is concealed, the logical structure of the data is very important to understand. In brief form, the structure of AQS can be stated as: “Sites contain monitors which contain raw data, summary data, precision data and accuracy data.”

In order to present the data to the user logically, **views** have been created that collect the data that is dispersed throughout the database and present it as a logically structured, unified dataset.

A **site** is logically identified by two or three elements: State/County codes (or Tribal code) and Site ID. While multiple sites may be in a County and/or Tribal area, they each must have a unique site ID. These codes describe the unique identifier of the Site or the **key**. Each site record then contains required data elements such as location data (lat/lon or UTM, elevation, address, etc.) Optional information such as the agency that services it, associated meteorological site or congressional district are also included in the view of the site.

There are 3 views associated with sites. In addition to the main site view there is a Tangent Road view and an Open Path view. Because there can be multiple roads near a site, each road can be treated as a separate entity associated with the site. Multiple site views avoids burdening a single view with all the data associated with a site.

The unique ID key elements for a **monitor** are its site elements, plus a pollutant code and a parameter occurrence code (POC). Note: A “monitor” in AQS represents not a device but the pollutant measured by a device. A single device that measures multiple pollutants appears as multiple monitors within AQS, each AQS monitor representing one pollutant. Sites may have more than one monitor measuring the same pollutant. Each monitor is uniquely identified with a unique POC. Data elements associated with the monitor include the agency reporting the data, the group responsible for entering the data, data collection frequency, collection method, etc. Different fields are required depending on the pollutant. To fully describe a monitor there are 13 views available.


**Raw data** values are the pollutant levels reported by a monitor. The logical identifier key for raw data is made up of the site/monitor elements plus Date and Time elements. Raw Data Views described in this Data Dictionary present date/time as a single field in the form of Year, Month, Day, Hour, Minute (YYMMDDHH:mm). When this same identifier is presented in the AQS tools for data entry and reports it is usually broken into separate Date and Time fields. The AQS Data Table Fields section of this book includes definitions and descriptions for both the combined and separated fields. (It is in the database as a single field.)

While raw data is linked to a monitor, Qualifiers and Comments are linked to raw data. Qualifier codes represent natural or anthropogenic events that explain high, low or null raw data values.

Precision, Accuracy and Blanks records are logically identified using the same elements used to identify raw data.

**Summaries** are identified with their unique identifier key being the monitor identifier elements, year element, duration element and qualifier type. Each monitor has summaries pre-calculated from its associated raw data and stored in the repository for each year it is active. There are multiple summaries calculated based on sample durations and with different types of qualifiers included or excluded.

The illustration below shows the links between logical data elements in AQS.



More illustrations showing the relationships between each of the views are in the Data Model section below.

### 2.1.3 AQS Tools

It is the AQS tools that make the AQS data in the repository useful and meaningful. The AQS repository is now accessed through web browser interfaces for:

- Loading data,
- Maintaining/correcting data and
- Reporting/extracting data.

AQS tools are described in more detail in the AQS Coding Manual and AQS Users Manual.

## 2.2 Definitions

<b>Term</b>	<b>Definition</b>
Active Day	A day occurring within a valid sample period.
AQCR	Air Quality Control Region
AQS	Air Quality System
AQS Field Name	The standard term for an AQS data element. When AQS data is presented in a tabular view the column header would be the field name.
Average	Arithmetic mean
CEILING	A CEILING function returns the smallest integer higher than, or equal to, the given number. Frequently referred to as “rounding up”.
CFR	Code of Federal Regulations
CMSA	Consolidated Metropolitan Statistical Area
CO	Carbon Monoxide
Composite Data	An average pollutant value entered as a single record in the database that is calculated from multiple samples.
Database Field Name	The Oracle field name for an AQS data element. The name must conform to Oracle field name constraints, e.g., a maximum of 30 characters, no spaces, no punctuation marks, etc. The database field name will generally be an abbreviated form of the AQS field name.
EDR	Environmental Data Registry
EPA	Environmental Protection Agency

<b>Term</b>	<b>Definition</b>
Exceedance	A sample value measurement that is above the level of the applicable standard.
Field Type (Length)	<p>There are four field types used in AQS: character, numeric, float, and date.</p> <p>The lengths represent the length of the underlying physical field. The physical length is large enough to accommodate the current lengths used plus any future growth. For example, Method Code has a length of 8, which accommodates the 3-digit logical length currently used and any conceivable expansion needed in the future.</p> <p>Character types have maximum lengths associated with them. The lengths of numeric fields are indicated by the number of digits to the left and right of the decimal point. For example, a numeric field with a length of 8.2 has 8 digits to the left of the decimal point, and 2 to the right, for a maximum of 10, i.e., nnnnnnnn.nn. Date and float types have a fixed length by definition. The date type includes both date and time in that same fixed length; the float type can accommodate numbers in the range of 1.0E-129 through 9.999E125.</p>
FIPS	Federal Information Processing Standards
FRM	Federal Reference Method
GPS	Global Positioning System
Hourly Sample	A sample whose sample duration, or interval, is one (1) hour.
HQ	EPA Headquarters
ID	Numeric identifier
Key	<p>An indication of whether a field is part of the unique identification of a record in the view.</p> <p>The combination of data elements that uniquely identify a record in the view</p>
LDP	Locational Data Policy
LST	Local Standard Time
Make-Up Sample	A sample recorded as a replacement for a missing Scheduled Sample.

<b>Term</b>	<b>Definition</b>
MDL	Method detectable limit, or the lowest concentration that can be detected by a sampling instrument and method.
MINIMUM	A MINIMUM function returns the least of a series of numbers.
Monitoring Season (Defined)	The consecutive sub-annual period, defined by state, county, or site, during which ozone monitoring is required for National Air Monitoring Station (NAMS) and Local Air Monitoring Station (SLAMS) monitors, as, listed in the ambient monitoring rule (40CFR58, Appendix D.)
Monitoring Season (Effective)	The defined monitoring season for a National Air Monitoring Station (NAMS) or Local Air Monitoring Station (SLAMS) monitor extended to include the earliest and latest exceedances occurring outside that defined season.
MSA	Metropolitan Statistical Area
NAAQS	National Ambient Air Quality Standards
NAMS	National Air Monitoring Station
NO2	Nitrogen Dioxide
PAMS	Photochemical Assessment Monitoring System
Parameter	Pollutant measured by a device
Pb	Lead
PEP	Performance Evaluation Program
PM	Particulate Matter
PM10	PM10 Total 0-10um
PM2.5	PM2.5 - Local Conditions
POC	Parameter Occurrence Code
ppm	Parts Per Million
O3	Ozone
Raw Data	Parameter level value reported from a single observation. The duration of the sample depends on the device and method of collection.
RCF	Required Collection Frequency

<b>Term</b>	<b>Definition</b>
Required	An indication of whether a field always has a value, i.e., not null. It should be noted that an indication that a field value is required does not mean that it must be user-specified; it may be system-generated. Some columns are conditionally user-specified and system generated. For example, for site coordinates the user may specify the latitude and longitude coordinates, and the system will generate the Universe Transverse Mercator (UTM) coordinates, or vice versa.
Row	Collection of data fields that, together, make up a single record in a data table.
Scheduled Day	A day where sampling is required for a monitor, as determined by the applicable required collection frequency and the National Air Monitoring Station (NAMS) schedule.
Scheduled Sample	A sample recorded on a Scheduled Day.
Scheduled Stratum	A period of time starting from a Scheduled Day up to, but not including the immediately succeeding Scheduled Day.
SLAMS	Local Air Monitoring Station
SO <sub>2</sub>	Sulfur Dioxide
Table	A collection of related data organized into logical rows and columns. The structure that is the repository of data in the computer. See "View"
TSP	Total Suspended Particulate
μg/m <sup>3</sup> LC	micrograms per cubic meter – local conditions
μg/m <sup>3</sup> SC	micrograms per cubic meter – standard conditions
USGS	United States Geological Survey
UTM	Universal Transverse Mercator. A geospatial positioning system that breaks areas of the earth into zones and identifies a location with a pair of numbers (Easting and Northing for US locations)


<b>Term</b>	<b>Definition</b>
Valid Daily Maximum	The maximum value recorded, or computed, on a day that meets daily summary criteria.
Valued Stratum	A Scheduled Stratum during which at least one observation was recorded.
Value Set	A collection of data values associated together in a table or view. When presented in tabular form, a row or part of a row containing associated values. The ten highest reported pollutant values in a year is a value set in the <i>Annual Summary</i> view made up of the fields containing the values, their ranks and the date/time of each value.
View	A logical representation of data, looking like a table, where data elements are grouped, joined or transformed together from one or more tables of data. Views are used, rather than actual data tables, to simplify the AQS database for users.
WGS	World Geodetic Survey

## 2.3 Data Model


### 2.3.1 Sites and Monitors

In the data model diagram below the relationships between the logical data views is illustrated. The arrows indicate a Parent>Child relationship.


- A Site record can be a parent to Tangent Roads, Open Paths, Monitors and Comments.
- A Monitor Tangent Road record is the child of BOTH the Tangent Road of a site and the Monitor of the same site. (Sites can be large enough that devices on the site can have significant differences in distance from roads.)
- Monitor views may reference Open Paths defined on the parent site. There is no corresponding monitor open path view.
- Comments may be accessed from a single view and are the children of EITHER a Monitor OR a Site.



### 2.3.2 Monitors and Pollutant Data




### 2.3.3 Monitors and Summaries



### 2.3.4 Monitors and Precision & Accuracy Data

Note that this diagram shows the subordinate relationships between views and does not show the derivation of the data. A Monitor Precision Summary is subordinate to a Monitor Agency Role within a Monitor. Reporting Organization Summaries contain data from multiple monitors and therefore are not subordinate to a view of a single monitor.



## 3 AQS Views

### AQS Site Views

#### 3.1 Sites

##### 3.1.1 Description

The Sites view contains information about Air Quality Sites, including: geographical information, (e.g., latitude and longitude, Universe Transverse Mercator, i.e., UTM coordinates), historical information, (e.g., established and terminated dates), site location information, (e.g., street address, city, Air Quality Control Region or AQCR), and other general characteristics, (e.g., land use, location setting). In addition, the view contains all information required by the Locational Data Policy. A Sites record is uniquely identified by the combination of state, county, and site ID. Alternative unique identifiers are the latitude-longitude combination, and the UTM coordinates. Its parent is the Counties view; its child views are: Tangent Roads, Open Paths, Monitors, and Comments.

##### 3.1.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
State Code	STATE_CODE	CHARACTER (2)	√	√
County Code	COUNTY_CODE	CHARACTER (3)	√	√
Site ID	SITE_ID	CHARACTER (4)	√	√
Status Indicator	STATUS_IND	CHARACTER (1)	√	
Latitude	LATITUDE	NUMBER (2.6)	√	
Longitude	LONGITUDE	NUMBER (3.6)	√	
UTM Zone	UTM_ZONE	NUMBER (12)	√	
UTM Easting	UTM_EASTING	NUMBER (8.2)	√	
UTM Northing	UTM_NORTHING	NUMBER (8.2)	√	
Horizontal Collection Method	LDP_COLL_METHOD_CODE	CHARACTER (8)	√	
Horizontal Datum	LDP_HORIZ_DATUM	CHARACTER (120)	√	
Horizontal Accuracy	LDP_HORIZ_ACC_VALUE	NUMBER (8.2)	√	
Source Scale	LDP_SOURCE_SCALE	NUMBER (12.0)	√	
Geometric Type	LDP_GEOMETRIC_TYPE	CHARACTER (50)	√	
Reference Point	LDP_REFERENCE_POINT	CHARACTER (50)	√	
Vertical Measure	LDP_VERT_MEAS	NUMBER (8.2)	√	
Vertical Collection Method	LDP_VERTICAL_METHOD_CODE	CHARACTER (3)	√	
Vertical Datum	LDP_VERTICAL_DATUM	CHARACTER (60)	√	
Vertical Accuracy	LDP_VERT_ACC_VALUE	NUMBER (8.2)	√	
Time Zone	TIME_ZONE_NAME	CHARACTER (30)	√	
Supporting Agency	AGENCY_CODE	CHARACTER (8)		
Street Address	STREET_ADDRESS	CHARACTER (240)	√	
City Code	CITY_CODE	CHARACTER (8)	√	
Urban Area Code	UAR_CODE	CHARACTER (4)	√	
AQCR	AQCR_CODE	CHARACTER (8)	√	
Land Use Type	LAND_USE_TYPE	CHARACTER (20)	√	

<b>Name</b>	<b>Database Field</b>	<b>Type (Length)</b>	<b>Req'd</b>	<b>Key</b>
Location Setting	LOCATION_SETTING	CHARACTER (50)	√	
Date Site Established	SITE_ESTAB_DATE	DATE	√	
Date Site Terminated	SITE_TERMINATED_DATE	DATE		
Zip Code	ZIP_CODE	CHARACTER (9)		
Congressional District	CONGR_DISTR_NUM	NUMBER (12.0)		
Census Tract	CENSUS_TRACT_NUM	CHARACTER (6)		
Block Group	BLOCK_GROUP_NUM	CHARACTER (1)		
Block	BLOCK_NUM	CHARACTER (4)		
Class I Area	CLASS_I_AREA_CODE	CHARACTER (8)		
Local Region	LOCAL_REGION_CODE	CHARACTER (8)		
Local Site Name	LOCAL_SITE_NAME	CHARACTER (70)		
HQ Evaluation Date	HQ_EVAL_DATE	DATE		
EPA Region Evaluation Date	REGIONAL_EVAL_DATE	DATE		
Direction from Central Business District to Site	COMPASS_SECTOR_CBD	CHARACTER (3)		
Distance from Central Business District to Site	CITY_DIST	NUMBER (8.2)		
Meteorological Site Type	MET_SITE_TYPE	CHARACTER (20)		
Meteorological Site ID	MET_SITE_ID	CHARACTER (11)		
Direction to Meteorological Site	COMPASS_SECTOR_MET_SITE	CHARACTER (3)		
Distance to Meteorological Site	MET_SITE_DIST	NUMBER (8.2)		
Local Site ID	LOCAL_SITE_ID	CHARACTER (40)		
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		
Modified Date	MODIFIED_DATE	DATE		

## 3.2 Tangent Roads

### 3.2.1 Description

The Tangent Roads view contains information about streets near a monitoring site, including: the name, positioning relative to the site, and general use characteristics. A Tangent Roads record is uniquely identified by the combination of state, county, site ID, and street number. Its parent is the Sites view; its child view is Monitor Tangent Roads.

### 3.2.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
State Code	STATE_CODE	CHARACTER (2)	√	√
County Code	COUNTY_CODE	CHARACTER (3)	√	√
Site ID	SITE_ID	CHARACTER (4)	√	√
Tangent Street Number	TANGENT_ROAD_NUM	NUMBER (12.0)	√	√
Status Indicator	STATUS_IND	CHARACTER (1)	√	
Street Name	TANGENT_ROAD_NAME	CHARACTER (50)	√	
Road Type	ROAD_TYPE	CHARACTER (20)	√	
Direction from Site to Street	COMPASS_SECTOR	CHARACTER (3)	√	
Traffic Count	DAILY_TRAFFIC_CNT	NUMBER (12.0)		
Year of Traffic Count	DAILY_TRAFFIC_YEAR	NUMBER (4.0)		
Source of Traffic Count	TRAFFIC_VOLUME_SOURCE	CHARACTER (50)		
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		
Modified Date	MODIFIED_DATE	DATE		

### 3.3 Open Paths

#### 3.3.1 Description

The Open Paths view contains information about open paths at a monitoring site, including relative positioning and dimensions. An open paths record is uniquely identified by the combination of state, county, site ID, and path number. Its parent is the Sites view.

#### 3.3.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
State Code	STATE_CODE	CHARACTER (2)	√	√
County Code	COUNTY_CODE	CHARACTER (3)	√	√
Site ID	SITE_ID	CHARACTER (4)	√	√
Open Path Number	OPEN_PATH_NUM	NUMBER (12.0)	√	√
Status Indicator	STATUS_IND	CHARACTER (1)	√	
Direction from Receiver to Transmitter	COMPASS_SECTOR	CHARACTER (3)	√	
Land Use Under Path	LAND_USE_TYPE	CHARACTER (20)	√	
Beam Length	BEAM_LENGTH	NUMBER (8.2)		
Minimum Beam Height	MIN_BEAM_HEIGHT	NUMBER (8.2)		
Maximum Beam Height	MAX_BEAM_HEIGHT	NUMBER (8.2)		
Height of Receiver	RECEIVER_HEIGHT	NUMBER (8.2)		
Height of Transmitter	TRANSMITTER_HEIGHT	NUMBER (8.2)		
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		
Modified Date	MODIFIED_DATE	DATE		

# AQS Monitor Views

## 3.4 Monitors

### 3.4.1 Description

The Monitors view contains information about air quality monitoring stations, including: parameter, Pollutant Occurrence Code (POC), dominant source of pollution, measurement scale, and probe description information. A Monitors record is uniquely identified by the combination of state, county, site ID, parameter, and POC. Its parent is the Sites view; its child views are: Sample Periods, Monitor Type Assignments, Monitor Agency Roles, Monitor Objectives, Required Collection Frequencies, Monitor Tangent Roads, Monitor Pollutant Areas, Monitor Regulatory Compliances, Monitor Protocols, Monitor Collocation Periods, Probe Obstructions, Comments, NAAQS Averages, Daily Summaries, Quarterly Summaries, and Annual Summaries.

### 3.4.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
State Code	STATE_CODE	CHARACTER (2)	√	√
County Code	COUNTY_CODE	CHARACTER (3)	√	√
Site ID	SITE_ID	CHARACTER (4)	√	√
Parameter	PARAMETER_CODE	CHARACTER (5)	√	√
POC	POC	NUMBER (2.0)	√	√
Status Indicator	STATUS_IND	CHARACTER (1)	√	
Monitor ID	MONITOR_ID	CHARACTER (20)	√	
Screening Group	SCREENING_GROUP_NUM	NUMBER (12.0)	√	
Project Class	PROJECT_TYPE_CODE	CHARACTER (8)		
Dominant Source	DOMINANT_SOURCE	CHARACTER (20)		
Measurement Scale	MEASUREMENT_SCALE	CHARACTER (20)		
Open Path Number	OPEN_PATH_NUM	NUMBER (12.0)		
Probe Location	PROBE_LOCATION	CHARACTER (20)		
Probe Height	PROBE_HEIGHT	NUMBER (8.2)		
Probe Horizontal Distance	PROBE_HORIZ_DIST	NUMBER (8.2)		
Probe Vertical Distance	PROBE_VERT_DIST	NUMBER (8.2)		
Surrogate Indicator	SURROGATE_IND	CHARACTER (1)		
Unrestricted Air Flow Indicator	UNRESTR_AIR_FLOW_IND	CHARACTER (1)		
Sample Residence Time	SAMPLE_RESIDENCE_TIME	NUMBER (8.2)		
Last Post Date	LAST_RAW_DATA_POST_DATE	DATE		
Last Sampling Date	LAST_SAMPLING_DATE	DATE		
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		

<b>Name</b>	<b>Database Field</b>	<b>Type (Length)</b>	<b>Req'd</b>	<b>Key</b>
Modified Date	MODIFIED_DATE	DATE		

## 3.5 Monitor Pollutant Areas

### 3.5.1 Description

The Monitor Pollutant Areas view contains information about designations of monitors to pollutant areas, which are geographic areas defined by a program office in which a certain pollutant should be closely watched. Pollutant area types are Monitoring Areas, Monitor Planning Areas, and Status Areas. A Monitor Pollutant Areas record is uniquely identified by the combination of monitor and pollutant area. Its parent is the Monitors view.

### 3.5.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Pollutant Area Code	POLLUTANT_AREA_CODE	CHARACTER (5)	√	√
Status Indicator	STATUS_IND	CHARACTER (1)	√	
Pollutant Area Type	POLLUTANT_AREA_TYPE	CHARACTER (40)	√	
Worst Site Type	WORST_SITE_TYPE	CHARACTER (8)		
Community Monitoring Zone	COMMUNITY_MONITORING_ZONE	NUMBER (4.0)		
Applicable NAAQS Indicator	APPLICABLE_NAAQS_IND	CHARACTER (1)		
Spatial Average Indicator	SPATIAL_AVERAGE_IND	CHARACTER (1)		
Schedule Exemption Indicator	SCHEDULE_EXEMPTION_IND	CHARACTER (1)		
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		
Modified Date	MODIFIED_DATE	DATE		

## 3.6 Sample Periods

### 3.6.1 Description

The Sample Periods view defines the time periods during which sampling took place at a monitor. A Sample Periods record is uniquely identified by the combination of monitor and the date sampling began. Its parent is the Monitors view.

### 3.6.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Date Sampling Began	SAMPLING_BEGIN_DATE	DATE	√	√
Date Sampling Ended	SAMPLING_END_DATE	DATE		
Status Indicator	STATUS_IND	CHARACTER (1)	√	
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		
Modified Date	MODIFIED_DATE	DATE		

## 3.7 Monitor Type Assignments

### 3.7.1 Description

The Monitor Type Assignments view defines time periods during which a monitor was assigned a particular monitor type, e.g. Local Air Monitoring Station (SLAMS), National Air Monitoring Station (NAMS), or Photochemical Assessment Monitoring System (PAMS). A Monitor Type Assignments record is uniquely identified by the combination of monitor, monitor type, and the date the assignment began. Its parent is the Monitors view.

### 3.7.2 Elements

Name	Database Field	Type (Length)	Length	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	20	√	√
Monitor Type	MONITOR_TYPE	CHARACTER (20)	20	√	√
Monitor Type Begin Date	MONITOR_TYPE_BEGIN_DATE	DATE		√	√
Monitor Type End Date	MONITOR_TYPE_END_DATE	DATE			
Status Indicator	STATUS_IND	CHARACTER (1)	1	√	
Action Type	ACTION_TYPE	CHARACTER (8)			
Action Date	MONITOR_TYPE_ACTION_DATE	DATE			
Action Reason	ACTION_REASON_CODE	CHARACTER (8)			
Created User	CREATED_USER	CHARACTER (40)			
Created Date	CREATED_DATE	DATE			
Modified User	MODIFIED_USER	CHARACTER (40)			
Modified Date	MODIFIED_DATE	DATE			

## 3.8 Monitor Agency Roles

### 3.8.1 Description

The Monitor Agency Roles view defines time periods during which a role, (reporting, collecting, analyzing), for a monitor was assigned to an agency. A Monitor Agency Roles record is uniquely identified by the combination of monitor, role, and the date the role assignment began. Its parent is the Monitors view.

### 3.8.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Agency Role Name	ROLE	CHARACTER (20)	√	√
Agency Code	AGENCY_CODE	CHARACTER (8)	√	
Agency Role Begin Date	AGENCY_ROLE_BEGIN_DATE	DATE		√
Agency Role End Date	AGENCY_ROLE_END_DATE	DATE		
Status Indicator	STATUS_IND	CHARACTER (1)	√	
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		
Modified Date	MODIFIED_DATE	DATE		

## 3.9 Monitor Objectives

### 3.9.1 Description

The Monitor Objectives view contains information that classifies the reason air monitoring is being performed, and the target of that monitoring. A Monitor Objectives record is uniquely identified by the combination of monitor and the objective type. Its parent is the Monitors.

### 3.9.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Monitor Objective Type	MONITOR_OBJ_TYPE	CHARACTER (50)	√	√
Status Indicator	STATUS_IND	CHARACTER (1)	√	
Urban Area Represented	UAR_CODE	CHARACTER (4)		
MSA Represented	MSA_CODE	CHARACTER (8)		
CMSA Represented	CMSA_CODE	CHARACTER (8)		
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		
Modified Date	MODIFIED_DATE	DATE		

## 3.10 Required Collection Frequencies

### 3.10.1 Description

The Required Collection Frequencies view defines time periods during which a designated frequency of data collection was required. A Required Collection Frequencies record is uniquely identified by the combination of monitor, and the date the required frequency became effective. Its parent is the Monitors view.

### 3.10.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Required Collection Frequency Begin Date	REQ_COLL_FREQ_BEGIN_DATE	DATE	√	√
Required Collection Frequency End Date	REQ_COLL_FREQ_END_DATE	DATE		
Required Collection Frequency Code	COLL_FREQ_CODE	CHARACTER (8)	√	
Status Indicator	STATUS_IND	CHARACTER (1)	√	
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		
Modified Date	MODIFIED_DATE	DATE		

## 3.11 Sample Schedules

### 3.11.1 Description

The Sample Schedules view contains information about monthly collection frequencies for seasonal or random required collection frequency period. A Sample Schedules record is uniquely identified by the combination of monitor, the date a required collection frequency became effective, and month. Its parent is the Required Collection Frequencies view.

### 3.11.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Required Collection Frequency Begin Date	REQ_COLL_FREQ_BEGIN_DATE	DATE	√	√
Sample Schedule Month	SAMPLE_SCHEDULE_MONTH	NUMBER (2,0)	√	√
Status Indicator	STATUS_IND	CHARACTER (1)	√	
Monthly Required Collection Frequency	COLL_FREQ_CODE	CHARACTER (8)	√	
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		
Modified Date	MODIFIED_DATE	DATE		

## 3.12 Monitor Tangent Roads

### 3.12.1 Description

The Monitor Tangent Roads view defines the distance between a monitor and a tangent road. A Monitor Tangent Roads record is uniquely identified by the combination of monitor and street number. Its parents are the Monitors and Tangent Roads views.

### 3.12.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Tangent Street Number	TANGENT_ROAD_NUM	NUMBER (12.0)	√	√
Status Indicator	STATUS_IND	CHARACTER (1)	√	
Distance from Monitor to Tangent Road	DIST_TO_TANGENT_ROAD	NUMBER (8.2)	√	
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		
Modified Date	MODIFIED_DATE	DATE		

### 3.13 Probe Obstructions

#### 3.13.1 Description

The Probe Obstructions view contains information about any restriction of airflow around the probe. A Probe Obstructions record is uniquely identified by the combination of monitor and obstruction type. Its parent is the Monitors view.

#### 3.13.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Probe Obstruction Type	PROBE_OBSTR_TYPE	CHARACTER (20)	√	√
Direction from Monitor to Probe Obstruction	COMPASS_SECTOR	CHARACTER (3)	√	√
Status Indicator	STATUS_IND	CHARACTER (1)	√	
Distance from Monitor to Probe Obstruction	PROBE_OBSTR_DIST	NUMBER (8.2)	√	
Probe Obstruction Height	PROBE_OBSTR_HEIGHT	NUMBER (8.2)	√	
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		
Modified Date	MODIFIED_DATE	DATE		

## 3.14 Monitor Regulatory Compliances

### 3.14.1 Description

The Monitor Regulatory Compliances view documents compliance of a monitor with a regulation. A Monitor Regulatory Compliances record is uniquely identified by monitor and regulation. Its parent is the Monitors view.

### 3.14.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Regulation Code	REGULATION_CODE	CHARACTER (8)	√	√
Status Indicator	STATUS_IND	CHARACTER (1)	√	
Compliance Indicator	COMPLIANCE_IND	CHARACTER (3)		
Compliance Date	COMPLIANCE_DATE	DATE		
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		
Modified Date	MODIFIED_DATE	DATE		

## 3.15 Monitor Collocation Periods

### 3.15.1 Description

The Monitor Collocation Periods view defines the periods of time during which a monitor pair were collocated for the purpose of collecting precision data. A Monitor Collocation Periods record is uniquely identified by the combination of monitor and the date collocation began. Its parent is the Monitors view.

### 3.15.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Collocation Begin Date	CLOC_BEGIN_DATE	DATE	√	√
Status Indicator	STATUS_IND	CHARACTER (1)	√	
Primary Sampler Indicator	PRI_MONITOR_IND	CHARACTER (1)	√	
Distance from Primary Sampler	CLOC_DIST	NUMBER (8.2)		
Collocation End Date	CLOC_END_DATE	DATE		
Primary Sampler Monitor ID	PRIMARY_MONITOR_ID	CHARACTER (20)		
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		
Modified Date	MODIFIED_DATE	DATE		

## 3.16 Monitor Protocols

### 3.16.1 Description

The Monitor Protocols view contains the protocols by which sample data for a monitor are collected. A Monitor Protocols record is uniquely identified by the combination of monitor, protocols, and alternate method detectable limit (MDL). Its parents are the Monitors and Protocols views; its child views are Raw Data, Composite Data, Summary Protocols, Precision Summary Protocols, and Accuracy Summary Protocols.

### 3.16.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Monitor Protocol ID	MP_ID	NUMBER (4.0)	√	√
Status Indicator	STATUS_IND	CHARACTER (1)	√	
Duration Code	DURATION_CODE	CHARACTER (8)	√	
Reported Unit	UNIT	CHARACTER (3)	√	
Method Code	METHODOLOGY_CODE	CHARACTER (8)	√	
Collection Frequency Code	COLL_FREQ_CODE	CHARACTER (8)		
Composite Type	COMP_TYPE	CHARACTER (10)		
Alternate Method Detectable Limit (MDL)	ALT_MDL	NUMBER (5.5)		
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		
Modified Date	MODIFIED_DATE	DATE		

## AQS Pollutant Data Views

### 3.17 Composite Data

#### 3.17.1 Description

The Composite Data view contains the concentrations of air pollutants as measured by air monitoring equipment from composite air samples. In the composite sampling technique, two or more air samples obtained at different times are combined and analyzed as one sample. This yields something of an average concentration for the time period during which the individual samples were collected. A Composite Data record is uniquely identified by the combination of monitor, year, and composite period. Its parent is the Monitor Protocols view; its child view is Composite Qualifier Details.

#### 3.17.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Composite Year	COMP_YEAR	NUMBER (4.0)	√	√
Composite Period	PERIOD	NUMBER (2.0)	√	√
Status Indicator	STATUS_IND	CHARACTER (1)	√	√
Monitor Protocol ID	MP_ID	NUMBER (4.0)	√	
Number of Samples	SAMPLE_CNT	NUMBER (10.0)		
Reported Sample Value	REPORTED_SAMPLE_VALUE	NUMBER (5.5)		
Reported Scale	REPORTED_SCALE	NUMBER (1.0)		
Standard Sample Value	STD_SAMPLE_VALUE	NUMBER (5.5)		
Standard Scale	SUMMARY_SCALE	NUMBER (1.0)		
Standard Unit	UN_UNIT_STD	CHARACTER (3)		
Uncertainty Value	UNCERTAINTY_VALUE	NUMBER (6.5)		
Primary Qualifier Code	QUALIFIER_CODE	CHARACTER (8)		
Primary Qualifier Type	QUALIFIER_TYPE	CHARACTER (8)		
Half MDL Substitution Indicator	LT_HALF_MDL_IND	CHARACTER (1)		
EPA Region Concurrence Indicator	EPA_CONCURRENCE_IND	CHARACTER (1)		
Exclusion Indicator	EXCLUSION_IND	CHARACTER (1)		
Exclusion Date	EXCLUSION_DATE	DATE		
Freeze Indicator	FREEZE_IND	CHARACTER (3)		
Action Indicator	ACTION_IND	CHARACTER (1)		
Session Screening Group	SCREENING_GROUP_NUM	NUMBER (12.0)		
Session User	ORACLE_USER_ID	CHARACTER (40)		
Session Date/Time	SESSION_DATE	DATE		

## 3.18 Composite Qualifier Details

### 3.18.1 Description

The Composite Qualifier Details view contains qualification information about the composite sample. Types of qualification are: exceptional event, natural events, and quality assurance. A Composite Qualifier Details record is uniquely identified by the combination of monitor, year, composite period and qualifier. Its parent is the Composite Data view.

### 3.18.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Composite Year	COMP_YEAR	NUMBER (4.0)	√	√
Composite Period	PERIOD	NUMBER (2.0)	√	√
Status Indicator	STATUS_IND	CHARACTER (1)	√	√
Qualifier Code	QUALIFIER_CODE	CHARACTER (8)	√	√

## 3.19 Raw Data

### 3.19.1 Description

The Raw Data view contains the concentrations of various air pollutants as measured by air monitoring equipment throughout the U.S. The values may result from equipment that monitors continuously, or monitors that require manual intervention to collect the data, e.g., a monitor that draw air through a filter would require the removal and weighting of the filter to determine the amount of particulate matter in the sampled air. A Raw Data record is uniquely identified by the combination of monitor and date/time. Its parent is the Monitor Protocols view; its child view is Raw Qualifier Details.

### 3.19.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Sample Date/Time	SAMPLING_BEGIN_DATETIME	DATE	√	√
Status Indicator	STATUS_IND	CHARACTER (1)	√	√
Monitor Protocol ID	MP_ID	NUMBER (4.0)	√	
Reported Sample Value	REPORTED_SAMPLE_VALUE	NUMBER (5.5)		
Reported Scale	REPORTED_SCALE	NUMBER (1.0)		
Standard Sample Value	STD_SAMPLE_VALUE	NUMBER (5.5)		
Standard Scale	SUMMARY_SCALE	NUMBER (1.0)		
Standard Unit	UN_UNIT_STD	CHARACTER (3)		
Uncertainty Value	UNCERTAINTY_VALUE	NUMBER (6.5)		
Primary Qualifier Code	QUALIFIER_CODE	CHARACTER (8)		
Primary Qualifier Type	QUALIFIER_TYPE	CHARACTER (8)		
Half MDL Substitution Indicator	LT_HALF_MDL_IND	CHARACTER (1)		
EPA Region Concurrence Indicator	EPA_CONCURRENCE_IND	CHARACTER (1)		
Exclusion Indicator	EXCLUSION_IND	CHARACTER (1)		
Exclusion Date	EXCLUSION_DATE	DATE		
Freeze Indicator	FREEZE_IND	CHARACTER (3)		
Action Indicator	ACTION_IND	CHARACTER (1)		
Session Screening Group	SCREENING_GROUP_NUM	NUMBER (12.0)		
Session User	ORACLE_USER_ID	CHARACTER (40)		
Session Date/Time	SESSION_DATE	DATE		

## 3.20 Raw Qualifier Details

### 3.20.1 Description

The Raw Qualifier Details view contains qualification information about the raw sample. Types of qualification are: null data, exceptional event, natural events, and quality assurance. A Raw Qualifier Details record is uniquely identified by the combination of monitor, sample date/time, and qualifier. Its parent is the Raw Data view.

### 3.20.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Sample Date/Time	SAMPLING_BEGIN_DATETIME	DATE	√	√
Status Indicator	STATUS_IND	CHARACTER (1)	√	√
Qualifier Code	QUALIFIER_CODE	CHARACTER (8)	√	√

## 3.21 Precision Data

### 3.21.1 Description

The Precision Data view contains the precision check results for monitors for a pollutant. Precision checks are determined by performing repeated measurements of ambient-level “calibration” gases at two-week intervals for continuous analyzers, or by obtaining duplicate results from collocated samplers for manual methods. Precision Data record is uniquely identified by the combination of monitor and date. Its parent is the Monitor Protocols view.

### 3.21.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Precision Date	PREC_DATE	DATE	√	√
Precision ID	PREC_ID	NUMBER (2.0)	√	√
Monitor Protocol ID	MP_ID	NUMBER (4.0)	√	
Precision Class	AUDIT_CLASS	CHARACTER (20)	√	
Precision Scale	PREC_SCALE	NUMBER (1.0)	√	
Precision Sample ID	PREC_SAMPLE_ID	CHARACTER (10)		
Actual Value	ACTUAL_VALUE	NUMBER (5.5)	√	
Actual Method	ACTUAL_METHODODOLOGY_CODE	CHARACTER (8)		
Indicated Value	INDICATED_VALUE	NUMBER (5.5)	√	
Indicated Method	INDICATED_METHODODOLOGY_CODE	CHARACTER (8)	√	
Percent Difference	PERCENT_DIFF	NUMBER	√	
Collocated POC	COLLOCATED_POC	NUMBER (2.0)		
Agency Performing FRM Audit	AGENCY_CODE	CHARACTER (8)		
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		
Modified Date	MODIFIED_DATE	DATE		

## 3.22 Accuracy Data

### 3.22.1 Description

The Accuracy Data view contains the accuracy audits results for monitors for a pollutant. Accuracy assessments indicate the agreement between an analyzer measurement and a known audit standard concentration for continuous analyzers, or the agreement between an observed value and a known or reference value for manual methods. Accuracy Data record is uniquely identified by the combination of monitor, audit class, accuracy type, date and Accuracy Audit ID Number. Its parent is the Monitor Protocols view.

### 3.22.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Accuracy Date	ACC_DATE	DATE	√	√
Audit Class	AUDIT_CLASS	CHARACTER (20)	√	√
Accuracy Type	ACC_TYPE	CHARACTER (20)	√	√
Accuracy Audit ID Number	ACC_AUDIT_ID	NUMBER (2.0)	√	√
Audit Level	LEVEL_NUM	NUMBER (2.0)	√	√
Monitor Protocol ID	MP_ID	NUMBER (4.0)	√	
Local Primary Standard	LOCAL_PRI_STD	CHARACTER (30)	√	
Audit Type	AUDIT_TYPE	CHARACTER (20)	√	
Year Represented	YEAR_REPRESENTED	NUMBER (4.0)	√	
Quarter Represented	QTR_REPRESENTED	NUMBER (1.0)	√	
Audit Sample ID	AUDIT_SAMPLE_ID	CHARACTER (10)		
Expiration Date	EXPIRATION_DATE	DATE		
Audit Scheduled	AUDIT_SCHEDULED	DATE		
Zero Span	ZERO_SPAN_VALUE	NUMBER (5.5)		
Zero Span Scale	ZERO_SPAN_SCALE	NUMBER (1.0)		
Audit Scale	ACC_AUDIT_SCALE	NUMBER (1.0)	√	
Actual Value	ACTUAL_VALUE	NUMBER (5.5)	√	
Indicated Value	INDICATED_VALUE	NUMBER (5.5)	√	
Percent Difference	PERCENT_DIFF	NUMBER	√	
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		
Modified Date	MODIFIED_DATE	DATE		

### 3.23 Blank Data

#### 3.23.1 Description

The Blank Data view contains information about field and trip blank assessments. A Blank Data record is uniquely identified by the combination of monitor, date/time, and blank type. Its parent is the Monitor Protocols view.

#### 3.23.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Blank Date/Time	BLANK_DATETIME	DATE	√	√
Blank Type	BLANK_TYPE	CHARACTER (20)	√	√
Monitor Protocol ID	MP_ID	NUMBER (4.0)	√	
Blank Value	BLANK_VALUE	NUMBER (5.5)		
Blank Scale	BLANK_SCALE	NUMBER (1.0)		
Uncertainty Value	UNCERTAINTY_VALUE	NUMBER (6.5)		
Primary Qualifier Code	QUALIFIER_CODE	CHARACTER (8)		
Primary Qualifier Type	QUALIFIER_TYPE	CHARACTER (8)		

## 3.24 Blank Qualifier Details

### 3.24.1 Description

The Blank Qualifier Details view contains qualification information about the blanks sample. Types of qualification are: exceptional event, natural events, and quality assurance. A Blank Qualifier Detail record is uniquely identified by the combination of monitor, sample date/time, and qualifier. Its parent is the Blank Data view.

### 3.24.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Blank Date/Time	BLANK_DATETIME	DATE	√	√
Blank Type	BLANK_TYPE	CHARACTER (20)	√	√
Qualifier Code	QUALIFIER_CODE	CHARACTER (8)	√	√

## Comments View

### 3.25 Comments

#### 3.25.1 Description

The Comments view contains free text narratives for sites, and monitors. Its parent is either the Sites or Monitors views.

#### 3.25.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
State-County-Site	SITE_ID	CHARACTER (11)		
Monitor ID	MONITOR_ID	CHARACTER (20)		
Sequence Number	SEQUENCE_NUM	NUMBER (12.0)	√	
Text	COMMENT_TEXT	CHARACTER (255)	√	

## AQS Pollutant Summary Views

### 3.26 NAAQS Averages

#### 3.26.1 Description

The NAAQS Averages view contains system-calculated averages of hourly sample data for some criteria pollutants. The averages are used for evaluation of compliance with National Ambient Air Quality Standards (NAAQS). The averages cover multi-hour periods  $\leq 24$ . A NAAQS Averages record is uniquely identified by the combination of monitor, date/time duration, and exceptional data type. Its parent is the Monitors view.

#### 3.26.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
NAAQS Date/Time	NAAQS_AVG_DATETIME	DATE	√	√
Duration Code	DURATION_CODE	CHARACTER (8)	√	√
Exceptional Data Type ID	EDT_ID	NUMBER (10.0)	√	√
Arithmetic Mean	NAAQS_ARITH_MEAN	NUMBER (5.5)	√	

## 3.27 Daily Summaries

### 3.27.1 Description

The Daily Summaries view contains calculated values of concentrations of monitor samples, which have been summarized for a day, sampling duration, and exceptional data indicator combination. A Daily Summaries record is uniquely identified by the combination of monitor, date duration, and exceptional data type. Its parent is the Monitors view.

### 3.27.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Collection Date	DAILY_COLL_DATE	DATE	√	√
Duration Code	DURATION_CODE	CHARACTER (8)	√	√
Exceptional Data Type ID	EDT_ID	NUMBER (10.0)	√	√
Arithmetic Mean	DAILY_ARITH_MEAN	FLOAT		
Count of Observations	DAILY_OBS_CNT	NUMBER (10.0)		
Percent of Observations	DAILY_OBS_PCT	NUMBER (6.4)		
Summary Criteria Indicator	DAILY_CRITERIA_IND	CHARACTER (1)		
Maximum Value	DAILY_MAX_SAMPLE_VALUE	NUMBER (5.5)		
Hour of Maximum Value	DAILY_MAX_COLL_HOUR	NUMBER (2.0)		
Count of Primary Exceedances	VALUES_GT_PRI_LEVEL_DS	NUMBER (10.0)		
Count of Secondary Exceedances	VALUES_GT_SEC_LEVEL_DS	NUMBER (10.0)		
Count of Non-Overlapping Exceedances	NON_OVERLAPPING_AVG_GT_STD	NUMBER (10.0)		
Daily Rank	DAILY_RANKING_NUM	NUMBER (3.0)		

## 3.28 Quarterly Summaries

### 3.28.1 Description

The Quarterly Summaries view contains calculated values of concentrations of monitor samples, which have been summarized for a quarter, sampling duration, and exceptional data indicator combination. A Quarterly Summaries record is uniquely identified by the combination of monitor, year, quarter, duration, and exceptional data type. Its parent is the Monitors view.

### 3.28.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Summary Year	QTR_YEAR	NUMBER (4.0)	√	√
Summary Quarter	QTR_NUM	NUMBER (1.0)	√	√
Duration Code	DURATION_CODE	CHARACTER (8)	√	√
Exceptional Data Type ID	EDT_ID	NUMBER (10.0)	√	√
Arithmetic Mean	QTR_ARITH_MEAN	FLOAT		
Count of Observations	QTR_OBS_CNT	NUMBER (10.0)		
Percent of Observations	QTR_OBS_PCT	NUMBER (6.4)		
Summary Criteria Indicator	QTR_CRITERIA_IND	CHARACTER (1)		

## 3.29 Annual Summaries

### 3.29.1 Description

The Annual Summaries view contains calculated values of concentrations of monitor samples, which have been summarized for a year, sampling duration, and exceptional data indicator combination. An Annual Summaries record is uniquely identified by the combination of monitor, year, duration, and exceptional data type. Its parent is the Monitors view; its child view is Summary Maximums, Summary Percentiles, and Summary Protocols.

### 3.29.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Summary Year	ANNUAL_SUMMARY_YEAR	NUMBER (4.0)	√	√
Duration Code	DURATION_CODE	CHARACTER (8)	√	√
Exceptional Data Type ID	EDT_ID	NUMBER (10.0)	√	√
Arithmetic Mean	ANNUAL_ARITH_MEAN	NUMBER (5.5)		
Arithmetic Standard Deviation	ANNUAL_ARITH_STDDV	NUMBER (5.5)		
Geometric Mean	ANNUAL_GEOM_MEAN	NUMBER (5.5)		
Geometric Standard Deviation	ANNUAL_GEOM_STDDV	NUMBER (5.5)		
Weighted Arithmetic Mean	WEIGHTED_ARITH_MEAN	NUMBER (5.5)		
Summary Criteria Indicator	ANNUAL_CRITERIA_IND	CHARACTER (1)		
Direct Entry Indicator	ANNUAL_DIRECT_ENTRY_IND	CHARACTER (3)		
Certification Indicator	CERT_IND	CHARACTER (3)		
Count of Observations	ANNUAL_OBS_CNT	NUMBER (10.0)		
Percent of Observations	ANNUAL_OBS_PCT	NUMBER (6.4)		
Count of Null Data Values	NULL_DATA_OBS_CNT	NUMBER (10.0)		
Count of Exceptional Events	EXCEPTIONAL_DATA_CNT	NUMBER (10.0)		
Count of Primary Exceedances	VALUES_GT_PRI_LEVEL	NUMBER (10.0)		
Count of Secondary Exceedances	VALUES_GT_SEC_LEVEL	NUMBER (10.0)		
Count of Days Greater Than Alert Level	DAYS_GT_ALERT_LEVEL	NUMBER (10.0)		
Count of Half-MDL Substitutions	OBS_CNT_LT_HALF_MDL	NUMBER (10.0)		
Count of Non-Overlapping Exceedances	NON_OVERLAPPING_AVG_GT_STD	NUMBER (10.0)		
Count of Methods	SUMMARY_METHOD_CNT	NUMBER (12.0)		

<b>Name</b>	<b>Database Field</b>	<b>Type (Length)</b>	<b>Req'd</b>	<b>Key</b>
Count of Valid Days	VALID_DAY_CNT	NUMBER (3.0)		
Count of Required Days	REQ_MONITORING_CNT	NUMBER (3.0)		
Count of Missing Days Assumed Less Than Standard	MISSING_DAYS_ASSUMED_LT_STD	NUMBER (3.0)		
Estimate of Days Greater Than Standard	EST_DAYS_GT_STD	NUMBER (3.2)		
Minimum Collection Frequency	COLL_FREQ_CODE	CHARACTER (8)		
Minimum Sample Value	MIN_SAMPLE_VALUE	NUMBER (5.5)		
Created User	CREATED_USER	CHARACTER (40)		
Created Date	CREATED_DATE	DATE		
Modified User	MODIFIED_USER	CHARACTER (40)		
Modified Date	MODIFIED_DATE	DATE		

### 3.30 Summary Maximums

#### 3.30.1 Description

The Summary Maximums view contains information about a predetermined number of the highest values that were recorded by a monitor within a year. A Summary Maximums record is uniquely identified by the combination of monitor, year, duration, exceptional data type, maximum type, and level. Its parent is the Annual Summaries view.

#### 3.30.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Summary Year	ANNUAL_SUMMARY_YEAR	NUMBER (4.0)	√	√
Duration Code	DURATION_CODE	CHARACTER (8)	√	√
Exceptional Data Type ID	EDT_ID	NUMBER (10.0)	√	√
Maximum Indicator	MAX_IND	NUMBER (3.0)	√	√
Maximum Level	MAX_LEVEL	NUMBER (4.0)	√	√
Maximum Value	MAX_SAMPLE_VALUE	NUMBER (5.5)	√	
Maximum Value Date/Time	MAX_COLL_DATETIME	DATE	√	

### 3.31 Summary Percentiles

#### 3.31.1 Description

The Summary Percentiles view contains information about predetermined percentiles that were calculated for a monitor within a year. A Summary Percentiles record is uniquely identified by the combination of monitor, year, duration, exceptional data type, and percentile. Its parent is the Annual Summaries view.

#### 3.31.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Summary Year	ANNUAL_SUMMARY_YEAR	NUMBER (4.0)	√	√
Duration Code	DURATION_CODE	CHARACTER (8)	√	√
Exceptional Data Type ID	EDT_ID	NUMBER (10.0)	√	√
Percentile	PERCENTILE_NUM	NUMBER	√	√
Percentile Sample Value	PERCENTILE_SAMPLE_VALUE	NUMBER	√	

## 3.32 Summary Protocols

### 3.32.1 Description

The Summary Protocols view documents the protocols that were used for a monitor within a year. A Summary Protocols record is uniquely identified by the combination of monitor, year, duration, exceptional data type, and monitor protocol. Its parent is the Annual Summaries view.

### 3.32.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Summary Year	ANNUAL_SUMMARY_YEAR	NUMBER (4.0)	√	√
Duration Code	DURATION_CODE	CHARACTER (8)	√	√
Exceptional Data Type ID	EDT_ID	NUMBER (10.0)	√	√
Monitor Protocol ID	MP_ID	NUMBER (4.0)	√	√

### 3.33 Monitor Precision Summaries

#### 3.33.1 Description

The Monitor Precision Summaries view contains information about yearly and quarterly precision statistics for monitors for a pollutant by a reporting organization. Types of information that are calculated are: number of checks, mean, standard deviation, and number of valid collocated sample pairs. A Monitor Precision Summaries record is uniquely identified by the combination of monitor, reporting organization, class and time period. Its parent is the Monitor Agency Roles view; its child view is Precision Summary Protocols.

#### 3.33.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Reporting Organization	AGENCY_CODE	CHARACTER (8)	√	√
Precision Class	AUDIT_CLASS	CHARACTER (20)	√	√
Summary Year	PREC_YEAR	NUMBER (4.0)	√	√
Time Period	TIME_PERIOD	CHARACTER (2)	√	√
Recording Mode	RECORDING_MODE	CHARACTER (30)	√	
Mean	PREC_MEAN	NUMBER (6.4)	√	
Standard Deviation	PREC_STDDV	NUMBER (6.4)	√	
Count of Precision Checks	PREC_CHECK_CNT	NUMBER (3.0)	√	
Count of Valid Collocated Data Pairs	VALID_CLOC_DATA_PAIR_CNT	NUMBER (3.0)	√	

### 3.34 Precision Summary Protocols

#### 3.34.1 Description

The Precision Summary Protocols view contains information about the protocols used to assess precision checks for a monitor for a year by a reporting organization. A Precision Summary Protocols record is uniquely identified by the combination of monitor, reporting organization, class, time period, and monitor protocols. Its parent is the Monitor Precision Summaries view.

#### 3.34.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Reporting Organization	AGENCY_CODE	CHARACTER (8)	√	√
Precision Class	AUDIT_CLASS	CHARACTER (20)	√	√
Summary Year	PREC_YEAR	NUMBER (4.0)	√	√
Time Period	TIME_PERIOD	CHARACTER (2)	√	√
Monitor Protocol ID	MP_ID	NUMBER (4.0)	√	√

### 3.35 Reporting Organization Precision Summaries

#### 3.35.1 Description

The Reporting Organization Precision Summaries view contains information about yearly and quarterly precision statistics for reporting organizations and pollutants. Types of information that are calculated are: number of checks, mean, standard deviation, number of valid collocated sample pairs, and lower and upper probability limits or confidence intervals. A Reporting Organization Precision Summaries record is uniquely identified by the combination of reporting organization, parameter, class and time period. Its parent is the Agencies and Parameters views.

#### 3.35.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Reporting Organization	AGENCY_CODE	CHARACTER (8)	√	√
Parameter	PARAMETER_CODE	CHARACTER (5)	√	√
Precision Class	AUDIT_CLASS	CHARACTER (20)	√	√
Summary Year	PREC_YEAR	NUMBER (4.0)	√	√
Time Period	TIME_PERIOD	CHARACTER (2)	√	√
Recording Mode	RECORDING_MODE	CHARACTER (30)	√	
Mean	PREC_MEAN	NUMBER (6.4)	√	
Standard Deviation	PREC_STDDV	NUMBER (6.4)		
Count of Precision Checks	PREC_CHECK_CNT	NUMBER (3.0)	√	
Count of Valid Collocated Data Pairs	VALID_CLOC_DATA_PAIR_CNT	NUMBER (3.0)		
Count of Analyzers	ANALYZER_CNT	NUMBER (12.0)	√	
Count of Collocated Sites	CLOC_SITE_CNT	NUMBER (12.0)	√	
Lower Probability/Confidence Limit	PREC_LOWER_PROB_LIMIT	NUMBER (6.4)	√	
Upper Probability/Confidence Limit	PREC_UPPER_PROB_LIMIT	NUMBER (6.4)	√	

### 3.36 Monitor Accuracy Summaries

#### 3.36.1 Description

The Monitor Accuracy Summaries view contains information about yearly and quarterly accuracy statistics for reporting organizations and pollutants. Types of information that are calculated are: number of audits. A Monitor Accuracy Summaries record is uniquely identified by the combination of monitor, reporting organization, class, type, and time period. Its parent is the Agencies Roles view; its child view is Accuracy Summary Protocols.

#### 3.36.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Reporting Organization	AGENCY_CODE	CHARACTER (8)	√	√
Recording Mode	RECORDING_MODE	CHARACTER (30)	√	√
Audit Class	AUDIT_CLASS	CHARACTER (20)	√	√
Accuracy Type	ACC_TYPE	CHARACTER (20)	√	√
Summary Year	ACC_SUMMARY_YEAR	NUMBER (4)	√	√
Time Period	TIME_PERIOD	CHARACTER (2)	√	√
Local Primary Standard	LOCAL_PRI_STD	CHARACTER (30)	√	
Audit Type	AUDIT_TYPE	CHARACTER (30)	√	
Audit Level	LEVEL_NUM	NUMBER (2)	√	
Count of Accuracy Audits	AUDIT_CNT	NUMBER (12)	√	
Mean	ACC_MEAN	NUMBER (5.5)		

### 3.37 Accuracy Summary Protocols

#### 3.37.1 Description

The Accuracy Summary Protocols view documents the protocols used to collect accuracy audits for a monitor for a year or quarter. An Accuracy Summary Protocols record is uniquely identified by the combination of monitor, reporting organization, class, type, time period, and monitor protocol. Its parent is the Monitor Accuracy Summaries view.

#### 3.37.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Monitor ID	MONITOR_ID	CHARACTER (20)	√	√
Reporting Organization	AGENCY_CODE	CHARACTER (8)	√	√
Recording Mode	RECORDING_MODE	CHARACTER (30)	√	√
Audit Class	AUDIT_CLASS	CHARACTER (20)	√	√
Accuracy Type	ACC_TYPE	CHARACTER (20)	√	√
Summary Year	ACC_SUMMARY_YEAR	NUMBER (4)	√	√
Time Period	TIME_PERIOD	CHARACTER (2)	√	√
Monitor Protocol ID	MP_ID	NUMBER (4)	√	√

### 3.38 Reporting Organization Accuracy Summaries

#### 3.38.1 Description

The Reporting Organization Accuracy Summaries view contains information about yearly and quarterly accuracy statistics for reporting organizations and pollutants. Types of information that are calculated are: number of audits, mean, standard deviation, and lower and upper probability limits or confidence intervals. A Reporting Organization Accuracy Summaries record is uniquely identified by the combination of reporting organization, parameter, recording mode, class, type, and time period. Its parent is the Agencies and Parameters views.

#### 3.38.2 Elements

Name	Database Field	Type (Length)	Req'd	Key
Reporting Organization	AGENCY_CODE	CHARACTER (8)	√	√
Parameter	PARAMETER_CODE	CHARACTER (5)	√	√
Recording Mode	RECORDING_MODE	CHARACTER (30)	√	√
Audit Class	AUDIT_CLASS	CHARACTER (20)	√	√
Accuracy Type	ACC_TYPE	CHARACTER (20)	√	√
Summary Year	ACC_SUMMARY_YEAR	NUMBER (4)	√	√
Time Period	TIME_PERIOD	CHARACTER (2)	√	√
Local Primary Standard	LOCAL_PRI_STD	CHARACTER (30)	√	
Audit Type	AUDIT_TYPE	CHARACTER (30)	√	
Audit Level	LEVEL_NUM	NUMBER (2)	√	
Count of Accuracy Audits	AUDIT_CNT	NUMBER (12)	√	
Mean	ACC_MEAN	NUMBER (5.5)		
Standard Deviation	ACC_STDDV	NUMBER (7.5)		
Lower Probability/Confidence Limit	ACC_LOWER_PROB_LIMIT	NUMBER (6.4)		
Upper Probability/Confidence Limit	ACC_UPPER_PROB_LIMIT	NUMBER (6.4)		

## **4 AQS Data Table Fields**

### **4.1 Accuracy Audit ID Number**

#### **4.1.1 Description**

A sequentially assigned number used to identify a unique measurement data group for a monitor on a specific date.

#### **4.1.2 Source**

User-specified, via Accuracy Data (RA) Transaction, or AQS Maintain Accuracy (L62).

#### **4.1.3 Attributes**

Type: Number

Length: 2.0

Required: Yes

#### **4.1.4 Uses**

Accuracy Data

## **4.2 Accuracy Date**

### **4.2.1 Description**

The calendar date for which the accuracy audit information pertains.

### **4.2.2 Source**

User-specified, via Accuracy Data (RA) Transaction, or AQS Maintain Accuracy (L62).

### **4.2.3 Attributes**

Type: Date

Length: Not Applicable

Required: Yes

### **4.2.4 Uses**

Accuracy Data

### **4.2.5 Value Assignment**

The field is only assigned a date, with the time portion defaulting to 00:00:00.

## **4.3 Accuracy Type**

### **4.3.1 Description**

A description of the type of accuracy test performed.

### **4.3.2 Source**

User-specified, via Accuracy Data (RA) Transaction, or AQS Maintain Accuracy (L62).

### **4.3.3 Attributes**

Type: Character

Length: 20

Required: Yes

### **4.3.4 Uses**

Accuracy Data

Monitor Accuracy Summaries

Accuracy Summary Protocols

Reporting Organization Accuracy Summaries

### **4.3.5 Value Assignment**

#### **4.3.5.1 Accuracy Data**

Must be an entry in the *Accuracy Types* view.

#### **4.3.5.2 Monitor & Reporting Organization Accuracy Summaries**

Represents the *Accuracy Type* value assigned to all *Accuracy Data* records that are aggregated in the summary record.

## **4.4 Action Date**

### **4.4.1 Description**

The date that administrative action was taken by EPA headquarters.

### **4.4.2 Source**

User-specified, via AQS Maintain Monitor (L2).

### **4.4.3 Attributes**

Type: Date

Length: Not Applicable

Required: No

### **4.4.4 Uses**

Monitor Type Assignments

### **4.4.5 Value Assignment**

Applies only to the assignment of the monitor types National Air Monitoring Station (NAMS) or Photochemical Assessment Monitoring System (PAMS).

## **4.5 Action Indicator**

### **4.5.1 Description**

Indicates the data manipulation action to be performed by the transaction.

### **4.5.2 Source**

User-specified, via Raw Data (RD) or Composite Data (RC) Transactions, or AQS Maintain Raw Data (L54) or Maintain Composite Data (L51).

### **4.5.3 Attributes**

Type: Character

Length: 1

Required: No

### **4.5.4 Uses**

Raw Data

Composite Data

### **4.5.5 Value Assignment**

#### **4.5.5.1 Pre-Production Status**

A value is required when the *Raw Data* or *Composite Data* record is at pre-production status, (i.e., the *Status Indicator* value is “R” or “S”). The valid values are:

I - Insert

U - Update

D - Delete

#### **4.5.5.2 Production Status**

The field must be null when the *Raw Data* or *Composite Data* record is at production status, (i.e., the *Status Indicator* value is “P”).

## **4.6 Action Reason**

### **4.6.1 Description**

A code indicating the reason for negative actions by EPA headquarters with regard to a monitor.

### **4.6.2 Source**

User-specified, via AQS Maintain Monitor (L2).

### **4.6.3 Attributes**

Type: Character

Length: 8

Required: No

### **4.6.4 Uses**

Monitor Type Assignments

### **4.6.5 Value Assignment**

Must be an entry in the *Action Reasons* view.

## **4.7 Action Type**

### **4.7.1 Description**

The type of administrative action taken by EPA headquarters.

### **4.7.2 Source**

User-specified, via AQS Maintain Monitor (L2).

### **4.7.3 Attributes**

Type: Character

Length: 8

Required: No

### **4.7.4 Uses**

Monitor Type Assignments

### **4.7.5 Value Assignment**

Must be an entry in the *Action Types* view.

## **4.8 Actual Method**

### **4.8.1 Description**

Identifies the particular method for collecting and analyzing a precision check value.

#### **4.8.1.1 Analytical**

The method used to collect and analyze the known gaseous concentration with which the sampler is challenged.

#### **4.8.1.2 Flow**

The method used to collect and analyze the known flow rate with which the sampler is challenged.

#### **4.8.1.3 Collocated**

The method used to collect and analyze the ambient air sample from the primary sampler.

### **4.8.2 Source**

User-specified, via Precision Data (RP) Transaction, or AQS Maintain Precision (L61).

### **4.8.3 Attributes**

Type: Character

Length: 3

Required: Yes

### **4.8.4 Uses**

Precision Data

### **4.8.5 Value Assignment**

The *Actual Method* value, in combination with the *Parameter* value, must exist in the *Sampling Methodologies* view.

## **4.9 Actual Value**

### **4.9.1 Description**

#### **4.9.1.1 Analytical**

The standard gaseous concentration value with which the sampler is challenged.

#### **4.9.1.2 Flow**

The standard flow rate value with which the monitor is challenged.

#### **4.9.1.3 Collocated**

The concentration produced from the primary sampler, (i.e., routine monitor), in a collocated sampler pair.

### **4.9.2 Source**

For a precision check, user-specified, via Precision Data (RP) Transaction, or AQS Maintain Precision (L61). For an accuracy audit, user-specified, via Accuracy Data (RA) Transaction, or AQS Maintain Accuracy (L62).

### **4.9.3 Attributes**

Type: Number

Length: 5.5

Required: Yes

### **4.9.4 Uses**

Precision Data

Accuracy Data

### **4.9.5 Value Assignment**

#### **4.9.5.1 Analytical Check**

The *Actual Value* for a precision check must not exceed the maximum value allowed for the *Parameter*.

#### **4.9.5.2 Analytical Audit**

The *Actual Value* for an analytical audit must fall within the range of standard concentrations specified for the *Parameter* at the given *Audit Level*.

#### **4.9.5.3 Collocated Check**

The *Actual Value* for a precision check must not exceed the maximum value allowed for the *Parameter*.

## **4.10 Agency Code**

### **4.10.1 Description**

An agency responsible for performing a role for the monitor.

### **4.10.2 Source**

User-specified, via Basic Site Information (AA) transaction or AQS Maintain Site (L1).

User-specified, via Monitor Agency Roles (MD) Transaction, or AQS Maintain Monitor (L2).

### **4.10.3 Attributes**

Type: Character

Length: 8

Required: Yes

### **4.10.4 Uses**

Monitor Agency Roles

### **4.10.5 Value Assignment**

Must be an entry on the *Agencies* view, and, in combination with *State Code*, on the *State Agencies* view.

## **4.11 Agency Performing FRM Audit**

### **4.11.1 Description**

The agency submitting precision data resulting from a Federal Reference Method (FRM) audit of the manual method for Particulate Matter (PM)-2.5 monitoring. This agency is commonly an Environmental Protection Agency (EPA) laboratory or independent laboratory.

### **4.11.2 Source**

User-specified, via Precision Data (RP) Transaction, or AQS Maintain Precision (L61).

### **4.11.3 Attributes**

Type: Character  
Length: 8  
Required: No

### **4.11.4 Uses**

Precision Data

### **4.11.5 Value Assignment**

The *Agency Performing FRM Audit* value must exist on the *Agencies* view.

## **4.12 Agency Role Begin Date**

### **4.12.1 Description**

The date on which the agency began performance of the role for the monitor. For the role of reporting, it also indicates the date that precision and accuracy data applies to the agency as reporting organization.

### **4.12.2 Source**

User-specified, via Monitor Agency Roles (MD) Transaction, or AQS Maintain Monitor (L2).

### **4.12.3 Attributes**

Type: Date

Length: Not Applicable

Required: No

### **4.12.4 Uses**

Monitor Agency Roles

### **4.12.5 Value Assignment**

#### **4.12.5.1 Reporting Role**

*Agency Role Begin Date* is required when the *Agency Role Name* is "REPORTING".

#### **4.12.5.2 Other Roles**

*Agency Role Begin Date* is optional when the *Agency Role Name* is other than "REPORTING".

## **4.13 Agency Role End Date**

### **4.13.1 Description**

The date on which the agency ended a period of performance of the role for the monitor. For the role of reporting, it also indicates the last date that precision and accuracy data applies to the agency as reporting organization.

### **4.13.2 Source**

User-specified, via Monitor Agency Roles (MD) Transaction, or AQS Maintain Monitor (L2).

### **4.13.3 Attributes**

Type: Date

Length: Not Applicable

Required: No

### **4.13.4 Uses**

Monitor Agency Roles

## **4.14 Agency Role Name**

### **4.14.1 Description**

Classification of an agency's role in regard to the monitor.

### **4.14.2 Source**

User-specified, via Monitor Agency Roles (MD) Transaction, or AQS Maintain Monitor (L2).

### **4.14.3 Attributes**

Type: Character

Length: 20

Required: Yes

### **4.14.4 Uses**

Monitor Agency Roles

### **4.14.5 Value Assignment**

Must be "REPORTING", "COLLECTING", or "ANALYZING".

## **4.15 *Alternate Method Detectable Limit***

### **4.15.1 Description**

The method detectable limit (MDL) defined for the monitor by the reporting agency, which supercedes the EPA-defined method detectable limit for the designated methodology.

### **4.15.2 Source**

User-specified, via the Raw Data (RD), Composite Data (RC), or Monitor Protocols (MK) Transactions (), or via Maintain Monitor (L2).

### **4.15.3 Attributes**

Type: Number  
Length: 5.5  
Required: No

### **4.15.4 Uses**

Monitor Protocols

## **4.16 Applicable NAAQS Indicator**

### **4.16.1 Description**

An indication of whether the data from a monitor in a monitor planning area should be compared to either the short-term or annual National Ambient Air Quality Standards (NAAQS), or both.

### **4.16.2 Source**

User-specified, via Basic Monitor Information (MA) Transaction, or AQS Maintain Monitor (L2).

### **4.16.3 Attributes**

Type: Character

Length: 3

Required: No

### **4.16.4 Uses**

Monitor Pollutant Areas

### **4.16.5 Value Assignment**

The valid values are:

S – Short-Term

A – Annual

B - Both

#### **4.16.5.1 Monitor Pollutant Areas**

*Applicable NAAQS Indicator* is required for Monitor Planning Areas (PM2.5).

#### **4.16.5.2 Default**

*Applicable NAAQS Indicator* is not allowed for other than Monitor Planning Areas (PM2.5).

## **4.17 AQCR**

### **4.17.1 Description**

Specifies in which of the 247 Air Quality Control Regions (AQCRs) the monitoring site is located.

### **4.17.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.17.3 Attributes**

Type: Character

Length: 8

Required: Yes

### **4.17.4 Uses**

Sites

### **4.17.5 Value Assignment**

Must be a value on the *AQCR* view, and, in combination with the *State Code* and *County Code*, on the *AQCR Counties* view.

## 4.18 Arithmetic Mean (Annual)

### 4.18.1 Description

The measure of central tendency obtained from the sum of the observed pollutant data values or National Ambient Air Quality Standards (NAAQS) averages in the yearly data set divided by the number of values that comprise the sum for the yearly data set.

### 4.18.2 Source

System-generated during the Post process, or user-specified via the Annual Summaries (RS) Transaction () or Maintain Annual Summaries (L9).

### 4.18.3 Attributes

Type: Number

Length: 5.5

Required: No

### 4.18.4 Uses

Annual Summaries

### 4.18.5 Value Assignment

#### 4.18.5.1 1-Hour & 8-Hour Ozone

$$u = \frac{\sum_{j=1}^n d_j}{v}$$

where:

$u$  = mean,

$d$  = valid 1-hour or 8-hour daily maximum occurring in effective monitoring season,

$v$  = *Count of Valid Days*.

#### 4.18.5.2 Non-Ozone National Ambient Air Quality Standards (NAAQS) Durations

Not valued.

#### 4.18.5.3 Default

$$u = \frac{\sum_{j=1}^n s_j}{n}$$

where:

$u$  = mean,

$s$  = sample value,

$n$  = *Count of Observations (Annual)*.

## 4.19 Arithmetic Mean (Daily)

### 4.19.1 Description

The measure of central tendency obtained from the sum of the observed pollutant data values or National Ambient Air Quality Standards (NAAQS) averages in the daily data set divided by the number of values that comprise the sum for the daily data set.

### 4.19.2 Source

System-generated during the Post process.

### 4.19.3 Attributes

Type: Number

Length: 5.5

Required: No

### 4.19.4 Uses

Daily Summaries

### 4.19.5 Value Assignment

#### 4.19.5.1 Hourly & NAAQS Durations

$$u = \frac{\sum_{j=1}^n S_j}{n}$$

where:

$u$  = mean,

$s$  = sample value or valid *NAAQS Arithmetic Mean*,

$n$  = *Count of Observations (Daily)*.

#### 4.19.5.2 Daily Criteria

$$u = S$$

where:

$u$  = mean,

$s$  = sample value.

## **4.20 Arithmetic Mean (NAAQS)**

### **4.20.1 Description**

The measure of central tendency obtained from the sum of the observed pollutant data values in National Ambient Air Quality Standards (NAAQS) hourly interval divided by the number of values that comprise the sum for the NAAQS hourly interval.

### **4.20.2 Source**

System-generated during the Post process.

### **4.20.3 Attributes**

Type: Number  
Length: 5.5  
Required: Yes

### **4.20.4 Uses**

NAAQS Averages

## 4.20.5 Value Assignment

### 4.20.5.1 8-Hour Ozone

Where there are between 6 and 8 hourly samples in an 8-hour period, (i.e. at least 75% of the required data is present):

$$u = \frac{\sum_{j=1}^n s_j}{n}$$

where:

$u$  = arithmetic mean,  
 $s$  = sample value,  
 $n$  = number of samples.

Where there are less than 6 samples in an 8-hour period, (i.e. at least 75% of the required data is not present):

$$u = \frac{\left( \sum_{j=1}^n s_j + ((8-n)*h) \right)}{8}$$

where:

$u$  = arithmetic mean,  
 $s$  = 1-hour sample value,  
 $h$  = ½ method detectable limit (MDL) substitution,  
 $n$  = number of 1-hour sample values,

and  $u$  exceeds the standard.

#### 4.20.5.2 8-Hour Carbon Monoxide

Where there are between 6 and 8 samples in an 8-hour period, (i.e. at least 75% of the required data is present):

$$u = \frac{\sum_{j=1}^n S_j}{n}$$

where:

$u$  = arithmetic mean,  
 $s$  = sample value,  
 $n$  = number of sample values.

#### 4.20.5.3 3-Hour Sulfur Dioxide

When there are 3 hourly samples in a 3-hour block:

$$u = \frac{\sum_{j=1}^3 S_j}{3}$$

where:

$u$  = arithmetic mean,  
 $s$  = sample value.

When there less than 3 hourly samples in a 3-hour block:

$$u = \frac{\sum_{j=1}^n S_j}{3}$$

where:

$u$  = arithmetic mean,  
 $s$  = 1-hour sample value,  
 $n$  = number of 1-hour sample values,

and  $u$  exceeds the secondary standard.

#### 4.20.5.4 24-Hour Sulfur Dioxide

When there are between 18 and 24 hourly samples in an 24-hour period, (i.e. at least 75% of the required data is present):

$$u = \frac{\sum_{j=1}^n S_j}{n}$$

where:

$u$  = arithmetic mean,  
 $s$  = sample value,  
 $n$  = number of samples.

When there are less than 18 hourly samples in a 24-hour period:

$$u = \frac{\sum_{j=1}^n S_j}{24}$$

where:

$u$  = arithmetic mean,  
 $s$  = sample value,  
 $n$  = number of samples,

and  $u$  exceeds the primary standard.

#### 4.20.5.5 24-Hour PM10

Where there are between 18 and 24 hourly samples in an 24-hour period, (i.e. at least 75% of the required data is present):

$$u = \frac{\sum_{j=1}^n S_j}{n}$$

where:

$u$  = arithmetic mean,  
 $s$  = 1-hour sample value,  
 $n$  = number of 1-hour sample values.

Where there are less than 18 hourly samples in a 24-hour period:

$$u = \frac{\sum_{j=1}^n S_j}{24}$$

where:

$u$  = arithmetic mean,  
 $s$  = 1-hour sample value,  
 $n$  = number of 1-hour sample values,

and  $u$ , when rounded to -1 places, (i.e., to the nearest 10), exceeds the primary standard.

#### 4.20.5.6 24-Hour PM2.5

Where there are between 18 and 24 hourly samples in an 24-hour period, (i.e. at least 75% of the required data is present):

$$u = \frac{\sum_{j=1}^n S_j}{n}$$

where:

$u$  = arithmetic mean,  
 $s$  = 1-hour sample value,  
 $n$  = number of 1-hour sample values.

Where there are less than 18 hourly samples in a 24-hour period:

$$u = \frac{\sum_{j=1}^n S_j}{24}$$

where:

$u$  = arithmetic mean,  
 $s$  = 1-hour sample value,  
 $n$  = number of 1-hour sample values,

and  $u$ , when rounded to zero places, i.e., to the nearest integer, exceeds the primary standard.

## 4.21 Arithmetic Mean (Quarterly)

### 4.21.1 Description

The measure of central tendency obtained from the sum of the observed pollutant data values in the quarterly data set divided by the number of values that comprise the sum for the quarterly data set.

### 4.21.2 Source

System-generated during the Post process.

### 4.21.3 Attributes

Type: Number

Length: 5.5

Required: No

### 4.21.4 Uses

Quarterly Summaries

### 4.21.5 Value Assignment

$$u = \frac{\sum_{j=1}^n S_j}{n}$$

where:

$u$  = mean,

$s$  = sample value or valid *NAAQS Arithmetic Mean*,

$n$  = *Count of Observations (Quarterly)*.

## 4.22 Arithmetic Standard Deviation

### 4.22.1 Description

The measure of the dispersion about the central tendency of a pollutant that is the square root of the arithmetic mean of the squares of the variation of each data value from the arithmetic mean of the data values of the yearly data set.

### 4.22.2 Source

System-generated during the Post process, or user-specified via the Annual Summaries (RS) Transaction () or Maintain Annual Summaries (L9).

### 4.22.3 Attributes

Type: Number  
Length: 5.5  
Required: No

### 4.22.4 Uses

Annual Summaries

### 4.22.5 Value Assignment

#### 4.22.5.1 1-Hour & 8-Hour Ozone

$$\sigma = \sqrt{\frac{\left( \left( v * \sum_{j=1}^v d_j^2 \right) - \left( \sum_{j=1}^v d_j \right)^2 \right)}{v * (v - 1)}}$$

where:

$\sigma$  = standard deviation,  
 $d$  = valid 1-hour or 8-hour daily maximum occurring in effective monitoring season,  
 $v$  = *Count of Valid Days*,

and  $v > 1$ .

If the number of valid days is exactly 1, then the standard deviation is assigned a value of 0.

#### 4.22.5.2 Non-Ozone National Ambient Air Quality Standards (NAAQS) Durations

No value assigned.

#### 4.22.5.3 Default

$$\sigma = \sqrt{\frac{\left( \left( n * \sum_{j=1}^n s_j^2 \right) - \left( \sum_{j=1}^n s_j \right)^2 \right)}{(n * (n - 1))}}$$

where:

$\sigma$  = standard deviation,  
 $s$  = hourly sample value,  
 $n$  = *Count of Observations (Annual)*,

and  $n > 1$ .

If the number of samples is exactly 1, then the standard deviation is assigned a value of 0.

## **4.23 Audit Class**

### **4.23.1 Description**

Description of the class of audit taken at the monitor.

### **4.23.2 Source**

User-specified via Accuracy Data (RA) Transaction, or AQS Maintain Accuracy (L62), or system-generated via Accuracy Data (RA) Transaction, or AQS Maintain Accuracy (L62).

### **4.23.3 Attributes**

Type: Character

Length: 20

Required: Yes

### **4.23.4 Uses**

Accuracy Data

Monitor Accuracy Summaries

Accuracy Summary Protocols

Reporting Organization Accuracy Summaries

### **4.23.5 Value Assignment**

#### **4.23.5.1 Accuracy Data**

Must be a value on the *Audit Classes* view.

#### **4.23.5.2 Monitor & Reporting Organization Accuracy Summaries**

Represents the *Audit Class* value assigned to all *Accuracy Data* records that are aggregated in the summary record.

## **4.24 Audit Level**

### **4.24.1 Description**

A number identifying a regulatory-specified concentration range for the Parameter, or, when there is no level defined, a sequential identifier use to differentiate multiple value pairs in an accuracy audit.

### **4.24.2 Source**

Derived from User-specified via the Accuracy Data (RA) Transaction, or AQS Maintain Accuracy (L62).

### **4.24.3 Attributes**

Type: Date

Length: Not Applicable

Required: Yes

### **4.24.4 Uses**

Accuracy Data

### **4.24.5 Value Assignment**

The values of *Audit Level* are derived from *Level n* fields on the RA transaction, with *Other Level* being assigned a value of 5. From Maintain Accuracy (L62), the levels are explicitly entered by the user.

## **4.25 Audit Sample ID**

### **4.25.1 Description**

The unique identity (ID) number of the reference sample used to challenge the instrument.

### **4.25.2 Source**

User-specified via the Accuracy Data (RA) Transaction, or AQS Maintain Accuracy (L62).

### **4.25.3 Attributes**

Type: Character

Length: 10

Required: No

### **4.25.4 Uses**

Accuracy Data

## **4.26 Audit Scale**

### **4.26.1 Description**

The number of digits to the right of the decimal point of the accuracy audit.

### **4.26.2 Source**

Derived from User-specified via the Accuracy Data (RA) Transaction, or AQS Maintain Accuracy (L62).

### **4.26.3 Attributes**

Type: Number

Length: 1

Required: Yes

### **4.26.4 Uses**

Accuracy Data

### **4.26.5 Value Assignment**

The value is derived from the number of digits to the right of the decimal point for the corresponding audit value pair in the Accuracy Data (RA) Transaction, or on the L62 form.

## **4.27 Audit Scheduled**

### **4.27.1 Description**

The initial date that the performance audit was scheduled.

### **4.27.2 Source**

User-specified via the Accuracy Data (RA) Transaction, or AQS Maintain Accuracy (L62).

### **4.27.3 Attributes**

Type: Date

Length: Not Applicable

Required: No

### **4.27.4 Uses**

Accuracy Data

## **4.28 Audit Type**

### **4.28.1 Description**

Description of who performed the audit and how the audit standard was certified.

### **4.28.2 Source**

User-specified via the Accuracy Data (RA) Transaction, or AQS Maintain Accuracy (L62).

### **4.28.3 Attributes**

Type: Character

Length: 20

Required: Yes

### **4.28.4 Uses**

Accuracy Data

Monitor Accuracy Summaries

Reporting Organization Accuracy Summaries

### **4.28.5 Value Assignment**

#### **4.28.5.1 Accuracy Data**

Must be a value on the *Audit Types* view.

#### **4.28.5.2 Monitor & Reporting Organization Accuracy Summaries**

The most frequently assigned audit type for accuracy audits aggregated in the summary record.

## **4.29 Beam Length**

### **4.29.1 Description**

The length of the beam projected between the transmitter and the receiver at the site, in meters.

### **4.29.2 Source**

User-specified via the Open Paths (AC) Transaction, or AQS Maintain Site (L1).

### **4.29.3 Attributes**

Type: Number

Length: 8.2

Required: No

### **4.29.4 Uses**

Open Paths

## **4.30 Blank Date**

### **4.30.1 Description**

The calendar date at which the blank data was recorded.

### **4.30.2 Source**

User-specified via the Blank Data (RB) Transaction, or AQS Maintain Blank Data (L53).

### **4.30.3 Attributes**

Type: Date

Length: 8

Required: Yes

### **4.30.4 Uses**

Forms and Reports

### **4.30.5 Value Assignment**

On input: Coupled with Blank Time to set Blank Date/Time

On output: Extracted from Blank Date/Time

## **4.31 Blank Date/Time**

### **4.31.1 Description**

The calendar date and time at which the blank data was recorded.

### **4.31.2 Source**

User-specified via the Blank Data (RB) Transaction, or AQS Maintain Blank Data (L53).

### **4.31.3 Attributes**

Type: Date

Length: Not Applicable

Required: Yes

### **4.31.4 Uses**

Blank Data

Blank Qualifier Details

## **4.32 Blank Scale**

### **4.32.1 Description**

The number of digits to the right of the decimal point of the blank value.

### **4.32.2 Source**

User-specified via the Blank Data (RB) Transaction, or AQS Maintain Blank Data (L53).

### **4.32.3 Attributes**

Type: Number

Length: 1

Required: Yes

### **4.32.4 Uses**

Blank Data

### **4.32.5 Value Assignment**

The value is derived from the number of digits to the right of the decimal point in the Blank Data (RB) Transaction, or on the L53 form.

## **4.33 Blank Time**

### **4.33.1 Description**

The 24 hour clock time at which the blank data was recorded.

### **4.33.2 Source**

User-specified via the Blank Data (RB) Transaction, or AQS Maintain Blank Data (L53).

### **4.33.3 Attributes**

Type: Date  
Length: 5  
Required: Yes

### **4.33.4 Uses**

Forms and Reports

### **4.33.5 Value Assignment**

On input: Coupled with Blank Time to set Blank Date/Time  
On output: Extracted from Blank Date/Time

Blank Type

#### **4.33.6 Description**

The type of blank data being recorded.

#### **4.33.7 Source**

User-specified via Blank Data (RB) Transaction, or AQS Maintain Blank Data (L53).

#### **4.33.8 Attributes**

Type: Character

Length: 20

Required: Yes

#### **4.33.9 Uses**

Blank Data

Blank Qualifier Details

#### **4.33.10 Value Assignment**

Must be a value on the *Blank Types* view, (i.e., “TRIP” or “FIELD”).

## **4.34 Blank Value**

### **4.34.1 Description**

The reported blank value.

### **4.34.2 Source**

User-specified via Blank Data (RB) Transaction, or AQS Maintain Blank Data (L53).

### **4.34.3 Attributes**

Type: Number

Length: 5.5

Required: Yes

### **4.34.4 Uses**

Blank Data

## **4.35 Block**

### **4.35.1 Description**

The U.S. Census Bureau block within which the site is located.

### **4.35.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.35.3 Attributes**

Type: Character

Length: 4

Required: No

### **4.35.4 Uses**

Sites

### **4.35.5 Value Assignment**

In combination with *State Code*, *County Code*, *Census Tract*, and *Block Group*, must be a value on the *Blocks* view.

## **4.36 Block Group**

### **4.36.1 Description**

The U.S. Census Bureau block group within which the site is located.

### **4.36.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.36.3 Attributes**

Type: Character

Length: 1

Required: No

### **4.36.4 Uses**

Sites

### **4.36.5 Value Assignment**

In combination with *State Code*, *County Code*, and *Census Tract*, must be a value on the *Block Groups* view.

## **4.37 Census Tract**

### **4.37.1 Description**

The U.S. Census Bureau census tract/block numbering area within which the site is located.

### **4.37.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.37.3 Attributes**

Type: Character

Length: 6

Required: No

### **4.37.4 Uses**

Sites

### **4.37.5 Value Assignment**

In combination with *State Code* and *County Code*, must be a value on the *Census Tracts* view.

## **4.38 Certification Indicator**

### **4.38.1 Description**

An indication that the accuracy of the information on the annual summary record has been certified by the owner.

### **4.38.2 Source**

User-specified via the Certification (J) form.

### **4.38.3 Attributes**

Type: Character

Length: 3

Required: No

### **4.38.4 Uses**

Annual Summaries

### **4.38.5 Value Assignment**

The only valid value is “Y”.

## **4.39 City Code**

### **4.39.1 Description**

The city within whose legal boundaries the monitoring site is located.

### **4.39.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.39.3 Attributes**

Type: Character

Length: 5

Required: Yes

### **4.39.4 Uses**

Sites

### **4.39.5 Value Assignment**

In combination with *State Code*, must be a value on the *Cities* table, and with both *State Code* and *County Code*, a value on the *County Cities* view.

## **4.40 Class I Area**

### **4.40.1 Description**

The Class One Area within which the site is located. A Class One Area is a geographic area recognized by EPA as being of the highest environmental quality and requiring maximum protection.

### **4.40.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.40.3 Attributes**

Type: Character  
Length: 8  
Required: No

### **4.40.4 Uses**

Sites

### **4.40.5 Value Assignment**

Must be a value on the *Class One Areas* view.

## **4.41 CMSA Represented**

### **4.41.1 Description**

The Consolidated Metropolitan Statistical Area (CMSA) from which the concentrations originated, not the location of the monitor.

### **4.41.2 Source**

User-specified via the Monitoring Objective Information (ME) Transaction, or AQS Maintain Monitor (L2).

### **4.41.3 Attributes**

Type: Character  
Length: 8  
Required: No

### **4.41.4 Uses**

Monitor Objectives

### **4.41.5 Value Assignment**

Must have a value if neither *MSA Represented* nor *Urban Area Represented* is valued. Conversely, may not have a value if either *MSA Represented* or *Urban Area Represented* is valued. If valued, that value must exist on the *CMSAs* view.

## **4.42 Collection Date**

### **4.42.1 Description**

The date for which sample data is summarized.

### **4.42.2 Source**

System-generated as part of the Post process.

### **4.42.3 Attributes**

Type: Date

Length: Not Applicable

Required: Yes

### **4.42.4 Uses**

Daily Summaries

## **4.43 Collection Frequency Code**

### **4.43.1 Description**

The frequency, according to which sample observations are to be made, specified as the amount of time that elapses between observations. Indicates how often 24-hour samples are taken, e.g., daily, every third day, stratified random, etc.

### **4.43.2 Source**

User-specified via the Monitor Protocol (MK) or Raw Data (RD) Transaction, or AQS Maintain Monitor (L2).

### **4.43.3 Attributes**

Type: Character

Length: 8

Required: No

### **4.43.4 Uses**

Monitor Protocols

### **4.43.5 Value Assignment**

The value must be on the *Collection Frequencies* view, and, in conjunction with *Duration Code*, *Parameter*, *Method Code*, *Unit*, and *Composite Type*, on the *Protocols* view.

## **4.44 Collocated POC**

### **4.44.1 Description**

The Parameter Occurrence Code (POC) of the duplicate sampler. Only applies to collocated data where the duplicate value is a recorded daily raw data point.

### **4.44.2 Source**

User-specified via the Precision Data (RP) Transaction, or AQS Maintain Precision Data (L61).

### **4.44.3 Attributes**

Type: Number  
Length: 2  
Required: No

### **4.44.4 Uses**

Precision Data

### **4.44.5 Value Assignment**

In conjunction with *State Code*, *County Code*, *Site ID*, and *Parameter*, the value must exist on the *Monitors* view.

## **4.45 Collocation Begin Date**

### **4.45.1 Description**

The beginning date of the time period during which a collocated monitor pair recorded precision and accuracy data. Used to determine data completeness.

### **4.45.2 Source**

User-specified via the Monitor Protocol (MJ) Transaction, or AQS Maintain Monitor (L2).

### **4.45.3 Attributes**

Type: Date

Length: Not Applicable

Required: Yes

### **4.45.4 Uses**

Monitor Collocation Periods

## **4.46 Collocation End Date**

### **4.46.1 Description**

The ending date of the time period during which a collocated monitor pair recorded precision and accuracy data. Used to determine data completeness.

### **4.46.2 Source**

User-specified via the Monitor Protocol (MJ) Transaction, or AQS Maintain Monitor (L2).

### **4.46.3 Attributes**

Type: Date

Length: Not Applicable

Required: Yes

### **4.46.4 Uses**

Monitor Collocation Periods

## **4.47 Comment Text**

### **4.47.1 Description**

A free-form narrative to be used in anyway the user desires, but generally to explain or further describe the related item, i.e., site, monitor, or sample.

### **4.47.2 Source**

User-specified, via Maintain Site (L1), Maintain Monitor (L2), Maintain Raw Data (L54), or Maintain Composite Data (L51).

### **4.47.3 Attributes**

Type: Character

Length: 255

Required: Yes

### **4.47.4 Uses**

Comments

## **4.48 Community Monitoring Zone**

### **4.48.1 Description**

A sequential number assigned to an optional averaging area with an established, defined boundary within a monitor planning area that has relatively uniform concentration of annual PM-2.5. Community monitoring zones do not cross geographical lines.

### **4.48.2 Source**

User-specified via the Basic Monitor Information (MA) Transaction, or AQS Maintain Monitor (L2).

### **4.48.3 Attributes**

Type: Number  
Length: 4.0  
Required: No

### **4.48.4 Uses**

Monitor Pollutant Areas

### **4.48.5 Value Assignment**

#### **4.48.5.1 Monitor Planning Areas**

May be assigned a value when the *Pollutant Area Type* value is not Monitor Planning Area.

#### **4.48.5.2 Default**

May not be assigned a value when the *Pollutant Area Type* value is not Monitor Planning Area.

## **4.49 Compliance Date**

### **4.49.1 Description**

The date on which the current status of the monitor's compliance with the regulation was achieved.

### **4.49.2 Source**

User-specified via the Monitor Regulatory Compliance (MI) Transaction, or AQS Maintain Monitor (L2).

### **4.49.3 Attributes**

Type: Date

Length: Not Applicable

Required: No

### **4.49.4 Uses**

Monitor Regulatory Compliances

### **4.49.5 Assignment**

## **4.50 Compliance Indicator**

### **4.50.1 Description**

The compliance status of a monitor with respect to an EPA regulation.

### **4.50.2 Source**

User-specified via the Monitor Regulatory Compliance (MI) Transaction, or AQS Maintain Monitor (L2).

### **4.50.3 Attributes**

Type: Character

Length: 3

Required: Yes

### **4.50.4 Uses**

Monitor Regulatory Compliances

### **4.50.5 Value Assignment**

Regulation Code	Valid Values
ST	Y, N
RM	Y, N
FC	Y, N
QA	Y, N, C
SC	Y, N, W

## **4.51 Composite Period**

### **4.51.1 Description**

Indicates the time period within the year to which the observation applies. It is expressed in units that may be inferred from the Composite Type.

### **4.51.2 Source**

User-specified via the Composite Data (RC) Transaction, or AQS Maintain Composite Data (L51).

### **4.51.3 Attributes**

Type: Number  
Length: 2.0  
Required: Yes

### **4.51.4 Uses**

Composite Data  
Composite Qualifier Details

## **4.52 Composite Type**

### **4.52.1 Description**

The time period over which samples are composited, or the frequency of submitting composite samples.

### **4.52.2 Source**

User-specified via the Monitor Protocol (MK) or Composite Data (RC) Transactions, or AQS Maintain Monitor (L2).

### **4.52.3 Attributes**

Type: Character

Length: 10

Required: No

### **4.52.4 Uses**

Composite Type

### **4.52.5 Value Assignment**

The value must be on the Composite Types view, and, in conjunction with Duration Code, Parameter, Method Code, Unit, and Collection Frequency Code, on the Protocols view.

## **4.53 Composite Year**

### **4.53.1 Description**

The calendar year for which the observation was reported.

### **4.53.2 Source**

User-specified via the Composite Data (RC) Transaction, or AQS Maintain Composite Data (L51).

### **4.53.3 Attributes**

Type: Number

Length: 4.0

Required: Yes

### **4.53.4 Uses**

Composite Data

Composite Qualifier Details

## **4.54 Congressional District**

### **4.54.1 Description**

The Congressional district within which the site is located.

### **4.54.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.54.3 Attributes**

Type: Number

Length: 12.0

Required: No

### **4.54.4 Uses**

Sites

### **4.54.5 Value Assignment**

The value must exist on the *Congressional Districts* view.

## **4.55 Count of Accuracy Audits (Monitor Accuracy Summary)**

### **4.55.1 Description**

The number of accuracy audits recorded during the time period for the monitor.

### **4.55.2 Source**

System-generated via Accuracy Data (RA) Transaction, or Maintain Accuracy (L61).

### **4.55.3 Attributes**

Type: Number

Length: 12.0

Required: Yes

### **4.55.4 Uses**

Monitor Accuracy Summaries

## **4.56 Count of Accuracy Audits (Reporting Organization Accuracy Summary)**

### **4.56.1 Description**

The number of accuracy audits recorded during the time period.

### **4.56.2 Source**

System-generated via Accuracy Data (RA) Transaction, or Maintain Accuracy (L61).

### **4.56.3 Attributes**

Type: Number

Length: 12.0

Required: Yes

### **4.56.4 Uses**

Reporting Organization Accuracy Summaries

### **4.56.5 Value Assignment**

If either quarter in either half of the year has an *Audit Count* of 1, then the audits for both quarters will be counted and reported with the second quarter for the half (Q2 or Q4).

However, for the first quarter in the half (Q1 or Q3), the audits will still be counted and reported with that quarter.

## **4.57 Count of Analyzers**

### **4.57.1 Description**

The average number of approved analyzers in the network.

### **4.57.2 Source**

System-generated via Precision Data (RP) Transaction, or Maintain Precision (L62).

### **4.57.3 Attributes**

Type: Number

Length: 12.0

Required: Yes

### **4.57.4 Uses**

Reporting Organization Precision Summaries

### **4.57.5 Value Assignment**

#### **4.57.5.1 Gaseous or Flow**

The number of monitors for which checks were recorded during the time period.

#### **4.57.5.2 Collocated**

The number of collocated sampler pairs that recorded collocated value pairs during the time period, (i.e., the Count of Collocated Sites).

#### **4.57.5.3 Federal Reference Method (FRM) audits**

Assigned a default value of 0.

## **4.58 Count of Collocated Sites**

### **4.58.1 Description**

The average number of sites having collocated samplers.

### **4.58.2 Source**

System-generated via Precision Data (RP) Transaction, or Maintain Precision (L62).

### **4.58.3 Attributes**

Type: Number

Length: 12.0

Required: Yes

### **4.58.4 Uses**

Reporting Organization Precision Summaries

### **4.58.5 Value Assignment**

#### **4.58.5.1 Collocated**

The number of collocated sampler pairs that recorded collocated value pairs during the time period.

#### **4.58.5.2 Gaseous, Flow, or Federal Reference Method (FRM) Audits**

Assigned a default value of 0

## **4.59 Count of Exceptional Events**

### **4.59.1 Description**

The number of data points in the annual data set affected by events.

### **4.59.2 Source**

System-generated via the Post process, or user-generated via either the Annual Summaries (RS) Transaction or Maintain Annual Summaries (L7).

### **4.59.3 Attributes**

Type: Number

Length: 10.0

Required: Yes

### **4.59.4 Uses**

Annual Summaries

### **4.59.5 Value Assignment**

#### **4.59.5.1 Observed Durations**

A count of the *Raw Data* or *Composite Data* records for the monitor and year whose *Primary Qualifier Type* value is either “EX”, (for exceptional event qualifiers), or “NAT”, (for natural event qualifiers).

#### **4.59.5.2 National Ambient Air Quality Standards (NAAQS) Durations**

Not valued.

## **4.60 Count of Days Greater Than Alert Level**

### **4.60.1 Description**

The number of days within the year where the monitor had sample values that exceeded the alert level for the pollutant.

### **4.60.2 Source**

System-generated via the Post Process.

### **4.60.3 Attributes**

Type: Number

Length: 3.0

Required: No

### **4.60.4 Uses**

Annual Summaries

### **4.60.5 Value Assignment**

Comparisons to alert levels are based on sample values converted to the pollutant's standard unit.

#### **4.60.5.1 1-Hour Ozone**

The number of days where the hourly *Maximum Value (Daily)* is greater than 0.2 parts per million (ppm).

#### **4.60.5.2 8-Hour Carbon Monoxide**

The number of days where the 8-Hour *Maximum Value (Daily)* is greater than 15 ppm.

#### **4.60.5.3 Daily & 24-Hour Sulfur Dioxide**

The number of days where daily sample value or 24-hour block average is greater than 0.3 ppm.

#### **4.60.5.4 Annual Nitrogen Dioxide**

If the *Arithmetic Mean (Annual)* exceeds 0.6 ppm, then 1; otherwise, 0.

#### **4.60.5.5 Daily & 24 Hour PM10**

The number of days where either the daily sample value or 24-hour block average is greater than 350 micrograms per cubic meter – standard conditions ( $\mu\text{g}/\text{m}^3$  SC).

#### **4.60.5.6 Default**

Not valued.

## **4.61 Count of Half-MDL Substitutions**

### **4.61.1 Description**

The number of samples in the calendar year whose calculated standard value was less than the applicable method detectable limit (MDL), and for which ½ of that MDL was substituted for the calculated standard value.

### **4.61.2 Source**

System-generated as part of the Post process.

### **4.61.3 Attributes**

Type: Number  
Length: 10.0  
Required: No

### **4.61.4 Uses**

Annual Summaries

### **4.61.5 Value Assignment**

#### **4.61.5.1 Hourly PM2.5**

Not valued.

#### **4.61.5.2 National Ambient Air Quality Standards (NAAQS) Durations**

Not valued.

#### **4.61.5.3 Default**

The count of *Raw Data* or *Composite Data* records for the year that are flagged as having had half the MDL substituted (*Half MDL Substitution Indicator* = "Y") for the calculated *Standard Sample Value*, where the latter value is less than the MDL.

## **4.62 Count of Methods**

### **4.62.1 Description**

The number of methods used to collect samples for the monitor during the year.

### **4.62.2 Source**

System-generated via the Post process.

### **4.62.3 Attributes**

Type: Number

Length: 12.0

Required: No

### **4.62.4 Uses**

Annual Summaries

### **4.62.5 Value Assignment**

#### **4.62.5.1 Observed Durations**

Always valued.

#### **4.62.5.2 National Ambient Air Quality Standards (NAAQS) Durations**

Never valued.

## **4.63 Count of Missing Days Assumed Less Than Standard**

### **4.63.1 Description**

The number of invalid or missing days in the effective monitoring season whose daily maximums are assumed to be less than or equal to the standard.

### **4.63.2 Source**

System-generated via the Post process.

### **4.63.3 Attributes**

Type: Number

Length: 3.0

Required: No

### **4.63.4 Uses**

Annual Summaries

### **4.63.5 Value Assignment**

#### **4.63.5.1 1-Hour Ozone**

A missing or invalid day is assumed to be less than the standard when either of the following conditions exists:

- The daily maximums on the days immediately preceding, and immediately succeeding, the missing day were less than, or equal to, 75% of the standard.
- The number of valid samples for the day was less than 18, and the sum of the following is greater than, or equal, to 18, i.e., 75% of the possible values:
  - Number of valid samples;
  - Number of null samples that were both flagged as not likely to exceed the standard, and for which the Regional Office has indicated concurrence;
  - Number of omitted samples that were flagged with event qualifiers, and for which the Regional Office has indicated concurrence.

#### **4.63.5.2 8-Hour Ozone**

A missing or invalid day is assumed to be less than the standard for the following condition:

- The number of valid 8-hour arithmetic averages for the day was less than 18, and the sum of the following is greater than, or equal, to 18, i.e., 75% of the possible values:
  - Number of valid 8-hour arithmetic averages;
  - Number of missing 8-hour arithmetic averages that would be valid if excluded samples (null or event-qualified) were included, where those excluded samples have concurrence from the EPA Regional Office.

#### **4.63.5.3 Default**

Not valued.

## **4.64 Count of Non-Overlapping Exceedances (Annual)**

### **4.64.1 Description**

The number of primary exceedances with 8 or more hours between any other exceedances.

### **4.64.2 Source**

System-generated via the Post process.

### **4.64.3 Attributes**

Type: Number

Length: 10.0

Required: No

### **4.64.4 Uses**

Annual Summaries

### **4.64.5 Value Assignment**

#### **4.64.5.1 8-Hour Carbon Monoxide**

Always valued with an integer of 0 or greater.

#### **4.64.5.2 Default**

Not valued.

## **4.65 Count of Non-Overlapping Exceedances (Daily)**

### **4.65.1 Description**

The number of primary exceedances with 8 or more hours between any other exceedances.

### **4.65.2 Source**

System-generated via the Post process.

### **4.65.3 Attributes**

Type: Number

Length: 10.0

Required: No

### **4.65.4 Uses**

Daily Summaries

### **4.65.5 Value Assignment**

#### **4.65.5.1 8-Hour Carbon Monoxide**

Always valued with an integer of 0 or greater.

#### **4.65.5.2 Default**

Not valued.

## **4.66 Count of Null Data Values**

### **4.66.1 Description**

The number of null samples that occurred within the calendar year

### **4.66.2 Source**

System-generated during the Post process.

### **4.66.3 Attributes**

Type: Number

Length: 10.0

Required: No

### **4.66.4 Uses**

Annual Summaries

### **4.66.5 Value Assignment**

#### **4.66.5.1 Composite Data**

Not valued.

#### **4.66.5.2 National Ambient Air Quality Standards (NAAQS) Durations**

Not valued.

#### **4.66.5.3 Default**

The count of Raw Data records where the Primary Qualifier Type is “NULL”.

## **4.67 Count of Observations (Annual)**

### **4.67.1 Description**

The number of raw data values that are the basis for the summary values.

### **4.67.2 Source**

System-generated via the Post process, or user-generated via either the Annual Summaries (RS) Transaction or Maintain Annual Summaries (L7).

### **4.67.3 Attributes**

Type: Number

Length: 10.0

Required: No

### **4.67.4 Uses**

Annual Summaries

## **4.68 Count of Observations (Daily)**

### **4.68.1 Description**

The number of raw data values that are the basis for the summary values.

### **4.68.2 Source**

System-generated via the Post process.

### **4.68.3 Attributes**

Type: Number

Length: 10.0

Required: No

### **4.68.4 Uses**

Daily Summaries

## **4.69 Count of Observations (Quarterly)**

### **4.69.1 Description**

The number of raw data values that are the basis for the summary values.

### **4.69.2 Source**

System-generated via the Post process.

### **4.69.3 Attributes**

Type: Number

Length: 10.0

Required: No

### **4.69.4 Uses**

Quarterly Summaries

## **4.70 Count of Precision Checks (Monitor Precision Summary)**

### **4.70.1 Description**

The number of precision checks, (gaseous, flow, collocated, Federal Reference Method, i.e., FRM) recorded during the time period.

### **4.70.2 Source**

System-generated via Precision Data (RP) Transaction, or Maintain Precision (L62).

### **4.70.3 Attributes**

Type: Number

Length: 3.0

Required: No

### **4.70.4 Uses**

Monitor Precision Summaries

## **4.71 Count of Precision Checks (Reporting Organization Precision Summary)**

### **4.71.1 Description**

The number of precision checks, (gaseous, flow, collocated, Federal Reference Method, i.e., FRM) recorded during the time period.

### **4.71.2 Source**

System-generated via Precision Data (RP) Transaction, or Maintain Precision (L62).

### **4.71.3 Attributes**

Type: Number

Length: 12.0

Required: No

### **4.71.4 Uses**

Reporting Organization Precision Summaries

## **4.72 Count of Primary Exceedances (Annual)**

### **4.72.1 Description**

The number of exceedances of the primary standard during the year for the monitor.

### **4.72.2 Source**

System-generated via the Post process.

### **4.72.3 Attributes**

Type: Number

Length: 10.0

Required: No

### **4.72.4 Uses**

Annual Summaries

### **4.72.5 Value Assignment**

#### **4.72.5.1 1-Hour Ozone**

The number of days in the effective monitoring season when the *Maximum Value (Daily)* was greater than, or equal to, 0.125 parts per million (ppm).

#### **4.72.5.2 8-Hour Ozone**

The number of days in the effective monitoring season where the *Maximum Value (Daily)* was greater than, or equal to, 0.085 ppm.

#### **4.72.5.3 1-Hour Carbon Monoxide**

The number of samples in the year that were greater than, or equal to, 35.5 ppm.

#### **4.72.5.4 8-Hour Carbon Monoxide**

The number of 8-hour *Arithmetic Mean (NAAQS)* values in the year that were greater than, or equal to, 9.5 ppm.

#### **4.72.5.5 Daily & 24-Hour Sulfur Dioxide**

The number of daily samples, or 24-hour block *Arithmetic Mean (NAAQS)* values, in the year that were greater than, or equal to, 0.145 ppm.

#### **4.72.5.6 Daily & 24-Hour PM10**

The number of daily samples, or 24-hour block *Arithmetic Mean (NAAQS)* values, in the year that were greater than, or equal to, 155 micrograms per cubic meter – standard conditions ( $\mu\text{g}/\text{m}^3$  SC).

#### **4.72.5.7 Daily & 24-Hour PM2.5**

The number of daily samples, or 24-hour block *Arithmetic Mean (NAAQS)* values, in the year that were greater than, or equal to, 65 micrograms per cubic meter – local conditions ( $\mu\text{g}/\text{m}^3$  LC).

#### **4.72.5.8 Nitrogen Dioxide**

If the *Arithmetic Mean (Annual)* is greater than, or equal to, 0.053 ppm, then 1; otherwise, 0.

#### **4.72.5.9 Lead**

The number of *Arithmetic Mean (Quarterly)* values, that are greater than, or equal to, 1.55  $\mu\text{g}/\text{m}^3$  SC.

#### **4.72.5.10 Default**

Not valued

## **4.73 Count of Primary Exceedances (Daily)**

### **4.73.1 Description**

The number of exceedances of the primary standard during the 24-hour period for the monitor.

### **4.73.2 Source**

System-generated via the Post process.

### **4.73.3 Attributes**

Type: Number

Length: 10.0

Required: No

### **4.73.4 Uses**

Daily Summaries

### **4.73.5 Value Assignment**

#### **4.73.5.1 1-Hour Ozone**

The number of samples within the 24-hour period that were greater than, or equal to, 0.125 parts per million (ppm).

#### **4.73.5.2 8-Hour Ozone**

The number of 8-hour *Arithmetic Mean (NAAQS)* values, in the 24-hour period that were greater than, or equal to, 0.085 ppm.

#### **4.73.5.3 1-Hour Carbon Monoxide**

The number of samples in the 24-hour period that were greater than, or equal to, 35.5 ppm.

#### **4.73.5.4 8-Hour Carbon Monoxide**

The number of 8-hour *Arithmetic Mean (NAAQS)* values, in the 24-hour period that were greater than, or equal to, 9.5 ppm.

#### **4.73.5.5 Daily & 24-Hour Sulfur Dioxide**

The number of samples, or 24-hour block *Arithmetic Mean (NAAQS)* values, in the 24-hour period that were greater than, or equal to, 0.145 ppm, i.e., 0 or 1.

#### **4.73.5.6 Daily & 24-Hour PM10**

The number of daily samples, or 24-hour block *Arithmetic Mean (NAAQS)* values, in the 24-hour period that were greater than, or equal to, 155 micrograms per cubic meter – standard conditions ( $\mu\text{g}/\text{m}^3$  SC), i.e., 0 or 1.

#### **4.73.5.7 Daily & 24-Hour PM2.5**

The number of daily samples, or 24-hour block *Arithmetic Mean (NAAQS)* values, in the 24-hour period that were greater than, or equal to, 65 micrograms per cubic meter – local conditions ( $\mu\text{g}/\text{m}^3$  LC), i.e., 0 or 1.

#### **4.73.5.8 Default**

Not valued

## **4.74 Count of Required Days**

### **4.74.1 Description**

The number of required monitoring days during the year.

### **4.74.2 Source**

System-generated via the Post process.

### **4.74.3 Attributes**

Type: Number

Length: 3.0

Required: No

### **4.74.4 Uses**

Annual Summaries

### **4.74.5 Value Assignment**

#### **4.74.5.1 1-Hour & 8-Hour Ozone**

The number of active days within the effective monitoring season.

#### **4.74.5.2 Daily PM10 & PM2.5**

Scheduled days are the number of days within the year that were scheduled for sampling, as determined by the EPA-defined calendar for the required collection frequency, and which also fall within the period of operation, as defined by sampling periods.

Seasonal and random frequencies are sub-divided in monthly-required frequencies; otherwise, the required frequency applies to a defined period of time. A PM10 or PM2.5 monitor must have a defined collection frequency for each active day, by rule.

The reference point for the EPA calendar is January 4, 1956. For example, in the year 2003, the every 6<sup>th</sup> day calendar would comprise: 1/3/2003, 1/9/2003, 1/15/2003, etc., and the every 3<sup>rd</sup> day calendar would comprise: 1/3/2003, 1/6/2003, 1/9/2003, 1/12/2003, etc. For a monitor doing seasonal sampling, with every 6<sup>th</sup> day sampling in April and every 3<sup>rd</sup> day sampling in May, both months in 2003, the schedule would be as follows: 4/15/03, 4/21/03, 4/27/03, 5/3/03, 5/6/03, 5/9/03, etc.

#### **4.74.5.3 24-Hour PM10 & PM2.5**

The number of active days in the year.

#### **4.74.5.4 Default**

Not valued.

## **4.75 Count of Secondary Exceedances (Annual)**

### **4.75.1 Description**

The number of exceedances of the secondary standard during the year for the monitor.

### **4.75.2 Source**

System-generated via the Post process.

### **4.75.3 Attributes**

Type: Number

Length: 10.0

Required: No

### **4.75.4 Uses**

Annual Summaries

### **4.75.5 Value Assignment**

#### **4.75.5.1 1-Hour Ozone**

The number of days in the effective monitoring season when the *Maximum Value (Daily)* was greater than, or equal to, 0.125 parts per million (ppm).

#### **4.75.5.2 8-Hour Ozone**

The number of days in the effective monitoring season where the *Maximum Value (Daily)* was greater than, or equal to, 0.085 ppm.

#### **4.75.5.3 1-Hour Carbon Monoxide**

The number of samples in the year that were greater than, or equal to, 35.5 ppm.

#### **4.75.5.4 8-Hour Carbon Monoxide**

The number of 8-hour *Arithmetic Mean (NAAQS)* values in the year that were greater than, or equal to, 9.5 ppm.

#### **4.75.5.5 3-Hour Sulfur Dioxide**

The number of 3-hour *Arithmetic Mean (NAAQS)* values in the year that were greater than, or equal to, 0.55 ppm.

#### **4.75.5.6 Daily & 24-Hour PM10**

The number of daily samples, or 24-hour block *Arithmetic Mean (NAAQS)* values, in the year that were greater than, or equal to, 155 micrograms per cubic meter – standard conditions ( $\mu\text{g}/\text{m}^3$  SC).

#### **4.75.5.7 Daily & 24-Hour PM2.5**

The number of daily samples, or 24-hour block *Arithmetic Mean (NAAQS)* values, in the year that were greater than, or equal to, 65 micrograms per cubic meter – local conditions ( $\mu\text{g}/\text{m}^3$  LC).

**4.75.5.8 Nitrogen Dioxide**

If the *Arithmetic Mean (Annual)* is greater than, or equal to, the secondary standard of 0.053 ppm, then 1; otherwise, 0.

**4.75.5.9 Lead**

The number of *Arithmetic Mean (Quarterly)* values that were greater than, or equal to, 1.55  $\mu\text{g}/\text{m}^3$  SC.

**4.75.5.10 Default**

Not valued.

## **4.76 Count of Secondary Exceedances (Daily)**

### **4.76.1 Description**

The number of exceedances of the secondary standard during the 24-hour period for the monitor.

### **4.76.2 Source**

System-generated via the Post process.

### **4.76.3 Attributes**

Type: Number

Length: 10.0

Required: No

### **4.76.4 Uses**

Daily Summaries

### **4.76.5 Value Assignment**

#### **4.76.5.1 1-Hour Ozone**

The number of samples within the 24-hour period that were greater than, or equal to, 0.125 parts per million (ppm).

#### **4.76.5.2 8-Hour Ozone**

The number of 8-hour *Arithmetic Mean (NAAQS)* values in the 24-hour period that were greater than, or equal to, 0.085 ppm.

#### **4.76.5.3 1-Hour Carbon Monoxide**

The number of samples in the 24-hour period that were greater than, or equal to, 35.5 ppm.

#### **4.76.5.4 8-Hour Carbon Monoxide**

The number of 8-hour *Arithmetic Mean (NAAQS)* values in the 24-hour period that were greater than, or equal to, 9.5 ppm.

#### **4.76.5.5 3-Hour Sulfur Dioxide**

The number of 3-hour *Arithmetic Mean (NAAQS)* values in the 24-hour period that were greater than, or equal to, 0.55 ppm.

#### **4.76.5.6 Daily & 24-Hour PM10**

The number of daily samples, or 24-hour block *Arithmetic Mean (NAAQS)* values, in the 24-hour period that were greater than, or equal to, 155 micrograms per cubic meter – standard conditions ( $\mu\text{g}/\text{m}^3$  SC), i.e., 0 or 1.

#### **4.76.5.7 Daily & 24-Hour PM2.5**

The number of daily samples, or 24-hour block *Arithmetic Mean (NAAQS)* values, in the 24-hour period that were greater than, or equal to, 65  $\mu\text{g}/\text{m}^3$  LC, i.e., 0 or 1.

#### **4.76.5.8 Default**

Not valued

## 4.77 Count of Valid Collocated Data Pairs (Monitor Precision Summary)

### 4.77.1 Description

The number of valid collocated value pairs recorded during the time period.

### 4.77.2 Source

System-generated via Precision Data (RP) Transaction, or Maintain Precision (L62).

### 4.77.3 Attributes

Type: Number

Length: 3.0

Required: No

### 4.77.4 Uses

Monitor Precision Summaries

### 4.77.5 Value Assignment

#### 4.77.5.1 Collocated

A valid collocated value pair is one where both the primary and duplicate value exceeds the minimum collocated value defined for the parameter on the Parameters view. The minimum values for criteria pollutants are:

Parameter		Minimum
Code	Name	Value
11101	TSP	20 $\mu\text{g}/\text{m}^3$ SC
12128	Lead	.015 $\mu\text{g}/\text{m}^3$ SC
42401	SO2	.01717 ppm
42602	NO2	.01593 ppm
81102	PM10	20 $\mu\text{g}/\text{m}^3$ SC
88101	PM2.5	6 $\mu\text{g}/\text{m}^3$ LC

where:

ppm - parts per million

$\mu\text{g}/\text{m}^3$  SC - micrograms per cubic meter (standard conditions)

$\mu\text{g}/\text{m}^3$  LC - micrograms per cubic meter (local conditions).

If a minimum collocated value is not defined for the parameter, then the value pair is assumed valid.

#### **4.77.5.2 Default**

The field is not applicable to gaseous or flow checks, in which cases it is assigned a default value of 0.

## 4.78 Count of Valid Collocated Data Pairs (Reporting Organization Precision Summary)

### 4.78.1 Description

The number of valid collocated value pairs recorded during the time period.

### 4.78.2 Source

System-generated via Precision Data (RP) Transaction, or Maintain Precision (L62).

### 4.78.3 Attributes

Type: Number

Length: 12.0

Required: No

### 4.78.4 Uses

Reporting Organization Precision Summaries

### 4.78.5 Value Assignment

#### 4.78.5.1 Collocated

A valid collocated value pair is one where both the primary and duplicate value exceeds the minimum collocated value defined for the parameter on the Parameters view. The minimum values for criteria pollutants are:

Parameter		Minimum
Code	Name	Value
11101	TSP	20 $\mu\text{g}/\text{m}^3$ SC
12128	Lead	.015 $\mu\text{g}/\text{m}^3$ SC
42401	SO2	.01717 ppm
42602	NO2	.01593 ppm
81102	PM10	20 $\mu\text{g}/\text{m}^3$ SC
88101	PM2.5	6 $\mu\text{g}/\text{m}^3$ LC

where:

ppm - parts per million

$\mu\text{g}/\text{m}^3$  SC - micrograms per cubic meter (standard conditions)

$\mu\text{g}/\text{m}^3$  LC - micrograms per cubic meter (local conditions).

If a minimum collocated value is not defined for the parameter, then the value pair is assumed valid.

#### **4.78.5.2 Default**

The field is not applicable to gaseous or flow checks, in which cases it is assigned a default value of 0.

## **4.79 Count of Valid Days**

### **4.79.1 Description**

The number of required monitoring days where the monitoring criteria were met.

### **4.79.2 Source**

System-generated via the Post process.

### **4.79.3 Attributes**

Type: Number

Length: 3.0

Required: No

### **4.79.4 Uses**

Annual Summaries

### **4.79.5 Value Assignment**

#### **4.79.5.1 1-Hour & 8-Hour Ozone**

The number of active days within the effective monitoring season when minimum daily criteria were met, i.e., the *Summary Criteria Indicator (Daily)* value is “Y”.

#### **4.79.5.2 Daily PM10**

The number of valued strata in the year. (A valued stratum is where at least one observation is made on, or after, a scheduled day, but before the next scheduled day.)

#### **4.79.5.3 Daily PM2.5**

The sum of valued, scheduled sampling days, plus make-ups for missing scheduled days. A make-up day is a sample recorded in the same stratum as, or exactly seven days after, a missing scheduled sample. In both conditions, the make-up sample must occur within the same quarter as the missed sample. A maximum of five make-up samples are allowed per quarter. (References: EPA-454/R-99-008 Guideline on Data Handling Conventions for the PM NAAQS; Memorandum: February 3, 1999 Use of Make-Up Samples to Replace Scheduled PM Samples)

#### **4.79.5.4 24-Hour PM10 & PM2.5**

The number of valid 24-hour block *Arithmetic Mean (NAAQS)* values within the year.

#### **4.79.5.5 Default**

Not valued.

## **4.80 County Code**

### **4.80.1 Description**

A Federal Information Processing Standards (FIPS) code that identifies a county, or equivalent geo-political entity, such as parish or independent city. For foreign countries, it identifies the geo-political equivalent to U. S. states, such as Mexican states or Canadian provinces.

### **4.80.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.80.3 Attributes**

Type: Character

Length: 3

Required: Yes

### **4.80.4 Uses**

Sites

Tangent Roads

Open Paths

Monitors

### **4.80.5 Value Assignment**

The value must exist on the Counties view.

## **4.81 Created Date**

### **4.81.1 Description**

The date when the record was created.

### **4.81.2 Source**

System-generated via any of the AQS transactions, or any of the Maintain modules.

### **4.81.3 Attributes**

Type: Date

Length: Not applicable

Required: No

### **4.81.4 Uses**

Sites

Tangent Roads

Open Paths

Monitors

Monitor Pollutant Areas

Sample Periods

Monitor Type Assignments

Monitor Agency Roles

Monitor Objectives

Required Collection Frequencies

Sample Schedules

Monitor Tangent Roads

Probe Obstructions

Monitor Regulatory Compliances

Monitor Collocation Periods

Monitor Protocols

Accuracy Data

Precision Data

## **4.82 Created User**

### **4.82.1 Description**

The Oracle user ID of the user who created the record.

### **4.82.2 Source**

System-generated via any of the AQS transactions, or any of the Maintain modules.

### **4.82.3 Attributes**

Type: Character

Length: 40

Required: No

### **4.82.4 Uses**

Sites

Tangent Roads

Open Paths

Monitors

Monitor Pollutant Areas

Sample Periods

Monitor Type Assignments

Monitor Agency Roles

Monitor Objectives

Required Collection Frequencies

Sample Schedules

Monitor Tangent Roads

Probe Obstructions

Monitor Regulatory Compliances

Monitor Collocation Periods

Monitor Protocols

Accuracy Data

Precision Data

Annual Summaries

### **4.82.5 Value Assignment**

The value must exist on the *AIRS User Profiles* view.

## **4.83 Daily Rank**

### **4.83.1 Description**

The rank of the Maximum Value relative to all other maximum values for the year, with 1 signifying the maximum value for the entire year.

### **4.83.2 Source**

System-generated via the Post process.

### **4.83.3 Attributes**

Type: Number

Length: 3.0

Required: No

### **4.83.4 Uses**

Daily Summaries

### **4.83.5 Value Assignment**

Only computed for *Exceptional Data Type* values 0 and 2.

## **4.84 Date Sampling Began**

### **4.84.1 Description**

The date, on which a distinct period of operations, i.e., collection of air quality samples, began for the monitor.

### **4.84.2 Source**

User-specified via the Monitor Sampling Periods (MB) Transaction, or AQS Maintain Monitor (L2).

### **4.84.3 Attributes**

Type: Date

Length: Not Applicable

Required: Yes

### **4.84.4 Uses**

Sample Periods

## **4.85 Date Sampling Ended**

### **4.85.1 Description**

The date, on which a distinct period of operations, i.e., collection of air quality samples, stopped for the monitor.

### **4.85.2 Source**

User-specified via the Monitor Sampling Periods (MB) Transaction, or AQS Maintain Monitor (L2).

### **4.85.3 Attributes**

Type: Date

Length: Not Applicable

Required: No

### **4.85.4 Uses**

Sample Periods

## **4.86 Date Site Established**

### **4.86.1 Description**

The date on which an air-monitoring site began collecting air quality data.

### **4.86.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.86.3 Attributes**

Type: Date

Length: Not Applicable

Required: Yes

### **4.86.4 Uses**

Sites

## **4.87 Date Site Terminated**

### **4.87.1 Description**

The date on which a monitoring site ceased to operate.

### **4.87.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.87.3 Attributes**

Type: Date

Length: Not Applicable

Required: No

### **4.87.4 Uses**

Sites

## **4.88 Direct Entry Indicator**

### **4.88.1 Description**

An indication of whether the summary record was system-generated as part of the Post process, or user-specified via the Annual Summary Data (RS) Transaction, or AQS Maintain Annual Summary (L7).

### **4.88.2 Source**

System-generated via the Post or Load processes, or AQS Maintain Annual Summary (L7).

### **4.88.3 Attributes**

Type: Character

Length: 3

Required: No

### **4.88.4 Uses**

Annual Summaries

### **4.88.5 Value Assignment**

“N” signifies the record was system-generated via the Post process; “Y” signifies the record was user-specified via either the Annual Summary Data (RS) Transaction, or AQS Maintain Annual Summary (L7).

## **4.89 Direction from Central Business District to Site**

### **4.89.1 Description**

A representation of the true, as opposed to magnetic, direction of the site from the central business district. If the site is within the central business district, it is a representation of the direction the probe faces.

### **4.89.2 Source**

User-specified, via Sites (AA) Transaction, or AQS Maintain Site (L1).

### **4.89.3 Attributes**

Type: Character  
Length: 3  
Required: No

### **4.89.4 Uses**

Sites

### **4.89.5 Value Assignment**

The value must exist in the *Compass Sectors* view

## **4.90 Direction from Monitor to Probe Obstruction**

### **4.90.1 Description**

The direction from the monitor to the obstruction.

### **4.90.2 Source**

User-specified via the Monitor Obstruction Information (MH) Transaction, or AQS Maintain Monitor (L2).

### **4.90.3 Attributes**

Type: Character

Length: 3

Required: Yes

### **4.90.4 Uses**

Probe Obstructions

### **4.90.5 Value Assignment**

The value must exist on the *Compass Sectors* view.

## **4.91 Direction from Receiver to Transmitter**

### **4.91.1 Description**

The direction from the receiver to the transmitter at the site.

### **4.91.2 Source**

User-specified, via Site Open Path Information (AC) Transaction, or AQS Maintain Site (L1).

### **4.91.3 Attributes**

Type: Character

Length: 3

Required: Yes

### **4.91.4 Uses**

Open Paths

### **4.91.5 Value Assignment**

The value must exist on the *Compass Sectors* view.

## **4.92 Direction from Site to Street**

### **4.92.1 Description**

The direction from the site to the street at its nearest point.

### **4.92.2 Source**

User-specified, via Site Street Information (AB) Transaction, or AQS Maintain Site (L1).

### **4.92.3 Attributes**

Type: Character

Length: 3

Required: Yes

### **4.92.4 Uses**

Tangent Roads

### **4.92.5 Value Assignment**

The value must exist on the *Compass Sectors* view.

## **4.93 Direction to Meteorological Site**

### **4.93.1 Description**

The true, as opposed to the magnetic, direction of the meteorological site from this site.

### **4.93.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.93.3 Attributes**

Type: Character

Length: 3

Required: No

### **4.93.4 Uses**

Sites

### **4.93.5 Value Assignment**

The value must exist on the *Compass Sectors* view.

## **4.94 Distance from Central Business District to Site**

### **4.94.1 Description**

The distance, in kilometers, to the site from the center of the downtown central business district of the city in which the site is located.

### **4.94.2 Source**

User-specified, via Sites (AA) Transaction, or AQS Maintain Site (L1).

### **4.94.3 Attributes**

Type: Number

Length: 8.2

Required: No

### **4.94.4 Uses**

Sites

## **4.95 *Distance from Monitor to Probe Obstruction***

### **4.95.1 Description**

The distance, in meters, between the probe and obstruction

### **4.95.2 Source**

User-specified via the Monitor Obstruction Information (MH) Transaction, or AQS Maintain Monitor (L2).

### **4.95.3 Attributes**

Type: Number

Length: 8.2

Required: Yes

### **4.95.4 Uses**

Probe Obstructions

## **4.96 *Distance from Monitor to Tangent Road***

### **4.96.1 Description**

The distance in meters between the sensing of air sampling equipment at a monitoring site and the nearest edge of the roadway.

### **4.96.2 Source**

User-specified via the Monitor Street Description (MG) Transaction, or AQS Maintain Monitor (L2).

### **4.96.3 Attributes**

Type: Number

Length: 8.2

Required: Yes

### **4.96.4 Uses**

Monitor Tangent Roads

## **4.97 *Distance from Primary Sampler***

### **4.97.1 Description**

The distance, in meters, between a duplicate sampler and the primary sampler in a collocated pair.

### **4.97.2 Source**

User-specified via the Monitor Collocation Period (MJ) Transaction, or AQS Maintain Monitor (L2).

### **4.97.3 Attributes**

Type: Number

Length: 8.2

Required: No

### **4.97.4 Uses**

Monitor Collocation Periods

## **4.98 Distance to Meteorological Site**

### **4.98.1 Description**

The distance of the associated meteorological site from the air quality monitoring site, in meters. This information is required if the site has monitors that are part of a Photochemical Assessment Monitoring System (PAMS) network. The associated site need not be an AQS site.

### **4.98.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.98.3 Attributes**

Type: Number

Length: 8.2

Required: No

### **4.98.4 Uses**

Sites.

## **4.99 Dominant Source**

### **4.99.1 Description**

The primary source of the pollutant being measured.

### **4.99.2 Source**

User-specified via the Basic Monitor Information (MA) Transaction, or AQS Maintain Monitor (L2).

### **4.99.3 Attributes**

Type: Character  
Length: 20  
Required: No

### **4.99.4 Uses**

Monitors

### **4.99.5 Value Assignment**

The value must exist on the *Dominant Sources* view.

## **4.100 Duration Code**

### **4.100.1 Description**

The length of time used to acquire raw samples that are analyzed by monitors, also called interval.

### **4.100.2 Source**

User-specified via the Monitor Protocol (MK), Raw Data (RD), or Composite Data (RC) Transactions, or AQS Maintain Monitor (L2), or system-generated via the Post process.

### **4.100.3 Attributes**

Type: Character  
Length: 8  
Required: Yes

### **4.100.4 Uses**

Monitor Protocols  
NAAQS Averages  
Daily Summaries  
Quarterly Summaries  
Annual Summaries

### **4.100.5 Value Assignment**

#### **4.100.5.1 Monitor Protocols**

In combination with Parameter Code, Method Code, Reported Unit, Collection Frequency Code and Composite Type, must exist on the Protocols view.

#### **4.100.5.2 NAAQS Averages, Daily, Quarterly & Annual Summaries**

For summarized sample data, the duration used to acquire the sample data being summarized. For summarized National Ambient Air Quality Standards (NAAQS) averages, the duration assigned for the NAAQS interval being summarized.

## **4.101 EPA Region Concurrence Indicator**

### **4.101.1 Description**

Indicates whether the appropriate EPA regional office has concurred with either an event-qualified sample value, or a null ozone sample value qualified with the null data code “BG”, which signifies “Missing ozone data not likely to exceed level of standard”.

### **4.101.2 Source**

Specified by the appropriate EPA regional office via AQS Maintain Concurrence (L8).

### **4.101.3 Attributes**

Type: Character  
Length: 1  
Required: No

### **4.101.4 Uses**

Raw Data  
Composite Data

### **4.101.5 Value Assignment**

The valid values are “Y” and “N”. “Y” signifies that the regional office has reviewed the required supporting documentation provided by the data owner, and agrees that use of the qualification is appropriate. Conversely, “N” signifies that they have reviewed that documentation, but disagree with the use of the qualification. (No value signifies that the review has not occurred, or is still in process.)

## **4.102 EPA Region Evaluation Date**

### **4.102.1 Description**

The date on which the most recent regional evaluation of the site for siting criteria occurred.

### **4.102.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.102.3 Attributes**

Type: Date

Length: Not applicable

Required: No

### **4.102.4 Uses**

Sites

## **4.103 Estimate of Days Greater Than Standard**

### **4.103.1 Description**

The estimated number of days greater than the standard is computed and is utilized to determine whether the standard is attained. It is computed for specific pollutants when an exceedance has occurred during the year. The underlying assumption is that missing data is just as likely to exceed the standard as reported data.

### **4.103.2 Source**

System-generated via the Post process.

### **4.103.3 Attributes**

Type: Number

Length: 3.2

Required: No

### **4.103.4 Uses**

Annual Summaries

### **4.103.5 Value Assignment**

The estimate exceedance is rounded to 1 decimal place.

#### **4.103.5.1 1-Hour Ozone**

$$e = d + \left( \left( \frac{d}{v} \right) * (r - v - a) \right)$$

where

*e* = expected days greater than the standard,

*r* = Count of Required Days,

*v* = Count of Valid Days,

*a* = Count of Missing Days Assumed Less Than Standard,

*d* = Count of Primary Exceedances.

#### 4.103.5.2 Daily PM10

$$e = \sum_{q=1}^4 e_q$$

where:

- $e$  = estimated number of exceedances for the year,
- $e_q$  = the estimated number of exceedances for calendar quarter  $q$ ,
- $q$  = the index for calendar quarter,  $q=1, 2, 3$  or  $4$ .

The estimate of the expected number of exceedances for a quarter is calculated using the following formula:

$$e = \left(\frac{a}{v}\right) * \sum_{j=1}^v \left(\frac{x_j}{n_j}\right)$$

where:

- $e$  = the estimated number of exceedances for calendar quarter  $q$ ,
- $a$  = the number of days in calendar quarter  $q$ ,
- $v$  = the number of valued strata in calendar quarter  $q$ ,
- $x_j$  = the number of exceedances in stratum  $j$ ,
- $n_j$  = the number of observations in stratum  $j$ .

The quarterly exceedance estimate is set to 1 for a calendar quarter in which the first observed exceedance has occurred if:

1. There was only one exceedance in the calendar quarter,
2. Everyday sampling is subsequently initiated and maintained for 4 calendar quarters, in accordance with 40 CFR 58.13,
3. Data capture of 75 percent is achieved during the required period of everyday sampling.

In addition, if the first exceedance is observed in a calendar quarter in which the monitor is already sampling every day, no adjustment for missing data will be made to the first exceedance if a 75 percent data capture rate was achieved in the quarter in which it was observed.

#### 4.103.5.3 24-Hour PM10

$$e = \sum_{q=1}^4 e_q$$

where:

- $e$  = estimated number of exceedances for the year,
- $e_q$  = the estimated number of exceedances for calendar quarter  $q$ ,
- $q$  = the index for calendar quarter,  $q=1, 2, 3$  or  $4$ .

The estimate of the expected number of exceedances for a quarter is calculated using the following formula:

$$e = v * \left( \frac{a}{n} \right)$$

where:

- $e$  = the estimated number of exceedances for calendar quarter  $q$ ,
- $v$  = the observed number of exceedances for calendar quarter  $q$ ,
- $a$  = the number of days in calendar quarter  $q$ ,
- $n$  = the number of observations in calendar quarter  $q$ .

The quarterly exceedance estimate is set to 1 for a calendar quarter in which the first observed exceedance has occurred if:

1. There was only one exceedance in the calendar quarter,
2. Everyday sampling is subsequently initiated and maintained for 4 calendar quarters in accordance with 40 CFR 58.13,
3. Data capture of 75 percent is achieved during the required period of everyday sampling.

In addition, if the first exceedance is observed in a calendar quarter in which the monitor is already sampling every day, no adjustment for missing data will be made to the first exceedance if a 75 percent data capture rate was achieved in the quarter in which it was observed.

#### 4.103.5.4 Default

Not valued.

## **4.104 Exceptional Data Type ID**

### **4.104.1 Description**

Indication of whether exceptional data exists in the time period being summarized, and whether such exceptional data is included in the reported summary values.

### **4.104.2 Source**

System-generated via the Post process, or user-generated via either the Annual Summaries (RS) Transaction or Maintain Annual Summaries (L7).

### **4.104.3 Attributes**

Type: Number  
Length: 10.0  
Required: Yes

### **4.104.4 Uses**

NAAQS Averages  
Daily Summaries  
Quarterly Summaries  
Annual Summaries

#### 4.104.5 Value Assignment

The meaning of the identifiers are, as follows:

<b>ID</b>	<b>Description</b>
0	No events
1	Events excluded
2	Events included
3	Exceptional events excluded
4	Natural events excluded
5	Events with concurrence excluded
6	Exceptional events with concurrence excluded
7	Natural events with concurrence excluded

The event qualifiers and types are, as follows:

<b>Code</b>	<b>Description</b>	<b>Type</b>
A	High Winds	Natural Event
B	Stratospheric Ozone Intrusion	Natural Event
C	Volcanic Eruptions	Natural Event
D	Sandblasting	Exceptional Event
E	Forest Fire	Natural Event
F	Structural Fire	Exceptional Event
G	High Pollen Count	Natural Event
H	Chemical Spills & Indust. Accidents	Exceptional Event
I	Unusual Traffic Congestion	Exceptional Event
J	Construction/Demolition	Exceptional Event
K	Agricultural Tilling	Exceptional Event
L	Highway Construction	Exceptional Event
M	Rerouting Of Traffic	Exceptional Event
N	Sanding/Salting Of Streets	Exceptional Event
O	Infrequent Large Gatherings	Exceptional Event
P	Roofing Operations	Exceptional Event
Q	Prescribed Burning	Exceptional Event
R	Clean Up After A Major Disaster	Exceptional Event
S	Seismic Activity	Natural Event
U	Sahara Dust	Natural Event

## **4.105 Exclusion Date**

### **4.105.1 Description**

Indicates the date when the data owner flagged the pre-production sample data record to be excluded from the statistical check/critical review, and post processes.

### **4.105.2 Source**

System-generated via the AQS Maintain Raw Data (L54) or AQS Maintain Composite Data (L51) modules.

### **4.105.3 Attributes**

Type: Date

Length: Not Applicable

Required: No

### **4.105.4 Uses**

Raw Data

Composite Data

### **4.105.5 Value Assignment**

#### **4.105.5.1 Pre-Production Status**

May be valued when the *Status Indicator* is "R" or "S".

#### **4.105.5.2 Production Status**

May not be valued when the *Status Indicator* is "P".

## **4.106 Exclusion Indicator**

### **4.106.1 Description**

Indication by the data owner to exclude the pre-production sample data record from the statistical check/critical review, and post processes.

### **4.106.2 Source**

User-specified via the AQS Maintain Raw Data (L54) or AQS Maintain Composite Data (L51) modules.

### **4.106.3 Attributes**

Type: Character  
Length: 1  
Required: No

### **4.106.4 Uses**

Raw Data  
Composite Data

### **4.106.5 Value Assignment**

#### **4.106.5.1 Pre-Production Status**

May be assigned a value of “Y” when the *Status Indicator* is “R” or “S”.

#### **4.106.5.2 Production Status**

May not be assigned a value when the *Status Indicator* is “P”.

## **4.107 Expiration Date**

### **4.107.1 Description**

The expiration date for the local primary standard.

### **4.107.2 Source**

User-specified, via Accuracy Data (RA) Transaction, or AQS Maintain Accuracy (L62).

### **4.107.3 Attributes**

Type: Date

Length: Not Applicable

Required: No

### **4.107.4 Uses**

Accuracy Data

## **4.108 Freeze Indicator**

### **4.108.1 Description**

Indicates whether EPA headquarters has determined that the sample value cannot be changed by the owner of that value.

### **4.108.2 Source**

EPA Headquarters-specified via AQS Restore/Freeze Data (G1).

### **4.108.3 Attributes**

Type: Character

Length: 3

Required: No

### **4.108.4 Uses**

Raw Data

Composite Data

### **4.108.5 Value Assignment**

May be assigned a value of "Y".

## 4.109 Geometric Mean

### 4.109.1 Description

The measure of central tendency obtained from the sum of the logarithms of observed sample values in the yearly data set, divided by the number of values, with that result applied as an exponent to 10.

### 4.109.2 Source

System-generated via the Post process, or user-generated via either the Annual Summaries (RS) Transaction or Maintain Annual Summaries (L7).

### 4.109.3 Attributes

Type: Number

Length: 5.5

Required: No

### 4.109.4 Uses

Annual Summaries

### 4.109.5 Value Assignment

#### 4.109.5.1 Total Suspended Particulate (TSP) & Lead

$$\mu = 10^x$$

where:

$u$  = mean,

$x$  =

$$\frac{\sum_{j=1}^n \log_{10} S_j}{n}$$

and:

$s$  = sample value,

$n$  = *Count of Observations (Annual)*.

#### 4.109.5.2 Default

Not valued.

## **4.110 Geometric Standard Deviation**

### **4.110.1 Description**

The measure of the dispersion about the central tendency of a pollutant that is based on the variation between the geometric mean of a sample of values and the logarithms of the values themselves.

### **4.110.2 Source**

System-generated via the Post process, or user-generated via either the Annual Summaries (RS) Transaction or Maintain Annual Summaries (L7).

### **4.110.3 Attributes**

Type: Number

Length: 7.5

Required: No

### **4.110.4 Uses**

Annual Summaries

## 4.110.5 Value Assignment

### 4.110.5.1 Total Suspended Particulate (TSP) & Lead

$$\sigma = 10^x$$

where:

$\sigma$  = standard deviation,

$x$  =

$$\sqrt{\frac{\left( n * \sum_{j=1}^n \log_{10} S_j^2 \right) - \left( \sum_{j=1}^n \log_{10} S_j \right)^2}{n * (n - 1)}}$$

where:

$s$  = sample value,

$n$  = *Count of Observations (Annual)*.

and  $n > 1$ .

If the Count of Observations (Annual) is exactly 1, or:

$$n * \sum_{j=1}^n \log_{10} S_j^2 < \left( \sum_{j=1}^n \log_{10} S_j \right)^2$$

where:

$s$  = sample value,

$n$  = *Count of Observations (Annual)*,

then the standard deviation is assigned a value of 0.

### 4.110.5.2 Default

Not valued.

## **4.111 Geometric Type**

### **4.111.1 Description**

The geometric entity represented by the air-monitoring site.

This data element is required by EPA Locational Data Policy. More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website (<http://www.epa.gov/edr/>).

### **4.111.2 Source**

The system-generated via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.111.3 Attributes**

Type: Character

Length: 50

Required: Yes

### **4.111.4 Uses**

Sites

### **4.111.5 Value Assignment**

Always "POINT".

## **4.112 Half MDL Substitution Indicator**

### **4.112.1 Description**

Indicates whether  $\frac{1}{2}$  the applicable method detectable limit (MDL) was substituted for the computed standard sample value when that computed value is less the applicable MDL.

### **4.112.2 Source**

The system-generated via the Raw Data (RD) or Composite Data (RC) Transactions, or AQS Maintain Raw Data (L54), or AQS Maintain Composite Data (L51).

### **4.112.3 Attributes**

Type: Character  
Length: 1  
Required: No

### **4.112.4 Uses**

Raw Data  
Composite Data

### **4.112.5 Value Assignment**

#### **4.112.5.1 Hourly PM2.5**

Will not be assigned a value. (The actual computed standard value is always used in this case.)

#### **4.112.5.2 Default**

May be assigned a value of "Y".

## **4.113 Height of Receiver**

### **4.113.1 Description**

The height of the receiver above the ground, in meters.

### **4.113.2 Source**

The system-generated via the Site Open Path Information (AC) Transaction, or AQS Maintain Site (L1).

### **4.113.3 Attributes**

Type: Number

Length: 8.2

Required: No

### **4.113.4 Uses**

Open Paths

## **4.114 Height of Transmitter**

### **4.114.1 Description**

The height of the transmitter above the ground, in meters.

### **4.114.2 Source**

The system-generated via the Site Open Path Information (AC) Transaction, or AQS Maintain Site (L1).

### **4.114.3 Attributes**

Type: Number

Length: 8.2

Required: No

### **4.114.4 Uses**

Open Paths

## 4.115 Horizontal Accuracy

### 4.115.1 Description

Description of the accuracy of the site coordinates, as a range reported in meters. Only the least accurate measurement needs to be recorded, whether it is latitude or longitude (or Universe Transverse Mercator (UTM) coordinates).

For example, here are accuracy standards for various scale maps, assuming that the maps conform to the national mapping accuracy standards:

1:1,200 ± 3.33 feet
1:2,400 ± 6.67 feet
1:4,800 ± 13.33 feet
1:10,000 ± 27.78 feet
1:12,000 ± 33.33 feet
1:24,000 ± 40.00 feet
1:63,360 ± 105.60 feet
1:100,000 ± 166.67 feet

Map interpolation would also introduce error.

For Global Positioning System (GPS), the accuracy values vary. The type of GPS used along with operating conditions affect accuracy. The GPS receiver may provide accuracy values associated with specific coordinate readings.

This data element is required by EPA Locational Data Policy (LDP). More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website (<http://www.epa.gov/edr/>).

### 4.115.2 Source

User-specified via the via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.115.3 Attributes**

Type: Number

Length: 8.2

Required: Yes

### **4.115.4 Uses**

Sites

## **4.116 Horizontal Collection Method**

### **4.116.1 Description**

The code for the method used to determine the latitude/longitude or Universal Transverse Mercator (UTM) coordinates.

Required by EPA Locational Data Policy (LDP). More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website (<http://www.epa.gov/edr/>).

### **4.116.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.116.3 Attributes**

Type: Character

Length: 8

Required: Yes

### **4.116.4 Uses**

Sites

### **4.116.5 Value Assignment**

Must be a value on the *LDP Collection Methods* view

## **4.117 Horizontal Datum**

### **4.117.1 Description**

The edition of North American Datum used as the basis for determining the site coordinates. (The editions of North American Datum establish a network of monuments and reference points defining a mathematical surface from which geographic computations can be made.) The World Geodetic Survey 1984 (WGS84) is one horizontal datum used by many Global Positioning System (GPS) instruments. United States Geological Survey (USGS) maps often use the North Atlantic Datum 1927 (NAD27).

This data element is required by EPA Locational Data Policy. More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website (<http://www.epa.gov/edr/>).

### **4.117.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.117.3 Attributes**

Type: Character  
Length: 120  
Required: Yes

### **4.117.4 Uses**

Sites

### **4.117.5 Value Assignment**

The value must exist on the *LDP Horizontal Data* view.

## **4.118 Hour of Maximum Value**

### **4.118.1 Description**

The hour of the day at which the *Maximum Value (Daily)* was reported.

### **4.118.2 Source**

System-generated via the Post process.

### **4.118.3 Attributes**

Type: Number

Length: 2.0

Required: No

### **4.118.4 Uses**

Daily Summaries

### **4.118.5 Value Assignment**

Must be a value between 0 and 23.

## **4.119 HQ Evaluation Date**

### **4.119.1 Description**

The date on which the most recent evaluation of the site by EPA headquarters (HQ) occurred.

### **4.119.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.119.3 Attributes**

Type: Date

Length: Not Applicable

Required: No

### **4.119.4 Uses**

Sites

## **4.120 Indicated Method**

### **4.120.1 Description**

Identifies the particular method for collecting and analyzing a precision check value.

#### **4.120.1.1 Analytical**

The method used to collect and analyze the known gaseous concentration with which the sampler is challenged.

#### **4.120.1.2 Flow**

The method used to collect and analyze the known flow rate with which the sampler is challenged.

#### **4.120.1.3 Collocated**

The method used to collect and analyze the ambient air sample from the duplicate sampler.

### **4.120.2 Source**

User-specified, via Precision Data (RP) Transaction, or AQS Maintain Precision (L61).

### **4.120.3 Attributes**

Type: Character

Length: 3

Required: Yes

### **4.120.4 Uses**

Precision Data

### **4.120.5 Value Assignment**

The *Indicated Method* value, in combination with the *Parameter* value, must exist in the *Sampling Methodologies* view.

## **4.121 Indicated Value**

### **4.121.1 Description**

#### **4.121.1.1 Analytical**

The measurement recorded by a monitor for a standard gaseous concentration with which it has been challenged.

#### **4.121.1.2 Flow**

The measurement recorded by a monitor for a standard flow rate with which it has been challenged.

#### **4.121.1.3 Collocated**

The concentration produced from the duplicate sampler in a collocated sampler pair.

### **4.121.2 Source**

For a precision check, user-specified, via Precision Data (RP) Transaction, or AQS Maintain Precision (L61). For an accuracy audit, user-specified, via Accuracy Data (RA) Transaction, or AQS Maintain Accuracy (L62).

### **4.121.3 Attributes**

Type: Number

Length: 5.5

Required: Yes

### **4.121.4 Uses**

Precision Data

Accuracy Data

### **4.121.5 Value Assignment**

#### **4.121.5.1 Analytical Check**

The *Indicated Value* for a precision check must not exceed the maximum value allowed for the *Parameter*.

#### **4.121.5.2 Collocated Check**

The *Indicated Value* for a precision check must not exceed the maximum value allowed for the *Parameter*.

## **4.122 Land Use Type**

### **4.122.1 Description**

For a site, the prevalent land use within 1/4 mile of that site.

### **4.122.2 Source**

User-specified, via Sites (AA) or AQS Maintain Sites (L1).

### **4.122.3 Attributes**

Type: Character

Length: 20

Required: Yes

### **4.122.4 Uses**

Sites

Open Paths

### **4.122.5 Value Assignment**

The value must exist on the *Land Use Types* view.

## **4.123 Land Use Under Path**

### **4.123.1 Description**

For an open path, the prevalent land use under the path of the beam being projected between the receiver and transmitter.

### **4.123.2 Source**

Open Paths (AC) Transaction, or AQS Maintain Sites (L1), Open Paths.

### **4.123.3 Attributes**

Type: Character

Length: 20

Required: Yes

### **4.123.4 Uses**

Sites

Open Paths

### **4.123.5 Value Assignment**

The value must exist on the *Land Use Types* view.

## **4.124 Last Post Date**

### **4.124.1 Description**

The last date and time at which the screening group owner, (or data administrator acting as a proxy), ran a Post process that posted data for the monitor.

### **4.124.2 Source**

System-generated via the Post process.

### **4.124.3 Attributes**

Type: Date

Length: Not Applicable

Required: No

### **4.124.4 Uses**

Monitors

## **4.125 Last Sampling Date**

### **4.125.1 Description**

The maximum date for which sample date has been reported for the monitor.

### **4.125.2 Source**

System-generated via the Post process.

### **4.125.3 Attributes**

Type: Date

Length: Not Applicable

Required: No

### **4.125.4 Uses**

Monitors

## **4.126 Latitude**

### **4.126.1 Description**

The monitoring site's angular distance north or south of the equator measured in decimal degrees. The associated sign specifies the direction of measurement, a positive number indicating north and negative indicating south.

EPA Locational Data Policy (LDP) requires that coordinates be provided for all sites. More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website (<http://www.epa.gov/edr/>).

### **4.126.2 Source**

User-specified, or system-generated from user-specified Universe Transverse Mercator (UTM) coordinates, via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.126.3 Attributes**

Type: Number

Length: 2.6

Required: Yes

### **4.126.4 Uses**

Sites

## **4.127 Local Primary Standard**

### **4.127.1 Description**

A description of the source of the local primary standards.

### **4.127.2 Source**

User-specified via Accuracy Data (RA) Transaction, or AQS Maintain Accuracy (L62), or system-generated via Accuracy Data (RA) Transaction, or AQS Maintain Accuracy (L62).

### **4.127.3 Attributes**

Type: Character

Length: 30

Required: Yes

### **4.127.4 Uses**

Accuracy Data

Monitor Accuracy Summaries

Reporting Organization Accuracy Summaries

### **4.127.5 Value Assignment**

#### **4.127.5.1 Accuracy Data**

Must be a value on the *Local Primary Standards* view.

#### **4.127.5.2 Monitor & Reporting Organization Accuracy Summaries**

The most frequently assigned value for the population of source data.

## **4.128 Local Region**

### **4.128.1 Description**

A code representing a state-defined geographic/administrative area within which the site is located.

### **4.128.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.128.3 Attributes**

Type: Character

Length: 8

Required: No

### **4.128.4 Uses**

Sites

### **4.128.5 Value Assignment**

In combination with *State Code*, the value must exist on the *Local Regions* view

## **4.129 Local Site ID**

### **4.129.1 Description**

Identification code used by a state, tribe or local agency, if different from the AQS site ID.

### **4.129.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.129.3 Attributes**

Type: Character

Length: 40

Required: No

### **4.129.4 Uses**

Sites.

## **4.130 Local Site Name**

### **4.130.1 Description**

The locally defined name of the site.

### **4.130.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.130.3 Attributes**

Type: Character

Length: 70

Required: No

### **4.130.4 Uses**

Sites

## **4.131 Location Setting**

### **4.131.1 Description**

A description of the environmental setting within which the site is located.

### **4.131.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.131.3 Attributes**

Type: Character

Length: 50

Required: Yes

### **4.131.4 Uses**

Sites

### **4.131.5 Value Assignment**

The value must exist on the *Location Settings* view.

## **4.132 Longitude**

### **4.132.1 Description**

The monitoring site's angular distance east or west of the prime meridian at Greenwich, measured in decimal degrees. The associated sign specifies the direction of measurement, a positive number indicating east and negative indicating west.

EPA Locational Data Policy requires that coordinates be provided for all sites. More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website (<http://www.epa.gov/edr/>).

### **4.132.2 Source**

User-specified, or system-generated from user-specified Universe Transverse Mercator (UTM) coordinates, via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.132.3 Attributes**

Type: Number

Length: 3.6

Required: Yes

### **4.132.4 Uses**

Sites

## 4.133 Lower Probability/Confidence Limit (Reporting Organization Accuracy Summary)

### 4.133.1 Description

The lower bound of either a probability distribution, or confidence interval, for the applicable population of accuracy audits.

If either quarter in either half of the year has an Audit Count of 1, then the source data for both quarters in that half will be merged for purposes of calculating the lower probability/confidence limit, and reported with the second quarter of the half (i.e., Q2 or Q4). In this case, there will be no value for the corresponding first quarter in the half (i.e., Q1 or Q3).

### 4.133.2 Source

System-generated via Accuracy Data (RA) Transaction, or Maintain Accuracy (L61).

### 4.133.3 Attributes

Type: Number

Length: 6.4

Required: No

### 4.133.4 Uses

Reporting Organization Accuracy Summaries

### 4.133.5 Value Assignment

#### 4.133.5.1 PM2.5 Flow

$$l = D - \left( \frac{S * t_{0.975, n-1}}{\sqrt{n}} \right)$$

where:

$l$  = lower 95% confidence limit,

$D$  = Mean (Reporting Organization Accuracy Summary),

$S$  = Standard Deviation (Reporting Organization Accuracy Summary),

$t_{0.975, n-1}$  = the 0.975 quantile of the Student's T distribution with degrees of freedom equal to  $n-1$ ,

$n$  = Count of Accuracy Audits (Reporting Organization Accuracy Summary).

#### 4.133.5.2 Default

$$l = D - (S * 1.96)$$

where:

*l* = lower 95% probability limit,

*D* = Mean (*Reporting Organization Accuracy Summary*),

*S* = Standard Deviation (*Reporting Organization Accuracy Summary*).

## 4.134 Lower Probability/Confidence Limit (Reporting Organization Precision Summary)

### 4.134.1 Description

The lower bound of either a probability distribution, or confidence interval, for the applicable population of precision checks.

### 4.134.2 Source

System-generated via Precision Data (RP) Transaction, or Maintain Precision (L62).

### 4.134.3 Attributes

Type: Number

Length: 6.4

Required: No

### 4.134.4 Uses

Reporting Organization Precision Summaries

### 4.134.5 Value Assignment

#### 4.134.5.1 Analytical & Non-PM2.5 Flow

$$l = D - (S * 1.96)$$

where:

$l$  = lower 95% probability limit,

$D$  = Mean (Reporting Organization Precision Summary),

$S$  = Standard Deviation (Reporting Organization Precision Summary).

#### 4.134.5.2 PM2.5 Flow

$$l = D - \left( \frac{S * t_{0.975, n-1}}{\sqrt{n}} \right)$$

where:

$l$  = lower 95% confidence limit,

$D$  = Mean (Reporting Organization Precision Summary),

$S$  = Standard Deviation (Reporting Organization Precision Summary),

$t_{0.975, n-1}$  = the 0.975 quantile of the Student's T distribution with degrees of freedom equal to  $n-1$ ,

$n$  = Count of Precision Checks (Reporting Organization Precision Summary).

#### 4.134.5.3 PM2.5 Collocated

$$l = CV \sqrt{\frac{n}{\chi^2_{0.95, n}}}$$

where:

$l$  = lower 90% confidence limit,

$CV$  = coefficient of variation,

$n$  = Count of Valid Collocated Data Pairs (Reporting Organization Precision Summary),

$\chi^2_{0.95, n}$  = the 0.95 quantile of the chi-square distribution with degrees of freedom equal to  $n$ .

#### 4.134.5.4 Other Collocated

$$l = D - \left( \frac{S * 1.96}{\sqrt{2}} \right)$$

where:

$l$  = lower 95% probability limit,

$D$  = Mean (Reporting Organization Precision Summary),

$S$  = Standard Deviation (Reporting Organization Precision Summary).

#### 4.134.5.5 Federal Reference Method (FRM) Audit

$$l = D - \left( \frac{S * t_{0.975, n-1}}{\sqrt{n}} \right)$$

where:

$l$  = lower 95% confidence limit,

$D$  = Mean (Reporting Organization Precision Summary),

$S$  = Standard Deviation (Reporting Organization Precision Summary),

$t_{0.975, n-1}$  = the 0.975 quantile of the Student's T distribution with degrees of freedom equal to  $n-1$ ,

$n$  = Count of Precision Checks (Reporting Organization Precision Summary).

## **4.135 Maximum Beam Height**

### **4.135.1 Description**

The height of the beam (at the highest point from the ground) being projected between the receiver and transmitter at the site, in meters.

### **4.135.2 Source**

User-specified via the Site Open Path Information (AC) Transaction, or AQS Maintain Site (L1).

### **4.135.3 Attributes**

Type: Number

Length: 8.2

Required: No

### **4.135.4 Uses**

Open Paths

## **4.136 Maximum Indicator**

### **4.136.1 Description**

An indication of the type of maximum value.

### **4.136.2 Source**

System-generated via the Post process.

### **4.136.3 Attributes**

Type: Character

Length: 3

Required: Yes

### **4.136.4 Uses**

Summary Maximums

### **4.136.5 Value Assignment**

Indicator	Description
OVR	Non-overlapping 8-Hour Carbon Monoxide
ACT	Actual 8-Hour Carbon Monoxide
REG	All other cases

## **4.137 Maximum Level**

### **4.137.1 Description**

The numeric rank of a value, relative to other values in the same value set, in descending value order.

### **4.137.2 Source**

System-generated via the Post process.

### **4.137.3 Attributes**

Type: Number

Length: 4.0

Required: Yes

### **4.137.4 Uses**

Summary Maximums

## **4.138 Maximum Value (Annual)**

### **4.138.1 Description**

A value in a value set of a certain associated Daily Rank, relative to other values in the same value set.

### **4.138.2 Source**

System-generated via the Post process.

### **4.138.3 Attributes**

Type: Number

Length: 5.5

Required: Yes

### **4.138.4 Uses**

Summary Maximums

### **4.138.5 Value Assignment**

#### **4.138.5.1 Ozone (1-Hour & 8-Hour)**

The ten highest 1-hour or 8-hour *Maximum Value (Daily)* values for the year, regardless of monitoring season or whether daily summary criteria were met.

#### 4.138.5.2 Non-Overlapping 8-Hour Carbon Monoxide

The two highest valid 8-hour *Arithmetic Mean (NAAQS)* values of the year where there is at least one other non-overlapping *Arithmetic Mean (NAAQS)* that is greater than, or equal to, the second highest average, and the dates and hours for which each was computed. (Note: The first actual maximum is always the first non-overlapping maximum.)

In the following example, the fourth actual maximum is the second non-overlapping maximum because, while it overlaps the first and second actual maximums, it does not overlap the third. Since the second actual overlaps the first, and the third overlaps both the first and second, neither one qualifies to be the second non-overlapping maximum.

<b>Actual Rank</b>	<b>8-Hour Average (mg)</b>	<b>Date/Time</b>	<b>Does it overlap all of the higher values?</b>
1	16	Dec. 8 10:01 AM – 6:00 PM	--
2	15	Dec. 8 9:01 AM – 5:00 PM	Yes
3	15	Dec. 8 11:01 AM – 7:00 PM	Yes
4	14	Dec. 8 3:01 AM – 11:00 AM	No
5	13	Nov. 20 10:01 AM – 6:00 PM	
6	13	Nov. 11 11:01 AM – 7:00 PM	
7	13	Feb. 9 9:01 AM – 5:00 PM	
8	12	Nov. 11 10:01 AM – 6:00 PM	
9	12	Oct. 29 10:01 AM – 6: 00 PM	

#### 4.138.5.3 Actual 8-Hour Carbon Monoxide

The ten highest valid 8-hour *Arithmetic Mean (NAAQS)* values of the year, regardless of whether they overlap.

#### 4.138.5.4 Default

The ten highest values for the year

## **4.139 Maximum Value (and Second Highest through Fifth Highest)**

### **4.139.1 Description**

A value in a value set of a certain associated Daily Rank, relative to other values in the same value set.

### **4.139.2 Source**

User-generated using Annual Summary (RS) transaction, or AQS Maintain Annual Summary Information (L7).

### **4.139.3 Attributes**

Type: Number  
Length: 5.5  
Required: Yes

### **4.139.4 Uses**

Summary Maximums

### **4.139.5 Value Assignment**

On entry: Calculated and reported by the user in appropriate order.

## **4.140 Maximum Value (Daily)**

### **4.140.1 Description**

The maximum value for the 24-hour period.

### **4.140.2 Source**

System-generated via the Post process.

### **4.140.3 Attributes**

Type: Number

Length: 5.5

Required: Yes

### **4.140.4 Uses**

Daily Summaries

## **4.141 Maximum Value Date**

### **4.141.1 Description**

The date for which an annual Maximum Value was recorded.

### **4.141.2 Source**

User specified via Summary (RS) Transaction, or AQS Maintain Annual Summary Information (L7).

### **4.141.3 Attributes**

Type: Date

Length: 8

Required: Yes

### **4.141.4 Uses**

Forms and reports

### **4.141.5 Value Assignment**

On input: Coupled with Maximum Value Time to set Maximum Value Date/Time on field where Maximum Level = 1

On output: Extracted from Maximum Value Date/Time on field where Maximum Level = 1

## **4.142 Maximum Value Date of Second Highest**

### **4.142.1 Description**

The date for which a second highest Maximum Value was recorded.

### **4.142.2 Source**

User specified via Summary (RS) Transaction, or AQS Maintain Annual Summary Information (L7).

### **4.142.3 Attributes**

Type: Date

Length: 8

Required: Yes

### **4.142.4 Uses**

Forms and reports

### **4.142.5 Value Assignment**

On input: Coupled with Maximum Value Time to set Maximum Value Date/Time on record where Maximum Level = 2

On output: Extracted from Maximum Value Date/Time on record where Maximum Level = 2

## **4.143 Maximum Value Date/Time**

### **4.143.1 Description**

The date and time for which an annual Maximum Value was recorded.

### **4.143.2 Source**

System-generated as part of the Post process.

### **4.143.3 Attributes**

Type: Date

Length: Not Applicable

Required: Yes

### **4.143.4 Uses**

Summary Maximums

## **4.144 Maximum Value Time**

### **4.144.1 Description**

The 24-hour clock time at which an annual Maximum Value was recorded.

### **4.144.2 Source**

User specified via Summary (RS) Transaction, or AQS Maintain Annual Summary Information (L7).

### **4.144.3 Attributes**

Type: Date

Length: 5

Required: Yes

### **4.144.4 Uses**

Forms and reports

### **4.144.5 Value Assignment**

On input: Coupled with Maximum Value Date to set Maximum Value Date/Time on field where Maximum Level = 1

On output: Extracted from Maximum Value Date/Time on field where Maximum Level = 1

## **4.145 Maximum Value Date of Second Highest**

### **4.145.1 Description**

The 24-hour clock time at which a second highest Maximum Value was recorded.

### **4.145.2 Source**

User specified via Summary (RS) Transaction, or AQS Maintain Annual Summary Information (L7).

### **4.145.3 Attributes**

Type: Date

Length: 5

Required: Yes

### **4.145.4 Uses**

Forms and reports

### **4.145.5 Value Assignment**

On input: Coupled with Maximum Value Date to set Maximum Value Date/Time on record where Maximum Level = 2

On output: Extracted from Maximum Value Date/Time on record where Maximum Level = 2

## **4.146 Mean (Monitor Accuracy Summary)**

### **4.146.1 Description**

A measure of the central tendency of the applicable population of accuracy audits.

### **4.146.2 Source**

System-generated via Accuracy Data (RA) Transaction, or Maintain Accuracy (L61).

### **4.146.3 Attributes**

Type: Number

Length: 5.5

Required: No

### **4.146.4 Uses**

Monitor Accuracy Summaries

### **4.146.5 Value Assignment**

$$D = \frac{\sum_{i=1}^n d_i}{n}$$

where:

$D$  = estimate of accuracy (mean),

$d_i$  = *Percent Difference* of a analytical or flow audit,

$n$  = *Count of Accuracy Audits (Monitor Accuracy Summary)*.

## 4.147 Mean (Monitor Precision Summary)

### 4.147.1 Description

A measure of the central tendency of the applicable population of precision checks.

### 4.147.2 Source

System-generated via Precision Data (RP) Transaction, or Maintain Precision (L62).

### 4.147.3 Attributes

Type: Number

Length: 6.4

Required: Yes

### 4.147.4 Uses

Monitor Precision Summaries

### 4.147.5 Value Assignment

#### 4.147.5.1 Analytical & Flow

$$D = \frac{\sum_{i=1}^n d_i}{n}$$

where:

$D$  = estimate of precision (mean),

$d_i$  = *Percent Difference* of an analytical or flow precision check,

$n$  = *Count of Precision Checks (Monitor Precision Summary)*.

#### 4.147.5.2 Collocated (PM2.5)

$$CV = \sqrt{\frac{\sum_{i=1}^n \left( \frac{|d_i|}{\sqrt{2}} \right)^2}{n}}$$

where:

$CV$  = coefficient of variation, i.e., estimate of precision,

$d_i$  = *Percent Difference* of a valid collocated data pair,

$n$  = *Count of Valid Collocated Data Pairs (Monitor Precision Summary)*.

#### 4.147.5.3 Collocated (Other)

$$D = \frac{\sum_{i=1}^n d_i}{n}$$

where:

$D$  = estimate of precision (mean),

$d_i$  = *Percent Difference* of a valid collocated data pair,

$n$  = *Count of Valid Collocated Data Pairs (Monitor Precision Summary)*.

## 4.148 Mean (Reporting Organization Accuracy Summary)

### 4.148.1 Description

A measure of the central tendency of the applicable population of accuracy audits.

### 4.148.2 Source

System-generated via Accuracy Data (RA) Transaction, or Maintain Accuracy (L61).

### 4.148.3 Attributes

Type: Character

Length: 5.5

Required: No

### 4.148.4 Uses

Reporting Organization Accuracy Summaries

### 4.148.5 Value Assignment

$$D = \frac{\sum_{i=1}^n d_i}{n}$$

where:

$D$  = estimate of accuracy (mean),

$d_i$  = *Percent Difference* of a analytical or flow audit,

$n$  = *Count of Accuracy Audits (Reporting Organization Accuracy Summary)*.

If either quarter in either half of the year has a *Count of Accuracy Audits (Reporting Organization Accuracy Summary)* of 1, then the source data for both quarters in that half will be merged for purposes of calculating the mean, and reported with the second quarter of the half (i.e., Q2 or Q4). In this case, there will be no value for the corresponding first quarter in the half (i.e., Q1 or Q3).

## 4.149 Mean (Reporting Organization Precision Summary)

### 4.149.1 Description

A measure of the central tendency of the applicable population of precision checks.

### 4.149.2 Source

System-generated via Precision Data (RP) Transaction, or Maintain Precision (L62).

### 4.149.3 Attributes

Type: Number

Length: 6.4

Required: No

### 4.149.4 Uses

Reporting Organization Precision Summaries

### 4.149.5 Value Assignment

#### 4.149.5.1 Analytical & Flow

$$D = \frac{\sum_{i=1}^n d_i}{n}$$

where:

$D$  = estimate of precision (mean),

$d_i$  = *Percent Difference* of a analytical or flow precision check,

$n$  = *Count of Precision Checks (Reporting Organization Precision Summary)*.

#### 4.149.5.2 Collocated (PM 2.5)

$$CV = \sqrt{\frac{\sum_{i=1}^n \left( \frac{|d_i|}{\sqrt{2}} \right)^2}{n}}$$

where:

$CV$  = coefficient of variation, i.e., estimate of precision,

$d_i$  = *Percent Difference* of a valid collocated data pair,

$n$  = *Count of Valid Collocated Data Pairs (Reporting Organization Precision Summary)*.

#### 4.149.6 Collocated (Other)

$$D = \frac{\sum_{i=1}^n d_i}{n}$$

where:

$D$  = estimate of precision (mean),

$d_i$  = *Percent Difference* of a valid collocated data pair,

$n$  = *Count of Valid Collocated Data Pairs (Reporting Organization Precision Summary)*.

##### 4.149.6.1 Federal Reference Method (FRM) Audit

$$D = \frac{\sum_{i=1}^n d_i}{n}$$

where:

$D$  = estimate of precision (mean),

$d_i$  = *Percent Difference* of an FRM audit pair,

$n$  = *Count of Precision Checks (Reporting Organization Precision Summary)* (i.e., FRM audits).

## **4.150 Measurement Scale**

### **4.150.1 Description**

A denotation of the geographic scope of the air quality measurements made by the monitor. The implication is that the same measurement made elsewhere within the measurement scale would produce an equivalent result to that produced at the monitoring site.

### **4.150.2 Source**

User-specified via the Basic Monitor Information (MA) Transaction, or AQS Maintain Monitor (L2).

### **4.150.3 Attributes**

Type: Character

Length: 20

Required: No

### **4.150.4 Uses**

Monitors

### **4.150.5 Value Assignment**

The value must exist on the *Measurement Scales* view.

## **4.151 Meteorological Site ID**

### **4.151.1 Description**

The AQS site ID where meteorological data is collected, if not collected at this site.

### **4.151.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.151.3 Attributes**

Type: Character

Length: 11

Required: No

### **4.151.4 Uses**

Sites

### **4.151.5 Value Assignment**

The value must reference an existing record on the *Sites* view.

## **4.152 Meteorological Site Type**

### **4.152.1 Description**

The type of meteorological station identified for the monitoring site. Required for sites with monitors in a Photochemical Assessment Monitoring System (PAMS) network.

### **4.152.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.152.3 Attributes**

Type: Character

Length: 20

Required: No

### **4.152.4 Uses**

Sites

### **4.152.5 Value Assignment**

The value must exist on the *Met Site Types* view

## **4.153 Method Code**

### **4.153.1 Description**

A code representing a particular method for collecting and analyzing samples of the specified parameter.

### **4.153.2 Source**

User-specified via the Monitor Protocol (MK), Raw Data (RD), or Composite Data (RC) Transactions, or AQS Maintain Monitor (L2).

### **4.153.3 Attributes**

Type: Character  
Length: 8  
Required: Yes

### **4.153.4 Uses**

Monitor Protocols

### **4.153.5 Value Assignment**

In combination with *Parameter*, the value must exist on the *Sampling Methodologies* view.

## **4.154 Minimum Beam Height**

### **4.154.1 Description**

The height of the beam (at the lowest point from the ground) being projected between the receiver and transmitter at the site, in meters.

### **4.154.2 Source**

### **4.154.3 Source**

User-specified via the Site Open Path Information (AC) Transaction, or AQS Maintain Site (L1).

### **4.154.4 Attributes**

Type: Number

Length: 8.2

Required: No

### **4.154.5 Uses**

Open Paths

## **4.155 Minimum Collection Frequency**

### **4.155.1 Description**

The code for the minimum collection frequency with which the yearly samples were reported.

### **4.155.2 Source**

System-generated via the Post process.

### **4.155.3 Attributes**

Type: Character

Length: 8

Required: No

### **4.155.4 Uses**

Annual Summaries

### **4.155.5 Value Assignment**

#### **4.155.5.1 Daily PM10**

Must be assigned a value, which is a code on the *Collection Frequencies* table.

#### **4.155.5.2 24-Hour PM10**

Always valued with “1”, which signifies “Every Day” on the *Collection Frequencies* table.

#### **4.155.5.3 Default**

Not valued.

## **4.156 Minimum Sample Value**

### **4.156.1 Description**

The lowest value for the year.

### **4.156.2 Source**

System-generated via the Post process.

### **4.156.3 Attributes**

Type: Number

Length: 5.5

Required: No

### **4.156.4 Uses**

Annual Summaries

### **4.156.5 Value Assignment**

#### **4.156.5.1 Ozone (1-Hour and 8-Hour)**

The lowest 1-hour or 8-hour *Maximum Value (Daily)* that occurred in the year, regardless of monitoring season or whether daily summary criteria were met.

#### **4.156.5.2 Non-Ozone National Ambient Air Quality Standards (NAAQS) Durations**

The lowest valid *Arithmetic Mean (NAAQS)* that occurred in the year.

#### **4.156.5.3 Default**

The lowest sample data value that occurred in the year.

## **4.157 Modified Date**

### **4.157.1 Description**

The date when the record was last modified.

### **4.157.2 Source**

System-generated via any of the AQS transactions, or any of the Maintain modules.

### **4.157.3 Attributes**

Type: Date

Length: Not applicable

Required: No

### **4.157.4 Uses**

Sites

Tangent Roads

Open Paths

Monitors

Monitor Pollutant Areas

Sample Periods

Monitor Type Assignments

Monitor Agency Roles

Monitor Objectives

Required Collection Frequencies

Sample Schedules

Monitor Tangent Roads

Probe Obstructions

Monitor Regulatory Compliances

Monitor Collocation Periods

Monitor Protocols

Accuracy Data

Precision Data

## **4.158 Modified User**

### **4.158.1 Description**

The Oracle ID of the user who last modified the record.

### **4.158.2 Source**

System-generated via any of the AQS transactions, or any of the Maintain modules.

### **4.158.3 Attributes**

Type: Character

Length: 40

Required: No

### **4.158.4 Uses**

Sites

Tangent Roads

Open Paths

Monitors

Monitor Pollutant Areas

Sample Periods

Monitor Type Assignments

Monitor Agency Roles

Monitor Objectives

Required Collection Frequencies

Sample Schedules

Monitor Tangent Roads

Probe Obstructions

Monitor Regulatory Compliances

Monitor Collocation Periods

Monitor Protocols

Accuracy Data

Precision Data

### **4.158.5 Value Assignment**

The value must exist on the *AIRS User Profiles* view.

## **4.159 Monitor ID**

### **4.159.1 Description**

The AIRS Monitor ID, which identifies the monitor to which the data applies.

### **4.159.2 Source**

User-specified by any of the following transactions:

- Basic Monitor Information (MA)
- Monitor Sampling Periods (MB)
- Monitor Type Information (MC)
- Monitor Agency Role (MD)
- Monitoring Objective Information (ME)
- Monitor Sampling Schedule (MF)
- Monitor Street Description (MG)
- Monitor Obstruction Information (MH)
- Monitor Regulatory Compliance (MI)
- Monitor Collocation Period (MJ)
- Monitor Protocol (MK)
- Composite Raw Data (RC)
- Raw Data (RD)
- Accuracy Data (RA)
- Precision Data (RP)
- Blank Data (RB)
- Annual Summary (RS)

or user-specified via any of the following AQS Maintenance Forms:

- Maintain Monitor (L2)
- Maintain Composite Data (L51)
- Maintain Blank Data (L53)
- Maintain Raw Data (L54)
- Maintain Accuracy Data (L62)
- Maintain Precision Data (L61)
- Maintain Annual Summary (L7)

or system-generated via the Post process, or system-generated via the Accuracy Data (RA) or Precision Data (RP) Transactions, or system-generated via AQS Maintain Accuracy Data (L62) or AQS Maintain Precision Data (L61).

### **4.159.3 Attributes**

Type: Character  
Length: 20  
Required: Yes

#### **4.159.4 Uses**

- Monitors
- Monitor Pollutant Areas
- Sample Periods
- Monitor Type Assignments
- Monitor Agency Roles
- Monitor Objectives
- Required Collection Frequencies
- Sample Schedules
- Monitor Tangent Roads
- Probe Obstructions
- Monitor Regulatory Compliances
- Monitor Collocation Periods
- Monitor Protocols
- Composite Data
- Composite Qualifier Details
- Raw Data
- Raw Qualifier Details
- Precision Data
- Accuracy Data
- Blank Data
- Blank Qualifier Details
- Comments
- NAAQS Averages
- Daily Summaries
- Quarterly Summaries
- Annual Summaries
- Summary Maximums
- Summary Percentiles
- Summary Protocols
- Monitor Precision Summaries
- Precision Summary Protocols
- Monitor Accuracy Summaries
- Accuracy Summary Protocols*

#### **4.159.5 Value Assignment**

The value is a concatenation of *State Code*, *County Code*, *Site ID*, *Parameter*, and *POC*, with each separated by “-”.

## **4.160 Monitor Objective Type**

### **4.160.1 Description**

Identification of the reason for measuring air quality by the monitor.

### **4.160.2 Source**

User-specified via the Monitoring Objective Information (ME) Transaction, or AQS Maintain Monitor (L2).

### **4.160.3 Attributes**

Type: Character

Length: 50

Required: Yes

### **4.160.4 Uses**

Monitor Objectives

### **4.160.5 Value Assignment**

The value must exist on the *Monitor Objective Types* view.

## **4.161 Monitor Protocol ID**

### **4.161.1 Description**

The sequential identification number used to distinguish combinations of sample duration, unit, method, collection frequency, composite type, and alternate method detectable limit (MDL) for a monitor.

### **4.161.2 Source**

User-specified via the Monitor Protocols (MK), Composite Data (RC), Raw Data (RD), Blanks Data (RB), Accuracy Data (RA), or Precision Data (RP) Transactions, or AQS Maintain Monitor (L2).

### **4.161.3 Attributes**

Type: Number

Length: 4.0

Required: Yes

### **4.161.4 Uses**

Monitor Protocols

Raw Data

Composite Data

Blank Data

Accuracy Data

Precision Data

## **4.162 Monitor Protocol ID (Annual)**

### **4.162.1 Description**

The ID for one of the protocols used to collect, analyze, and report the monitor's sample data for the year.

### **4.162.2 Source**

System-generated via the Post process.

### **4.162.3 Attributes**

Type: Number

Length: 4.0

Required: Yes

### **4.162.4 Uses**

Summary Protocols

## **4.163 Monitor Protocol ID (Monitor Accuracy Summary)**

### **4.163.1 Description**

The protocols used to collect, analyze, and report the audits for the time period.

### **4.163.2 Source**

System-generated via the Accuracy Data (RA) Transaction, or AQS Maintain Accuracy Data (L62).

### **4.163.3 Attributes**

Type: Number

Length: 4.0

Required: Yes

### **4.163.4 Uses**

Accuracy Summary Protocols

## **4.164 Monitor Protocol ID (Monitor Precision Summary)**

### **4.164.1 Description**

The protocols used to collect, analyze, and report the precision checks for the time period.

### **4.164.2 Source**

System-generated via the Precision Data (RP) Transaction, or AQS Maintain Precision Data (L61).

### **4.164.3 Attributes**

Type: Number

Length: 4.0

Required: Yes

### **4.164.4 Uses**

Precision Summary Protocols

## **4.165 Monitor Type**

### **4.165.1 Description**

An administrative classification for the monitor.

### **4.165.2 Source**

User-specified via the Monitor Type Information (MC), or AQS Maintain Monitor (L2).

### **4.165.3 Attributes**

Type: Character

Length: 20

Required: Yes

### **4.165.4 Uses**

Monitor Type Assignments

### **4.165.5 Value Assignment**

The value must exist on the *Monitor Types* view.

## **4.166 Monitor Type Begin Date**

### **4.166.1 Description**

The date on which the monitor type assignment went into effect

### **4.166.2 Source**

User-specified via the Monitor Type Information (MC), or AQS Maintain Monitor (L2).

### **4.166.3 Attributes**

Type: Date

Length: Not Applicable

Required: Yes

### **4.166.4 Uses**

Monitor Type Assignments

## **4.167 Monitor Type End Date**

### **4.167.1 Description**

The date on which a monitor type assignment ends.

### **4.167.2 Source**

User-specified via the Monitor Type Information (MC), or AQS Maintain Monitor (L2).

### **4.167.3 Attributes**

Type: Date

Length: Not Applicable

Required: No

### **4.167.4 Uses**

Monitor Type Assignments

## **4.168 Monthly Required Collection Frequency**

### **4.168.1 Description**

Specifies the collection frequency required for the Sample Schedule Month when the Required Collection Frequency Code represents “Stratified Random”, “Random”, or “Seasonal”.

### **4.168.2 Source**

User-specified via the Monitor Sampling Schedule (MF), or AQS Maintain Monitor (L2).

### **4.168.3 Attributes**

Type: Character

Length: 8

Required: Yes

### **4.168.4 Uses**

Sample Schedules

### **4.168.5 Value Assignment**

The value must exist on the *Collection Frequencies* view.

## **4.169 MSA Represented**

### **4.169.1 Description**

The Metropolitan Statistical Area (MSA) from which the concentrations originated, not the location of the monitor.

### **4.169.2 Source**

User-specified via the Monitoring Objective Information (ME) Transaction, or AQS Maintain Monitor (L2).

### **4.169.3 Attributes**

Type: Character  
Length: 8  
Required: No

### **4.169.4 Uses**

Monitor Objectives

### **4.169.5 Value Assignment**

Must have a value if neither *CMSA Represented* nor *Urban Area Represented* is valued. Conversely, may not have a value if either *CMSA Represented* or *Urban Area Represented* is valued. If valued, that value must exist on the *MSAs* view.

## **4.170 NAAQS Date/Time**

### **4.170.1 Description**

The date and hour identifying a National Ambient Air Quality Standards (NAAQS) average.

### **4.170.2 Source**

System-generated via the Post process.

### **4.170.3 Attributes**

Type: Date

Length: Not Applicable

Required: Yes

### **4.170.4 Uses**

NAAQS Averages

### **4.170.5 Value Assignment**

#### **4.170.5.1 8-Hour Ozone**

The first hour of the 8-hour period.

#### **4.170.5.2 8-Hour Carbon Monoxide**

The last hour of the 8-hour period.

#### **4.170.5.3 3-Hour Sulfur Dioxide**

The last hour of the 3-hour period.

#### **4.170.5.4 24-Hour Sulfur Dioxide, PM10, & PM2.5**

The last hour of the 24-hour period.

## **4.171 Number of Samples**

### **4.171.1 Description**

Indicates the number of samples that were combined to yield the composite sample value.

### **4.171.2 Source**

User-specified via the Composite Data (RC) Transaction, or AQS Maintain Composite Data (L51).

### **4.171.3 Attributes**

Type: Number

Length: 10.0

Required: Yes

### **4.171.4 Uses**

Composite Data

## **4.172 Open Path Number**

### **4.172.1 Description**

A unique numeric identifier for the individual open path at a site. Each open path represents a different monitor.

### **4.172.2 Source**

User-specified via the Site Open Path Information (AC) Transaction, or AQS Maintain Site (L1).

### **4.172.3 Attributes**

Type: Number

Length: 12.0

Required: Yes

### **4.172.4 Uses**

Open Paths

Monitors

## **4.173 Parameter**

### **4.173.1 Description**

The code assigned to the parameter measured by the monitor. Parameters may be pollutants or non-pollutants.

### **4.173.2 Source**

User-specified

### **4.173.3 Attributes**

Type: Character

Length: 5

Required: Yes

### **4.173.4 Uses**

Monitors

Reporting Organization Precision Summaries

Reporting Organization Accuracy Summaries

## **4.174 Percent Difference**

### **4.174.1 Description**

The measure of variation between the values in a precision check or accuracy audit value pair.

### **4.174.2 Source**

System-generated via the Accuracy Data (RA) or Precision Data (RP) Transactions, or AQS Maintain Accuracy (L62), or AQS Maintain Precision (L61).

### **4.174.3 Attributes**

Type: Number

Length: Unbounded

Required: Yes

### **4.174.4 Uses**

Precision Data

Accuracy Data

### **4.174.5 Value Assignment**

#### **4.174.5.1 Analytical & Flow**

$$d = \frac{(Y - X)}{X} * 100$$

where:

$d$  = percent difference,

$Y$  = indicated concentration or flow rate,

$X$  = actual, or known, concentration or flow rate,

#### 4.174.5.2 Collocated

$$d = \frac{(Y - X)}{\left(\frac{(Y + X)}{2}\right)} * 100$$

where:

$d$  = percent difference,

$X$  = measurement produced by primary sampler (routine monitor), i.e., the Actual Value,

$Y$  = measurement produced by duplicate sampler (monitor used for quality control), i.e., the Indicated Value.

#### 4.174.5.3 Federal Reference Method (FRM) Audit

$$d = \frac{(Y - X)}{X} * 100$$

where:

$d$  = percent difference,

$Y$  = measurement produced from the state-operated sampler, i.e. Indicated Value,

$X$  = measurement produced from the Performance Evaluation Program (PEP) sampler, i.e., Actual Value.

## **4.175 Percent of Observations (Annual)**

### **4.175.1 Description**

The percent of actual data values that were reported compared to the number of data values that could have been reported for the year.

### **4.175.2 Source**

System-generated via the Post process, or user-generated via either the Annual Summaries (RS) Transaction or Maintain Annual Summaries (L7).

### **4.175.3 Attributes**

Type: Number

Length: 6.4

Required: No

### **4.175.4 Uses**

Annual Summaries

### **4.175.5 Value Assignment**

The value is always rounded to the integer.

#### **4.175.5.1 1-Hour & 8-Hour Ozone**

$$p = \left( \frac{v}{r} \right) * 100$$

where:

$p$  = percentage,

$v$  = *Count of Valid Days*,

$r$  = *Count of Required Days*.

#### **4.175.5.2 Daily & 24-Hour PM2.5 & PM10**

$$p = \left( \frac{v}{m} \right) * 100$$

where:

$p$  = percentage,

$v$  = *Count of Valid Days*,

$m$  = number of scheduled days (i.e., *Count of Required Days*).

#### 4.175.5.3 8-Hour Carbon Monoxide, and 3-Hour & 24-Hour Sulfur Dioxide

Not valued.

#### 4.175.5.4 Default Daily

Not valued.

#### 4.175.5.5 Default Hourly

$$p = \left( \frac{n}{\left( a * \frac{24}{l} \right)} \right) * 100$$

where:

- $p$  = observation percentage,
- $n$  = *Count of Observations (Annual)*,
- $l$  = duration length (in hours),
- $a$  = number of active days in the year.

## **4.176 Percent of Observations (Daily)**

### **4.176.1 Description**

The percent of actual data values that were reported compared to the number of data values that could have been reported for the 24-hour period.

### **4.176.2 Source**

System-generated via the Post process.

### **4.176.3 Attributes**

Type: Number

Length: 6.4

Required: No

### **4.176.4 Uses**

Daily Summaries

### **4.176.5 Value Assignment**

The value is always rounded to the integer.

$$p = \left( \frac{n}{\left( \frac{24}{l} \right)} \right) * 100$$

where:

$p$  = observation percentage,  
 $n$  = *Count of Observations (Daily)*,  
 $l$  = duration length (in hours).

## 4.177 Percent of Observations (Quarterly)

### 4.177.1 Description

The percent of actual data values that were reported compared to the number of data values that could have been reported for the quarter.

### 4.177.2 Source

System-generated via the Post process.

### 4.177.3 Attributes

Type: Number

Length: 6.4

Required: No

### 4.177.4 Uses

Quarterly Summaries

### 4.177.5 Value Assignment

The value is always rounded to the integer.

#### 4.177.5.1 1-Hour & 8-Hour Ozone

$$p = \left( \frac{n}{(q * 24)} \right) * 100$$

where:

$p$  = observation percentage,

$n$  = number of samples or 8-hour averages in the quarter, regardless of monitoring season, (i.e., *Count of Observations (Quarterly)*),

$q$  = number of active days in the quarter, regardless of monitoring season.

#### 4.177.5.2 24-Hour PM2.5 & PM10

$$p = \left( \frac{n}{q} \right) * 100$$

where:

$p$  = observation percentage,

$n$  = number of valid 24-hour block averages (i.e., *Number of Observations (Quarterly)*),

$q$  = number of active days in the quarter.

#### 4.177.5.3 Daily PM10

$$p = \left( \frac{v}{q} \right) * 100$$

where:

$p$  = observation percentage,

$v$  = number of valued strata (i.e., *Count of Valid Days*),

$r$  = number of scheduled days (i.e., *Count of Required Days*).

A valid stratum is one where the scheduled day occurs in the quarter and at least one observation occurs in the stratum.

Scheduled days are the number of days within the quarter that were scheduled for sampling, as determined by the EPA-defined calendar for the required collection frequency, and which also fall within the period of operation, as defined by sampling periods.

Seasonal and random frequencies are sub-divided in monthly-required frequencies; otherwise, the required frequency applies to a defined period of time

The reference point for the EPA calendar is January 4, 1956. For example, in the year 2003, the every 6<sup>th</sup> day calendar would comprise: 1/3/2003, 1/9/2003, 1/15/2003, etc., and the every 3<sup>rd</sup> day calendar would comprise: 1/3/2003, 1/6/2003, 1/9/2003, 1/12/2003, etc. For a monitor doing seasonal sampling, with every 6<sup>th</sup> day sampling in April and every 3<sup>rd</sup> day sampling in May, both months in 2003, the schedule would be as follows: 4/15/03, 4/21/03, 4/27/03, 5/3/03, 5/6/03, 5/9/03, etc.

#### 4.177.5.4 PM2.5

$$p = \left( \frac{v}{r} \right) * 100$$

where:

$p$  = observation percentage,

$v$  = *Count of Valid Days*,

$r$  = number of scheduled days (i.e., *Count of Required Days*).

Valid days are equal to the sum of valued, scheduled sampling days, plus make-ups for missing scheduled days. A make-up day is a sample recorded in the same stratum as, or exactly seven days after, a missing scheduled sample. In both conditions, the make-up sample must occur within the same quarter as the missed sample. A maximum of five make-up samples are allowed per quarter.

Scheduled days are the number of days within the quarter that were scheduled for sampling, as determined by the EPA-defined calendar for the required collection frequency, and which also fall within a period of operation, as defined in sampling periods.

Seasonal and random frequencies are sub-divided in monthly-required frequencies; otherwise, the required frequency applies to a defined period of time. A PM2.5 monitor must have a defined collection frequency for each active day, by rule.

The reference point for the EPA calendar is January 4, 1956. For example, in the year 2003, the every 6<sup>th</sup> day calendar would comprise: 1/3/2003, 1/9/2003, 1/15/2003, etc., and the every 3<sup>rd</sup> day calendar would comprise: 1/3/2003, 1/6/2003, 1/9/2003, 1/12/2003, etc. For a monitor doing seasonal sampling, with every 6<sup>th</sup> day sampling in April and every 3<sup>rd</sup> day sampling in May, the scheduled days for 2003 would be as follows: 4/15/03, 4/21/03, 4/27/03, 5/3/03, 5/6/03, 5/9/03, etc.

#### 4.177.5.5 Default Hourly

$$p = \left( \frac{n}{\left( a * \frac{24}{l} \right)} \right) * 100$$

where:

$p$  = observation percentage,

$n$  = *Count of Observations (Quarterly)*,

$l$  = duration length (in hours),

$a$  = number of active days in the quarter.

**4.177.5.6 Default Daily**

Not valued.

## **4.178 Percentile**

### **4.178.1 Description**

An EPA-assigned percentile level for which a *Percentile Sample Value* is determined.

### **4.178.2 Source**

System-generated via the Post Process, or user-specified via the Annual Summary (RS) Transaction or AQS Maintain Annual Summary (L7).

### **4.178.3 Attributes**

Type: Number

Length: 3

Required: Yes

### **4.178.4 Uses**

Summary Percentiles

### **4.178.5 Value Assignment**

The possible values are: 10, 25, 50, 75, 90, 95, 98, and 99.

## 4.179 Percentile Sample Value

### 4.179.1 Description

The value for the year where there are  $k$  values less than or equal to it, where  $k$  is the calculated rank for the *Percentile*.

### 4.179.2 Source

System-generated via the Post Process, or user-specified via the Annual Summary (RS) Transaction or AQS Maintain Annual Summary (L7).

### 4.179.3 Attributes

Type: Number  
Length: 5.5  
Required: Yes

### 4.179.4 Uses

Summary Percentiles  
In forms and reports there are 8 instances of this field with values based on the *Percentile*.

### 4.179.5 Value Assignment

#### 4.179.5.1 Ozone 1-Hour & 8-Hour

The 1-hour or 8-hour *Maximum Value (Daily)* where there are  $k$  *Maximum Value (Daily)* values less than or equal to it, where  $k$  is the calculated rank for the *Percentile*. The formula for determining the rank is:

$$k = \text{CEILING}\left(v * \left(\frac{p}{100}\right)\right)$$

where:

$k$  = percentile rank  
 $p$  = *Percentile*,  
 $v$  = *Count of Valid Days*.

Note: A CEILING function returns the smallest integer higher than, or equal to, the given number.

#### 4.179.5.2 Daily Non-Seasonal PM2.5

The sample value where there are  $k$  values less than or equal to it, where  $k$  is the calculated rank for the percentile. The formula for determining the rank is:

$$k = \text{CEILING} \left( \sum_{q=1}^4 \text{MINIMUM}(r_q, n_q) * \left( \frac{p}{100} \right) \right) + n - \left( \sum_{q=1}^4 \text{MINIMUM}(r_q, n_q) \right)$$

where:

- $k$  = percentile rank
- $r_q$  = number of required samples for the quarter,
- $n_q$  = number of actual samples for the quarter,
- $q$  = quarter,
- $p$  = Percentile,
- $n$  = Count of Observations (Annual).

Note: A CEILING function returns the smallest integer higher than, or equal to, the given number. A MINIMUM function returns the least of a series of numbers.

#### 4.179.5.3 Daily Seasonal PM2.5

The minimum sample value that makes:

$$W(x) > \left( \frac{p}{100} \right)$$

where:

$$W(x) = \left( \left( \frac{d_h}{d_h + d_l} \right) * F_h(x) \right) + \left( \left( \frac{d_l}{d_h + d_l} \right) * F_l(x) \right)$$

where:

$d_h$  = number of calendar days in the high season,

$d_l$  = number of calendar days in the low season,

$p$  = Percentile,

$x$  = the measured concentration, and

$$F_a(x) = \frac{l_a}{n_a}$$

where:

$a$  = high or low,

$l_a$  = number of samples in season  $a$  that are  $\leq x$ ,

$n_a$  = number of samples in season  $a$ .

The high season are those months where the monthly required frequency is that with minimum daily interval for the year; the low season is all others months.

(Reference: EPA-454/R-99-008 Guideline on Data Handling Conventions for the PM NAAQS)

#### 4.179.5.4 Hourly and Non-PM2.5 Daily

The sample value where there are  $k$  sample values less than or equal to it, where  $k$  is the calculated rank for the percentile. The formula for calculating the rank is:

$$k = \text{CEILING}\left(n * \left(\frac{p}{100}\right)\right)$$

where:

- $k$  = percentile rank
- $p$  = *Percentile*,
- $n$  = *Count of Observations (Annual)*.

Note: A CEILING function returns the smallest integer higher than, or equal to, the given number.

#### 4.179.5.5 Non-Ozone National Ambient Air Quality Standards (NAAQS)

The valid 8-hour average where there are  $k$  valid 8-hour averages less than or equal to it, where  $k$  is the calculated rank for the percentile. The formula for calculating the rank is:

$$k = \text{CEILING}\left(n * \left(\frac{p}{100}\right)\right)$$

where:

- $k$  = percentile rank
- $p$  = *Percentile*,
- $n$  = *Count of Observations (Annual)*.

Note: A CEILING function returns the smallest integer higher than, or equal to, the given number.

## **4.180 POC**

### **4.180.1 Description**

Pollutant Occurrence Code. An identifier used to distinguish between multiple monitors at the same site that are measuring the same parameter. For example, the first monitor established to measure carbon monoxide (CO) at a site could have a *POC* of 1. If an additional monitor were established at the same site to measure CO, that monitor could have a *POC* of 2. However, if a new instrument were installed to replace the original instrument used as the first monitor, that would be the same monitor and it would still have a *POC* of 1.

For criteria pollutants, data from different sampling methods should only be stored under the same *POC* if the sampling intervals are the same and the methods are reference or equivalent. For sites where duplicate sampling is being conducted by multiple agencies or by one agency with multiple samplers, multiple *POCs* must be utilized to store all samples.

For non-criteria pollutants, data from multiple sampling methods can be stored under the same *POC* if the sampling intervals are the same and there is only one sample for the time reported. If multiple open path monitors are reporting data for the same parameter, each open path would be assigned a different *POC*.

### **4.180.2 Source**

User-specified via the Basic Monitor Information (MA) Transaction, or AQS Maintain Monitor (L2).

### **4.180.3 Attributes**

Type: Number  
Length: 2.0  
Required: Yes

### **4.180.4 Uses**

Monitors

## **4.181 Pollutant Area Code**

### **4.181.1 Description**

Designation of a pollutant area to which the monitor is assigned. Pollutant areas are geographic areas defined by a program office in which a certain pollutant should be closely watched. Most are problem or non-attainment areas, but attainment areas requiring special attention may also be defined. Types of pollutant areas are: status areas, monitoring areas, and monitor planning areas.

### **4.181.2 Source**

User-specified, via the Monitor Basic (MA) Transaction, or Maintain Monitor (L2).

### **4.181.3 Attributes**

Type: Character

Length: 5

Required: Yes

### **4.181.4 Uses**

Monitor Pollutant Areas. There are 5 pollutant areas that can be defined for a monitor.

### **4.181.5 Value Assignment**

The value must exist on the *Pollutant Areas* view, and the corresponding type must be valid for the *Parameter*.

## **4.182 Pollutant Area Type**

### **4.182.1 Description**

Types of pollutant areas, such as status area, monitoring area, monitor-planning area.

### **4.182.2 Source**

System-generated, via the Monitor Basic (MA) Transaction (), or Maintain Monitor (L2).

### **4.182.3 Attributes**

Type: Character

Length: 40

Required: Yes

### **4.182.4 Uses**

Monitor Pollutant Areas

### **4.182.5 Value Assignment**

The value must exist on the *Pollutant Area Types* view.

## **4.183 Precision Class**

### **4.183.1 Description**

Description of the class of precision check taken at the monitor.

### **4.183.2 Source**

System-generated, via the Precision Data (RP) Transaction (), or Maintain Precision Data (L61).

### **4.183.3 Attributes**

Type: Character

Length: 20

Required: Yes

### **4.183.4 Uses**

Precision Data

Monitor Precision Summaries

Precision Summary Protocols

Reporting Organization Precision Summaries

### **4.183.5 Value Assignment**

#### **4.183.5.1 Precision Data**

1. If the method is automated (continuous), and the unit is not a flow unit, and the reported duration is not 24-hour block average, then the class is “Analytical”. This class will generally include gaseous criteria pollutants, such as ozone (O3), carbon monoxide (CO), sulfur dioxide (SO2), and nitrogen dioxide (NO2), that were recorded using automated methods.
2. If the method is either automated or manual (intermittent), and the unit is a flow unit, then the class is “Flow”. This category will generally include particulate criteria pollutants, such as lead (Pb), PM2.5 and PM10, that were recorded using automated methods.
3. If the method is manual and the unit is not a flow unit, or the method is automated, the unit is not a flow unit, and the duration is a 24-hour block average, then the class is “Collocated”. This category will include particulate criteria pollutants such as PM2.5 (both manual and automated) and PM10 (manual only).

#### **4.183.5.2 Monitor & Reporting Organization Precision Summaries**

The *Precision Class* specified for the precision checks that are being aggregated in the summary.

## **4.184 Precision Date**

### **4.184.1 Description**

The calendar date for which the precision check is being reported.

### **4.184.2 Source**

User-specified, via the Precision Data (RP) Transaction (), or Maintain Precision Data (L61).

### **4.184.3 Attributes**

Type: Date

Length: Not Applicable

Required: Yes

### **4.184.4 Uses**

Precision Data

## **4.185 Precision ID**

### **4.185.1 Description**

A sequentially assigned number used to identify a particular precision check from others, when multiple checks are performed on the same day.

### **4.185.2 Source**

User-specified, via the Precision Data (RP) Transaction (), or Maintain Precision Data (L61).

### **4.185.3 Attributes**

Type: Number

Length: 2.0

Required: Yes

### **4.185.4 Uses**

Precision Data

## **4.186 Precision Sample ID**

### **4.186.1 Description**

The unique identity (ID) number of the reference sample used to challenge the instrument.

### **4.186.2 Source**

User-specified, via the Precision Data (RP) Transaction (), or Maintain Precision Data (L61).

### **4.186.3 Attributes**

Type: Character

Length: 10

Required: No

### **4.186.4 Uses**

Precision Data

## **4.187 Precision Scale**

### **4.187.1 Description**

Indicates the number of places to the right of the decimal point provided by the data owner at submission, including trailing zeros.

### **4.187.2 Source**

System-generated, via the Precision Data (RP) Transaction (), or Maintain Precision Data (L61).

### **4.187.3 Attributes**

Type: Number

Length: 1.0

Required: Yes

### **4.187.4 Uses**

Precision Data

## **4.188 Primary Qualifier Code**

### **4.188.1 Description**

The primary qualifier for a raw, composite, or blank sample.

### **4.188.2 Source**

User-specified or system-generated, via the Raw Data (RD), Composite Data (RC), or Blank Data (RB) Transactions, or AQS Maintain Raw Data (L54), Maintain Composite Data (L51), or Maintain Blank Data (L53).

### **4.188.3 Attributes**

Type: Character

Length: 8

Required: No

### **4.188.4 Uses**

Raw Data

Composite Data

Blank Data

### **4.188.5 Value Assignment**

If the user specifies a Null Data code, that value is always assigned, else, it is replicated from the corresponding *Qualifier Details (Raw, Composite, or Blank)* for the record, according to the following hierarchy:

1. Exceptional Event codes,
2. Natural Event codes,
3. The code for “Validated Value”,
4. Any other qualifier code.

Note: Null Data codes are not valid for *Composite Data*.

## **4.189 Primary Qualifier Type**

### **4.189.1 Description**

The qualifier type of the *Primary Qualifier Code*.

### **4.189.2 Source**

User-specified or system-generated, via the Raw Data (RD), Composite Data (RC), or Blank Data (RB) Transactions, or AQS Maintain Raw Data (L54), Maintain Composite Data (L51), or Maintain Blank Data (L53).

### **4.189.3 Attributes**

Type: Character

Length: 8

Required: No

### **4.189.4 Uses**

Raw Data

Composite Data

Blank Data

## **4.190 Primary Sampler Indicator**

### **4.190.1 Description**

Indicates whether the monitor is the primary or duplicate monitor in a collocated monitor pair.

### **4.190.2 Source**

User-specified, via the Monitor Collocation Period (MJ) Transaction (), or Maintain Monitor (L2).

### **4.190.3 Attributes**

Type: Character

Length: 1

Required: Yes

### **4.190.4 Uses**

Monitor Collocation Periods

### **4.190.5 Value Assignment**

The value must be “Y”, which indicates the monitor is the primary sampler, or “N”, which indicates that it is the duplicate sampler.

## **4.191 Primary Sampler Monitor ID**

### **4.191.1 Description**

The monitor ID of the duplicate sampler's primary sampler in the collocated pair.

### **4.191.2 Source**

System-generated, via the Monitor Collocation Period (MJ) Transaction (), or Maintain Monitor (L2).

### **4.191.3 Attributes**

Type: Character

Length: 20

Required: No

### **4.191.4 Uses**

Monitor Collocation Periods

### **4.191.5 Value Assignment**

Must be valued when *Primary Sampler Indicator* is "N"; may not be valued when it is "Y".

## **4.192 Probe Height**

### **4.192.1 Description**

The height of the sampling probe from the ground in meters.

### **4.192.2 Source**

User-specified via the Basic Monitor Information (MA) Transaction, or AQS Maintain Monitor (L2).

### **4.192.3 Attributes**

Type: Number

Length: 8.2

Required: No

### **4.192.4 Uses**

Monitors

## **4.193 Probe Horizontal Distance**

### **4.193.1 Description**

The horizontal distance, in meters, of the probe from its supports.

### **4.193.2 Source**

User-specified via the Basic Monitor Information (MA) Transaction, or AQS Maintain Monitor (L2).

### **4.193.3 Attributes**

Type: Number

Length: 8.2

Required: No

### **4.193.4 Uses**

Monitors

## **4.194 Probe Location**

### **4.194.1 Description**

The location of the sampling probe.

### **4.194.2 Source**

User-specified via the Basic Monitor Information (MA) Transaction, or AQS Maintain Monitor (L2).

### **4.194.3 Attributes**

Type: Character

Length: 20

Required: No

### **4.194.4 Uses**

Monitors

### **4.194.5 Value Assignment**

The value must exist on the *Probe Locations* view.

## **4.195 Probe Obstruction Height**

### **4.195.1 Description**

The height, in meters, of the top of the obstruction above the probe.

### **4.195.2 Source**

User-specified via the Monitor Obstruction Information (MH) Transaction, or AQS Maintain Monitor (L2).

### **4.195.3 Attributes**

Type: Number

Length: 8.2

Required: Yes

### **4.195.4 Uses**

Probe Obstructions

## **4.196 Probe Obstruction Type**

### **4.196.1 Description**

The type of obstruction responsible for the restricted airflow of a monitor.

### **4.196.2 Source**

User-specified via the Monitor Obstruction Information (MH) Transaction, or AQS Maintain Monitor (L2).

### **4.196.3 Attributes**

Type: Character

Length: 20

Required: Yes

### **4.196.4 Uses**

Probe Obstructions

### **4.196.5 Value Assignment**

The value must exist on the *Probe Obstruction Types* view

## **4.197 Probe Vertical Distance**

### **4.197.1 Description**

The vertical distance, in meters, of the probe from its supports.

### **4.197.2 Source**

User-specified via the Basic Monitor Information (MA) Transaction, or AQS Maintain Monitor (L2).

### **4.197.3 Attributes**

Type: Number

Length: 8.2

Required: No

### **4.197.4 Uses**

Monitors

## **4.198 Project Class**

### **4.198.1 Description**

The code for the type of sampling performed by the monitor.

### **4.198.2 Source**

User-specified via the Basic Monitor Information (MA) Transaction, or AQS Maintain Monitor (L2).

### **4.198.3 Attributes**

Type: Character

Length: 8

Required: No

### **4.198.4 Uses**

Monitors

### **4.198.5 Value Assignment**

The value must exist on the *Project Types* view.

## **4.199 Qualifier Code**

### **4.199.1 Description**

Qualifications used to describe the sample data point. They may document exceptional data events that are natural or anthropogenic, or quality assurance exceptions.

### **4.199.2 Source**

User-specified, via the Raw Data (RD), Blank Data (RB), or Composite Data (RC) Transactions, or AQS Maintain Raw Data (L54), Maintain Blank Data (L53), or Maintain Composite Data (L51).

### **4.199.3 Attributes**

Type: Character

Length: 8

Required: Yes

### **4.199.4 Uses**

Raw Qualifier Details

Composite Qualifier Details

Blank Qualifier Details

Data records can contain up to 10 qualifier codes

### **4.199.5 Value Assignment**

The value must exist on the *Qualifiers* view.

The value must be a type allowed for the pollutant parameter.

Only one Null type qualifier is allowed per record

A Null type Qualifier code precludes entry of other Qualifier Codes

A Null type Qualifier Code requires an empty Sample Value in the Record.

## **4.200 Qualifier Code- Null Data**

### **4.200.1 Description**

Qualifications used to describe the sample data point. They may document exceptional data events that are natural or anthropogenic, or quality assurance exceptions.

### **4.200.2 Source**

User-specified, via the Raw Data (RD) transactions, or AQS Maintain Raw Data (L54)

### **4.200.3 Attributes**

Type: Character

Length: 8

Required: Yes

### **4.200.4 Uses**

Raw Qualifier Details

### **4.200.5 Value Assignment**

On Data Input: A Null Data value precludes entry of other Qualifier Codes. Code is stored in Qualifier Code field.

The value must exist as a NULL type in the *Qualifiers* view.

The value must be a type allowed for the pollutant parameter.

Only one Null Data qualifier is allowed per record

## **4.201 Quarter Represented**

### **4.201.1 Description**

The quarter represented by the audit.

### **4.201.2 Source**

User-specified or system-generated, via the Accuracy Data (RA) Transaction (), or Maintain Accuracy Data (L62).

### **4.201.3 Attributes**

Type: Number

Length: 1.0

Required: Yes

### **4.201.4 Uses**

Accuracy Data

### **4.201.5 Value Assignment**

#### **4.201.5.1 Lead**

User-specified, via the Accuracy Data (RA) Transaction (), or AQS Maintain Accuracy Data (L62).

#### **4.201.5.2 Default**

Derived from the record's *Accuracy Date* value.

## **4.202 Recording Mode**

### **4.202.1 Description**

A term that describes how the methods recorded the source samples.

### **4.202.2 Source**

System-generated, via the Accuracy Data (RA) or Precision Data (RP) Transactions, or AQS Maintain Precision Data (L61) or Maintain Accuracy Data (L62).

### **4.202.3 Attributes**

Type: Character

Length: 30

Required: Yes

### **4.202.4 Uses**

Monitor Precision Summaries

Reporting Organization Precision Summaries

Monitor Accuracy Summaries

Accuracy Summary Protocols

Reporting Organization Accuracy Summaries

### **4.202.5 Value Assignment**

The possible values are: CONTINUOUS (i.e., Automated), and INTERMITTENT (i.e., Manual). The value is derived from the applicable methodology records.

## **4.203 Reference Point**

### **4.203.1 Description**

A term that describes the place for which locational coordinates were determined.

This data element is required by EPA Locational Data Policy. More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website (<http://www.epa.gov/edr/>).

### **4.203.2 Source**

System-generated via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.203.3 Attributes**

Type: Character

Length: 50

Required: Yes

### **4.203.4 Uses**

Sites

### **4.203.5 Value Assignment**

Always "MONITORING POINT".

## **4.204 Regulation Code**

### **4.204.1 Description**

A code, which represents an EPA regulation for which compliance documentation is required.

### **4.204.2 Source**

User-specified via the Monitor Regulation Compliance (MI) Transaction, or AQS Maintain Monitor (L2).

### **4.204.3 Attributes**

Type: Character

Length: 8

Required: Yes

### **4.204.4 Uses**

Monitor Regulatory Compliances

### **4.204.5 Value Assignment**

<b>Code</b>	<b>Description</b>
RM	Reference Method Used
SC	Siting Criteria Met
QC	Quality Assurance Criteria Met
FC	First PM10 Exceedance Correction
ST	Short Term Satisfied

## **4.205 Reported Sample Value**

### **4.205.1 Description**

The value of an observation being reported.

### **4.205.2 Source**

User-specified via the Raw Data (RD) or Composite Data (RC) Transactions, AQS Maintain Raw Data (L54), or AQS Maintain Composite Data (L51).

### **4.205.3 Attributes**

Type: Number

Length: 5.5

Required: No

### **4.205.4 Uses**

Raw Data

Composite Data

## **4.206 Reported Scale**

### **4.206.1 Description**

Indicates the number of places to the right of the decimal point provided by the data owner at submission, including trailing zeros.

### **4.206.2 Source**

System-generated via the Raw Data (RD) or Composite Data (RC) Transactions, AQS Maintain Raw Data (L54), or AQS Maintain Composite Data (L51).

### **4.206.3 Attributes**

Type: Number

Length: 1.0

Required: No

### **4.206.4 Uses**

Raw Data

Composite Data

## **4.207 Reported Unit**

### **4.207.1 Description**

The dimensional system in which a pollutant concentration or parameter reading is expressed.

### **4.207.2 Source**

User-specified via the Monitor Protocol (MK), Raw Data (RD), or Composite Data (RC) Transactions, or AQS Maintain Monitor (L2).

### **4.207.3 Attributes**

Type: Character

Length: 3

Required: Yes

### **4.207.4 Uses**

Monitor Protocols

### **4.207.5 Value Assignment**

The value must exist on the *Units* view

## **4.208 Reporting Organization**

### **4.208.1 Description**

A code that identifies the agency that generated the source precision or accuracy data for the summary.

### **4.208.2 Source**

System-generated, via the Accuracy Data (RA) or Precision Data (RP) Transactions, or AQS Maintain Precision Data (L61) or Maintain Accuracy Data (L62).

### **4.208.3 Attributes**

Type: Character

Length: 8

Required: Yes

### **4.208.4 Uses**

Monitor Precision Summaries

Precision Summary Protocols

Reporting Organization Precision Summaries

Monitor Accuracy Summaries

Accuracy Summary Protocols

Reporting Organization Accuracy Summaries

## **4.209 Required Collection Frequency Begin Date**

### **4.209.1 Description**

The date on which the Required Collection Frequency (RCF) went into effect.

### **4.209.2 Source**

User-specified via the Monitor Sampling Schedule (MF) Transaction, or AQS Maintain Monitor (L2).

### **4.209.3 Attributes**

Type: Date

Length: Not Applicable

Required: Yes

### **4.209.4 Uses**

Required Collection Frequencies

Sample Schedules

## **4.210 Required Collection Frequency Code**

### **4.210.1 Description**

The Required Collection Frequency (RCF), required by either Photochemical Assessment Monitoring System (PAMS) regulations for organic compounds: PM-2.5 or PM-10 monitors.

### **4.210.2 Source**

User-specified via the Monitor Sampling Schedule (MF) Transaction, or AQS Maintain Monitor (L2).

### **4.210.3 Attributes**

Type: Character

Length: 8

Required: Yes

### **4.210.4 Uses**

Required Collection Frequencies

### **4.210.5 Value Assignment**

The value must exist on the *Collection Frequencies* view.

## **4.211 Required Collection Frequency End Date**

### **4.211.1 Description**

The date on which the Required Collection Frequency (RCF) ended.

### **4.211.2 Source**

User-specified via the Monitor Sampling Schedule (MF) Transaction, or AQS Maintain Monitor (L2).

### **4.211.3 Attributes**

Type: Date

Length: Not Applicable

Required: No

### **4.211.4 Uses**

Required Collection Frequencies

## **4.212 Road Type**

### **4.212.1 Description**

The type of road or street being described.

### **4.212.2 Source**

User-specified via the Site Street Information (AB) Transaction, or AQS Maintain Site (L1).

### **4.212.3 Attributes**

Type: Character

Length: 20

Required: Yes

### **4.212.4 Uses**

Tangent Roads

### **4.212.5 Value Assignment**

The value must exist on the *Road Types* view

## **4.213 Sample Date**

### **4.213.1 Description**

The calendar date at which the sample data was recorded.

### **4.213.2 Source**

User-specified via the Raw Data (RD) Transaction, or AQS Maintain Raw Data (L51).

### **4.213.3 Attributes**

Type: Date

Length: 8

Required: Yes

### **4.213.4 Uses**

Forms and Reports

### **4.213.5 Value Assignment**

On input: Coupled with Sample Time to set Sample Date/Time

On output: Extracted from Sample Date/Time

## **4.214 Sample Date/Time**

### **4.214.1 Description**

The date and time for which the observation is being reported.

### **4.214.2 Source**

User-specified via the Raw Data (RD) Transaction, or AQS Maintain Raw Data (L54).

### **4.214.3 Attributes**

Type: Date

Length: Not Applicable

Required: Yes

### **4.214.4 Uses**

Raw Data

Raw Qualifier Details

## **4.215 Sample Residence Time**

### **4.215.1 Description**

The time in seconds for the sample to move from the probe inlet to the monitor.

### **4.215.2 Source**

User-specified via the Basic Monitor Information (MA) Transaction, or AQS Maintain Monitor (L2).

### **4.215.3 Attributes**

Type: Number

Length: 8.2

Required: No

### **4.215.4 Uses**

Monitors

## **4.216 Sample Schedule Month**

### **4.216.1 Description**

The month number for which a Monthly Required Collection Frequency applies.

### **4.216.2 Source**

System-generated via the Monitor Sampling Schedule (MF) Transaction, or AQS Maintain Monitor (L2).

### **4.216.3 Attributes**

Type: Number

Length: 2.0

Required: Yes

### **4.216.4 Uses**

Sample Schedules

### **4.216.5 Value Assignment**

Number	Month
1	January
2	February
3	March
4	April
5	May
6	June
7	July
8	August
9	September
10	October
11	November
12	December

## **4.217 Sample Time**

### **4.217.1 Description**

The 24-hour clock time at which the sampling for the reported observation began, in standard time at the location of the monitoring site.

### **4.217.2 Source**

User-specified via the Raw Data (RD) Transaction, or AQS Maintain Raw Data (L51).

### **4.217.3 Attributes**

Type: Date

Length: 5

Required: Yes

### **4.217.4 Uses**

Forms and Reports

### **4.217.5 Value Assignment**

On input: Coupled with Sample Date to set Sample Date/Time

On output: Extracted from Sample Date/Time

## **4.218 Schedule Exemption Indicator**

### **4.218.1 Description**

Indicates whether the sampling schedule differs from that required by the standard, by approval of the Regional Administrator.

### **4.218.2 Source**

User-specified via the Basic Monitor Information (MA) Transaction, or AQS Maintain Monitor (L2).

### **4.218.3 Attributes**

Type: Character

Length: 1

Required: No

### **4.218.4 Uses**

Monitor Pollutant Areas

### **4.218.5 Value Assignment**

#### **4.218.5.1 Monitor Planning Areas**

The field may be “Y” and “N” for Monitor Planning Areas.

#### **4.218.5.2 Default**

Not valued.

## **4.219 Screening Group Number**

### **4.219.1 Description**

The number for the screening group that created the monitor, i.e., its owner.

### **4.219.2 Source**

System-generated via the Basic Monitor Information (MA) Transaction, or AQS Maintain Monitor (L2).

### **4.219.3 Attributes**

Type: Number

Length: 12.0

Required: Yes

### **4.219.4 Uses**

Monitors

### **4.219.5 Value Assignment**

The value must exist on the *Screening Groups* view.

## **4.220 Sequence Number**

### **4.220.1 Description**

The sequential identification number used to distinguish Comment Texts for a specific monitor, site, or qualifier detail.

### **4.220.2 Source**

User-specified via AQS Maintain Site (L1), Maintain Monitor (L2), Maintain Raw Data (L54), or Maintain Composite Data (L51).

### **4.220.3 Attributes**

Type: Number  
Length: 12.0  
Required: Yes

### **4.220.4 Uses**

Comments

## **4.221 Session Date**

### **4.221.1 Description**

The date and time of the AQS session under which the sample point was submitted.

### **4.221.2 Source**

System-generated via Raw Data (RD) or Composite Data (RC) Transactions, or AQS Maintain Raw Data (L54) or Maintain Composite Data (L51).

### **4.221.3 Attributes**

Type: Date

Length: Not Applicable

Required: No

### **4.221.4 Uses**

Raw Data

Composite Data

### **4.221.5 Value Assignment**

#### **4.221.5.1 Pre-Production Status**

May be valued when the *Status Indicator* is “R” or “S”.

#### **4.221.5.2 Production Status**

May not be valued when the *Status Indicator* is “P”.

## **4.222 Session Screening Group**

### **4.222.1 Description**

The number of the AQS session screening group under which the sample point was submitted.

### **4.222.2 Source**

System-generated via Raw Data (RD) or Composite Data (RC) Transactions, or AQS Maintain Raw Data (L54) or Maintain Composite Data (L51).

### **4.222.3 Attributes**

Type: Number

Length: 12.0

Required: No

### **4.222.4 Uses**

Raw Data

Composite Data

### **4.222.5 Value Assignment**

#### **4.222.5.1 Pre-Production Status**

May be valued when the *Status Indicator* is “R” or “S”. The value must exist on the *Screening Groups* view.

#### **4.222.5.2 Production Status**

May not be valued when the *Status Indicator* is “P”.

## **4.223 Session User ID**

### **4.223.1 Description**

The user of the AQS session under which the sample point was submitted.

### **4.223.2 Source**

System-generated via Raw Data (RD) or Composite Data (RC) Transactions, or AQS Maintain Raw Data (L54) or Maintain Composite Data (L51).

### **4.223.3 Attributes**

Type: Character

Length: 40

Required: No

### **4.223.4 Uses**

Raw Data

Composite Data

### **4.223.5 Value Assignment**

#### **4.223.5.1 Pre-Production Status**

May be valued when the *Status Indicator* is “R” or “S”. The value must exist on the *Airs User Profiles* view.

#### **4.223.5.2 Production Status**

May not be valued when the *Status Indicator* is “P”.

## **4.224 Site ID**

### **4.224.1 Description**

A numeric identifier (ID) that uniquely identifies each air monitoring site within a county. There is no requirement that *Site IDs* be assigned continuously or in any particular order. Local organizations are thus free to allocate *Site IDs* in any way they choose, as long as there is no duplication within a county.

A specific *Site ID* is associated with a specific physical location and address. Any change in address requires a new *Site ID* to be assigned. This address change could include a change from the roof of one building to another. A change in location on the same roof should not normally require a new *Site ID*. Although an address change would routinely mean a new *Site ID*, some changes that do not change the site's location in respect to surrounding sources and its measurement scale would require no change. An EPA regional office should be consulted for assistance in determining whether a new site ID is required.

If a new *Site ID* is needed for a site not operated by the air pollution control agency, that agency should be contacted to assist in the ID assignment, to ensure that the ID is unique within the county. In other words, when a new *Site ID* is assigned, it must be different from any other *Site ID* already existing for that combination of *State Code* and *County Code*.

### **4.224.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.224.3 Attributes**

Type: Character  
Length: 4  
Required: Yes

### **4.224.4 Uses**

Sites

## **4.225 Source of Traffic Count**

### **4.225.1 Description**

The method by which the traffic volume/flow count was obtained.

### **4.225.2 Source**

User-specified via the Site Street Information (AB) Transaction, or AQS Maintain Site (L1).

### **4.225.3 Attributes**

Type: Character

Length: 50

Required: No

### **4.225.4 Uses**

Tangent Roads

### **4.225.5 Value Assignment**

The value must exist on the *Traffic Volume Sources* view.

## **4.226 Source Scale**

### **4.226.1 Description**

Identifies the ratio of the map or cartographic product to the true location. The data element for scale should be the X value of the 1:X ratio (e.g., if the scale is 1:24,000, the value of the scale data element should be 24,000). The United States Geological Survey 1:24,000 is usually the smallest reasonable scale for locating sub-facility points, such as stacks or pipes. The relative accuracies of maps as a locational tool decreases as the X value increases.

This data element is required by EPA Locational Data Policy. More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website (<http://www.epa.gov/edr/>).

### **4.226.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.226.3 Attributes**

Type: Number

Length: 12.0

Required: No

### **4.226.4 Uses**

Sites

### **4.226.5 Value Assignment**

This field is required when the *Horizontal Collection Method* is based upon using a map.

## **4.227 Spatial Average Indicator**

### **4.227.1 Description**

Indicates whether spatial averaging is to be performed for the all-individual annual weighted means for sites that are flagged and in the same community-monitoring zone.

### **4.227.2 Source**

User-specified via the Basic Monitor Information (MA) Transaction, or AQS Maintain Monitor (L2).

### **4.227.3 Attributes**

Type: Character  
Length: 1  
Required: No

### **4.227.4 Uses**

Monitor Pollutant Areas

### **4.227.5 Value Assignment**

#### **4.227.5.1 Monitor Pollutant Areas**

The field may be “Y” and “N” for Monitor Planning Areas.

#### **4.227.5.2 Default**

Not valued.

## 4.228 Standard Deviation (Monitor Precision Summary)

### 4.228.1 Description

The measure of the dispersion about the central tendency of a pollutant that is the square root of the precision mean of the squares of the variation of each Relative Percent Differences of a value pair from the precision mean of the Relative Percent Differences of the value pairs for the time period.

### 4.228.2 Source

System-generated, via the Precision Data (RP) Transaction, or AQS Maintain Precision Data (L61).

### 4.228.3 Attributes

Type: Number

Length: 6.4

Required: Yes

### 4.228.4 Uses

Monitor Precision Summaries

### 4.228.5 Value Assignment

#### 4.228.5.1 Analytical & Flow

$$S = \sqrt{\frac{\left( \left( n * \sum_{i=1}^n d_i^2 \right) - \left( \sum_{i=1}^n d_i \right)^2 \right)}{n * (n - 1)}}$$

where:

$S$  = standard deviation,

$d_i$  = *Percent Difference* of a analytical or flow precision check,

$n$  = number of gaseous or flow checks (i.e., *Count of Precision Checks (Monitor Precision Summary)*),

and  $n > 1$ .

If  $n = 1$ , then the standard deviation is assigned to be 0.

#### 4.228.5.2 Collocated (PM2.5)

Standard deviation is not computed for collocated PM2.5.

#### 4.228.5.3 Collocated (Other)

$$S = \sqrt{\frac{\left( n * \sum_{i=1}^n d_i^2 \right) - \left( \sum_{i=1}^n d_i \right)^2}{n * (n - 1)}}$$

where:

$S$  = standard deviation,

$d_i$  = *Percent Difference* of a valid collocated pair,

$n$  = *Count of Valid Collocated Data Pairs (Monitor Precision Summary)*,

and  $n > 1$ .

If  $n = 1$ , then the standard deviation is assigned to be 0.

## 4.229 Standard Deviation (Reporting Organization Accuracy Summary)

### 4.229.1 Description

The measure of the dispersion about the central tendency of a pollutant that is the square root of the precision mean of the squares of the variation of each Relative Percent Differences of a value pair from the precision mean of the Relative Percent Differences of the value pairs for the time period.

### 4.229.2 Source

System-generated, via the Accuracy Data (RA) Transaction, or Maintain Accuracy Data (L62).

### 4.229.3 Attributes

Type: Number

Length: 7.5

Required: No

### 4.229.4 Uses

Reporting Organization Accuracy Summaries

### 4.229.5 Value Assignment

$$S = \sqrt{\frac{\left( \left( n * \sum_{i=1}^n d_i^2 \right) - \left( \sum_{i=1}^n d_i \right)^2 \right)}{n * (n - 1)}}$$

where:

$S$  = standard deviation,

$d_i$  = *Percent Difference* of a analytical or flow audit,

$n$  = *Count of Accuracy Audits (Reporting Organization Accuracy Summary)*.

If either quarter in either half of the year has an *Count of Accuracy Audits (Reporting Organization Accuracy Summary)* of 1, then the source data for both quarters in that half will be merged for purposes of calculating the standard deviation, and reported with the second quarter of the half (i.e., Q2 or Q4). In this case, there will be no value for the corresponding first quarter in the half (i.e., Q1 or Q3)

## 4.230 Standard Deviation (Reporting Organization Precision Summary)

### 4.230.1 Description

The measure of the dispersion about the central tendency of a pollutant that is the square root of the precision mean of the squares of the variation of each Relative Percent Differences of a value pair from the precision mean of the Relative Percent Differences of the value pairs for the time period.

### 4.230.2 Source

System-generated, via the Precision Data (RP) Transaction, or AQS Maintain Precision Data (L61).

### 4.230.3 Attributes

Type: Number

Length: 6.4

Required: No

### 4.230.4 Uses

Reporting Organization Precision Summaries

### 4.230.5 Value Assignment

#### 4.230.5.1 Analytical & Flow

$$S = \sqrt{\frac{\left( \left( n * \sum_{i=1}^n d_i^2 \right) - \left( \sum_{i=1}^n d_i \right)^2 \right)}{(n * (n - k))}}$$

where:

$S$  = standard deviation,

$d_i$  = *Percent Difference* of a analytical or flow precision check,

$n$  = number of gaseous or flow checks (i.e., Count of Precision Checks (Reporting Organization Precision Summary)),

$k$  = number of monitors (i.e. Count of Analyzers).

and  $n > k$ .

If  $n = k$ , then the standard deviation is assigned to be 0.

#### 4.230.5.2 Collocated (PM2.5)

Standard deviation is not computed for collocated PM2.5.

#### 4.230.5.3 Collocated (Other)

$$S = \sqrt{\frac{\left( \left( n * \sum_{i=1}^n d_i^2 \right) - \left( \sum_{i=1}^n d_i \right)^2 \right)}{(n * (n - k))}}$$

where:

$S$  = standard deviation,

$d_i$  = *Percent Difference* of a valid collocated pair,

$n$  = Count of Valid Collocated Data Pairs (Reporting Organization Precision Summary),

$k$  = number of collocated sites (i.e. Count of Collocated Sites).

and  $n > k$ .

If  $n = k$ , then the standard deviation is assigned to be 0.

#### 4.230.5.4 Federal Reference Method (FRM) Audit

$$S = \sqrt{\frac{\left( \left( n * \sum_{i=1}^n d_i^2 \right) - \left( \sum_{i=1}^n d_i \right)^2 \right)}{(n * (n - 1))}}$$

where:

$S$  = standard deviation,

$d_i$  = *Percent Difference* of an FRM audit pair ([2.1.3 Percent Difference](#)),

$n$  = number of FRM audits (i.e., *Count of Precision Checks (Reporting Organization Precision Summary)*),

and  $n > 1$ .

If  $n = 1$ , then the standard deviation is assigned to be 0.

## 4.231 Standard Sample Value

### 4.231.1 Description

The *Reported Sample Value* converted to a value in the *Standard Unit* for the *Parameter*.

### 4.231.2 Source

System-generated via the Raw Data (RD) or Composite Data (RC) Transactions, AQS Maintain Raw Data (L54), or AQS Maintain Composite Data (L51).

### 4.231.3 Attributes

Type: Number

Length: 5.5

Required: No

### 4.231.4 Uses

Raw Data

Composite Data

### 4.231.5 Value Assignment

Each *Reported Unit-Standard Unit* combination has a record in the *Unit Conversions* view. That record specifies the values to be used in the following formula:

$$v = s + (l * r * m^i * c^j)$$

where:

$v$  = the value in standard units (*Standard Sample Value*),

$s$  = the scalar factor,

$l$  = the linear factor,

$r$  = the sample value in reported units (*Reported Sample Value*),

$m$  = the molecular weight of the *Parameter*,

$i$  = indication of whether molecular weight applies, (0 means “No”, 1 means “Yes”),

$c$  = the carbon count of the *Parameter*,

$j$  = indication of whether carbon count applies, (0 means “No”, 1 means “Yes”).

When the calculated *Standard Sample Value* is less than the applicable method detectable limit (MDL), (and where the *Parameter* is not 88101), the calculated value is superceded by a value equal to ½ the applicable MDL. When such a substitution occurs, the *Half MDL Substitution Indicator* is set to “Y”.

For any sample, the applicable MDL generally is that which is assigned to the method by the EPA. This EPA-assigned, i.e., federal, MDL, may be superceded by an alternative MDL. An *Alternate MDL* is specified by the submitting agency as part of a raw data transaction. This *Alternate MDL* is stored with the corresponding *Monitor Protocol*, and is converted to

the *Standard Unit*, using the above formula, for comparison to the corresponding *Standard Sample Value*.

A *Standard Sample Value* that is either greater than, or equal to, the applicable MDL, or below that applicable MDL but flagged for rescaling of  $\frac{1}{2}$  MDL substitutions, is subject to rescaling. If the applicable MDL is the Federal MDL, then the scaling factor is that scale which is assigned to the method by the EPA, (i.e., the summary scale). If the applicable MDL is an *Alternate MDL*, then the scaling factor is the number of digits of that *Alternate MDL* when it is converted to the *Standard Unit*. (Note: The maximum possible scale is 5.) Rescaling is either rounding or truncation of the converted value to the number of decimal places specified in the summary scale. Each parameter has a *Conversion Indicator* field, which specifies whether truncation or rounding applies. (Rounding is the default.)

## **4.232 Standard Scale**

### **4.232.1 Description**

Indicates the number of places to the right of the decimal point for the Standard Sample Value, including trailing zeros.

### **4.232.2 Source**

System-generated via the Raw Data (RD) or Composite Data (RC) Transactions, AQS Maintain Raw Data (L54), or AQS Maintain Composite Data (L51).

### **4.232.3 Attributes**

Type: Number  
Length: 1.0  
Required: No

### **4.232.4 Uses**

Raw Data  
Composite Data

### **4.232.5 Value Assignment**

Replicated from the Summary Scale for the Parameter and Method Code on the Sampling Methodologies view.

## **4.233 Standard Unit**

### **4.233.1 Description**

The Standard Unit for the Parameter.

### **4.233.2 Source**

System-generated via the Raw Data (RD) or Composite Data (RC) Transactions, AQS Maintain Raw Data (L54), or AQS Maintain Composite Data (L51).

### **4.233.3 Attributes**

Type: Character

Length: 3

Required: No

### **4.233.4 Uses**

Raw Data

Composite Data

### **4.233.5 Value Assignment**

Replicated from the *Standard Unit* for the *Parameter* on the *Parameters* view.

## **4.234 State Code**

### **4.234.1 Description**

A Federal Information Processing Standards (FIPS) code that identifies one of the 50 states, U. S. territories, Washington, DC, or foreign countries.

### **4.234.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.234.3 Attributes**

Type: Character

Length: 2

Required: Yes

### **4.234.4 Uses**

Sites

### **4.234.5 Value Assignment**

The value must exist on the *States* view.

## **4.235 Status Indicator**

### **4.235.1 Description**

An indication of the status of the record.

### **4.235.2 Source**

System-generated by AQS Load, Stat/CR, Post, Maintain Site (L1), Maintain Monitor (L2), Maintain Raw Data (L54), and Maintain Composite Data (L51).

### **4.235.3 Attributes**

Type: Character

Length: 1

Required: Yes

### **4.235.4 Uses**

Sites  
Tangent Roads  
Open Paths  
Monitors  
Monitor Pollutant Areas  
Sample Periods  
Monitor Type Assignments  
Monitor Agency Roles  
Monitor Objectives  
Required Collection Frequencies  
Sample Schedules  
Monitor Tangent Roads  
Probe Obstructions  
Monitor Regulatory Compliances  
Monitor Collocation Periods  
Monitor Protocols  
Raw Data  
Composite Data

### **4.235.5 Value Assignment**

<b>Indicator</b>	<b>Description</b>
F	Validated to field-level
R	Relationally complete (Raw & Composite Data Only)
S	Statistically checked (Raw & Composite Data Only)
P	Production
I	Inactive (Raw & Composite Data Only)

## **4.236 Street Address**

### **4.236.1 Description**

Specifies the building/street location of the monitoring site.

### **4.236.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.236.3 Attributes**

Type: Character

Length: 240

Required: Yes

### **4.236.4 Uses**

Sites

## **4.237 Street Name**

### **4.237.1 Description**

The name of a street near to the monitoring site.

### **4.237.2 Source**

User-specified via the Site Street Information (AB) Transaction, or AQS Maintain Site (L1).

### **4.237.3 Attributes**

Type: Character

Length: 50

Required: Yes

### **4.237.4 Uses**

Tangent Roads

## 4.238 Summary Criteria Indicator (Annual)

### 4.238.1 Description

An indication of whether minimum summary criteria have been by the monitor for the year.

### 4.238.2 Source

System-generated via the Post process.

### 4.238.3 Attributes

Type: Character

Length: 3

Required: No

### 4.238.4 Uses

Annual Summaries

### 4.238.5 Value Assignment

The possible values are “Y” and “N”.

#### 4.238.5.1 8-Hour Ozone

Minimum summary criteria are met when the percentage derived from the following formula, rounded to an integer, is greater than, or equal to, 75%:

$$p = \left( \frac{(v + a)}{r} \right) * 100$$

where:

$p$  = percentage,

$v$  = *Count of Valid Days*,

$a$  = *Count of Missing Days Assumed Less Than Standard*,

$r$  = *Count of Required Days*.

#### 4.238.5.2 8-Hour Carbon Monoxide, 3-Hour and 24-Hour Sulfur Dioxide

Minimum summary criteria are met where the annual Count of Observations is greater than 0.

#### 4.238.5.3 Default Hourly

Minimum summary criteria are met when the *Percent of Observations (Annual)* is greater than, or equal to, 75%.

#### **4.238.5.4 Default Daily & 24-Hour PM10 & PM2.5**

For daily, 24-Hour PM10, 24-Hour PM2.5, weekly, monthly, composite weekly, and composite monthly data, annual minimum summary criteria are met when each of the four quarters in the year have met quarterly minimum summary criteria, i.e. the *Summary Criteria Indicator (Quarterly)* values are “Y”.

For quarterly, composite quarterly, and composite seasonal data, minimum summary criteria are met when the *Count of Observations (Annual)* is greater than, or equal to, 3.

## **4.239 Summary Criteria Indicator (Daily)**

### **4.239.1 Description**

An indication of whether minimum summary criteria have been by the monitor for the day.

### **4.239.2 Source**

System-generated via the Post process.

### **4.239.3 Attributes**

Type: Character

Length: 3

Required: No

### **4.239.4 Uses**

Daily Summaries

### **4.239.5 Value Assignment**

#### **4.239.5.1 1-Hour Ozone**

Minimum summary criteria are met when there were either at least nine samples from 9:01 AM Local Standard Time (LST) to 9:00 PM LST, (i.e., at least 75% of possible hourly samples were measured), or at least one exceedance.

#### **4.239.5.2 8-Hour Ozone**

Minimum summary criteria are met where either of the following conditions exists:

- there are at least 18 valid 8-hour averages (i.e., *Count of Observations (Daily)*) for the 24-hour period,
- the *Maximum Value (Daily)* is greater than the standard (i.e., *Count of Primary Exceedances (Daily)*  $\geq 1$ ).

#### **4.239.5.3 1-Hour PM10 & PM2.5**

Minimum summary criteria are met when the *Percent of Observations (Daily)* is greater than, or equal to, 75%.

#### **4.239.5.4 Default**

Not valued.

## 4.240 Summary Criteria Indicator (Quarterly)

### 4.240.1 Description

An indication of whether minimum summary criteria have been by the monitor for the quarter.

### 4.240.2 Source

System-generated via the Post process.

### 4.240.3 Attributes

Type: Character

Length: 3

Required: No

### 4.240.4 Uses

Quarterly Summaries

### 4.240.5 Value Assignment

#### 4.240.5.1 Daily & 24-Hour PM10 & PM2.5

Minimum summary criteria are met when the *Percent of Observations (Quarterly)* is greater than, or equal to, 75%.

#### 4.240.5.2 Default Hourly

Minimum summary criteria are met when the *Percent of Observations (Quarterly)* is greater than, or equal to, 75%.

#### 4.240.5.3 Default Daily

Minimum summary criteria are met for the quarter when the *Count of Observations (Quarterly)* is greater than, or equal to, a duration-specific threshold. Those thresholds are:

Duration	Threshold
Daily	12
Weekly; Composite Weekly	9
Monthly; Composite Monthly	2
Quarterly; Composite Quarterly; Composite Seasonal	1

## **4.241 Summary Quarter**

### **4.241.1 Description**

The quarter number (1-4) identifying a quarterly summary.

### **4.241.2 Source**

System-generated via the Post process.

### **4.241.3 Attributes**

Type: Number

Length: 1.0

Required: Yes

### **4.241.4 Uses**

Quarterly Summaries

## **4.242 Summary Year**

### **4.242.1 Description**

The year identifying a summary.

### **4.242.2 Source**

System-generated via the Post process, the Accuracy Data (RA) or Precision Data (RP) Transactions, or AQS Maintain Accuracy Data (L62) or Maintain Precision Data (L61).

### **4.242.3 Attributes**

Type: Number

Length: 4.0

Required: Yes

### **4.242.4 Uses**

Annual Summaries

Quarterly Summaries

Monitor Precision Summaries

Precision Summary Protocols

Reporting Organization Precision Summaries

Monitor Accuracy Summaries

Accuracy Summary Protocols

Reporting Organization Accuracy Summaries

## **4.243 Supporting Agency**

### **4.243.1 Description**

Identifies the agency responsible for the operation of the monitoring site.

### **4.243.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.243.3 Attributes**

Type: Character

Length: 8

Required: No

### **4.243.4 Uses**

Sites

### **4.243.5 Value Assignment**

The value must exist on the *Agencies* view, and, in combination with *State Code*, on the *State Agencies* view.

## **4.244 Surrogate Indicator**

### **4.244.1 Description**

Indicates whether a Total Suspended Particulate (TSP) monitor serves as a surrogate monitor for PM-10.

### **4.244.2 Source**

User-specified via the Basic Monitor Information (MA) Transaction, or AQS Maintain Monitor (L2).

### **4.244.3 Attributes**

Type: Character  
Length: 1  
Required: No

### **4.244.4 Uses**

Monitors

### **4.244.5 Value Assignment**

The valid values are “Y” and “N”.

## **4.245 Tangent Street Number**

### **4.245.1 Description**

Identifies the number of the street around the site for which the data are being submitted. Street number is used to associate detailed street information for the site to streets closest to the monitors at this site.

### **4.245.2 Source**

User-specified via the Site Street Information (AB) Transaction, or AQS Maintain Site (L1).

### **4.245.3 Attributes**

Type: Number  
Length: 12.0  
Required: Yes

### **4.245.4 Uses**

Tangent Roads

## **4.246 Time Period**

### **4.246.1 Description**

Indicates the period of time for which the summary covers.

### **4.246.2 Source**

System-generated via the Accuracy Data (RA) or Precision Data (RP) Transactions, or AQS Maintain Accuracy Data (L62) or Maintain Precision Data (L61).

### **4.246.3 Attributes**

Type: Character

Length: 2

Required: Yes

### **4.246.4 Uses**

Monitor Precision Summaries

Precision Summary Protocols

Reporting Organization Precision Summaries

Monitor Accuracy Summaries

Accuracy Summary Protocols

Reporting Organization Accuracy Summaries

### **4.246.5 Value Assignment**

Time Period	Description
Q1	1 <sup>st</sup> quarter
Q2	2 <sup>nd</sup> quarter
Q3	3 <sup>rd</sup> quarter
Q4	4 <sup>th</sup> quarter
YR	Entire year

## **4.247 Time Zone**

### **4.247.1 Description**

A standard time zone, as established by Section 1 of the Standard Time Act, as amended by Section 4 of the Uniform Time Act of 1966 (15 U.S.C. 261).

### **4.247.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.247.3 Attributes**

Type: Character

Length: 30

Required: No

### **4.247.4 Uses**

Sites

### **4.247.5 Value Assignment**

The value must exist on the *Time Zones* view.

## **4.248 Traffic Count**

### **4.248.1 Description**

An estimate of the daily traffic volume on the roadway.

### **4.248.2 Source**

User-specified via the Site Street Information (AB) Transaction, or AQS Maintain Site (L1).

### **4.248.3 Attributes**

Type: Number

Length: 12.0

Required: No

### **4.248.4 Uses**

Tangent Roads

## **4.249 Uncertainty Value**

### **4.249.1 Description**

The measure of method uncertainty associated with the sample data point, which will include components of both the analytical and the volume uncertainty. No blank corrections are assumed (other than laboratory baseline corrections which are an integral part of each analysis).

### **4.249.2 Source**

User-specified via the Raw Data (RD), Composite Data (RC), or Blank Data (RB) Transactions, AQS Maintain Raw Data (L54), Maintain Blank Data (L53), or AQS Maintain Composite Data (L51).

### **4.249.3 Attributes**

Type: Number

Length: 6.5

Required: No

### **4.249.4 Uses**

Raw Data

Composite Data

Blank Data

## **4.250 Unrestricted Air Flow Indicator**

### **4.250.1 Description**

Indication of whether the flow of air to the monitor is restricted.

### **4.250.2 Source**

User-specified via the Basic Monitor Information (MA) Transaction, or AQS Maintain Monitor (L2).

### **4.250.3 Attributes**

Type: Character

Length: 1

Required: No

### **4.250.4 Uses**

Monitors

### **4.250.5 Value Assignment**

<b>Indicator</b>	<b>Description</b>
Y	Flow is unrestricted
N	Flow is restricted by obstructions
W	Flow is restricted unavoidably, and the probe location has been approved by the EPA

## **4.251 Upper Probability Limit (Reporting Organization Accuracy Summary)**

### **4.251.1 Description**

The upper bound of either a probability distribution, or confidence interval, for the applicable population of accuracy audits.

If either quarter in either half of the year has an *Count of Accuracy Audits (Reporting Organization Accuracy Summary)* of 1, then the source data for both quarters in that half will be merged for purposes of calculating the upper probability/confidence limit, and reported with the second quarter of the half (i.e., Q2 or Q4). In this case, there will be no value for the corresponding first quarter in the half (i.e., Q1 or Q3).

### **4.251.2 Source**

System-generated via Accuracy Data (RA) Transaction, or Maintain Accuracy (L61).

### **4.251.3 Attributes**

Type: Number

Length: 6.4

Required: No

### **4.251.4 Uses**

Reporting Organization Accuracy Summaries

### **4.251.5 Value Assignment**

#### **4.251.5.1 Analytical & Flow (Non-PM 2.5)**

$$u = D + (S * 1.96)$$

$u$  = upper 95% probability limit, where:

$D$  = Mean (*Reporting Organization Accuracy Summaries*),

$S$  = Standard Deviation (*Reporting Organization Accuracy Summaries*).

**4.251.5.2 Flow (PM 2.5)**

$$u = D + \left( \frac{S * t_{0.975, n - 1}}{\sqrt{n}} \right)$$

where:

*u* = upper 95% confidence limit,

*D* = Mean (Reporting Organization Accuracy Summaries),

*S* = Standard Deviation (Reporting Organization Accuracy Summaries),

*t*<sub>0.975, n-1</sub> = the 0.975 quantile of the Student's T distribution with degrees of freedom equal to *n-1*,

*n* = Count of Accuracy Audits (Reporting Organization Accuracy Summary).

## **4.252 Upper Probability Limit (Reporting Organization Precision Summary)**

### **4.252.1 Description**

The upper bound of either a probability distribution, or confidence interval, for the applicable population of precision checks.

### **4.252.2 Source**

System-generated via Precision Data (RP) Transaction, or Maintain Precision (L62).

### **4.252.3 Attributes**

Type: Number

Length: 6.4

Required: No

### **4.252.4 Uses**

Reporting Organization Precision Summaries

### **4.252.5 Value Assignment**

#### **4.252.5.1 Analytical & Flow (Other)**

$$u = D + (S * 1.96)$$

where:

$u$  = upper 95% probability limit,

$D$  = Mean (Reporting Organization Precision Summaries),

$S$  = Standard Deviation (Reporting Organization Precision Summaries).

#### 4.252.5.2 Flow (PM 2.5)

$$u = D + \left( \frac{S * t_{0.975, n-1}}{\sqrt{n}} \right)$$

where:

$u$  = upper 95% confidence limit,

$D$  = Mean (Reporting Organization Precision Summaries),

$S$  = Standard Deviation (Reporting Organization Precision Summaries)

$t_{0.975, n-1}$  = the 0.975 quantile of the Student's T distribution with degrees of freedom equal to  $n-1$ ,

$n$  = number of flow checks (i.e. *Count of Precision Checks (Reporting Organization Precision Summary)*).

#### 4.252.5.3 Collocated (PM 2.5)

$$u = CV \sqrt{\frac{n}{\chi^2_{0.05, n}}}$$

where:

$u$  = upper 90% confidence limit,

$CV$  = coefficient of variation, (i.e., mean),

$n$  = *Count of Valid Collocated Data Pairs (Reporting Organization Precision Summary)*,

$\chi^2_{0.05, n}$  = the 0.95 quantile of the chi-square distribution with degrees of freedom equal to  $n$ .

#### 4.252.5.4 Collocated (Other)

$$u = D + \left( \frac{S * 1.96}{\sqrt{2}} \right)$$

where:

$u$  = upper 95% probability limit,

$D$  = Mean (Reporting Organization Precision Summaries),

$S$  = Standard Deviation (Reporting Organization Precision Summaries).

#### 4.252.5.5 Federal Reference Method (FRM) Audit

$$u = D + \left( \frac{S * t_{0.975, n - 1}}{\sqrt{n}} \right)$$

where:

$u$  = upper 95% confidence limit,

$D$  = Mean (*Reporting Organization Precision Summaries*),

$S$  = Standard Deviation (*Reporting Organization Precision Summaries*),

$t_{0.975, n-1}$  = the 0.975 quantile of the Student's T distribution with degrees of freedom equal to  $n-1$ ,

$n$  = number of FRM pairs (i.e., *Count of Precision Checks (Reporting Organization Precision Summary)*).

## **4.253 Urban Area Code**

### **4.253.1 Description**

The urbanized area within which the monitoring site is located. An urbanized area is a U.S. Census Bureau demographic entity that comprises a place and the adjacent densely-settled surrounding territory that together have a minimum population of 50,000 people.

### **4.253.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.253.3 Attributes**

Type: Character

Length: 4

Required: Yes

### **4.253.4 Uses**

Sites

### **4.253.5 Value Assignment**

The value must exist on the *Urbanized Areas* view, and, in combination with *State Code*, on the *State Urbanized Areas* view.

## **4.254 Urban Area Represented**

### **4.254.1 Description**

The urbanized area from which the concentrations originated (not the location of the monitor).

### **4.254.2 Source**

User-specified via the Monitoring Objective Information (ME) Transaction, or AQS Maintain Monitor (L2).

### **4.254.3 Attributes**

Type: Character

Length: 4

Required: No

### **4.254.4 Uses**

Monitor Objectives

### **4.254.5 Value Assignment**

Must have a value if neither *CMSA Represented* nor *MSA Represented* is valued. Conversely, may not have a value if either *CMSA Represented* or *MSA Represented* is valued. If valued, that value must exist on the *Urbanized Areas* view.

## **4.255 UTM Easting**

### **4.255.1 Description**

The easting Universe Transverse Mercator (UTM) coordinate, expressed in meters (i.e., the horizontal distance from the reference edge of the UTM zone) for the site.

EPA Locational Data Policy requires that coordinates be provided for all sites. More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website (<http://www.epa.gov/edr/>).

### **4.255.2 Source**

User-specified, or system-generated from user-specified latitude/longitude coordinates, via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.255.3 Attributes**

Type: Number

Length: 8.2

Required: Yes

### **4.255.4 Uses**

Sites

## **4.256 UTM Northing**

### **4.256.1 Description**

The northing Universe Transverse Mercator (UTM) coordinate expressed in meters (i.e., for the Northern hemisphere, the vertical distance from the equator; for the Southern hemisphere, 10,000,000 minus the vertical distance from the equator) for the site.

EPA Locational Data Policy requires that coordinates be provided for all sites. More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website (<http://www.epa.gov/edr/>).

### **4.256.2 Source**

User-specified, or system-generated from user-specified latitude/longitude coordinates, via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.256.3 Attributes**

Type: Number

Length: 8.2

Required: Yes

### **4.256.4 Uses**

Sites

## **4.257 UTM Zone**

### **4.257.1 Description**

The zone of the Universal Transverse Mercator (UTM) system in which a site is located.

EPA Locational Data Policy requires that coordinates be provided for all sites. More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website (<http://www.epa.gov/edr/>).

### **4.257.2 Source**

User-specified, or system-generated from user-specified latitude/longitude coordinates, via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.257.3 Attributes**

Type: Number

Length: 12

Required: Yes

### **4.257.4 Uses**

Sites

## **4.258 Vertical Accuracy**

### **4.258.1 Description**

Description of the accuracy of the vertical measure, reported in meters.

This data element is required by EPA Locational Data Policy (LDP). More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website (<http://www.epa.gov/edr/>).

### **4.258.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.258.3 Attributes**

Type: Number

Length: 8.2

Required: Yes

### **4.258.4 Uses**

Sites

## **4.259 Vertical Collection Method**

### **4.259.1 Description**

The method used to determine the Locational Data Policy (LDP) vertical measure.

This data element is required by EPA LDP. More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website (<http://www.epa.gov/edr/>).

### **4.259.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.259.3 Attributes**

Type: Character

Length: 3

Required: Yes

### **4.259.4 Uses**

Sites

### **4.259.5 Value Assignment**

The value must exist on the *Vertical Collection Methods* view

## **4.260 Vertical Datum**

### **4.260.1 Description**

The edition of North American Datum used as the basis for determining the site coordinates. (The editions of North American Datum establish a network of monuments and reference points defining a mathematical surface from which geographic computations can be made.)

This data element is required by EPA Locational Data Policy (LDP). More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website (<http://www.epa.gov/edr/>).

### **4.260.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.260.3 Attributes**

Type: Character

Length: 60

Required: Yes

### **4.260.4 Uses**

Sites

### **4.260.5 Value Assignment**

The value must exist on the *Vertical Data* view.

## **4.261 Vertical Measure**

### **4.261.1 Description**

The elevation, in meters, above or below mean sea level (MSL) of the site.

This data element is required by EPA Locational Data Policy (LDP). More information regarding EPA's data standards and policies may be found on EPA's Environmental Data Registry (EDR) Website (<http://www.epa.gov/edr/>).

### **4.261.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.261.3 Attributes**

Type: Number

Length: 8.2

Required: Yes

### **4.261.4 Uses**

Sites

## 4.262 Weighted Arithmetic Mean

### 4.262.1 Description

The weighted arithmetic mean.

### 4.262.2 Source

System-generated via the Post process.

### 4.262.3 Attributes

Type: Number

Length: 5.5

Required: No

### 4.262.4 Uses

Annual Summaries

### 4.262.5 Value Assignment

#### 4.262.5.1 Seasonal and Everyday PM10

$$\frac{\sum_{i=1}^q u_i}{q}$$

where:

i = quarter,

$u_i$  = *Arithmetic Mean (Quarterly)*,

q = number of active quarters.

#### 4.262.5.2 Stratified PM10

$$\frac{\sum_{k=1}^q \left( \frac{\sum_{j=1}^s \left( \frac{\sum_{i=1}^n v_i}{n} \right)_j}{s} \right)_k}{q}$$

where:

- i = a sample value occurrence,
- n = number of sample values in a stratum,
- v<sub>i</sub> = a sample value,
- j = a valued stratum,
- s = number of valued strata,
- k = a quarter with valued strata,
- q = number of quarters with valued strata.

#### 4.262.5.3 Default

Not valued.

## 4.263 Worst Site Type

### 4.263.1 Description

Within a particular monitoring area, those monitors with the highest PM-10 concentrations must have their worst site type set to 1, and are expected to monitor at the recommended collection frequency. Other monitors must be classified as either not worst site monitors, or monitoring on an accelerated schedule, but not at the recommended collection frequency.

### 4.263.2 Source

User-specified via the Basic Monitor Information (MA) Transaction, or AQS Maintain Monitor (L2).

### 4.263.3 Attributes

Type: Character

Length: 20

Required: Yes

### 4.263.4 Uses

Monitor Pollutant Areas

### 4.263.5 Value Assignment

Value	Description
1	Classified as having the highest PM-10 concentration and is expected to monitor at recommended sampling frequency.
2	Classified as not being a worst site monitor.
3	Monitoring on an accelerated schedule, but not at the recommended sampling frequency.

#### 4.263.5.1 Monitoring Areas

May be valued for a Monitoring Area.

#### 4.263.5.2 Default

Not valued.

## **4.264 Year of Traffic Count**

### **4.264.1 Description**

The year when the Traffic Count value was estimated.

### **4.264.2 Source**

User-specified via the Site Street Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.264.3 Attributes**

Type: Number

Length: 4.0

Required: Yes

### **4.264.4 Uses**

Tangent Roads

## **4.265 Year Represented**

### **4.265.1 Description**

The year represented by the audit.

### **4.265.2 Source**

User-specified or system-generated via the Accuracy Data (RA) Transaction or AQS Maintain Accuracy (L62).

### **4.265.3 Attributes**

Type: Number

Length: 4

Required: Yes

### **4.265.4 Uses**

Accuracy Data

### **4.265.5 Value Assignment**

#### **4.265.5.1 Lead**

User-specified.

#### **4.265.5.2 Default**

Derived from *Accuracy Date*.

## **4.266 Zero Span**

### **4.266.1 Description**

A measurement obtained with gas from a zero concentration. Zero span is the observed value read from the instrument when the concentration of the specific parameter used to test the monitor was zero.

### **4.266.2 Source**

User-specified via the Accuracy Data (RA) Transaction or AQS Maintain Accuracy (L62).

### **4.266.3 Attributes**

Type: Number

Length: 5.5

Required: No

### **4.266.4 Uses**

Accuracy Data

## **4.267 Zero Span Scale**

### **4.267.1 Description**

The number of digits to the right of the decimal point that were specified by the user, including trailing zeros.

### **4.267.2 Source**

System-generated via the Accuracy Data (RA) Transaction or AQS Maintain Accuracy (L62).

### **4.267.3 Attributes**

Type: Number

Length: 1.0

Required: No

### **4.267.4 Uses**

Accuracy Data

## **4.268 Zip Code**

### **4.268.1 Description**

The U.S. Postal Service Zone Improvement Plan (ZIP) Code used to address the monitoring site.

### **4.268.2 Source**

User-specified via the Basic Site Information (AA) Transaction, or AQS Maintain Site (L1).

### **4.268.3 Attributes**

Type: Character

Length: 9

Required: No

### **4.268.4 Uses**

Sites

### **4.268.5 Value Assignment**

In combination with *State Code* and *County Code*, the value must exist on the *County Zip Codes* view.