

---

**2014 – 4<sup>th</sup> Quarter Report**  
**Support for Conducting Systems &**  
**Performance Audits of CASTNET Sites and**  
**NADP Monitoring Stations**

**EPA Contract No. EPW12019**

**Prepared for:**

**U. S. Environmental Protection Agency**

**Prepared by:**



**1128 NW 39<sup>th</sup> Drive**  
**Gainesville, FL 32605**

**June 2016**

---

## Table of Contents

<b>1.0 CASTNET Quarterly Report.....</b>	<b>1-1</b>
1.1 Introduction.....	1-1
1.2 Project Objectives .....	1-1
1.3 CASTNET Sites Visited Fourth Quarter 2014.....	1-4
1.4 Audit Results.....	1-5
<b>2.0 NADP Quarterly Report .....</b>	<b>2-1</b>
2.1 Introduction.....	2-1
2.2 Project Objectives .....	2-1
2.3 Sites Visited Fourth Quarter 2014.....	2-2
2.4 Survey Results.....	2-3

### List of Appendices

<b>Appendix A</b>	CASNTET Audit Report Forms
<b>Appendix B</b>	CASTNET Site Spot Report Forms
<b>Appendix C</b>	CASTNET Ozone Performance Evaluation Forms

### List of Tables

<b>Table 1.</b>	Performance Audit Challenge and Acceptance Criteria	1-2
<b>Table 2.</b>	Site Audit Visits	1-4
<b>Table 3.</b>	TTP Pollutant PE Visits	1-4
<b>Table 4.</b>	Sites Surveyed – Fourth Quarter 2014	2-2

## List of Acronyms and Abbreviations

% diff	percent difference
A/D	analog to digital converter
ARS	Air Resource Specialist, Inc.
ASTM	American Society for Testing and Materials
CASTNET	Clean Air Status and Trends Network
DAS	data acquisition system
DC	direct current
deg	degree
DVM	digital voltmeter
EEMS	Environmental, Engineering & Measurement Services, Inc.
EPA	U.S. Environmental Protection Agency
ESC	Environmental Systems Corporation
FSAD	Field Site Audit Database
GPS	geographical positioning system
lpm	liters per minute
MLM	Multilayer Model
m/s	meters per second
mv	milivolt
NIST	National Institute of Standards and Technology
NOAA	National Oceanic and Atmospheric Administration
NPS	National Park Service
QAPP	Quality Assurance Project Plan
SOP	standard operating procedure
TEI	Thermo Environmental Instruments
USNO	United States Naval Observatory
V	volts
WRR	World Radiation Reference

## **1.0 CASTNET Quarterly Report**

### **1.1 Introduction**

The Clean Air Status and Trends Network (CASTNET) is a national air monitoring program developed under mandate of the 1990 Clean Air Act Amendments. Each site in the network measures acidic gases and particles and other forms of atmospheric pollution using a continuous collection filter aggregated over a one week period. Hourly averages of surface ozone concentrations and selected meteorological variables are also measured.

Site measurements are used to estimate deposition rates of the various pollutants with the objective of determining relationships between emissions, air quality, deposition, and ecological effects. In conjunction with other national monitoring networks, CASTNET data are used to determine the effectiveness of national emissions control programs and to assess temporal trends and spatial deposition patterns in atmospheric pollutants. CASTNET data are also used for long-range transport model evaluations and effects research.

CASTNET pollutant flux estimates are calculated as the aggregate product of weekly measured chemical concentrations and model-estimated deposition velocities. Currently, the National Oceanic and Atmospheric Administration's multilayer inferential model (NOAA-MLM) described by Meyers et al. [1998] is used to derive deposition velocity estimates.

As of June 2016, the network is comprised of 94 active rural sampling sites across the United States and Canada, cooperatively operated by the Environmental Protection Agency (EPA), the National Park Service (NPS), Environment Canada, Bureau of Land Management (BLM) and several independent partners. AMEC is responsible for operating the EPA and Environment Canada sponsored sites, and Air Resource Specialist, Inc. (ARS) is responsible for operating the NPS and BLM sponsored sites.

### **1.2 Project Objectives**

The objectives of this project are to establish an independent and unbiased program of performance and systems audits for all CASTNET sampling sites. Ongoing Quality Assurance (QA) programs are an essential part of any long-term monitoring network.

Performance audits verify that all evaluated variables are consistent with the accuracy goals as defined in the CASTNET Quality Assurance Project Plan (QAPP). The parameter specific accuracy goals are presented in Table 1. Only four EPA sponsored sites that are operated by AMEC continue to operate meteorological sensors. Those sites are BEL116, BVL30, CHE185,

and PAL190. Five new sites sponsored by EPA and operated by the BLM in WY also operate meteorological sensors and are BAS601, NEC602, BUF603, FOR604, and SHE604.

Some or all of the additional monitored variables, NO<sub>y</sub>, CO, and SO<sub>2</sub> have been added to the EPA sponsored sites BVL130, HWF187, PND165, PNF126, ROM206, and BEL116. Those variables were audited at the PNF126, HWF187, and BEL116 stations during fourth quarter 2014. All of the SO<sub>2</sub> and NO<sub>y</sub> results for those audits were found to be within acceptance criteria. The preliminary reports of those results were delivered following the audits and are not included in this report.

**Table 1. Performance Audit Challenge and Acceptance Criteria**

Sensor	Parameter	Audit Challenge	Acceptance Criteria
Precipitation	Response	10 manual tips	1 DAS count per tip
Precipitation	Accuracy	2 introductions of known amounts of water	≤ ±10.0% of input amount
Relative Humidity	Accuracy	Compared to reference instrument or standard solution	≤ ±10.0% RH
Solar Radiation	Accuracy	Compared to WRR traceable standard	≤ ±10.0% of daytime average
Surface Wetness	Response	Distilled water spray mist	Positive response
Surface Wetness	Sensitivity	1% decade resistance	N/A
Temperature	Accuracy	Comparison to 3 NIST measured baths (~ 0° C, ambient, ~ full-scale)	≤ ± 0.5° C
Temperature Difference	Accuracy	Comparison to station temperature sensor	≤ ± 0.50° C
Wind Direction	Orientation Accuracy	Parallel to alignment rod/crossarm, or sighted to distant point	≤ ±5° from degrees true
Wind Direction	Linearity	Eight cardinal points on test fixture	≤ ±5° mean absolute error
Wind Direction	Response Threshold	Starting torque tested with torque gauge	< 10 g-cm Climatronics; < 20 g-cm R.M. Young
Wind Speed	Accuracy	Shaft rotational speed generated and measured with certified synchronous motor	≤ ±0.5 mps below 5.0 mps input; ≤ ±5.0% of input at or above 5.0 mps
Wind Speed	Starting Threshold	Starting torque tested with torque gauge	< 0.5 g-cm
Mass Flow Controller	Flow Rate	Comparison with Primary Standard	≤ ± 5.0% of designated rate

Sensor	Parameter	Audit Challenge	Acceptance Criteria
Ozone	Slope	Linear regression of multi-point test gas concentration as measured with a certified transfer standard	$0.9000 \leq m \leq 1.1000$
Ozone	Intercept		$-5.0 \text{ ppb} \leq b \leq 5.0 \text{ ppb}$
Ozone	Correlation Coefficient		$0.9950 \leq r$
DAS	Accuracy	Comparison with certified standard	$\leq \pm 0.003 \text{ VDC}$

Performance audits are conducted using standards that are traceable to the National Institute of Standards and Technology (NIST), or another authoritative organization, and certified as current.

Site systems audits are intended to provide a qualitative appraisal of the total measurement system. Site planning, organization, and operation are evaluated to ensure that good Quality Assurance/Quality Control (QA/QC) practices are being applied. At a minimum the following audit issues were addressed at each site systems audit:

- Site locations and configurations match those provided in the CASTNET QAPP.
- Meteorological instruments are in good physical and operational condition and are sited to meet EPA ambient monitoring guidelines (EPA-600/4-82-060).
- Sites are accessible, orderly, and if applicable, compliant with OSHA safety standards.
- Sampling lines are free of leaks, kinks, visible contamination, weathering, and moisture.
- Site shelters provide adequate temperature control.
- All ambient air quality instruments are functional, being operated in the appropriate range, and the zero air supply desiccant is unsaturated.
- All instruments are in current calibration.
- Site documentation (maintenance schedules, on-site SOPs, etc.) is current and log book records are complete.
- All maintenance and on-site SOPs are performed on schedule.
- Corrective actions are documented and appropriate for required maintenance/repair activity.
- Site operators demonstrate an adequate knowledge and ability to perform required site activities, including documentation and maintenance activities.

### 1.3 CASTNET Sites Visited Fourth Quarter 2014

This report consists of the systems and performance and other audit results from the CASTNET sites visited during the fourth quarter (October through December) of 2014. The locations and dates of the site visits for complete audits are presented in Table 2.

**Table 2. Site Audit Visits**

<u>Side ID</u>	<u>Audit Type</u>	<u>Sponsor</u>	<u>Site Visit Date</u>	<u>Station Name</u>
HWF187	Without met	EPA	10/1/2014	Huntington Wildlife Forest
ACA416	With met	NPS	10/03/2014	Acadia National Park
HOW191	Without met	EPA	10/6/2014	Howland Ameriflux
ASH135	Without met	EPA	10/7/2014	Ashland
PNF126	Without met	EPA	10/30/2014	Cranberry
ABT147	Without met	EPA	11/09/2014	Abington
WST109	Without met	EPA	11/10/2014	Woodstock
BEL116	Without met	EPA	11/10/2014	Beltsville

In addition to the sites listed in Table 2 that were visited for complete audits, the sites listed in Table 3 were visited to conduct Through-The-Probe (TTP) pollutant Performance Evaluations (PE).

**Table 3. TTP Pollutant PE Visits**

<u>Side ID</u>	<u>Audit Type</u>	<u>Sponsor</u>	<u>Site Visit Date</u>	<u>Station Name</u>
HWF187	NOy	EPA	09/30/2014	Huntington Wildlife Forest
GRS420	Ozone PE	NPS	10/27/2014	Great Smoky NP - Look Rock
PNF126	NOy	EPA	10/30/2014	Cranberry
PED108	Ozone PE	EPA	11/3/2014	Prince Edward

<b><u>Side ID</u></b>	<b><u>Audit Type</u></b>	<b><u>Sponsor</u></b>	<b><u>Site Visit Date</u></b>	<b><u>Station Name</u></b>
BEL116	SO <sub>2</sub>	EPA	11/10/2014	Beltsville
BEL116	Nitrotrain	EPA	11/10/2014	Beltsville
BWR139	Ozone PE	EPA	11/13/2014	Blackwater NWR
WSP144	Ozone PE	EPA	11/14/2014	Washington Crossing State Park
VPI120	Ozone PE	EPA	11/17/2014	Horton Station
SHN418	Ozone PE	NPS	11/18/2014	Shenandoah NP - Big Meadows
PAR107	Ozone PE	EPA	11/19/2014	Parsons
CDR119	Ozone PE	EPA	11/21/2014	Cedar Creek
CND125	Ozone PE	EPA	11/24/2014	Candor
BFT142	Ozone PE	EPA	11/25/2014	Beaufort

#### **1.4 Audit Results**

The observations and results of the systems and performance audits are included in Appendix A, *Audit Report Forms* by site, arranged by audit date.

Photographs of site conditions are included within each systems report where necessary.

Copies of the spot reports that were sent immediately following the audit of each site are included as Appendix B, *Site Spot Report Forms*.

The Ozone PE results and observations are included in Appendix C, *Ozone Performance Evaluation Forms*.



## 2.0 NADP Quarterly Report

### 2.1 Introduction

The National Atmospheric Deposition Program (NADP) operates three precipitation chemistry networks and two atmospheric concentration networks. The National Trends Network (NTN) has been measuring acidic precipitation since 1978. The network currently has more than 250 sites. The Atmospheric Integrated Research Monitoring Network (AIRMoN) began operation in 1992 and currently measures event based precipitation events at 6 sites. The Mercury Deposition Network (MDN) measures total mercury in precipitation samples from more than 120 stations. The MDN began operation in 1996 and includes sites throughout the US and Canada. The Atmospheric Mercury Network (AMNet) and the Ammonia Monitoring Network (AMoN) measure ambient concentrations of mercury and ammonia, respectively.

The NADP and other long-term monitoring networks provide critical information to the EPA regarding evaluating the effectiveness of emission reduction control programs from the power industry.

The NADP Program Office operates and administers the three precipitation chemistry networks (NTN, MDN and AIRMoN), two atmospheric concentration networks (AMNet and AMoN), two analytical laboratories (the Central Analytical Laboratory (CAL) located at the University of Illinois/Illinois State Water Survey and the Mercury Analytical Laboratory (HAL) located at Frontier Global Sciences), and the network equipment depot (NED).

### 2.2 Project Objectives

The objective of this project is to perform independent and unbiased evaluations of the sites along with its operations. These evaluations provide quality assurance pertaining to siting, sample collection and handling, equipment operation and maintenance, record keeping and field laboratory procedures.

More specifically, the surveys determine and report findings based on an established methodology consisting of completing a site questionnaire, testing the equipment and documenting with photographs the location, siting criteria, existing equipment, and any issues encountered that require such documentation.

### 2.3 Sites Visited Fourth Quarter 2014

This report covers the results from the NADP sites surveyed during the fourth quarter (October through December) of 2014. The station names and dates of the audits are presented in Table 4.

**Table 4. Sites Surveyed – Fourth Quarter 2015**

<u>Side ID</u>	<u>Network</u>	<u>Visit Date</u>	<u>Station Name</u>
ME00	MDN/NTN	10/7/2014	Caribou
ME94	NTN	10/10/2014	Indian Township
ME98	MDN/NTN	10/2/2014	Acadia National Park-McFarland Hill
MN08	NTN	10/22/2014	Hovland
MN16	MDN/NTN	10/20/2014	Marcell Experimental Forest
MN18	MDN/AMoN	10/21/2014	Fernberg
MN99	NTN	10/22/2014	Wolf Ridge
NC45	NTN	10/28/2014	Mt. Mitchell
NF19	MDN	10/15/2014	Stephenville
NS01	MDN/AMoN	10/13/2014	Kejimikujik National Park
CT15	NTN/AMoN	11/9/2014	Abington
MD99	MDN/NTN/AMoN	11/11/2014	Beltsville
NC03	NTN	11/17/2014	Lewiston
NC08	MDN	11/18/2014	Waccamaw State Park
NC34	NTN	11/24/2014	Piedmont Research Station
NC41	NTN	11/25/2014	Finley Farm
NH02	NTN/AMoN	11/10/2014	Hubbard Brook
NY29	NTN	11/13/2014	Moss Lake
NY52	NTN	11/13/2014	Bennett Bridge
NY99	NTN	11/7/2014	West Point
VA00	NTN	11/4/2014	Charlottesville
VA13	NTN	11/17/2014	Horton's Station
VA24	NTN/AMoN	11/3/2014	Prince Edward

<u>Side ID</u>	<u>Network</u>	<u>Visit Date</u>	<u>Station Name</u>
VA28	MDN/NTN	11/18/2014	Shenandoah NP - Big Meadows
VA99	NTN	11/25/2014	Natural Bridge Station
VT01	NTN	11/8/2014	Bennington
VT99	MDN/NTN/AMoN	11/12/2014	Underhill
WV04	NTN	11/24/2014	Babcock State Park
WV18	AMoN	11/19/2014	Parsons
WV99	AIRMoN	11/20/2014	Canaan Valley Institute

## 2.4 Survey Results

Site survey results are entered into a relational database. The database in turn generates Site Spot Reports which are distributed among the interested parties as soon as all the site data has been entered. Database tables with all the data collected and reviewed are then sent to the NADP Program Office and to the U.S. EPA Project Officers.

Other items gathered during the surveys (i.e., photographs, Belfort charts, etc.) are uploaded to EEMS' server where the NADP PO and the U.S. EPA POs can access them and download them as needed by login into the server site.

Given the volume of data generated, and the fact that data is distributed and/or is available through EEMS' server, no survey results are included in this report.

---

**APPENDIX A**

**CASTNET Audit Report Forms**

---

## *Site Inventory by Site Visit*

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>	
<i>HWF187-Eric Hebert-09/30/2014</i>						
1	9/30/2014	Computer	Dell	000290	D520	unknown
2	9/30/2014	DAS	Campbell	000356	CR3000	2134
3	9/30/2014	Elevation	Elevation	None	1	None
4	9/30/2014	Filter pack flow pump	Thomas	02358	illegible	illegible
5	9/30/2014	Flow Rate	Apex	000592	AXMC105LPM DPCV	illegible
6	9/30/2014	Infrastructure	Infrastructure	none	none	none
7	9/30/2014	Met tower	Universal Tower	03579	unknown	none
8	9/30/2014	Modem	Raven	06807	H4223-C	0934393748
9	9/30/2014	Ozone	ThermoElectron Inc	000681	49i A1NAA	1030244790
10	9/30/2014	Ozone Standard	ThermoElectron Inc	000445	49i A3NAA	CM08200021
11	9/30/2014	Sample Tower	Aluma Tower	illegible	B	AT-5107-E-4-12
12	9/30/2014	Shelter Temperature	Campbell	none	107-L	unknown
13	9/30/2014	Shield (10 meter)	RM Young	04676	Aspirated 43408	none
14	9/30/2014	Siting Criteria	Siting Criteria	None	1	None
15	9/30/2014	Temperature	RM Young	06401	41342VO	14034
16	9/30/2014	Zero air pump	Teledyne	000775	701H	611

# DAS Data Form

DAS Time Max Error:

Mfg	Serial Number	Site	Technician	Site Visit Date	Parameter	Use Desc.
Campbell	2134	HWF187	Eric Hebert	09/30/2014	DAS	Primary

Das Date:	<input type="text" value="10/1 /2014"/>	Audit Date:	<input type="text" value="10/1 /2014"/>
Das Time:	<input type="text" value="9:00:15"/>	Audit Time:	<input type="text" value="9:00:00"/>
Das Day:	<input type="text" value="274"/>	Audit Day:	<input type="text" value="274"/>
Low Channel:		High Channel:	
Avg Diff:	<input type="text" value="0.0002"/>	Max Diff:	<input type="text" value="0.0004"/>
		Avg Diff:	<input type="text" value="0.0002"/>
		Max Diff:	<input type="text" value="0.0004"/>

Mfg	<input type="text" value="HY"/>	Parameter	<input type="text" value="DAS"/>
Serial Number	<input type="text" value="12010039329"/>	Tfer Desc.	<input type="text" value="Source generator (D"/>
Tfer ID	<input type="text" value="01322"/>		
Slope	<input type="text" value="1.00000"/>	Intercept	<input type="text" value="0.00000"/>
Cert Date	<input type="text" value="6/15/2014"/>	CorrCoff	<input type="text" value="1.00000"/>
Mfg	<input type="text" value="Fluke"/>	Parameter	<input type="text" value="DAS"/>
Serial Number	<input type="text" value="86590148"/>	Tfer Desc.	<input type="text" value="DVM"/>
Tfer ID	<input type="text" value="01310"/>		
Slope	<input type="text" value="1.00000"/>	Intercept	<input type="text" value="0.00000"/>
Cert Date	<input type="text" value="1/22/2014"/>	CorrCoff	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
7	0.0000	-0.0004	0.0000	V	V	0.0004
7	0.1000	0.0997	0.0997	V	V	0.0000
7	0.2000	0.1996	0.1995	V	V	-0.0001
7	0.5000	0.4994	0.4995	V	V	0.0001
7	0.7000	0.6999	0.6997	V	V	-0.0002
7	0.9000	0.8995	0.8994	V	V	-0.0001
7	1.0000	1.0003	1.0005	V	V	0.0002

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Apex	illegible		HWF187	Eric Hebert	09/30/2014	Flow Rate	000592

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	131818	<b>Tfer Desc.</b>	BIOS 220-H
<b>Tfer ID</b>	01417		
<b>Slope</b>	1.00000	<b>Intercept</b>	0.00000
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
1.12%	1.35%

<b>Cal Factor Zero</b>	0.01
<b>Cal Factor Full Scale</b>	0.99
<b>Rotometer Reading:</b>	1.55

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignal	PctDifference
primary	pump off	0.000	0.000	0.01	0.000	0.02	l/m	l/m	
primary	leak check	0.000	0.000	0.01	0.000	0.01	l/m	l/m	
primary	test pt 1	1.483	1.480	1.52	0.000	1.50	l/m	l/m	1.35%
primary	test pt 2	1.485	1.480	1.51	0.000	1.50	l/m	l/m	1.35%
primary	test pt 3	1.492	1.490	1.52	0.000	1.50	l/m	l/m	0.67%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	See comments	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	6.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	0.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	180 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Tag Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1030244790	HWF187	Eric Hebert	09/30/2014	Ozone	000681

<b>Slope:</b>	0.97152	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.17924	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	1.00000	<b>CorrCoff</b>	0.00000

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0419606966	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01112		
<b>Slope</b>	1.00928	<b>Intercept</b>	0.11780
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
3.2%	3.4%		

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	-0.20	-0.31	-0.50	ppb	
primary	2	26.78	26.41	25.55	ppb	-3.26%
primary	3	47.59	47.03	45.44	ppb	-3.38%
primary	4	77.75	76.91	74.56	ppb	-3.06%
primary	5	107.83	106.72	103.50	ppb	-3.02%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.000	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.006	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	90.4 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>	See comments	<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.72 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	34.9 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	692.5 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	89.7 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.32 lpm	<b>Status</b>	Fail
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass



# Temperature Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	14034		HWF187	Eric Hebert	09/30/2014	Temperature	06401

<b>Mfg</b>	Extech	<b>Parameter</b>	Temperature
<b>Serial Number</b>	H232679	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01228		
<b>Slope</b>	1.00496	<b>Intercept</b>	-0.23009
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>		<b>DAS 2:</b>	
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>
0.14	0.29		

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Range	-0.02	0.21	0.000	0.3	C	0.06
primary	Temp Mid Range	24.57	24.68	0.000	24.6	C	-0.06
primary	Temp High Range	47.90	47.89	0.000	48.2	C	0.29

<b>Sensor Component</b>	Shield	<b>Condition</b>	Moderately clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	Functioning	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Campbell	unknown	HWF187	Eric Hebert	09/30/2014	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
0.28	0.36		

<b>Mfg</b>	Extech	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	H232679	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01228		
<b>Slope</b>	1.00496	<b>Intercept</b>	-0.23009
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Mid Range	22.40	22.52	0.000	22.9	C	0.36
primary	Temp Mid Range	22.02	22.14	0.000	22.4	C	0.21

## Infrastructure Data For

Site ID  Technician  Site Visit Date

Shelter Make	Shelter Model	Shelter Size
<input type="text" value="ESF"/>	<input type="text" value="none"/>	<input type="text" value="1630 cuft"/>

Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text" value="Type B"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Functioning"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="3/8 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>

# Site Visit Comments

Parameter	Site	Technician	S.V. Date	Component	Mfg	Serial No.	Hazard	Problem
Flow Rate	HWF187	Eric Hebert	09/30/2014	Moisture Present	Apex	4026	<input type="checkbox"/>	<input type="checkbox"/>
The filter sample tubing has drops of moisture in low sections outside the shelter.								
Ozone	HWF187	Eric Hebert	09/30/2014	Cell A Flow	ThermoElectron	3368	<input type="checkbox"/>	<input checked="" type="checkbox"/>
This analyzer diagnostic check is outside the manufacturer's recommended value.								

# Field Systems Comments

1 **Parameter:** SiteOpsProcedures

The ozone inlet filter is replaced and the sample train is leak tested every other week.

2 **Parameter:** ShelterCleanNotes

The shelter is in good condition.

# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)	<input type="text" value="EPA"/>	USGS Map	<input type="text" value="Newcomb"/>
Operating Group	<input type="text" value="SUNY/ESF"/>	Map Scale	<input type="text"/>
AQS #	<input type="text" value="36-031-9991"/>	Map Date	<input type="text"/>
Meteorological Type	<input type="text" value="R.M. Young"/>		
Air Pollutant Analyzer	<input type="text" value="Ozone, Hg"/>	QAPP Latitude	<input type="text" value="43.9732"/>
Deposition Measurement	<input type="text" value="dry, wet, Hg"/>	QAPP Longitude	<input type="text" value="-74.2232"/>
Land Use	<input type="text" value="woodland - mixed"/>	QAPP Elevation Meters	<input type="text" value="502"/>
Terrain	<input type="text" value="complex"/>	QAPP Declination	<input type="text" value="14.5"/>
Conforms to MLM	<input type="text" value="No"/>	QAPP Declination Date	<input type="text" value="6/17/2004"/>
Site Telephone	<input type="text" value="(518) 582-4800"/>	Audit Latitude	<input type="text" value="43.973044"/>
Site Address 1	<input type="text" value="Adirondack Ecological Center"/>	Audit Longitude	<input type="text" value="-74.223317"/>
Site Address 2	<input type="text"/>	Audit Elevation	<input type="text" value="497"/>
County	<input type="text" value="Essex"/>	Audit Declination	<input type="text" value="-14"/>
City, State	<input type="text" value="Newcomb, NY"/>		
Zip Code	<input type="text" value="12852"/>	Fire Extinguisher <input checked="" type="checkbox"/>	<input type="text" value="Inspected Oct 2014"/>
Time Zone	<input type="text" value="Eastern"/>	First Aid Kit <input checked="" type="checkbox"/>	<input type="text"/>
Primary Operator	<input type="text"/>	Safety Glasses <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. Phone #	<input type="text"/>	Safety Hard Hat <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. E-mail	<input type="text"/>	Climbing Belt <input checked="" type="checkbox"/>	<input type="text"/>
Backup Operator	<input type="text"/>	Security Fence <input type="checkbox"/>	<input type="text"/>
Backup Op. Phone #	<input type="text"/>	Secure Shelter <input type="checkbox"/>	<input type="text"/>
Backup Op. E-mail	<input type="text"/>	Stable Entry Step <input checked="" type="checkbox"/>	<input type="text"/>
Shelter Working Room <input checked="" type="checkbox"/>	Make <input type="text" value="ESF"/>	Model <input type="text" value="none"/>	Shelter Size <input type="text" value="1630 cuft"/>
Shelter Clean <input checked="" type="checkbox"/>	Notes <input type="text" value="The shelter is in good condition."/>		
Site OK <input checked="" type="checkbox"/>	Notes <input type="text"/>		

Driving Directions

# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID

Technician

Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km	<input type="text"/>	<input checked="" type="checkbox"/>
City > 50,000 population	40 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Feedlot operations	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Limited agricultural operations	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Large parking lot	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Small parking lot	100 m	<input type="text"/>	<input checked="" type="checkbox"/>
Tree line	50 m	20 m	<input type="checkbox"/>
Obstacles to wind	10 times obstacle height	<input type="text"/>	<input checked="" type="checkbox"/>

Siting Distances OK

Siting Criteria Comment

# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID

Technician

Site Visit Date

- |    |  |                                     |     |
|----|--|-------------------------------------|-----|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> | N/A |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> | N/A |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> | N/A |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |     |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |     |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> | N/A |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> | N/A |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> | N/A |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> | N/A |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> | N/A |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | N/A |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:



# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

Technician

Site Visit Date

1	Do all the meteorological sensors appear to be intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	Temperature only
2	Are all the meteorological sensors operational online, and reporting data?	<input checked="" type="checkbox"/>	Temperature only
3	Are the shields for the temperature and RH sensors clean?	<input checked="" type="checkbox"/>	Moderately clean
4	Are the aspirated motors working?	<input checked="" type="checkbox"/>	
5	Is the solar radiation sensor's lens clean and free of scratches?	<input checked="" type="checkbox"/>	N/A
6	Is the surface wetness sensor grid clean and undamaged?	<input checked="" type="checkbox"/>	N/A
7	Are the sensor signal and power cables intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	
8	Are the sensor signal and power cable connections protected from the elements and well maintained?	<input checked="" type="checkbox"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID

Technician

Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- 1 Do the sample inlets have at least a 270 degree arc of unrestricted airflow?
- 2 Are the sample inlets 3 - 15 meters above the ground?
- 3 Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees?


**Pollutant analyzers and deposition equipment operations and maintenance**

- 1 Do the analyzers and equipment appear to be in good condition and well maintained?
- 2 Are the analyzers and monitors operational, on-line, and reporting data?
- 3 Describe ozone sample tube.
- 4 Describe dry dep sample tube.
- 5 Are in-line filters used in the ozone sample line? (if yes indicate location)
- 6 Are sample lines clean, free of kinks, moisture, and obstructions?
- 7 Is the zero air supply desiccant unsaturated?
- 8 Are there moisture traps in the sample lines?
- 9 Is there a rotometer in the dry deposition filter line, and is it clean?

1/4 teflon by 12 meters
3/8 teflon by 12 meters
At inlet only
Moisture in tubing only
Flow line only
Clean and dry

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

--

# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

- |                                     |  |  |                  |          |                                     |                                     |  |
|-------------------------------------|--|--|------------------|----------|-------------------------------------|-------------------------------------|--|
| 1                                   | Do the DAS instruments appear to be in good condition and well maintained?           | <input checked="" type="checkbox"/>  |                  |          |                                     |                                     |  |
| 2                                   | Are all the components of the DAS operational? (printers, modem, backup, etc)        | <input checked="" type="checkbox"/>  |                  |          |                                     |                                     |  |
| 3                                   | Do the analyzer and sensor signal leads pass through lightning protection circuitry? | <input checked="" type="checkbox"/>  | Met sensors only |          |                                     |                                     |  |
| 4                                   | Are the signal connections protected from the weather and well maintained?           | <input checked="" type="checkbox"/>  |                  |          |                                     |                                     |  |
| 5                                   | Are the signal leads connected to the correct DAS channel?                           | <input checked="" type="checkbox"/>  |                  |          |                                     |                                     |  |
| 6                                   | Are the DAS, sensor translators, and shelter properly grounded?                      | <input checked="" type="checkbox"/>  |                  |          |                                     |                                     |  |
| 7                                   | Does the instrument shelter have a stable power source?                              | <input checked="" type="checkbox"/>  |                  |          |                                     |                                     |  |
| 8                                   | Is the instrument shelter temperature controlled?                                    | <input checked="" type="checkbox"/>  |                  |          |                                     |                                     |  |
| 9                                   | Is the met tower stable and grounded?  | <table border="1"><tr><td>Stable</td><td>Grounded</td></tr><tr><td><input checked="" type="checkbox"/></td><td><input checked="" type="checkbox"/></td></tr></table> | Stable           | Grounded | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |  |
| Stable                              | Grounded   |  |                  |          |                                     |                                     |  |
| <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/>  |  |                  |          |                                     |                                     |  |
| 10                                  | Is the sample tower stable and grounded?   | <table border="1"><tr><td>Stable</td><td>Grounded</td></tr><tr><td><input checked="" type="checkbox"/></td><td><input checked="" type="checkbox"/></td></tr></table> | Stable           | Grounded | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |  |
| Stable                              | Grounded   |  |                  |          |                                     |                                     |  |
| <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/>  |  |                  |          |                                     |                                     |  |
| 11                                  | Tower comments?  |  |                  |          |                                     |                                     |  |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Computer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Solar radiation sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Modem	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Printer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	UPS	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Ozone analyzer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Filter pack flow controller	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input checked="" type="checkbox"/>	Oct 2001	<input type="checkbox"/>
HASP	<input checked="" type="checkbox"/>	Nov 2009	<input checked="" type="checkbox"/>
Field Ops Manual	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Calibration Reports	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Preventive maintenance schedul	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>

- 1 Is the station log properly completed during every site visit?
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?  Control charts not used

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID

Technician

Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Every 2 weeks"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Zero Air Desiccant Check	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID

Technician

Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed morinings
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF, call-in
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	Clean gloves on and off
9	Are the site conditions reported regularly to the field operations manager or staff?	<input checked="" type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input type="checkbox"/>	<input type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID

Technician

Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
Computer	Dell	D520	unknown	000290
DAS	Campbell	CR3000	2134	000356
Elevation	Elevation	1	None	None
Filter pack flow pump	Thomas	illegible	illegible	02358
Flow Rate	Apex	AXMC105LPMDPC	illegible	000592
Infrastructure	Infrastructure	none	none	none
Met tower	Universal Tower	unknown	none	03579
Modem	Raven	H4223-C	0934393748	06807
Ozone	ThermoElectron Inc	49i A1NAA	1030244790	000681
Ozone Standard	ThermoElectron Inc	49i A3NAA	CM08200021	000445
Sample Tower	Aluma Tower	B	AT-5107-E-4-12	illegible
Shelter Temperature	Campbell	107-L	unknown	none
Shield (10 meter)	RM Young	Aspirated 43408	none	04676
Siting Criteria	Siting Criteria	1	None	None
Temperature	RM Young	41342VO	14034	06401
Zero air pump	Teledyne	701H	611	000775

# *Site Inventory by Site Visit*

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>	
<i>ACA416-Eric Hebert-10/03/2014</i>						
1	10/3/2014	Computer	Hewlett Packard	none	8460p	CNU20941M6
2	10/3/2014	DAS	Environmental Sys Corp	ACADIA1	8832	unknown2
3	10/3/2014	Delta Temperature	Climatronics	none	100093	illegible
4	10/3/2014	Elevation	Elevation	None	1	None
5	10/3/2014	F460 translator	Climatronics	none	100163	683
6	10/3/2014	Filter pack flow pump	Thomas	none	107CAB11	109500000040
7	10/3/2014	Flow Rate	Tylan	none	FC260	AW02213003
8	10/3/2014	Infrastructure	Infrastructure	none	none	none
9	10/3/2014	Mainframe	Climatronics	01342	100081	1288
10	10/3/2014	Met tower	Climatronics	none	unknown	illegible
11	10/3/2014	MFC power supply	Tylan	none	RO-32	none
12	10/3/2014	Modem	US Robotics	none	33.6 fax modem	unknown
13	10/3/2014	Ozone	ThermoElectron Inc	90744	49C	49C-74536-376
14	10/3/2014	Ozone Standard	ThermoElectron Inc	none	49CPS	49CPS-70752-366
15	10/3/2014	Precipitation	Climatronics	01322	100508-2	illegible
16	10/3/2014	Precipitation	Texas Electronics	02179	TR-525i-HT	illegible
17	10/3/2014	Printer	Hewlett Packard	none	842C	unknown
18	10/3/2014	Relative Humidity	Vaisala	none	HMP45AC	Y0730050
19	10/3/2014	Sample Tower	Aluma Tower	none	B	AT-71103-7I-3
20	10/3/2014	Shelter Temperature	unknown	none	none	none
21	10/3/2014	Shield (10 meter)	Climatronics	none	100325	illegible
22	10/3/2014	Shield (2 meter)	Climatronics	none	100325	illegible
23	10/3/2014	Siting Criteria	Siting Criteria	None	1	None
24	10/3/2014	Solar Radiation	Licor	none	LI-200	PY16746
25	10/3/2014	Solar Radiation Translator	Climatronics	none	100144	309
26	10/3/2014	Surface Wetness	RM Young	90725	58101	none
27	10/3/2014	Temperature	Climatronics	none	100093	illegible
28	10/3/2014	Temperature Translator	Climatronics	03630	100088-2	401



---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>	
29	10/3/2014	Wind Direction	Climatronics	none	100076	illegible
30	10/3/2014	Wind Speed	Climatronics	none	100075	1947
31	10/3/2014	Zero air pump	ThermoElectron Inc	none	111	111-30215-237

---

# DAS Data Form

DAS Time Max Error:

Mfg	Serial Number	Site	Technician	Site Visit Date	Parameter	Use Desc.
Environmental Sys	unknown2	ACA416	Eric Hebert	10/03/2014	DAS	Primary

**Das Date:**       **Audit Date:**   
**Das Time:**       **Audit Time:**   
**Das Day:**       **Audit Day:**

**Low Channel:**      **High Channel:**  
**Avg Diff:**      **Max Diff:**      **Avg Diff:**      **Max Diff:**  
                 

<b>Mfg</b>	<input type="text" value="HY"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="12010039329"/>	<b>Tfer Desc.</b>	<input type="text" value="Source generator (D"/>
<b>Tfer ID</b>	<input type="text" value="01322"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="6/15/2014"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>
<b>Mfg</b>	<input type="text" value="Fluke"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="86590148"/>	<b>Tfer Desc.</b>	<input type="text" value="DVM"/>
<b>Tfer ID</b>	<input type="text" value="01310"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="1/22/2014"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
2	0.0000	-0.0002	-0.0002	V	V	0.0000
2	0.1000	0.1001	0.1002	V	V	0.0001
2	0.3000	0.3010	0.3011	V	V	0.0001
2	0.5000	0.5004	0.5004	V	V	0.0000
2	0.7000	0.6991	0.6991	V	V	0.0000
2	0.9000	0.8995	0.8995	V	V	0.0000
2	1.0000	0.9997	0.9996	V	V	-0.0001
15	0.0000	-0.0005	-0.0006	V	V	-0.0001
15	0.1000	0.0997	0.0997	V	V	0.0000
15	0.3000	0.2999	0.2994	V	V	-0.0005
15	0.5000	0.4998	0.4995	V	V	-0.0003
15	0.7000	0.6990	0.6984	V	V	-0.0006
15	0.9000	0.8998	0.8996	V	V	-0.0002
15	1.0000	0.9998	0.9992	V	V	-0.0006

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Tylan	AW02213003	ACA416	Eric Hebert	10/03/2014	Flow Rate	none

<b>Mfg</b>	Tylan
<b>SN/Owner ID</b>	none none
<b>Parameter</b>	MFC power supply

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	131818	<b>Tfer Desc.</b>	BIOS 220-H
<b>Tfer ID</b>	01417		
<b>Slope</b>	1.00000	<b>Intercept</b>	0.00000
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
6.30%	6.44%

<b>Cal Factor Zero</b>	0.03
<b>Cal Factor Full Scale</b>	15.05
<b>Rotometer Reading:</b>	1.6

UseDescription:	Test type:	Input l/m:	Input STP:	MfcDisp.:	OutputSignal:	Output S E:	InputUnit:	OutputSignal:	PctDifference:
primary	pump off	0.000	0.000	-0.08	-0.025	-0.04	l/m	l/m	
primary	leak check	0.000	0.000	-0.08	-0.025	-0.04	l/m	l/m	
primary	test pt 1	0.000	1.593	0.96	0.481	1.49	l/m	l/m	-6.44%
primary	test pt 2	0.000	1.592	0.96	0.481	1.49	l/m	l/m	-6.38%
primary	test pt 3	0.000	1.587	0.96	0.481	1.49	l/m	l/m	-6.08%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	90 deg	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	- 2.0 cm	<b>Status</b>	Fail
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Poor	<b>Status</b>	Fail
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	See comments	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>	See comments	<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	6.0 cm	<b>Status</b>	pass

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Tag</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	49C-74536-376		ACA416	Eric Hebert	10/03/2014	Ozone	90744

<b>Slope:</b>	1.02704	<b>Slope:</b>	0.00000
<b>Intercept</b>	0.18362	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99995	<b>CorrCoff</b>	0.00000

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0419606966	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01112		
<b>Slope</b>	1.00928	<b>Intercept</b>	0.11780
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
2.9%	3.4%		

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	0.16	0.04	0.47	ppb	
primary	2	29.03	28.64	29.54	ppb	3.14%
primary	3	52.38	51.78	53.26	ppb	2.86%
primary	4	76.89	76.06	77.73	ppb	2.20%
primary	5	104.61	103.53	107.00	ppb	3.35%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.7 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	9.9976	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.1	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.059	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	83.9 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>	See comments	<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Fair	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.73 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	34.2 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	752 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.8 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	91.3 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.72 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	0.000	<b>Status</b>	pass

# Wind Speed Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Climatronics	1947		ACA416	Eric Hebert	10/03/2014	Wind Speed	none

<b>Mfg</b>	Climatronics
<b>SN/Owner ID</b>	683 none
<b>Parameter</b>	F460 translator

<b>Prop or Cups SN</b>	2033
<b>Prop or Cups Torque</b>	0.3 to 0.3
<b>Prop Correction Fact</b>	N/A

<b>Mfg</b>	RM Young	<b>Parameter</b>	wind speed
<b>Serial Number</b>		<b>Tfer Desc.</b>	wind speed motor (h
<b>Tfer ID</b>	01262		
<b>Slope</b>	1.00000	<b>Intercept</b>	0.00000
<b>Cert Date</b>	1/16/2014	<b>CorrCoff</b>	1.00000
<b>Mfg</b>	RM Young	<b>Parameter</b>	wind speed
<b>Serial Number</b>		<b>Tfer Desc.</b>	wind speed motor (l
<b>Tfer ID</b>	01261		
<b>Slope</b>	1.00000	<b>Intercept</b>	0.00000
<b>Cert Date</b>	1/16/2014	<b>CorrCoff</b>	1.00000

	<b>DAS 1:</b>		<b>DAS 2:</b>	
	<b>Low Range</b>	<b>High Range</b>	<b>Low Range</b>	<b>High Range</b>
<b>Abs Avg Err</b>	0.17	10.23%		
<b>Abs Max Er</b>	0.20	38.59%		

UseDescription:	InputDevice:	Input RPM:	Input m/s:	Output V:	DAS m/s:	Diff/ %Diff:	Difference:
primary	00000	0	0.20	0.000	0.0		-0.20
primary	00000	50	1.40	0.000	1.2		-0.20
primary	00000	100	2.57	0.000	2.4		-0.17
primary	00000	170	4.22	0.000	4.1		-0.12
primary	00000	250	6.10	0.000	6.0	-1.64%	
primary	00000	500	11.97	0.000	11.9	-0.58%	
primary	00000	800	19.02	0.000	19.0	-0.11%	
primary	00000	2000	47.22	0.000	29.0	-38.59%	

<b>Sensor Component</b>	System Memo	<b>Condition</b>	See comments	<b>Status</b>	pass
<b>Sensor Component</b>	Sensor Plumb	<b>Condition</b>	Plumb	<b>Status</b>	pass
<b>Sensor Component</b>	Sensor Heater	<b>Condition</b>	Functioning	<b>Status</b>	pass
<b>Sensor Component</b>	Prop or Cups Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Torque	<b>Condition</b>	Good	<b>Status</b>	pass

# Wind Direction Data Form

Mfg	Serial Number	Ta	Site	Technician	Site Visit Date	Parameter	Owner ID
Climatronics	illegible		ACA416	Eric Hebert	10/03/2014	Wind Direction	none

Mfg	Climatronics
SN/Owner ID	683 none
Parameter	F460 translator

Mfg	RM Young	Parameter	wind direction
Serial Number		Tfer Desc.	wind direction wheel
Tfer ID	01264		

Vane SN: 1491 C. A. Align. deg. true:

Vane Torque 10 to 10 180

Mfg	Ushikata	Parameter	wind direction
Serial Number	190037	Tfer Desc.	transit
Tfer ID	01265		
Slope	1.00000	Intercept	0.00000
Cert Date	1/30/2012	CorrCoff	1.00000

DAS 1:	DAS 2:		
Orientation	Linearity:	Orientation	Linearity:
Abs Avg Err	2.6	1.5	
Abs Max Er	5	3	

UseDescription:	TferID:	Input Raw:	Linearity	Output V:	Output Deg.:	Difference:	Change:	Error:
primary	01264	0	<input checked="" type="checkbox"/>	0.000	357	3	42	-3
primary	01264	45	<input checked="" type="checkbox"/>	0.000	42	3	45	0
primary	01264	90	<input checked="" type="checkbox"/>	0.000	85	5	43	-2
primary	01264	135	<input checked="" type="checkbox"/>	0.000	132	3	47	2
primary	01264	180	<input checked="" type="checkbox"/>	0.000	178	2	46	1
primary	01264	225	<input checked="" type="checkbox"/>	0.000	222	3	44	-1
primary	01264	270	<input checked="" type="checkbox"/>	0.000	268	2	46	1
primary	01264	315	<input checked="" type="checkbox"/>	0.000	315	0	47	2
primary	01265	90	<input type="checkbox"/>	0.000	85	5		5
primary	01265	90	<input type="checkbox"/>	0.000	89	1		1
primary	01265	180	<input type="checkbox"/>	0.000	178	2		2
primary	01265	270	<input type="checkbox"/>	0.000	268	2		2
primary	01265	360	<input type="checkbox"/>	0.000	357	3		3

Sensor Component	Mast	Condition	Good	Status	pass
Sensor Component	Condition	Condition	Good	Status	pass
Sensor Component	Sensor Heater	Condition	Functioning	Status	pass
Sensor Component	Sensor Plumb	Condition	Plumb	Status	pass
Sensor Component	Torque	Condition	Good	Status	pass
Sensor Component	Vane Condition	Condition	Good	Status	pass
Sensor Component	System Memo	Condition		Status	pass

# Temperature Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Climatronics	illegible		ACA416	Eric Hebert	10/03/2014	Temperature	none

<b>Mfg</b>	Climatronics
<b>SN/Owner ID</b>	401 03630
<b>Parameter</b>	Temperature Translator

<b>Mfg</b>	Extech	<b>Parameter</b>	Temperature
<b>Serial Number</b>	H232679	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01228		
<b>Slope</b>	1.00496	<b>Intercept</b>	-0.23009
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>
0.17	0.27		

UseDesc.:	Test type:	InputTmpRaw	InputTmpCorr.:	OutputTmpSignal:	OutputSignalEng:	OSE Unit:	Difference:
primary	Temp Low Range	-0.10	0.13	0.377	0.2	C	0.03
primary	Temp Mid Range	25.65	25.75	0.694	25.5	C	-0.22
primary	Temp High Range	49.95	49.93	0.995	49.7	C	-0.27

<b>Sensor Component</b>	Shield	<b>Condition</b>	Moderately clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	Functioning	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Humidity Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Vaisala	Y0730050		ACA416	Eric Hebert	10/03/2014	Relative Humidity	none

<b>Mfg</b>	Rotronic	<b>Parameter</b>	Relative Humidity
<b>Serial Number</b>	124432	<b>Tfer Desc.</b>	Hygroclip
<b>Tfer ID</b>	01225		
<b>Slope</b>	1.00000	<b>Intercept</b>	0.00000
<b>Cert Date</b>	1/29/2013	<b>CorrCoff</b>	1.00000

**DAS 1:**

**DAS 2:**

	<b>Low Range</b>	<b>High Range</b>	<b>Low Range</b>	<b>High Range</b>
<b>Abs Avg Err</b>	1.3			
<b>Abs Max Er</b>	2.0			

UseDesc.:	Test type:	Device:	Input RH:	GTL Raw:	RH Corr.:	DAS Volts:	DAS %RH:	Difference:
primary	RH Low Range	Hygroclip	32.8	0.0	32.8	0.328	32.8	0.0
primary	RH Low Range	Hygroclip	52.9	0.0	52.9	0.510	51.0	-1.9
primary	RH High Range	Hygroclip	75.3	0.0	75.3	0.734	73.4	-2.0

<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	RH Filter	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Shield	<b>Condition</b>	Moderately clean	<b>Status</b>	pass



# Solar Radiation Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Licor	PY16746		ACA416	Eric Hebert	10/03/2014	Solar Radiation	none

<b>Mfg</b>	Climatronics	
<b>SN/Owner ID</b>	309	none
<b>Parameter</b>	Solar Radiation Translator	

<b>Mfg</b>	Eppley	<b>Parameter</b>	solar radiation
<b>Serial Number</b>	10765	<b>Tfer Desc.</b>	SR transfer translat
<b>Tfer ID</b>	01246		
<b>Slope</b>	1.00000	<b>Intercept</b>	0.00000
<b>Cert Date</b>	12/16/2010	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>
% Diff of Avg	%Diff of Max
%Diff of Avg	%Diff of Max

<b>Mfg</b>	Eppley	<b>Parameter</b>	solar radiation
<b>Serial Number</b>	34341F3	<b>Tfer Desc.</b>	SR transfer sensor
<b>Tfer ID</b>	01245		
<b>Slope</b>	1.00000	<b>Intercept</b>	0.00000
<b>Cert Date</b>	12/16/2010	<b>CorrCoff</b>	1.00000

2.6%	1.8%	0.0%	0.0%
------	------	------	------

UseDescription:	Measure Date	MeasureTime	Tfer Corr:	DAS w/m2:	PctDifference:
primary	10/3/2014	8:00	647	636	-1.8%
primary	10/3/2014	9:00	522	505	-3.2%
primary	10/3/2014	10:00	425	410	-3.5%
primary	10/3/2014	11:00	495	462	-6.7%
primary	10/3/2014	12:00	420	402	-4.3%
primary	10/3/2014	14:00	278	288	3.7%
primary	10/3/2014	15:00	371	371	0.2%
primary	10/3/2014	16:00	418	409	-2.0%

<b>Sensor Component</b>	Sensor Level	<b>Condition</b>	Level	<b>Status</b>	pass
<b>Sensor Component</b>	Sensor Clean	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Properly Sited	<b>Condition</b>	Properly sited	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Precipitation Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Climatronics	illegible		ACA416	Eric Hebert	10/03/2014	Precipitation	01322

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
2.0%	4.0%		

<b>Mfg</b>	PMP	<b>Parameter</b>	Precipitation
<b>Serial Number</b>	EW-06134-50	<b>Tfer Desc.</b>	250ml graduate
<b>Tfer ID</b>	01250		
<b>Slope</b>	1.00000	<b>Intercept</b>	0.00000
<b>Cert Date</b>	9/5/2005	<b>CorrCoff</b>	1.00000

UseDesc.	Test type:	TferVolume:	Iteration:	TimePerTip:	Eq.Ht:	DAS eng:	Eq.HtUnit:	OSE Unit:	TferUnits:	PctDifference
primary	test 1	231.5	1	8 - 10 sec	5.00	4.80	mm	mm	ml	-4.0%
primary	test 2	231.5	2	8 - 10 sec	5.00	5.00	mm	mm	ml	0.0%

<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Sensor Heater	<b>Condition</b>	Functioning	<b>Status</b>	pass
<b>Sensor Component</b>	Properly Sited	<b>Condition</b>	See comments	<b>Status</b>	pass
<b>Sensor Component</b>	Gauge Drain Screen	<b>Condition</b>	Not installed	<b>Status</b>	pass
<b>Sensor Component</b>	Level	<b>Condition</b>	Level	<b>Status</b>	pass
<b>Sensor Component</b>	Gauge Clean	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Funnel Clean	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Gauge Screen	<b>Condition</b>	Installed	<b>Status</b>	pass

# Surface Wetness Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	none		ACA416	Eric Hebert	10/03/2014	Surface Wetness	90725

<b>Mfg</b>	Ohmite	<b>Parameter</b>	surface wetness
<b>Serial Number</b>	296-1200	<b>Tfer Desc.</b>	decade box
<b>Tfer ID</b>	01210		
<b>Slope</b>	1.00000	<b>Intercept</b>	0.00000
<b>Cert Date</b>	1/4/2011	<b>CorrCoff</b>	1.00000

**Manual Test Pass**

UseDescription:	Test Type:	Tfer kOhms:	OutputSignal:	DAS eng:	OutputSignalEngUni	TferUnits:	OutputSignalUnit
primary	wet	N/A	0.994	99.40	V	N/A	% Wet
primary	dry	N/A	0.298	0.30	V	N/A	% Wet

<b>Sensor Component</b>	Grid Orientation	<b>Condition</b>	North	<b>Status</b>	pass
<b>Sensor Component</b>	Grid Clean	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Grid Angle	<b>Condition</b>	about 45 deg	<b>Status</b>	pass
<b>Sensor Component</b>	Grid Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Properly Sited	<b>Condition</b>	Properly sited	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Grid Type	<b>Condition</b>	Grid without holes	<b>Status</b>	pass

# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
unknown	none	ACA416	Eric Hebert	10/03/2014	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
1.24	2.27		

<b>Mfg</b>	Extech	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	H232679	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01228		
<b>Slope</b>	1.00496	<b>Intercept</b>	-0.23009
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

UseDesc.:	Test type:	InputTmpRaw	InputTmpCorr.:	OutputTmpSignal:	OutputSignalEng:	OSE Unit:	Difference:
primary	Temp Mid Range	19.30	19.43	0.000	21.7	C	2.27
primary	Temp Mid Range	21.85	21.97	0.000	22.4	C	0.4
primary	Temp Mid Range	21.02	21.15	0.000	22.2	C	1.04

## Infrastructure Data For

Site ID  Technician  Site Visit Date

Shelter Make	Shelter Model	Shelter Size
<input type="text" value="Ekto"/>	<input type="text" value="8818 (s/n 2920-1)"/>	<input type="text" value="1152 cuft"/>

Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text" value="Type B"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Not installed"/>	Status	<input type="text" value="Fail"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Functioning"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="3/8 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="Pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>

# Site Visit Comments

Parameter	Site	Technician	S.V. Date	Component	Mfg	Serial No.	Hazard	Problem
Flow Rate	ACA416	Eric Hebert	10/03/2014	Moisture Present	Tylan	4022	<input type="checkbox"/>	<input type="checkbox"/>
Although there currently is no moisture in the flow sample train, there is evidence of previous moisture events.								
Flow Rate	ACA416	Eric Hebert	10/03/2014	Moisture Present	Tylan	4022	<input type="checkbox"/>	<input type="checkbox"/>
The filter sample tubing has drops of moisture in low sections outside the shelter.								
Ozone	ACA416	Eric Hebert	10/03/2014	System Memo	ThermoElectron	814	<input type="checkbox"/>	<input type="checkbox"/>
The ozone sample train is composed of materials other than the recommended materials which are Teflon and glass only.								
Precipitation	ACA416	Eric Hebert	10/03/2014	Properly Sited	Climatronics	4018	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Objects violate the 45 degree rule for the tipping bucket rain gage.								

# Field Systems Comments

1 **Parameter:** SiteOpsProcComm

This site is operated partly by the NPS and the State of Maine DEP. It is not visited by ARS for semiannual calibration and maintenance visits. The site operator does not perform many of the routine checks conducted at other CASTNET sites, such as tip checks, wetness sensor tests, and visual checks of the blowers. The state of Maine personnel maintain the meteorological systems.

2 **Parameter:** DocumentationCo

The site operator reported that low flow rate conditions had been observed and reported to ARS recently. The Flow controller has been replaced since then to correct the issue.

3 **Parameter:** SiteOpsProcedures

The meteorological and ozone instrument checks and maintenance are performed by the State of Maine DEP.

4 **Parameter:** ShelterCleanNotes

The shelter is clean and well organized.

5 **Parameter:** PollAnalyzerCom

The ozone sample inlet still has a stainless steel fittings. The recommended material for ozone sample train is Teflon or glass. The site operator indicated that the fittings would be changed.

6 **Parameter:** MetSensorComme

The wind speed translator span is set to 25 m/s and not 50 m/s. This may have affected the low output observed at the highest wind speed challenge.

7 **Parameter:** MetOpMaintCom

The sensor signal cables are beginning to show signs of wear.



# Field Systems Data Form

F-02058-1500-S1-rev001

Site ID  Technician  Site Visit Date

Site Sponsor (agency)	<input type="text" value="NPS/EPA"/>	USGS Map	<input type="text" value="Salsbury Cove"/>
Operating Group	<input type="text" value="NPS/MEDEP"/>	Map Scale	<input type="text"/>
AQS #	<input type="text" value="23-009-0103"/>	Map Date	<input type="text"/>
Meteorological Type	<input type="text" value="Climatronics"/>		
Air Pollutant Analyzer	<input type="text" value="Ozone, SO2, NOx, NOy, PM, VOC"/>	QAPP Latitude	<input type="text" value="44.3770"/>
Deposition Measurement	<input type="text" value="dry, wet, Hg"/>	QAPP Longitude	<input type="text" value="-68.2610"/>
Land Use	<input type="text" value="Costal, woodland - mixed"/>	QAPP Elevation Meters	<input type="text" value="158"/>
Terrain	<input type="text" value="rolling"/>	QAPP Declination	<input type="text"/>
Conforms to MLM	<input type="text" value="No"/>	QAPP Declination Date	<input type="text"/>
Site Telephone	<input type="text" value="(432) 288-9322"/>	Audit Latitude	<input type="text" value="44.377086"/>
Site Address 1	<input type="text" value="Route 233"/>	Audit Longitude	<input type="text" value="-68.2608"/>
Site Address 2	<input type="text"/>	Audit Elevation	<input type="text" value="153"/>
County	<input type="text" value="Hancock"/>	Audit Declination	<input type="text" value="-16.4"/>
City, State	<input type="text" value="Bar Harbor, ME"/>		
Zip Code	<input type="text" value="04609"/>	Fire Extinguisher <input checked="" type="checkbox"/>	<input type="text" value="Inspected Dec 2011"/>
Time Zone	<input type="text" value="Eastern"/>	First Aid Kit <input checked="" type="checkbox"/>	<input type="text"/>
Primary Operator	<input type="text"/>	Safety Glasses <input type="checkbox"/>	<input type="text"/>
Primary Op. Phone #	<input type="text"/>	Safety Hard Hat <input type="checkbox"/>	<input type="text"/>
Primary Op. E-mail	<input type="text"/>	Climbing Belt <input type="checkbox"/>	<input type="text"/>
Backup Operator	<input type="text"/>	Security Fence <input type="checkbox"/>	<input type="text"/>
Backup Op. Phone #	<input type="text"/>	Secure Shelter <input checked="" type="checkbox"/>	<input type="text"/>
Backup Op. E-mail	<input type="text"/>	Stable Entry Step <input checked="" type="checkbox"/>	<input type="text"/>
Shelter Working Room <input checked="" type="checkbox"/>	Make <input type="text" value="Ekto"/>	Model <input type="text" value="8818 (s/n 2920-1)"/>	Shelter Size <input type="text" value="1152 cuft"/>
Shelter Clean <input checked="" type="checkbox"/>	Notes <input type="text" value="The shelter is clean and well organized."/>		
Site OK <input checked="" type="checkbox"/>	Notes <input type="text"/>		

Driving Directions



# Field Systems Data Form

F-02058-1500-S2-rev001

Site ID

Technician

Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km	<input type="text"/>	<input checked="" type="checkbox"/>
City > 50,000 population	40 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Feedlot operations	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Limited agricultural operations	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Large parking lot	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Small parking lot	100 m	<input type="text"/>	<input checked="" type="checkbox"/>
Tree line	50 m	25 m	<input type="checkbox"/>
Obstacles to wind	10 times obstacle height	<input type="text"/>	<input checked="" type="checkbox"/>

Siting Distances OK

Siting Criteria Comment



# Field Systems Data Form

F-02058-1500-S3-rev001

Site ID

Technician

Site Visit Date

- |    |  |                                     |                          |
|----|--|-------------------------------------|--------------------------|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> |                          |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> |                          |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> |                          |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |                          |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |                          |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> |                          |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> |                          |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> |                          |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input type="checkbox"/>            | 45 degree rule violation |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> |                          |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> |                          |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

The wind speed translator span is set to 25 m/s and not 50 m/s. This may have affected the low output observed at the highest wind speed challenge.



# Field Systems Data Form

F-02058-1500-S4-rev001

Site ID  Technician  Site Visit Date

- 1 Do all the meteorological sensors appear to be intact, in good condition, and well maintained?
- 2 Are all the meteorological sensors operational online, and reporting data?
- 3 Are the shields for the temperature and RH sensors clean?
- 4 Are the aspirated motors working?
- 5 Is the solar radiation sensor's lens clean and free of scratches?
- 6 Is the surface wetness sensor grid clean and undamaged?
- 7 Are the sensor signal and power cables intact, in good condition, and well maintained?
- 8 Are the sensor signal and power cable connections protected from the elements and well maintained?

Parameter	Manufacturer	Model	S/N	Client ID
Wind Speed	Climatronics	100075	1947	none
Wind Direction	Climatronics	100076	illegible	none
Met tower	Climatronics	unknown	illegible	none
Shield (10 meter)	Climatronics	100325	illegible	none
Shield (2 meter)	Climatronics	100325	illegible	none
Surface Wetness	RM Young	58101	none	90725
Relative Humidity	Vaisala	HMP45AC	Y0730050	none
Temperature	Climatronics	100093	illegible	none
Delta Temperature	Climatronics	100093	illegible	none
Precipitation	Climatronics	100508-2	illegible	01322
Solar Radiation	Licor	LI-200	PY16746	none

**Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:**

The sensor signal cables are beginning to show signs of wear.



# Field Systems Data Form

F-02058-1500-S5-rev001

Site ID  Technician  Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- 1 Do the sample inlets have at least a 270 degree arc of unrestricted airflow?
- 2 Are the sample inlets 3 - 15 meters above the ground?
- 3 Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees?

**Pollutant analyzers and deposition equipment operations and maintenance**

- 1 Do the analyzers and equipment appear to be in good condition and well maintained?
- 2 Are the analyzers and monitors operational, on-line, and reporting data?
- 3 Describe ozone sample tube.  3/8 teflon by 12 meters and Stainless Steel
- 4 Describe dry dep sample tube.  3/8 teflon by 12 meters
- 5 Are in-line filters used in the ozone sample line? (if yes indicate location)  At inlet only
- 6 Are sample lines clean, free of kinks, moisture, and obstructions?
- 7 Is the zero air supply desiccant unsaturated?
- 8 Are there moisture traps in the sample lines?  No moisture traps present
- 9 Is there a rotometer in the dry deposition filter line, and is it clean?  Clean and dry

Parameter	Manufacturer	Model	S/N	Client ID
Sample Tower	Aluma Tower	B	AT-71103-71-3	none
Ozone	ThermoElectron Inc	49C	49C-74536-376	90744
Zero air pump	ThermoElectron Inc	111	111-30215-237	none
Filter pack flow pump	Thomas	107CAB11	109500000040	none
MFC power supply	Tylan	RO-32	none	none

**Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:**

The ozone sample inlet still has a stainless steel fittings. The recommended material for ozone sample train is Teflon or glass. The site operator indicated that the fittings would be changed.



# Field Systems Data Form

F-02058-1500-S6-rev001

Site ID

Technician

Site Visit Date

DAS, sensor translators, and peripheral equipment operations and maintenance

- 1 Do the DAS instruments appear to be in good condition and well maintained?
  - 2 Are all the components of the DAS operational? (printers, modem, backup, etc)
  - 3 Do the analyzer and sensor signal leads pass through lightning protection circuitry?
  - 4 Are the signal connections protected from the weather and well maintained?
  - 5 Are the signal leads connected to the correct DAS channel?
  - 6 Are the DAS, sensor translators, and shelter properly grounded?
  - 7 Does the instrument shelter have a stable power source?
  - 8 Is the instrument shelter temperature controlled?
- 9 Is the met tower stable and grounded?
- 10 Is the sample tower stable and grounded?
- 11 Tower comments?


<b>Stable</b>	<b>Grounded</b>
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

--

Parameter	Manufacturer	Model	S/N	Client ID
Computer	Hewlett Packard	8460p	CNU20941M6	none
DAS	Environmental Sys Corp	8832	unknown2	ACADIA1
F460 translator	Climatronics	100163	683	none
Mainframe	Climatronics	100081	1288	01342
Modem	US Robotics	33.6 fax modem	unknown	none
Printer	Hewlett Packard	842C	unknown	none
Solar Radiation Translator	Climatronics	100144	309	none
Temperature Translator	Climatronics	100088-2	401	03630

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

--



# Field Systems Data Form

F-02058-1500-S7-rev001

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Data logger	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Computer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Solar radiation sensor	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Modem	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Printer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Solar radiation translator	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	UPS	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Tipping bucket rain gauge	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Ozone analyzer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack flow controller	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text" value="Dataview"/>	<input checked="" type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input checked="" type="checkbox"/>	<input type="text" value="June 2000"/>	<input checked="" type="checkbox"/>
HASP	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Field Ops Manual	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Calibration Reports	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Preventive maintenance schedule	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>

- 1 Is the station log properly completed during every site visit?
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

The site operator reported that low flow rate conditions had been observed and reported to ARS recently. The Flow controller has been replaced since then to correct the issue.



# Field Systems Data Form

F-02058-1500-S8-rev001

Site ID

Technician

Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency		Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually by MEDEP"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="Monthly"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input type="checkbox"/>	<input type="text" value="Not performed"/>	<input type="checkbox"/>	<input type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency		Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Monthly"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Monthly"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Zero Air Desiccant Check	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:



# Field Systems Data Form

F-02058-1500-S9-rev001

Site ID  Technician  Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed morinings, 90%
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	Flow and general observation sections only
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	Clean gloves on and off
9	Are the site conditions reported regularly to the field operations manager or staff?	<input type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input type="checkbox"/> Not performed	<input type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> As needed	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input type="checkbox"/> Not performed	<input type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

This site is operated partly by the NPS and the State of Maine DEP. It is not visited by ARS for semiannual calibration and maintenance visits. The site operator does not perform many of the routine checks conducted at other CASTNET sites, such as tip checks, wetness sensor tests, and visual checks of the blowers. The state of Maine personnel maintain the meteorological systems.



---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

### *HOW191-Eric Hebert-10/06/2014*

1	10/6/2014	DAS	Campbell	000419	CR3000	2527
2	10/6/2014	elevation	Elevation	none	none	none
3	10/6/2014	Filter pack flow pump	Thomas	04921	107CAB18	060300019983
4	10/6/2014	Flow Rate	Apex	000645	AXMC105LPMDCV	illegible
5	10/6/2014	Infrastructure	Infrastructure	none	none	none
6	10/6/2014	Modem	Raven	06470	H4222-C	0808311250
7	10/6/2014	Ozone	ThermoElectron Inc	000616	49i A1NAA	1009241781
8	10/6/2014	Ozone Standard	ThermoElectron Inc	000435	49i A3NAA	CM08200011
9	10/6/2014	Shelter Temperature	Campbell	none	107-L	none
10	10/6/2014	siting criteria	Siting Criteria	none	none	None
11	10/6/2014	Temperature	RM Young	04449	41342VC	4547
12	10/6/2014	Zero air pump	Werther International	06908	C 70/4	000821900

# DAS Data Form

DAS Time Max Error:

Mfg	Serial Number	Site	Technician	Site Visit Date	Parameter	Use Desc.
Campbell	2527	HOW191	Eric Hebert	10/06/2014	DAS	Primary

Das Date:	<input type="text" value="10/6 /2014"/>	Audit Date:	<input type="text" value="10/6 /2014"/>
Das Time:	<input type="text" value="11:34:00"/>	Audit Time:	<input type="text" value="11:34:00"/>
Das Day:	<input type="text" value="279"/>	Audit Day:	<input type="text" value="279"/>
Low Channel:		High Channel:	
Avg Diff:	<input type="text" value="0.0001"/>	Max Diff:	<input type="text" value="0.0002"/>
		Avg Diff:	<input type="text" value="0.0001"/>
		Max Diff:	<input type="text" value="0.0002"/>

Mfg	<input type="text" value="HY"/>	Parameter	<input type="text" value="DAS"/>
Serial Number	<input type="text" value="12010039329"/>	Tfer Desc.	<input type="text" value="Source generator (D"/>
Tfer ID	<input type="text" value="01322"/>		
Slope	<input type="text" value="1.00000"/>	Intercept	<input type="text" value="0.00000"/>
Cert Date	<input type="text" value="6/15/2014"/>	CorrCoff	<input type="text" value="1.00000"/>
Mfg	<input type="text" value="Fluke"/>	Parameter	<input type="text" value="DAS"/>
Serial Number	<input type="text" value="86590148"/>	Tfer Desc.	<input type="text" value="DVM"/>
Tfer ID	<input type="text" value="01310"/>		
Slope	<input type="text" value="1.00000"/>	Intercept	<input type="text" value="0.00000"/>
Cert Date	<input type="text" value="1/22/2014"/>	CorrCoff	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
7	0.0000	0.0000	0.0000	V	V	0.0000
7	0.1000	0.0995	0.0997	V	V	0.0002
7	0.3000	0.3011	0.3010	V	V	-0.0001
7	0.5000	0.5010	0.5009	V	V	-0.0001
7	0.7000	0.6996	0.6995	V	V	-0.0001
7	0.9000	0.8998	0.8996	V	V	-0.0002
7	1.0000	0.9997	0.9995	V	V	-0.0002

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Apex	illegible		HOW191	Eric Hebert	10/06/2014	Flow Rate	000645

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	131818	<b>Tfer Desc.</b>	BIOS 220-H
<b>Tfer ID</b>	01417		
<b>Slope</b>	1.00000	<b>Intercept</b>	0.00000
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
0.88%	1.32%

<b>Cal Factor Zero</b>	0.02
<b>Cal Factor Full Scale</b>	1.03
<b>Rotometer Reading:</b>	0

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignal	PctDifference
primary	pump off	0.000	0.000	-0.02	0.000	0.00	l/m	l/m	
primary	leak check	0.000	0.000	0.01	0.000	0.03	l/m	l/m	
primary	test pt 1	1.516	1.520	1.47	0.000	1.50	l/m	l/m	-1.32%
primary	test pt 2	1.508	1.510	1.47	0.000	1.50	l/m	l/m	-0.66%
primary	test pt 3	1.509	1.510	1.47	0.000	1.50	l/m	l/m	-0.66%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	No moisture present	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	3.0 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	3,0 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	360 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Tag Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1009241781	HOW191	Eric Hebert	10/06/2014	Ozone	000616

<b>Slope:</b>	0.98661	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.31884	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	1.00000	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
2.0%	2.5%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0419606966	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01112		
<b>Slope</b>	1.00928	<b>Intercept</b>	0.11780
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	0.12	0.00	-0.31	ppb	
primary	2	29.84	29.44	28.70	ppb	-2.51%
primary	3	52.07	51.47	50.43	ppb	-2.02%
primary	4	78.85	78.00	76.73	ppb	-1.63%
primary	5	113.02	111.86	110.00	ppb	-1.66%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.5 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.20	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.007	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	96.4 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.69 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	33.8 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	702 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	88.5 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.68 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass

# Temperature Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	4547		HOW191	Eric Hebert	10/06/2014	Temperature	04449

<b>Mfg</b>	Extech	<b>Parameter</b>	Temperature
<b>Serial Number</b>	H232679	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01228		
<b>Slope</b>	1.00496	<b>Intercept</b>	-0.23009
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>
0.05	0.09		

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Range	-0.16	0.07	0.000	0.1	C	0.04
primary	Temp Mid Range	21.84	21.96	0.000	21.9	C	-0.02
primary	Temp High Range	45.69	45.69	0.000	45.8	C	0.09

<b>Sensor Component</b>	Shield	<b>Condition</b>	Moderately clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Campbell	none	HOW191	Eric Hebert	10/06/2014	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
0.31	0.76		

<b>Mfg</b>	Extech	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	H232679	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01228		
<b>Slope</b>	1.00496	<b>Intercept</b>	-0.23009
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Mid Range	20.98	21.11	0.000	21.1	C	0.01
primary	Temp Mid Range	21.73	21.85	0.000	21.7	C	-0.17
primary	Temp Mid Range	21.47	21.59	0.000	20.8	C	-0.76

## Infrastructure Data For

Site ID  Technician  Site Visit Date

Shelter Make	Shelter Model	Shelter Size
<input type="text" value="custom"/>	<input type="text" value="custom"/>	<input type="text" value="800 cuft"/>

Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Functioning"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Not installed"/>	Status	<input type="text" value="Fail"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="1/4 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>

# Field Systems Comments

**1 Parameter:** SiteOpsProcComm

The site operator reported that gloves are not consistently used to handle the filter pack.

**2 Parameter:** SitingCriteriaCom

The CASTNET filter pack at this location is located above a tree canopy at approximately 23.5 meters from the ground. This is an AmeriFlux site which is approximately 2.5 km to the SW of the HOW132 CASTNET site.

**3 Parameter:** ShelterCleanNotes

The custom built shelter is clean and organized.

**4 Parameter:** MetSensorComme

Other than a temperature sensor located at the CASTNET filter location the meteorological instrumentation is being operated by the University of Maine and AmeriFlux.



# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)	<input type="text" value="EPA"/>	USGS Map	<input type="text" value="Howland"/>
Operating Group	<input type="text" value="University of ME"/>	Map Scale	<input type="text"/>
AQS #	<input type="text"/>	Map Date	<input type="text"/>
Meteorological Type	<input type="text" value="R.M. Young"/>		
Air Pollutant Analyzer	<input type="text" value="Ozone"/>	QAPP Latitude	<input type="text"/>
Deposition Measurement	<input type="text" value="dry"/>	QAPP Longitude	<input type="text"/>
Land Use	<input type="text" value="Woodland - mixed"/>	QAPP Elevation Meters	<input type="text"/>
Terrain	<input type="text" value="flat, gently rolling"/>	QAPP Declination	<input type="text"/>
Conforms to MLM	<input type="text" value="Yes"/>	QAPP Declination Date	<input type="text"/>
Site Telephone	<input type="text"/>	Audit Latitude	<input type="text" value="45.203963"/>
Site Address 1	<input type="text"/>	Audit Longitude	<input type="text" value="-68.740041"/>
Site Address 2	<input type="text"/>	Audit Elevation	<input type="text" value="68"/>
County	<input type="text" value="Penobscot"/>	Audit Declination	<input type="text" value="-17"/>
City, State	<input type="text" value="Howland, ME"/>		
Zip Code	<input type="text"/>	<b>Present</b>	
Time Zone	<input type="text" value="Eastern"/>	Fire Extinguisher <input checked="" type="checkbox"/>	<input type="text"/>
Primary Operator	<input type="text"/>	First Aid Kit <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. Phone #	<input type="text"/>	Safety Glasses <input type="checkbox"/>	<input type="text"/>
Primary Op. E-mail	<input type="text"/>	Safety Hard Hat <input checked="" type="checkbox"/>	<input type="text"/>
Backup Operator	<input type="text"/>	Climbing Belt <input checked="" type="checkbox"/>	<input type="text"/>
Backup Op. Phone #	<input type="text"/>	Security Fence <input type="checkbox"/>	<input type="text"/>
Backup Op. E-mail	<input type="text"/>	Secure Shelter <input checked="" type="checkbox"/>	<input type="text"/>
		Stable Entry Step <input checked="" type="checkbox"/>	<input type="text"/>
Shelter Working Room <input checked="" type="checkbox"/>	Make <input type="text" value="custom"/>	Model <input type="text" value="custom"/>	Shelter Size <input type="text" value="800 cuft"/>
Shelter Clean <input checked="" type="checkbox"/>	Notes	<input type="text" value="The custom built shelter is clean and organized."/>	
Site OK <input checked="" type="checkbox"/>	Notes	<input type="text"/>	
Driving Directions	<input type="text" value="Arrange for site visit and access with the site operator."/>		

# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID  Technician  Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km	<input type="text"/>	<input checked="" type="checkbox"/>
City > 50,000 population	40 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Feedlot operations	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Limited agricultural operations	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Large parking lot	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Small parking lot	100 m	<input type="text"/>	<input checked="" type="checkbox"/>
Tree line	50 m	<input type="text"/>	<input checked="" type="checkbox"/>
Obstacles to wind	10 times obstacle height	<input type="text"/>	<input checked="" type="checkbox"/>

Siting Distances OK

**Siting Criteria Comment**

The CASTNET filter pack at this location is located above a tree canopy at approximately 23.5 meters from the ground. This is an AmeriFlux site which is approximately 2.5 km to the SW of the HOW132 CASTNET site.

# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID

Technician

Site Visit Date

- |    |  |                                     |     |
|----|--|-------------------------------------|-----|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> | N/A |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> | N/A |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> | N/A |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |     |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |     |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> | N/A |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> | N/A |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> | N/A |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> | N/A |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> | N/A |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | N/A |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

Other than a temperature sensor located at the CASTNET filter location the meteorological instrumentation is being operated by the University of Maine and AmeriFlux.

# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

Technician

Site Visit Date

1	Do all the meteorological sensors appear to be intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	N/A
2	Are all the meteorological sensors operational online, and reporting data?	<input checked="" type="checkbox"/>	N/A
3	Are the shields for the temperature and RH sensors clean?	<input checked="" type="checkbox"/>	
4	Are the aspirated motors working?	<input checked="" type="checkbox"/>	N/A
5	Is the solar radiation sensor's lens clean and free of scratches?	<input checked="" type="checkbox"/>	N/A
6	Is the surface wetness sensor grid clean and undamaged?	<input checked="" type="checkbox"/>	N/A
7	Are the sensor signal and power cables intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	
8	Are the sensor signal and power cable connections protected from the elements and well maintained?	<input checked="" type="checkbox"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID

Technician

Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- |   |   |                                     |              |
|---|---|-------------------------------------|--------------|
| 1 | Do the sample inlets have at least a 270 degree arc of unrestricted airflow?          | <input checked="" type="checkbox"/> |              |
| 2 | Are the sample inlets 3 - 15 meters above the ground?                                 | <input checked="" type="checkbox"/> |              |
| 3 | Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees? | <input checked="" type="checkbox"/> | Above canopy |

**Pollutant analyzers and deposition equipment operations and maintenance**

- |   |  |                                     |                         |
|---|--|-------------------------------------|-------------------------|
| 1 | Do the analyzers and equipment appear to be in good condition and well maintained? | <input checked="" type="checkbox"/> |                         |
| 2 | Are the analyzers and monitors operational, on-line, and reporting data?           | <input checked="" type="checkbox"/> |                         |
| 3 | Describe ozone sample tube.  |                                     | 1/4 teflon by 40 meters |
| 4 | Describe dry dep sample tube.  |                                     | 1/4 teflon by 40 meters |
| 5 | Are in-line filters used in the ozone sample line? (if yes indicate location)      | <input checked="" type="checkbox"/> | At inlet only           |
| 6 | Are sample lines clean, free of kinks, moisture, and obstructions?                 | <input checked="" type="checkbox"/> |                         |
| 7 | Is the zero air supply desiccant unsaturated?                                      | <input checked="" type="checkbox"/> |                         |
| 8 | Are there moisture traps in the sample lines?                                      | <input type="checkbox"/>            |                         |
| 9 | Is there a rotometer in the dry deposition filter line, and is it clean?           | <input checked="" type="checkbox"/> |                         |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

- |                                     |  |  |   |  |          |                                     |  |                                     |  |
|-------------------------------------|--|--|---|--|----------|-------------------------------------|--|-------------------------------------|--|
| 1                                   | Do the DAS instruments appear to be in good condition and well maintained?           | <input checked="" type="checkbox"/>  |   |  |          |                                     |  |                                     |  |
| 2                                   | Are all the components of the DAS operational? (printers, modem, backup, etc)        | <input checked="" type="checkbox"/>  |   |  |          |                                     |  |                                     |  |
| 3                                   | Do the analyzer and sensor signal leads pass through lightning protection circuitry? | <input type="checkbox"/>   |   |  |          |                                     |  |                                     |  |
| 4                                   | Are the signal connections protected from the weather and well maintained?           | <input checked="" type="checkbox"/>  |   |  |          |                                     |  |                                     |  |
| 5                                   | Are the signal leads connected to the correct DAS channel?                           | <input checked="" type="checkbox"/>  |   |  |          |                                     |  |                                     |  |
| 6                                   | Are the DAS, sensor translators, and shelter properly grounded?                      | <input checked="" type="checkbox"/>  |   |  |          |                                     |  |                                     |  |
| 7                                   | Does the instrument shelter have a stable power source?                              | <input checked="" type="checkbox"/>  |   |  |          |                                     |  |                                     |  |
| 8                                   | Is the instrument shelter temperature controlled?                                    | <input checked="" type="checkbox"/>  |   |  |          |                                     |  |                                     |  |
| 9                                   | Is the met tower stable and grounded?  | <table border="1"><tr><td>Stable</td><td></td><td>Grounded</td></tr><tr><td><input checked="" type="checkbox"/></td><td></td><td><input checked="" type="checkbox"/></td></tr></table> | Stable  |  | Grounded | <input checked="" type="checkbox"/> |  | <input checked="" type="checkbox"/> |  |
| Stable                              |  | Grounded   |   |  |          |                                     |  |                                     |  |
| <input checked="" type="checkbox"/> |  | <input checked="" type="checkbox"/>  |   |  |          |                                     |  |                                     |  |
| 10                                  | Is the sample tower stable and grounded?   | <table border="1"><tr><td>Stable</td><td></td><td>Grounded</td></tr><tr><td><input checked="" type="checkbox"/></td><td></td><td><input checked="" type="checkbox"/></td></tr></table> | Stable  |  | Grounded | <input checked="" type="checkbox"/> |  | <input checked="" type="checkbox"/> |  |
| Stable                              |  | Grounded   |   |  |          |                                     |  |                                     |  |
| <input checked="" type="checkbox"/> |  | <input checked="" type="checkbox"/>  |   |  |          |                                     |  |                                     |  |
| 11                                  | Tower comments?  |  | <input type="text" value="24 meter walk-up tower"/> |  |          |                                     |  |                                     |  |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Computer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Solar radiation sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Modem	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Printer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	UPS	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Ozone analyzer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack flow controller	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Site Ops Manual	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
HASP	<input checked="" type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Field Ops Manual	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Calibration Reports	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Preventive maintenance schedul	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>

- 1 Is the station log properly completed during every site visit?
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?  Control charts not used

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID  Technician  Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Monthly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input type="checkbox"/>
Zero Air Desiccant Check	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:



# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID

Technician

Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	Clean gloves on and off
9	Are the site conditions reported regularly to the field operations manager or staff?	<input checked="" type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input type="checkbox"/>	<input type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

The site operator reported that gloves are not consistently used to handle the filter pack.

# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID

Technician

Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
DAS	Campbell	CR3000	2527	000419
elevation	Elevation	none	none	none
Filter pack flow pump	Thomas	107CAB18	060300019983	04921
Flow Rate	Apex	AXMC105LPMDPC	illegible	000645
Infrastructure	Infrastructure	none	none	none
Modem	Raven	H4222-C	0808311250	06470
Ozone	ThermoElectron Inc	49i A1NAA	1009241781	000616
Ozone Standard	ThermoElectron Inc	49i A3NAA	CM08200011	000435
Shelter Temperature	Campbell	107-L	none	none
siting criteria	Siting Criteria	none	None	none
Temperature	RM Young	41342VC	4547	04449
Zero air pump	Werther International	C 70/4	000821900	06908

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

### *ASH135-Eric Hebert-10/07/2014*

1	10/7/2014	Computer	Dell	000430	D630	unknown
2	10/7/2014	DAS	Campbell	000343	CR3000	2122
3	10/7/2014	Elevation	Elevation	None	1	None
4	10/7/2014	Filter pack flow pump	Thomas	01458	107CA110	028871488
5	10/7/2014	Flow Rate	Apex	000648	AXMC105LPMDPCV	54777
6	10/7/2014	Infrastructure	Infrastructure	none	none	none
7	10/7/2014	Modem	Raven	06471	H4222-C	0808311148
8	10/7/2014	Ozone	ThermoElectron Inc	000620	49i A1NAA	1009241793
9	10/7/2014	Ozone Standard	ThermoElectron Inc	000375	49i A3NAA	0726124696
10	10/7/2014	Sample Tower	Aluma Tower	03536	A	none
11	10/7/2014	Shelter Temperature	Campbell	none	107-L	none
12	10/7/2014	Siting Criteria	Siting Criteria	None	1	None
13	10/7/2014	Temperature	RM Young	06389	41342	13994
14	10/7/2014	UPS	APC	06797	RS900	unknown
15	10/7/2014	Zero air pump	Werther International	06923	C 70/4	000836208

# DAS Data Form

DAS Time Max Error:

<b>Mfg</b>	<b>Serial Number</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Use Desc.</b>
Campbell	2122	ASH135	Eric Hebert	10/07/2014	DAS	Primary

<b>Das Date:</b>	<input type="text" value="10/7 /2014"/>	<b>Audit Date</b>	<input type="text" value="10/7 /2014"/>
<b>Das Time:</b>	<input type="text" value="12:44:00"/>	<b>Audit Time</b>	<input type="text" value="12:44:00"/>
<b>Das Day:</b>	<input type="text" value="280"/>	<b>Audit Day</b>	<input type="text" value="280"/>
<b>Low Channel:</b>		<b>High Channel:</b>	
<b>Avg Diff:</b>	<input type="text" value="0.0001"/>	<b>Max Diff:</b>	<input type="text" value="0.0002"/>
		<b>Avg Diff:</b>	<input type="text" value="0.0001"/>
		<b>Max Diff:</b>	<input type="text" value="0.0002"/>

<b>Mfg</b>	<input type="text" value="HY"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="12010039329"/>	<b>Tfer Desc.</b>	<input type="text" value="Source generator (D"/>
<b>Tfer ID</b>	<input type="text" value="01322"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="6/15/2014"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>
<b>Mfg</b>	<input type="text" value="Fluke"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="86590148"/>	<b>Tfer Desc.</b>	<input type="text" value="DVM"/>
<b>Tfer ID</b>	<input type="text" value="01310"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="1/22/2014"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
7	0.0000	-0.0001	0.0000	V	V	0.0001
7	0.1000	0.0995	0.0995	V	V	0.0000
7	0.3000	0.2992	0.2992	V	V	0.0000
7	0.5000	0.4998	0.4999	V	V	0.0001
7	0.7000	0.6998	0.6996	V	V	-0.0002
7	0.9000	0.8998	0.8998	V	V	0.0000
7	1.0000	0.9997	0.9997	V	V	0.0000

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Apex	54777		ASH135	Eric Hebert	10/07/2014	Flow Rate	000648

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	131818	<b>Tfer Desc.</b>	BIOS 220-H
<b>Tfer ID</b>	01417		
<b>Slope</b>	1.00000	<b>Intercept</b>	0.00000
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
1.96%	1.96%

<b>Cal Factor Zero</b>	0.01
<b>Cal Factor Full Scale</b>	1.01
<b>Rotometer Reading:</b>	1.45

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignal	PctDifference
primary	pump off	0.000	0.000	-0.01	0.000	0.00	l/m	l/m	
primary	leak check	0.000	0.000	0.00	0.000	0.05	l/m	l/m	
primary	test pt 1	1.529	1.530	1.49	0.000	1.50	l/m	l/m	-1.96%
primary	test pt 2	1.527	1.530	1.49	0.000	1.50	l/m	l/m	-1.96%
primary	test pt 3	1.528	1.530	1.49	0.000	1.50	l/m	l/m	-1.96%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	No moisture present	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	6.0 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	2.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	270 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>	See comments	<b>Status</b>	pass

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Tag Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1009241793	ASH135	Eric Hebert	10/07/2014	Ozone	000620

<b>Slope:</b>	0.99168	<b>Slope:</b>	0.00000
<b>Intercept</b>	-1.27949	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99992	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
2.7%	3.5%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0419606966	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01112		
<b>Slope</b>	1.00928	<b>Intercept</b>	0.11780
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	0.14	0.02	-1.96	ppb	
primary	2	24.32	23.97	23.14	ppb	-3.46%
primary	3	47.76	47.20	45.93	ppb	-2.69%
primary	4	80.72	79.86	77.81	ppb	-2.57%
primary	5	107.62	106.51	104.10	ppb	-2.26%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	1.1 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-0.10	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.009	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	91.6 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.74 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	30.6 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	716.4 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.9 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	87.6 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.74 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass

# Temperature Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	13994		ASH135	Eric Hebert	10/07/2014	Temperature	06389

<b>Mfg</b>	Extech	<b>Parameter</b>	Temperature
<b>Serial Number</b>	H232679	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01228		
<b>Slope</b>	1.00496	<b>Intercept</b>	-0.23009
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>		<b>DAS 2:</b>	
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>
0.02	0.05		

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Range	0.28	0.51	0.000	0.6	C	0.05
primary	Temp Mid Range	22.75	22.87	0.000	22.9	C	0
primary	Temp High Range	45.20	45.21	0.000	45.2	C	0.01

<b>Sensor Component</b>	Shield	<b>Condition</b>	Moderately clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Campbell	none	ASH135	Eric Hebert	10/07/2014	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
0.55	0.87		

<b>Mfg</b>	Extech	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	H232679	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01228		
<b>Slope</b>	1.00496	<b>Intercept</b>	-0.23009
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Mid Range	23.07	23.19	0.000	23.5	C	0.28
primary	Temp Mid Range	21.85	21.97	0.000	22.8	C	0.87
primary	Temp Mid Range	23.12	23.23	0.000	22.7	C	-0.49



## Infrastructure Data For

Site ID  Technician  Site Visit Date

Shelter Make	Shelter Model	Shelter Size
<input type="text" value="Ekto"/>	<input type="text" value="8810 (s/n 2149-17)"/>	<input type="text" value="640 cuft"/>

Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text" value="Type A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Functioning"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="3/8 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>

# Site Visit Comments

<b>Parameter</b>	<b>Site</b>	<b>Technician</b>	<b>S.V. Date</b>	<b>Component</b>	<b>Mfg</b>	<b>Serial No.</b>	<b>Hazard</b>	<b>Problem</b>
------------------	-------------	-------------------	------------------	------------------	------------	-------------------	---------------	----------------

Flow Rate	ASH135	Eric Hebert	10/07/2014	System Memo	Apex	3668	<input type="checkbox"/>	<input checked="" type="checkbox"/>
-----------	--------	-------------	------------	-------------	------	------	--------------------------	-------------------------------------

There is no plastic bag for the installed filter. The operator uses the received bag for the installed filter to ship the removed filter to the lab.

# Field Systems Comments

**1 Parameter:** DasComments

The met tower has been removed and the 10 meter temperature sensor is mounted in a naturally aspirated shield on the sample tower.

**2 Parameter:** SiteOpsProcedures

The ozone inlet filter is replaced and the sample train is leak tested once each month.

**3 Parameter:** SitingCriteriaCom

There is an evergreen plantation 20 meters south of the site.

**4 Parameter:** ShelterCleanNotes

The shelter is in good condition, clean, and very well organized.

# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)  USGS Map   
 Operating Group  Map Scale   
 AQS #  Map Date

Meteorological Type

Air Pollutant Analyzer  QAPP Latitude

Deposition Measurement  QAPP Longitude

Land Use  QAPP Elevation Meters

Terrain  QAPP Declination

Conforms to MLM  QAPP Declination Date

Site Telephone  Audit Latitude

Site Address 1  Audit Longitude

Site Address 2  Audit Elevation

County  Audit Declination

City, State

Zip Code  Fire Extinguisher  Present

Time Zone  First Aid Kit

Primary Operator  Safety Glasses

Primary Op. Phone #  Safety Hard Hat

Primary Op. E-mail  Climbing Belt

Backup Operator  Security Fence

Backup Op. Phone #  Secure Shelter

Backup Op. E-mail  Stable Entry Step

Shelter Working Room  Make  Model  Shelter Size

Shelter Clean  Notes

Site OK  Notes

Driving Directions

# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID  Technician  Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km	<input type="text"/>	<input checked="" type="checkbox"/>
City > 50,000 population	40 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Feedlot operations	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Limited agricultural operations	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Large parking lot	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Small parking lot	100 m	<input type="text"/>	<input checked="" type="checkbox"/>
Tree line	50 m	20 m	<input type="checkbox"/>
Obstacles to wind	10 times obstacle height	<input type="text"/>	<input checked="" type="checkbox"/>

Siting Distances OK

Siting Criteria Comment

# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID

Technician

Site Visit Date

- |    |  |                                     |     |
|----|--|-------------------------------------|-----|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> | N/A |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> | N/A |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> | N/A |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |     |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |     |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> | N/A |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> | N/A |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> | N/A |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> | N/A |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> | N/A |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | N/A |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

Technician

Site Visit Date

1	Do all the meteorological sensors appear to be intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	N/A
2	Are all the meteorological sensors operational online, and reporting data?	<input checked="" type="checkbox"/>	N/A
3	Are the shields for the temperature and RH sensors clean?	<input checked="" type="checkbox"/>	
4	Are the aspirated motors working?	<input checked="" type="checkbox"/>	N/A
5	Is the solar radiation sensor's lens clean and free of scratches?	<input checked="" type="checkbox"/>	N/A
6	Is the surface wetness sensor grid clean and undamaged?	<input checked="" type="checkbox"/>	N/A
7	Are the sensor signal and power cables intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	
8	Are the sensor signal and power cable connections protected from the elements and well maintained?	<input checked="" type="checkbox"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID

Technician

Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- |   |   |                                     |  |
|---|---|-------------------------------------|--|
| 1 | Do the sample inlets have at least a 270 degree arc of unrestricted airflow?          | <input checked="" type="checkbox"/> |  |
| 2 | Are the sample inlets 3 - 15 meters above the ground?                                 | <input checked="" type="checkbox"/> |  |
| 3 | Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees? | <input checked="" type="checkbox"/> |  |

**Pollutant analyzers and deposition equipment operations and maintenance**

- |   |  |                                     |                         |
|---|--|-------------------------------------|-------------------------|
| 1 | Do the analyzers and equipment appear to be in good condition and well maintained? | <input checked="" type="checkbox"/> |                         |
| 2 | Are the analyzers and monitors operational, on-line, and reporting data?           | <input checked="" type="checkbox"/> |                         |
| 3 | Describe ozone sample tube.  |                                     | 1/4 teflon by 12 meters |
| 4 | Describe dry dep sample tube.  |                                     | 3/8 teflon by 12 meters |
| 5 | Are in-line filters used in the ozone sample line? (if yes indicate location)      | <input checked="" type="checkbox"/> | At inlet only           |
| 6 | Are sample lines clean, free of kinks, moisture, and obstructions?                 | <input checked="" type="checkbox"/> |                         |
| 7 | Is the zero air supply desiccant unsaturated?                                      | <input checked="" type="checkbox"/> |                         |
| 8 | Are there moisture traps in the sample lines?                                      | <input checked="" type="checkbox"/> | Flow line only          |
| 9 | Is there a rotometer in the dry deposition filter line, and is it clean?           | <input checked="" type="checkbox"/> | Clean and dry           |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:



# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

- 1 Do the DAS instruments appear to be in good condition and well maintained?
- 2 Are all the components of the DAS operational? (printers, modem, backup, etc)
- 3 Do the analyzer and sensor signal leads pass through lightning protection circuitry?
- 4 Are the signal connections protected from the weather and well maintained?
- 5 Are the signal leads connected to the correct DAS channel?
- 6 Are the DAS, sensor translators, and shelter properly grounded?
- 7 Does the instrument shelter have a stable power source?
- 8 Is the instrument shelter temperature controlled?
- 9 Is the met tower stable and grounded?

<b>Stable</b>	<b>Grounded</b>
<input type="checkbox"/>	<input type="checkbox"/>
<input checked="" type="checkbox"/>	<input type="checkbox"/>
- 10 Is the sample tower stable and grounded?

<b>Stable</b>	<b>Grounded</b>
<input type="checkbox"/>	<input type="checkbox"/>
<input checked="" type="checkbox"/>	<input type="checkbox"/>
- 11 Tower comments?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

The met tower has been removed and the 10 meter temperature sensor is mounted in a naturally aspirated shield on the sample tower.

# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Computer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Solar radiation sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Modem	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Printer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	UPS	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Ozone analyzer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack flow controller	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input checked="" type="checkbox"/>	June 2007	<input checked="" type="checkbox"/>
HASP	<input checked="" type="checkbox"/>	Nov 2009	<input checked="" type="checkbox"/>
Field Ops Manual	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Calibration Reports	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Preventive maintenance schedul	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>

- 1 Is the station log properly completed during every site visit?
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?  Control charts not used

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID

Technician

Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input type="checkbox"/>	<input type="text" value="As needed"/>	<input checked="" type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input type="checkbox"/>	<input type="text" value="As needed"/>	<input checked="" type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Monthly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Zero Air Desiccant Check	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?  Unknown
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?  SSRF, call-in

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID

Technician

Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed morinings
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF, call-in
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	Clean gloves on and off
9	Are the site conditions reported regularly to the field operations manager or staff?	<input checked="" type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input type="checkbox"/>	<input type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID

Technician

Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
Computer	Dell	D630	unknown	000430
DAS	Campbell	CR3000	2122	000343
Elevation	Elevation	1	None	None
Filter pack flow pump	Thomas	107CA110	028871488	01458
Flow Rate	Apex	AXMC105LPMDPC	54777	000648
Infrastructure	Infrastructure	none	none	none
Modem	Raven	H4222-C	0808311148	06471
Ozone	ThermoElectron Inc	49i A1NAA	1009241793	000620
Ozone Standard	ThermoElectron Inc	49i A3NAA	0726124696	000375
Sample Tower	Aluma Tower	A	none	03536
Shelter Temperature	Campbell	107-L	none	none
Siting Criteria	Siting Criteria	1	None	None
Temperature	RM Young	41342	13994	06389
UPS	APC	RS900	unknown	06797
Zero air pump	Werther International	C 70/4	000836208	06923

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>	
<i>PNF126-Eric Hebert-10/30/2014</i>						
1	10/30/2014	Computer	Dell	000264	D520	unknown
2	10/30/2014	DAS	Campbell	000346	CR3000	2125
3	10/30/2014	Elevation	Elevation	None	1	None
4	10/30/2014	Filter pack flow pump	Thomas	06030	107CAB18	060400022677
5	10/30/2014	Flow Rate	Apex	000655	AXMC105LPMDPCV	illegible
6	10/30/2014	Infrastructure	Infrastructure	none	none	none
7	10/30/2014	Modem	Raven	06597	V4221-V	0844349884
8	10/30/2014	Ozone	ThermoElectron Inc	000695	49i A1NAA	1030244801
9	10/30/2014	Ozone Standard	ThermoElectron Inc	000437	49i A3NAA	CM08200013
10	10/30/2014	Sample Tower	Aluma Tower	000178	B	none
11	10/30/2014	Shelter Temperature	Campbell	none	107-L	none
12	10/30/2014	Siting Criteria	Siting Criteria	None	1	None
13	10/30/2014	Temperature	RM Young	missing	41342	none
14	10/30/2014	Zero air pump	Werther International	06886	C 70/4	000815259

# DAS Data Form

DAS Time Max Error:

<b>Mfg</b>	<b>Serial Number</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Use Desc.</b>
Campbell	2125	PNF126	Eric Hebert	10/30/2014	DAS	Primary

<b>Das Date:</b>	<input type="text" value="10/30/2014"/>	<b>Audit Date</b>	<input type="text" value="10/30/2014"/>
<b>Das Time:</b>	<input type="text" value="11:13:00"/>	<b>Audit Time</b>	<input type="text" value="11:13:00"/>
<b>Das Day:</b>	<input type="text" value="303"/>	<b>Audit Day</b>	<input type="text" value="303"/>
<b>Low Channel:</b>		<b>High Channel:</b>	
<b>Avg Diff:</b>	<input type="text" value="0.0002"/>	<b>Max Diff:</b>	<input type="text" value="0.0003"/>
		<b>Avg Diff:</b>	<input type="text" value="0.0002"/>
		<b>Max Diff:</b>	<input type="text" value="0.0003"/>

<b>Mfg</b>	<input type="text" value="Datel"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="4000392"/>	<b>Tfer Desc.</b>	<input type="text" value="Source generator (D"/>
<b>Tfer ID</b>	<input type="text" value="01321"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="2/13/2012"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>
<b>Mfg</b>	<input type="text" value="Fluke"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="95740243"/>	<b>Tfer Desc.</b>	<input type="text" value="DVM"/>
<b>Tfer ID</b>	<input type="text" value="01312"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="12/28/2013"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
7	0.0000	-0.0005	-0.0008	V	V	-0.0003
7	0.1000	0.1004	0.1004	V	V	0.0000
7	0.3000	0.2994	0.2992	V	V	-0.0002
7	0.5000	0.4996	0.4994	V	V	-0.0002
7	0.7000	0.6996	0.6995	V	V	-0.0001
7	0.9000	0.8996	0.8994	V	V	-0.0002
7	1.0000	0.9992	0.9990	V	V	-0.0002

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Apex	illegible		PNF126	Eric Hebert	10/30/2014	Flow Rate	000655

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	131818	<b>Tfer Desc.</b>	BIOS 220-H
<b>Tfer ID</b>	01417		
<b>Slope</b>	1.00000	<b>Intercept</b>	0.00000
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
1.10%	1.32%

<b>Cal Factor Zero</b>	-0.42
<b>Cal Factor Full Scale</b>	0.994
<b>Rotometer Reading:</b>	1.65

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignal	PctDifference
primary	pump off	0.000	0.000	0.06	0.000	0.01	l/m	l/m	
primary	leak check	0.000	0.000	0.02	0.000	0.01	l/m	l/m	
primary	test pt 1	1.511	1.510	1.56	0.000	1.49	l/m	l/m	-1.32%
primary	test pt 2	1.509	1.510	1.56	0.000	1.49	l/m	l/m	-1.32%
primary	test pt 3	1.512	1.510	1.56	0.000	1.50	l/m	l/m	-0.66%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	See comments	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	4.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	1.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	45 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass



# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1030244801		PNF126	Eric Hebert	10/30/2014	Ozone	000695

<b>Slope:</b>	0.98882	<b>Slope:</b>	0.00000
<b>Intercept</b>	0.45144	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	1.00000	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
0.6%	0.8%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49CPS-70008-364	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01110		
<b>Slope</b>	1.00707	<b>Intercept</b>	-0.21032
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	0.35	0.55	0.90	ppb	
primary	2	29.59	29.59	29.83	ppb	0.81%
primary	3	47.23	47.10	47.05	ppb	-0.11%
primary	4	77.66	77.32	76.88	ppb	-0.57%
primary	5	117.80	117.18	116.30	ppb	-0.75%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	1.1 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-0.10	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.003	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	90.6 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.65 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	34.9 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	633 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	1.0 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	100.9 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.61 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass



# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Campbell	none	PNF126	Eric Hebert	10/30/2014	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
0.51	0.89		

<b>Mfg</b>	Eutechnics	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	01D102193	<b>Tfer Desc.</b>	RTD translator
<b>Tfer ID</b>	01231		
<b>Slope</b>	1.00133	<b>Intercept</b>	-0.05731
<b>Cert Date</b>	12/27/2013	<b>CorrCoff</b>	1.00000
<b>Mfg</b>	Eutechnics	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	01H0060	<b>Tfer Desc.</b>	RTD probe
<b>Tfer ID</b>	01230		
<b>Slope</b>	1.00133	<b>Intercept</b>	-0.05731
<b>Cert Date</b>	12/27/2013	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Mid Range	21.23	21.26	0.000	22.2	C	0.89
primary	Temp Mid Range	23.41	23.44	0.000	23.1	C	-0.34
primary	Temp Mid Range	24.10	24.13	0.000	23.8	C	-0.29

## Infrastructure Data For

Site ID  Technician  Site Visit Date

Shelter Make	Shelter Model	Shelter Size
<input type="text" value="Ekto"/>	<input type="text" value="8810"/>	<input type="text" value="640 cuft"/>

Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text" value="Type B"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Functioning"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="3/8 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>

# Site Visit Comments

<b>Parameter</b>	<b>Site</b>	<b>Technician</b>	<b>S.V. Date</b>	<b>Component</b>	<b>Mfg</b>	<b>Serial No.</b>	<b>Hazard</b>	<b>Problem</b>
Flow Rate	PNF126	Eric Hebert	10/30/2014	Moisture Present	Apex	4015	<input type="checkbox"/>	<input type="checkbox"/>
The filter sample tubing has drops of moisture in low sections outside the shelter.								

# Field Systems Comments

1 **Parameter:** DasComments

The towers are not grounded.

2 **Parameter:** SitingCriteriaCom

The site is in a mountain bowl. The wind pattern from this site would be expected to follow up and down slope patterns. The site is also located in a hay field which is cut 2 or 3 times per year.

3 **Parameter:** ShelterCleanNotes

The shelter is in fair condition.

# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)  USGS Map

Operating Group  Map Scale

AQS #  Map Date

Meteorological Type

Air Pollutant Analyzer  QAPP Latitude

Deposition Measurement  QAPP Longitude

Land Use  QAPP Elevation Meters

Terrain  QAPP Declination

Conforms to MLM  QAPP Declination Date

Site Telephone  Audit Latitude

Site Address 1  Audit Longitude

Site Address 2  Audit Elevation

County  Audit Declination

City, State

Zip Code  **Present**  
 Fire Extinguisher

Time Zone   First Aid Kit

Primary Operator   Safety Glasses

Primary Op. Phone #   Safety Hard Hat

Primary Op. E-mail   Climbing Belt

Backup Operator   Security Fence

Backup Op. Phone #   Secure Shelter

Backup Op. E-mail   Stable Entry Step

Shelter Working Room  Make  Model  Shelter Size

Shelter Clean  Notes

Site OK  Notes

Driving Directions

# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID  Technician  Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km	<input type="text"/>	<input checked="" type="checkbox"/>
City > 50,000 population	40 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Feedlot operations	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Limited agricultural operations	200 m	5 m <input type="text"/>	<input type="checkbox"/>
Large parking lot	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Small parking lot	100 m	<input type="text"/>	<input checked="" type="checkbox"/>
Tree line	50 m	<input type="text"/>	<input checked="" type="checkbox"/>
Obstacles to wind	10 times obstacle height	<input type="text"/>	<input checked="" type="checkbox"/>

Siting Distances OK

**Siting Criteria Comment**

The site is in a mountain bowl. The wind pattern from this site would be expected to follow up and down slope patterns. The site is also located in a hay field which is cut 2 or 3 times per year.



# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID

Technician

Site Visit Date

- |    |  |                                     |     |
|----|--|-------------------------------------|-----|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> | N/A |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> | N/A |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> | N/A |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |     |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |     |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> | N/A |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> | N/A |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> | N/A |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> | N/A |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> | N/A |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | N/A |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

Technician

Site Visit Date

1	Do all the meteorological sensors appear to be intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	Temperature only
2	Are all the meteorological sensors operational online, and reporting data?	<input checked="" type="checkbox"/>	Temperature only
3	Are the shields for the temperature and RH sensors clean?	<input checked="" type="checkbox"/>	
4	Are the aspirated motors working?	<input checked="" type="checkbox"/>	N/A
5	Is the solar radiation sensor's lens clean and free of scratches?	<input checked="" type="checkbox"/>	N/A
6	Is the surface wetness sensor grid clean and undamaged?	<input checked="" type="checkbox"/>	N/A
7	Are the sensor signal and power cables intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	
8	Are the sensor signal and power cable connections protected from the elements and well maintained?	<input checked="" type="checkbox"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID

Technician

Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- |   |   |                                     |  |
|---|---|-------------------------------------|--|
| 1 | Do the sample inlets have at least a 270 degree arc of unrestricted airflow?          | <input checked="" type="checkbox"/> |  |
| 2 | Are the sample inlets 3 - 15 meters above the ground?                                 | <input checked="" type="checkbox"/> |  |
| 3 | Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees? | <input checked="" type="checkbox"/> |  |

**Pollutant analyzers and deposition equipment operations and maintenance**

- |   |  |                                     |                         |
|---|--|-------------------------------------|-------------------------|
| 1 | Do the analyzers and equipment appear to be in good condition and well maintained? | <input checked="" type="checkbox"/> |                         |
| 2 | Are the analyzers and monitors operational, on-line, and reporting data?           | <input checked="" type="checkbox"/> |                         |
| 3 | Describe ozone sample tube.  |                                     | 1/4 teflon by 12 meters |
| 4 | Describe dry dep sample tube.  |                                     | 3/8 teflon by 12 meters |
| 5 | Are in-line filters used in the ozone sample line? (if yes indicate location)      | <input checked="" type="checkbox"/> | At inlet only           |
| 6 | Are sample lines clean, free of kinks, moisture, and obstructions?                 | <input checked="" type="checkbox"/> |                         |
| 7 | Is the zero air supply desiccant unsaturated?                                      | <input checked="" type="checkbox"/> |                         |
| 8 | Are there moisture traps in the sample lines?                                      | <input checked="" type="checkbox"/> | Flow line only          |
| 9 | Is there a rotometer in the dry deposition filter line, and is it clean?           | <input checked="" type="checkbox"/> | Clean and dry           |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

- |                                     |  |   |                      |  |          |                                     |  |                          |  |
|-------------------------------------|--|---|----------------------|--|----------|-------------------------------------|--|--------------------------|--|
| 1                                   | Do the DAS instruments appear to be in good condition and well maintained?           | <input checked="" type="checkbox"/>   |                      |  |          |                                     |  |                          |  |
| 2                                   | Are all the components of the DAS operational? (printers, modem, backup, etc)        | <input checked="" type="checkbox"/>   |                      |  |          |                                     |  |                          |  |
| 3                                   | Do the analyzer and sensor signal leads pass through lightning protection circuitry? | <input checked="" type="checkbox"/>   |                      |  |          |                                     |  |                          |  |
| 4                                   | Are the signal connections protected from the weather and well maintained?           | <input checked="" type="checkbox"/>   |                      |  |          |                                     |  |                          |  |
| 5                                   | Are the signal leads connected to the correct DAS channel?                           | <input checked="" type="checkbox"/>   |                      |  |          |                                     |  |                          |  |
| 6                                   | Are the DAS, sensor translators, and shelter properly grounded?                      | <input checked="" type="checkbox"/>   |                      |  |          |                                     |  |                          |  |
| 7                                   | Does the instrument shelter have a stable power source?                              | <input checked="" type="checkbox"/>   |                      |  |          |                                     |  |                          |  |
| 8                                   | Is the instrument shelter temperature controlled?                                    | <input checked="" type="checkbox"/>   |                      |  |          |                                     |  |                          |  |
| 9                                   | Is the met tower stable and grounded?  | <table border="1"><tr><td>Stable</td><td></td><td>Grounded</td></tr><tr><td><input checked="" type="checkbox"/></td><td></td><td><input type="checkbox"/></td></tr></table> | Stable               |  | Grounded | <input checked="" type="checkbox"/> |  | <input type="checkbox"/> |  |
| Stable                              |  | Grounded  |                      |  |          |                                     |  |                          |  |
| <input checked="" type="checkbox"/> |  | <input type="checkbox"/>  |                      |  |          |                                     |  |                          |  |
| 10                                  | Is the sample tower stable and grounded?   | <table border="1"><tr><td>Stable</td><td></td><td>Grounded</td></tr><tr><td><input checked="" type="checkbox"/></td><td></td><td><input type="checkbox"/></td></tr></table> | Stable               |  | Grounded | <input checked="" type="checkbox"/> |  | <input type="checkbox"/> |  |
| Stable                              |  | Grounded  |                      |  |          |                                     |  |                          |  |
| <input checked="" type="checkbox"/> |  | <input type="checkbox"/>  |                      |  |          |                                     |  |                          |  |
| 11                                  | Tower comments?  |   | <input type="text"/> |  |          |                                     |  |                          |  |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Computer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Solar radiation sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Modem	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Printer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Zero air pump	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	UPS	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Ozone analyzer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack flow controller	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input checked="" type="checkbox"/>	Oct 2001	<input type="checkbox"/>
HASP	<input checked="" type="checkbox"/>	Nov 2009	<input checked="" type="checkbox"/>
Field Ops Manual	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Calibration Reports	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Preventive maintenance schedul	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>

- 1 Is the station log properly completed during every site visit?  Minimal information
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?  Control charts not used

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID  Technician  Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Monthly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Zero Air Desiccant Check	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID

Technician

Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed afternoons
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF
5	Are site supplies on-hand and replenished in a timely fashion?	<input type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF, call-in
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	One set of gloves only
9	Are the site conditions reported regularly to the field operations manager or staff?	<input checked="" type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input type="checkbox"/>	<input type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID

Technician

Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
Computer	Dell	D520	unknown	000264
DAS	Campbell	CR3000	2125	000346
Elevation	Elevation	1	None	None
Filter pack flow pump	Thomas	107CAB18	060400022677	06030
Flow Rate	Apex	AXMC105LPMDPC	illegible	000655
Infrastructure	Infrastructure	none	none	none
Modem	Raven	V4221-V	0844349884	06597
Ozone	ThermoElectron Inc	49i A1NAA	1030244801	000695
Ozone Standard	ThermoElectron Inc	49i A3NAA	CM08200013	000437
Sample Tower	Aluma Tower	B	none	000178
Shelter Temperature	Campbell	107-L	none	none
Siting Criteria	Siting Criteria	1	None	None
Temperature	RM Young	41342	none	missing
Zero air pump	Werther International	C 70/4	000815259	06886



## *Site Inventory by Site Visit*

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>	
<i>ABT147-Sandy Grenville-11/09/2014</i>						
1	11/9/2014	Computer	Dell	000296	D520	unknown
2	11/9/2014	DAS	Campbell	000413	CR3000	2519
3	11/9/2014	Elevation	Elevation	None	1	None
4	11/9/2014	Filter pack flow pump	Thomas	02974	107CAB18	0493002469
5	11/9/2014	Flow Rate	Apex	missing	AXMC105LPM DPCV	illegible
6	11/9/2014	Infrastructure	Infrastructure	none	none	none
7	11/9/2014	Met tower	Universal Tower	06486	unknown	none
8	11/9/2014	Modem	Raven	06609	H4223-C	0844356221
9	11/9/2014	Ozone	ThermoElectron Inc	000627	49i A1NAA	1009241772
10	11/9/2014	Ozone Standard	ThermoElectron Inc	000440	49i A3NAA	CM08200025
11	11/9/2014	Sample Tower	Aluma Tower	000017	B	AT-61152-A-H8-C
12	11/9/2014	Shelter Temperature	Campbell	none	107-L	none
13	11/9/2014	Shield (10 meter)	RM Young	02804	Aspirated 43408	none
14	11/9/2014	Siting Criteria	Siting Criteria	None	1	None
15	11/9/2014	Temperature	RM Young	06503	41342	14623
16	11/9/2014	Zero air pump	Werther International	06930	P 70/4	000829168

# DAS Data Form

DAS Time Max Error:

<b>Mfg</b>	<b>Serial Number</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Use Desc.</b>
Campbell	2519	ABT147	Sandy Grenville	11/09/2014	DAS	Primary

<b>Das Date:</b>	<input type="text" value="11/9 /2014"/>	<b>Audit Date</b>	<input type="text" value="11/9 /2014"/>
<b>Das Time:</b>	<input type="text" value="16:43:21"/>	<b>Audit Time</b>	<input type="text" value="16:43:21"/>
<b>Das Day:</b>	<input type="text" value="313"/>	<b>Audit Day</b>	<input type="text" value="313"/>
<b>Low Channel:</b>		<b>High Channel:</b>	
<b>Avg Diff:</b>	<input type="text" value="0.0001"/>	<b>Max Diff:</b>	<input type="text" value="0.0001"/>
		<b>Avg Diff:</b>	<input type="text" value="0.0001"/>
		<b>Max Diff:</b>	<input type="text" value="0.0001"/>

<b>Mfg</b>	<input type="text" value="Datel"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="15510194"/>	<b>Tfer Desc.</b>	<input type="text" value="Source generator (D"/>
<b>Tfer ID</b>	<input type="text" value="01320"/>		
<b>Mfg</b>	<input type="text" value="Fluke"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="95740135"/>	<b>Tfer Desc.</b>	<input type="text" value="DVM"/>
<b>Tfer ID</b>	<input type="text" value="01311"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="12/28/2013"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
7	0.0000	0.0000	0.0001	V	V	0.0001
7	0.1000	0.0999	0.1000	V	V	0.0001
7	0.3000	0.2997	0.2998	V	V	0.0001
7	0.5000	0.4996	0.4997	V	V	0.0001
7	0.7000	0.6996	0.6996	V	V	0.0000
7	0.9000	0.8995	0.8994	V	V	-0.0001
7	1.0000	0.9993	0.9993	V	V	0.0000

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Apex	illegible		ABT147	Sandy Grenville	11/09/2014	Flow Rate	missing

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	103471	<b>Tfer Desc.</b>	nexus
<b>Tfer ID</b>	01420		
<b>Slope</b>	1.00846	<b>Intercept</b>	0.01358
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	0.99997
<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	103424	<b>Tfer Desc.</b>	BIOS cell
<b>Tfer ID</b>	01410		
<b>Slope</b>	1.00846	<b>Intercept</b>	0.01358
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	0.99997

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
0.22%	0.67%
<b>A Avg %Dif</b>	<b>A Max % Di</b>

<b>Cal Factor Zero</b>	0.01
<b>Cal Factor Full Scale</b>	1.01
<b>Rotometer Reading:</b>	1.5

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignal	PctDifference
primary	pump off	0.000	0.000	-0.02	0.000	-0.03	l/m	l/m	
primary	leak check	0.000	0.000	0.00	0.000	0.00	l/m	l/m	
primary	test pt 1	1.520	1.490	1.49	0.000	1.49	l/m	l/m	0.00%
primary	test pt 2	1.520	1.490	1.48	0.000	1.50	l/m	l/m	0.67%
primary	test pt 3	1.522	1.500	1.49	0.000	1.50	l/m	l/m	0.00%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	No moisture present	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	2.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	0.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	180 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1009241772		ABT147	Sandy Grenville	11/09/2014	Ozone	000627

<b>Slope:</b>	1.01003	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.59769	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99995	<b>CorrCoff</b>	0.00000

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49C-73104-373	<b>Tfer Desc.</b>	Ozone transfer
<b>Tfer ID</b>	01100		
<b>Slope</b>	1.00458	<b>Intercept</b>	-0.11484
<b>Cert Date</b>	12/10/2013	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
0.8%	1.3%		

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	0.04	0.15	-0.15	ppb	
primary	2	30.45	30.42	30.02	ppb	-1.31%
primary	3	50.43	50.31	49.96	ppb	-0.70%
primary	4	82.51	82.24	82.00	ppb	-0.29%
primary	5	102.30	101.94	102.90	ppb	0.94%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.9 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.20	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	0.997	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	96.3 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.70 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	31.4 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	717 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.9 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	91.8 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.71 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass

# Temperature Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	14623		ABT147	Sandy Grenville	11/09/2014	Temperature	06503

<b>Mfg</b>	Extech	<b>Parameter</b>	Temperature
<b>Serial Number</b>	H232734	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01227		
<b>Slope</b>	1.00288	<b>Intercept</b>	-0.15155
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>		<b>DAS 2:</b>	
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>
0.12	0.17		

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Range	0.00	0.15	0.000	0.3	C	0.15
primary	Temp Mid Range	26.45	26.53	0.000	26.6	C	0.04
primary	Temp High Range	48.48	48.49	0.000	48.3	C	-0.17

<b>Sensor Component</b>	Shield	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	Functioning	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Campbell	none	ABT147	Sandy Grenville	11/09/2014	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
0.30	0.38		

<b>Mfg</b>	Extech	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	H232734	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01227		
<b>Slope</b>	1.00288	<b>Intercept</b>	-0.15155
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Mid Range	16.77	16.87	0.000	17.3	C	0.38
primary	Temp Mid Range	16.43	16.53	0.000	16.3	C	-0.25
primary	Temp Mid Range	15.46	15.57	0.000	15.8	C	0.26

## Infrastructure Data For

Site ID  Technician  Site Visit Date

Shelter Make	Shelter Model	Shelter Size
<input type="text" value="Ekto"/>	<input type="text" value="8810 (s/n 2149-9)"/>	<input type="text" value="640 cuft"/>

Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text" value="Type B"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Functioning"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="3/8 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>

# Field Systems Comments

1 **Parameter:** DasComments

The sample tower is no longer grounded. The lower section of the met tower has been replaced.

2 **Parameter:** SitingCriteriaCom

Manure is routinely spread on the hay fields surrounding the site during the summer.

3 **Parameter:** ShelterCleanNotes

The shelter is clean and well organized.

4 **Parameter:** MetSensorComme

10-meter temperature is operated and maintained on the meteorological tower.



# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)	<input type="text" value="EPA"/>	USGS Map	<input type="text" value="Hampton"/>
Operating Group	<input type="text" value="private"/>	Map Scale	<input type="text"/>
AQS #	<input type="text" value="09-015-9991"/>	Map Date	<input type="text"/>
Meteorological Type	<input type="text" value="R.M. Young"/>		
Air Pollutant Analyzer	<input type="text" value="Ozone"/>	QAPP Latitude	<input type="text" value="41.8402"/>
Deposition Measurement	<input type="text" value="dry, wet"/>	QAPP Longitude	<input type="text" value="-72.0111"/>
Land Use	<input type="text" value="agriculture, woodland - mixed"/>	QAPP Elevation Meters	<input type="text" value="209"/>
Terrain	<input type="text" value="rolling"/>	QAPP Declination	<input type="text" value="14.8"/>
Conforms to MLM	<input type="text" value="Marginally"/>	QAPP Declination Date	<input type="text" value="2/22/2006"/>
Site Telephone	<input type="text" value="(860) 974-2273"/>	Audit Latitude	<input type="text" value="41.84046"/>
Site Address 1	<input type="text" value="80 Ayers Road"/>	Audit Longitude	<input type="text" value="-72.010368"/>
Site Address 2	<input type="text"/>	Audit Elevation	<input type="text" value="202"/>
County	<input type="text" value="Windham"/>	Audit Declination	<input type="text" value="-14.5"/>
City, State	<input type="text" value="Abington, CT"/>		
Zip Code	<input type="text" value="06230"/>	<b>Present</b>	
Time Zone	<input type="text" value="Eastern"/>	Fire Extinguisher <input checked="" type="checkbox"/>	<input type="text" value="Inspected Nov 1992"/>
Primary Operator	<input type="text"/>	First Aid Kit <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. Phone #	<input type="text"/>	Safety Glasses <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. E-mail	<input type="text"/>	Safety Hard Hat <input checked="" type="checkbox"/>	<input type="text"/>
Backup Operator	<input type="text"/>	Climbing Belt <input checked="" type="checkbox"/>	<input type="text"/>
Backup Op. Phone #	<input type="text"/>	Security Fence <input type="checkbox"/>	<input type="text"/>
Backup Op. E-mail	<input type="text"/>	Secure Shelter <input checked="" type="checkbox"/>	<input type="text"/>
		Stable Entry Step <input checked="" type="checkbox"/>	<input type="text"/>
Shelter Working Room <input checked="" type="checkbox"/>	Make <input type="text" value="Ekto"/>	Model <input type="text" value="8810 (s/n 2149-9)"/>	Shelter Size <input type="text" value="640 cuft"/>
Shelter Clean <input checked="" type="checkbox"/>	Notes <input type="text" value="The shelter is clean and well organized."/>		
Site OK <input checked="" type="checkbox"/>	Notes <input type="text"/>		

**Driving Directions**

# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID  Technician  Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km	<input type="text"/>	<input checked="" type="checkbox"/>
City > 50,000 population	40 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Feedlot operations	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Limited agricultural operations	200 m	<input type="text" value="10 m"/>	<input type="checkbox"/>
Large parking lot	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Small parking lot	100 m	<input type="text"/>	<input checked="" type="checkbox"/>
Tree line	50 m	<input type="text"/>	<input checked="" type="checkbox"/>
Obstacles to wind	10 times obstacle height	<input type="text"/>	<input checked="" type="checkbox"/>

Siting Distances OK

Siting Criteria Comment

# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID

Technician

Site Visit Date

- |    |  |                                     |     |
|----|--|-------------------------------------|-----|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> | N/A |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> | N/A |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> | N/A |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |     |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |     |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> | N/A |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> | N/A |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> | N/A |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> | N/A |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> | N/A |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | N/A |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

10-meter temperature is operated and maintained on the meteorological tower.

# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

Technician

Site Visit Date

1	Do all the meteorological sensors appear to be intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	N/A
2	Are all the meteorological sensors operational online, and reporting data?	<input checked="" type="checkbox"/>	N/A
3	Are the shields for the temperature and RH sensors clean?	<input checked="" type="checkbox"/>	
4	Are the aspirated motors working?	<input checked="" type="checkbox"/>	
5	Is the solar radiation sensor's lens clean and free of scratches?	<input checked="" type="checkbox"/>	N/A
6	Is the surface wetness sensor grid clean and undamaged?	<input checked="" type="checkbox"/>	N/A
7	Are the sensor signal and power cables intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	
8	Are the sensor signal and power cable connections protected from the elements and well maintained?	<input checked="" type="checkbox"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID

Technician

Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- 1 Do the sample inlets have at least a 270 degree arc of unrestricted airflow?
- 2 Are the sample inlets 3 - 15 meters above the ground?
- 3 Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees?


**Pollutant analyzers and deposition equipment operations and maintenance**

- 1 Do the analyzers and equipment appear to be in good condition and well maintained?
- 2 Are the analyzers and monitors operational, on-line, and reporting data?
- 3 Describe ozone sample tube.
- 4 Describe dry dep sample tube.
- 5 Are in-line filters used in the ozone sample line? (if yes indicate location)
- 6 Are sample lines clean, free of kinks, moisture, and obstructions?
- 7 Is the zero air supply desiccant unsaturated?
- 8 Are there moisture traps in the sample lines?
- 9 Is there a rotometer in the dry deposition filter line, and is it clean?

<input type="checkbox"/> Ozone sample pump not functioning
<input checked="" type="checkbox"/>
1/4 teflon by 15 meters
3/8 teflon by 15 meters
<input checked="" type="checkbox"/> At inlet only
<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/>
<input checked="" type="checkbox"/> Flow line only
<input checked="" type="checkbox"/> Clean and dry

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

--

# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

- |                                     |  |  |                  |          |                                     |                                     |  |
|-------------------------------------|--|--|------------------|----------|-------------------------------------|-------------------------------------|--|
| 1                                   | Do the DAS instruments appear to be in good condition and well maintained?           | <input checked="" type="checkbox"/>  |                  |          |                                     |                                     |  |
| 2                                   | Are all the components of the DAS operational? (printers, modem, backup, etc)        | <input checked="" type="checkbox"/>  |                  |          |                                     |                                     |  |
| 3                                   | Do the analyzer and sensor signal leads pass through lightning protection circuitry? | <input checked="" type="checkbox"/>  | Met sensors only |          |                                     |                                     |  |
| 4                                   | Are the signal connections protected from the weather and well maintained?           | <input checked="" type="checkbox"/>  |                  |          |                                     |                                     |  |
| 5                                   | Are the signal leads connected to the correct DAS channel?                           | <input checked="" type="checkbox"/>  |                  |          |                                     |                                     |  |
| 6                                   | Are the DAS, sensor translators, and shelter properly grounded?                      | <input checked="" type="checkbox"/>  |                  |          |                                     |                                     |  |
| 7                                   | Does the instrument shelter have a stable power source?                              | <input checked="" type="checkbox"/>  |                  |          |                                     |                                     |  |
| 8                                   | Is the instrument shelter temperature controlled?                                    | <input checked="" type="checkbox"/>  |                  |          |                                     |                                     |  |
| 9                                   | Is the met tower stable and grounded?  | <table border="1"><tr><td>Stable</td><td>Grounded</td></tr><tr><td><input checked="" type="checkbox"/></td><td><input type="checkbox"/></td></tr></table>            | Stable           | Grounded | <input checked="" type="checkbox"/> | <input type="checkbox"/>            |  |
| Stable                              | Grounded   |  |                  |          |                                     |                                     |  |
| <input checked="" type="checkbox"/> | <input type="checkbox"/>   |  |                  |          |                                     |                                     |  |
| 10                                  | Is the sample tower stable and grounded?   | <table border="1"><tr><td>Stable</td><td>Grounded</td></tr><tr><td><input checked="" type="checkbox"/></td><td><input checked="" type="checkbox"/></td></tr></table> | Stable           | Grounded | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |  |
| Stable                              | Grounded   |  |                  |          |                                     |                                     |  |
| <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/>  |  |                  |          |                                     |                                     |  |
| 11                                  | Tower comments?  |  |                  |          |                                     |                                     |  |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

The sample tower is no longer grounded. The lower section of the met tower has been replaced.

# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Computer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Solar radiation sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Modem	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Printer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	UPS	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Ozone analyzer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack flow controller	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input checked="" type="checkbox"/>	Oct 2001	<input type="checkbox"/>
HASP	<input checked="" type="checkbox"/>	Feb 2014	<input checked="" type="checkbox"/>
Field Ops Manual	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Calibration Reports	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Preventive maintenance schedul	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>

- 1 Is the station log properly completed during every site visit?
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?  Control charts not used

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID  Technician  Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="As needed"/>	<input checked="" type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input checked="" type="checkbox"/>	<input type="text" value="As needed"/>	<input checked="" type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Every 2 weeks"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Zero Air Desiccant Check	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?  Unknown
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?  SSRF, call-in

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:



# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID

Technician

Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed morinings
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF, logbook
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF, call-in
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	Clean gloves on and off
9	Are the site conditions reported regularly to the field operations manager or staff?	<input checked="" type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input type="checkbox"/>	<input type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID

Technician

Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
Computer	Dell	D520	unknown	000296
DAS	Campbell	CR3000	2519	000413
Elevation	Elevation	1	None	None
Filter pack flow pump	Thomas	107CAB18	0493002469	02974
Flow Rate	Apex	AXMC105LPMDPC	illegible	missing
Infrastructure	Infrastructure	none	none	none
Met tower	Universal Tower	unknown	none	06486
Modem	Raven	H4223-C	0844356221	06609
Ozone	ThermoElectron Inc	49i A1NAA	1009241772	000627
Ozone Standard	ThermoElectron Inc	49i A3NAA	CM08200025	000440
Sample Tower	Aluma Tower	B	AT-61152-A-H8-C	000017
Shelter Temperature	Campbell	107-L	none	none
Shield (10 meter)	RM Young	Aspirated 43408	none	02804
Siting Criteria	Siting Criteria	1	None	None
Temperature	RM Young	41342	14623	06503
Zero air pump	Werther International	P 70/4	000829168	06930

## *Site Inventory by Site Visit*

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>	
<i>WST109-Sandy Grenville-11/10/2014</i>						
1	11/10/2014	Computer	Dell	000291	D520	unknown
2	11/10/2014	DAS	Campbell	000427	CR3000	2526
3	11/10/2014	Elevation	Elevation	None	1	None
4	11/10/2014	Filter pack flow pump	Thomas	00476	107CA18	000025705
5	11/10/2014	Flow Rate	Apex	000466	AXMC105LPMDPCV	43970
6	11/10/2014	Infrastructure	Infrastructure	none	none	none
7	11/10/2014	Met tower	Universal Tower	03532	unknown	none
8	11/10/2014	Modem	Raven	06598	V4221-V	0844349943
9	11/10/2014	Ozone	ThermoElectron Inc	000611	49i A1NAA	1009241795
10	11/10/2014	Ozone Standard	ThermoElectron Inc	000696	49i A3NAA	1030244812
11	11/10/2014	Sample Tower	Aluma Tower	03531	A	none
12	11/10/2014	Shelter Temperature	Campbell	none	107-L	none
13	11/10/2014	Shield (10 meter)	RM Young	00947	Aspirated 43408	none
14	11/10/2014	Siting Criteria	Siting Criteria	None	1	None
15	11/10/2014	Temperature2meter	RM Young	04317	41342	4014
16	11/10/2014	Zero air pump	Werther International	06934	P 70/4	000821881

# DAS Data Form

DAS Time Max Error:

<b>Mfg</b>	<b>Serial Number</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Use Desc.</b>
Campbell	2526	WST109	Sandy Grenville	11/10/2014	DAS	Primary

<b>Das Date:</b>	<input type="text" value="11/10/2014"/>	<b>Audit Date</b>	<input type="text" value="11/10/2014"/>
<b>Das Time:</b>	<input type="text" value="16:34:45"/>	<b>Audit Time</b>	<input type="text" value="16:34:45"/>
<b>Das Day:</b>	<input type="text" value="314"/>	<b>Audit Day</b>	<input type="text" value="314"/>
<b>Low Channel:</b>		<b>High Channel:</b>	
<b>Avg Diff:</b>	<input type="text" value="0.0001"/>	<b>Max Diff:</b>	<input type="text" value="0.0002"/>
		<b>Avg Diff:</b>	<input type="text" value="0.0001"/>
		<b>Max Diff:</b>	<input type="text" value="0.0002"/>

<b>Mfg</b>	<input type="text" value="Datel"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="15510194"/>	<b>Tfer Desc.</b>	<input type="text" value="Source generator (D"/>
<b>Tfer ID</b>	<input type="text" value="01320"/>		
<b>Mfg</b>	<input type="text" value="Fluke"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="95740135"/>	<b>Tfer Desc.</b>	<input type="text" value="DVM"/>
<b>Tfer ID</b>	<input type="text" value="01311"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="12/28/2013"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
7	0.0000	-0.0001	0.0001	V	V	0.0002
7	0.1000	0.0998	0.0999	V	V	0.0001
7	0.3000	0.2996	0.2998	V	V	0.0002
7	0.5000	0.4996	0.4996	V	V	0.0000
7	0.7000	0.6995	0.6995	V	V	0.0000
7	0.9000	0.8993	0.8994	V	V	0.0001
7	1.0000	0.9992	0.9993	V	V	0.0001

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Apex	43970		WST109	Sandy Grenville	11/10/2014	Flow Rate	000466

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	103471	<b>Tfer Desc.</b>	nexus
<b>Tfer ID</b>	01420		
<b>Slope</b>	1.00846	<b>Intercept</b>	0.01358
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	0.99997
<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	103424	<b>Tfer Desc.</b>	BIOS cell
<b>Tfer ID</b>	01410		
<b>Slope</b>	1.00846	<b>Intercept</b>	0.01358
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	0.99997

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
0.67%	0.67%
<b>A Avg %Dif</b>	<b>A Max % Di</b>

<b>Cal Factor Zero</b>	-0.01
<b>Cal Factor Full Scale</b>	0.99
<b>Rotometer Reading:</b>	1.5

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignal	PctDifference
primary	pump off	0.000	0.000	-0.01	0.000	-0.02	l/m	l/m	
primary	leak check	0.000	0.000	0.00	0.000	0.01	l/m	l/m	
primary	test pt 1	1.521	1.490	1.51	0.000	1.50	l/m	l/m	0.67%
primary	test pt 2	1.515	1.490	1.51	0.000	1.50	l/m	l/m	0.67%
primary	test pt 3	1.513	1.490	1.51	0.000	1.50	l/m	l/m	0.67%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	No moisture present	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	3.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	0.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	45 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1009241795		WST109	Sandy Grenville	11/10/2014	Ozone	000611

<b>Slope:</b>	1.00183	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.02369	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99998	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
0.4%	0.6%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49C-73104-373	<b>Tfer Desc.</b>	Ozone transfer
<b>Tfer ID</b>	01100		
<b>Slope</b>	1.00458	<b>Intercept</b>	-0.11484
<b>Cert Date</b>	12/10/2013	<b>CorrCoff</b>	1.00000

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	0.34	0.45	0.30	ppb	
primary	2	30.38	30.35	30.29	ppb	-0.20%
primary	3	51.36	51.24	51.56	ppb	0.62%
primary	4	79.28	79.03	79.47	ppb	0.56%
primary	5	100.84	100.49	100.30	ppb	-0.19%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.9 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-0.2	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.005	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	90.2 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.69 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	32.5 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	718 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.9 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	89.4 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.69 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass

# Temperature Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	4014		WST109	Sandy Grenville	11/10/2014	Temperature	04317

<b>Mfg</b>	Extech	<b>Parameter</b>	Temperature
<b>Serial Number</b>	H232734	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01227		
<b>Slope</b>	1.00288	<b>Intercept</b>	-0.15155
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>		<b>DAS 2:</b>	
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>
0.14	0.21		

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Range	0.00	0.15	0.000	0.1	C	-0.05
primary	Temp Mid Range	24.99	25.07	0.000	24.9	C	-0.21
primary	Temp High Range	49.36	49.37	0.000	49.2	C	-0.17

<b>Sensor Component</b>	Shield	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	Functioning	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	Functioning	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Campbell	none	WST109	Sandy Grenville	11/10/2014	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
0.77	1.45		

<b>Mfg</b>	Extech	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	H232734	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01227		
<b>Slope</b>	1.00288	<b>Intercept</b>	-0.15155
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Mid Range	18.32	18.42	0.000	18.2	C	-0.21
primary	Temp Mid Range	22.15	22.24	0.000	21.6	C	-0.64
primary	Temp Mid Range	25.15	25.23	0.000	23.8	C	-1.45



## Infrastructure Data For

Site ID  Technician  Site Visit Date

Shelter Make	Shelter Model	Shelter Size
<input type="text" value="Ekto"/>	<input type="text" value="8810 (s/n 2149-16)"/>	<input type="text" value="640 cuft"/>

Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text" value="Type B"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="Poor"/>	Status	<input type="text" value="Fail"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Functioning"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="3/8 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>

# Field Systems Comments

**1 Parameter:** DasComments

The sample tower is kinked at the hinge point and is in poor condition. One leg of the met tower is split. Both of these conditions were reported following the two previous site audit visits.

**2 Parameter:** SiteOpsProcedures

The state of NH DES performs monthly multi-point audits of the ozone analyzer. Ozone sample train leak checks are being conducted every two weeks.

**3 Parameter:** SitingCriteriaCom

The site is in a small clearing surrounded by mountain forest. There is a small parking lot used by forest service employees located 50 meters from the site.

**4 Parameter:** SiteOKNotes

State of NH Department of Environmental Services contact is Tom Fazzina (603) 271-0911 and tfazzina@DES.state.NH.US

**5 Parameter:** ShelterCleanNotes

The shelter floor and roof have been repaired. Hand rails have been installed on platform.

**6 Parameter:** MetSensorComme

10-meter temperature is being operated and maintained on the meteorological tower.

# *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

## *BEL116-Eric Hebert-11/10/2014*

1	11/10/2014	Computer	Dell	000266	D520	unknown
2	11/10/2014	DAS	Campbell	000341	CR3000	2120
3	11/10/2014	Elevation	Elevation	None	1	None
4	11/10/2014	Filter pack flow pump	Thomas	02755	107CAB18	1192001881
5	11/10/2014	Infrastructure	Infrastructure	none	none	none
6	11/10/2014	Met tower	Universal Tower	06484	unknown	none
7	11/10/2014	Modem	Raven	06475	H4222-C	0808311155
8	11/10/2014	Ozone	ThermoElectron Inc	000684	49i A1NAA	1030244795
9	11/10/2014	Ozone Standard	ThermoElectron Inc	000373	49i A3NAA	0726124685
10	11/10/2014	Precipitation	Texas Electronics	06332	TR-525i-HT	43527-807
11	11/10/2014	Relative Humidity	Vaisala	06749	HMP50UA	E3420005
12	11/10/2014	Sample Tower	Aluma Tower	000127	B	none
13	11/10/2014	Shelter Temperature	Campbell	none	107-L	44281
14	11/10/2014	Shield (10 meter)	RM Young	05042	Aspirated 43408	none
15	11/10/2014	Shield (2 meter)	RM Young	05041	Aspirated 43408	none
16	11/10/2014	Siting Criteria	Siting Criteria	None	1	None
17	11/10/2014	Solar Radiation	Licor	04935	LI-200	PY47675
18	11/10/2014	Solar Radiation Translator	RM Young	04888	70101-X	none
19	11/10/2014	Surface Wetness	RM Young	04608	58101	none
20	11/10/2014	Temperature	RM Young	06308	41342VO	12533
21	11/10/2014	Temperature2meter	RM Young	06309	41342VO	12534
22	11/10/2014	Wind Direction	RM Young	03416	AQ05103-5	17096wdr
23	11/10/2014	Wind Speed	RM Young	03416	AQ05103-5	17096wsp
24	11/10/2014	Zero air pump	Teledyne	000776	701H	606

# DAS Data Form

DAS Time Max Error:

Mfg	Serial Number	Site	Technician	Site Visit Date	Parameter	Use Desc.
Campbell	2120	BEL116	Eric Hebert	11/10/2014	DAS	Primary

Das Date:	<input type="text" value="11/12/2014"/>	Audit Date:	<input type="text" value="11/12/2014"/>
Das Time:	<input type="text" value="15:12:00"/>	Audit Time:	<input type="text" value="15:12:01"/>
Das Day:	<input type="text" value="316"/>	Audit Day:	<input type="text" value="316"/>
Low Channel:		High Channel:	
Avg Diff:	<input type="text" value="0.0002"/>	Max Diff:	<input type="text" value="0.0004"/>
		Avg Diff:	<input type="text" value="0.0002"/>
		Max Diff:	<input type="text" value="0.0004"/>

Mfg	<input type="text" value="Datel"/>	Parameter	<input type="text" value="DAS"/>
Serial Number	<input type="text" value="4000392"/>	Tfer Desc.	<input type="text" value="Source generator (D"/>
Tfer ID	<input type="text" value="01321"/>		
Slope	<input type="text" value="1.00000"/>	Intercept	<input type="text" value="0.00000"/>
Cert Date	<input type="text" value="2/13/2012"/>	CorrCoff	<input type="text" value="1.00000"/>
Mfg	<input type="text" value="Fluke"/>	Parameter	<input type="text" value="DAS"/>
Serial Number	<input type="text" value="95740243"/>	Tfer Desc.	<input type="text" value="DVM"/>
Tfer ID	<input type="text" value="01312"/>		
Slope	<input type="text" value="1.00000"/>	Intercept	<input type="text" value="0.00000"/>
Cert Date	<input type="text" value="12/28/2013"/>	CorrCoff	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
7	0.0000	-0.0004	-0.0006	V	V	-0.0002
7	0.1000	0.0998	0.0996	V	V	-0.0002
7	0.3000	0.2996	0.2996	V	V	0.0000
7	0.5000	0.4997	0.4995	V	V	-0.0002
7	0.7000	0.6996	0.6995	V	V	-0.0001
7	0.9000	0.8999	0.8995	V	V	-0.0004
7	1.0000	0.9999	0.9996	V	V	-0.0003

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Apex	illegible		BEL116	Eric Hebert	11/10/2014	Flow Rate	000596

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	131818	<b>Tfer Desc.</b>	BIOS 220-H
<b>Tfer ID</b>	01417		
<b>Slope</b>	1.00000	<b>Intercept</b>	0.00000
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>	<b>Cal Factor Zero</b>	0.05
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>Cal Factor Full Scale</b>	1.05
2.80%	3.23%	<b>Rotometer Reading:</b>	1.65

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignalI	PctDifference
primary	pump off	0.000	0.000	-0.07	0.000	-0.02	l/m	l/m	
primary	leak check	0.000	0.000	-0.02	0.000	0.03	l/m	l/m	
primary	test pt 1	1.547	1.550	1.46	0.000	1.50	l/m	l/m	-3.23%
primary	test pt 2	1.549	1.550	1.46	0.000	1.51	l/m	l/m	-2.58%
primary	test pt 3	1.552	1.550	1.46	0.000	1.51	l/m	l/m	-2.58%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	No moisture present	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	6.0 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	1.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	180 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1030244795		BEL116	Eric Hebert	11/10/2014	Ozone	000684

<b>Slope:</b>	1.00369	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.41489	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99992	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
0.4%	0.6%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49CPS-70008-364	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01110		
<b>Slope</b>	1.00707	<b>Intercept</b>	-0.21032
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	0.11	0.31	-0.77	ppb	
primary	2	28.79	28.79	28.96	ppb	0.59%
primary	3	46.76	46.64	46.71	ppb	0.15%
primary	4	77.96	77.62	77.88	ppb	0.33%
primary	5	114.11	113.51	113.00	ppb	-0.45%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.7 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-0.10	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	0.997	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	91.9 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.64 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	34.9 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	723 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	96.3 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.69 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass

# Wind Speed Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	17096wsp		BEL116	Eric Hebert	11/10/2014	Wind Speed	03416

<b>Mfg</b>	RM Young	<b>Parameter</b>	wind speed
<b>Serial Number</b>	CA04013	<b>Tfer Desc.</b>	wind speed motor (h
<b>Tfer ID</b>	01253		
<b>Slope</b>	1.00000	<b>Intercept</b>	0.00000
<b>Cert Date</b>	1/16/2014	<b>CorrCoff</b>	1.00000

**Prop or Cups SN**   
**Prop or Cups Torque**  to   
**Prop Correction Fact**

	<b>DAS 1:</b>		<b>DAS 2:</b>	
	<b>Low Range</b>	<b>High Range</b>	<b>Low Range</b>	<b>High Range</b>
<b>Abs Avg Err</b>	<input type="text" value="0.05"/>	<input type="text" value="0.00%"/>	<input type="text"/>	<input type="text"/>
<b>Abs Max Er</b>	<input type="text" value="0.20"/>	<input type="text" value="0.00%"/>	<input type="text"/>	<input type="text"/>

UseDescription:	Input Device	Input RPM	Input m/s	Out V	DAS m/s	Diff/ %Diff	Diff	WsM
primary	none	0	0.20	0.0	0.0		-0.20	
primary	01253	200	1.02	0.0	1.0		0.00	
primary	01253	400	2.05	0.0	2.1		0.00	
primary	01253	800	4.10	0.0	4.1		0.00	
primary	01253	1200	6.14	0.0	6.1	0.00%		
primary	01253	2400	12.29	0.0	12.3	0.00%		
primary	01253	4000	20.48	0.0	20.5	0.00%		
primary	01253	9400	48.13	0.0	48.1	0.00%		

<b>Sensor Component</b>	Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Prop or Cups Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Sensor Heater	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Torque	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Sensor Plumb	<b>Condition</b>	Plumb	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass



# Wind Direction Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	17096wdr	BEL116	Eric Hebert	11/10/2014	Wind Direction	03416

**Vane SN:**  **C. A. Align. deg. true:**

**Vane Torque**  **to**

<b>Mfg</b>	<input type="text" value="RM Young"/>	<b>Parameter</b>	<input type="text" value="wind direction"/>
<b>Serial Number</b>	<input type="text"/>	<b>Tfer Desc.</b>	<input type="text" value="wind direction wheel"/>
<b>Tfer ID</b>	<input type="text" value="01264"/>		
<b>Mfg</b>	<input type="text" value="Ushikata"/>	<b>Parameter</b>	<input type="text" value="wind direction"/>
<b>Serial Number</b>	<input type="text" value="192034"/>	<b>Tfer Desc.</b>	<input type="text" value="transit"/>
<b>Tfer ID</b>	<input type="text" value="01270"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="1/30/2014"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>Orientation</b>	<b>Linearity:</b>	<b>Orientation</b>	<b>Linearity:</b>
<b>Abs Avg Err</b>	<input type="text" value="2.0"/>	<input type="text" value="1.0"/>	<input type="text"/>
<b>Abs Max Er</b>	<input type="text" value="4"/>	<input type="text" value="3"/>	<input type="text"/>

UseDescription	TferID	Input Raw	Linearity	Output V	Output Deg.	Difference	Change	Error
primary	01264	0	<input checked="" type="checkbox"/>	0.000	0	0	48	3
primary	01264	45	<input checked="" type="checkbox"/>	0.000	45	0	45	0
primary	01264	90	<input checked="" type="checkbox"/>	0.000	89	1	44	-1
primary	01264	135	<input checked="" type="checkbox"/>	0.000	133	2	44	-1
primary	01264	180	<input checked="" type="checkbox"/>	0.000	178	2	45	0
primary	01264	225	<input checked="" type="checkbox"/>	0.000	223	2	45	0
primary	01264	270	<input checked="" type="checkbox"/>	0.000	266	4	43	-2
primary	01264	315	<input checked="" type="checkbox"/>	0.000	312	3	46	1
primary	01270	90	<input type="checkbox"/>	0.000	94	4		4
primary	01270	180	<input type="checkbox"/>	0.000	182	2		2
primary	01270	270	<input type="checkbox"/>	0.000	269	1		1
primary	01270	360	<input type="checkbox"/>	0.000	1	1		1

<b>Sensor Component</b>	<input type="text" value="Torque"/>	<b>Condition</b>	<input type="text"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Sensor Plumb"/>	<b>Condition</b>	<input type="text" value="Plumb"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Sensor Heater"/>	<b>Condition</b>	<input type="text" value="N/A"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Mast"/>	<b>Condition</b>	<input type="text" value="Good"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Condition"/>	<b>Condition</b>	<input type="text" value="Good"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Vane Condition"/>	<b>Condition</b>	<input type="text" value="Good"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="System Memo"/>	<b>Condition</b>	<input type="text"/>	<b>Status</b>	<input type="text" value="pass"/>

# Temperature Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	12533		BEL116	Eric Hebert	11/10/2014	Temperature	06308

<b>DAS 1:</b>		<b>DAS 2:</b>	
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>

<b>Mfg</b>	Eutechnics	<b>Parameter</b>	Temperature
<b>Serial Number</b>	01D102193	<b>Tfer Desc.</b>	RTD translator
<b>Tfer ID</b>	01231		
<b>Slope</b>	1.00133	<b>Intercept</b>	-0.05731
<b>Cert Date</b>	12/27/2013	<b>CorrCoff</b>	1.00000
<b>Mfg</b>	Eutechnics	<b>Parameter</b>	Temperature
<b>Serial Number</b>	01H0060	<b>Tfer Desc.</b>	RTD probe
<b>Tfer ID</b>	01230		
<b>Slope</b>	1.00133	<b>Intercept</b>	-0.05731
<b>Cert Date</b>	12/27/2013	<b>CorrCoff</b>	1.00000

0.09	0.13		
------	------	--	--

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Range	0.13	0.19	0.000	0.07	C	-0.12
primary	Temp Mid Range	23.01	23.04	0.000	23.03	C	-0.01
primary	Temp High Range	46.65	46.65	0.000	46.78	C	0.13

<b>Sensor Component</b>	Shield	<b>Condition</b>	Moderately clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	Functioning	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	Not functioning	<b>Status</b>	Fail
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# 2 Meter Temperature Data For

Calc. Difference

Mfg	Serial Number	Ta	Site	Technician	Site Visit Date	Parameter	Owner ID
RM Young	12534		BEL116	Eric Hebert	11/10/2014	Temperature2meter	06309

**DAS 1:**  
Abs Avg Err   Abs Max Er

**DAS 2:**  
Abs Avg Err   Abs Max Er

<b>Mfg</b>	Eutechnics	<b>Parameter</b>	Temperature
<b>Serial Number</b>	01H0060	<b>Tfer Desc.</b>	RTD probe
<b>Tfer ID</b>	01230		
<b>Slope</b>	1.00133	<b>Intercept</b>	-0.05731
<b>Cert Date</b>	12/27/2013	<b>CorrCoff</b>	1.00000
<b>Mfg</b>	Eutechnics	<b>Parameter</b>	Temperature
<b>Serial Number</b>	01D102193	<b>Tfer Desc.</b>	RTD translator
<b>Tfer ID</b>	01231		
<b>Slope</b>	1.00133	<b>Intercept</b>	-0.05731
<b>Cert Date</b>	12/27/2013	<b>CorrCoff</b>	1.00000

0.16   0.25     

UseDescription	Test type	InputTmpRaw	InputTmpCorrected	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Rang	0.13	0.19	0.000	0.06	C	-0.13
primary	Temp Mid Rang	23.01	23.04	0.000	23.13	C	0.09
primary	Temp High Rang	46.65	46.65	0.000	46.90	C	0.25

<b>Sensor Component</b>	Shield	<b>Condition</b>	Moderately clean	<b>Status</b>	pass
<b>Sensor Component</b>	Properly Sited	<b>Condition</b>	Properly sited	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	Functioning	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	Not functioning	<b>Status</b>	Fail
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Solar Radiation Data Form

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Licor	PY47675	BEL116	Eric Hebert	11/10/2014	Solar Radiation	04935

<b>Mfg</b>	RM Young
<b>SN/Owner ID</b>	none 04888
<b>Parameter</b>	Solar Radiation Translator

<b>Mfg</b>	RM Young	<b>Parameter</b>	solar radiation
<b>Serial Number</b>		<b>Tfer Desc.</b>	SR transfer translat
<b>Tfer ID</b>	01240		
<b>Slope</b>	1.02678	<b>Intercept</b>	-16.91000
<b>Cert Date</b>	6/14/2014	<b>CorrCoff</b>	0.99800
<b>Mfg</b>	Licor	<b>Parameter</b>	solar radiation
<b>Serial Number</b>		<b>Tfer Desc.</b>	SR transfer sensor
<b>Tfer ID</b>	01241		
<b>Slope</b>	1.02678	<b>Intercept</b>	-16.91000
<b>Cert Date</b>	6/14/2014	<b>CorrCoff</b>	0.99800

**DAS 1:**                      **DAS 2:**  
 % Diff of Avg   %Diff of Max   %Diff of Avg   %Diff of Max

0.0%      0.0%      0.0%      0.0%

<b>Sensor Component</b>	Sensor Clean	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Sensor Level	<b>Condition</b>	Level	<b>Status</b>	pass
<b>Sensor Component</b>	Properly Sited	<b>Condition</b>	Properly sited	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Humidity Data Form

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Vaisala	E3420005	BEL116	Eric Hebert	11/10/2014	Relative Humidity	06749

<b>Mfg</b>	Rotronic	<b>Parameter</b>	Relative Humidity
<b>Serial Number</b>	75296	<b>Tfer Desc.</b>	GTL
<b>Tfer ID</b>	01220		
<b>Slope</b>	1.00000	<b>Intercept</b>	0.00000
<b>Cert Date</b>	1/5/2010	<b>CorrCoff</b>	1.00000

DAS 1:

DAS 2:

	Low Range	High Range	Low Range	High Range
<b>Abs Avg Err</b>	1.5	2.2		
<b>Abs Max Er</b>	1.9	2.2		

UseDesc.	Test type	Device	Input RH	GTL Raw	RH Corr.	DAS Volts	DAS %RH	Difference
primary	RH Low Range	GTL	32.8	0.0	32.8	0.000	30.9	-1.9
primary	RH Low Range	GTL	52.9	0.0	52.9	0.000	54.0	1.1
primary	RH High Range	GTL	93.6	0.0	93.6	0.000	95.9	2.2

<b>Sensor Component</b>	RH Filter	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Shield	<b>Condition</b>	Moderately clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Precipitation Data Form

Mfg	Serial Number	Ta	Site	Technician	Site Visit Date	Parameter	Owner ID
Texas Electronics	43527-807		BEL116	Eric Hebert	11/10/2014	Precipitation	06332

<b>DAS 1:</b>		<b>DAS 2:</b>	
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
4.0%	6.0%		

<b>Mfg</b>	PMP	<b>Parameter</b>	Precipitation
<b>Serial Number</b>	EW-06134-50	<b>Tfer Desc.</b>	250ml graduate
<b>Tfer ID</b>	01250		
<b>Slope</b>	1.00000	<b>Intercept</b>	0.00000
<b>Cert Date</b>	9/5/2005	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	TferVolume	Iteration	TimePerTip	Eq.Ht	DAS eng	Eq.HtUnit	OSE Unit	TferUnits	PctDifference
primary	tip check	10 manual	1	2 sec	0.10	0.10	in	in	ml	
primary	test 1	231.5	1	8 - 12 sec	0.50	0.53	in	in	ml	6.0%
primary	test 2	231.5	2	8 - 12 sec	0.50	0.49	in	in	ml	-2.0%

<b>Sensor Component</b>	Properly Sited	<b>Condition</b>	Properly sited	<b>Status</b>	pass
<b>Sensor Component</b>	Gauge Drain Screen	<b>Condition</b>	Installed	<b>Status</b>	pass
<b>Sensor Component</b>	Funnel Clean	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Gauge Screen	<b>Condition</b>	Installed	<b>Status</b>	pass
<b>Sensor Component</b>	Gauge Clean	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Level	<b>Condition</b>	Level	<b>Status</b>	pass
<b>Sensor Component</b>	Sensor Heater	<b>Condition</b>	Functioning	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Campbell	44281	BEL116	Eric Hebert	11/10/2014	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
0.66	0.78		

<b>Mfg</b>	Eutechnics	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	01D102193	<b>Tfer Desc.</b>	RTD translator
<b>Tfer ID</b>	01231		
<b>Slope</b>	1.00133	<b>Intercept</b>	-0.05731
<b>Cert Date</b>	12/27/2013	<b>CorrCoff</b>	1.00000
<b>Mfg</b>	Eutechnics	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	01H0060	<b>Tfer Desc.</b>	RTD probe
<b>Tfer ID</b>	01230		
<b>Slope</b>	1.00133	<b>Intercept</b>	-0.05731
<b>Cert Date</b>	12/27/2013	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Mid Range	27.25	27.27	0.000	26.8	C	-0.49
primary	Temp Mid Range	26.74	26.76	0.000	26.0	C	-0.78
primary	Temp Mid Range	25.64	25.66	0.000	24.9	C	-0.72

# Surface Wetness Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	none		BEL116	Eric Hebert	11/10/2014	Surface Wetness	04608

<b>Mfg</b>	Ohmite	<b>Parameter</b>	surface wetness
<b>Serial Number</b>	296-1200	<b>Tfer Desc.</b>	decade box
<b>Tfer ID</b>	01210		
<b>Slope</b>	1.00000	<b>Intercept</b>	0.00000
<b>Cert Date</b>	1/4/2011	<b>CorrCoff</b>	1.00000

**Manual Test Pass**

UseDescription	Test Type	Tfer kOhms	OutputSignal	DAS eng	OutputSignalEngUni	TferUnits	OutputSignalUnit
primary	wet	N/A	0.000	1.02	V	N/A	V
primary	dry	N/A	0.000	0.01	V	N/A	V

<b>Sensor Component</b>	Properly Sited	<b>Condition</b>	Properly sited	<b>Status</b>	pass
<b>Sensor Component</b>	Grid Clean	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Grid Angle	<b>Condition</b>	about 45 deg	<b>Status</b>	pass
<b>Sensor Component</b>	Grid Orientation	<b>Condition</b>	North	<b>Status</b>	pass
<b>Sensor Component</b>	Grid Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Grid Type	<b>Condition</b>	Grid without holes	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass



## Infrastructure Data For

Site ID  Technician  Site Visit Date

Shelter Make	Shelter Model	Shelter Size
<input type="text" value="Unknown"/>	<input type="text" value="Unknown"/>	<input type="text" value="Unknown"/>

Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text" value="Type B"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Functioning"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="3/8 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>

# Field Systems Comments

**1 Parameter:** SitingCriteriaCom

The site is located between Washington DC and Baltimore, MD near a major transportation corridor. Although the site surroundings are woodland and agriculture, the region surrounding the research center is densely populated and urban.

# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)  USGS Map   
 Operating Group  Map Scale   
 AQS #  Map Date

Meteorological Type   
 Air Pollutant Analyzer  QAPP Latitude

Deposition Measurement  QAPP Longitude   
 Land Use  QAPP Elevation Meters

Terrain  QAPP Declination   
 Conforms to MLM  QAPP Declination Date

Site Telephone  Audit Latitude   
 Site Address 1  Audit Longitude

Site Address 2   
 County  Audit Elevation   
 City, State  Audit Declination

Zip Code  Present  
 Time Zone  Fire Extinguisher

Primary Operator  First Aid Kit   
 Primary Op. Phone #  Safety Glasses

Primary Op. E-mail  Safety Hard Hat   
 Backup Operator  Climbing Belt

Backup Op. Phone #  Security Fence   
 Backup Op. E-mail  Secure Shelter

Stable Entry Step   
 Shelter Working Room  Make  Model  Shelter Size

Shelter Clean  Notes

Site OK  Notes

Driving Directions

# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID  Technician  Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km		<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km		<input checked="" type="checkbox"/>
City > 50,000 population	40 km		<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km		<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km		<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km		<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m		<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m		<input checked="" type="checkbox"/>
Feedlot operations	500 m		<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m		<input checked="" type="checkbox"/>
Limited agricultural operations	200 m		<input checked="" type="checkbox"/>
Large parking lot	200 m		<input checked="" type="checkbox"/>
Small parking lot	100 m	50 m	<input type="checkbox"/>
Tree line	50 m	10 - 30 m	<input type="checkbox"/>
Obstacles to wind	10 times obstacle height		<input checked="" type="checkbox"/>

Siting Distances OK

**Siting Criteria Comment**

The site is in a small clearing surrounded by mountain forest. There is a small parking lot used by forest service employees located 50 meters from the site.

# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID  Technician  Site Visit Date

- |    |  |                                     |     |
|----|--|-------------------------------------|-----|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> | N/A |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> | N/A |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> | N/A |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |     |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |     |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> | N/A |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> | N/A |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> | N/A |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> | N/A |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> | N/A |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | N/A |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

10-meter temperature is being operated and maintained on the meteorological tower.

# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

Technician

Site Visit Date

1	Do all the meteorological sensors appear to be intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	Temperature only
2	Are all the meteorological sensors operational online, and reporting data?	<input checked="" type="checkbox"/>	Temperature only
3	Are the shields for the temperature and RH sensors clean?	<input checked="" type="checkbox"/>	Moderately clean
4	Are the aspirated motors working?	<input checked="" type="checkbox"/>	
5	Is the solar radiation sensor's lens clean and free of scratches?	<input checked="" type="checkbox"/>	N/A
6	Is the surface wetness sensor grid clean and undamaged?	<input checked="" type="checkbox"/>	N/A
7	Are the sensor signal and power cables intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	
8	Are the sensor signal and power cable connections protected from the elements and well maintained?	<input checked="" type="checkbox"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID

Technician

Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- 1 Do the sample inlets have at least a 270 degree arc of unrestricted airflow?
- 2 Are the sample inlets 3 - 15 meters above the ground?
- 3 Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees?


**Pollutant analyzers and deposition equipment operations and maintenance**

- 1 Do the analyzers and equipment appear to be in good condition and well maintained?
- 2 Are the analyzers and monitors operational, on-line, and reporting data?
- 3 Describe ozone sample tube.
- 4 Describe dry dep sample tube.
- 5 Are in-line filters used in the ozone sample line? (if yes indicate location)
- 6 Are sample lines clean, free of kinks, moisture, and obstructions?
- 7 Is the zero air supply desiccant unsaturated?
- 8 Are there moisture traps in the sample lines?
- 9 Is there a rotometer in the dry deposition filter line, and is it clean?

1/4 teflon by 15 meters
3/8 teflon by 15 meters
At inlet only
Moisture in tubing only
Flow line only
Clean and dry

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

--

# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

1	Do the DAS instruments appear to be in good condition and well maintained?	<input checked="" type="checkbox"/>					
2	Are all the components of the DAS operational? (printers, modem, backup, etc)	<input checked="" type="checkbox"/>					
3	Do the analyzer and sensor signal leads pass through lightning protection circuitry?	<input checked="" type="checkbox"/>	Met sensors only				
4	Are the signal connections protected from the weather and well maintained?	<input checked="" type="checkbox"/>					
5	Are the signal leads connected to the correct DAS channel?	<input checked="" type="checkbox"/>					
6	Are the DAS, sensor translators, and shelter properly grounded?	<input checked="" type="checkbox"/>					
7	Does the instrument shelter have a stable power source?	<input checked="" type="checkbox"/>					
8	Is the instrument shelter temperature controlled?	<input checked="" type="checkbox"/>					
9	Is the met tower stable and grounded?	<table border="1"><tr><td>Stable</td><td>Grounded</td></tr><tr><td><input checked="" type="checkbox"/></td><td><input type="checkbox"/></td></tr></table>	Stable	Grounded	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
Stable	Grounded						
<input checked="" type="checkbox"/>	<input type="checkbox"/>						
10	Is the sample tower stable and grounded?	<table border="1"><tr><td>Stable</td><td>Grounded</td></tr><tr><td><input checked="" type="checkbox"/></td><td><input checked="" type="checkbox"/></td></tr></table>	Stable	Grounded	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
Stable	Grounded						
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>						
11	Tower comments?						

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

The sample tower is kinked at the hinge point and is in poor condition. One leg of the met tower is split. Both of these conditions were reported following the two previous site audit visits.



# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Computer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Solar radiation sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Modem	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Printer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	UPS	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Ozone analyzer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack flow controller	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input checked="" type="checkbox"/>	Oct 2001	<input type="checkbox"/>
HASP	<input checked="" type="checkbox"/>	Nov 2014	<input checked="" type="checkbox"/>
Field Ops Manual	<input checked="" type="checkbox"/>	July 1990	<input type="checkbox"/>
Calibration Reports	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Preventive maintenance schedul	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>

- 1 Is the station log properly completed during every site visit?
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?  Control charts not used

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID  Technician  Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?  The site operator was trained by the previous operator, who was trained by the previous operator
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="As needed"/>	<input checked="" type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input checked="" type="checkbox"/>	<input type="text" value="As needed"/>	<input checked="" type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Every 2 weeks"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Zero Air Desiccant Check	<input checked="" type="checkbox"/>	<input type="text" value="Every 2 weeks"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?  Unknown
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?  SSRF, logbook, call-in

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

The state of NH DES performs monthly multi-point audits of the ozone analyzer. Ozone sample train leak checks are being conducted every two weeks.

# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID

Technician

Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed morinings
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF, logbook
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF, logbook, call-in
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	Clean gloves on and off
9	Are the site conditions reported regularly to the field operations manager or staff?	<input checked="" type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input type="checkbox"/>	<input type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID  Technician  Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
Computer	Dell	D520	unknown	000291
DAS	Campbell	CR3000	2526	000427
Elevation	Elevation	1	None	None
Filter pack flow pump	Thomas	107CA18	000025705	00476
Flow Rate	Apex	AXMC105LPMDPC	43970	000466
Infrastructure	Infrastructure	none	none	none
Met tower	Universal Tower	unknown	none	03532
Modem	Raven	V4221-V	0844349943	06598
Ozone	ThermoElectron Inc	49i A1NAA	1009241795	000611
Ozone Standard	ThermoElectron Inc	49i A3NAA	1030244812	000696
Sample Tower	Aluma Tower	A	none	03531
Shelter Temperature	Campbell	107-L	none	none
Shield (10 meter)	RM Young	Aspirated 43408	none	00947
Siting Criteria	Siting Criteria	1	None	None
Temperature	RM Young	41342	4014	04317
Zero air pump	Werther International	P 70/4	000821881	06934

# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)	<input type="text" value="EPA"/>	USGS Map	<input type="text" value="Laurel"/>
Operating Group	<input type="text" value="BARC/private"/>	Map Scale	<input type="text"/>
AQS #	<input type="text" value="24-033-9991"/>	Map Date	<input type="text"/>
Meteorological Type	<input type="text" value="R.M. Young"/>		
Air Pollutant Analyzer	<input type="text" value="Ozone, SO2, NOy, NOx, CO, Hg"/>	QAPP Latitude	<input type="text" value="39.0283"/>
Deposition Measurement	<input type="text" value="dry, wet, Hg"/>	QAPP Longitude	<input type="text" value="-76.8175"/>
Land Use	<input type="text" value="urban - agriculture"/>	QAPP Elevation Meters	<input type="text" value="46"/>
Terrain	<input type="text" value="flat"/>	QAPP Declination	<input type="text" value="11.25"/>
Conforms to MLM	<input type="text" value="No"/>	QAPP Declination Date	<input type="text" value="2/23/2006"/>
Site Telephone	<input type="text" value="(301) 474-3019"/>	Audit Latitude	<input type="text" value="39.028177"/>
Site Address 1	<input type="text" value="BARC old airport"/>	Audit Longitude	<input type="text" value="-76.817127"/>
Site Address 2	<input type="text" value="Springfield Road"/>	Audit Elevation	<input type="text" value="47"/>
County	<input type="text" value="Prince George's"/>	Audit Declination	<input type="text" value="-11"/>
City, State	<input type="text" value="Laurel, MD"/>		
Zip Code	<input type="text" value="20708"/>	<b>Present</b>	
Time Zone	<input type="text" value="Eastern"/>	Fire Extinguisher <input checked="" type="checkbox"/>	<input type="text" value="No inspection date"/>
Primary Operator	<input type="text"/>	First Aid Kit <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. Phone #	<input type="text"/>	Safety Glasses <input type="checkbox"/>	<input type="text"/>
Primary Op. E-mail	<input type="text"/>	Safety Hard Hat <input checked="" type="checkbox"/>	<input type="text"/>
Backup Operator	<input type="text"/>	Climbing Belt <input checked="" type="checkbox"/>	<input type="text"/>
Backup Op. Phone #	<input type="text"/>	Security Fence <input type="checkbox"/>	<input type="text"/>
Backup Op. E-mail	<input type="text"/>	Secure Shelter <input checked="" type="checkbox"/>	<input type="text"/>
		Stable Entry Step <input checked="" type="checkbox"/>	<input type="text"/>
Shelter Working Room <input checked="" type="checkbox"/>	Make <input type="text" value="Unknown"/>	Model <input type="text" value="Unknown"/>	Shelter Size <input type="text" value="Unknown"/>
Shelter Clean <input checked="" type="checkbox"/>	Notes <input type="text"/>		
Site OK <input checked="" type="checkbox"/>	Notes <input type="text"/>		

**Driving Directions**

# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID  Technician  Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km		<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km		<input checked="" type="checkbox"/>
City > 50,000 population	40 km	25 km	<input type="checkbox"/>
City 10,000 to 50,000 population	10 km		<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km		<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km		<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m		<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m		<input checked="" type="checkbox"/>
Feedlot operations	500 m		<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m		<input checked="" type="checkbox"/>
Limited agricultural operations	200 m		<input checked="" type="checkbox"/>
Large parking lot	200 m		<input checked="" type="checkbox"/>
Small parking lot	100 m		<input checked="" type="checkbox"/>
Tree line	50 m		<input checked="" type="checkbox"/>
Obstacles to wind	10 times obstacle height		<input checked="" type="checkbox"/>

Siting Distances OK

**Siting Criteria Comment**

The site is located between Washington DC and Baltimore, MD near a major transportation corridor. Although the site surroundings are woodland and agriculture, the region surrounding the research center is densely populated and urban.

# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID

Technician

Site Visit Date

- |    |  |                                     |                  |
|----|--|-------------------------------------|------------------|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> |                  |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> |                  |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> |                  |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |                  |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |                  |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> |                  |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> |                  |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> |                  |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> |                  |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> |                  |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | About 45 degrees |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

Technician

Site Visit Date

- 1 Do all the meteorological sensors appear to be intact, in good condition, and well maintained?
- 2 Are all the meteorological sensors operational online, and reporting data?
- 3 Are the shields for the temperature and RH sensors clean?
- 4 Are the aspirated motors working?
- 5 Is the solar radiation sensor's lens clean and free of scratches?
- 6 Is the surface wetness sensor grid clean and undamaged?
- 7 Are the sensor signal and power cables intact, in good condition, and well maintained?
- 8 Are the sensor signal and power cable connections protected from the elements and well maintained?


Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

--



# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID

Technician

Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- 1 Do the sample inlets have at least a 270 degree arc of unrestricted airflow?
- 2 Are the sample inlets 3 - 15 meters above the ground?
- 3 Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees?


**Pollutant analyzers and deposition equipment operations and maintenance**

- 1 Do the analyzers and equipment appear to be in good condition and well maintained?
- 2 Are the analyzers and monitors operational, on-line, and reporting data?
- 3 Describe ozone sample tube.
- 4 Describe dry dep sample tube.
- 5 Are in-line filters used in the ozone sample line? (if yes indicate location)
- 6 Are sample lines clean, free of kinks, moisture, and obstructions?
- 7 Is the zero air supply desiccant unsaturated?
- 8 Are there moisture traps in the sample lines?
- 9 Is there a rotometer in the dry deposition filter line, and is it clean?

1/4 teflon by 15 meters
3/8 teflon by 15 meters
At inlet only
Flow line only
Clean and dry

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

--

# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

- |                                     |  |  |                      |          |                                     |                                     |  |
|-------------------------------------|--|--|----------------------|----------|-------------------------------------|-------------------------------------|--|
| 1                                   | Do the DAS instruments appear to be in good condition and well maintained?           | <input checked="" type="checkbox"/>  |                      |          |                                     |                                     |  |
| 2                                   | Are all the components of the DAS operational? (printers, modem, backup, etc)        | <input checked="" type="checkbox"/>  |                      |          |                                     |                                     |  |
| 3                                   | Do the analyzer and sensor signal leads pass through lightning protection circuitry? | <input checked="" type="checkbox"/>  | Met sensors only     |          |                                     |                                     |  |
| 4                                   | Are the signal connections protected from the weather and well maintained?           | <input checked="" type="checkbox"/>  |                      |          |                                     |                                     |  |
| 5                                   | Are the signal leads connected to the correct DAS channel?                           | <input checked="" type="checkbox"/>  |                      |          |                                     |                                     |  |
| 6                                   | Are the DAS, sensor translators, and shelter properly grounded?                      | <input checked="" type="checkbox"/>  |                      |          |                                     |                                     |  |
| 7                                   | Does the instrument shelter have a stable power source?                              | <input checked="" type="checkbox"/>  |                      |          |                                     |                                     |  |
| 8                                   | Is the instrument shelter temperature controlled?                                    | <input checked="" type="checkbox"/>  |                      |          |                                     |                                     |  |
| 9                                   | Is the met tower stable and grounded?  | <table border="1"><tr><td>Stable</td><td>Grounded</td></tr><tr><td><input checked="" type="checkbox"/></td><td><input checked="" type="checkbox"/></td></tr></table> | Stable               | Grounded | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |  |
| Stable                              | Grounded   |  |                      |          |                                     |                                     |  |
| <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/>  |  |                      |          |                                     |                                     |  |
| 10                                  | Is the sample tower stable and grounded?   | <table border="1"><tr><td>Stable</td><td>Grounded</td></tr><tr><td><input checked="" type="checkbox"/></td><td><input checked="" type="checkbox"/></td></tr></table> | Stable               | Grounded | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |  |
| Stable                              | Grounded   |  |                      |          |                                     |                                     |  |
| <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/>  |  |                      |          |                                     |                                     |  |
| 11                                  | Tower comments?  |  | <input type="text"/> |          |                                     |                                     |  |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Computer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Solar radiation sensor	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Modem	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Printer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	UPS	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Ozone analyzer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack flow controller	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input checked="" type="checkbox"/>	Feb 2014	<input checked="" type="checkbox"/>
HASP	<input checked="" type="checkbox"/>	Feb 2014	<input type="checkbox"/>
Field Ops Manual	<input checked="" type="checkbox"/>	Feb 2014	<input checked="" type="checkbox"/>
Calibration Reports	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Preventive maintenance schedul	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>

- 1 Is the station log properly completed during every site visit?
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?  Control charts not used

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID

Technician

Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Every 2 weeks"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Zero Air Desiccant Check	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?  Unknown
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?  SSRF, call-in

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID

Technician

Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed mornings
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF, call-in
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	Clean glove on and off
9	Are the site conditions reported regularly to the field operations manager or staff?	<input checked="" type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input type="checkbox"/>	<input type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID  Technician  Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
Computer	Dell	D520	unknown	000266
DAS	Campbell	CR3000	2120	000341
Elevation	Elevation	1	None	None
Filter pack flow pump	Thomas	107CAB18	1192001881	02755
Flow Rate	Apex	AXMC105LPMDPC	illegible	000596
Infrastructure	Infrastructure	none	none	none
Met tower	Universal Tower	unknown	none	06484
Modem	Raven	H4222-C	0808311155	06475
Ozone	ThermoElectron Inc	49i A1NAA	1030244795	000684
Ozone Standard	ThermoElectron Inc	49i A3NAA	0726124685	000373
Precipitation	Texas Electronics	TR-525i-HT	43527-807	06332
Relative Humidity	Vaisala	HMP50UA	E3420005	06749
Sample Tower	Aluma Tower	B	none	000127
Shelter Temperature	Campbell	107-L	44281	none
Shield (10 meter)	RM Young	Aspirated 43408	none	05042
Shield (2 meter)	RM Young	Aspirated 43408	none	05041
Siting Criteria	Siting Criteria	1	None	None
Solar Radiation	Licor	LI-200	PY47675	04935
Solar Radiation Translator	RM Young	70101-X	none	04888
Surface Wetness	RM Young	58101	none	04608
Temperature	RM Young	41342VO	12533	06308
Temperature2meter	RM Young	41342VO	12534	06309
Wind Direction	RM Young	AQ05103-5	17096wdr	03416
Wind Speed	RM Young	AQ05103-5	17096wsp	03416
Zero air pump	Teledyne	701H	606	000776

---

**APPENDIX B**

**CASTNET Site Spot Report Forms**

---

# EEMS Spot Report

Data Compiled: 5/21/2016 3:36:03 PM

Site Visit Date	Site	Technician
11/09/2014	ABT147	Sandy Grenville

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature average error	P	4	0.5	9	0.12	c	P
2	Temperature max error	P	4	0.5	9	0.17	c	P
3	Ozone Slope	P	0	1.1	4	1.01003	unitless	P
4	Ozone Intercept	P	0	5	4	-0.59769	ppb	P
5	Ozone correlation	P	0	0.995	4	0.99995	unitless	P
6	Ozone % difference avg	P	7	10	4	0.8	%	P
7	Ozone % difference max	P	7	10	4	1.3	%	P
8	Flow Rate average % difference	P	10	5	2	0.22	%	P
9	Flow Rate max % difference	P	10	5	2	0.67	%	P
10	DAS Time maximum error	P	0	5	1	0.00	min	P
11	DAS Voltage average error	P	7	0.003	35	0.0001	V	P

## Field Systems Comments

**1 Parameter:** DasComments

The sample tower is no longer grounded. The lower section of the met tower has been replaced.

**2 Parameter:** SitingCriteriaCom

Manure is routinely spread on the hay fields surrounding the site during the summer.

**3 Parameter:** ShelterCleanNotes

The shelter is clean and well organized.

**4 Parameter:** MetSensorComme

10-meter temperature is operated and maintained on the meteorological tower.



# EEMS Spot Report

Data Compiled: 10/21/2015 1:04:19 PM

Site Visit Date Site Technician

10/03/2014 ACA416 Eric Hebert

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Wind Speed average error below 5m/s in m/s	P	3	0.5	8	0.17	m/s	P
2	Wind Speed max error below 5m/s in m/s	P	3	0.5	8	0.20	m/s	P
3	Wind Speed average % difference above 5 m/s	P	3	5	8	10.2	%	Fail
4	Wind Speed max % difference above 5 m/s	P	3	5	8	38.6	%	Fail
5	Wind Speed Torque average error	P	3	0.5	1	0.30	g-cm	P
6	Wind Speed Torque max error	P	3	0.5	1	0.3	g-cm	P
7	Wind Direction Input Deg True average error (de	P	2	5	10	2.6	degrees	P
8	Wind Direction Input Deg True max error (deg)	P	2	5	10	5	degrees	P
9	Wind Direction Linearity average error (deg)	P	2	5	16	1.5	degrees	P
10	Wind Direction Linearity max error (deg)	P	2	5	16	3	degrees	P
11	Wind Direction Torque average error	P	2	20	1	10	g-cm	P
12	Wind Direction Torque max error	P	2	20	1	10	g-cm	P
13	Temperature average error	P	5	0.5	3	0.17	c	P
14	Temperature max error	P	5	0.5	3	0.27	c	P
15	Delta Temperature average error	P	6	0.5	1	0.02	c	P
16	Delta Temperature average error	P	5	0.5	2	0.04	c	P
17	Delta Temperature max error	P	5	0.5	2	0.05	c	P
18	Delta Temperature max error	P	6	0.5	1	0.02	c	P
19	Relative Humidity average below 85%	P	6	10	9	1.3	%	P
20	Relative Humidity max below 85%	P	6	10	9	2.0	%	P
21	Solar Radiation % diff of avg	P	9	10	8	2.56	%	P
22	Solar Radiation % diff of max STD value	P	9	10	8	1.8	%	P
23	Precipitation average % difference	P	1	10	2	2.0	%	P
24	Precipitation max % difference	P	1	10	2	4.0	%	P
25	Ozone Slope	P	0	1.1	4	1.02704	unitless	P
26	Ozone Intercept	P	0	5	4	0.18362	ppb	P
27	Ozone correlation	P	0	0.995	4	0.99995	unitless	P
28	Ozone % difference avg	P	7	10	4	2.9	%	P
29	Ozone % difference max	P	7	10	4	3.4	%	P
30	Flow Rate average % difference	P	13	5	2	6.3	%	Fail
31	Flow Rate max % difference	P	13	5	2	6.44	%	Fail
32	DAS Time maximum error	P	0	5	1	0.00	min	P
33	DAS Voltage average error	P	15	0.003	28	0.0003	V	P
34	DAS Voltage average error	P	2	0.003	28	0.0000	V	P

**SiteVisitDate Site Technician**

---

10/03/2014	ACA416	Eric Hebert							
35	Surface Wetness Response	P	10	100	1	99.4			<b>P</b>
36	Shelter Temperature average error	P	5	1	6	1.24	c		<b>Fail</b>
37	Shelter Temperature max error	P	5	1	6	2.27	c		<b>Fail</b>

## Field Performance Comments

- Parameter:** Flow Rate      **SensorComponent:** Moisture Present      **CommentCode** 70  
Although there currently is no moisture in the flow sample train, there is evidence of previous moisture events.
- Parameter:** Flow Rate      **SensorComponent:** Moisture Present      **CommentCode** 72  
The filter sample tubing has drops of moisture in low sections outside the shelter.
- Parameter:** Ozone      **SensorComponent:** System Memo      **CommentCode** 208  
The ozone sample train is composed of materials other than the recommended materials which are Teflon and glass only.
- Parameter:** Precipitation      **SensorComponent:** Properly Sited      **CommentCode** 193  
Objects violate the 45 degree rule for the tipping bucket rain gage.

## Field Systems Comments

- Parameter:** SiteOpsProcComm  
This site is operated partly by the NPS and the State of Maine DEP. It is not visited by ARS for semiannual calibration and maintenance visits. The site operator does not perform many of the routine checks conducted at other CASTNET sites, such as tip checks, wetness sensor tests, and visual checks of the blowers. The state of Maine personnel maintain the meteorological systems.
- Parameter:** SiteOpsProcedures  
The meteorological and ozone instrument checks and maintenance are performed by the State of Maine DEP.
- Parameter:** DocumentationCo  
The site operator reported that low flow rate conditions had been observed and reported to ARS recently. The Flow controller has been replaced since then to correct the issue.
- Parameter:** ShelterCleanNotes  
The shelter is clean and well organized.
- Parameter:** PollAnalyzerCom  
The ozone sample inlet still has a stainless steel fittings. The recommended material for ozone sample train is Teflon or glass. The site operator indicated that the fittings would be changed.
- Parameter:** MetSensorComme  
The wind speed translator span is set to 25 m/s and not 50 m/s. This may have affected the low output observed at the highest wind speed challenge.
- Parameter:** MetOpMaintCom  
The sensor signal cables are beginning to show signs of wear.

# EEMS Spot Report

Data Compiled: 5/21/2016 3:58:58 PM

Site Visit Date Site Technician

---

10/07/2014 ASH135 Eric Hebert

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature average error	P	4	0.5	12	0.02	c	P
2	Temperature max error	P	4	0.5	12	0.05	c	P
3	Ozone Slope	P	0	1.1	4	0.99168	unitless	P
4	Ozone Intercept	P	0	5	4	-1.27949	ppb	P
5	Ozone correlation	P	0	0.995	4	0.99992	unitless	P
6	Ozone % difference avg	P	7	10	4	2.7	%	P
7	Ozone % difference max	P	7	10	4	3.5	%	P
8	Flow Rate average % difference	P	10	5	3	1.96	%	P
9	Flow Rate max % difference	P	10	5	3	1.96	%	P
10	DAS Time maximum error	P	0	5	1	0.00	min	P
11	DAS Voltage average error	P	7	0.003	42	0.0001	V	P

SiteVisitDate	Site	Technician
10/07/2014	ASH135	Eric Hebert

## Field Performance Comments

1 **Parameter:** Flow Rate      **SensorComponent:** System Memo      **CommentCode** 81

There is no plastic bag for the installed filter. The operator uses the received bag for the installed filter to ship the removed filter to the lab.

## Field Systems Comments

1 **Parameter:** DasComments

The met tower has been removed and the 10 meter temperature sensor is mounted in a naturally aspirated shield on the sample tower.

2 **Parameter:** SiteOpsProcedures

The ozone inlet filter is replaced and the sample train is leak tested once each month.

3 **Parameter:** SitingCriteriaCom

There is an evergreen plantation 20 meters south of the site.

4 **Parameter:** ShelterCleanNotes

The shelter is in good condition, clean, and very well organized.

# EEMS Spot Report

Data Compiled: 5/21/2016 4:57:00 PM

Site Visit Date Site Technician

11/10/2014 BEL116 Eric Hebert

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature 2 meter average error	P	5	0.5	3	0.16	c	P
2	Temperature 2 meter max error	P	5	0.5	3	0.25	c	P
3	Wind Speed average error below 5m/s in m/s	P	3	0.5	8	0.05	m/s	P
4	Wind Speed max error below 5m/s in m/s	P	3	0.5	8	0.20	m/s	P
5	Wind Speed average % difference above 5 m/s	P	3	5	8	0.0	%	P
6	Wind Speed max % difference above 5 m/s	P	3	5	8	0.0	%	P
7	Wind Speed Torque average error	P	3	0.5	1	0.35	g-cm	P
8	Wind Speed Torque max error	P	3	0.5	1	0.4	g-cm	P
9	Wind Direction Input Deg True average error (deg)	P	2	5	8	2.0	degrees	P
10	Wind Direction Input Deg True max error (deg)	P	2	5	8	4	degrees	P
11	Wind Direction Linearity average error (deg)	P	2	5	16	1.0	degrees	P
12	Wind Direction Linearity max error (deg)	P	2	5	16	3	degrees	P
13	Wind Direction Torque average error	P	2	20	1	12	g-cm	P
14	Wind Direction Torque max error	P	2	20	1	12	g-cm	P
15	Temperature average error	P	4	0.5	12	0.09	c	P
16	Temperature max error	P	4	0.5	12	0.13	c	P
17	Relative Humidity average above 85%	P	6	10	1	2.2	%	P
18	Relative Humidity max above 85%	P	6	10	1	2.2	%	P
19	Relative Humidity average below 85%	P	6	10	2	1.5	%	P
20	Relative Humidity max below 85%	P	6	10	2	1.9	%	P
21	Precipitation average % difference	P	1	10	2	4.0	%	P
22	Precipitation max % difference	P	1	10	2	6.0	%	P
23	Ozone Slope	P	0	1.1	4	1.00369	unitless	P
24	Ozone Intercept	P	0	5	4	-0.41489	ppb	P
25	Ozone correlation	P	0	0.995	4	0.99992	unitless	P
26	Ozone % difference avg	P	7	10	4	0.4	%	P
27	Ozone % difference max	P	7	10	4	0.6	%	P
28	Flow Rate average % difference	P	10	5	2	2.8	%	P
29	Flow Rate max % difference	P	10	5	2	3.23	%	P
30	DAS Time maximum error	P	0	5	1	0.02	min	P
31	DAS Voltage average error	P	7	0.003	49	0.0002	V	P
32	Surface Wetness Response	P	12	0.5	1	1.02		P

<b>SiteVisitDate</b>	<b>Site</b>	<b>Technician</b>
11/10/2014	BEL116	Eric Hebert

## Field Systems Comments

**1 Parameter:** SitingCriteriaCom

The site is located between Washington DC and Baltimore, MD near a major transportation corridor. Although the site surroundings are woodland and agriculture, the region surrounding the research center is densely populated and urban.

# EEMS Spot Report

Data Compiled: 4/9/2015 9:31:09 PM

SiteVisitDate	Site	Technician
11/25/2014	BFT142	Sandy Grenville

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	1.03135	unitless	P
2	Ozone Intercept	P	0	5	4	-0.65714	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99993	unitless	P
4	Ozone % difference avg	P	7	10	4	2.2	%	P
5	Ozone % difference max	P	7	10	4	2.9	%	P



# EEMS Spot Report

Data Compiled: 4/9/2015 8:23:34 PM

Site Visit Date	Site	Technician
11/13/2014	BWR139	Eric Hebert

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	1.00631	unitless	P
2	Ozone Intercept	P	0	5	4	-0.08494	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99997	unitless	P
4	Ozone % difference avg	P	7	10	4	0.6	%	P
5	Ozone % difference max	P	7	10	4	1.2	%	P

# EEMS Spot Report

Data Compiled: 4/9/2015 9:10:19 PM

SiteVisitDate	Site	Technician
11/21/2014	CDR119	Eric Hebert

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	0.98684	unitless	P
2	Ozone Intercept	P	0	5	4	-0.57024	ppb	P
3	Ozone correlation	P	0	0.995	4	1.00000	unitless	P
4	Ozone % difference avg	P	7	10	4	2.4	%	P
5	Ozone % difference max	P	7	10	4	3.5	%	P

# EEMS Spot Report

Data Compiled: 4/9/2015 9:21:32 PM

Site Visit Date	Site	Technician
11/24/2014	CND125	Sandy Grenville

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	0.99966	unitless	P
2	Ozone Intercept	P	0	5	4	-0.05026	ppb	P
3	Ozone correlation	P	0	0.995	4	1.00000	unitless	P
4	Ozone % difference avg	P	7	10	4	0.1	%	P
5	Ozone % difference max	P	7	10	4	0.2	%	P

# EEMS Spot Report

Data Compiled: 4/9/2015 7:48:11 PM

Site Visit Date	Site	Technician
10/27/2014	GRS420	Eric Hebert

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	0.99279	unitless	P
2	Ozone Intercept	P	0	5	4	0.12506	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99999	unitless	P
4	Ozone % difference avg	P	7	10	4	0.4	%	P
5	Ozone % difference max	P	7	10	4	0.8	%	P

# EEMS Spot Report

Data Compiled: 5/21/2016 5:27:52 PM

Site Visit Date Site Technician

10/06/2014 HOW191 Eric Hebert

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature average error	P	4	0.5	9	0.05	c	P
2	Temperature max error	P	4	0.5	9	0.09	c	P
3	Ozone Slope	P	0	1.1	4	0.98661	unitless	P
4	Ozone Intercept	P	0	5	4	-0.31884	ppb	P
5	Ozone correlation	P	0	0.995	4	1.00000	unitless	P
6	Ozone % difference avg	P	7	10	4	2.0	%	P
7	Ozone % difference max	P	7	10	4	2.5	%	P
8	Flow Rate average % difference	P	10	5	3	0.88	%	P
9	Flow Rate max % difference	P	10	5	3	1.32	%	P
10	DAS Time maximum error	P	0	5	1	0.00	min	P
11	DAS Voltage average error	P	7	0.003	35	0.0001	V	P

## Field Systems Comments

**1 Parameter:** SiteOpsProcComm

The site operator reported that gloves are not consistently used to handle the filter pack.

**2 Parameter:** SitingCriteriaCom

The CASTNET filter pack at this location is located above a tree canopy at approximately 23.5 meters from the ground. This is an AmeriFlux site which is approximately 2.5 km to the SW of the HOW132 CASTNET site.

**3 Parameter:** ShelterCleanNotes

The custom built shelter is clean and organized.

**4 Parameter:** MetSensorComme

Other than a temperature sensor located at the CASTNET filter location the meteorological instrumentation is being operated by the University of Maine and AmeriFlux.

# EEMS Spot Report

Data Compiled: 6/9/2016 6:54:00 PM

Site Visit Date Site Technician

09/30/2014 HWF187 Eric Hebert

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature average error	P	4	0.5	12	0.14	c	P
2	Temperature max error	P	4	0.5	12	0.29	c	P
3	Ozone Slope	P	0	1.1	4	0.97152	unitless	P
4	Ozone Intercept	P	0	5	4	-0.17924	ppb	P
5	Ozone correlation	P	0	0.995	4	1.00000	unitless	P
6	Ozone % difference avg	P	7	10	4	3.2	%	P
7	Ozone % difference max	P	7	10	4	3.4	%	P
8	Flow Rate average % difference	P	10	5	2	1.12	%	P
9	Flow Rate max % difference	P	10	5	2	1.35	%	P
10	DAS Time maximum error	P	0	5	1	0.25	min	P
11	DAS Voltage average error	P	7	0.003	42	0.0002	V	P

## Field Performance Comments

- Parameter:** Flow Rate **SensorComponent:** Moisture Present **CommentCode** 72  
The filter sample tubing has drops of moisture in low sections outside the shelter.
- Parameter:** Ozone **SensorComponent:** Cell A Flow **CommentCode** 99  
This analyzer diagnostic check is outside the manufacturer's recommended value.

## Field Systems Comments

- Parameter:** SiteOpsProcedures  
The ozone inlet filter is replaced and the sample train is leak tested every other week.
- Parameter:** ShelterCleanNotes  
The shelter is in good condition.

# EEMS Spot Report

Data Compiled: 4/9/2015 9:00:48 PM

Site Visit Date	Site	Technician
11/19/2014	PAR107	Eric Hebert

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	0.99033	unitless	P
2	Ozone Intercept	P	0	5	4	-0.42713	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99999	unitless	P
4	Ozone % difference avg	P	7	10	4	1.6	%	P
5	Ozone % difference max	P	7	10	4	1.8	%	P

# EEMS Spot Report

Data Compiled: 4/9/2015 8:01:31 PM

SiteVisitDate	Site	Technician
11/03/2014	PED108	Eric Hebert

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	0.98841	unitless	P
2	Ozone Intercept	P	0	5	4	-0.05787	ppb	P
3	Ozone correlation	P	0	0.995	4	1.00000	unitless	P
4	Ozone % difference avg	P	7	10	4	1.2	%	P
5	Ozone % difference max	P	7	10	4	1.3	%	P



# EEMS Spot Report

Data Compiled: 5/21/2016 9:33:36 PM

Site Visit Date Site Technician

10/30/2014 PNF126 Eric Hebert

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature average error	P	4	0.5	3	0.28	c	P
2	Temperature max error	P	4	0.5	3	0.48	c	P
3	Ozone Slope	P	0	1.1	4	0.98882	unitless	P
4	Ozone Intercept	P	0	5	4	0.45144	ppb	P
5	Ozone correlation	P	0	0.995	4	1.00000	unitless	P
6	Ozone % difference avg	P	7	10	4	0.6	%	P
7	Ozone % difference max	P	7	10	4	0.8	%	P
8	Flow Rate average % difference	P	10	5	2	1.1	%	P
9	Flow Rate max % difference	P	10	5	2	1.32	%	P
10	DAS Time maximum error	P	0	5	1	0.00	min	P
11	DAS Voltage average error	P	7	0.003	42	0.0002	V	P

## Field Performance Comments

1 **Parameter:** Flow Rate **SensorComponent:** Moisture Present **CommentCode** 72

The filter sample tubing has drops of moisture in low sections outside the shelter.

## Field Systems Comments

1 **Parameter:** DasComments

The towers are not grounded.

2 **Parameter:** SitingCriteriaCom

The site is in a mountain bowl. The wind pattern from this site would be expected to follow up and down slope patterns. The site is also located in a hay field which is cut 2 or 3 times per year.

3 **Parameter:** ShelterCleanNotes

The shelter is in fair condition.

# EEMS Spot Report

Data Compiled: 4/9/2015 8:49:32 PM

Site Visit Date	Site	Technician
11/18/2014	SHN418	Eric Hebert

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	1.00083	unitless	P
2	Ozone Intercept	P	0	5	4	1.29253	ppb	P
3	Ozone correlation	P	0	0.995	4	1.00000	unitless	P
4	Ozone % difference avg	P	7	10	4	2.6	%	P
5	Ozone % difference max	P	7	10	4	5.0	%	P

# EEMS Spot Report

Data Compiled: 4/9/2015 8:35:38 PM

Site Visit Date	Site	Technician
11/17/2014	VPI120	Eric Hebert

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	0.99285	unitless	P
2	Ozone Intercept	P	0	5	4	0.42120	ppb	P
3	Ozone correlation	P	0	0.995	4	1.00000	unitless	P
4	Ozone % difference avg	P	7	10	4	0.5	%	P
5	Ozone % difference max	P	7	10	4	1.2	%	P

# EEMS Spot Report

Data Compiled: 4/9/2015 8:22:55 PM

SiteVisitDate	Site	Technician
11/14/2014	WSP144	Eric Hebert

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	0.99369	unitless	P
2	Ozone Intercept	P	0	5	4	0.05217	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99998	unitless	P
4	Ozone % difference avg	P	7	10	4	0.9	%	P
5	Ozone % difference max	P	7	10	4	2.0	%	P

# EEMS Spot Report

Data Compiled: 5/21/2016 9:57:03 PM

Site Visit Date	Site	Technician
11/10/2014	WST109	Sandy Grenville

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature average error	P	4	0.5	3	0.14	c	P
2	Temperature max error	P	4	0.5	3	0.21	c	P
3	Ozone Slope	P	0	1.1	4	1.00183	unitless	P
4	Ozone Intercept	P	0	5	4	-0.02369	ppb	P
5	Ozone correlation	P	0	0.995	4	0.99998	unitless	P
6	Ozone % difference avg	P	7	10	4	0.4	%	P
7	Ozone % difference max	P	7	10	4	0.6	%	P
8	Flow Rate average % difference	P	10	5	4	0.67	%	P
9	Flow Rate max % difference	P	10	5	4	0.67	%	P
10	DAS Time maximum error	P	0	5	1	0.00	min	P
11	DAS Voltage average error	P	7	0.003	42	0.0001	V	P

## Field Systems Comments

**1 Parameter:** DasComments

The sample tower is kinked at the hinge point and is in poor condition. One leg of the met tower is split. Both of these conditions were reported following the two previous site audit visits.

**2 Parameter:** SiteOpsProcedures

The state of NH DES performs monthly multi-point audits of the ozone analyzer. Ozone sample train leak checks are being conducted every two weeks.

**3 Parameter:** SitingCriteriaCom

The site is in a small clearing surrounded by mountain forest. There is a small parking lot used by forest service employees located 50 meters from the site.

**4 Parameter:** SiteOKNotes

State of NH Department of Environmental Services contact is Tom Fazzina (603) 271-0911 and tfazzina@DES.state.NH.US

**5 Parameter:** ShelterCleanNotes

The shelter floor and roof have been repaired. Hand rails have been installed on platform.

**6 Parameter:** MetSensorComme

10-meter temperature is being operated and maintained on the meteorological tower.

---

**APPENDIX C**

**CASTNET Ozone Performance Evaluation Forms**

---

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*GRS420-Eric Hebert-10/27/2014*

1	10/27/2014	Computer	Hewlett Packard	none	6560 b	5CB1520H5W
2	10/27/2014	DAS	Environmental Sys Corp	none	8832	unknown4
3	10/27/2014	Ozone	ThermoElectron Inc	none	49i A3NAA	1023943903
4	10/27/2014	Ozone Standard	ThermoElectron Inc	none	49i A1NAA	CM08460051
5	10/27/2014	Sample Tower	Aluma Tower	90945	B	none
6	10/27/2014	Zero air pump	Werther International	none	PC70/4	531385



# Ozone Data Form

Mfg	Serial Number	Ta	Site	Technician	Site Visit Date	Parameter	Owner ID
ThermoElectron Inc	1023943903		GRS420	Eric Hebert	10/27/2014	Ozone	none

<b>Slope:</b>	0.99279	<b>Slope:</b>	0.00000
<b>Intercept</b>	0.12506	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99999	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Avg %Dif</b>
<b>A Max % Di</b>	<b>A Max % Di</b>
0.4%	0.8%

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49CPS-70008-364	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01110		
<b>Slope</b>	1.00707	<b>Intercept</b>	-0.21032
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	0.33	0.53	0.53	ppb	
primary	2	28.00	28.01	27.91	ppb	-0.36%
primary	3	46.61	46.49	46.42	ppb	-0.15%
primary	4	79.35	79.00	78.74	ppb	-0.33%
primary	5	113.46	112.87	112.00	ppb	-0.77%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	1.0005	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.000	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.001	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	82.1 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.71 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	31.7 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	686 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.7 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	87.0 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.70 Lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	0.0006	<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*PED108-Eric Hebert-11/03/2014*

1	11/3/2014	DAS	Campbell	000406	CR3000	2511
2	11/3/2014	Ozone	ThermoElectron Inc	000732	49i A1NAA	1105347319
3	11/3/2014	Ozone Standard	ThermoElectron Inc	000215	49i A3NAA	0622717856
4	11/3/2014	Sample Tower	Aluma Tower	000788	B	unknown
5	11/3/2014	Zero air pump	Werther International	06883	C 70/4	000815257

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1105347319		PED108	Eric Hebert	11/03/2014	Ozone	000732

<b>Slope:</b>	0.98841	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.05787	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	1.00000	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
1.2%	1.3%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49CPS-70008-364	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01110		
<b>Slope</b>	1.00707	<b>Intercept</b>	-0.21032
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	0.22	0.42	0.30	ppb	
primary	2	26.27	26.29	25.96	ppb	-1.26%
primary	3	49.36	49.22	48.60	ppb	-1.26%
primary	4	83.10	82.72	81.80	ppb	-1.11%
primary	5	115.48	114.87	113.40	ppb	-1.28%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	2.0 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.10	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	0.995	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	105.4 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.72 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	29.2 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	731 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	1.3 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	94.0 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.72 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*BWR139-Eric Hebert-11/13/2014*

1	11/13/2014	DAS	Campbell	000431	CR3000	2536
2	11/13/2014	Ozone	ThermoElectron Inc	000731	49i A1NAA	1105347309
3	11/13/2014	Ozone Standard	ThermoElectron Inc	000697	49i A3NAA	1030244814
4	11/13/2014	Sample Tower	Aluma Tower	missing	B	none
5	11/13/2014	Zero air pump	Werther International	06877	C 70/4	000815258

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1105347309		BWR139	Eric Hebert	11/13/2014	Ozone	000731

<b>Slope:</b>	1.00631	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.08494	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99997	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
0.6%	1.2%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49CPS-70008-364	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01110		
<b>Slope</b>	1.00707	<b>Intercept</b>	-0.21032
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	0.18	0.38	0.08	ppb	
primary	2	26.95	26.96	27.07	ppb	0.41%
primary	3	48.90	48.76	49.04	ppb	0.57%
primary	4	76.67	76.34	77.23	ppb	1.17%
primary	5	115.23	114.62	114.90	ppb	0.24%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.000	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.023	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	87.0 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.70 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	30.8 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	741 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.7 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	111.3 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.71 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*WSP144-Eric Hebert-11/14/2014*

1	11/14/2014	DAS	Campbell	000430	CR3000	2525
2	11/14/2014	Ozone	ThermoElectron Inc	000734	49i A1NAA	1105347317
3	11/14/2014	Ozone Standard	ThermoElectron Inc	000543	49i A3NAA	0929938240
4	11/14/2014	Sample Tower	Aluma Tower	000126	B	none
5	11/14/2014	UPS	APC	06267	RS900	unknown
6	11/14/2014	Zero air pump	Werther International	06880	C 70/4	000814273

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1105347317		WSP144	Eric Hebert	11/14/2014	Ozone	000734

<b>Slope:</b>	0.99369	<b>Slope:</b>	0.00000
<b>Intercept</b>	0.05217	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99998	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Avg %Dif</b>
<b>A Max % Di</b>	<b>A Max % Di</b>
0.9%	2.0%

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49CPS-70008-364	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01110		
<b>Slope</b>	1.00707	<b>Intercept</b>	-0.21032
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	0.19	0.39	0.78	ppb	
primary	2	27.14	27.15	26.61	ppb	-1.99%
primary	3	49.35	49.21	48.89	ppb	-0.65%
primary	4	77.55	77.21	76.83	ppb	-0.49%
primary	5	116.20	115.59	115.00	ppb	-0.51%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	1.3 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.40	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	0.997	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	100.5 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.69 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	31.7 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	732 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.9 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	99.6 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.73 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	Functioning	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*VPI120-Eric Hebert-11/17/2014*

1	11/17/2014	DAS	Campbell	000402	CR3000	2514
2	11/17/2014	Ozone	ThermoElectron Inc	000730	49i A1NAA	1105347325
3	11/17/2014	Ozone Standard	ThermoElectron Inc	000443	49i A3NAA	CM08200019
4	11/17/2014	Sample Tower	Aluma Tower	000631	B	none
5	11/17/2014	Zero air pump	Werther International	06879	C 70/4	000814275



# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1105347325		VPI120	Eric Hebert	11/17/2014	Ozone	000730

<b>Slope:</b>	0.99285	<b>Slope:</b>	0.00000
<b>Intercept</b>	0.42120	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	1.00000	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
0.5%	1.2%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49CPS-70008-364	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01110		
<b>Slope</b>	1.00707	<b>Intercept</b>	-0.21032
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	0.25	0.45	0.77	ppb	
primary	2	26.32	26.34	26.66	ppb	1.21%
primary	3	49.24	49.10	49.21	ppb	0.22%
primary	4	77.17	76.83	76.75	ppb	-0.10%
primary	5	103.31	102.79	102.40	ppb	-0.38%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Moderately clean	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-0.70	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.004	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	92.7 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.69 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	33.4 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	652 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	103.2 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.69 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*SHN418-Eric Hebert-11/18/2014*

1	11/18/2014	DAS	Environmental Sys Corp	90603	8816	2272
2	11/18/2014	Ozone	ThermoElectron Inc	none	49i A3NAA	0903334535
3	11/18/2014	Ozone Standard	ThermoElectron Inc	none	49i A1NAA	CM08460009
4	11/18/2014	Sample Tower	Aluma Tower	923307	B	none
5	11/18/2014	Zero air pump	Werther International	none	C 70/4	000855578

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	0903334535		SHN418	Eric Hebert	11/18/2014	Ozone	none

<b>Slope:</b>	1.00083	<b>Slope:</b>	0.00000
<b>Intercept</b>	1.29253	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	1.00000	<b>CorrCoff</b>	0.00000

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49CPS-70008-364	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01110		
<b>Slope</b>	1.00707	<b>Intercept</b>	-0.21032
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
2.6%	5.0%		

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	0.27	0.47	1.83	ppb	
primary	2	26.89	26.91	28.26	ppb	5.02%
primary	3	50.43	50.28	51.44	ppb	2.31%
primary	4	79.75	79.39	80.74	ppb	1.70%
primary	5	105.68	105.14	106.60	ppb	1.39%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	1.2 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	0.9998	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-1.5	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.012	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	92.5 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.66 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	31.6 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	655 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.9 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	88.6 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.65 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	0.0002	<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*PAR107-Eric Hebert-11/19/2014*

1	11/19/2014	DAS	Campbell	000333	CR3000	2112
2	11/19/2014	Ozone	ThermoElectron Inc	000685	49i A1NAA	1030244789
3	11/19/2014	Ozone Standard	ThermoElectron Inc	000436	49i A3NAA	CM08200012
4	11/19/2014	Sample Tower	Aluma Tower	03449	A	none
5	11/19/2014	Zero air pump	Werther International	06932	C 70/4	000829174

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1030244789		PAR107	Eric Hebert	11/19/2014	Ozone	000685

<b>Slope:</b>	0.99033	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.42713	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99999	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
1.6%	1.8%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49CPS-70008-364	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01110		
<b>Slope</b>	1.00707	<b>Intercept</b>	-0.21032
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	0.30	0.50	-0.19	ppb	
primary	2	26.02	26.04	25.57	ppb	-1.80%
primary	3	49.43	49.29	48.53	ppb	-1.54%
primary	4	86.50	86.10	84.90	ppb	-1.39%
primary	5	114.18	113.58	111.90	ppb	-1.48%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	1.1 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.50	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	0.997	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	90.1 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.65 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	31.6 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	687 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	1.3 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	92.2 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.64 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*CDR119-Eric Hebert-11/21/2014*

1	11/21/2014	DAS	Campbell	000332	CR3000	2111
2	11/21/2014	Ozone	ThermoElectron Inc	000623	49i A1NAA	1009241790
3	11/21/2014	Ozone Standard	ThermoElectron Inc	000365	49i A3NAA	0726124688
4	11/21/2014	Sample Tower	Aluma Tower	928376	B	AT-51060-56
5	11/21/2014	Zero air pump	Werther International	06903	C 70/4	000899159

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1009241790		CDR119	Eric Hebert	11/21/2014	Ozone	000623

<b>Slope:</b>	0.98684	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.57024	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	1.00000	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
2.4%	3.5%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49CPS-70008-364	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01110		
<b>Slope</b>	1.00707	<b>Intercept</b>	-0.21032
<b>Cert Date</b>	1/8/2014	<b>CorrCoff</b>	1.00000

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	0.24	0.44	-0.10	ppb	
primary	2	27.17	27.18	26.24	ppb	-3.46%
primary	3	50.65	50.50	49.20	ppb	-2.57%
primary	4	87.79	87.38	85.70	ppb	-1.92%
primary	5	117.63	117.01	114.90	ppb	-1.80%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	1.7 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Dirty	<b>Status</b>	Fail
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.30	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	0.993	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	93.6 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.77 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	28.4 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	728 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	1.7 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	95.4 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.72 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*CND125-Sandy Grenville-11/24/2014*

1	11/24/2014	DAS	Campbell	000499	CR3000	3816
2	11/24/2014	Ozone	ThermoElectron Inc	000692	49i A1NAA	1030244803
3	11/24/2014	Ozone Standard	ThermoElectron Inc	000376	49i A3NAA	0726124693
4	11/24/2014	Zero air pump	Werther International	06868	C 70/4	000814284



# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1030244803		CND125	Sandy Grenville	11/24/2014	Ozone	000692

<b>Slope:</b>	0.99966	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.05026	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	1.00000	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
0.1%	0.2%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49C-73104-373	<b>Tfer Desc.</b>	Ozone transfer
<b>Tfer ID</b>	01100		
<b>Slope</b>	1.00458	<b>Intercept</b>	-0.11484
<b>Cert Date</b>	12/10/2013	<b>CorrCoff</b>	1.00000

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	0.07	0.18	0.06	ppb	
primary	2	29.98	29.95	29.94	ppb	-0.03%
primary	3	50.84	50.72	50.75	ppb	0.06%
primary	4	81.21	80.95	80.80	ppb	-0.19%
primary	5	100.64	100.29	100.20	ppb	-0.09%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.7 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-0.20	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.003	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	89.7 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.72 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	34.3 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	718 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.7 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	92.5 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.72 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass

# EEMS Spot Report

Data Compiled: 4/9/2015 9:31:09 PM

SiteVisitDate	Site	Technician
11/25/2014	BFT142	Sandy Grenville

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	1.03135	unitless	P
2	Ozone Intercept	P	0	5	4	-0.65714	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99993	unitless	P
4	Ozone % difference avg	P	7	10	4	2.2	%	P
5	Ozone % difference max	P	7	10	4	2.9	%	P

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1045347307		BFT142	Sandy Grenville	11/25/2014	Ozone	000738

<b>Slope:</b>	1.03135	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.65714	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99993	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
2.2%	2.9%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49C-73104-373	<b>Tfer Desc.</b>	Ozone transfer
<b>Tfer ID</b>	01100		
<b>Slope</b>	1.00458	<b>Intercept</b>	-0.11484
<b>Cert Date</b>	12/10/2013	<b>CorrCoff</b>	1.00000

UseDescription:	ConcGroup:	Tfer Raw:	Tfer Corr:	Site:	Site Unit:	PctDifference:
primary	1	0.06	0.17	-0.83	ppb	
primary	2	30.91	30.88	31.25	ppb	1.20%
primary	3	50.54	50.42	51.76	ppb	2.66%
primary	4	80.90	80.64	83.00	ppb	2.93%
primary	5	101.26	100.91	102.80	ppb	1.87%

<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.5 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.000	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.039	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	87.7 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.70 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	34.2 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	743 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	89.0 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.76 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*BFT142-Sandy Grenville-11/25/2014*

1	11/25/2014	DAS	Campbell	000498	CR3000	3815
2	11/25/2014	Ozone	ThermoElectron Inc	000738	49i A1NAA	1045347307
3	11/25/2014	Ozone Standard	ThermoElectron Inc	000453	49i A3NAA	CM08200027
4	11/25/2014	Sample Tower	Aluma Tower	000632	B	unknown
5	11/25/2014	Zero air pump	Werther International	06897	C 70/4	000821893