

---

**2016 – 3<sup>rd</sup> Quarter Report**  
**Support for Conducting Systems &**  
**Performance Audits of CASTNET Sites and**  
**NADP Monitoring Stations**

**EPA Contract No. EPW12019**

**Prepared for:**

**U. S. Environmental Protection Agency**

**Prepared by:**



**1128 NW 39<sup>th</sup> Drive**  
**Gainesville, FL 32605**

**October 2016**

---

## Table of Contents

<b>1.0 CASTNET Quarterly Report.....</b>	<b>1-1</b>
1.1 Introduction.....	1-1
1.2 Project Objectives .....	1-1
1.3 CASTNET Sites Visited Third Quarter 2016 .....	1-4
1.4 Audit Results.....	1-5
<b>2.0 NADP Quarterly Report .....</b>	<b>2-1</b>
2.1 Introduction.....	2-1
2.2 Project Objectives .....	2-1
2.3 Sites Visited Third Quarter 2016 .....	2-2
2.4 Survey Results.....	2-4

### List of Appendices

<b>Appendix A</b>	CASNTET Audit Report Forms
<b>Appendix B</b>	CASTNET Site Spot Report Forms
<b>Appendix C</b>	CASTNET Ozone Performance Evaluation Forms

### List of Tables

<b>Table 1.</b>	Performance Audit Challenge and Acceptance Criteria	1-2
<b>Table 2.</b>	Site Audit Visits	1-4
<b>Table 3.</b>	TTP Pollutant PE Visits	1-5
<b>Table 4.</b>	Sites Surveyed – Third Quarter 2016	2-2

## List of Acronyms and Abbreviations

% diff	percent difference
A/D	analog to digital converter
ARS	Air Resource Specialist, Inc.
ASTM	American Society for Testing and Materials
CASTNET	Clean Air Status and Trends Network
DAS	data acquisition system
DC	direct current
deg	degree
DVM	digital voltmeter
EEMS	Environmental, Engineering & Measurement Services, Inc.
EPA	U.S. Environmental Protection Agency
ESC	Environmental Systems Corporation
FSAD	Field Site Audit Database
GPS	geographical positioning system
lpm	liters per minute
MLM	Multilayer Model
m/s	meters per second
mv	milivolt
NIST	National Institute of Standards and Technology
NOAA	National Oceanic and Atmospheric Administration
NPS	National Park Service
QAPP	Quality Assurance Project Plan
SOP	standard operating procedure
TEI	Thermo Environmental Instruments
USNO	United States Naval Observatory
V	volts
WRR	World Radiation Reference

## **1.0 CASTNET Quarterly Report**

### **1.1 Introduction**

The Clean Air Status and Trends Network (CASTNET) is a national air monitoring program developed under mandate of the 1990 Clean Air Act Amendments. Each site in the network measures acidic gases and particles and other forms of atmospheric pollution using a continuous collection filter aggregated over a one week period. Hourly averages of surface ozone concentrations and selected meteorological variables are also measured.

Site measurements are used to estimate deposition rates of the various pollutants with the objective of determining relationships between emissions, air quality, deposition, and ecological effects. In conjunction with other national monitoring networks, CASTNET data are used to determine the effectiveness of national emissions control programs and to assess temporal trends and spatial deposition patterns in atmospheric pollutants. CASTNET data are also used for long-range transport model evaluations and effects research.

CASTNET pollutant flux estimates are calculated as the aggregate product of weekly measured chemical concentrations and model-estimated deposition velocities. Currently, the National Oceanic and Atmospheric Administration's multilayer inferential model (NOAA-MLM) described by Meyers et al. [1998] is used to derive deposition velocity estimates.

As of October 2016, the network is comprised of 95 active rural sampling sites across the United States and Canada, cooperatively operated by the Environmental Protection Agency (EPA), the National Park Service (NPS), Environment Canada, Bureau of Land Management (BLM) and several independent partners. AMEC Foster Wheeler (AMEC) is responsible for operating the EPA and Environment Canada sponsored sites, and Air Resource Specialist, Inc. (ARS) is responsible for operating the NPS and BLM sponsored sites.

### **1.2 Project Objectives**

The objectives of this project are to establish an independent and unbiased program of performance and systems audits for all CASTNET sampling sites. Ongoing Quality Assurance (QA) programs are an essential part of any long-term monitoring network.

Performance audits verify that all evaluated variables are consistent with the accuracy goals as defined in the CASTNET Quality Assurance Project Plan (QAPP). The parameter specific accuracy goals are presented in Table 1. Only four EPA sponsored sites that are operated by AMEC continue to operate meteorological sensors. Those sites are BEL116, BVL30, CHE185,

and PAL190. Five new sites in WY sponsored by EPA and operated by the BLM/ARS also operate meteorological sensors and are BAS601, NEC602, BUF603, FOR604, and SHE604. No site audits at stations operating meteorological sensors were performed during third quarter 2016.

Some or all of the additional monitored variables, NO<sub>y</sub>, CO, and SO<sub>2</sub> have been added to the EPA sponsored sites BVL130, HWF187, PND165, PNF126, ROM206, and BEL116. Those variables were audited at the BVL130 station during third quarter 2016. All of the trace gas results for those audits were found to be within acceptance criteria. The preliminary reports of those results were delivered following the audits and are not included in this report.

**Table 1. Performance Audit Challenge and Acceptance Criteria**

Sensor	Parameter	Audit Challenge	Acceptance Criteria
Precipitation	Response	10 manual tips	1 DAS count per tip
Precipitation	Accuracy	2 introductions of known amounts of water	≤ ±10.0% of input amount
Relative Humidity	Accuracy	Compared to reference instrument or standard solution	≤ ±10.0% RH
Solar Radiation	Accuracy	Compared to WRR traceable standard	≤ ±10.0% of daytime average
Surface Wetness	Response	Distilled water spray mist	Positive response
Surface Wetness	Sensitivity	1% decade resistance	N/A
Temperature	Accuracy	Comparison to 3 NIST measured baths (~ 0° C, ambient, ~ full-scale)	≤ ± 0.5° C
Temperature Difference	Accuracy	Comparison to station temperature sensor	≤ ± 0.50° C
Shelter Temperature	Accuracy	Comparison to station temperature sensor	≤ ± 2.0° C
Wind Direction	Orientation Accuracy	Parallel to alignment rod/crossarm, or sighted to distant point	≤ ±5° from degrees true
Wind Direction	Linearity	Eight cardinal points on test fixture	≤ ±5° mean absolute error
Wind Direction	Response Threshold	Starting torque tested with torque gauge	< 10 g-cm Climatronics; < 20 g-cm R.M. Young
Wind Speed	Accuracy	Shaft rotational speed generated and measured with certified synchronous motor	≤ ±0.5 mps below 5.0 mps input; ≤ ±5.0% of input at or above 5.0 mps
Wind Speed	Starting Threshold	Starting torque tested with torque gauge	< 0.5 g-cm

Sensor	Parameter	Audit Challenge	Acceptance Criteria
Mass Flow Controller	Flow Rate	Comparison with Primary Standard	$\leq \pm 5.0\%$ of designated rate
Ozone	Slope	Linear regression of multi-point test gas concentration as measured with a certified transfer standard	$0.9000 \leq m \leq 1.1000$
Ozone	Intercept		$-5.0 \text{ ppb} \leq b \leq 5.0 \text{ ppb}$
Ozone	Correlation Coefficient		$0.9950 \leq r$
DAS	Accuracy	Comparison with certified standard	$\leq \pm 0.003 \text{ VDC}$

Performance audits are conducted using standards that are traceable to the National Institute of Standards and Technology (NIST), or another authoritative organization, and certified as current.

Site systems audits are intended to provide a qualitative appraisal of the total measurement system. Site planning, organization, and operation are evaluated to ensure that good Quality Assurance/Quality Control (QA/QC) practices are being applied. At a minimum the following audit issues were addressed at each site systems audit:

- Site locations and configurations match those provided in the CASTNET QAPP.
- Meteorological instruments are in good physical and operational condition and are sited to meet EPA ambient monitoring guidelines (EPA-600/4-82-060).
- Sites are accessible, orderly, and if applicable, compliant with OSHA safety standards.
- Sampling lines are free of leaks, kinks, visible contamination, weathering, and moisture.
- Site shelters provide adequate temperature control.
- All ambient air quality instruments are functional, being operated in the appropriate range, and the zero air supply desiccant is unsaturated.
- All instruments are in current calibration.
- Site documentation (maintenance schedules, on-site SOPs, etc.) is current and log book records are complete.
- All maintenance and on-site SOPs are performed on schedule.
- Corrective actions are documented and appropriate for required maintenance/repair activity.
- Site operators demonstrate an adequate knowledge and ability to perform required site activities, including documentation and maintenance activities.

### 1.3 CASTNET Sites Visited Third Quarter 2016

This report consists of the systems and performance and other audit results from the CASTNET sites visited during the third quarter (July through September) of 2016. The locations and dates of the site visits for complete audits are presented in Table 2.

**Table 2. Site Audit Visits**

<u>Side ID</u>	<u>Audit Type</u>	<u>Sponsor</u>	<u>Site Visit Date</u>	<u>Station Name</u>
DEN417	Without Met	NPS	07/07/2016	Denali National Park
SAL133	Without Met	EPA	07/19/2016	Salamonie Reservoir
MKG113	Without Met	EPA	08/15/2016	M. K. Goddard St. Park
ANA115	Without Met	EPA	08/15/2016	Ann Arbor
UVL124	Without Met	EPA	08/16/2016	Unionville
KEF112	Without Met	EPA	08/17/2016	Kane Experimental Forest
HOX148	Without Met	EPA	08/18/2016	Hoxeyville
PSU106	Without Met	EPA	08/22/2016	Penn State
RED004	Flow only	EPA	08/30/2016	Red Lake Nation
WST109	Without Met	EPA	09/15/2016	Woodstock
ABT147	Without Met	EPA	09/17/2016	Abington

In addition to the sites listed in Table 2 that were visited for complete audits, the sites listed in Table 3 were visited to conduct Through-The-Probe (TTP) pollutant Performance Evaluations (PE).

**Table 3. TTP Pollutant PE Visits**

<u>Side ID</u>	<u>PE Audit Type</u>	<u>Sponsor</u>	<u>Site Visit Date</u>	<u>Station Name</u>
STK138	Ozone	EPA	07/20/2016	Stockton
ALH157	Ozone	EPA	07/21/2016	Alhambra
VIN140	Ozone	EPA	07/22/2016	Vincennes
CNT169	Ozone	EPA	08/18/2016	Centennial
LRL117	Ozone	EPA	08/23/2016	Laurel Hill
NEC602	Ozone	BLM	08/24/2016	Newcastle
VOY413	Ozone	NPS	08/29/2016	Voyageurs NP
PRK134	Ozone	EPA	09/01/2016	Perkinstown
SAN189	Ozone	EPA	09/09/2016	Santee Sioux
GRB411	Ozone	NPS	09/18/2016	Great Basin NP
BVL130	Ozone, NO <sub>y</sub> , SO <sub>2</sub> , CO	EPA	09/24/2016	Bondville
GLR468	Ozone	NPS	09/26/2016	Glacier NP

#### **1.4 Audit Results**

The observations and results of the systems and performance audits are included in Appendix A, *CASTNET Audit Report Forms* by site, arranged by audit date.

Photographs of site conditions are included within each systems report where necessary.

Copies of the spot reports that were sent immediately following the audit of each site are included as Appendix B, *CASTNET Site Spot Report Forms*.

The Ozone PE results and observations are included in Appendix C, *CASTNET Ozone Performance Evaluation Forms*.



## **2.0 NADP Quarterly Report**

### **2.1 Introduction**

The National Atmospheric Deposition Program (NADP) operates three precipitation chemistry networks and two atmospheric concentration networks. The National Trends Network (NTN) has been measuring acidic precipitation since 1978. The network currently has more than 250 sites. The Atmospheric Integrated Research Monitoring Network (AIRMoN) began operation in 1992 and currently measures event based precipitation events at 6 sites. The Mercury Deposition Network (MDN) measures total mercury in precipitation samples from more than 120 stations. The MDN began operation in 1996 and includes sites throughout the US and Canada. The Atmospheric Mercury Network (AMNet) and the Ammonia Monitoring Network (AMoN) measure ambient concentrations of mercury and ammonia, respectively.

The NADP and other long-term monitoring networks provide critical information to the EPA regarding evaluating the effectiveness of emission reduction control programs from the power industry.

The NADP Program Office operates and administers the three precipitation chemistry networks (NTN, MDN and AIRMoN), two atmospheric concentration networks (AMNet and AMoN), two analytical laboratories (the Central Analytical Laboratory (CAL) located at the University of Illinois/Illinois State Water Survey and the Mercury Analytical Laboratory (HAL) located at Frontier Global Sciences), and the network equipment depot (NED).

### **2.2 Project Objectives**

The objective of this project is to perform independent and unbiased evaluations of the sites along with its operations. These evaluations provide quality assurance pertaining to siting, sample collection and handling, equipment operation and maintenance, record keeping and field laboratory procedures.

More specifically, the surveys determine and report findings based on an established methodology consisting of completing a site questionnaire, testing the equipment and documenting with photographs the location, siting criteria, existing equipment, and any issues encountered that require such documentation.

### 2.3 Sites Visited Third Quarter 2016

This report covers the results from the NADP sites surveyed during the third quarter (July through September) of 2016. The station names and dates of the audits are presented in Table 4.

**Table 4. Sites Surveyed – Third Quarter 2016**

<u>Side ID</u>	<u>Network</u>	<u>Visit Date</u>	<u>Station Name</u>
AK01	NTN	7/11/2016	Poker Creek
AK03	NTN	7/7/2016	Denali National Park-Mt. McKinley
AK97	NTN	7/5/2016	Katmai National Park-King Salmon
CO93	NTN	7/26/2016	Dry Lake
IL46	NTN/AMoN	7/21/2016	Alhambra
IL73	AMoN	7/20/2016	Stockton
IN20	NTN	7/19/2016	Roush Lake
IN22	NTN	7/22/2016	Southwest Purdue Agriculture Center
IN41	NTN	7/19/2016	Agronomy Center for Research and Extension
ID02	NTN	8/5/2016	Priest River Experimental Forest
ID03	NTN/AMoN	8/2/2016	Craters of the Moon National Monument
ID11	NTN	8/3/2016	Reynolds Creek
MI52	MDN/NTN/AMoN	8/15/2016	Ann Arbor
MI99	NTN	8/22/2016	Chassell
MN23	MDN/NTN	8/30/2016	Camp Ripley
MN28	NTN	8/31/2016	Grindstone Lake
MN32	NTN	8/29/2016	Voyageurs National Park-Sullivan Bay
ND00	NTN	8/23/2016	Theodore Roosevelt National Park-Painted Canyon
OR09	NTN	8/11/2016	Silver Lake Ranger Station
OR10	NTN	8/9/2016	H. J. Andrews Experimental Forest

<b><u>Side ID</u></b>	<b><u>Network</u></b>	<b><u>Visit Date</u></b>	<b><u>Station Name</u></b>
OR18	NTN	8/4/2016	Starkey Experimental Forest
OR97	NTN	8/10/2016	Hyslop Farm
PA13	MDN/NTN	8/21/2016	Allegheny Portage Railroad National Historic Site
PA29	MDN/NTN/AMoN	8/17/2016	Kane Experimental Forest
PA30	MDN/NTN	8/15/2016	Erie
PA42	MDN/NTN	8/22/2016	Leading Ridge
PA90	MDN	8/19/2016	Hills Creek State Park
SD04	NTN	8/24/2016	Wind Cave National Park-Elk Mountain
WI08	MDN/NTN	8/23/2016	Brule River
WI36	MDN/NTN	8/23/2016	Trout Lake
CT15	AMoN	9/17/2016	Abington
IL11	AMoN	9/24/2016	Bondville
MA22	NTN	9/14/2016	Boston University
MA98	NTN	9/14/2016	Arnold Arboretum
MT00	NTN	9/29/2016	Little Bighorn Battlefield National Monument
MT05	MDN/NTN	9/26/2016	Glacier National Park-Fire Weather Station
MT07	NTN	9/28/2016	Clancy
MT95	MDN	9/29/2016	Badger Peak
NY06	MDN/NTN	9/13/2016	Bronx
NY10	NTN	9/27/2016	Chautauqua
NY43	MDN/NTN	9/28/2016	Rochester
NY94	NTN	9/29/2016	Nick's Lake
OH71/71OH	NTN	9/26/2016	Wooster

<u>Side ID</u>	<u>Network</u>	<u>Visit Date</u>	<u>Station Name</u>
PA47	MDN/NTN	9/12/2016	Millersville
PA60	MDN	9/18/2016	Valley Forge
MT95	MDN	9/29/2016	Badger Peak

## 2.4 Survey Results

Site survey results are entered into a relational database. The database in turn generates Site Spot Reports which are distributed among the interested parties as soon as all the site data has been entered. Database tables with all the data collected and reviewed are then sent to the NADP Program Office and to the U.S. EPA Project Officers.

Other items gathered during the surveys (i.e., photographs, Belfort charts, etc.) are uploaded to EEMS' server where the NADP PO and the U.S. EPA POs can access them and download them as needed by login into the server site.

Given the volume of data generated, and the fact that data is distributed and/or is available through EEMS' server, no survey results are included in this report.

---

**APPENDIX A**

**CASTNET Audit Report Forms**

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

### *DEN417-Martin Valvur-07/07/2016*

1	7/7/2016	Computer	Hewlett Packard	none	ProBook	5CB22906R7
2	7/7/2016	DAS	Environmental Sys Corp	90600	8816	2274
3	7/7/2016	Elevation	Elevation	None	1	None
4	7/7/2016	Filter pack flow pump	Thomas	none	107CAB18B	099800009739
5	7/7/2016	Flow Rate	Tylan	90966	FC280SAV	AW9706011
6	7/7/2016	Infrastructure	Infrastructure	none	none	none
7	7/7/2016	Mainframe	Climatronics	none	100081	1293
8	7/7/2016	Mainframe power supply	Climatronics	none	101074	685
9	7/7/2016	Met tower	Glen Martin Engineering	none	unknown	none
10	7/7/2016	MFC power supply	Tylan	90967	RO-32	FP9706004
11	7/7/2016	Modem	US Robotics	none	33.6 fax modem	unknown
12	7/7/2016	Ozone	ThermoElectron Inc	90778	49C	49C-77033-384
13	7/7/2016	Ozone Standard	ThermoElectron Inc	none	49C	49C-71310-368
14	7/7/2016	Printer	Hewlett Packard	none	840C	unknown
15	7/7/2016	Sample Tower	Aluma Tower	none	B	AT-71102-7I-5
16	7/7/2016	Shelter Temperature	ARS	none	none	006
17	7/7/2016	Siting Criteria	Siting Criteria	None	1	None
18	7/7/2016	Temperature2meter	RM Young	none	41342	018533
19	7/7/2016	Zero air pump	Werther International	none	PC70/4	526281

# DAS Data Form

DAS Time Max Error:

Mfg	Serial Number	Site	Technician	Site Visit Date	Parameter	Use Desc.
Environmental Sys	2274	DEN417	Martin Valvur	07/07/2016	DAS	Primary

Das Date:	<input type="text" value="7 / 7 / 2016"/>	Audit Date:	<input type="text" value="7 / 7 / 2016"/>
Das Time:	<input type="text" value="8:20:00"/>	Audit Time:	<input type="text" value="8:20:00"/>
Das Day:	<input type="text" value="189"/>	Audit Day:	<input type="text" value="189"/>
Low Channel:		High Channel:	
Avg Diff:	Max Diff:	Avg Diff:	Max Diff:
<input type="text" value="0.0002"/>	<input type="text" value="0.0003"/>	<input type="text" value="0.0002"/>	<input type="text" value="0.0003"/>

Mfg	<input type="text" value="HY"/>	Parameter	<input type="text" value="DAS"/>
Serial Number	<input type="text" value="12010039329"/>	Tfer Desc.	<input type="text" value="Source generator (D"/>
Tfer ID	<input type="text" value="01322"/>		
Slope	<input type="text" value="1.00000"/>	Intercept	<input type="text" value="0.00000"/>
Cert Date	<input type="text" value="6/15/2014"/>	CorrCoff	<input type="text" value="1.00000"/>
Mfg	<input type="text" value="Fluke"/>	Parameter	<input type="text" value="DAS"/>
Serial Number	<input type="text" value="95740243"/>	Tfer Desc.	<input type="text" value="DVM"/>
Tfer ID	<input type="text" value="01312"/>		
Slope	<input type="text" value="1.00000"/>	Intercept	<input type="text" value="0.00000"/>
Cert Date	<input type="text" value="12/23/2015"/>	CorrCoff	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
7	0.0000	-0.0004	-0.0005	V	V	-0.0001
7	0.1000	0.0994	0.0997	V	V	0.0003
7	0.3000	0.2996	0.2997	V	V	0.0001
7	0.5000	0.4994	0.4997	V	V	0.0003
7	0.7000	0.7002	0.6999	V	V	-0.0003
7	0.9000	0.8996	0.8999	V	V	0.0003
7	1.0000	1.0000	1.0001	V	V	0.0001

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Tylan	AW9706011		DEN417	Martin Valvur	07/07/2016	Flow Rate	90966

<b>Mfg</b>	Tylan
<b>SN/Owner ID</b>	FP9706004 90967
<b>Parameter</b>	MFC power supply

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	122974	<b>Tfer Desc.</b>	BIOS 220-H
<b>Tfer ID</b>	01416		
<b>Slope</b>	0.99895	<b>Intercept</b>	0.01185
<b>Cert Date</b>	2/10/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
0.61%	0.64%

<b>Cal Factor Zero</b>	0
<b>Cal Factor Full Scale</b>	0
<b>Rotometer Reading:</b>	0

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignalI	PctDifference
primary	pump off	0.000	0.000	-0.19	-0.146	-0.06	l/m	l/m	
primary	leak check	0.000	0.000	-0.18	-0.141	-0.05	l/m	l/m	
primary	test pt 1	2.992	2.980	2.58	2.586	3.00	l/m	l/m	0.60%
primary	test pt 2	2.992	2.980	2.58	2.586	3.00	l/m	l/m	0.64%
primary	test pt 3	2.989	2.980	2.58	2.586	3.00	l/m	l/m	0.60%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Poor	<b>Status</b>	Fail
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	No moisture present	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	5.0 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	-0.5 cm	<b>Status</b>	fail
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	10 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>	See comments	<b>Status</b>	pass



# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	49C-77033-384		DEN417	Martin Valvur	07/07/2016	Ozone	90778

<b>Slope:</b>	1.06973	<b>Slope:</b>	0.00000
<b>Intercept</b>	-1.07240	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99999	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
4.7%	6.1%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49CPS-70008-364	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01110		
<b>Slope</b>	0.99832	<b>Intercept</b>	-0.26452
<b>Cert Date</b>	1/29/2016	<b>CorrCoff</b>	1.00000

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	-0.06	0.20	-0.69	ppb	
primary	2	27.93	28.24	28.88	ppb	2.27%
primary	3	50.31	50.65	53.20	ppb	5.03%
primary	4	80.18	80.57	85.02	ppb	5.52%
primary	5	110.40	110.85	117.60	ppb	6.09%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	1.2	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.030	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	-0.0016	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	0.9990	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	117.1 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.8 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.65 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	6.78.7 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	33.3 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	90.9 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.69 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	< 1 %	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# 2 Meter Temperature Data Form

Calc. Difference

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	018533		DEN417	Martin Valvur	07/07/2016	Temperature2meter	none

<b>Mfg</b>	Fluke	<b>Parameter</b>	Temperature
<b>Serial Number</b>	3275143	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01229		
<b>Slope</b>	0.99980	<b>Intercept</b>	-0.02840
<b>Cert Date</b>	1/19/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>		<b>DAS 2:</b>	
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>

0.12	0.28		
------	------	--	--

UseDescription	Test type	InputTmpRaw	InputTmpCorrected	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Rang	0.04	0.07	0.000	0.13	C	0.06
primary	Temp Mid Rang	23.33	23.36	0.000	23.34	C	-0.02
primary	Temp High Rang	48.71	48.75	0.000	48.47	C	-0.28

<b>Sensor Component</b>	Properly Sited	<b>Condition</b>	Properly sited	<b>Status</b>	pass
<b>Sensor Component</b>	Shield	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	Functioning	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
ARS	006	DEN417	Martin Valvur	07/07/2016	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
1.35	2.90		

<b>Mfg</b>	Fluke	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	3275143	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01229		
<b>Slope</b>	0.99980	<b>Intercept</b>	-0.02840
<b>Cert Date</b>	1/19/2016	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Mid Range	22.51	22.54	0.000	23.6	C	1.01
primary	Temp Mid Range	20.66	20.69	0.000	23.6	C	2.9
primary	Temp Mid Range	23.97	24.00	0.000	24.1	C	0.14

<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
-------------------------	-------------	------------------	--	---------------	------

## Infrastructure Data For

Site ID  Technician  Site Visit Date

Shelter Make	Shelter Model	Shelter Size
<input type="text" value="Ekto"/>	<input type="text" value="8814"/>	<input type="text" value="896 cuft"/>

Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text" value="Type B"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Not installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Functioning"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="3/8 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>

# Site Visit Comments

<b>Parameter</b>	<b>Site</b>	<b>Technician</b>	<b>S.V. Date</b>	<b>Component</b>	<b>Mfg</b>	<b>Serial No.</b>	<b>Hazard</b>	<b>Problem</b>
------------------	-------------	-------------------	------------------	------------------	------------	-------------------	---------------	----------------

Flow Rate	DEN417	Martin Valvur	07/07/2016	Filter Position	Tylan	3168	<input type="checkbox"/>	<input checked="" type="checkbox"/>
-----------	--------	---------------	------------	-----------------	-------	------	--------------------------	-------------------------------------

The filter attachment plate is mounted too low in the enclosure resulting in the filter being exposed to wind-driven rain and in the standard geometric orientation.

# Field Systems Comments

1 **Parameter:** SiteOpsProcComm

The site operator uses one gloved hand, and the same glove, to remove and install the filter pack. Leak checks are performed when the ambient temperature is above -10 C.

2 **Parameter:** ShelterCleanNotes

The shelter is in good condition, clean, neat, and very well organized.

# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)	<input type="text" value="NPS/EPA"/>	USGS Map	<input type="text" value="Healy C-4"/>
Operating Group	<input type="text" value="NPS"/>	Map Scale	<input type="text"/>
AQS #	<input type="text" value="02-068-0003"/>	Map Date	<input type="text"/>
Meteorological Type	<input type="text" value="Climatronics"/>		
Air Pollutant Analyzer	<input type="text" value="ozone, IMPROVE"/>	QAPP Latitude	<input type="text"/>
Deposition Measurement	<input type="text" value="dry, wet"/>	QAPP Longitude	<input type="text"/>
Land Use	<input type="text" value="woodland - mixed"/>	QAPP Elevation Meters	<input type="text"/>
Terrain	<input type="text" value="complex"/>	QAPP Declination	<input type="text"/>
Conforms to MLM	<input type="text" value="No"/>	QAPP Declination Date	<input type="text"/>
Site Telephone	<input type="text" value="(907) 683-9638"/>	Audit Latitude	<input type="text" value="63.7232"/>
Site Address 1	<input type="text" value="mile 238 Parks Highway"/>	Audit Longitude	<input type="text" value="-148.9676"/>
Site Address 2	<input type="text"/>	Audit Elevation	<input type="text" value="663"/>
County	<input type="text" value="Denali Borough"/>	Audit Declination	<input type="text" value="19.3"/>
City, State	<input type="text" value="Denali Park, AK"/>		
Zip Code	<input type="text" value="99755"/>	Fire Extinguisher <input type="checkbox"/>	<input type="text"/>
Time Zone	<input type="text" value="Alaska Time Zone"/>	First Aid Kit <input type="checkbox"/>	<input type="text"/>
Primary Operator	<input type="text"/>	Safety Glasses <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. Phone #	<input type="text"/>	Safety Hard Hat <input type="checkbox"/>	<input type="text"/>
Primary Op. E-mail	<input type="text"/>	Climbing Belt <input checked="" type="checkbox"/>	<input type="text"/>
Backup Operator	<input type="text"/>	Security Fence <input type="checkbox"/>	<input type="text"/>
Backup Op. Phone #	<input type="text"/>	Secure Shelter <input checked="" type="checkbox"/>	<input type="text"/>
Backup Op. E-mail	<input type="text"/>	Stable Entry Step <input checked="" type="checkbox"/>	<input type="text"/>

Shelter Working Room  Make  Model  Shelter Size

Shelter Clean  Notes

Site OK  Notes

**Driving Directions**

# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID

Technician

Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO <sub>2</sub> or NO <sub>x</sub>	20 to 40 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km	<input type="text"/>	<input checked="" type="checkbox"/>
City > 50,000 population	40 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Feedlot operations	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Limited agricultural operations	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Large parking lot	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Small parking lot	100 m	<input type="text"/>	<input checked="" type="checkbox"/>
Tree line	50 m	20 - 30 m	<input type="checkbox"/>
Obstacles to wind	10 times obstacle height	<input type="text"/>	<input checked="" type="checkbox"/>

Siting Distances OK

Siting Criteria Comment



# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID

Technician

Site Visit Date

- |    |  |                                     |     |
|----|--|-------------------------------------|-----|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> | N/A |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> | N/A |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> | N/A |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |     |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |     |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> | N/A |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> | N/A |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> | N/A |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> | N/A |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> | N/A |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | N/A |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

Technician

Site Visit Date

1	Do all the meteorological sensors appear to be intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	Temperature only
2	Are all the meteorological sensors operational online, and reporting data?	<input checked="" type="checkbox"/>	Temperature only
3	Are the shields for the temperature and RH sensors clean?	<input checked="" type="checkbox"/>	
4	Are the aspirated motors working?	<input checked="" type="checkbox"/>	
5	Is the solar radiation sensor's lens clean and free of scratches?	<input checked="" type="checkbox"/>	N/A
6	Is the surface wetness sensor grid clean and undamaged?	<input checked="" type="checkbox"/>	N/A
7	Are the sensor signal and power cables intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	
8	Are the sensor signal and power cable connections protected from the elements and well maintained?	<input checked="" type="checkbox"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID

Technician

Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- 1 Do the sample inlets have at least a 270 degree arc of unrestricted airflow?
- 2 Are the sample inlets 3 - 15 meters above the ground?
- 3 Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees?


**Pollutant analyzers and deposition equipment operations and maintenance**

- 1 Do the analyzers and equipment appear to be in good condition and well maintained?
- 2 Are the analyzers and monitors operational, on-line, and reporting data?
- 3 Describe ozone sample tube.
- 4 Describe dry dep sample tube.
- 5 Are in-line filters used in the ozone sample line? (if yes indicate location)
- 6 Are sample lines clean, free of kinks, moisture, and obstructions?
- 7 Is the zero air supply desiccant unsaturated?
- 8 Are there moisture traps in the sample lines?
- 9 Is there a rotometer in the dry deposition filter line, and is it clean?

1/4 teflon by 12 meters
3/8 teflon by 12 meters
At inlet only
Clean and dry

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

--

# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

- |                                     |  |  |                      |  |          |                                     |  |                                     |                      |
|-------------------------------------|--|--|----------------------|--|----------|-------------------------------------|--|-------------------------------------|----------------------|
| 1                                   | Do the DAS instruments appear to be in good condition and well maintained?           | <input checked="" type="checkbox"/>  | <input type="text"/> |  |          |                                     |  |                                     |                      |
| 2                                   | Are all the components of the DAS operational? (printers, modem, backup, etc)        | <input checked="" type="checkbox"/>  | <input type="text"/> |  |          |                                     |  |                                     |                      |
| 3                                   | Do the analyzer and sensor signal leads pass through lightning protection circuitry? | <input checked="" type="checkbox"/>  | <input type="text"/> |  |          |                                     |  |                                     |                      |
| 4                                   | Are the signal connections protected from the weather and well maintained?           | <input checked="" type="checkbox"/>  | <input type="text"/> |  |          |                                     |  |                                     |                      |
| 5                                   | Are the signal leads connected to the correct DAS channel?                           | <input checked="" type="checkbox"/>  | <input type="text"/> |  |          |                                     |  |                                     |                      |
| 6                                   | Are the DAS, sensor translators, and shelter properly grounded?                      | <input checked="" type="checkbox"/>  | <input type="text"/> |  |          |                                     |  |                                     |                      |
| 7                                   | Does the instrument shelter have a stable power source?                              | <input checked="" type="checkbox"/>  | <input type="text"/> |  |          |                                     |  |                                     |                      |
| 8                                   | Is the instrument shelter temperature controlled?                                    | <input checked="" type="checkbox"/>  | <input type="text"/> |  |          |                                     |  |                                     |                      |
| 9                                   | Is the met tower stable and grounded?  | <table border="1"><tr><td>Stable</td><td></td><td>Grounded</td></tr><tr><td><input checked="" type="checkbox"/></td><td></td><td><input checked="" type="checkbox"/></td></tr></table> | Stable               |  | Grounded | <input checked="" type="checkbox"/> |  | <input checked="" type="checkbox"/> | <input type="text"/> |
| Stable                              |  | Grounded   |                      |  |          |                                     |  |                                     |                      |
| <input checked="" type="checkbox"/> |  | <input checked="" type="checkbox"/>  |                      |  |          |                                     |  |                                     |                      |
| 10                                  | Is the sample tower stable and grounded?   | <table border="1"><tr><td>Stable</td><td></td><td>Grounded</td></tr><tr><td><input checked="" type="checkbox"/></td><td></td><td><input checked="" type="checkbox"/></td></tr></table> | Stable               |  | Grounded | <input checked="" type="checkbox"/> |  | <input checked="" type="checkbox"/> | <input type="text"/> |
| Stable                              |  | Grounded   |                      |  |          |                                     |  |                                     |                      |
| <input checked="" type="checkbox"/> |  | <input checked="" type="checkbox"/>  |                      |  |          |                                     |  |                                     |                      |
| 11                                  | Tower comments?  |  | <input type="text"/> |  |          |                                     |  |                                     |                      |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Computer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Solar radiation sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Modem	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Printer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	UPS	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Ozone analyzer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack flow controller	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text" value="Dataview"/>	<input checked="" type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
HASP	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Field Ops Manual	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Calibration Reports	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Ozone z/s/p Control Charts	<input checked="" type="checkbox"/>	<input type="text" value="Dataview"/>	<input checked="" type="checkbox"/>
Preventive maintenance schedul	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>

- 1 Is the station log properly completed during every site visit?
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID

Technician

Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="Monthly"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Monthly"/>	<input checked="" type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Alarm values only"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Quarterly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Zero Air Desiccant Check	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID

Technician

Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed various times
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	One set of gloves only
9	Are the site conditions reported regularly to the field operations manager or staff?	<input type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> As needed	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> As needed	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

The site operator uses one gloved hand, and the same glove, to remove and install the filter pack. Leak checks are performed when the ambient temperature is above -10 C.

# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID

Technician

Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
Computer	Hewlett Packard	ProBook	5CB22906R7	none
DAS	Environmental Sys Corp	8816	2274	90600
Elevation	Elevation	1	None	None
Filter pack flow pump	Thomas	107CAB18B	099800009739	none
Flow Rate	Tylan	FC280SAV	AW9706011	90966
Infrastructure	Infrastructure	none	none	none
Mainframe	Climatronics	100081	1293	none
Mainframe power supply	Climatronics	101074	685	none
Met tower	Glen Martin Engineering	unknown	none	none
MFC power supply	Tylan	RO-32	FP9706004	90967
Modem	US Robotics	33.6 fax modem	unknown	none
Ozone	ThermoElectron Inc	49C	49C-77033-384	90778
Ozone Standard	ThermoElectron Inc	49C	49C-71310-368	none
Printer	Hewlett Packard	840C	unknown	none
Sample Tower	Aluma Tower	B	AT-71102-7I-5	none
Shelter Temperature	ARS	none	006	none
Siting Criteria	Siting Criteria	1	None	None
Temperature2meter	RM Young	41342	018533	none
Zero air pump	Werther International	PC70/4	526281	none



## *Site Inventory by Site Visit*

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>	
<i>SAL133-Sandy Grenville-07/19/2016</i>						
1	7/19/2016	Computer	Dell	07014	Inspiron 15	OF3WC8
2	7/19/2016	DAS	Campbell	000351	CR3000	2129
3	7/19/2016	Elevation	Elevation	None	1	None
4	7/19/2016	Filter pack flow pump	Thomas	00765	107CA110	0000141
5	7/19/2016	Flow Rate	Apex	000599	AXMC105LPMDPCV	illegible
6	7/19/2016	Infrastructure	Infrastructure	none	none	none
7	7/19/2016	Met tower	Universal Tower	03558	unknown	none
8	7/19/2016	Modem	Raven	06612	H4223-C	0844355815
9	7/19/2016	Ozone	ThermoElectron Inc	000741	49i A1NAA	1105347316
10	7/19/2016	Ozone Standard	ThermoElectron Inc	000370	49i A3NAA	0726124689
11	7/19/2016	Sample Tower	Aluma Tower	none	B	AT-51065-5-G-A
12	7/19/2016	Shelter Temperature	Campbell	none	107-L	none
13	7/19/2016	Siting Criteria	Siting Criteria	None	1	None
14	7/19/2016	Temperature	RM Young	06410	41342	14043
15	7/19/2016	Zero air pump	Werther International	06935	C 70/4	000829172

# DAS Data Form

DAS Time Max Error:

<b>Mfg</b>	<b>Serial Number</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Use Desc.</b>
Campbell	2129	SAL133	Sandy Grenville	07/19/2016	DAS	Primary

<b>Das Date:</b>	<input type="text" value="7 /19/2016"/>	<b>Audit Date</b>	<input type="text" value="7 /19/2016"/>
<b>Das Time:</b>	<input type="text" value="18:51:00"/>	<b>Audit Time</b>	<input type="text" value="18:51:00"/>
<b>Das Day:</b>	<input type="text" value="201"/>	<b>Audit Day</b>	<input type="text" value="201"/>
<b>Low Channel:</b>		<b>High Channel:</b>	
<b>Avg Diff:</b>	<input type="text" value="0.0001"/>	<b>Max Diff:</b>	<input type="text" value="0.0001"/>
		<b>Avg Diff:</b>	<input type="text" value="0.0001"/>
		<b>Max Diff:</b>	<input type="text" value="0.0001"/>

<b>Mfg</b>	<input type="text" value="Datel"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="15510194"/>	<b>Tfer Desc.</b>	<input type="text" value="Source generator (D"/>
<b>Tfer ID</b>	<input type="text" value="01320"/>		
<b>Mfg</b>	<input type="text" value="Fluke"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="95740135"/>	<b>Tfer Desc.</b>	<input type="text" value="DVM"/>
<b>Tfer ID</b>	<input type="text" value="01311"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="12/23/2015"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
7	0.0000	0.0000	0.0000	V	V	0.0000
7	0.1000	0.0999	0.0999	V	V	0.0000
7	0.3000	0.2998	0.2997	V	V	-0.0001
7	0.5000	0.4996	0.4996	V	V	0.0000
7	0.7000	0.6996	0.6995	V	V	-0.0001
7	0.9000	0.8994	0.8993	V	V	-0.0001
7	1.0000	0.9993	0.9992	V	V	-0.0001

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Apex	illegible		SAL133	Sandy Grenville	07/19/2016	Flow Rate	000599

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	103471	<b>Tfer Desc.</b>	nexus
<b>Tfer ID</b>	01420		
<b>Slope</b>	0.99091	<b>Intercept</b>	0.03172
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	0.99988
<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	103424	<b>Tfer Desc.</b>	BIOS cell
<b>Tfer ID</b>	01410		
<b>Slope</b>	0.99091	<b>Intercept</b>	0.03172
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	0.99988

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
1.75%	1.96%
<b>A Avg %Dif</b>	<b>A Max % Di</b>

<b>Cal Factor Zero</b>	0
<b>Cal Factor Full Scale</b>	0
<b>Rotometer Reading:</b>	0

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignal	PctDifference
primary	pump off	0.000	0.000	0.02	0.000	-0.03	l/m	l/m	
primary	leak check	0.000	0.000	0.01	0.000	-0.04	l/m	l/m	
primary	test pt 1	1.542	1.520	1.55	0.000	1.50	l/m	l/m	-1.32%
primary	test pt 2	1.545	1.530	1.55	0.000	1.50	l/m	l/m	-1.96%
primary	test pt 3	1.545	1.530	1.55	0.000	1.50	l/m	l/m	-1.96%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	No moisture present	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	2.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	2.3 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	180 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1105347316		SAL133	Sandy Grenville	07/19/2016	Ozone	000741

<b>Slope:</b>	0.98516	<b>Slope:</b>	0.00000
<b>Intercept</b>	0.28944	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99998	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
0.7%	1.5%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0419606966	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01112		
<b>Slope</b>	0.99524	<b>Intercept</b>	-0.33070
<b>Cert Date</b>	1/28/2016	<b>CorrCoff</b>	1.00000

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	0.01	0.34	0.32	ppb	
primary	2	30.02	30.49	30.47	ppb	-0.07%
primary	3	50.04	50.61	50.43	ppb	-0.36%
primary	4	80.13	80.84	80.10	ppb	-0.92%
primary	5	110.30	111.15	109.50	ppb	-1.48%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.10	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.020	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	114.7 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.8 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.68 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	732.7 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	38.6 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	96.5 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.55 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	732.4 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Temperature Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	14043		SAL133	Sandy Grenville	07/19/2016	Temperature	06410

<b>Mfg</b>	Extech	<b>Parameter</b>	Temperature
<b>Serial Number</b>	H232734	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01227		
<b>Slope</b>	1.00772	<b>Intercept</b>	0.12514
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>		<b>DAS 2:</b>	
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>
0.10	0.16		

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Range	0.18	0.05	0.000	0.2	C	0.16
primary	Temp Mid Range	25.15	24.83	0.000	24.9	C	0.04
primary	Temp High Range	47.84	47.35	0.000	47.3	C	-0.09

<b>Sensor Component</b>	Shield	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Campbell	none	SAL133	Sandy Grenville	07/19/2016	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
0.46	0.79		

<b>Mfg</b>	Extech	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	H232734	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01227		
<b>Slope</b>	1.00772	<b>Intercept</b>	0.12514
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Mid Range	26.21	25.89	0.000	26.7	C	0.79
primary	Temp Mid Range	26.10	25.78	0.000	26.3	C	0.55
primary	Temp Mid Range	28.78	28.44	0.000	28.4	C	-0.04

<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
-------------------------	-------------	------------------	--	---------------	------

## Infrastructure Data For

Site ID  Technician  Site Visit Date

Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text" value="Type B"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Functioning"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="3/8 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>

# Field Systems Comments

**1 Parameter:** SiteOpsProcedures

The ozone inlet filter is replaced and the sample train is leak tested every two weeks.

**2 Parameter:** SitingCriteriaCom

The site is located next to a field usually planted with corn or soy beans.

**3 Parameter:** ShelterCleanNotes

The shelter is in fair condition and there is evidence of a leak in the shelter roof and ants are present. It is clean, neat, and well organized. Only one light is working.



# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)	<input type="text" value="EPA"/>	USGS Map	<input type="text" value="Lagro"/>
Operating Group	<input type="text" value="private"/>	Map Scale	<input type="text"/>
AQS #	<input type="text" value="18-169-9991"/>	Map Date	<input type="text"/>
Meteorological Type	<input type="text" value="Climatronics"/>		
Air Pollutant Analyzer	<input type="text" value="Ozone"/>	QAPP Latitude	<input type="text"/>
Deposition Measurement	<input type="text" value="dry"/>	QAPP Longitude	<input type="text"/>
Land Use	<input type="text" value="agriculture"/>	QAPP Elevation Meters	<input type="text"/>
Terrain	<input type="text" value="flat"/>	QAPP Declination	<input type="text"/>
Conforms to MLM	<input type="text" value="Yes"/>	QAPP Declination Date	<input type="text"/>
Site Telephone	<input type="text" value="(260) 782-2428"/>	Audit Latitude	<input type="text" value="40.816038"/>
Site Address 1	<input type="text" value="Hamilton Road"/>	Audit Longitude	<input type="text" value="-85.661407"/>
Site Address 2	<input type="text"/>	Audit Elevation	<input type="text" value="250"/>
County	<input type="text" value="Wabash"/>	Audit Declination	<input type="text" value="-5"/>
City, State	<input type="text" value="Lagro, IN"/>		
Zip Code	<input type="text" value="46941"/>	<b>Present</b>	
Time Zone	<input type="text" value="Eastern"/>	Fire Extinguisher <input checked="" type="checkbox"/>	<input type="text" value="New in 2015"/>
Primary Operator	<input type="text"/>	First Aid Kit <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. Phone #	<input type="text"/>	Safety Glasses <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. E-mail	<input type="text"/>	Safety Hard Hat <input type="checkbox"/>	<input type="text"/>
Backup Operator	<input type="text"/>	Climbing Belt <input checked="" type="checkbox"/>	<input type="text"/>
Backup Op. Phone #	<input type="text"/>	Security Fence <input type="checkbox"/>	<input type="text"/>
Backup Op. E-mail	<input type="text"/>	Secure Shelter <input checked="" type="checkbox"/>	<input type="text"/>
		Stable Entry Step <input checked="" type="checkbox"/>	<input type="text"/>

Shelter Working Room  Make  Model  Shelter Size

Shelter Clean  Notes

Site OK  Notes

Driving Directions

# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID  Technician  Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km	<input type="text"/>	<input checked="" type="checkbox"/>
City > 50,000 population	40 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Feedlot operations	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m	<input type="text" value="20 m"/>	<input type="checkbox"/>
Limited agricultural operations	200 m	<input type="text" value="20 m"/>	<input type="checkbox"/>
Large parking lot	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Small parking lot	100 m	<input type="text"/>	<input checked="" type="checkbox"/>
Tree line	50 m	<input type="text"/>	<input checked="" type="checkbox"/>
Obstacles to wind	10 times obstacle height	<input type="text"/>	<input checked="" type="checkbox"/>

Siting Distances OK

Siting Criteria Comment

# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID

Technician

Site Visit Date

- |    |  |                                     |     |
|----|--|-------------------------------------|-----|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> | N/A |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> | N/A |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> | N/A |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |     |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |     |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> | N/A |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> | N/A |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> | N/A |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> | N/A |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> | N/A |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | N/A |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

Technician

Site Visit Date

1	Do all the meteorological sensors appear to be intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	Temperature only
2	Are all the meteorological sensors operational online, and reporting data?	<input checked="" type="checkbox"/>	Temperature only
3	Are the shields for the temperature and RH sensors clean?	<input checked="" type="checkbox"/>	
4	Are the aspirated motors working?	<input checked="" type="checkbox"/>	N/A
5	Is the solar radiation sensor's lens clean and free of scratches?	<input checked="" type="checkbox"/>	N/A
6	Is the surface wetness sensor grid clean and undamaged?	<input checked="" type="checkbox"/>	N/A
7	Are the sensor signal and power cables intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	
8	Are the sensor signal and power cable connections protected from the elements and well maintained?	<input checked="" type="checkbox"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID

Technician

Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- |   |   |                                     |  |
|---|---|-------------------------------------|--|
| 1 | Do the sample inlets have at least a 270 degree arc of unrestricted airflow?          | <input checked="" type="checkbox"/> |  |
| 2 | Are the sample inlets 3 - 15 meters above the ground?                                 | <input checked="" type="checkbox"/> |  |
| 3 | Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees? | <input checked="" type="checkbox"/> |  |

**Pollutant analyzers and deposition equipment operations and maintenance**

- |   |  |                                     |                         |
|---|--|-------------------------------------|-------------------------|
| 1 | Do the analyzers and equipment appear to be in good condition and well maintained? | <input checked="" type="checkbox"/> |                         |
| 2 | Are the analyzers and monitors operational, on-line, and reporting data?           | <input checked="" type="checkbox"/> |                         |
| 3 | Describe ozone sample tube.  |                                     | 1/4 teflon by 15 meters |
| 4 | Describe dry dep sample tube.  |                                     | 3/8 teflon by 15 meters |
| 5 | Are in-line filters used in the ozone sample line? (if yes indicate location)      | <input checked="" type="checkbox"/> | At inlet only           |
| 6 | Are sample lines clean, free of kinks, moisture, and obstructions?                 | <input checked="" type="checkbox"/> |                         |
| 7 | Is the zero air supply desiccant unsaturated?                                      | <input checked="" type="checkbox"/> |                         |
| 8 | Are there moisture traps in the sample lines?                                      | <input checked="" type="checkbox"/> | Flow line only          |
| 9 | Is there a rotometer in the dry deposition filter line, and is it clean?           | <input checked="" type="checkbox"/> | Clean and dry           |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

- 1 Do the DAS instruments appear to be in good condition and well maintained?
- 2 Are all the components of the DAS operational? (printers, modem, backup, etc)
- 3 Do the analyzer and sensor signal leads pass through lightning protection circuitry?
- 4 Are the signal connections protected from the weather and well maintained?
- 5 Are the signal leads connected to the correct DAS channel?
- 6 Are the DAS, sensor translators, and shelter properly grounded?
- 7 Does the instrument shelter have a stable power source?
- 8 Is the instrument shelter temperature controlled?
- 9 Is the met tower stable and grounded?

<b>Stable</b>	<b>Grounded</b>
<input type="checkbox"/>	<input type="checkbox"/>
<input checked="" type="checkbox"/>	<input type="checkbox"/>
- 10 Is the sample tower stable and grounded?

<b>Stable</b>	<b>Grounded</b>
<input type="checkbox"/>	<input type="checkbox"/>
<input checked="" type="checkbox"/>	<input type="checkbox"/>
- 11 Tower comments?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID  Technician  Site Visit Date

Documentation

Does the site have the required instrument and equipment manuals?

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Computer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Solar radiation sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Modem	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Printer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	UPS	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Ozone analyzer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack flow controller	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>				

Does the site have the required and most recent QC documents and report forms?

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input checked="" type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
HASP	<input checked="" type="checkbox"/>	November 2009	<input type="checkbox"/>
Field Ops Manual	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Calibration Reports	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Preventive maintenance schedul	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>

- 1 Is the station log properly completed during every site visit?
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?  Control charts not used

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

Site ID  Technician  Site Visit Date

Documentation

# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID  Technician  Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Every 2 weeks"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Zero Air Desiccant Check	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

Site ID  Technician  Site Visit Date



# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID  Technician  Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed afternoons
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF, logbook
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF, call-in
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	Clean gloves on and off
9	Are the site conditions reported regularly to the field operations manager or staff?	<input checked="" type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input type="checkbox"/>	<input type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

Site ID  Technician  Site Visit Date

Site operation procedures

# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID

Technician

Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
Computer	Dell	Inspiron 15	OF3WC8	07014
DAS	Campbell	CR3000	2129	000351
Elevation	Elevation	1	None	None
Filter pack flow pump	Thomas	107CA110	0000141	00765
Flow Rate	Apex	AXMC105LPMDPC	illegible	000599
Infrastructure	Infrastructure	none	none	none
Met tower	Universal Tower	unknown	none	03558
Modem	Raven	H4223-C	0844355815	06612
Ozone	ThermoElectron Inc	49i A1NAA	1105347316	000741
Ozone Standard	ThermoElectron Inc	49i A3NAA	0726124689	000370
Sample Tower	Aluma Tower	B	AT-51065-5-G-A	none
Shelter Temperature	Campbell	107-L	none	none
Siting Criteria	Siting Criteria	1	None	None
Temperature	RM Young	41342	14043	06410
Zero air pump	Werther International	C 70/4	000829172	06935

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

### *MKG113-Sandy Grenville-08/15/2016*

1	8/15/2016	Computer	Dell	07030	Inspiron 15	Unknown
2	8/15/2016	DAS	Campbell	000404	CR3000	2521
3	8/15/2016	Elevation	Elevation	None	1	None
4	8/15/2016	Filter pack flow pump	Thomas	03639	107CAB18	049400004427
5	8/15/2016	Flow Rate	Apex	000637	AXMC105LPMDPCV	illegible
6	8/15/2016	Infrastructure	Infrastructure	none	none	none
7	8/15/2016	Modem	Raven	06593	V4221-V	0844350394
8	8/15/2016	Ozone	ThermoElectron Inc	000703	49i A1NAA	1030244805
9	8/15/2016	Ozone Standard	ThermoElectron Inc	000374	49i A3NAA	0726124694
10	8/15/2016	Sample Tower	Aluma Tower	666362	B	AT-5107-E-4-11
11	8/15/2016	Shelter Temperature	Campbell	none	107-L	none
12	8/15/2016	Siting Criteria	Siting Criteria	None	1	None
13	8/15/2016	Temperature	RM Young	04313	41342	4010
14	8/15/2016	Zero air pump	Werther International	06937	C 70/4	000821896

# DAS Data Form

DAS Time Max Error:

<b>Mfg</b>	<b>Serial Number</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Use Desc.</b>
Campbell	2521	MKG113	Sandy Grenville	08/15/2016	DAS	Primary

<b>Das Date:</b>	<input type="text" value="8 /15/2016"/>	<b>Audit Date</b>	<input type="text" value="8 /15/2016"/>
<b>Das Time:</b>	<input type="text" value="17:30:10"/>	<b>Audit Time</b>	<input type="text" value="17:30:10"/>
<b>Das Day:</b>	<input type="text" value="228"/>	<b>Audit Day</b>	<input type="text" value="228"/>
<b>Low Channel:</b>		<b>High Channel:</b>	
<b>Avg Diff:</b>	<input type="text" value="0.0001"/>	<b>Max Diff:</b>	<input type="text" value="0.0002"/>
		<b>Avg Diff:</b>	<input type="text" value="0.0001"/>
		<b>Max Diff:</b>	<input type="text" value="0.0002"/>

<b>Mfg</b>	<input type="text" value="Datel"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="15510194"/>	<b>Tfer Desc.</b>	<input type="text" value="Source generator (D"/>
<b>Tfer ID</b>	<input type="text" value="01320"/>		
<b>Mfg</b>	<input type="text" value="Fluke"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="95740135"/>	<b>Tfer Desc.</b>	<input type="text" value="DVM"/>
<b>Tfer ID</b>	<input type="text" value="01311"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="12/23/2015"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
7	0.0000	0.0000	0.0000	V	V	0.0000
7	0.1000	0.0999	0.0999	V	V	0.0000
7	0.3000	0.2997	0.2997	V	V	0.0000
7	0.5000	0.4996	0.4996	V	V	0.0000
7	0.7000	0.6996	0.6995	V	V	-0.0001
7	0.9000	0.8994	0.8993	V	V	-0.0001
7	1.0000	0.9993	0.9991	V	V	-0.0002

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Apex	illegible		MKG113	Sandy Grenville	08/15/2016	Flow Rate	000637

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	103471	<b>Tfer Desc.</b>	nexus
<b>Tfer ID</b>	01420		
<b>Slope</b>	0.99091	<b>Intercept</b>	0.03172
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	0.99988
<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	103424	<b>Tfer Desc.</b>	BIOS cell
<b>Tfer ID</b>	01410		
<b>Slope</b>	0.99091	<b>Intercept</b>	0.03172
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	0.99988

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
0.22%	0.67%
<b>A Avg %Dif</b>	<b>A Max % Di</b>

<b>Cal Factor Zero</b>	0
<b>Cal Factor Full Scale</b>	1.001
<b>Rotometer Reading:</b>	1.6

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignal	PctDifference
primary	pump off	0.000	0.000	-0.09	0.000	-0.01	l/m	l/m	
primary	leak check	0.000	0.000	0.00	0.000	0.01	l/m	l/m	
primary	test pt 1	1.514	1.500	1.50	0.000	1.51	l/m	l/m	0.67%
primary	test pt 2	1.516	1.500	1.50	0.000	1.50	l/m	l/m	0.00%
primary	test pt 3	1.516	1.500	1.50	0.000	1.50	l/m	l/m	0.00%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	No moisture present	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	3.0 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	2.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	180 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1030244805		MKG113	Sandy Grenville	08/15/2016	Ozone	000703

<b>Slope:</b>	1.00272	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.79901	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99998	<b>CorrCoff</b>	0.00000

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0419606966	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01112		
<b>Slope</b>	0.99524	<b>Intercept</b>	-0.33070
<b>Cert Date</b>	1/28/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
1.0%	2.0%		

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	0.02	0.35	-0.73	ppb	
primary	2	30.02	30.49	29.87	ppb	-2.03%
primary	3	50.06	50.63	50.24	ppb	-0.77%
primary	4	80.33	81.04	80.70	ppb	-0.42%
primary	5	110.07	110.92	110.10	ppb	-0.74%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.10	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.010	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	93.8 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.9 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.74 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	705.5 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	38.0 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	88.4 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	1.0 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	1.01 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	705.5 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Temperature Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	4010		MKG113	Sandy Grenville	08/15/2016	Temperature	04313

<b>Mfg</b>	Extech	<b>Parameter</b>	Temperature
<b>Serial Number</b>	H232734	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01227		
<b>Slope</b>	1.00772	<b>Intercept</b>	0.12514
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>		<b>DAS 2:</b>	
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>
0.04	0.06		

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Range	0.19	0.06	0.000	0.1	C	0.04
primary	Temp Mid Range	25.12	24.80	0.000	24.8	C	0.01
primary	Temp High Range	48.00	47.51	0.000	47.5	C	-0.06

<b>Sensor Component</b>	Shield	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Campbell	none	MKG113	Sandy Grenville	08/15/2016	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
0.07	0.13		

<b>Mfg</b>	Extech	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	H232734	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01227		
<b>Slope</b>	1.00772	<b>Intercept</b>	0.12514
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Mid Range	28.32	27.98	0.000	28.0	C	0.03
primary	Temp Mid Range	27.77	27.43	0.000	27.3	C	-0.13
primary	Temp Mid Range	27.94	27.60	0.000	27.6	C	0.04

<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
-------------------------	-------------	------------------	--	---------------	------



## Infrastructure Data For

Site ID  Technician  Site Visit Date

Shelter Make	Shelter Model	Shelter Size
<input type="text" value="Ekto"/>	<input type="text" value="8810 (s/n 2116-4)"/>	<input type="text" value="640 cuft"/>

Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text" value="Type B"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Functioning"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="3/8 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>

# Field Systems Comments

1 **Parameter:** DasComments

The Met tower has been removed and the temperature sensor is now mounted on the sample tower in a naturally aspirated shield.

2 **Parameter:** ShelterCleanNotes

The shelter is clean and organized. Leak and rot below the air conditioner and on the floor under the counter. Mold beginning on walls and floor.

# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)	<input type="text" value="EPA"/>	USGS Map	<input type="text" value="Hadley"/>
Operating Group	<input type="text" value="PA/private"/>	Map Scale	<input type="text"/>
AQS #	<input type="text" value="42-085-9991"/>	Map Date	<input type="text"/>
Meteorological Type	<input type="text" value="Climatronics"/>		
Air Pollutant Analyzer	<input type="text" value="Ozone, IMPROVE"/>	QAPP Latitude	<input type="text" value="41.4250"/>
Deposition Measurement	<input type="text" value="dry"/>	QAPP Longitude	<input type="text" value="-80.1447"/>
Land Use	<input type="text" value="woodland - mixed, agriculture"/>	QAPP Elevation Meters	<input type="text" value="384"/>
Terrain	<input type="text" value="gently rolling"/>	QAPP Declination	<input type="text" value="9.25"/>
Conforms to MLM	<input type="text" value="Marginally"/>	QAPP Declination Date	<input type="text" value="2/22/2006"/>
Site Telephone	<input type="text" value="(724) 253-3685"/>	Audit Latitude	<input type="text" value="41.426847"/>
Site Address 1	<input type="text" value="M. K. Goddard St. Park"/>	Audit Longitude	<input type="text" value="-80.145247"/>
Site Address 2	<input type="text" value="684 Lake Wilhelm Rd."/>	Audit Elevation	<input type="text" value="377"/>
County	<input type="text" value="Mercer"/>	Audit Declination	<input type="text" value="-9.3"/>
City, State	<input type="text" value="Sandy Lake, PA"/>		
Zip Code	<input type="text" value="16145"/>	Fire Extinguisher <input checked="" type="checkbox"/>	<input type="text" value="New in 2014"/>
Time Zone	<input type="text" value="Eastern"/>	First Aid Kit <input checked="" type="checkbox"/>	<input type="text"/>
Primary Operator	<input type="text"/>	Safety Glasses <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. Phone #	<input type="text"/>	Safety Hard Hat <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. E-mail	<input type="text"/>	Climbing Belt <input checked="" type="checkbox"/>	<input type="text"/>
Backup Operator	<input type="text"/>	Security Fence <input type="checkbox"/>	<input type="text"/>
Backup Op. Phone #	<input type="text"/>	Secure Shelter <input checked="" type="checkbox"/>	<input type="text"/>
Backup Op. E-mail	<input type="text"/>	Stable Entry Step <input checked="" type="checkbox"/>	<input type="text"/>
Shelter Working Room <input checked="" type="checkbox"/>	Make <input type="text" value="Ekto"/>	Model <input type="text" value="8810 (s/n 2116-4)"/>	Shelter Size <input type="text" value="640 cuft"/>
Shelter Clean <input checked="" type="checkbox"/>	Notes	<input type="text" value="The shelter is clean and organized. Leak and rot below the air conditioner and on the floor under the counter. Mold beginning on walls and floor."/>	
Site OK <input checked="" type="checkbox"/>	Notes	<input type="text"/>	
Driving Directions	<input type="text" value="From I-79 take exit 130 (route 358). Go west and bear right onto Sheakleyville Road. Continue less than a mile to the stop sign, and turn right onto Lake Wilhelm Road. Continue approximately 1.5 miles, just after crossing the lake the site will be visible on the right at the state park headquarters facility."/>		

# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID  Technician  Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km		<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km		<input checked="" type="checkbox"/>
City > 50,000 population	40 km		<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km		<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km		<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km	1.5 km	<input type="checkbox"/>
Secondary road, heavily traveled	500 m		<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m		<input checked="" type="checkbox"/>
Feedlot operations	500 m		<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m		<input checked="" type="checkbox"/>
Limited agricultural operations	200 m		<input checked="" type="checkbox"/>
Large parking lot	200 m		<input checked="" type="checkbox"/>
Small parking lot	100 m	60 m	<input type="checkbox"/>
Tree line	50 m	10 - 30 m	<input type="checkbox"/>
Obstacles to wind	10 times obstacle height		<input checked="" type="checkbox"/>

Siting Distances OK

Siting Criteria Comment

# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID

Technician

Site Visit Date

- |    |  |                                     |     |
|----|--|-------------------------------------|-----|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> | N/A |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> | N/A |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> | N/A |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |     |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |     |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> | N/A |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> | N/A |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> | N/A |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> | N/A |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> | N/A |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | N/A |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

Technician

Site Visit Date

1	Do all the meteorological sensors appear to be intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	Temperature only
2	Are all the meteorological sensors operational online, and reporting data?	<input checked="" type="checkbox"/>	Temperature only
3	Are the shields for the temperature and RH sensors clean?	<input checked="" type="checkbox"/>	
4	Are the aspirated motors working?	<input checked="" type="checkbox"/>	N/A
5	Is the solar radiation sensor's lens clean and free of scratches?	<input checked="" type="checkbox"/>	N/A
6	Is the surface wetness sensor grid clean and undamaged?	<input checked="" type="checkbox"/>	N/A
7	Are the sensor signal and power cables intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	
8	Are the sensor signal and power cable connections protected from the elements and well maintained?	<input checked="" type="checkbox"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID

Technician

Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- |   |   |                                     |  |
|---|---|-------------------------------------|--|
| 1 | Do the sample inlets have at least a 270 degree arc of unrestricted airflow?          | <input checked="" type="checkbox"/> |  |
| 2 | Are the sample inlets 3 - 15 meters above the ground?                                 | <input checked="" type="checkbox"/> |  |
| 3 | Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees? | <input type="checkbox"/>            | One tree as tall as inlet within 12 meters |

**Pollutant analyzers and deposition equipment operations and maintenance**

- |   |  |                                     |                         |
|---|--|-------------------------------------|-------------------------|
| 1 | Do the analyzers and equipment appear to be in good condition and well maintained? | <input checked="" type="checkbox"/> |                         |
| 2 | Are the analyzers and monitors operational, on-line, and reporting data?           | <input checked="" type="checkbox"/> |                         |
| 3 | Describe ozone sample tube.  |                                     | 1/4 teflon by 15 meters |
| 4 | Describe dry dep sample tube.  |                                     | 3/8 teflon by 15 meters |
| 5 | Are in-line filters used in the ozone sample line? (if yes indicate location)      | <input checked="" type="checkbox"/> | At inlet only           |
| 6 | Are sample lines clean, free of kinks, moisture, and obstructions?                 | <input checked="" type="checkbox"/> |                         |
| 7 | Is the zero air supply desiccant unsaturated?                                      | <input checked="" type="checkbox"/> |                         |
| 8 | Are there moisture traps in the sample lines?                                      | <input checked="" type="checkbox"/> | Flow line only          |
| 9 | Is there a rotometer in the dry deposition filter line, and is it clean?           | <input checked="" type="checkbox"/> | Clean and dry           |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

1	Do the DAS instruments appear to be in good condition and well maintained?	<input checked="" type="checkbox"/>							
2	Are all the components of the DAS operational? (printers, modem, backup, etc)	<input checked="" type="checkbox"/>							
3	Do the analyzer and sensor signal leads pass through lightning protection circuitry?	<input checked="" type="checkbox"/>	Met sensors only						
4	Are the signal connections protected from the weather and well maintained?	<input checked="" type="checkbox"/>							
5	Are the signal leads connected to the correct DAS channel?	<input checked="" type="checkbox"/>							
6	Are the DAS, sensor translators, and shelter properly grounded?	<input checked="" type="checkbox"/>							
7	Does the instrument shelter have a stable power source?	<input checked="" type="checkbox"/>							
8	Is the instrument shelter temperature controlled?	<input checked="" type="checkbox"/>							
9	Is the met tower stable and grounded?	<table border="1"><tr><td><b>Stable</b></td><td><b>Grounded</b></td></tr><tr><td><input type="checkbox"/></td><td><input type="checkbox"/></td></tr><tr><td><input checked="" type="checkbox"/></td><td><input checked="" type="checkbox"/></td></tr></table>	<b>Stable</b>	<b>Grounded</b>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
<b>Stable</b>	<b>Grounded</b>								
<input type="checkbox"/>	<input type="checkbox"/>								
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>								
10	Is the sample tower stable and grounded?	<table border="1"><tr><td><b>Stable</b></td><td><b>Grounded</b></td></tr><tr><td><input type="checkbox"/></td><td><input type="checkbox"/></td></tr><tr><td><input checked="" type="checkbox"/></td><td><input checked="" type="checkbox"/></td></tr></table>	<b>Stable</b>	<b>Grounded</b>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
<b>Stable</b>	<b>Grounded</b>								
<input type="checkbox"/>	<input type="checkbox"/>								
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>								
11	Tower comments?		Met tower removed						

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

The Met tower has been removed and the temperature sensor is now mounted on the sample tower in a naturally aspirated shield.



# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Computer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Solar radiation sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Modem	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Printer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	UPS	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Ozone analyzer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack flow controller	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input checked="" type="checkbox"/>	Feb 2014	<input type="checkbox"/>
HASP	<input checked="" type="checkbox"/>	Feb 2014	<input checked="" type="checkbox"/>
Field Ops Manual	<input checked="" type="checkbox"/>	Feb 2014	<input checked="" type="checkbox"/>
Calibration Reports	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Preventive maintenance schedul	<input type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>

- 1 Is the station log properly completed during every site visit?
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?  Control charts not used

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID  Technician  Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="As needed"/>	<input checked="" type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input checked="" type="checkbox"/>	<input type="text" value="As needed"/>	<input checked="" type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Every 2 weeks"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Zero Air Desiccant Check	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID

Technician

Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed various times of day
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF, logbook, call-in
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	Clean gloves on and off
9	Are the site conditions reported regularly to the field operations manager or staff?	<input checked="" type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID  Technician  Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
Computer	Dell	Inspiron 15	Unknown	07030
DAS	Campbell	CR3000	2521	000404
Elevation	Elevation	1	None	None
Filter pack flow pump	Thomas	107CAB18	049400004427	03639
Flow Rate	Apex	AXMC105LPMDPC	illegible	000637
Infrastructure	Infrastructure	none	none	none
Modem	Raven	V4221-V	0844350394	06593
Ozone	ThermoElectron Inc	49i A1NAA	1030244805	000703
Ozone Standard	ThermoElectron Inc	49i A3NAA	0726124694	000374
Sample Tower	Aluma Tower	B	AT-5107-E-4-11	666362
Shelter Temperature	Campbell	107-L	none	none
Siting Criteria	Siting Criteria	1	None	None
Temperature	RM Young	41342	4010	04313
Zero air pump	Werther International	C 70/4	000821896	06937

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

### *ANA115-Eric Hebert-08/15/2016*

1	8/15/2016	Computer	Dell	07017	Inspiron 15	Unknown
2	8/15/2016	DAS	Campbell	000338	CR3000	2117
3	8/15/2016	Elevation	Elevation	None	1	None
4	8/15/2016	Filter pack flow pump	Thomas	06025	107CAB18	060400022682
5	8/15/2016	Flow Rate	Apex	000809	AXMC105LPMDPCV	illegible
6	8/15/2016	Infrastructure	Infrastructure	none	none	none
7	8/15/2016	Modem	Raven	06588	V4221-V	0844352818
8	8/15/2016	Ozone	ThermoElectron Inc	000702	49i A1NAA	1030244799
9	8/15/2016	Ozone Standard	ThermoElectron Inc	000364	49i A3NAA	0726124687
10	8/15/2016	Sample Tower	Aluma Tower	000180	B	none
11	8/15/2016	Shelter Temperature	Campbell	none	107-L	none
12	8/15/2016	Siting Criteria	Siting Criteria	None	1	None
13	8/15/2016	Temperature	RM Young	06535	41342	14796
14	8/15/2016	Zero air pump	Werther International	06933	C 70/4	000836202

# DAS Data Form

DAS Time Max Error:

<b>Mfg</b>	<b>Serial Number</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Use Desc.</b>
Campbell	2117	ANA115	Eric Hebert	08/15/2016	DAS	Primary

<b>Das Date:</b>	<input type="text" value="8 /15/2016"/>	<b>Audit Date</b>	<input type="text" value="8 /15/2016"/>
<b>Das Time:</b>	<input type="text" value="10:12:00"/>	<b>Audit Time</b>	<input type="text" value="10:12:00"/>
<b>Das Day:</b>	<input type="text" value="227"/>	<b>Audit Day</b>	<input type="text" value="227"/>
<b>Low Channel:</b>		<b>High Channel:</b>	
<b>Avg Diff:</b>	<input type="text" value="0.0001"/>	<b>Max Diff:</b>	<input type="text" value="0.0001"/>
		<b>Avg Diff:</b>	<input type="text" value="0.0001"/>
		<b>Max Diff:</b>	<input type="text" value="0.0001"/>

<b>Mfg</b>	<input type="text" value="Datel"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="4000392"/>	<b>Tfer Desc.</b>	<input type="text" value="Source generator (D"/>
<b>Tfer ID</b>	<input type="text" value="01321"/>		
<b>Mfg</b>	<input type="text" value="Fluke"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="86590148"/>	<b>Tfer Desc.</b>	<input type="text" value="DVM"/>
<b>Tfer ID</b>	<input type="text" value="01310"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="12/23/2015"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
7	0.0000	0.0000	0.0000	V	V	0.0000
7	0.1000	0.1000	0.0999	V	V	-0.0001
7	0.3000	0.3000	0.2999	V	V	-0.0001
7	0.5000	0.4999	0.4999	V	V	0.0000
7	0.7000	0.6999	0.6998	V	V	-0.0001
7	0.9000	0.8999	0.8998	V	V	-0.0001
7	1.0000	0.9998	0.9998	V	V	0.0000

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Apex	illegible		ANA115	Eric Hebert	08/15/2016	Flow Rate	000809

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	148613	<b>Tfer Desc.</b>	BIOS 220-H
<b>Tfer ID</b>	01421		
<b>Slope</b>	1.00309	<b>Intercept</b>	-0.00231
<b>Cert Date</b>	4/21/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
0.45%	0.67%

<b>Cal Factor Zero</b>	-0.03
<b>Cal Factor Full Scale</b>	0.99
<b>Rotometer Reading:</b>	1.5

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignal	PctDifference
primary	pump off	0.000	0.000	0.00	0.000	-0.02	l/m	l/m	
primary	leak check	0.000	0.000	0.01	0.000	-0.01	l/m	l/m	
primary	test pt 1	1.490	1.490	1.51	0.000	1.50	l/m	l/m	0.67%
primary	test pt 2	1.491	1.490	1.51	0.000	1.50	l/m	l/m	0.67%
primary	test pt 3	1.498	1.500	1.51	0.000	1.50	l/m	l/m	0.00%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	See comments	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	5.0 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	1.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	225 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1030244799		ANA115	Eric Hebert	08/15/2016	Ozone	000702

<b>Slope:</b>	0.99502	<b>Slope:</b>	0.00000
<b>Intercept</b>	0.55491	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	1.00000	<b>CorrCoff</b>	0.00000

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0517112167	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01113		
<b>Slope</b>	1.00500	<b>Intercept</b>	-0.28841
<b>Cert Date</b>	1/28/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
0.6%	1.3%		

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	-0.23	0.05	0.60	ppb	
primary	2	27.89	28.03	28.38	ppb	1.25%
primary	3	49.89	49.92	50.29	ppb	0.74%
primary	4	79.82	79.70	79.94	ppb	0.30%
primary	5	104.68	104.44	104.40	ppb	-0.04%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.10	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.003	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	89.7 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.71 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	712.5 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	37.7 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	102.9 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.8 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.68 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	712.2 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass



# Temperature Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	14796		ANA115	Eric Hebert	08/15/2016	Temperature	06535

<b>Mfg</b>	Extech	<b>Parameter</b>	Temperature
<b>Serial Number</b>	H232679	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01228		
<b>Slope</b>	1.00760	<b>Intercept</b>	-0.05710
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>
0.08	0.12		

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Range	0.11	0.17	0.000	0.2	C	0.06
primary	Temp Mid Range	25.74	25.60	0.000	25.7	C	0.05
primary	Temp High Range	50.10	49.78	0.000	49.9	C	0.12

<b>Sensor Component</b>	Shield	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Campbell	none	ANA115	Eric Hebert	08/15/2016	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
0.75	1.11		

<b>Mfg</b>	Extech	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	H232679	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01228		
<b>Slope</b>	1.00760	<b>Intercept</b>	-0.05710
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Mid Range	24.28	24.15	0.000	24.8	C	0.61
primary	Temp Mid Range	28.65	28.49	0.000	28.0	C	-0.54
primary	Temp Mid Range	25.80	25.66	0.000	26.8	C	1.11

<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
-------------------------	-------------	------------------	--	---------------	------

## Infrastructure Data For

Site ID  Technician  Site Visit Date

Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text" value="Type B"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Functioning"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="3/8 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>

# Site Visit Comments

<b>Parameter</b>	<b>Site</b>	<b>Technician</b>	<b>S.V. Date</b>	<b>Component</b>	<b>Mfg</b>	<b>Serial No.</b>	<b>Hazard</b>	<b>Problem</b>
Flow Rate	ANA115	Eric Hebert	08/15/2016	Moisture Present	Apex	3990	<input type="checkbox"/>	<input type="checkbox"/>
The filter sample tubing has drops of moisture in low sections outside the shelter.								

# Field Systems Comments

**1 Parameter:** DasComments

The met tower has been removed. The DAS controls the shelter heating and cooling.

**2 Parameter:** SitingCriteriaCom

Site is confined within a fenced area that is somewhat small. There is available space adjacent to the fenced area that could be utilized to improve the instrument siting.

**3 Parameter:** ShelterCleanNotes

The shelter is in fair condition, however somewhat cluttered.

**4 Parameter:** PollAnalyzerCom

Moisture is present in the flow tubing outside of the shelter.

# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)	<input type="text" value="EPA"/>	USGS Map	<input type="text" value="Pinckney"/>
Operating Group	<input type="text" value="University of MI"/>	Map Scale	<input type="text"/>
AQS #	<input type="text" value="26-161-9991"/>	Map Date	<input type="text"/>
Meteorological Type	<input type="text" value="Climatronics"/>		
Air Pollutant Analyzer	<input type="text" value="Ozone"/>	QAPP Latitude	<input type="text"/>
Deposition Measurement	<input type="text" value="dry, wet, Hg"/>	QAPP Longitude	<input type="text"/>
Land Use	<input type="text" value="woodland - mixed"/>	QAPP Elevation Meters	<input type="text"/>
Terrain	<input type="text" value="flat"/>	QAPP Declination	<input type="text"/>
Conforms to MLM	<input type="text" value="Marginally"/>	QAPP Declination Date	<input type="text"/>
Site Telephone	<input type="text" value="(734) 426-0060"/>	Audit Latitude	<input type="text" value="42.416636"/>
Site Address 1	<input type="text" value="8420 Strawberry Lake Rd."/>	Audit Longitude	<input type="text" value="-83.90218"/>
Site Address 2	<input type="text"/>	Audit Elevation	<input type="text" value="266"/>
County	<input type="text" value="Washtenaw"/>	Audit Declination	<input type="text" value="-6.6"/>
City, State	<input type="text" value="Dexter, MI"/>		
Zip Code	<input type="text" value="48130"/>	<b>Present</b>	
Time Zone	<input type="text" value="Eastern"/>	Fire Extinguisher <input checked="" type="checkbox"/>	<input type="text" value="New in 2015"/>
Primary Operator	<input type="text"/>	First Aid Kit <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. Phone #	<input type="text"/>	Safety Glasses <input type="checkbox"/>	<input type="text"/>
Primary Op. E-mail	<input type="text"/>	Safety Hard Hat <input checked="" type="checkbox"/>	<input type="text"/>
Backup Operator	<input type="text"/>	Climbing Belt <input type="checkbox"/>	<input type="text"/>
Backup Op. Phone #	<input type="text"/>	Security Fence <input checked="" type="checkbox"/>	<input type="text"/>
Backup Op. E-mail	<input type="text"/>	Secure Shelter <input checked="" type="checkbox"/>	<input type="text"/>
		Stable Entry Step <input checked="" type="checkbox"/>	<input type="text"/>
Shelter Working Room <input checked="" type="checkbox"/>	Make <input type="text" value="Ekto"/>	Model <input type="text" value="8810"/>	Shelter Size <input type="text" value="640 cuft"/>
Shelter Clean <input checked="" type="checkbox"/>	Notes	<input type="text" value="The shelter is in fair condition, however somewhat cluttered."/>	
Site OK <input checked="" type="checkbox"/>	Notes	<input type="text"/>	

**Driving Directions** From Ann Arbor take I-94 west to exit 169 to Dexter, turning right (north) to Dexter. Continue a few miles to the stop sign and turn left. Continue approximately one block to the small park in the center of town and turn right (north). Continue through Dexter, across the railroad tracks and river. Turn left (west) just across the river on Huron River Drive. Continue about 8 miles on Huron River Drive which becomes a dirt road after the intersection of North Territorial Rd. The site is on the left, just past the first sharp turn in the road (to the right) where it becomes Strawberry Lake Road.

# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID  Technician  Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km	<input type="text"/>	<input checked="" type="checkbox"/>
City > 50,000 population	40 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Feedlot operations	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Limited agricultural operations	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Large parking lot	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Small parking lot	100 m	<input type="text"/>	<input checked="" type="checkbox"/>
Tree line	50 m	<input type="text"/>	<input checked="" type="checkbox"/>
Obstacles to wind	10 times obstacle height	<input type="text"/>	<input checked="" type="checkbox"/>

Siting Distances OK

**Siting Criteria Comment**

# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID

Technician

Site Visit Date

- |    |  |                                     |     |
|----|--|-------------------------------------|-----|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> | N/A |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> | N/A |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> | N/A |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |     |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |     |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> | N/A |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> | N/A |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> | N/A |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> | N/A |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> | N/A |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | N/A |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:



# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

Technician

Site Visit Date

1	Do all the meteorological sensors appear to be intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	Temperature only
2	Are all the meteorological sensors operational online, and reporting data?	<input checked="" type="checkbox"/>	Temperature only
3	Are the shields for the temperature and RH sensors clean?	<input checked="" type="checkbox"/>	
4	Are the aspirated motors working?	<input type="checkbox"/>	N/A
5	Is the solar radiation sensor's lens clean and free of scratches?	<input checked="" type="checkbox"/>	N/A
6	Is the surface wetness sensor grid clean and undamaged?	<input checked="" type="checkbox"/>	N/A
7	Are the sensor signal and power cables intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	
8	Are the sensor signal and power cable connections protected from the elements and well maintained?	<input checked="" type="checkbox"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID

Technician

Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- |   |   |                                     |  |
|---|---|-------------------------------------|--|
| 1 | Do the sample inlets have at least a 270 degree arc of unrestricted airflow?          | <input checked="" type="checkbox"/> |  |
| 2 | Are the sample inlets 3 - 15 meters above the ground?                                 | <input checked="" type="checkbox"/> |  |
| 3 | Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees? | <input checked="" type="checkbox"/> |  |

**Pollutant analyzers and deposition equipment operations and maintenance**

- |   |  |                                     |                         |
|---|--|-------------------------------------|-------------------------|
| 1 | Do the analyzers and equipment appear to be in good condition and well maintained? | <input checked="" type="checkbox"/> |                         |
| 2 | Are the analyzers and monitors operational, on-line, and reporting data?           | <input checked="" type="checkbox"/> |                         |
| 3 | Describe ozone sample tube.  |                                     | 1/4 teflon by 12 meters |
| 4 | Describe dry dep sample tube.  |                                     | 3/8 teflon by 12 meters |
| 5 | Are in-line filters used in the ozone sample line? (if yes indicate location)      | <input checked="" type="checkbox"/> | At inlet only           |
| 6 | Are sample lines clean, free of kinks, moisture, and obstructions?                 | <input type="checkbox"/>            | Moisture in tubing only |
| 7 | Is the zero air supply desiccant unsaturated?                                      | <input checked="" type="checkbox"/> |                         |
| 8 | Are there moisture traps in the sample lines?                                      | <input checked="" type="checkbox"/> | Flow line only          |
| 9 | Is there a rotometer in the dry deposition filter line, and is it clean?           | <input checked="" type="checkbox"/> | Clean and dry           |

**Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:**

Moisture is present in the flow tubing outside of the shelter.

# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

- |                                     |  |  |                           |                 |                          |                          |                                     |                          |  |
|-------------------------------------|--|--|---------------------------|-----------------|--------------------------|--------------------------|-------------------------------------|--------------------------|--|
| 1                                   | Do the DAS instruments appear to be in good condition and well maintained?           | <input checked="" type="checkbox"/>  |                           |                 |                          |                          |                                     |                          |  |
| 2                                   | Are all the components of the DAS operational? (printers, modem, backup, etc)        | <input checked="" type="checkbox"/>  |                           |                 |                          |                          |                                     |                          |  |
| 3                                   | Do the analyzer and sensor signal leads pass through lightning protection circuitry? | <input checked="" type="checkbox"/>  | Met sensors only          |                 |                          |                          |                                     |                          |  |
| 4                                   | Are the signal connections protected from the weather and well maintained?           | <input checked="" type="checkbox"/>  |                           |                 |                          |                          |                                     |                          |  |
| 5                                   | Are the signal leads connected to the correct DAS channel?                           | <input checked="" type="checkbox"/>  |                           |                 |                          |                          |                                     |                          |  |
| 6                                   | Are the DAS, sensor translators, and shelter properly grounded?                      | <input checked="" type="checkbox"/>  |                           |                 |                          |                          |                                     |                          |  |
| 7                                   | Does the instrument shelter have a stable power source?                              | <input checked="" type="checkbox"/>  |                           |                 |                          |                          |                                     |                          |  |
| 8                                   | Is the instrument shelter temperature controlled?                                    | <input checked="" type="checkbox"/>  |                           |                 |                          |                          |                                     |                          |  |
| 9                                   | Is the met tower stable and grounded?  | <table border="1"><tr><td><b>Stable</b></td><td><b>Grounded</b></td></tr><tr><td><input type="checkbox"/></td><td><input type="checkbox"/></td></tr><tr><td><input checked="" type="checkbox"/></td><td><input type="checkbox"/></td></tr></table> | <b>Stable</b>             | <b>Grounded</b> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |  |
| <b>Stable</b>                       | <b>Grounded</b>  |  |                           |                 |                          |                          |                                     |                          |  |
| <input type="checkbox"/>            | <input type="checkbox"/>   |  |                           |                 |                          |                          |                                     |                          |  |
| <input checked="" type="checkbox"/> | <input type="checkbox"/>   |  |                           |                 |                          |                          |                                     |                          |  |
| 10                                  | Is the sample tower stable and grounded?   |  |                           |                 |                          |                          |                                     |                          |  |
| 11                                  | Tower comments?  |  | Sample tower not grounded |                 |                          |                          |                                     |                          |  |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

The met tower has been removed. The DAS controls the shelter heating and cooling.

# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Computer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Solar radiation sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Modem	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Printer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	UPS	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Ozone analyzer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack flow controller	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
HASP	<input checked="" type="checkbox"/>	Oct 2014	<input checked="" type="checkbox"/>
Field Ops Manual	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Calibration Reports	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Preventive maintenance schedul	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>

- 1 Is the station log properly completed during every site visit?
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?  Control charts not used

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID

Technician

Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Every 2 weeks"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Zero Air Desiccant Check	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID

Technician

Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed various times
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF, logbook
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF, logbook, call-in
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	Clean gloves on and off
9	Are the site conditions reported regularly to the field operations manager or staff?	<input checked="" type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input type="checkbox"/>	<input type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID

Technician

Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
Computer	Dell	Inspiron 15	Unknown	07017
DAS	Campbell	CR3000	2117	000338
Elevation	Elevation	1	None	None
Filter pack flow pump	Thomas	107CAB18	060400022682	06025
Flow Rate	Apex	AXMC105LPMDPC	illegible	000809
Infrastructure	Infrastructure	none	none	none
Modem	Raven	V4221-V	0844352818	06588
Ozone	ThermoElectron Inc	49i A1NAA	1030244799	000702
Ozone Standard	ThermoElectron Inc	49i A3NAA	0726124687	000364
Sample Tower	Aluma Tower	B	none	000180
Shelter Temperature	Campbell	107-L	none	none
Siting Criteria	Siting Criteria	1	None	None
Temperature	RM Young	41342	14796	06535
Zero air pump	Werther International	C 70/4	000836202	06933

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>	
<i>UVL124-Eric Hebert-08/16/2016</i>						
1	8/16/2016	Computer	Dell	07012	Inspiron 15	Unknown
2	8/16/2016	DAS	Campbell	000423	CR3000	2517
3	8/16/2016	Elevation	Elevation	None	1	None
4	8/16/2016	Filter pack flow pump	Thomas	02973	107CAB18	0493002467
5	8/16/2016	Flow Rate	Apex	000600	AXMC105LPMDPCV	illegible
6	8/16/2016	Infrastructure	Infrastructure	none	none	none
7	8/16/2016	Modem	Raven	06466	V4221-V	0808339409
8	8/16/2016	Ozone	ThermoElectron Inc	000745	49i A1NAA	1105347315
9	8/16/2016	Ozone Standard	ThermoElectron Inc	000362	49i A3NAA	0726124686
10	8/16/2016	Sample Tower	Aluma Tower	03557	A	none
11	8/16/2016	Shelter Temperature	Campbell	none	107-L	none
12	8/16/2016	Siting Criteria	Siting Criteria	None	1	None
13	8/16/2016	Temperature	RM Young	06504	41342	14624
14	8/16/2016	Zero air pump	Werther International	06936	C 70/4	000829169



# DAS Data Form

DAS Time Max Error:

<b>Mfg</b>	<b>Serial Number</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Use Desc.</b>
Campbell	2517	UVL124	Eric Hebert	08/16/2016	DAS	Primary

<b>Das Date:</b>	<input type="text" value="8 /16/2016"/>	<b>Audit Date</b>	<input type="text" value="8 /16/2016"/>
<b>Das Time:</b>	<input type="text" value="18:20:00"/>	<b>Audit Time</b>	<input type="text" value="18:20:01"/>
<b>Das Day:</b>	<input type="text" value="229"/>	<b>Audit Day</b>	<input type="text" value="229"/>
<b>Low Channel:</b>		<b>High Channel:</b>	
<b>Avg Diff:</b>	<input type="text" value="0.0000"/>	<b>Max Diff:</b>	<input type="text" value="0.0000"/>
		<b>Avg Diff:</b>	<input type="text" value="0.0000"/>
		<b>Max Diff:</b>	<input type="text" value="0.0000"/>

<b>Mfg</b>	<input type="text" value="Datel"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="4000392"/>	<b>Tfer Desc.</b>	<input type="text" value="Source generator (D"/>
<b>Tfer ID</b>	<input type="text" value="01321"/>		
<b>Mfg</b>	<input type="text" value="Fluke"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="86590148"/>	<b>Tfer Desc.</b>	<input type="text" value="DVM"/>
<b>Tfer ID</b>	<input type="text" value="01310"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="12/23/2015"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
7	0.0000	0.0000	0.0000	V	V	0.0000
7	0.1000	0.1000	0.1000	V	V	0.0000
7	0.3000	0.3000	0.3000	V	V	0.0000
7	0.5000	0.4999	0.4999	V	V	0.0000
7	0.7000	0.6999	0.6999	V	V	0.0000
7	0.9000	0.8999	0.8999	V	V	0.0000
7	1.0000	0.9999	0.9999	V	V	0.0000

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Apex	illegible		UVL124	Eric Hebert	08/16/2016	Flow Rate	000600

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	148613	<b>Tfer Desc.</b>	BIOS 220-H
<b>Tfer ID</b>	01421		
<b>Slope</b>	1.00309	<b>Intercept</b>	-0.00231
<b>Cert Date</b>	4/21/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
0.44%	0.67%

<b>Cal Factor Zero</b>	-0.02
<b>Cal Factor Full Scale</b>	0.99
<b>Rotometer Reading:</b>	1.5

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignalI	PctDifference
primary	pump off	0.000	0.000	0.01	0.000	-0.02	l/m	l/m	
primary	leak check	0.000	0.000	0.00	0.000	-0.03	l/m	l/m	
primary	test pt 1	1.497	1.490	1.51	0.000	1.50	l/m	l/m	0.67%
primary	test pt 2	1.504	1.500	1.50	0.000	1.50	l/m	l/m	0.00%
primary	test pt 3	1.516	1.510	1.51	0.000	1.50	l/m	l/m	-0.66%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	No moisture present	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	5.0 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	2.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	360 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1105347315		UVL124	Eric Hebert	08/16/2016	Ozone	000745

<b>Slope:</b>	1.00000	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.57786	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99996	<b>CorrCoff</b>	0.00000

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0517112167	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01113		
<b>Slope</b>	1.00500	<b>Intercept</b>	-0.28841
<b>Cert Date</b>	1/28/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
1.1%	3.0%		

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	-0.10	0.18	-0.57	ppb	
primary	2	27.33	27.48	26.67	ppb	-2.95%
primary	3	50.12	50.15	50.14	ppb	-0.02%
primary	4	80.01	79.89	79.51	ppb	-0.48%
primary	5	104.98	104.74	103.80	ppb	-0.90%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.000	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.011	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	94.6 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.8 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.71 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	717.2 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	39.0 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	96.8 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.7 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.00 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	717.4 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass



# Temperature Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	14624		UVL124	Eric Hebert	08/16/2016	Temperature	06504

<b>Mfg</b>	Extech	<b>Parameter</b>	Temperature
<b>Serial Number</b>	H232679	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01228		
<b>Slope</b>	1.00760	<b>Intercept</b>	-0.05710
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>		<b>DAS 2:</b>	
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>
0.04	0.08		

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Range	2.10	2.14	0.000	2.1	C	-0.02
primary	Temp Mid Range	26.67	26.53	0.000	26.5	C	-0.03
primary	Temp High Range	49.63	49.31	0.000	49.2	C	-0.08

<b>Sensor Component</b>	Shield	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Campbell	none	UVL124	Eric Hebert	08/16/2016	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
0.57	0.60		

<b>Mfg</b>	Extech	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	H232679	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01228		
<b>Slope</b>	1.00760	<b>Intercept</b>	-0.05710
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Mid Range	26.15	26.01	0.000	26.6	C	0.6
primary	Temp Mid Range	25.88	25.74	0.000	26.3	C	0.54

<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
-------------------------	-------------	------------------	--	---------------	------

## Infrastructure Data For

Site ID  Technician  Site Visit Date

Shelter Make	Shelter Model	Shelter Size
<input type="text" value="Ekto"/>	<input type="text" value="8810"/>	<input type="text" value="640 cuft"/>

Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text" value="Type A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Functioning"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="3/8 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>

# Field Systems Comments

**1 Parameter:** SiteOpsProcedures

Ozone sample train leak-check performed every two weeks.

**2 Parameter:** DocumentationCo

The ozone diagnostic and observation sections of the SSRF were completed during the filter removal visit and not the installation visit as indicated on the form. This was noted during the previous audit visit. It was discussed with the site operator who indicated she would be recording the information on the correct date.

**3 Parameter:** SitingCriteriaCom

The site is located in an active agriculture field usually planted with beans or corn.

**4 Parameter:** ShelterCleanNotes

The shelter is clean and in good condition.

**5 Parameter:** MetOpMaintCom

Met tower removed and temperature mounted in naturally aspirated shield on sample tower.



# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)	<input type="text" value="EPA"/>	USGS Map	<input type="text" value="Ellington"/>
Operating Group	<input type="text" value="private"/>	Map Scale	<input type="text"/>
AQS #	<input type="text" value="26-157-9991"/>	Map Date	<input type="text"/>
Meteorological Type	<input type="text" value="R.M. Young"/>		
Air Pollutant Analyzer	<input type="text" value="Ozone"/>	QAPP Latitude	<input type="text"/>
Deposition Measurement	<input type="text" value="dry, wet"/>	QAPP Longitude	<input type="text"/>
Land Use	<input type="text" value="agriculture"/>	QAPP Elevation Meters	<input type="text"/>
Terrain	<input type="text" value="flat"/>	QAPP Declination	<input type="text"/>
Conforms to MLM	<input type="text" value="Yes"/>	QAPP Declination Date	<input type="text"/>
Site Telephone	<input type="text" value="(989) 673-5901"/>	Audit Latitude	<input type="text" value="43.613572"/>
Site Address 1	<input type="text" value="1821 E. Dickerson Rd."/>	Audit Longitude	<input type="text" value="-83.359869"/>
Site Address 2	<input type="text"/>	Audit Elevation	<input type="text" value="202"/>
County	<input type="text" value="Tuscola"/>	Audit Declination	<input type="text" value="-7"/>
City, State	<input type="text" value="Unionville, MI"/>		
Zip Code	<input type="text" value="48767"/>	Fire Extinguisher <input checked="" type="checkbox"/>	<input type="text" value="New in 2015"/>
Time Zone	<input type="text" value="Eastern"/>	First Aid Kit <input checked="" type="checkbox"/>	<input type="text"/>
Primary Operator	<input type="text"/>	Safety Glasses <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. Phone #	<input type="text"/>	Safety Hard Hat <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. E-mail	<input type="text"/>	Climbing Belt <input type="checkbox"/>	<input type="text"/>
Backup Operator	<input type="text"/>	Security Fence <input type="checkbox"/>	<input type="text"/>
Backup Op. Phone #	<input type="text"/>	Secure Shelter <input checked="" type="checkbox"/>	<input type="text"/>
Backup Op. E-mail	<input type="text"/>	Stable Entry Step <input checked="" type="checkbox"/>	<input type="text"/>
Shelter Working Room <input checked="" type="checkbox"/>	Make <input type="text" value="Ekto"/> Model <input type="text" value="8810"/>	Shelter Size	<input type="text" value="640 cuft"/>
Shelter Clean <input checked="" type="checkbox"/>	Notes	<input type="text" value="The shelter is clean and in good condition."/>	
Site OK <input checked="" type="checkbox"/>	Notes	<input type="text"/>	

**Driving Directions**

# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID  Technician  Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km	<input type="text"/>	<input checked="" type="checkbox"/>
City > 50,000 population	40 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Feedlot operations	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m	30 m	<input type="checkbox"/>
Limited agricultural operations	200 m	<input type="text"/>	<input type="checkbox"/>
Large parking lot	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Small parking lot	100 m	<input type="text"/>	<input checked="" type="checkbox"/>
Tree line	50 m	<input type="text"/>	<input checked="" type="checkbox"/>
Obstacles to wind	10 times obstacle height	<input type="text"/>	<input checked="" type="checkbox"/>

Siting Distances OK

Siting Criteria Comment

# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID

Technician

Site Visit Date

- |    |  |                                     |     |
|----|--|-------------------------------------|-----|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> | N/A |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> | N/A |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> | N/A |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |     |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |     |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> | N/A |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> | N/A |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> | N/A |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> | N/A |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> | N/A |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | N/A |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

UVL124

Technician

Eric Hebert

Site Visit Date

08/16/2016

1	Do all the meteorological sensors appear to be intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	Temperature only
2	Are all the meteorological sensors operational online, and reporting data?	<input checked="" type="checkbox"/>	Temperature only
3	Are the shields for the temperature and RH sensors clean?	<input checked="" type="checkbox"/>	
4	Are the aspirated motors working?	<input checked="" type="checkbox"/>	
5	Is the solar radiation sensor's lens clean and free of scratches?	<input checked="" type="checkbox"/>	N/A
6	Is the surface wetness sensor grid clean and undamaged?	<input checked="" type="checkbox"/>	N/A
7	Are the sensor signal and power cables intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	
8	Are the sensor signal and power cable connections protected from the elements and well maintained?	<input checked="" type="checkbox"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

Met tower removed and temperature mounted in naturally aspirated shield on sample tower.

# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID

Technician

Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- |   |   |                                     |  |
|---|---|-------------------------------------|--|
| 1 | Do the sample inlets have at least a 270 degree arc of unrestricted airflow?          | <input checked="" type="checkbox"/> |  |
| 2 | Are the sample inlets 3 - 15 meters above the ground?                                 | <input checked="" type="checkbox"/> |  |
| 3 | Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees? | <input checked="" type="checkbox"/> |  |

**Pollutant analyzers and deposition equipment operations and maintenance**

- |   |  |                                     |                         |
|---|--|-------------------------------------|-------------------------|
| 1 | Do the analyzers and equipment appear to be in good condition and well maintained? | <input checked="" type="checkbox"/> |                         |
| 2 | Are the analyzers and monitors operational, on-line, and reporting data?           | <input checked="" type="checkbox"/> |                         |
| 3 | Describe ozone sample tube.  |                                     | 1/4 teflon by 12 meters |
| 4 | Describe dry dep sample tube.  |                                     | 3/8 teflon by 12 meters |
| 5 | Are in-line filters used in the ozone sample line? (if yes indicate location)      | <input checked="" type="checkbox"/> | At inlet only           |
| 6 | Are sample lines clean, free of kinks, moisture, and obstructions?                 | <input checked="" type="checkbox"/> |                         |
| 7 | Is the zero air supply desiccant unsaturated?                                      | <input checked="" type="checkbox"/> |                         |
| 8 | Are there moisture traps in the sample lines?                                      | <input checked="" type="checkbox"/> | Flow line only          |
| 9 | Is there a rotometer in the dry deposition filter line, and is it clean?           | <input checked="" type="checkbox"/> | Clean and dry           |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

- |                                     |  |  |                    |                 |                          |                          |                                     |                          |  |
|-------------------------------------|--|--|--------------------|-----------------|--------------------------|--------------------------|-------------------------------------|--------------------------|--|
| 1                                   | Do the DAS instruments appear to be in good condition and well maintained?           | <input checked="" type="checkbox"/>  |                    |                 |                          |                          |                                     |                          |  |
| 2                                   | Are all the components of the DAS operational? (printers, modem, backup, etc)        | <input checked="" type="checkbox"/>  |                    |                 |                          |                          |                                     |                          |  |
| 3                                   | Do the analyzer and sensor signal leads pass through lightning protection circuitry? | <input checked="" type="checkbox"/>  | Met sensors only   |                 |                          |                          |                                     |                          |  |
| 4                                   | Are the signal connections protected from the weather and well maintained?           | <input checked="" type="checkbox"/>  |                    |                 |                          |                          |                                     |                          |  |
| 5                                   | Are the signal leads connected to the correct DAS channel?                           | <input checked="" type="checkbox"/>  |                    |                 |                          |                          |                                     |                          |  |
| 6                                   | Are the DAS, sensor translators, and shelter properly grounded?                      | <input checked="" type="checkbox"/>  |                    |                 |                          |                          |                                     |                          |  |
| 7                                   | Does the instrument shelter have a stable power source?                              | <input checked="" type="checkbox"/>  |                    |                 |                          |                          |                                     |                          |  |
| 8                                   | Is the instrument shelter temperature controlled?                                    | <input checked="" type="checkbox"/>  |                    |                 |                          |                          |                                     |                          |  |
| 9                                   | Is the met tower stable and grounded?  | <table border="1"><tr><td><b>Stable</b></td><td><b>Grounded</b></td></tr><tr><td><input type="checkbox"/></td><td><input type="checkbox"/></td></tr><tr><td><input checked="" type="checkbox"/></td><td><input type="checkbox"/></td></tr></table> | <b>Stable</b>      | <b>Grounded</b> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |  |
| <b>Stable</b>                       | <b>Grounded</b>  |  |                    |                 |                          |                          |                                     |                          |  |
| <input type="checkbox"/>            | <input type="checkbox"/>   |  |                    |                 |                          |                          |                                     |                          |  |
| <input checked="" type="checkbox"/> | <input type="checkbox"/>   |  |                    |                 |                          |                          |                                     |                          |  |
| 10                                  | Is the sample tower stable and grounded?   |  |                    |                 |                          |                          |                                     |                          |  |
| 11                                  | Tower comments?  |  | Tower not grounded |                 |                          |                          |                                     |                          |  |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Computer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Solar radiation sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Modem	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Printer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	UPS	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Ozone analyzer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack flow controller	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input checked="" type="checkbox"/>	Oct 2014	<input checked="" type="checkbox"/>
HASP	<input checked="" type="checkbox"/>	Oct 2014	<input checked="" type="checkbox"/>
Field Ops Manual	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Calibration Reports	<input checked="" type="checkbox"/>	4/14/2016	<input checked="" type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Preventive maintenance schedule	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>

- 1 Is the station log properly completed during every site visit?
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?  Control charts not used

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

The ozone diagnostic and observation sections of the SSRF were completed during the filter removal visit and not the installation visit as indicated on the form. This was noted during the previous audit visit. It was discussed with the site operator who indicated she would be recording the information on the correct date.

# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID  Technician  Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Every 2 weeks"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Zero Air Desiccant Check	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:



# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID

Technician

Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed mornings
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	With noted exceptions
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF, logbook, call-in
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	Clean gloves on and off
9	Are the site conditions reported regularly to the field operations manager or staff?	<input checked="" type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input type="checkbox"/>	<input type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID

Technician

Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
Computer	Dell	Inspiron 15	Unknown	07012
DAS	Campbell	CR3000	2517	000423
Elevation	Elevation	1	None	None
Filter pack flow pump	Thomas	107CAB18	0493002467	02973
Flow Rate	Apex	AXMC105LPMDPC	illegible	000600
Infrastructure	Infrastructure	none	none	none
Modem	Raven	V4221-V	0808339409	06466
Ozone	ThermoElectron Inc	49i A1NAA	1105347315	000745
Ozone Standard	ThermoElectron Inc	49i A3NAA	0726124686	000362
Sample Tower	Aluma Tower	A	none	03557
Shelter Temperature	Campbell	107-L	none	none
Siting Criteria	Siting Criteria	1	None	None
Temperature	RM Young	41342	14624	06504
Zero air pump	Werther International	C 70/4	000829169	06936

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

### *KEF112-Sandy Grenville-08/17/2016*

1	8/17/2016	Computer	Dell	07054	Inspiron 15	Unknown
2	8/17/2016	DAS	Campbell	000414	CR3000	2537
3	8/17/2016	Elevation	Elevation	None	1	None
4	8/17/2016	Filter pack flow pump	Thomas	000965	107CA18	00000878
5	8/17/2016	Flow Rate	Apex	000671	AXMC105LPMDPCV	illegible
6	8/17/2016	Infrastructure	Infrastructure	none	none	none
7	8/17/2016	Modem	Raven	06455	V4221-V	0808337420
8	8/17/2016	Ozone	ThermoElectron Inc	000728	49i A1NAA	1105347306
9	8/17/2016	Ozone Standard	ThermoElectron Inc	000432	49i A3NAA	CM08200008
10	8/17/2016	Sample Tower	Aluma Tower	03443	A	none
11	8/17/2016	Shelter Temperature	Campbell	none	107-L	none
12	8/17/2016	Shield (10 meter)	RM Young	01399	Aspirated 43408	none
13	8/17/2016	Siting Criteria	Siting Criteria	None	1	None
14	8/17/2016	Temperature	RM Young	06388	41342	13992
15	8/17/2016	Zero air pump	Werther International	06922	C 70/4	000836217

# DAS Data Form

DAS Time Max Error:

<b>Mfg</b>	<b>Serial Number</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Use Desc.</b>
Campbell	2537	KEF112	Sandy Grenville	08/17/2016	DAS	Primary

<b>Das Date:</b>	<input type="text" value="8 /17/2016"/>	<b>Audit Date</b>	<input type="text" value="8 /17/2016"/>
<b>Das Time:</b>	<input type="text" value="12:54:00"/>	<b>Audit Time</b>	<input type="text" value="12:53:56"/>
<b>Das Day:</b>	<input type="text" value="230"/>	<b>Audit Day</b>	<input type="text" value="230"/>
<b>Low Channel:</b>		<b>High Channel:</b>	
<b>Avg Diff:</b>	<input type="text" value="0.0001"/>	<b>Max Diff:</b>	<input type="text" value="0.0001"/>
		<b>Avg Diff:</b>	<input type="text" value="0.0001"/>
		<b>Max Diff:</b>	<input type="text" value="0.0001"/>

<b>Mfg</b>	<input type="text" value="Datel"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="15510194"/>	<b>Tfer Desc.</b>	<input type="text" value="Source generator (D"/>
<b>Tfer ID</b>	<input type="text" value="01320"/>		
<b>Mfg</b>	<input type="text" value="Fluke"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="95740135"/>	<b>Tfer Desc.</b>	<input type="text" value="DVM"/>
<b>Tfer ID</b>	<input type="text" value="01311"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="12/23/2015"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
7	0.0000	0.0000	0.0000	V	V	0.0000
7	0.1000	0.0999	0.0999	V	V	0.0000
7	0.3000	0.2997	0.2998	V	V	0.0001
7	0.5000	0.4996	0.4997	V	V	0.0001
7	0.7000	0.6996	0.6996	V	V	0.0000
7	0.9000	0.8994	0.8995	V	V	0.0001
7	1.0000	0.9993	0.9994	V	V	0.0001

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Apex	illegible		KEF112	Sandy Grenville	08/17/2016	Flow Rate	000671

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	103471	<b>Tfer Desc.</b>	nexus
<b>Tfer ID</b>	01420		
<b>Slope</b>	0.99091	<b>Intercept</b>	0.03172
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	0.99988
<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	103424	<b>Tfer Desc.</b>	BIOS cell
<b>Tfer ID</b>	01410		
<b>Slope</b>	0.99091	<b>Intercept</b>	0.03172
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	0.99988

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
1.62%	1.71%
<b>A Avg %Dif</b>	<b>A Max % Di</b>

<b>Cal Factor Zero</b>	0.005
<b>Cal Factor Full Scale</b>	0.979
<b>Rotometer Reading:</b>	1.55

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignal	PctDifference
primary	pump off	0.000	0.000	0.01	0.000	0.01	l/m	l/m	
primary	leak check	0.000	0.000	0.01	0.000	0.01	l/m	l/m	
primary	test pt 1	1.538	1.520	1.53	0.000	1.50	l/m	l/m	-1.58%
primary	test pt 2	1.535	1.520	1.53	0.000	1.49	l/m	l/m	-1.71%
primary	test pt 3	1.536	1.520	1.53	0.000	1.50	l/m	l/m	-1.58%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	See comments	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	4.0 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	1.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	20 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1105347306		KEF112	Sandy Grenville	08/17/2016	Ozone	000728

<b>Slope:</b>	0.98447	<b>Slope:</b>	0.00000
<b>Intercept</b>	0.27377	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99995	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
1.3%	2.2%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0419606966	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01112		
<b>Slope</b>	0.99524	<b>Intercept</b>	-0.33070
<b>Cert Date</b>	1/28/2016	<b>CorrCoff</b>	1.00000

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	0.03	0.36	0.94	ppb	
primary	2	30.01	30.48	30.11	ppb	-1.21%
primary	3	50.14	50.71	49.60	ppb	-2.19%
primary	4	80.07	80.78	80.30	ppb	-0.59%
primary	5	110.34	111.20	109.70	ppb	-1.35%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.10	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.011	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	92.7 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.9 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.71 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	684.8 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	37.7 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	92.4 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.9 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.73 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	684.2 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Temperature Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	13992		KEF112	Sandy Grenville	08/17/2016	Temperature	06388

<b>Mfg</b>	Extech	<b>Parameter</b>	Temperature
<b>Serial Number</b>	H232734	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01227		
<b>Slope</b>	1.00772	<b>Intercept</b>	0.12514
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>		<b>DAS 2:</b>	
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>
0.08	0.18		

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Range	0.17	0.04	0.000	0.1	C	0.06
primary	Temp Mid Range	25.51	25.19	0.000	25.2	C	-0.01
primary	Temp High Range	49.69	49.19	0.000	49.0	C	-0.18

<b>Sensor Component</b>	Shield	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Campbell	none	KEF112	Sandy Grenville	08/17/2016	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
0.56	0.75		

<b>Mfg</b>	Extech	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	H232734	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01227		
<b>Slope</b>	1.00772	<b>Intercept</b>	0.12514
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Mid Range	25.71	25.39	0.000	25.7	C	0.32
primary	Temp Mid Range	29.16	28.81	0.000	28.2	C	-0.61
primary	Temp Mid Range	24.34	24.03	0.000	24.8	C	0.75

<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
-------------------------	-------------	------------------	--	---------------	------



## Infrastructure Data For

Site ID  Technician  Site Visit Date

Shelter Make	Shelter Model	Shelter Size
<input type="text" value="Ekto"/>	<input type="text" value="8810 (s/n 2149-14)"/>	<input type="text" value="640 cuft"/>

Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text" value="Type A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Functioning"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="3/8 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>

# Site Visit Comments

<b>Parameter</b>	<b>Site</b>	<b>Technician</b>	<b>S.V. Date</b>	<b>Component</b>	<b>Mfg</b>	<b>Serial No.</b>	<b>Hazard</b>	<b>Problem</b>
Flow Rate	KEF112	Sandy Grenville	08/17/2016	Moisture Present	Apex	3652	<input type="checkbox"/>	<input type="checkbox"/>
The filter sample tubing has drops of moisture in low sections outside the shelter.								

# Field Systems Comments

1 **Parameter:** SiteOpsProcedures

The inlet filter is replaced and the ozone sample train is leak tested every two weeks.

2 **Parameter:** SitingCriteriaCom

The site is in a clearing within the Kane Experimental Forest, the tree line is within 10 meters of the site.

3 **Parameter:** ShelterCleanNotes

The shelter is clean and very well organized. The floor and bottom of walls are beginning to deteriorate.

4 **Parameter:** PollAnalyzerCom

Trees to the east are within 20 meters of the ozone inlet.

5 **Parameter:** MetSensorComme

The meteorological tower is attached to the shelter and the temperature sensor is positioned directly over the metal roof of the shelter.

# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)	<input type="text" value="EPA"/>	USGS Map	<input type="text" value="James City"/>
Operating Group	<input type="text" value="PAFS/private"/>	Map Scale	<input type="text"/>
AQS #	<input type="text" value="42-047-9991"/>	Map Date	<input type="text"/>
Meteorological Type	<input type="text" value="R.M. Young"/>		
Air Pollutant Analyzer	<input type="text" value="Ozone"/>	QAPP Latitude	<input type="text" value="41.5981"/>
Deposition Measurement	<input type="text" value="dry, wet"/>	QAPP Longitude	<input type="text" value="-78.7683"/>
Land Use	<input type="text" value="woodland - mixed"/>	QAPP Elevation Meters	<input type="text" value="622"/>
Terrain	<input type="text" value="rolling"/>	QAPP Declination	<input type="text" value="10.5"/>
Conforms to MLM	<input type="text" value="Yes"/>	QAPP Declination Date	<input type="text" value="2/24/2006"/>
Site Telephone	<input type="text" value="(814) 837-8069"/>	Audit Latitude	<input type="text" value="41.598119"/>
Site Address 1	<input type="text" value="Kane Experimental Forest Hdqts"/>	Audit Longitude	<input type="text" value="-78.767866"/>
Site Address 2	<input type="text" value="Seven Mile Road"/>	Audit Elevation	<input type="text" value="618"/>
County	<input type="text" value="Elk"/>	Audit Declination	<input type="text" value="-10.3"/>
City, State	<input type="text" value="Kane, PA"/>		
Zip Code	<input type="text" value="16735"/>	<b>Present</b>	
Time Zone	<input type="text" value="Eastern"/>	Fire Extinguisher <input checked="" type="checkbox"/>	<input type="text" value="New in 2015"/>
Primary Operator	<input type="text"/>	First Aid Kit <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. Phone #	<input type="text"/>	Safety Glasses <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. E-mail	<input type="text"/>	Safety Hard Hat <input checked="" type="checkbox"/>	<input type="text"/>
Backup Operator	<input type="text"/>	Climbing Belt <input type="checkbox"/>	<input type="text"/>
Backup Op. Phone #	<input type="text"/>	Security Fence <input type="checkbox"/>	<input type="text"/>
Backup Op. E-mail	<input type="text"/>	Secure Shelter <input checked="" type="checkbox"/>	<input type="text"/>
		Stable Entry Step <input checked="" type="checkbox"/>	<input type="text"/>

Shelter Working Room  Make  Model  Shelter Size

Shelter Clean  Notes

Site OK  Notes

**Driving Directions** From Kane go south on route 66 for approximately 1 mile. Just past the 2nd cemetery turn left. Continue to the stop sign just over the railroad tracks. Turn right and continue approximately 3.2 miles through the town of Lamont. About 0.5 mile past Lamont, turn left on a gravel road which is marked with a brown Forest Service sign for the NE Forest Experimental Station. Continue approximately 2 miles and bear left at the fork. The site is behind the green Forest Service buildings on the left.

# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID  Technician  Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km	<input type="text"/>	<input checked="" type="checkbox"/>
City > 50,000 population	40 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Feedlot operations	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Limited agricultural operations	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Large parking lot	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Small parking lot	100 m	<input type="text"/>	<input checked="" type="checkbox"/>
Tree line	50 m	10 m	<input type="checkbox"/>
Obstacles to wind	10 times obstacle height	<input type="text"/>	<input checked="" type="checkbox"/>

Siting Distances OK

**Siting Criteria Comment**

# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID

Technician

Site Visit Date

- |    |  |                                     |  |
|----|--|-------------------------------------|--|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> | N/A  |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> | N/A  |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> | N/A  |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |  |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input type="checkbox"/>            | Temperature sensor mounted over shelter roof |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> | N/A  |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> | N/A  |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> | N/A  |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> | N/A  |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> | N/A  |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | N/A  |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

The meteorological tower is attached to the shelter and the temperature sensor is positioned directly over the metal roof of the shelter.

# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

Technician

Site Visit Date

1	Do all the meteorological sensors appear to be intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	Temperature only
2	Are all the meteorological sensors operational online, and reporting data?	<input checked="" type="checkbox"/>	Temperature only
3	Are the shields for the temperature and RH sensors clean?	<input checked="" type="checkbox"/>	
4	Are the aspirated motors working?	<input checked="" type="checkbox"/>	N/A
5	Is the solar radiation sensor's lens clean and free of scratches?	<input checked="" type="checkbox"/>	N/A
6	Is the surface wetness sensor grid clean and undamaged?	<input checked="" type="checkbox"/>	N/A
7	Are the sensor signal and power cables intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	
8	Are the sensor signal and power cable connections protected from the elements and well maintained?	<input checked="" type="checkbox"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID

Technician

Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- 1 Do the sample inlets have at least a 270 degree arc of unrestricted airflow?
- 2 Are the sample inlets 3 - 15 meters above the ground?
- 3 Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees?


**Pollutant analyzers and deposition equipment operations and maintenance**

- 1 Do the analyzers and equipment appear to be in good condition and well maintained?
- 2 Are the analyzers and monitors operational, on-line, and reporting data?
- 3 Describe ozone sample tube.
- 4 Describe dry dep sample tube.
- 5 Are in-line filters used in the ozone sample line? (if yes indicate location)
- 6 Are sample lines clean, free of kinks, moisture, and obstructions?
- 7 Is the zero air supply desiccant unsaturated?
- 8 Are there moisture traps in the sample lines?
- 9 Is there a rotometer in the dry deposition filter line, and is it clean?

1/4 teflon by 15 meters
3/8 teflon by 12 meters
At inlet only
Flow line only
Clean and dry

**Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:**

Trees to the east are within 20 meters of the ozone inlet.



# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

- |                                     |  |  |   |                 |                          |                          |                                     |                          |  |
|-------------------------------------|--|--|---|-----------------|--------------------------|--------------------------|-------------------------------------|--------------------------|--|
| 1                                   | Do the DAS instruments appear to be in good condition and well maintained?           | <input checked="" type="checkbox"/>  |   |                 |                          |                          |                                     |                          |  |
| 2                                   | Are all the components of the DAS operational? (printers, modem, backup, etc)        | <input checked="" type="checkbox"/>  |   |                 |                          |                          |                                     |                          |  |
| 3                                   | Do the analyzer and sensor signal leads pass through lightning protection circuitry? | <input checked="" type="checkbox"/>  | Met sensors only                            |                 |                          |                          |                                     |                          |  |
| 4                                   | Are the signal connections protected from the weather and well maintained?           | <input checked="" type="checkbox"/>  |   |                 |                          |                          |                                     |                          |  |
| 5                                   | Are the signal leads connected to the correct DAS channel?                           | <input checked="" type="checkbox"/>  |   |                 |                          |                          |                                     |                          |  |
| 6                                   | Are the DAS, sensor translators, and shelter properly grounded?                      | <input checked="" type="checkbox"/>  |   |                 |                          |                          |                                     |                          |  |
| 7                                   | Does the instrument shelter have a stable power source?                              | <input checked="" type="checkbox"/>  |   |                 |                          |                          |                                     |                          |  |
| 8                                   | Is the instrument shelter temperature controlled?                                    | <input checked="" type="checkbox"/>  |   |                 |                          |                          |                                     |                          |  |
| 9                                   | Is the met tower stable and grounded?  | <table border="1"><tr><td><b>Stable</b></td><td><b>Grounded</b></td></tr><tr><td><input type="checkbox"/></td><td><input type="checkbox"/></td></tr><tr><td><input checked="" type="checkbox"/></td><td><input type="checkbox"/></td></tr></table> | <b>Stable</b>                               | <b>Grounded</b> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> |  |
| <b>Stable</b>                       | <b>Grounded</b>  |  |   |                 |                          |                          |                                     |                          |  |
| <input type="checkbox"/>            | <input type="checkbox"/>   |  |   |                 |                          |                          |                                     |                          |  |
| <input checked="" type="checkbox"/> | <input type="checkbox"/>   |  |   |                 |                          |                          |                                     |                          |  |
| 10                                  | Is the sample tower stable and grounded?   |  |   |                 |                          |                          |                                     |                          |  |
| 11                                  | Tower comments?  |  | Met Tower removed, SampleTower not grounded |                 |                          |                          |                                     |                          |  |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Computer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Solar radiation sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Modem	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Printer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	UPS	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Ozone analyzer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack flow controller	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input checked="" type="checkbox"/>	Feb 2014	<input type="checkbox"/>
HASP	<input checked="" type="checkbox"/>	Feb 2014	<input checked="" type="checkbox"/>
Field Ops Manual	<input checked="" type="checkbox"/>	Oct 2011	<input checked="" type="checkbox"/>
Calibration Reports	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Preventive maintenance schedul	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>

- 1 Is the station log properly completed during every site visit?
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?  Control charts not used

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID

Technician

Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input type="checkbox"/>	<input type="text" value="As needed"/>	<input checked="" type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input type="checkbox"/>	<input type="text" value="As needed"/>	<input checked="" type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Every 2 weeks"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Zero Air Desiccant Check	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID

Technician

Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed morinings 90% of the time
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF, logbook
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF, logbook, call-in
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	Clean gloves on and off
9	Are the site conditions reported regularly to the field operations manager or staff?	<input checked="" type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input type="checkbox"/>	<input type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> As needed	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID

Technician

Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
Computer	Dell	Inspiron 15	Unknown	07054
DAS	Campbell	CR3000	2537	000414
Elevation	Elevation	1	None	None
Filter pack flow pump	Thomas	107CA18	00000878	000965
Flow Rate	Apex	AXMC105LPMDPC	illegible	000671
Infrastructure	Infrastructure	none	none	none
Modem	Raven	V4221-V	0808337420	06455
Ozone	ThermoElectron Inc	49i A1NAA	1105347306	000728
Ozone Standard	ThermoElectron Inc	49i A3NAA	CM08200008	000432
Sample Tower	Aluma Tower	A	none	03443
Shelter Temperature	Campbell	107-L	none	none
Shield (10 meter)	RM Young	Aspirated 43408	none	01399
Siting Criteria	Siting Criteria	1	None	None
Temperature	RM Young	41342	13992	06388
Zero air pump	Werther International	C 70/4	000836217	06922

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>	
<i>HOX148-Eric Hebert-08/18/2016</i>						
1	8/18/2016	Computer	Dell	07062	Inspiron 15	Unknown
2	8/18/2016	DAS	Campbell	000426	CR3000	2533
3	8/18/2016	Elevation	Elevation	None	1	None
4	8/18/2016	Filter pack flow pump	Thomas	04927	107CAB18	110300021225
5	8/18/2016	Flow Rate	Apex	000526	AXMC105LPMDPCV	48099
6	8/18/2016	Infrastructure	Infrastructure	none	none	none
7	8/18/2016	Modem	Raven	06480	H4222-C	0808311145
8	8/18/2016	Ozone	ThermoElectron Inc	000614	49i A1NAA	1009241794
9	8/18/2016	Ozone Standard	ThermoElectron Inc	000438	49i A3NAA	CM08200014
10	8/18/2016	Sample Tower	Aluma Tower	000131	B	none
11	8/18/2016	Shelter Temperature	Campbell	none	107-L	none
12	8/18/2016	Siting Criteria	Siting Criteria	None	1	None
13	8/18/2016	Temperature	RM Young	06544	41342	14805
14	8/18/2016	Zero air pump	Werther International	06938	C 70/4	000829164

# DAS Data Form

DAS Time Max Error:

<b>Mfg</b>	<b>Serial Number</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Use Desc.</b>
Campbell	2533	HOX148	Eric Hebert	08/18/2016	DAS	Primary

<b>Das Date:</b>	<input type="text" value="8/18/2016"/>	<b>Audit Date</b>	<input type="text" value="8/18/2016"/>
<b>Das Time:</b>	<input type="text" value="8:35:32"/>	<b>Audit Time</b>	<input type="text" value="8:35:30"/>
<b>Das Day:</b>	<input type="text" value="231"/>	<b>Audit Day</b>	<input type="text" value="231"/>
<b>Low Channel:</b>		<b>High Channel:</b>	
<b>Avg Diff:</b>	<input type="text" value="0.0000"/>	<b>Max Diff:</b>	<input type="text" value="0.0001"/>
		<b>Avg Diff:</b>	<input type="text" value="0.0000"/>
		<b>Max Diff:</b>	<input type="text" value="0.0001"/>

<b>Mfg</b>	<input type="text" value="Datel"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="4000392"/>	<b>Tfer Desc.</b>	<input type="text" value="Source generator (D"/>
<b>Tfer ID</b>	<input type="text" value="01321"/>		
<b>Mfg</b>	<input type="text" value="Fluke"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="86590148"/>	<b>Tfer Desc.</b>	<input type="text" value="DVM"/>
<b>Tfer ID</b>	<input type="text" value="01310"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="12/23/2015"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
7	0.0000	0.0000	0.0000	V	V	0.0000
7	0.1000	0.1000	0.1000	V	V	0.0000
7	0.3000	0.3000	0.3000	V	V	0.0000
7	0.5000	0.5000	0.5000	V	V	0.0000
7	0.7000	0.7000	0.7001	V	V	0.0001
7	0.9000	0.9000	0.9001	V	V	0.0001
7	1.0000	1.0000	1.0000	V	V	0.0000

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Apex	48099		HOX148	Eric Hebert	08/18/2016	Flow Rate	000526

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	148613	<b>Tfer Desc.</b>	BIOS 220-H
<b>Tfer ID</b>	01421		
<b>Slope</b>	1.00309	<b>Intercept</b>	-0.00231
<b>Cert Date</b>	4/21/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
0.44%	0.67%

<b>Cal Factor Zero</b>	0.05
<b>Cal Factor Full Scale</b>	1.06
<b>Rotometer Reading:</b>	1.45

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignal	PctDifference
primary	pump off	0.000	0.000	-0.08	0.000	-0.03	l/m	l/m	
primary	leak check	0.000	0.000	-0.01	0.000	0.03	l/m	l/m	
primary	test pt 1	1.493	1.490	1.43	0.000	1.50	l/m	l/m	0.67%
primary	test pt 2	1.500	1.500	1.43	0.000	1.50	l/m	l/m	0.00%
primary	test pt 3	1.508	1.510	1.43	0.000	1.50	l/m	l/m	-0.66%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	See comments	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	5.0 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	3.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	235 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass



# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1009241794		HOX148	Eric Hebert	08/18/2016	Ozone	000614

<b>Slope:</b>	0.98573	<b>Slope:</b>	0.00000
<b>Intercept</b>	0.47845	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99998	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
0.8%	0.9%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0517112167	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01113		
<b>Slope</b>	1.00500	<b>Intercept</b>	-0.28841
<b>Cert Date</b>	1/28/2016	<b>CorrCoff</b>	1.00000

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	0.05	0.33	1.08	ppb	
primary	2	27.87	28.01	27.75	ppb	-0.93%
primary	3	49.94	49.97	49.66	ppb	-0.62%
primary	4	79.81	79.69	79.08	ppb	-0.77%
primary	5	104.46	104.22	103.30	ppb	-0.88%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-0.60	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.022	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	90.7 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.9 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.89 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	715.1 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	41.9 C	<b>Status</b>	Fail
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	93.9 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.72 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	715.7 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>	See comments	<b>Status</b>	pass

# Temperature Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	14805		HOX148	Eric Hebert	08/18/2016	Temperature	06544

<b>Mfg</b>	Extech	<b>Parameter</b>	Temperature
<b>Serial Number</b>	H232679	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01228		
<b>Slope</b>	1.00760	<b>Intercept</b>	-0.05710
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>		<b>DAS 2:</b>	
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>
0.12	0.24		

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Range	0.03	0.09	0.000	0.1	C	-0.02
primary	Temp Mid Range	30.98	30.80	0.000	30.9	C	0.1
primary	Temp High Range	49.78	49.46	0.000	49.7	C	0.24

<b>Sensor Component</b>	Shield	<b>Condition</b>	Moderately clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Campbell	none	HOX148	Eric Hebert	08/18/2016	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
0.52	0.89		

<b>Mfg</b>	Extech	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	H232679	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01228		
<b>Slope</b>	1.00760	<b>Intercept</b>	-0.05710
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Mid Range	29.70	29.53	0.000	29.7	C	0.16
primary	Temp Mid Range	24.01	23.89	0.000	24.8	C	0.89

<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
-------------------------	-------------	------------------	--	---------------	------

## Infrastructure Data For

Site ID  Technician  Site Visit Date

Shelter Make	Shelter Model	Shelter Size
<input type="text" value="Ekto"/>	<input type="text" value="8810"/>	<input type="text" value="640 cuft"/>

Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text" value="Type B"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Not functioning"/>	Status	<input type="text" value="Fail"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="3/8 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>

# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)	<input type="text" value="EPA"/>	USGS Map	<input type="text" value="Hoxeyville"/>
Operating Group	<input type="text" value="private"/>	Map Scale	<input type="text"/>
AQS #	<input type="text" value="26-165-9991"/>	Map Date	<input type="text"/>
Meteorological Type	<input type="text" value="R.M. Young"/>		
Air Pollutant Analyzer	<input type="text" value="Ozone"/>	QAPP Latitude	<input type="text"/>
Deposition Measurement	<input type="text" value="dry"/>	QAPP Longitude	<input type="text"/>
Land Use	<input type="text" value="woodlands - mixed"/>	QAPP Elevation Meters	<input type="text"/>
Terrain	<input type="text" value="gently rolling"/>	QAPP Declination	<input type="text"/>
Conforms to MLM	<input type="text" value="Yes"/>	QAPP Declination Date	<input type="text"/>
Site Telephone	<input type="text" value="(231) 862-3750"/>	Audit Latitude	<input type="text" value="44.18089"/>
Site Address 1	<input type="text" value="10637 South 9 Rd."/>	Audit Longitude	<input type="text" value="-85.73898"/>
Site Address 2	<input type="text"/>	Audit Elevation	<input type="text" value="297"/>
County	<input type="text" value="Wexford"/>	Audit Declination	<input type="text" value="-5"/>
City, State	<input type="text" value="Cadillac, MI"/>		
Zip Code	<input type="text" value="49601"/>	Fire Extinguisher <input checked="" type="checkbox"/>	<input type="text" value="New in 2015"/>
Time Zone	<input type="text" value="Eastern"/>	First Aid Kit <input checked="" type="checkbox"/>	<input type="text"/>
Primary Operator	<input type="text"/>	Safety Glasses <input type="checkbox"/>	<input type="text"/>
Primary Op. Phone #	<input type="text"/>	Safety Hard Hat <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. E-mail	<input type="text"/>	Climbing Belt <input type="checkbox"/>	<input type="text"/>
Backup Operator	<input type="text"/>	Security Fence <input type="checkbox"/>	<input type="text"/>
Backup Op. Phone #	<input type="text"/>	Secure Shelter <input checked="" type="checkbox"/>	<input type="text"/>
Backup Op. E-mail	<input type="text"/>	Stable Entry Step <input checked="" type="checkbox"/>	<input type="text"/>
Shelter Working Room <input checked="" type="checkbox"/>	Make <input type="text" value="Ekto"/> Model <input type="text" value="8810"/>	Shelter Size	<input type="text" value="640 cuft"/>
Shelter Clean <input checked="" type="checkbox"/>	Notes	<input type="text" value="The shelter is clean, neat, well organized. Major repairs are underway to the floor of the shelter."/>	
Site OK <input checked="" type="checkbox"/>	Notes	<input type="text"/>	

**Driving Directions** From Cadillac proceed west on route 55 for approximately 12.5 miles. Turn left (south) on Hoxeyville Road (S13) and continue approximately 2 miles to the first stop sign. Turn right (west) on an unmarked road and continue approximately 2 miles to 9 road. Turn left (south) on 9 road which is not paved and continue approximately 1 mile, the site is on the left.

# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID  Technician  Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km	~ 30 km	<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km	<input type="text"/>	<input checked="" type="checkbox"/>
City > 50,000 population	40 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Feedlot operations	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Limited agricultural operations	200 m	10 m	<input type="checkbox"/>
Large parking lot	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Small parking lot	100 m	<input type="text"/>	<input checked="" type="checkbox"/>
Tree line	50 m	<input type="text"/>	<input checked="" type="checkbox"/>
Obstacles to wind	10 times obstacle height	<input type="text"/>	<input checked="" type="checkbox"/>

Siting Distances OK

**Siting Criteria Comment**

There is a co-generating and smelting facility in Cadillac approximately 30 km to the northeast. The site is located in a hay field which is cut 2 or 3 times per year.

# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID

Technician

Site Visit Date

- |    |  |                                     |     |
|----|--|-------------------------------------|-----|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> | N/A |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> | N/A |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> | N/A |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |     |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |     |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> | N/A |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> | N/A |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> | N/A |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> | N/A |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> | N/A |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | N/A |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

Technician

Site Visit Date

1	Do all the meteorological sensors appear to be intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	Temperature only
2	Are all the meteorological sensors operational online, and reporting data?	<input checked="" type="checkbox"/>	Temperature only
3	Are the shields for the temperature and RH sensors clean?	<input checked="" type="checkbox"/>	
4	Are the aspirated motors working?	<input checked="" type="checkbox"/>	
5	Is the solar radiation sensor's lens clean and free of scratches?	<input checked="" type="checkbox"/>	N/A
6	Is the surface wetness sensor grid clean and undamaged?	<input checked="" type="checkbox"/>	N/A
7	Are the sensor signal and power cables intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	
8	Are the sensor signal and power cable connections protected from the elements and well maintained?	<input checked="" type="checkbox"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:



# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID

Technician

Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- |   |   |                                     |  |
|---|---|-------------------------------------|--|
| 1 | Do the sample inlets have at least a 270 degree arc of unrestricted airflow?          | <input checked="" type="checkbox"/> |  |
| 2 | Are the sample inlets 3 - 15 meters above the ground?                                 | <input checked="" type="checkbox"/> |  |
| 3 | Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees? | <input checked="" type="checkbox"/> |  |

**Pollutant analyzers and deposition equipment operations and maintenance**

- |   |  |                                     |                         |
|---|--|-------------------------------------|-------------------------|
| 1 | Do the analyzers and equipment appear to be in good condition and well maintained? | <input checked="" type="checkbox"/> |                         |
| 2 | Are the analyzers and monitors operational, on-line, and reporting data?           | <input checked="" type="checkbox"/> |                         |
| 3 | Describe ozone sample tube.  |                                     | 1/4 teflon by 15 meters |
| 4 | Describe dry dep sample tube.  |                                     | 3/8 teflon by 15 meters |
| 5 | Are in-line filters used in the ozone sample line? (if yes indicate location)      | <input checked="" type="checkbox"/> | At inlet only           |
| 6 | Are sample lines clean, free of kinks, moisture, and obstructions?                 | <input checked="" type="checkbox"/> |                         |
| 7 | Is the zero air supply desiccant unsaturated?                                      | <input checked="" type="checkbox"/> |                         |
| 8 | Are there moisture traps in the sample lines?                                      | <input checked="" type="checkbox"/> | Flow line only          |
| 9 | Is there a rotometer in the dry deposition filter line, and is it clean?           | <input checked="" type="checkbox"/> | Clean and dry           |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

- |    |  |                                     |                                     |
|----|--|-------------------------------------|-------------------------------------|
| 1  | Do the DAS instruments appear to be in good condition and well maintained?           | <input checked="" type="checkbox"/> |                                     |
| 2  | Are all the components of the DAS operational? (printers, modem, backup, etc)        | <input checked="" type="checkbox"/> |                                     |
| 3  | Do the analyzer and sensor signal leads pass through lightning protection circuitry? | <input checked="" type="checkbox"/> |                                     |
| 4  | Are the signal connections protected from the weather and well maintained?           | <input checked="" type="checkbox"/> |                                     |
| 5  | Are the signal leads connected to the correct DAS channel?                           | <input checked="" type="checkbox"/> |                                     |
| 6  | Are the DAS, sensor translators, and shelter properly grounded?                      | <input checked="" type="checkbox"/> |                                     |
| 7  | Does the instrument shelter have a stable power source?                              | <input checked="" type="checkbox"/> |                                     |
| 8  | Is the instrument shelter temperature controlled?                                    | <input type="checkbox"/>            | Temperature control off             |
| 9  | Is the met tower stable and grounded?  | <input type="checkbox"/>            | <input type="checkbox"/>            |
| 10 | Is the sample tower stable and grounded?   | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| 11 | Tower comments?  |                                     | Met tower removed                   |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

The shelter floor is being replaced. The shelter climate control is disabled due to the construction.

# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Computer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Solar radiation sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Modem	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Printer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	UPS	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Ozone analyzer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack flow controller	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input checked="" type="checkbox"/>	Oct 2014	<input type="checkbox"/>
HASP	<input checked="" type="checkbox"/>	Oct 2014	<input type="checkbox"/>
Field Ops Manual	<input checked="" type="checkbox"/>	June 1987	<input type="checkbox"/>
Calibration Reports	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Preventive maintenance schedul	<input type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>

- 1 Is the station log properly completed during every site visit?
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?  Control charts not used

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID  Technician  Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Every 2 weeks"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Zero Air Desiccant Check	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?

**Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:**

The ozone analyzer sample train is leak-checked every two weeks. The shelter climate control is disabled during repairs to the shelter. Although the shelter temperature is currently within acceptable limits there is an "Alarm High" temperature flag present on the site ozone monitor.

# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID

Technician

Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed mornings
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF, logbook
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF, call-in
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	Clean gloves on and off
9	Are the site conditions reported regularly to the field operations manager or staff?	<input checked="" type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input type="checkbox"/>	<input type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID

Technician

Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
Computer	Dell	Inspiron 15	Unknown	07062
DAS	Campbell	CR3000	2533	000426
Elevation	Elevation	1	None	None
Filter pack flow pump	Thomas	107CAB18	110300021225	04927
Flow Rate	Apex	AXMC105LPMDPC	48099	000526
Infrastructure	Infrastructure	none	none	none
Modem	Raven	H4222-C	0808311145	06480
Ozone	ThermoElectron Inc	49i A1NAA	1009241794	000614
Ozone Standard	ThermoElectron Inc	49i A3NAA	CM08200014	000438
Sample Tower	Aluma Tower	B	none	000131
Shelter Temperature	Campbell	107-L	none	none
Siting Criteria	Siting Criteria	1	None	None
Temperature	RM Young	41342	14805	06544
Zero air pump	Werther International	C 70/4	000829164	06938

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>	
<i>PSU106-Sandy Grenville-08/22/2016</i>						
1	8/22/2016	Computer	Dell	07046	Inspiron 15	Unknown
2	8/22/2016	DAS	Campbell	000407	CR3000	2512
3	8/22/2016	Elevation	Elevation	None	1	None
4	8/22/2016	Filter pack flow pump	Thomas	06023	107CAB18	060400022676
5	8/22/2016	Flow Rate	Apex	000560	AXMC105LPMDPCV	50732
6	8/22/2016	Infrastructure	Infrastructure	none	none	none
7	8/22/2016	Modem	Raven	06483	V4221-V	0808310813
8	8/22/2016	Ozone	ThermoElectron Inc	000678	49i A1NAA	1030244791
9	8/22/2016	Ozone Standard	ThermoElectron Inc	000434	49i A3NAA	CM08200010
10	8/22/2016	Sample Tower	Aluma Tower	02747	A	none
11	8/22/2016	Shelter Temperature	Campbell	none	107-L	none
12	8/22/2016	Siting Criteria	Siting Criteria	None	1	None
13	8/22/2016	Temperature	RM Young	05048	41342VC	9683
14	8/22/2016	Zero air pump	Werther International	06921	C 70/4	000836216

# DAS Data Form

DAS Time Max Error:

<b>Mfg</b>	<b>Serial Number</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Use Desc.</b>
Campbell	2512	PSU106	Sandy Grenville	08/22/2016	DAS	Primary

<b>Das Date:</b>	<input type="text" value="8 /21/2016"/>	<b>Audit Date</b>	<input type="text" value="8 /21/2016"/>
<b>Das Time:</b>	<input type="text" value="17:22:00"/>	<b>Audit Time</b>	<input type="text" value="17:21:55"/>
<b>Das Day:</b>	<input type="text" value="234"/>	<b>Audit Day</b>	<input type="text" value="234"/>
<b>Low Channel:</b>		<b>High Channel:</b>	
<b>Avg Diff:</b>	<input type="text" value="0.0000"/>	<b>Max Diff:</b>	<input type="text" value="0.0001"/>
		<b>Avg Diff:</b>	<input type="text" value="0.0000"/>
		<b>Max Diff:</b>	<input type="text" value="0.0001"/>

<b>Mfg</b>	<input type="text" value="Datel"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="15510194"/>	<b>Tfer Desc.</b>	<input type="text" value="Source generator (D"/>
<b>Tfer ID</b>	<input type="text" value="01320"/>		
<b>Mfg</b>	<input type="text" value="Fluke"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="95740135"/>	<b>Tfer Desc.</b>	<input type="text" value="DVM"/>
<b>Tfer ID</b>	<input type="text" value="01311"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="12/23/2015"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
7	0.0000	0.0000	0.0000	V	V	0.0000
7	0.1000	0.0999	0.0999	V	V	0.0000
7	0.3000	0.2997	0.2997	V	V	0.0000
7	0.5000	0.4996	0.4996	V	V	0.0000
7	0.7000	0.6995	0.6995	V	V	0.0000
7	0.9000	0.8994	0.8993	V	V	-0.0001
7	1.0000	0.9993	0.9992	V	V	-0.0001



# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Apex	50732	PSU106	Sandy Grenville	08/22/2016	Flow Rate	000560

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	103471	<b>Tfer Desc.</b>	nexus
<b>Tfer ID</b>	01420		
<b>Slope</b>	0.99091	<b>Intercept</b>	0.03172
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	0.99988
<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	103424	<b>Tfer Desc.</b>	BIOS cell
<b>Tfer ID</b>	01410		
<b>Slope</b>	0.99091	<b>Intercept</b>	0.03172
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	0.99988

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
0.66%	0.66%
<b>A Avg %Dif</b>	<b>A Max % Di</b>

<b>Cal Factor Zero</b>	-0.05
<b>Cal Factor Full Scale</b>	0.94
<b>Rotometer Reading:</b>	1.5

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignal	PctDifference
primary	pump off	0.000	0.000	0.02	0.000	-0.02	l/m	l/m	
primary	leak check	0.000	0.000	0.01	0.000	-0.03	l/m	l/m	
primary	test pt 1	1.525	1.510	1.58	0.000	1.50	l/m	l/m	-0.66%
primary	test pt 2	1.528	1.510	1.58	0.000	1.50	l/m	l/m	-0.66%
primary	test pt 3	1.529	1.510	1.58	0.000	1.50	l/m	l/m	-0.66%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Fair	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	No moisture present	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	4.0 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	0.0 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	90 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1030244791		PSU106	Sandy Grenville	08/22/2016	Ozone	000678

<b>Slope:</b>	0.98609	<b>Slope:</b>	0.00000
<b>Intercept</b>	0.18438	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	1.00000	<b>CorrCoff</b>	0.00000

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0419606966	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01112		
<b>Slope</b>	0.99524	<b>Intercept</b>	-0.33070
<b>Cert Date</b>	1/28/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
1.0%	1.2%		

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	-0.01	0.32	0.49	ppb	
primary	2	30.03	30.50	30.27	ppb	-0.75%
primary	3	50.03	50.60	50.07	ppb	-1.05%
primary	4	80.16	80.87	79.96	ppb	-1.13%
primary	5	110.13	110.98	109.60	ppb	-1.24%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.40	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.006	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	96.7 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.8 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.81 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	704.1 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	34.6 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	94.9 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.9 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.68 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Temperature Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	9683		PSU106	Sandy Grenville	08/22/2016	Temperature	05048

<b>Mfg</b>	Extech	<b>Parameter</b>	Temperature
<b>Serial Number</b>	H232734	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01227		
<b>Slope</b>	1.00772	<b>Intercept</b>	0.12514
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>		<b>DAS 2:</b>	
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>
0.27	0.33		

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Range	0.18	0.05	0.000	0.3	C	0.22
primary	Temp Mid Range	25.08	24.76	0.000	25.1	C	0.33
primary	Temp High Range	48.74	48.24	0.000	48.5	C	0.26

<b>Sensor Component</b>	Shield	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Campbell	none	PSU106	Sandy Grenville	08/22/2016	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
0.36	0.51		

<b>Mfg</b>	Extech	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	H232734	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01227		
<b>Slope</b>	1.00772	<b>Intercept</b>	0.12514
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Mid Range	25.48	25.16	0.000	25.7	C	0.51
primary	Temp Mid Range	25.70	25.38	0.000	25.7	C	0.36
primary	Temp Mid Range	26.00	25.68	0.000	25.9	C	0.22

<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
-------------------------	-------------	------------------	--	---------------	------

## Infrastructure Data For

Site ID  Technician  Site Visit Date

Shelter Make	Shelter Model	Shelter Size
<input type="text" value="PSU"/>	<input type="text" value="N/A"/>	<input type="text" value="3840 cuft"/>

Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text" value="Type A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Functioning"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="3/8 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>

# Field Systems Comments

**1 Parameter:** SiteOpsProcComm

The site operator uses the filter bag as a glove when handling the filter pack.

**2 Parameter:** DasComments

The meteorological tower has been removed.

**3 Parameter:** SitingCriteriaCom

The site is within 10 km of State College which has a population of approximately 50,000. The site is located in a university agricultural research field.

**4 Parameter:** ShelterCleanNotes

The shelter is owned by the university and is clean and orderly. The site is part of the Surfrad network.

**5 Parameter:** MetOpMaintCom

The 10-meter temperature sensor is now mounted in a naturally aspirated shield on the sample tower.

# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)  USGS Map   
 Operating Group  Map Scale   
 AQS #  Map Date

Meteorological Type   
 Air Pollutant Analyzer  QAPP Latitude

Deposition Measurement  QAPP Longitude   
 Land Use  QAPP Elevation Meters

Terrain  QAPP Declination   
 Conforms to MLM  QAPP Declination Date

Site Telephone  Audit Latitude   
 Site Address 1  Audit Longitude

Site Address 2  Audit Elevation   
 County  Audit Declination

City, State  Present  
 Zip Code  Fire Extinguisher

Time Zone  First Aid Kit   
 Primary Operator  Safety Glasses

Primary Op. Phone #  Safety Hard Hat   
 Primary Op. E-mail  Climbing Belt

Backup Operator  Security Fence   
 Backup Op. Phone #  Secure Shelter

Backup Op. E-mail  Stable Entry Step   
 Shelter Working Room  Make  Model  Shelter Size

Shelter Clean  Notes

Site OK  Notes

Driving Directions

# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID  Technician  Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km		<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km		<input checked="" type="checkbox"/>
City > 50,000 population	40 km		<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km	State College	<input type="checkbox"/>
City 1,000 to 10,000 population	5 km		<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km		<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m		<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m		<input checked="" type="checkbox"/>
Feedlot operations	500 m		<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m		<input checked="" type="checkbox"/>
Limited agricultural operations	200 m	10 m	<input type="checkbox"/>
Large parking lot	200 m		<input checked="" type="checkbox"/>
Small parking lot	100 m		<input checked="" type="checkbox"/>
Tree line	50 m		<input checked="" type="checkbox"/>
Obstacles to wind	10 times obstacle height		<input checked="" type="checkbox"/>

Siting Distances OK

**Siting Criteria Comment**

The site is within 10 km of State College which has a population of approximately 50,000. The site is located in a university agricultural research field.



# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID

Technician

Site Visit Date

- |    |  |                                     |     |
|----|--|-------------------------------------|-----|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> | N/A |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> | N/A |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> | N/A |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |     |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |     |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> | N/A |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> | N/A |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> | N/A |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> | N/A |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> | N/A |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | N/A |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

Technician

Site Visit Date

1	Do all the meteorological sensors appear to be intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	Temperature only
2	Are all the meteorological sensors operational online, and reporting data?	<input checked="" type="checkbox"/>	Temperature only
3	Are the shields for the temperature and RH sensors clean?	<input checked="" type="checkbox"/>	
4	Are the aspirated motors working?	<input checked="" type="checkbox"/>	N/A
5	Is the solar radiation sensor's lens clean and free of scratches?	<input checked="" type="checkbox"/>	N/A
6	Is the surface wetness sensor grid clean and undamaged?	<input checked="" type="checkbox"/>	N/A
7	Are the sensor signal and power cables intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	
8	Are the sensor signal and power cable connections protected from the elements and well maintained?	<input checked="" type="checkbox"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID PSU106

Technician Sandy Grenville

Site Visit Date 08/22/2016

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- 1 Do the sample inlets have at least a 270 degree arc of unrestricted airflow?
- 2 Are the sample inlets 3 - 15 meters above the ground?
- 3 Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees?


**Pollutant analyzers and deposition equipment operations and maintenance**

- 1 Do the analyzers and equipment appear to be in good condition and well maintained?
- 2 Are the analyzers and monitors operational, on-line, and reporting data?
- 3 Describe ozone sample tube.
- 4 Describe dry dep sample tube.
- 5 Are in-line filters used in the ozone sample line? (if yes indicate location)
- 6 Are sample lines clean, free of kinks, moisture, and obstructions?
- 7 Is the zero air supply desiccant unsaturated?
- 8 Are there moisture traps in the sample lines?
- 9 Is there a rotometer in the dry deposition filter line, and is it clean?

1/4 teflon by 20 meters
3/8 teflon by 20 meters
At inlet only
Flow line only
Clean and dry

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

--

# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

- |                                     |  |   |                   |                 |                          |                          |                                     |                                     |  |
|-------------------------------------|--|---|-------------------|-----------------|--------------------------|--------------------------|-------------------------------------|-------------------------------------|--|
| 1                                   | Do the DAS instruments appear to be in good condition and well maintained?           | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 2                                   | Are all the components of the DAS operational? (printers, modem, backup, etc)        | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 3                                   | Do the analyzer and sensor signal leads pass through lightning protection circuitry? | <input checked="" type="checkbox"/>   | Met sensors only  |                 |                          |                          |                                     |                                     |  |
| 4                                   | Are the signal connections protected from the weather and well maintained?           | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 5                                   | Are the signal leads connected to the correct DAS channel?                           | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 6                                   | Are the DAS, sensor translators, and shelter properly grounded?                      | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 7                                   | Does the instrument shelter have a stable power source?                              | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 8                                   | Is the instrument shelter temperature controlled?                                    | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 9                                   | Is the met tower stable and grounded?  | <table border="1"><tr><td><b>Stable</b></td><td><b>Grounded</b></td></tr><tr><td><input type="checkbox"/></td><td><input type="checkbox"/></td></tr><tr><td><input checked="" type="checkbox"/></td><td><input checked="" type="checkbox"/></td></tr></table> | <b>Stable</b>     | <b>Grounded</b> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |  |
| <b>Stable</b>                       | <b>Grounded</b>  |   |                   |                 |                          |                          |                                     |                                     |  |
| <input type="checkbox"/>            | <input type="checkbox"/>   |   |                   |                 |                          |                          |                                     |                                     |  |
| <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/>  |   |                   |                 |                          |                          |                                     |                                     |  |
| 10                                  | Is the sample tower stable and grounded?   |   |                   |                 |                          |                          |                                     |                                     |  |
| 11                                  | Tower comments?  |   | Met tower removed |                 |                          |                          |                                     |                                     |  |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Computer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Solar radiation sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Modem	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Printer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	UPS	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Ozone analyzer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Filter pack flow controller	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input checked="" type="checkbox"/>	Feb 2014	<input checked="" type="checkbox"/>
HASP	<input checked="" type="checkbox"/>	Feb 2014	<input checked="" type="checkbox"/>
Field Ops Manual	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Calibration Reports	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Preventive maintenance schedul	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>

- 1 Is the station log properly completed during every site visit?
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?  Control charts not used

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID  Technician  Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input type="checkbox"/>	<input type="text" value="As needed"/>	<input checked="" type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input type="checkbox"/>	<input type="text" value="As needed"/>	<input checked="" type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Every 2 weeks"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Zero Air Desiccant Check	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID

Technician

Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed morinings
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF, logbook
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF, logbook, call-in
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input type="checkbox"/>	gloves are not used
9	Are the site conditions reported regularly to the field operations manager or staff?	<input checked="" type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input type="checkbox"/>	<input type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

The site operator uses the filter bag as a glove when handling the filter pack.

# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID  Technician  Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
Computer	Dell	Inspiron 15	Unknown	07046
DAS	Campbell	CR3000	2512	000407
Elevation	Elevation	1	None	None
Filter pack flow pump	Thomas	107CAB18	060400022676	06023
Flow Rate	Apex	AXMC105LPMDPC	50732	000560
Infrastructure	Infrastructure	none	none	none
Modem	Raven	V4221-V	0808310813	06483
Ozone	ThermoElectron Inc	49i A1NAA	1030244791	000678
Ozone Standard	ThermoElectron Inc	49i A3NAA	CM08200010	000434
Sample Tower	Aluma Tower	A	none	02747
Shelter Temperature	Campbell	107-L	none	none
Siting Criteria	Siting Criteria	1	None	None
Temperature	RM Young	41342VC	9683	05048
Zero air pump	Werther International	C 70/4	000836216	06921



---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*RED004-Eric Hebert-08/30/2016*

1	8/30/2016	DAS	Campbell	none	CR850	28383
2	8/30/2016	elevation	Elevation	none	none	none
3	8/30/2016	Filter pack flow pump	Thomas	none	1420 VP	42624821
4	8/30/2016	Flow Rate	Apex	000527	AXMC105LPMDCV	48100
5	8/30/2016	Infrastructure	Infrastructure	none	none	none
6	8/30/2016	Modem	Sierra wireless	07000	unknown	unknown
7	8/30/2016	Sample Tower	Aluma Tower	000813	B	unknown
8	8/30/2016	siting criteria	Siting Criteria	none	none	None
9	8/30/2016	Temperature	RM Young	06986	41342	024087

# DAS Data Form

DAS Time Max Error:

Mfg	Serial Number	Site	Technician	Site Visit Date	Parameter	Use Desc.
Campbell	28383	RED004	Eric Hebert	08/30/2016	DAS	Primary

Das Date:       Audit Date:

Das Time:       Audit Time:

Das Day:       Audit Day:

Low Channel:

High Channel:

Avg Diff:

Max Diff:

Avg Diff:

Max Diff:

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Apex	48100		RED004	Eric Hebert	08/30/2016	Flow Rate	000527

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	148613	<b>Tfer Desc.</b>	BIOS 220-H
<b>Tfer ID</b>	01421		
<b>Slope</b>	1.00309	<b>Intercept</b>	-0.00231
<b>Cert Date</b>	4/21/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
0.00%	0.00%

<b>Cal Factor Zero</b>	-0.38
<b>Cal Factor Full Scale</b>	0.987
<b>Rotometer Reading:</b>	3

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignalI	PctDifference
primary	pump off	0.000	0.000	0.00	0.0000	-0.03	l/m	l/m	
primary	leak check	0.000	0.000	0.00	0.0000	-0.03	l/m	l/m	
primary	test pt 1	3.013	3.010	3.01	0.0000	3.01	l/m	l/m	0.00%
primary	test pt 2	3.021	3.010	3.01	0.0000	3.01	l/m	l/m	0.00%
primary	test pt 3	3.021	3.010	3.01	0.0000	3.01	l/m	l/m	0.00%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	See comments	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	2.0 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	2.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	270 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Temperature Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	024087		RED004	Eric Hebert	08/30/2016	Temperature	06986

<b>Mfg</b>	Extech	<b>Parameter</b>	Temperature
<b>Serial Number</b>	H232679	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01228		
<b>Slope</b>	1.00760	<b>Intercept</b>	-0.05710
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>		<b>DAS 2:</b>	
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>
0.07	0.18		

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Range	0.09	0.15	0.0000	0.0	C	-0.18
primary	Temp Mid Range	23.91	23.79	0.0000	23.8	C	-0.04
primary	Temp High Range	50.58	50.26	0.0000	50.3	C	0

<b>Sensor Component</b>	Shield	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

**Infrastructure Data For**

**Site ID**  **Technician**  **Site Visit Date**

Shelter Make	Shelter Model	Shelter Size
<input type="text"/>	<input type="text"/>	<input type="text"/>

<b>Sensor Component</b>	<input type="text" value="Sample Tower Type"/>	<b>Condition</b>	<input type="text" value="Type B"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Conduit"/>	<b>Condition</b>	<input type="text" value="N/A"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Met Tower"/>	<b>Condition</b>	<input type="text" value="N/A"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Moisture Trap"/>	<b>Condition</b>	<input type="text" value="Not installed"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Power Cables"/>	<b>Condition</b>	<input type="text" value="Good"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Shelter Temp Control"/>	<b>Condition</b>	<input type="text" value="N/A"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Rotometer"/>	<b>Condition</b>	<input type="text" value="Installed"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Sample Tower"/>	<b>Condition</b>	<input type="text" value="Good"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Shelter Condition"/>	<b>Condition</b>	<input type="text" value="N/A"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Shelter Door"/>	<b>Condition</b>	<input type="text" value="N/A"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Shelter Roof"/>	<b>Condition</b>	<input type="text" value="N/A"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Shelter Floor"/>	<b>Condition</b>	<input type="text" value="N/A"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Signal Cable"/>	<b>Condition</b>	<input type="text" value="Good"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Tubing Type"/>	<b>Condition</b>	<input type="text" value="3/8 teflon"/>	<b>Status</b>	<input type="text" value="pass"/>
<b>Sensor Component</b>	<input type="text" value="Sample Train"/>	<b>Condition</b>	<input type="text" value="Good"/>	<b>Status</b>	<input type="text" value="pass"/>

# Site Visit Comments

<b>Parameter</b>	<b>Site</b>	<b>Technician</b>	<b>S.V. Date</b>	<b>Component</b>	<b>Mfg</b>	<b>Serial No.</b>	<b>Hazard</b>	<b>Problem</b>
Flow Rate	RED004	Eric Hebert	08/30/2016	Moisture Present	Apex	3319	<input type="checkbox"/>	<input type="checkbox"/>
The filter sample tubing has drops of moisture in low sections outside the shelter.								

# Field Systems Comments

1 **Parameter:** DocumentationCo

There is no site logbook and all manuals are kept electronically since the site is a small footprint site with no place to store hardcopies.

2 **Parameter:** SitingCriteriaCom

The site was cleared when installed, however the underbrush is beginning to grow near the tower.

3 **Parameter:** ShelterCleanNotes

Small footprint site with enclosure for instruments only. No shelter.

# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)	<input type="text" value="EPA"/>	USGS Map	<input type="text"/>
Operating Group	<input type="text" value="Red Lake Nation / AMEC"/>	Map Scale	<input type="text"/>
AQS #	<input type="text"/>	Map Date	<input type="text"/>
Meteorological Type	<input type="text" value="R.M. Young"/>		
Air Pollutant Analyzer	<input type="text"/>	QAPP Latitude	<input type="text"/>
Deposition Measurement	<input type="text" value="dry"/>	QAPP Longitude	<input type="text"/>
Land Use	<input type="text"/>	QAPP Elevation Meters	<input type="text"/>
Terrain	<input type="text"/>	QAPP Declination	<input type="text"/>
Conforms to MLM	<input type="text"/>	QAPP Declination Date	<input type="text"/>
Site Telephone	<input type="text"/>	Audit Latitude	<input type="text" value="47.86382"/>
Site Address 1	<input type="text"/>	Audit Longitude	<input type="text" value="-94.83535"/>
Site Address 2	<input type="text"/>	Audit Elevation	<input type="text" value="374"/>
County	<input type="text" value="Beltrami"/>	Audit Declination	<input type="text"/>
City, State	<input type="text" value="Redby, MN"/>		
Zip Code	<input type="text" value="56670"/>	Fire Extinguisher <input type="checkbox"/>	<input type="text"/>
Time Zone	<input type="text" value="Central"/>	First Aid Kit <input type="checkbox"/>	<input type="text"/>
Primary Operator	<input type="text"/>	Safety Glasses <input type="checkbox"/>	<input type="text"/>
Primary Op. Phone #	<input type="text"/>	Safety Hard Hat <input type="checkbox"/>	<input type="text"/>
Primary Op. E-mail	<input type="text"/>	Climbing Belt <input type="checkbox"/>	<input type="text"/>
Backup Operator	<input type="text"/>	Security Fence <input type="checkbox"/>	<input type="text"/>
Backup Op. Phone #	<input type="text"/>	Secure Shelter <input type="checkbox"/>	<input type="text"/>
Backup Op. E-mail	<input type="text"/>	Stable Entry Step <input type="checkbox"/>	<input type="text"/>
Shelter Working Room <input type="checkbox"/>	Make <input type="text"/>	Model <input type="text"/>	Shelter Size <input type="text"/>
Shelter Clean <input type="checkbox"/>	Notes	<input type="text" value="Small footprint site with enclosure for instruments only. No shelter."/>	
Site OK <input checked="" type="checkbox"/>	Notes	<input type="text"/>	
Driving Directions	<input type="text"/>		



# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID  Technician  Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km	<input type="text"/>	<input checked="" type="checkbox"/>
City > 50,000 population	40 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Feedlot operations	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Limited agricultural operations	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Large parking lot	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Small parking lot	100 m	<input type="text"/>	<input checked="" type="checkbox"/>
Tree line	50 m	<input type="text"/>	<input checked="" type="checkbox"/>
Obstacles to wind	10 times obstacle height	<input type="text"/>	<input checked="" type="checkbox"/>

Siting Distances OK

**Siting Criteria Comment**

# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID

Technician

Site Visit Date

- |    |  |                                     |     |
|----|--|-------------------------------------|-----|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> | N/A |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> | N/A |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> | N/A |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |     |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |     |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> | N/A |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> | N/A |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> | N/A |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> | N/A |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> | N/A |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | N/A |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

Technician

Site Visit Date

1	Do all the meteorological sensors appear to be intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	Temperature only
2	Are all the meteorological sensors operational online, and reporting data?	<input checked="" type="checkbox"/>	Temperature only
3	Are the shields for the temperature and RH sensors clean?	<input checked="" type="checkbox"/>	
4	Are the aspirated motors working?	<input checked="" type="checkbox"/>	N/A
5	Is the solar radiation sensor's lens clean and free of scratches?	<input checked="" type="checkbox"/>	N/A
6	Is the surface wetness sensor grid clean and undamaged?	<input checked="" type="checkbox"/>	N/A
7	Are the sensor signal and power cables intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	
8	Are the sensor signal and power cable connections protected from the elements and well maintained?	<input checked="" type="checkbox"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID

Technician

Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- |   |   |                                     |  |
|---|---|-------------------------------------|--|
| 1 | Do the sample inlets have at least a 270 degree arc of unrestricted airflow?          | <input checked="" type="checkbox"/> |  |
| 2 | Are the sample inlets 3 - 15 meters above the ground?                                 | <input checked="" type="checkbox"/> |  |
| 3 | Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees? | <input checked="" type="checkbox"/> |  |

**Pollutant analyzers and deposition equipment operations and maintenance**

- |   |  |                                     |                        |
|---|--|-------------------------------------|------------------------|
| 1 | Do the analyzers and equipment appear to be in good condition and well maintained? | <input checked="" type="checkbox"/> |                        |
| 2 | Are the analyzers and monitors operational, on-line, and reporting data?           | <input checked="" type="checkbox"/> |                        |
| 3 | Describe ozone sample tube.  |                                     | N/A                    |
| 4 | Describe dry dep sample tube.  |                                     | 3/8 teflon by 8 meters |
| 5 | Are in-line filters used in the ozone sample line? (if yes indicate location)      | <input checked="" type="checkbox"/> | N/A                    |
| 6 | Are sample lines clean, free of kinks, moisture, and obstructions?                 | <input checked="" type="checkbox"/> |                        |
| 7 | Is the zero air supply desiccant unsaturated?                                      | <input checked="" type="checkbox"/> | N/A                    |
| 8 | Are there moisture traps in the sample lines?                                      | <input type="checkbox"/>            |                        |
| 9 | Is there a rotometer in the dry deposition filter line, and is it clean?           | <input checked="" type="checkbox"/> |                        |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

1	Do the DAS instruments appear to be in good condition and well maintained?	<input checked="" type="checkbox"/>	
2	Are all the components of the DAS operational? (printers, modem, backup, etc)	<input checked="" type="checkbox"/>	
3	Do the analyzer and sensor signal leads pass through lightning protection circuitry?	<input checked="" type="checkbox"/>	
4	Are the signal connections protected from the weather and well maintained?	<input checked="" type="checkbox"/>	
5	Are the signal leads connected to the correct DAS channel?	<input checked="" type="checkbox"/>	
6	Are the DAS, sensor translators, and shelter properly grounded?	<input checked="" type="checkbox"/>	
7	Does the instrument shelter have a stable power source?	<input checked="" type="checkbox"/>	
8	Is the instrument shelter temperature controlled?	<input checked="" type="checkbox"/>	N/A
9	Is the met tower stable and grounded?	<input type="checkbox"/>	<input type="checkbox"/>
10	Is the sample tower stable and grounded?	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
11	Tower comments?	<input type="text"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Computer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Solar radiation sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Modem	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Printer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	UPS	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Ozone analyzer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Filter pack flow controller	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input checked="" type="checkbox"/>	Oct 2014	<input checked="" type="checkbox"/>
HASP	<input checked="" type="checkbox"/>	Oct 2014	<input checked="" type="checkbox"/>
Field Ops Manual	<input checked="" type="checkbox"/>	Oct 2014	<input checked="" type="checkbox"/>
Calibration Reports	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Preventive maintenance schedul	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>

- 1 Is the station log properly completed during every site visit?  No Logbook
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?  N/A

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

There is no site logbook and all manuals are kept electronically since the site is a small footprint site with no place to store hardcopies.

# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID  Technician  Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Automatic Precision Level Tests	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input type="checkbox"/>
Analyzer Diagnostics Tests	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Zero Air Desiccant Check	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID

Technician

Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed various times
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	Clean gloves on and off
9	Are the site conditions reported regularly to the field operations manager or staff?	<input checked="" type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input type="checkbox"/>	<input type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:



# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID

Technician

Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
DAS	Campbell	CR850	28383	none
elevation	Elevation	none	none	none
Filter pack flow pump	Thomas	1420 VP	42624821	none
Flow Rate	Apex	AXMC105LPMDPC	48100	000527
Infrastructure	Infrastructure	none	none	none
Modem	Sierra wireless	unknown	unknown	07000
Sample Tower	Aluma Tower	B	unknown	000813
siting criteria	Siting Criteria	none	None	none
Temperature	RM Young	41342	024087	06986

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>	
<i>WST109-Sandy Grenville-09/15/2016</i>						
1	9/15/2016	Computer	Dell	07026	Inspiron 15	2Z2MC12
2	9/15/2016	DAS	Campbell	000427	CR3000	2526
3	9/15/2016	Elevation	Elevation	None	1	None
4	9/15/2016	Filter pack flow pump	Thomas	00476	107CA18	000025705
5	9/15/2016	Flow Rate	Apex	000466	AXMC105LPMDPCV	43970
6	9/15/2016	Infrastructure	Infrastructure	none	none	none
7	9/15/2016	Modem	Raven	06598	V4221-V	0844349943
8	9/15/2016	Ozone	ThermoElectron Inc	000611	49i A1NAA	1009241795
9	9/15/2016	Ozone Standard	ThermoElectron Inc	000696	49i A3NAA	1030244812
10	9/15/2016	Sample Tower	Aluma Tower	missing	B	unknown
11	9/15/2016	Shelter Temperature	Campbell	none	107-L	none
12	9/15/2016	Siting Criteria	Siting Criteria	None	1	None
13	9/15/2016	Temperature	RM Young	04317	41342	4014
14	9/15/2016	Zero air pump	Werther International	06934	P 70/4	000821881

# DAS Data Form

DAS Time Max Error:

<b>Mfg</b>	<b>Serial Number</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Use Desc.</b>
Campbell	2526	WST109	Sandy Grenville	09/15/2016	DAS	Primary

<b>Das Date:</b>	<input type="text" value="9/15/2016"/>	<b>Audit Date</b>	<input type="text" value="9/15/2016"/>
<b>Das Time:</b>	<input type="text" value="13:11:00"/>	<b>Audit Time</b>	<input type="text" value="13:11:00"/>
<b>Das Day:</b>	<input type="text" value="259"/>	<b>Audit Day</b>	<input type="text" value="259"/>
<b>Low Channel:</b>		<b>High Channel:</b>	
<b>Avg Diff:</b>	<input type="text" value="0.0001"/>	<b>Max Diff:</b>	<input type="text" value="0.0002"/>
		<b>Avg Diff:</b>	<input type="text" value="0.0001"/>
		<b>Max Diff:</b>	<input type="text" value="0.0002"/>

<b>Mfg</b>	<input type="text" value="Datel"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="15510194"/>	<b>Tfer Desc.</b>	<input type="text" value="Source generator (D"/>
<b>Tfer ID</b>	<input type="text" value="01320"/>		
<b>Mfg</b>	<input type="text" value="Fluke"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="95740135"/>	<b>Tfer Desc.</b>	<input type="text" value="DVM"/>
<b>Tfer ID</b>	<input type="text" value="01311"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="12/23/2015"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
7	0.0000	-0.0001	0.0000	V	V	0.0001
7	0.1000	0.0998	0.0999	V	V	0.0001
7	0.3000	0.2996	0.2997	V	V	0.0001
7	0.5000	0.4994	0.4996	V	V	0.0002
7	0.7000	0.6993	0.6995	V	V	0.0002
7	0.9000	0.8993	0.8993	V	V	0.0000
7	1.0000	0.9992	0.9992	V	V	0.0000

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Apex	43970		WST109	Sandy Grenville	09/15/2016	Flow Rate	000466

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	103471	<b>Tfer Desc.</b>	nexus
<b>Tfer ID</b>	01420		
<b>Slope</b>	0.99091	<b>Intercept</b>	0.03172
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	0.99988
<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	103424	<b>Tfer Desc.</b>	BIOS cell
<b>Tfer ID</b>	01410		
<b>Slope</b>	0.99091	<b>Intercept</b>	0.03172
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	0.99988

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
1.92%	2.11%
<b>A Avg % Dif</b>	<b>A Max % Di</b>

<b>Cal Factor Zero</b>	0.002
<b>Cal Factor Full Scale</b>	1
<b>Rotometer Reading:</b>	1.5

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignal	PctDifference
primary	pump off	0.000	0.000	0.01	0.000	0.01	l/m	l/m	
primary	leak check	0.000	0.000	0.00	0.000	0.00	l/m	l/m	
primary	test pt 1	1.491	1.470	1.50	0.000	1.50	l/m	l/m	2.04%
primary	test pt 2	1.493	1.470	1.50	0.000	1.50	l/m	l/m	2.11%
primary	test pt 3	1.495	1.480	1.50	0.000	1.50	l/m	l/m	1.62%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	No moisture present	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	4.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	2.0 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	90 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1009241795		WST109	Sandy Grenville	09/15/2016	Ozone	000611

<b>Slope:</b>	0.99396	<b>Slope:</b>	0.00000
<b>Intercept</b>	0.48937	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99999	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
0.2%	0.3%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0419606966	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01112		
<b>Slope</b>	0.99524	<b>Intercept</b>	-0.33070
<b>Cert Date</b>	1/28/2016	<b>CorrCoff</b>	1.00000

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	-0.02	0.31	0.94	ppb	
primary	2	29.96	30.43	30.51	ppb	0.26%
primary	3	49.97	50.54	50.70	ppb	0.32%
primary	4	79.96	80.67	80.80	ppb	0.16%
primary	5	109.95	110.80	110.60	ppb	-0.18%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-0.20	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.005	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	91.2 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.9 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.74 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	717.9 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	35.6 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	91.9 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.9 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.75 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	717.6 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Temperature Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	4014		WST109	Sandy Grenville	09/15/2016	Temperature	04317

<b>Mfg</b>	Extech	<b>Parameter</b>	Temperature
<b>Serial Number</b>	H232734	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01227		
<b>Slope</b>	1.00772	<b>Intercept</b>	0.12514
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>		<b>DAS 2:</b>	
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>
0.11	0.21		

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Range	0.17	0.04	0.000	0.3	C	0.21
primary	Temp Mid Range	25.93	25.61	0.000	25.7	C	0.12
primary	Temp High Range	49.10	48.60	0.000	48.6	C	-0.01

<b>Sensor Component</b>	Shield	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Campbell	none	WST109	Sandy Grenville	09/15/2016	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
0.67	1.08		

<b>Mfg</b>	Extech	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	H232734	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01227		
<b>Slope</b>	1.00772	<b>Intercept</b>	0.12514
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Mid Range	30.11	29.76	0.000	29.1	C	-0.68
primary	Temp Mid Range	26.27	25.94	0.000	27.0	C	1.08
primary	Temp Mid Range	29.80	29.45	0.000	29.2	C	-0.26

<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
-------------------------	-------------	------------------	--	---------------	------

## Infrastructure Data For

Site ID  Technician  Site Visit Date

Shelter Make	Shelter Model	Shelter Size
<input type="text" value="Ekto"/>	<input type="text" value="8810 (s/n 2149-16)"/>	<input type="text" value="640 cuft"/>

Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text" value="Type B"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Functioning"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="3/8 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>



# Field Systems Comments

**1 Parameter:** DasComments

The sample tower has been replaced and the met tower removed since the previous audit visit.

**2 Parameter:** SiteOpsProcedures

Ozone sample train leak checks are being conducted every two weeks.

**3 Parameter:** SitingCriteriaCom

The site is in a small clearing surrounded by mountain forest. There is a small parking lot used by forest service employees located 50 meters from the site.

**4 Parameter:** SiteOKNotes

State of NH Department of Environmental Services contact is Tom Fazzina (603) 271-0911 and tfazzina@DES.state.NH.US

**5 Parameter:** MetSensorComme

The temperature sensor is now mounted in a naturally aspirated shield on the sample tower.

# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)  USGS Map   
 Operating Group  Map Scale   
 AQS #  Map Date

Meteorological Type   
 Air Pollutant Analyzer  QAPP Latitude

Deposition Measurement  QAPP Longitude   
 Land Use  QAPP Elevation Meters

Terrain  QAPP Declination   
 Conforms to MLM  QAPP Declination Date

Site Telephone  Audit Latitude   
 Site Address 1  Audit Longitude

Site Address 2   
 County  Audit Elevation   
 City, State  Audit Declination

Zip Code  Present  
 Time Zone  Fire Extinguisher

Primary Operator  First Aid Kit   
 Primary Op. Phone #  Safety Glasses

Primary Op. E-mail  Safety Hard Hat   
 Backup Operator  Climbing Belt

Backup Op. Phone #  Security Fence   
 Backup Op. E-mail  Secure Shelter

Backup Op. E-mail  Stable Entry Step   
 Shelter Working Room  Make  Model  Shelter Size

Shelter Clean  Notes   
 Site OK  Notes

Driving Directions

# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID  Technician  Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km		<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km		<input checked="" type="checkbox"/>
City > 50,000 population	40 km		<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km		<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km		<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km		<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m		<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m		<input checked="" type="checkbox"/>
Feedlot operations	500 m		<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m		<input checked="" type="checkbox"/>
Limited agricultural operations	200 m		<input checked="" type="checkbox"/>
Large parking lot	200 m		<input checked="" type="checkbox"/>
Small parking lot	100 m	50 m	<input type="checkbox"/>
Tree line	50 m	10 - 30 m	<input type="checkbox"/>
Obstacles to wind	10 times obstacle height		<input checked="" type="checkbox"/>

Siting Distances OK

**Siting Criteria Comment**

The site is in a small clearing surrounded by mountain forest. There is a small parking lot used by forest service employees located 50 meters from the site.

# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID

Technician

Site Visit Date

- |    |  |                                     |     |
|----|--|-------------------------------------|-----|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> | N/A |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> | N/A |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> | N/A |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |     |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |     |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> | N/A |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> | N/A |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> | N/A |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> | N/A |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> | N/A |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | N/A |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

The temperature sensor is now mounted in a naturally aspirated shield on the sample tower.

# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

Technician

Site Visit Date

1	Do all the meteorological sensors appear to be intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	Temperature only
2	Are all the meteorological sensors operational online, and reporting data?	<input checked="" type="checkbox"/>	Temperature only
3	Are the shields for the temperature and RH sensors clean?	<input checked="" type="checkbox"/>	Moderately clean
4	Are the aspirated motors working?	<input checked="" type="checkbox"/>	N/A
5	Is the solar radiation sensor's lens clean and free of scratches?	<input checked="" type="checkbox"/>	N/A
6	Is the surface wetness sensor grid clean and undamaged?	<input checked="" type="checkbox"/>	N/A
7	Are the sensor signal and power cables intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	
8	Are the sensor signal and power cable connections protected from the elements and well maintained?	<input checked="" type="checkbox"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID

Technician

Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- 1 Do the sample inlets have at least a 270 degree arc of unrestricted airflow?
- 2 Are the sample inlets 3 - 15 meters above the ground?
- 3 Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees?


**Pollutant analyzers and deposition equipment operations and maintenance**

- 1 Do the analyzers and equipment appear to be in good condition and well maintained?
- 2 Are the analyzers and monitors operational, on-line, and reporting data?
- 3 Describe ozone sample tube.
- 4 Describe dry dep sample tube.
- 5 Are in-line filters used in the ozone sample line? (if yes indicate location)
- 6 Are sample lines clean, free of kinks, moisture, and obstructions?
- 7 Is the zero air supply desiccant unsaturated?
- 8 Are there moisture traps in the sample lines?
- 9 Is there a rotometer in the dry deposition filter line, and is it clean?

1/4 teflon by 15 meters
3/8 teflon by 15 meters
At inlet only
Flow line only
Clean and dry

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

--

# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

- |                                     |  |   |                   |                 |                          |                          |                                     |                                     |  |
|-------------------------------------|--|---|-------------------|-----------------|--------------------------|--------------------------|-------------------------------------|-------------------------------------|--|
| 1                                   | Do the DAS instruments appear to be in good condition and well maintained?           | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 2                                   | Are all the components of the DAS operational? (printers, modem, backup, etc)        | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 3                                   | Do the analyzer and sensor signal leads pass through lightning protection circuitry? | <input checked="" type="checkbox"/>   | Met sensors only  |                 |                          |                          |                                     |                                     |  |
| 4                                   | Are the signal connections protected from the weather and well maintained?           | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 5                                   | Are the signal leads connected to the correct DAS channel?                           | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 6                                   | Are the DAS, sensor translators, and shelter properly grounded?                      | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 7                                   | Does the instrument shelter have a stable power source?                              | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 8                                   | Is the instrument shelter temperature controlled?                                    | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 9                                   | Is the met tower stable and grounded?  | <table border="1"><tr><td><b>Stable</b></td><td><b>Grounded</b></td></tr><tr><td><input type="checkbox"/></td><td><input type="checkbox"/></td></tr><tr><td><input checked="" type="checkbox"/></td><td><input checked="" type="checkbox"/></td></tr></table> | <b>Stable</b>     | <b>Grounded</b> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |  |
| <b>Stable</b>                       | <b>Grounded</b>  |   |                   |                 |                          |                          |                                     |                                     |  |
| <input type="checkbox"/>            | <input type="checkbox"/>   |   |                   |                 |                          |                          |                                     |                                     |  |
| <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/>  |   |                   |                 |                          |                          |                                     |                                     |  |
| 10                                  | Is the sample tower stable and grounded?   |   |                   |                 |                          |                          |                                     |                                     |  |
| 11                                  | Tower comments?  |   | Met tower removed |                 |                          |                          |                                     |                                     |  |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

The sample tower has been replaced and the met tower removed since the previous audit visit.

# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Computer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Solar radiation sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Modem	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Printer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	UPS	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Ozone analyzer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack flow controller	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input checked="" type="checkbox"/>	Oct 2001	<input type="checkbox"/>
HASP	<input checked="" type="checkbox"/>	Nov 2014	<input checked="" type="checkbox"/>
Field Ops Manual	<input checked="" type="checkbox"/>	July 1990	<input type="checkbox"/>
Calibration Reports	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Preventive maintenance schedul	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>

- 1 Is the station log properly completed during every site visit?
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?  Control charts not used

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:



# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID  Technician  Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="As needed"/>	<input checked="" type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input checked="" type="checkbox"/>	<input type="text" value="As needed"/>	<input checked="" type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Every 2 weeks"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Zero Air Desiccant Check	<input checked="" type="checkbox"/>	<input type="text" value="Every 2 weeks"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID

Technician

Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed morinings
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF, logbook
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF, logbook, call-in
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	Clean gloves on and off
9	Are the site conditions reported regularly to the field operations manager or staff?	<input checked="" type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input type="checkbox"/>	<input type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID

Technician

Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
Computer	Dell	Inspiron 15	2Z2MC12	07026
DAS	Campbell	CR3000	2526	000427
Elevation	Elevation	1	None	None
Filter pack flow pump	Thomas	107CA18	000025705	00476
Flow Rate	Apex	AXMC105LPMDPC	43970	000466
Infrastructure	Infrastructure	none	none	none
Modem	Raven	V4221-V	0844349943	06598
Ozone	ThermoElectron Inc	49i A1NAA	1009241795	000611
Ozone Standard	ThermoElectron Inc	49i A3NAA	1030244812	000696
Sample Tower	Aluma Tower	B	unknown	missing
Shelter Temperature	Campbell	107-L	none	none
Siting Criteria	Siting Criteria	1	None	None
Temperature	RM Young	41342	4014	04317
Zero air pump	Werther International	P 70/4	000821881	06934

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>	
<i>ABT147-Sandy Grenville-09/17/2016</i>						
1	9/17/2016	Computer	Dell	07023	Inspiron 15	5C4MC12
2	9/17/2016	DAS	Campbell	000413	CR3000	2519
3	9/17/2016	Elevation	Elevation	None	1	None
4	9/17/2016	Filter pack flow pump	Thomas	02974	107CAB18	0493002469
5	9/17/2016	Flow Rate	Apex	000550	AXMC105LPMDPCV	50740
6	9/17/2016	Infrastructure	Infrastructure	none	none	none
7	9/17/2016	Modem	Raven	06609	H4223-C	0844356221
8	9/17/2016	Ozone	ThermoElectron Inc	000627	49i A1NAA	1009241772
9	9/17/2016	Ozone Standard	ThermoElectron Inc	000449	49i A3NAA	CM08200025
10	9/17/2016	Sample Tower	Aluma Tower	000017	B	AT-61152-A-H8-C
11	9/17/2016	Shelter Temperature	Campbell	none	107-L	none
12	9/17/2016	Siting Criteria	Siting Criteria	None	1	None
13	9/17/2016	Temperature	RM Young	06503	41342	14623
14	9/17/2016	Zero air pump	Werther International	06930	P 70/4	000829168

# DAS Data Form

DAS Time Max Error:

<b>Mfg</b>	<b>Serial Number</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Use Desc.</b>
Campbell	2519	ABT147	Sandy Grenville	09/17/2016	DAS	Primary

<b>Das Date:</b>	<input type="text" value="9/17/2016"/>	<b>Audit Date</b>	<input type="text" value="9/17/2016"/>
<b>Das Time:</b>	<input type="text" value="12:36:00"/>	<b>Audit Time</b>	<input type="text" value="12:36:00"/>
<b>Das Day:</b>	<input type="text" value="261"/>	<b>Audit Day</b>	<input type="text" value="261"/>
<b>Low Channel:</b>		<b>High Channel:</b>	
<b>Avg Diff:</b>	<input type="text" value="0.0001"/>	<b>Max Diff:</b>	<input type="text" value="0.0001"/>
		<b>Avg Diff:</b>	<input type="text" value="0.0001"/>
		<b>Max Diff:</b>	<input type="text" value="0.0001"/>

<b>Mfg</b>	<input type="text" value="Datel"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="15510194"/>	<b>Tfer Desc.</b>	<input type="text" value="Source generator (D"/>
<b>Tfer ID</b>	<input type="text" value="01320"/>		
<b>Mfg</b>	<input type="text" value="Fluke"/>	<b>Parameter</b>	<input type="text" value="DAS"/>
<b>Serial Number</b>	<input type="text" value="95740135"/>	<b>Tfer Desc.</b>	<input type="text" value="DVM"/>
<b>Tfer ID</b>	<input type="text" value="01311"/>		
<b>Slope</b>	<input type="text" value="1.00000"/>	<b>Intercept</b>	<input type="text" value="0.00000"/>
<b>Cert Date</b>	<input type="text" value="12/23/2015"/>	<b>CorrCoff</b>	<input type="text" value="1.00000"/>

Channel	Input	DVM Output	DAS Output	InputUnit	OutputUnit	Difference
7	0.0000	-0.0001	0.0000	V	V	0.0001
7	0.1000	0.0998	0.0999	V	V	0.0001
7	0.3000	0.2996	0.2997	V	V	0.0001
7	0.5000	0.4995	0.4996	V	V	0.0001
7	0.7000	0.6995	0.6995	V	V	0.0000
7	0.9000	0.8993	0.8993	V	V	0.0000
7	1.0000	0.9992	0.9992	V	V	0.0000

# Flow Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
Apex	50740		ABT147	Sandy Grenville	09/17/2016	Flow Rate	000550

<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	103471	<b>Tfer Desc.</b>	nexus
<b>Tfer ID</b>	01420		
<b>Slope</b>	0.99091	<b>Intercept</b>	0.03172
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	0.99988
<b>Mfg</b>	BIOS	<b>Parameter</b>	Flow Rate
<b>Serial Number</b>	103424	<b>Tfer Desc.</b>	BIOS cell
<b>Tfer ID</b>	01410		
<b>Slope</b>	0.99091	<b>Intercept</b>	0.03172
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	0.99988

<b>DAS 1:</b>	<b>DAS 2:</b>
<b>A Avg % Diff:</b>	<b>A Max % Di</b>
0.44%	0.66%
<b>A Avg %Dif</b>	<b>A Max % Di</b>

<b>Cal Factor Zero</b>	-0.04
<b>Cal Factor Full Scale</b>	0.98
<b>Rotometer Reading:</b>	1.5

Desc.	Test type	Input l/m	Input Corr_	MfcDisp.	OutputSignal	Output S E	InputUnit	OutputSignal	PctDifference
primary	pump off	0.000	0.000	0.01	0.000	-0.03	l/m	l/m	
primary	leak check	0.000	0.000	0.03	0.000	0.00	l/m	l/m	
primary	test pt 1	1.521	1.500	1.52	0.000	1.50	l/m	l/m	0.00%
primary	test pt 2	1.524	1.510	1.51	0.000	1.50	l/m	l/m	-0.66%
primary	test pt 3	1.526	1.510	1.51	0.000	1.50	l/m	l/m	-0.66%

<b>Sensor Component</b>	Leak Test	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Tubing Condition	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Position	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	Rotometer Condition	<b>Condition</b>	Clean and dry	<b>Status</b>	pass
<b>Sensor Component</b>	Moisture Present	<b>Condition</b>	See comments	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Distance	<b>Condition</b>	4.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Depth	<b>Condition</b>	1.5 cm	<b>Status</b>	pass
<b>Sensor Component</b>	Filter Azimuth	<b>Condition</b>	250 deg	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1009241772		ABT147	Sandy Grenville	09/17/2016	Ozone	000627

<b>Slope:</b>	0.97593	<b>Slope:</b>	0.00000
<b>Intercept</b>	0.31758	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99999	<b>CorrCoff</b>	0.00000

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0419606966	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01112		
<b>Slope</b>	0.99524	<b>Intercept</b>	-0.33070
<b>Cert Date</b>	1/28/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
1.9%	2.3%		

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	0.01	0.34	0.74	ppb	
primary	2	29.99	30.46	30.11	ppb	-1.15%
primary	3	49.99	50.56	49.42	ppb	-2.25%
primary	4	80.00	80.71	79.06	ppb	-2.04%
primary	5	109.99	110.84	108.60	ppb	-2.02%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.20	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	0.997	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	89.3 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.9 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.70 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	717.4 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	38.4 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	94.2 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.9 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.67 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	717.4 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

# Temperature Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
RM Young	14623		ABT147	Sandy Grenville	09/17/2016	Temperature	06503

<b>Mfg</b>	Extech	<b>Parameter</b>	Temperature
<b>Serial Number</b>	H232734	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01227		
<b>Slope</b>	1.00772	<b>Intercept</b>	0.12514
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>		<b>DAS 2:</b>	
<b>Abs Avg Err</b>	<b>Abs Max Er</b>	<b>Abs Avg Err</b>	<b>Abs Max Er</b>
0.80	1.67		

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Low Range	0.18	0.05	0.000	0.0	C	-0.01
primary	Temp Mid Range	26.02	25.70	0.000	25.0	C	-0.73
primary	Temp High Range	49.58	49.08	0.000	47.4	C	-1.67

<b>Sensor Component</b>	Shield	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Blower	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Blower Status Switch	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass



# Shelter Temperature Data For

Mfg	Serial Number	Ta Site	Technician	Site Visit Date	Parameter	Owner ID
Campbell	none	ABT147	Sandy Grenville	09/17/2016	Shelter Temperature	none

DAS 1:		DAS 2:	
Abs Avg Err	Abs Max Er	Abs Avg Err	Abs Max Er
0.28	0.37		

<b>Mfg</b>	Extech	<b>Parameter</b>	Shelter Temperatur
<b>Serial Number</b>	H232734	<b>Tfer Desc.</b>	RTD
<b>Tfer ID</b>	01227		
<b>Slope</b>	1.00772	<b>Intercept</b>	0.12514
<b>Cert Date</b>	2/28/2016	<b>CorrCoff</b>	1.00000

UseDesc.	Test type	InputTmpRaw	InputTmpCorr.	OutputTmpSignal	OutputSignalEng	OSE Unit	Difference
primary	Temp Mid Range	27.40	27.07	0.000	27.3	C	0.2
primary	Temp Mid Range	27.59	27.25	0.000	27.5	C	0.26
primary	Temp Mid Range	26.41	26.08	0.000	25.7	C	-0.37

<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass
-------------------------	-------------	------------------	--	---------------	------

## Infrastructure Data For

Site ID  Technician  Site Visit Date

Shelter Make	Shelter Model	Shelter Size
<input type="text" value="Ekto"/>	<input type="text" value="8810 (s/n 2149-9)"/>	<input type="text" value="640 cuft"/>

Sensor Component	<input type="text" value="Sample Tower Type"/>	Condition	<input type="text" value="Type B"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Conduit"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Met Tower"/>	Condition	<input type="text" value="N/A"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Moisture Trap"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Power Cables"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Temp Control"/>	Condition	<input type="text" value="Functioning"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Rotometer"/>	Condition	<input type="text" value="Installed"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Tower"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Condition"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Door"/>	Condition	<input type="text" value="Fair"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Roof"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Shelter Floor"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Signal Cable"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Tubing Type"/>	Condition	<input type="text" value="3/8 teflon"/>	Status	<input type="text" value="pass"/>
Sensor Component	<input type="text" value="Sample Train"/>	Condition	<input type="text" value="Good"/>	Status	<input type="text" value="pass"/>

# Site Visit Comments

<b>Parameter</b>	<b>Site</b>	<b>Technician</b>	<b>S.V. Date</b>	<b>Component</b>	<b>Mfg</b>	<b>Serial No.</b>	<b>Hazard</b>	<b>Problem</b>
Flow Rate	ABT147	Sandy Grenville	09/17/2016	Moisture Present	Apex	3683	<input type="checkbox"/>	<input type="checkbox"/>
The filter sample tubing has drops of moisture in low sections outside the shelter.								

# Field Systems Comments

1 **Parameter:** DasComments

The met tower has been removed.

2 **Parameter:** SitingCriteriaCom

Manure is routinely spread on the hay fields surrounding the site during the summer.

3 **Parameter:** ShelterCleanNotes

The shelter is clean and well organized.

4 **Parameter:** MetSensorComme

Temperature mounted in naturally aspirated shield on sample tower.

# Field Systems Data Form

F-02058-1500-S1-rev002

Site ID  Technician  Site Visit Date

Site Sponsor (agency)	<input type="text" value="EPA"/>	USGS Map	<input type="text" value="Hampton"/>
Operating Group	<input type="text" value="private"/>	Map Scale	<input type="text"/>
AQS #	<input type="text" value="09-015-9991"/>	Map Date	<input type="text"/>
Meteorological Type	<input type="text" value="R.M. Young"/>		
Air Pollutant Analyzer	<input type="text" value="Ozone"/>	QAPP Latitude	<input type="text" value="41.8402"/>
Deposition Measurement	<input type="text" value="dry, wet"/>	QAPP Longitude	<input type="text" value="-72.0111"/>
Land Use	<input type="text" value="agriculture, woodland - mixed"/>	QAPP Elevation Meters	<input type="text" value="209"/>
Terrain	<input type="text" value="rolling"/>	QAPP Declination	<input type="text" value="14.8"/>
Conforms to MLM	<input type="text" value="Marginally"/>	QAPP Declination Date	<input type="text" value="2/22/2006"/>
Site Telephone	<input type="text" value="(860) 974-2273"/>	Audit Latitude	<input type="text" value="41.84046"/>
Site Address 1	<input type="text" value="80 Ayers Road"/>	Audit Longitude	<input type="text" value="-72.010368"/>
Site Address 2	<input type="text"/>	Audit Elevation	<input type="text" value="202"/>
County	<input type="text" value="Windham"/>	Audit Declination	<input type="text" value="-14.5"/>
City, State	<input type="text" value="Abington, CT"/>		
Zip Code	<input type="text" value="06230"/>	<b>Present</b>	
Time Zone	<input type="text" value="Eastern"/>	Fire Extinguisher <input checked="" type="checkbox"/>	<input type="text" value="New in 2015"/>
Primary Operator	<input type="text"/>	First Aid Kit <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. Phone #	<input type="text"/>	Safety Glasses <input checked="" type="checkbox"/>	<input type="text"/>
Primary Op. E-mail	<input type="text"/>	Safety Hard Hat <input checked="" type="checkbox"/>	<input type="text"/>
Backup Operator	<input type="text"/>	Climbing Belt <input type="checkbox"/>	<input type="text"/>
Backup Op. Phone #	<input type="text"/>	Security Fence <input type="checkbox"/>	<input type="text"/>
Backup Op. E-mail	<input type="text"/>	Secure Shelter <input checked="" type="checkbox"/>	<input type="text"/>
		Stable Entry Step <input checked="" type="checkbox"/>	<input type="text"/>
Shelter Working Room <input checked="" type="checkbox"/>	Make <input type="text" value="Ekto"/>	Model <input type="text" value="8810 (s/n 2149-9)"/>	Shelter Size <input type="text" value="640 cuft"/>
Shelter Clean <input checked="" type="checkbox"/>	Notes <input type="text" value="The shelter is clean and well organized."/>		
Site OK <input checked="" type="checkbox"/>	Notes <input type="text"/>		

**Driving Directions**

# Field Systems Data Form

F-02058-1500-S2-rev002

Site ID

Technician

Site Visit Date

Potential Interferent	Minimum Distance From Measurement Apparatus	Distance	Pass = Checked
Large Point Source of SO2 or NOx	20 to 40 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major industrial complex	10 to 20 km	<input type="text"/>	<input checked="" type="checkbox"/>
City > 50,000 population	40 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 10,000 to 50,000 population	10 km	<input type="text"/>	<input checked="" type="checkbox"/>
City 1,000 to 10,000 population	5 km	<input type="text"/>	<input checked="" type="checkbox"/>
Major highway, airport or rail yard	2 km	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, heavily traveled	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Secondary road, lightly traveled	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Feedlot operations	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Intensive agricultural ops (including aerial spraying)	500 m	<input type="text"/>	<input checked="" type="checkbox"/>
Limited agricultural operations	200 m	<input type="text" value="10 m"/>	<input type="checkbox"/>
Large parking lot	200 m	<input type="text"/>	<input checked="" type="checkbox"/>
Small parking lot	100 m	<input type="text"/>	<input checked="" type="checkbox"/>
Tree line	50 m	<input type="text"/>	<input checked="" type="checkbox"/>
Obstacles to wind	10 times obstacle height	<input type="text"/>	<input checked="" type="checkbox"/>

Siting Distances OK

Siting Criteria Comment

# Field Systems Data Form

F-02058-1500-S3-rev002

Site ID

Technician

Site Visit Date

- |    |  |                                     |     |
|----|--|-------------------------------------|-----|
| 1  | Are wind speed and direction sensors sited so as to avoid being influenced by obstructions?  | <input checked="" type="checkbox"/> | N/A |
| 2  | Are wind sensors mounted so as to minimize tower effects? (i.e. wind sensors should be mounted atop the tower or on a horizontally extended boom >2x the max diameter of the tower into the prevailing wind)     | <input checked="" type="checkbox"/> | N/A |
| 3  | Are the tower and sensors plumb?   | <input checked="" type="checkbox"/> | N/A |
| 4  | Are the temperature shields pointed north or positioned to avoid radiated heat sources such as buildings, walls, etc?  | <input checked="" type="checkbox"/> |     |
| 5  | Are temperature and RH sensors sited to avoid unnatural conditions? (i.e. ground below sensors should be natural surface and not steeply sloped. Ridges, hollows, and areas of standing water should be avoided) | <input checked="" type="checkbox"/> |     |
| 6  | Is the solar radiation sensor plumb?   | <input checked="" type="checkbox"/> | N/A |
| 7  | Is it sited to avoid shading, or any artificial or reflected light?  | <input checked="" type="checkbox"/> | N/A |
| 8  | Is the rain gauge plumb?   | <input checked="" type="checkbox"/> | N/A |
| 9  | Is it sited to avoid sheltering effects from buildings, trees, towers, etc?  | <input checked="" type="checkbox"/> | N/A |
| 10 | Is the surface wetness sensor sited with the grid surface facing north?  | <input checked="" type="checkbox"/> | N/A |
| 11 | Is it inclined approximately 30 degrees?   | <input checked="" type="checkbox"/> | N/A |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S4-rev002

Site ID

Technician

Site Visit Date

1	Do all the meteorological sensors appear to be intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	N/A
2	Are all the meteorological sensors operational online, and reporting data?	<input checked="" type="checkbox"/>	N/A
3	Are the shields for the temperature and RH sensors clean?	<input checked="" type="checkbox"/>	
4	Are the aspirated motors working?	<input checked="" type="checkbox"/>	N/A
5	Is the solar radiation sensor's lens clean and free of scratches?	<input checked="" type="checkbox"/>	N/A
6	Is the surface wetness sensor grid clean and undamaged?	<input checked="" type="checkbox"/>	N/A
7	Are the sensor signal and power cables intact, in good condition, and well maintained?	<input checked="" type="checkbox"/>	
8	Are the sensor signal and power cable connections protected from the elements and well maintained?	<input checked="" type="checkbox"/>	

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:



# Field Systems Data Form

F-02058-1500-S5-rev002

Site ID

Technician

Site Visit Date

**Siting Criteria: Are the pollutant analyzers and deposition equipment sited in accordance with 40 CFR 58, Appendix E**

- 1 Do the sample inlets have at least a 270 degree arc of unrestricted airflow?
- 2 Are the sample inlets 3 - 15 meters above the ground?
- 3 Are the sample inlets > 1 meter from any major obstruction, and 20 meters from trees?


**Pollutant analyzers and deposition equipment operations and maintenance**

- 1 Do the analyzers and equipment appear to be in good condition and well maintained?
- 2 Are the analyzers and monitors operational, on-line, and reporting data?
- 3 Describe ozone sample tube.
- 4 Describe dry dep sample tube.
- 5 Are in-line filters used in the ozone sample line? (if yes indicate location)
- 6 Are sample lines clean, free of kinks, moisture, and obstructions?
- 7 Is the zero air supply desiccant unsaturated?
- 8 Are there moisture traps in the sample lines?
- 9 Is there a rotometer in the dry deposition filter line, and is it clean?

1/4 teflon by 15 meters
3/8 teflon by 15 meters
At inlet only
Moisture in tubing only
Flow line only
Clean and dry

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

--

# Field Systems Data Form

F-02058-1500-S6-rev002

Site ID

Technician

Site Visit Date

## DAS, sensor translators, and peripheral equipment operations and maintenance

- |                                     |  |   |                   |                 |                          |                          |                                     |                                     |  |
|-------------------------------------|--|---|-------------------|-----------------|--------------------------|--------------------------|-------------------------------------|-------------------------------------|--|
| 1                                   | Do the DAS instruments appear to be in good condition and well maintained?           | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 2                                   | Are all the components of the DAS operational? (printers, modem, backup, etc)        | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 3                                   | Do the analyzer and sensor signal leads pass through lightning protection circuitry? | <input checked="" type="checkbox"/>   | Met sensors only  |                 |                          |                          |                                     |                                     |  |
| 4                                   | Are the signal connections protected from the weather and well maintained?           | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 5                                   | Are the signal leads connected to the correct DAS channel?                           | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 6                                   | Are the DAS, sensor translators, and shelter properly grounded?                      | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 7                                   | Does the instrument shelter have a stable power source?                              | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 8                                   | Is the instrument shelter temperature controlled?                                    | <input checked="" type="checkbox"/>   |                   |                 |                          |                          |                                     |                                     |  |
| 9                                   | Is the met tower stable and grounded?  | <table border="1"><tr><td><b>Stable</b></td><td><b>Grounded</b></td></tr><tr><td><input type="checkbox"/></td><td><input type="checkbox"/></td></tr><tr><td><input checked="" type="checkbox"/></td><td><input checked="" type="checkbox"/></td></tr></table> | <b>Stable</b>     | <b>Grounded</b> | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |  |
| <b>Stable</b>                       | <b>Grounded</b>  |   |                   |                 |                          |                          |                                     |                                     |  |
| <input type="checkbox"/>            | <input type="checkbox"/>   |   |                   |                 |                          |                          |                                     |                                     |  |
| <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/>  |   |                   |                 |                          |                          |                                     |                                     |  |
| 10                                  | Is the sample tower stable and grounded?   |   |                   |                 |                          |                          |                                     |                                     |  |
| 11                                  | Tower comments?  |   | Met tower removed |                 |                          |                          |                                     |                                     |  |

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S7-rev002

Site ID

Technician

Site Visit Date

**Documentation**

**Does the site have the required instrument and equipment manuals?**

	Yes	No	N/A		Yes	No	N/A
Wind speed sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wind direction sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Data logger	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Temperature sensor	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Strip chart recorder	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Relative humidity sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Computer	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Solar radiation sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Modem	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Surface wetness sensor	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Printer	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Wind sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Zero air pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Temperature translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Filter flow pump	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Humidity sensor translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Surge protector	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Solar radiation translator	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	UPS	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Tipping bucket rain gauge	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Lightning protection device	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Ozone analyzer	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Shelter heater	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack flow controller	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Shelter air conditioner	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Filter pack MFC power supply	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>				

**Does the site have the required and most recent QC documents and report forms?**

	Present		Current
Station Log	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
SSRF	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Site Ops Manual	<input checked="" type="checkbox"/>	Sept 2016	<input checked="" type="checkbox"/>
HASP	<input checked="" type="checkbox"/>	Sept 2016	<input checked="" type="checkbox"/>
Field Ops Manual	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Calibration Reports	<input checked="" type="checkbox"/>	<input type="text"/>	<input checked="" type="checkbox"/>
Ozone z/s/p Control Charts	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>
Preventive maintenance schedul	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>

- 1 Is the station log properly completed during every site visit?
- 2 Are the Site Status Report Forms being completed and current?
- 3 Are the chain-of-custody forms properly used to document sample transfer to and from lab?
- 4 Are ozone z/s/p control charts properly completed and current?  Control charts not used

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S8-rev002

Site ID

Technician

Site Visit Date

**Site operation procedures**

- 1 Has the site operator attended a formal CASTNET training course? If yes, when and who instructed?
- 2 Has the backup operator attended a formal CASTNET training course? If yes, when and who instructed?
- 3 Is the site visited regularly on the required Tuesday schedule?
- 4 Are the standard CASTNET operational procedures being followed by the site operator?
- 5 Is the site operator(s) knowledgeable of, and able to perform the required site activities? (including documentation)

**Are regular operational QA/QC checks performed on meteorological instruments?**

QC Check Performed		Frequency	Compliant
Multipoint Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Visual Inspections	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Translator Zero/Span Tests (climatronics)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Manual Rain Gauge Test	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Confirm Reasonableness of Current Values	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Test Surface Wetness Response	<input checked="" type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>

**Are regular operational QA/QC checks performed on the ozone analyzer?**

QC Check Performed		Frequency	Compliant
Multi-point Calibrations	<input checked="" type="checkbox"/>	<input type="text" value="Semiannually"/>	<input checked="" type="checkbox"/>
Automatic Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Zero/Span Tests	<input checked="" type="checkbox"/>	<input type="text" value="As needed"/>	<input checked="" type="checkbox"/>
Automatic Precision Level Tests	<input checked="" type="checkbox"/>	<input type="text" value="Daily"/>	<input checked="" type="checkbox"/>
Manual Precision Level Test	<input checked="" type="checkbox"/>	<input type="text" value="As needed"/>	<input checked="" type="checkbox"/>
Analyzer Diagnostics Tests	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at inlet)	<input checked="" type="checkbox"/>	<input type="text" value="Every 2 weeks"/>	<input checked="" type="checkbox"/>
In-line Filter Replacement (at analyze)	<input type="checkbox"/>	<input type="text" value="N/A"/>	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>
Zero Air Desiccant Check	<input checked="" type="checkbox"/>	<input type="text" value="Weekly"/>	<input checked="" type="checkbox"/>

- 1 Do multi-point calibration gases go through the complete sample train including all filters?
- 2 Do automatic and manual z/s/p gasses go through the complete sample train including all filters?
- 3 Are the automatic and manual z/s/p checks monitored and reported? If yes, how?

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S9-rev002

Site ID

Technician

Site Visit Date

Site operation procedures

1	Is the filter pack being changed every Tuesday as scheduled?	<input checked="" type="checkbox"/>	Filter changed morinings
2	Are the Site Status Report Forms being completed and filed correctly?	<input checked="" type="checkbox"/>	
3	Are data downloads and backups being performed as scheduled?	<input type="checkbox"/>	No longer required
4	Are general observations being made and recorded? How?	<input checked="" type="checkbox"/>	SSRF, logbook
5	Are site supplies on-hand and replenished in a timely fashion?	<input checked="" type="checkbox"/>	
6	Are sample flow rates recorded? How?	<input checked="" type="checkbox"/>	SSRF, logbook, call-in
7	Are samples sent to the lab on a regular schedule in a timely fashion?	<input checked="" type="checkbox"/>	
8	Are filters protected from contamination during handling and shipping? How?	<input checked="" type="checkbox"/>	Clean gloves on and off
9	Are the site conditions reported regularly to the field operations manager or staff?	<input checked="" type="checkbox"/>	

QC Check Performed	Frequency	Compliant
Multi-point MFC Calibrations	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Flow System Leak Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Filter Pack Inspection	<input type="checkbox"/>	<input type="checkbox"/>
Flow Rate Setting Checks	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
Visual Check of Flow Rate Rotometer	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>
In-line Filter Inspection/Replacement	<input checked="" type="checkbox"/> Semiannually	<input checked="" type="checkbox"/>
Sample Line Check for Dirt/Water	<input checked="" type="checkbox"/> Weekly	<input checked="" type="checkbox"/>

Provide any additional explanation (photograph or sketch if necessary) regarding conditions listed above, or any other features, natural or man-made, that may affect the monitoring parameters:

# Field Systems Data Form

F-02058-1500-S10-rev002

Site ID

Technician

Site Visit Date

## Site Visit Sensors

Parameter	Manufacturer	Model	S/N	Client ID
Computer	Dell	Inspiron 15	5C4MC12	07023
DAS	Campbell	CR3000	2519	000413
Elevation	Elevation	1	None	None
Filter pack flow pump	Thomas	107CAB18	0493002469	02974
Flow Rate	Apex	AXMC105LPMDPC	50740	000550
Infrastructure	Infrastructure	none	none	none
Modem	Raven	H4223-C	0844356221	06609
Ozone	ThermoElectron Inc	49i A1NAA	1009241772	000627
Ozone Standard	ThermoElectron Inc	49i A3NAA	CM08200025	000449
Sample Tower	Aluma Tower	B	AT-61152-A-H8-C	000017
Shelter Temperature	Campbell	107-L	none	none
Siting Criteria	Siting Criteria	1	None	None
Temperature	RM Young	41342	14623	06503
Zero air pump	Werther International	P 70/4	000829168	06930

---

**APPENDIX B**

**CASTNET Site Spot Report Forms**

---

# EEMS Spot Report

Data Compiled: #####

SiteVisitDate	Site	Technician
09/17/2016	ABT147	Sandy Grenville

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature average error	P	4	0.5	12	0.80	c	Fail
2	Temperature max error	P	4	0.5	12	1.67	c	Fail
3	Ozone Slope	P	0	1.1	4	0.97593	unitless	P
4	Ozone Intercept	P	0	5	4	0.31758	ppb	P
5	Ozone correlation	P	0	0.995	4	0.99999	unitless	P
6	Ozone % difference avg	P	7	10	4	1.9	%	P
7	Ozone % difference max	P	7	10	4	2.3	%	P
8	Flow Rate average % difference	P	10	5	3	0.44	%	P
9	Flow Rate max % difference	P	10	5	3	0.66	%	P
10	DAS Time maximum error	P	0	5	1	0.00	min	P
11	DAS Voltage average error	P	7	0.003	42	0.0001	V	P
12	Shelter Temperature average error	P	5	2	12	0.28	c	P
13	Shelter Temperature max error	P	5	2	12	0.37	c	P

## Records without valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	DAS Voltage maximum error		7	0	42			
2	Shelter Temperature standard deviation		5	0	12			
3	Temperature standard deviation		4	0	12			



## Field Performance Comments

1 **Parameter:** Flow Rate **SensorComponent:** Moisture Present **CommentCode:** 72

The filter sample tubing has drops of moisture in low sections outside the shelter.

## Field Systems Comments

1 **Parameter:** DasComments

The met tower has been removed.

2 **Parameter:** SitingCriteriaCom

Manure is routinely spread on the hay fields surrounding the site during the summer.

3 **Parameter:** ShelterCleanNotes

The shelter is clean and well organized.

4 **Parameter:** MetSensorComme

Temperature mounted in naturally aspirated shield on sample tower.

# EEMS Spot Report

Data Compiled: 7/27/2016 4:33:50 PM

SiteVisitDate	Site	Technician
07/21/2016	ALH157	Sandy Grenville

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	0.97394	unitless	P
2	Ozone Intercept	P	0	5	4	0.53928	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99998	unitless	P
4	Ozone % difference avg	P	7	10	4	1.6	%	P
5	Ozone % difference max	P	7	10	4	2.5	%	P

## Records without valid pass/fail criteria

# EEMS Spot Report

Data Compiled: 9/4/2016 2:59:28 PM

Site Visit Date Site Technician

08/15/2016 ANA115 Eric Hebert

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature average error	P	4	0.5	6	0.08	c	P
2	Temperature max error	P	4	0.5	6	0.12	c	P
3	Ozone Slope	P	0	1.1	4	0.99502	unitless	P
4	Ozone Intercept	P	0	5	4	0.55491	ppb	P
5	Ozone correlation	P	0	0.995	4	1.00000	unitless	P
6	Ozone % difference avg	P	7	10	4	0.6	%	P
7	Ozone % difference max	P	7	10	4	1.2	%	P
8	Flow Rate average % difference	P	10	5	3	0.45	%	P
9	Flow Rate max % difference	P	10	5	3	0.67	%	P
10	DAS Time maximum error	P	0	5	1	0.00	min	P
11	DAS Voltage average error	P	7	0.003	56	0.0001	V	P
12	Shelter Temperature average error	P	5	2	12	0.75	c	P
13	Shelter Temperature max error	P	5	2	12	1.11	c	P

## Records without valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	DAS Voltage maximum error		7	0	56			
2	Shelter Temperature standard deviation		5	0	12			
3	Temperature standard deviation		4	0	6			

## Field Performance Comments

1 **Parameter:** Flow Rate      **SensorComponent:** Moisture Present      **CommentCode:** 72

The filter sample tubing has drops of moisture in low sections outside the shelter.

## Field Systems Comments

1 **Parameter:** DasComments

The met tower has been removed. The DAS controls the shelter heating and cooling.

2 **Parameter:** SitingCriteriaCom

Site is confined within a fenced area that is somewhat small. There is available space adjacent to the fenced area that could be utilized to improve the instrument siting.

3 **Parameter:** ShelterCleanNotes

The shelter is in fair condition, however somewhat cluttered.

4 **Parameter:** PollAnalyzerCom

Moisture is present in the flow tubing outside of the shelter.

# EEMS Spot Report

Data Compiled: 10/15/2016 7:39:19 PM

Site Visit Date Site Technician

---

09/24/2016 BVL130 Eric Hebert

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	0.99046	unitless	P
2	Ozone Intercept	P	0	5	4	-0.34535	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99999	unitless	P
4	Ozone % difference avg	P	7	10	4	1.8	%	P
5	Ozone % difference max	P	7	10	4	2.5	%	P

## Records without valid pass/fail criteria

# EEMS Spot Report

Data Compiled: 10/20/2016 9:48:18 PM

Site Visit Date Site Technician

---

08/18/2016 CNT169 Martin Valvur

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	1.07153	unitless	P
2	Ozone Intercept	P	0	5	4	-0.45958	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99999	unitless	P
4	Ozone % difference avg	P	7	10	4	6.4	%	P
5	Ozone % difference max	P	7	10	4	6.8	%	P

## Records without valid pass/fail criteria

# EEMS Spot Report

Data Compiled: 7/19/2016 9:49:39 AM

Site Visit Date Site Technician

07/07/2016 DEN417 Martin Valvur

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature2meter average error	P	5	0.5	3	0.12	c	P
2	Temperature2meter max error	P	5	0.5	3	0.28	c	P
3	Ozone Slope	P	0	1.1	4	1.06973	unitless	P
4	Ozone Intercept	P	0	5	4	-1.0724	ppb	P
5	Ozone correlation	P	0	0.995	4	0.99999	unitless	P
6	Ozone % difference avg	P	7	10	4	4.7	%	P
7	Ozone % difference max	P	7	10	4	6.1	%	P
8	Flow Rate average % difference	P	10	5	6	0.62	%	P
9	Flow Rate max % difference	P	10	5	6	0.64	%	P
10	DAS Time maximum error	P	0	5	1	0.00	min	P
11	DAS Voltage average error	P	7	0.003	56	0.0002	V	P
12	Shelter Temperature average error	P	5	2	15	1.35	c	P
13	Shelter Temperature max error	P	5	2	15	2.9	c	Fail

## Records without valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	DAS Voltage maximum error		7	0	56			
2	Shelter Temperature standard deviation		5	0	15			
3	Temperature2meter Standard Deviation		5	0	3			

## Field Performance Comments

- 1 **Parameter:** Flow Rate      **SensorComponent:** Filter Position      **CommentCode:** 71

The filter attachment plate is mounted too low in the enclosure resulting in the filter being exposed to wind-driven rain and in the standard geometric orientation.

## Field Systems Comments

- 1 **Parameter:** SiteOpsProcComm

The site operator uses one gloved hand, and the same glove, to remove and install the filter pack. Leak checks are performed when the ambient temperature is above -10 C.

- 2 **Parameter:** ShelterCleanNotes

The shelter is in good condition, clean, neat, and very well organized.



# EEMS Spot Report

Data Compiled: 10/22/2016 9:57:12 AM

SiteVisitDate	Site	Technician
09/26/2016	GLR468	Martin Valvur

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	1.0788	unitless	P
2	Ozone Intercept	P	0	5	4	-0.12526	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99998	unitless	P
4	Ozone % difference avg	P	7	10	4	7.7	%	P
5	Ozone % difference max	P	7	10	4	8.1	%	P

## Records without valid pass/fail criteria

# EEMS Spot Report

Data Compiled: 10/15/2016 7:22:32 PM

Site Visit Date Site Technician

---

09/18/2016 GRB411 Martin Valvur

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	0.94866	unitless	P
2	Ozone Intercept	P	0	5	4	-0.61043	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99996	unitless	P
4	Ozone % difference avg	P	7	10	4	6.5	%	P
5	Ozone % difference max	P	7	10	4	8.7	%	P

## Records without valid pass/fail criteria

# EEMS Spot Report

Data Compiled: 9/4/2016 5:35:10 PM

Site Visit Date Site Technician

08/18/2016 HOX148 Eric Hebert

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature average error	P	4	0.5	9	0.12	c	P
2	Temperature max error	P	4	0.5	9	0.24	c	P
3	Ozone Slope	P	0	1.1	4	0.98573	unitless	P
4	Ozone Intercept	P	0	5	4	0.47845	ppb	P
5	Ozone correlation	P	0	0.995	4	0.99998	unitless	P
6	Ozone % difference avg	P	7	10	4	0.8	%	P
7	Ozone % difference max	P	7	10	4	0.9	%	P
8	Flow Rate average % difference	P	10	5	6	0.44	%	P
9	Flow Rate max % difference	P	10	5	6	0.67	%	P
10	DAS Time maximum error	P	0	5	1	0.03	min	P
11	DAS Voltage average error	P	7	0.003	49	0.0000	V	P
12	Shelter Temperature average error	P	5	2	8	0.53	c	P
13	Shelter Temperature max error	P	5	2	8	0.89	c	P

## Records without valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	DAS Voltage maximum error		7	0	49			
2	Shelter Temperature standard deviation		5	0	8			
3	Temperature standard deviation		4	0	9			

## Field Performance Comments

- Parameter:** Flow Rate      **SensorComponent:** Moisture Present      **CommentCode:** 72  
The filter sample tubing has drops of moisture in low sections outside the shelter.
- Parameter:** Ozone      **SensorComponent:** Cell A Tmp.      **CommentCode:** 99  
This analyzer diagnostic check is outside the manufacturer's recommended value.

## Field Systems Comments

- Parameter:** DasComments  
The shelter floor is being replaced. The shelter climate control is disabled due to the construction.
- Parameter:** SiteOpsProcedures  
The ozone analyzer sample train is leak-checked every two weeks. The shelter climate control is disabled during repairs to the shelter. Although the shelter temperature is currently within acceptable limits there is an "Alarm High" temperature flag present on the site ozone monitor.
- Parameter:** SitingCriteriaCom  
There is a co-generating and smelting facility in Cadillac approximately 30 km to the northeast. The site is located in a hay field which is cut 2 or 3 times per year.
- Parameter:** ShelterCleanNotes  
The shelter is clean, neat, well organized. Major repairs are underway to the floor of the shelter.
- Parameter:** MetSensorComme  
Met tower removed and temperature installed in naturally aspirated shield on sample tower.

# EEMS Spot Report

Data Compiled: #####

SiteVisitDate	Site	Technician
08/17/2016	KEF112	Sandy Grenville

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature average error	P	4	0.5	12	0.08	c	P
2	Temperature max error	P	4	0.5	12	0.18	c	P
3	Ozone Slope	P	0	1.1	4	0.98447	unitless	P
4	Ozone Intercept	P	0	5	4	0.27377	ppb	P
5	Ozone correlation	P	0	0.995	4	0.99995	unitless	P
6	Ozone % difference avg	P	7	10	4	1.3	%	P
7	Ozone % difference max	P	7	10	4	2.2	%	P
8	Flow Rate average % difference	P	10	5	4	1.62	%	P
9	Flow Rate max % difference	P	10	5	4	1.71	%	P
10	DAS Time maximum error	P	0	5	1	0.07	min	P
11	DAS Voltage average error	P	7	0.003	49	0.0001	V	P
12	Shelter Temperature average error	P	5	2	12	0.56	c	P
13	Shelter Temperature max error	P	5	2	12	0.75	c	P

## Records without valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	DAS Voltage maximum error		7	0	49			
2	Shelter Temperature standard deviation		5	0	12			
3	Temperature standard deviation		4	0	12			

## Field Performance Comments

1 **Parameter:** Flow Rate      **SensorComponent:** Moisture Present      **CommentCode:** 72

The filter sample tubing has drops of moisture in low sections outside the shelter.

## Field Systems Comments

1 **Parameter:** SiteOpsProcedures

The inlet filter is replaced and the ozone sample train is leak tested every two weeks.

2 **Parameter:** SitingCriteriaCom

The site is in a clearing within the Kane Experimental Forest, the tree line is within 10 meters of the site.

3 **Parameter:** ShelterCleanNotes

The shelter is clean and very well organized. The floor and bottom of walls are beginning to deteriorate.

4 **Parameter:** PollAnalyzerCom

Trees to the east are within 20 meters of the ozone inlet.

5 **Parameter:** MetSensorComme

The meteorological tower is attached to the shelter and the temperature sensor is positioned directly over the metal roof of the shelter.

# EEMS Spot Report

Data Compiled: 10/15/2016 6:00:48 PM

SiteVisitDate	Site	Technician
08/23/2016	LRL117	Sandy Grenville

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	0.97730	unitless	P
2	Ozone Intercept	P	0	5	4	0.56697	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99998	unitless	P
4	Ozone % difference avg	P	7	10	4	1.2	%	P
5	Ozone % difference max	P	7	10	4	2.0	%	P

## Records without valid pass/fail criteria

# EEMS Spot Report

Data Compiled: #####

SiteVisitDate	Site	Technician
08/15/2016	MKG113	Sandy Grenville

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature average error	P	4	0.5	3	0.04	c	P
2	Temperature max error	P	4	0.5	3	0.06	c	P
3	Ozone Slope	P	0	1.1	4	1.00272	unitless	P
4	Ozone Intercept	P	0	5	4	-0.79901	ppb	P
5	Ozone correlation	P	0	0.995	4	0.99998	unitless	P
6	Ozone % difference avg	P	7	10	4	1.0	%	P
7	Ozone % difference max	P	7	10	4	2.0	%	P
8	Flow Rate average % difference	P	10	5	3	0.22	%	P
9	Flow Rate max % difference	P	10	5	3	0.67	%	P
10	DAS Time maximum error	P	0	5	1	0.00	min	P
11	DAS Voltage average error	P	7	0.003	49	0.0001	V	P
12	Shelter Temperature average error	P	5	2	12	0.07	c	P
13	Shelter Temperature max error	P	5	2	12	0.13	c	P

## Records without valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	DAS Voltage maximum error		7	0	49			
2	Shelter Temperature standard deviation		5	0	12			
3	Temperature standard deviation		4	0	3			



## Field Systems Comments

**1 Parameter:** DasComments

The Met tower has been removed and the temperature sensor is now mounted on the sample tower in a naturally aspirated shield.

**2 Parameter:** ShelterCleanNotes

The shelter is clean and organized. Leak and rot below the air conditioner and on the floor under the counter. Mold beginning on walls and floor.

# EEMS Spot Report

Data Compiled: 10/20/2016 9:58:36 PM

SiteVisitDate	Site	Technician
08/24/2016	NEC602	Martin Valvur

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	0.97977	unitless	P
2	Ozone Intercept	P	0	5	4	0.18790	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99995	unitless	P
4	Ozone % difference avg	P	7	10	4	1.7	%	P
5	Ozone % difference max	P	7	10	4	2.3	%	P

## Records without valid pass/fail criteria

## Field Performance Comments

1 **Parameter:** Ozone      **SensorComponent:** Cell B Freq.      **CommentCode:** 99

This analyzer diagnostic check is outside the manufacturer's recommended value.

# EEMS Spot Report

Data Compiled: 9/4/2016 6:07:02 PM

SiteVisitDate	Site	Technician
09/01/2016	PRK134	Eric Hebert

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	0.95671	unitless	P
2	Ozone Intercept	P	0	5	4	-0.02669	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99997	unitless	P
4	Ozone % difference avg	P	7	10	4	4.2	%	P
5	Ozone % difference max	P	7	10	4	4.7	%	P

## Records without valid pass/fail criteria

# EEMS Spot Report

Data Compiled: #####

SiteVisitDate	Site	Technician
08/22/2016	PSU106	Sandy Grenville

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature average error	P	4	0.5	9	0.27	c	P
2	Temperature max error	P	4	0.5	9	0.33	c	P
3	Ozone Slope	P	0	1.1	4	0.98609	unitless	P
4	Ozone Intercept	P	0	5	4	0.18438	ppb	P
5	Ozone correlation	P	0	0.995	4	1.00000	unitless	P
6	Ozone % difference avg	P	7	10	4	1.0	%	P
7	Ozone % difference max	P	7	10	4	1.2	%	P
8	Flow Rate average % difference	P	10	5	4	0.66	%	P
9	Flow Rate max % difference	P	10	5	4	0.66	%	P
10	DAS Time maximum error	P	0	5	1	0.08	min	P
11	DAS Voltage average error	P	7	0.003	49	0.0000	V	P
12	Shelter Temperature average error	P	5	2	12	0.36	c	P
13	Shelter Temperature max error	P	5	2	12	0.51	c	P

## Records without valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	DAS Voltage maximum error		7	0	49			
2	Shelter Temperature standard deviation		5	0	12			
3	Temperature standard deviation		4	0	9			

## Field Systems Comments

**1 Parameter:** SiteOpsProcComm

The site operator uses the filter bag as a glove when handling the filter pack.

**2 Parameter:** DasComments

The meteorological tower has been removed.

**3 Parameter:** SitingCriteriaCom

The site is within 10 km of State College which has a population of approximately 50,000. The site is located in a university agricultural research field.

**4 Parameter:** ShelterCleanNotes

The shelter is owned by the university and is clean and orderly. The site is part of the Surfrad network.

**5 Parameter:** MetOpMaintCom

The 10-meter temperature sensor is now mounted in a naturally aspirated shield on the sample tower.

# EEMS Spot Report

Data Compiled: 9/4/2016 6:38:21 PM

Site Visit Date	Site	Technician
08/30/2016	RED004	Eric Hebert

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature average error	P	4	0.5	6	0.07	c	P
2	Temperature max error	P	4	0.5	6	0.18	c	P
3	Flow Rate average % difference	P	10	5	3	0.00	%	P
4	Flow Rate max % difference	P	10	5	3	0.00	%	P

## Records without valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature standard deviation		4	0	6			

## Field Performance Comments

- 1 **Parameter:** Flow Rate      **SensorComponent:** Moisture Present      **CommentCode:** 72

The filter sample tubing has drops of moisture in low sections outside the shelter.

## Field Systems Comments

- 1 **Parameter:** DocumentationCo

There is no site logbook and all manuals are kept electronically since the site is a small footprint site with no place to store hardcopies.

- 2 **Parameter:** SitingCriteriaCom

The site was cleared when installed, however the underbrush is beginning to grow near the tower.

- 3 **Parameter:** ShelterCleanNotes

Small footprint site with enclosure for instruments only. No shelter.

# EEMS Spot Report

Data Compiled: 7/27/2016 4:09:06 PM

Site	Visit Date	Technician
SAL133	07/19/2016	Sandy Grenville

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature average error	P	4	0.5	6	0.10	c	P
2	Temperature max error	P	4	0.5	6	0.16	c	P
3	Ozone Slope	P	0	1.1	4	0.98516	unitless	P
4	Ozone Intercept	P	0	5	4	0.28944	ppb	P
5	Ozone correlation	P	0	0.995	4	0.99998	unitless	P
6	Ozone % difference avg	P	7	10	4	0.7	%	P
7	Ozone % difference max	P	7	10	4	1.5	%	P
8	Flow Rate average % difference	P	10	5	3	1.75	%	P
9	Flow Rate max % difference	P	10	5	3	1.96	%	P
10	DAS Time maximum error	P	0	5	1	0.00	min	P
11	DAS Voltage average error	P	7	0.003	49	0.0001	V	P
12	Shelter Temperature average error	P	5	2	12	0.46	c	P
13	Shelter Temperature max error	P	5	2	12	0.79	c	P

## Records without valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	DAS Voltage maximum error		7	0	49			
2	Shelter Temperature standard deviation		5	0	12			
3	Temperature standard deviation		4	0	6			



## Field Systems Comments

**1 Parameter:** SiteOpsProcedures

The ozone inlet filter is replaced and the sample train is leak tested every two weeks.

**2 Parameter:** SitingCriteriaCom

The site is located next to a field usually planted with corn or soy beans.

**3 Parameter:** ShelterCleanNotes

The shelter is in fair condition and there is evidence of a leak in the shelter roof and ants are present. It is clean, neat, and well organized. Only one light is working.

# EEMS Spot Report

Data Compiled: 10/15/2016 6:21:20 PM

Site Visit Date Site Technician

---

09/09/2016 SAN189 Martin Valvur

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	0.99074	unitless	P
2	Ozone Intercept	P	0	5	4	-0.92556	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99994	unitless	P
4	Ozone % difference avg	P	7	10	4	2.8	%	P
5	Ozone % difference max	P	7	10	4	4.0	%	P

## Records without valid pass/fail criteria

# EEMS Spot Report

Data Compiled: 7/27/2016 4:26:16 PM

SiteVisitDate	Site	Technician
07/20/2016	STK138	Sandy Grenville

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	0.97109	unitless	P
2	Ozone Intercept	P	0	5	4	0.68618	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99999	unitless	P
4	Ozone % difference avg	P	7	10	4	1.4	%	P
5	Ozone % difference max	P	7	10	4	2.4	%	P

## Records without valid pass/fail criteria

# EEMS Spot Report

Data Compiled: 9/4/2016 3:40:15 PM

Site	Visit Date	Technician
UVL124	08/16/2016	Eric Hebert

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature average error	P	4	0.5	12	0.04	c	P
2	Temperature max error	P	4	0.5	12	0.08	c	P
3	Ozone Slope	P	0	1.1	4	1.00000	unitless	P
4	Ozone Intercept	P	0	5	4	-0.57786	ppb	P
5	Ozone correlation	P	0	0.995	4	0.99996	unitless	P
6	Ozone % difference avg	P	7	10	4	1.1	%	P
7	Ozone % difference max	P	7	10	4	2.9	%	P
8	Flow Rate average % difference	P	10	5	3	0.44	%	P
9	Flow Rate max % difference	P	10	5	3	0.67	%	P
10	DAS Time maximum error	P	0	5	1	0.02	min	P
11	DAS Voltage average error	P	7	0.003	49	0.0000	V	P
12	Shelter Temperature average error	P	5	2	8	0.57	c	P
13	Shelter Temperature max error	P	5	2	8	0.60	c	P

## Records without valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	DAS Voltage maximum error		7	0	49			
2	Shelter Temperature standard deviation		5	0	8			
3	Temperature standard deviation		4	0	12			

## Field Systems Comments

**1 Parameter:** SiteOpsProcedures

Ozone sample train leak-check performed every two weeks.

**2 Parameter:** DocumentationCo

The ozone diagnostic and observation sections of the SSRF were completed during the filter removal visit and not the installation visit as indicated on the form. This was noted during the previous audit visit. It was discussed with the site operator who indicated she would be recording the information on the correct date.

**3 Parameter:** SitingCriteriaCom

The site is located in an active agriculture field usually planted with beans or corn.

**4 Parameter:** ShelterCleanNotes

The shelter is clean and in good condition.

**5 Parameter:** MetOpMaintCom

Met tower removed and temperature mounted in naturally aspirated shield on sample tower.

# EEMS Spot Report

Data Compiled: 7/27/2016 4:43:47 PM

SiteVisitDate	Site	Technician
07/22/2016	VIN140	Sandy Grenville

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	0.98104	unitless	P
2	Ozone Intercept	P	0	5	4	-0.18851	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99996	unitless	P
4	Ozone % difference avg	P	7	10	4	2.5	%	P
5	Ozone % difference max	P	7	10	4	4.4	%	P

## Records without valid pass/fail criteria

# EEMS Spot Report

Data Compiled: 9/4/2016 5:47:39 PM

Site Visit Date	Site	Technician
08/29/2016	VOY413	Eric Hebert

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Ozone Slope	P	0	1.1	4	0.97748	unitless	P
2	Ozone Intercept	P	0	5	4	0.57243	ppb	P
3	Ozone correlation	P	0	0.995	4	0.99994	unitless	P
4	Ozone % difference avg	P	7	10	4	1.1	%	P
5	Ozone % difference max	P	7	10	4	2.2	%	P

## Records without valid pass/fail criteria

## Field Performance Comments

1 **Parameter:** Ozone      **SensorComponent:** Cell A Freq.      **CommentCode:** 99

This analyzer diagnostic check is outside the manufacturer's recommended value.

# EEMS Spot Report

Data Compiled: #####

SiteVisitDate	Site	Technician
09/15/2016	WST109	Sandy Grenville

## Records with valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	Temperature average error	P	4	0.5	6	0.11	c	P
2	Temperature max error	P	4	0.5	6	0.21	c	P
3	Ozone Slope	P	0	1.1	4	0.99396	unitless	P
4	Ozone Intercept	P	0	5	4	0.48937	ppb	P
5	Ozone correlation	P	0	0.995	4	0.99999	unitless	P
6	Ozone % difference avg	P	7	10	4	0.2	%	P
7	Ozone % difference max	P	7	10	4	0.3	%	P
8	Flow Rate average % difference	P	10	5	6	1.92	%	P
9	Flow Rate max % difference	P	10	5	6	2.11	%	P
10	DAS Time maximum error	P	0	5	1	0.00	min	P
11	DAS Voltage average error	P	7	0.003	49	0.0001	V	P
12	Shelter Temperature average error	P	5	2	12	0.67	c	P
13	Shelter Temperature max error	P	5	2	12	1.08	c	P

## Records without valid pass/fail criteria

Line	Audited Parameter	DAS	Ch. #	Criteria +/-	Counts	QaResult	Units	Pass/Fail
1	DAS Voltage maximum error		7	0	49			
2	Shelter Temperature standard deviation		5	0	12			
3	Temperature standard deviation		4	0	6			



## Field Systems Comments

**1 Parameter:** DasComments

The sample tower has been replaced and the met tower removed since the previous audit visit.

**2 Parameter:** SiteOpsProcedures

Ozone sample train leak checks are being conducted every two weeks.

**3 Parameter:** SitingCriteriaCom

The site is in a small clearing surrounded by mountain forest. There is a small parking lot used by forest service employees located 50 meters from the site.

**4 Parameter:** SiteOKNotes

State of NH Department of Environmental Services contact is Tom Fazzina (603) 271-0911 and tfazzina@DES.state.NH.US

**5 Parameter:** MetSensorComme

The temperature sensor is now mounted in a naturally aspirated shield on the sample tower.

---

**APPENDIX C**

**CASTNET Ozone Performance Evaluation Forms**

---

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*STK138-Sandy Grenville-07/20/2016*

1	7/20/2016	DAS	Campbell	000349	CR3000	2128
2	7/20/2016	Ozone	ThermoElectron Inc	000743	49i A1NAA	1105347321
3	7/20/2016	Ozone Standard	ThermoElectron Inc	000687	49i A3NAA	1030244809
4	7/20/2016	Zero air pump	Werther International	06915	C 70/4	000829162

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1105347321		STK138	Sandy Grenville	07/20/2016	Ozone	000743

<b>Slope:</b>	0.97109	<b>Slope:</b>	0.00000
<b>Intercept</b>	0.68618	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99999	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
1.4%	2.4%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0419606966	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01112		
<b>Slope</b>	0.99524	<b>Intercept</b>	-0.33070
<b>Cert Date</b>	1/28/2016	<b>CorrCoff</b>	1.00000

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	0.02	0.35	0.77	ppb	
primary	2	30.02	30.49	30.50	ppb	0.03%
primary	3	50.03	50.60	50.04	ppb	-1.11%
primary	4	80.02	80.73	79.04	ppb	-2.09%
primary	5	109.89	110.74	108.10	ppb	-2.38%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-0.50	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	0.997	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	98.9 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.72 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	709.4 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	36.5 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	91.5 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.3 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.72 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	710.0 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*ALH157-Sandy Grenville-07/21/2016*

1	7/21/2016	DAS	Campbell	000405	CR3000	2522
2	7/21/2016	Ozone	ThermoElectron Inc	000683	49i A1NAA	1030244798
3	7/21/2016	Ozone Standard	ThermoElectron Inc	000440	49i A3NAA	CM08200016
4	7/21/2016	Zero air pump	Werther International	06910	C 70/4	000829160

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1030244798		ALH157	Sandy Grenville	07/21/2016	Ozone	000683

<b>Slope:</b>	0.97394	<b>Slope:</b>	0.00000
<b>Intercept</b>	0.53928	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99998	<b>CorrCoff</b>	0.00000

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0419606966	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01112		
<b>Slope</b>	0.99524	<b>Intercept</b>	-0.33070
<b>Cert Date</b>	1/28/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
1.6%	2.5%		

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	-0.02	0.31	0.87	ppb	
primary	2	30.10	30.57	30.20	ppb	-1.21%
primary	3	50.00	50.57	50.10	ppb	-0.93%
primary	4	80.10	80.81	78.82	ppb	-2.46%
primary	5	110.00	110.85	108.70	ppb	-1.94%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-0.10	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	0.989	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	97.2 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.8 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.64 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	722.2 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	38.4 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	91.6 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.64 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	722.2 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*VIN140-Sandy Grenville-07/22/2016*

1	7/22/2016	DAS	Campbell	000358	CR3000	2136
2	7/22/2016	Ozone	ThermoElectron Inc	000630	49i A1NAA	1009241798
3	7/22/2016	Ozone Standard	ThermoElectron Inc	000546	49i A3NAA	0929938239
4	7/22/2016	Zero air pump	Werther International	06906	C 70/4	000821908

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1009241798		VIN140	Sandy Grenville	07/22/2016	Ozone	000630

<b>Slope:</b>	0.98104	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.18851	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99996	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
2.5%	4.4%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0419606966	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01112		
<b>Slope</b>	0.99524	<b>Intercept</b>	-0.33070
<b>Cert Date</b>	1/28/2016	<b>CorrCoff</b>	1.00000

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	0.01	0.34	0.33	ppb	
primary	2	30.18	30.65	29.31	ppb	-4.37%
primary	3	48.87	49.43	48.62	ppb	-1.64%
primary	4	79.03	79.74	78.23	ppb	-1.89%
primary	5	109.96	110.81	108.40	ppb	-2.17%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.30	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.015	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	91.0 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.3 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.60 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	725.3 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	37.7 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	101.5 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.4 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.72 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	725.3 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass



---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*CNT169-Martin Valvur-08/18/2016*

1	8/18/2016	DAS	Campbell	000417	CR3000	2515
2	8/18/2016	Ozone	ThermoElectron Inc	000699	49i A1NAA	1030244804
3	8/18/2016	Ozone Standard	ThermoElectron Inc	000328	49i A3NAA	0622717850
4	8/18/2016	Zero air pump	Werther International	06925	P 70/4	000836220

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1030244804		CNT169	Martin Valvur	08/18/2016	Ozone	000699

<b>Slope:</b>	1.07153	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.45958	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99999	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
6.4%	6.8%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49CPS-70008-364	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01110		
<b>Slope</b>	0.99832	<b>Intercept</b>	-0.26452
<b>Cert Date</b>	1/29/2016	<b>CorrCoff</b>	1.00000

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	0.04	0.30	-0.27	ppb	
primary	2	27.83	28.14	29.71	ppb	5.58%
primary	3	49.95	50.29	53.56	ppb	6.50%
primary	4	80.05	80.44	85.90	ppb	6.79%
primary	5	111.02	111.47	118.80	ppb	6.58%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.9	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.013	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	103.5 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	1.0 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.58 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	505.8 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	101.6 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	1.7 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.54 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	505.8 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*LRL117-Sandy Grenville-08/23/2016*

1	8/23/2016	DAS	Campbell	000344	CR300	2123
2	8/23/2016	Ozone	ThermoElectron Inc	000701	49i A1NAA	1030244808
3	8/23/2016	Ozone Standard	ThermoElectron Inc	000444	49i A3NAA	CM08200020
4	8/23/2016	Zero air pump	Werther International	06904	C 70/4	000821901

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1030244808		LRL117	Sandy Grenville	08/23/2016	Ozone	000701

<b>Slope:</b>	0.97730	<b>Slope:</b>	0.00000
<b>Intercept</b>	0.56697	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99998	<b>CorrCoff</b>	0.00000

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0419606966	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01112		
<b>Slope</b>	0.99524	<b>Intercept</b>	-0.33070
<b>Cert Date</b>	1/28/2016	<b>CorrCoff</b>	1.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
1.2%	2.0%		

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	-0.01	0.32	0.80	ppb	
primary	2	30.17	30.64	30.56	ppb	-0.26%
primary	3	49.95	50.52	49.80	ppb	-1.43%
primary	4	80.01	80.72	79.90	ppb	-1.02%
primary	5	109.87	110.72	108.50	ppb	-2.01%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-0.10	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.011	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	112.6 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	1.0 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.69 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	698.8 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	36.6 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	91.6 kHz	<b>Status</b>	Pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	1.0 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.83 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*NEC602-Martin Valvur-08/24/2016*

1	8/24/2016	DAS	Campbell	none	CR1000	41007
2	8/24/2016	Ozone	ThermoElectron Inc	none	49i A1NAA	1214552974
3	8/24/2016	Ozone Standard	ThermoElectron Inc	L0534683	49i E3CAA	1214552972
4	8/24/2016	Zero air pump	Thomas	none	107C9818D	049400004418

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1214552974		NEC602	Martin Valvur	08/24/2016	Ozone	none

<b>Slope:</b>	0.97977	<b>Slope:</b>	0.00000
<b>Intercept</b>	0.18790	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99995	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
1.7%	2.3%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49CPS-70008-364	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01110		
<b>Slope</b>	0.99832	<b>Intercept</b>	-0.26452
<b>Cert Date</b>	1/29/2016	<b>CorrCoff</b>	1.00000

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	0.35	0.61	0.77	ppb	
primary	2	28.81	29.12	28.45	ppb	-2.30%
primary	3	46.96	47.30	46.60	ppb	-1.48%
primary	4	75.15	75.54	74.80	ppb	-0.98%
primary	5	105.50	105.94	103.60	ppb	-2.21%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-0.6	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.026	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	65.2 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.7 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.66 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	633.6 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	36.3 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	49.9 kHz	<b>Status</b>	Fail
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.5 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.67 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	633.3 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>	See comments	<b>Status</b>	pass

# Site Visit Comments

<b>Parameter</b>	<b>Site</b>	<b>Technician</b>	<b>S.V. Date</b>	<b>Component</b>	<b>Mfg</b>	<b>Serial No.</b>	<b>Hazard</b>	<b>Problem</b>
------------------	-------------	-------------------	------------------	------------------	------------	-------------------	---------------	----------------

Ozone	NEC602	Martin Valvur	08/24/2016	Cell B Freq.	ThermoElectron	3838	<input type="checkbox"/>	<input type="checkbox"/>
-------	--------	---------------	------------	--------------	----------------	------	--------------------------	--------------------------

This analyzer diagnostic check is outside the manufacturer's recommended value.

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*VOY413-Eric Hebert-08/29/2016*

1	8/29/2016	DAS	Environmental Sys Corp	none	8816	4059
2	8/29/2016	Ozone	ThermoElectron Inc	90730	49C	49C-70522-366
3	8/29/2016	Ozone Standard	ThermoElectron Inc	90569	49C	49C-59260-322
4	8/29/2016	Sample Tower	Aluma Tower	none	B	AT-51159-11-G
5	8/29/2016	Zero air pump	Twin Tower Engineering	90719	TT70/E4	526294



# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	49C-70522-366		VOY413	Eric Hebert	08/29/2016	Ozone	90730

<b>Slope:</b>	0.97748	<b>Slope:</b>	0.00000
<b>Intercept</b>	0.57243	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99994	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
1.1%	2.2%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0517112167	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01113		
<b>Slope</b>	1.00500	<b>Intercept</b>	-0.28841
<b>Cert Date</b>	1/28/2016	<b>CorrCoff</b>	1.00000

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	-0.59	-0.30	0.19	ppb	
primary	2	29.72	29.85	29.56	ppb	-0.97%
primary	3	45.59	45.65	45.27	ppb	-0.83%
primary	4	76.60	76.50	76.03	ppb	-0.61%
primary	5	104.90	104.66	102.40	ppb	-2.16%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	0.000	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.006	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	0.0002	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	1.0003	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	59.8 kHz	<b>Status</b>	Fail
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.7 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.41 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	714.3 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	33.1 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	70.5 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.75 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	714.1 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>	See comments	<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*PRK134-Eric Hebert-09/01/2016*

1	9/1/2016	DAS	Campbell	000411	CR3000	2509
2	9/1/2016	Ozone	ThermoElectron Inc	000690	49i A1NAA	1030244800
3	9/1/2016	Ozone Standard	ThermoElectron Inc	000686	49i A3NAA	1030244818
4	9/1/2016	Sample Tower	Aluma Tower	03518	A	none
5	9/1/2016	UPS	APC	06744	RS900	unknown
6	9/1/2016	Zero air pump	Werther International	06905	C 70/4	000821907

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1030244800		PRK134	Eric Hebert	09/01/2016	Ozone	000690

<b>Slope:</b>	0.95671	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.02669	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99997	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
4.2%	4.7%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0517112167	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01113		
<b>Slope</b>	1.00500	<b>Intercept</b>	-0.28841
<b>Cert Date</b>	1/28/2016	<b>CorrCoff</b>	1.00000

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	0.49	0.77	0.48	ppb	
primary	2	27.84	27.98	26.98	ppb	-3.57%
primary	3	49.65	49.68	47.35	ppb	-4.69%
primary	4	77.55	77.45	74.52	ppb	-3.78%
primary	5	110.89	110.62	105.50	ppb	-4.63%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	Functioning	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-0.40	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.020	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	99.2 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	1.8 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.65 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	710.7 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	37.0 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	83.4 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.8 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.57 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	710.7 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*SAN189-Martin Valvur-09/09/2016*

1	9/9/2016	DAS	Campbell	000360	CR3000	2138
2	9/9/2016	Ozone	ThermoElectron Inc	000740	49i A1NAA	1105347311
3	9/9/2016	Ozone Standard	ThermoElectron Inc	000367	49i A3NAA	0726124683
4	9/9/2016	Zero air pump	Werther International	06875	C 70/4	000814272

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1105347311		SAN189	Martin Valvur	09/09/2016	Ozone	000740

<b>Slope:</b>	0.99074	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.92556	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99994	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
2.8%	4.1%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49CPS-70008-364	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01110		
<b>Slope</b>	0.99832	<b>Intercept</b>	-0.26452
<b>Cert Date</b>	1/29/2016	<b>CorrCoff</b>	1.00000

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	0.59	0.85	0.26	ppb	
primary	2	34.53	34.85	33.44	ppb	-4.05%
primary	3	51.63	51.98	50.47	ppb	-2.90%
primary	4	81.05	81.45	79.13	ppb	-2.85%
primary	5	111.45	111.90	110.50	ppb	-1.25%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-0.10	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.005	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	96.8 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.69 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	690.7 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	34.0 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	85.2 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.8 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	1.44 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	690.7 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

### *GRB411-Martin Valvur-09/18/2016*

1	9/18/2016	DAS	Environmental Sys Corp	90635	8816	2507
2	9/18/2016	Ozone	ThermoElectron Inc	90565	49C	49C-59285-322
3	9/18/2016	Ozone Standard	ThermoElectron Inc	none	49C	0330302753
4	9/18/2016	Sample Tower	Aluma Tower	none	B	AT-5381-F9-2
5	9/18/2016	Zero air pump	Werther International	90722	TT70/4E	507782

# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	49C-59285-322		GRB411	Martin Valvur	09/18/2016	Ozone	90565

<b>Slope:</b>	0.94866	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.61043	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99996	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
6.6%	8.8%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49CPS-70008-364	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01110		
<b>Slope</b>	0.99953	<b>Intercept</b>	-0.18527
<b>Cert Date</b>	9/12/2016	<b>CorrCoff</b>	1.00000

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	0.85	1.03	0.65	ppb	
primary	2	33.07	33.27	30.36	ppb	-8.75%
primary	3	52.32	52.52	49.30	ppb	-6.13%
primary	4	77.74	77.96	73.65	ppb	-5.53%
primary	5	107.44	107.67	101.45	ppb	-5.78%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Dirty	<b>Status</b>	Fail
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-0.20	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	0.998	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	-0.0007	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	0.9992	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	77.1 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.70 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	582.2 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	37.4 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	68.0 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	2.3 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.65 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	582.7 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	7%	<b>Status</b>	Fail
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

*BVL130-Eric Hebert-09/24/2016*

1	9/24/2016	DAS	Campbell	000424	CR3000	2539
2	9/24/2016	Ozone	ThermoElectron Inc	000625	49i A1NAA	1009241797
3	9/24/2016	Ozone Standard	ThermoElectron Inc	000512	49i A3NAA	0922236890
4	9/24/2016	Zero air pump	Werther International	06926	PC70/4	000836218



# Ozone Data Form

<b>Mfg</b>	<b>Serial Number</b>	<b>Ta</b>	<b>Site</b>	<b>Technician</b>	<b>Site Visit Date</b>	<b>Parameter</b>	<b>Owner ID</b>
ThermoElectron Inc	1009241797		BVL130	Eric Hebert	09/24/2016	Ozone	000625

<b>Slope:</b>	0.99046	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.34535	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99999	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
1.8%	2.5%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	0517112167	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01113		
<b>Slope</b>	1.00261	<b>Intercept</b>	-0.15202
<b>Cert Date</b>	9/14/2016	<b>CorrCoff</b>	1.00000

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	0.64	0.78	0.57	ppb	
primary	2	29.19	29.26	28.53	ppb	-2.49%
primary	3	48.38	48.40	47.39	ppb	-2.09%
primary	4	76.01	75.96	75.05	ppb	-1.20%
primary	5	111.34	111.20	109.80	ppb	-1.26%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-0.40	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.012	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	96.7 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.79 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	716.7 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	34.9 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	100.8 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.72 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	716.7 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass

---

## *Site Inventory by Site Visit*

---

<i>Site Visit Date</i>	<i>Parameter</i>	<i>Mfg</i>	<i>Owner ID</i>	<i>Model Number</i>	<i>Serial Number</i>
------------------------	------------------	------------	-----------------	---------------------	----------------------

---

### *GLR468-Martin Valvur-09/26/2016*

1	9/26/2016	DAS	Environmental Sys Corp	90653	8816	2566
2	9/26/2016	Ozone	ThermoElectron Inc	none	49i A3NAA	1023943901
3	9/26/2016	Ozone Standard	ThermoElectron Inc	none	49i A3NAA	0733726104
4	9/26/2016	Zero air pump	Werther International	none	PC70/4	000756725

# Ozone Data Form

Mfg	Serial Number	Ta	Site	Technician	Site Visit Date	Parameter	Owner ID
ThermoElectron Inc	1023943901		GLR468	Martin Valvur	09/26/2016	Ozone	none

<b>Slope:</b>	1.07880	<b>Slope:</b>	0.00000
<b>Intercept</b>	-0.12526	<b>Intercept</b>	0.00000
<b>CorrCoff</b>	0.99998	<b>CorrCoff</b>	0.00000

<b>DAS 1:</b>	<b>DAS 2:</b>		
<b>A Avg % Diff:</b>	<b>A Max % Di</b>	<b>A Avg %Dif</b>	<b>A Max % Di</b>
7.7%	8.2%		

<b>Mfg</b>	ThermoElectron Inc	<b>Parameter</b>	ozone
<b>Serial Number</b>	49CPS-70008-364	<b>Tfer Desc.</b>	Ozone primary stan
<b>Tfer ID</b>	01110		
<b>Slope</b>	0.99953	<b>Intercept</b>	-0.18527
<b>Cert Date</b>	9/12/2016	<b>CorrCoff</b>	1.00000

UseDescription	ConcGroup	Tfer Raw	Tfer Corr	Site	Site Unit	PctDifference
primary	1	0.50	0.68	0.55	ppb	
primary	2	28.06	28.25	30.40	ppb	7.61%
primary	3	50.01	50.21	54.30	ppb	8.15%
primary	4	81.04	81.26	87.09	ppb	7.17%
primary	5	111.03	111.26	120.10	ppb	7.95%

<b>Sensor Component</b>	Sample Train	<b>Condition</b>	Good	<b>Status</b>	pass
<b>Sensor Component</b>	22.5 degree rule	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Inlet Filter Condition	<b>Condition</b>	Clean	<b>Status</b>	pass
<b>Sensor Component</b>	Battery Backup	<b>Condition</b>	N/A	<b>Status</b>	pass
<b>Sensor Component</b>	Offset	<b>Condition</b>	-0.4	<b>Status</b>	pass
<b>Sensor Component</b>	Span	<b>Condition</b>	1.017	<b>Status</b>	pass
<b>Sensor Component</b>	Zero Voltage	<b>Condition</b>	-0.0010	<b>Status</b>	pass
<b>Sensor Component</b>	Fullscale Voltage	<b>Condition</b>	0.9989	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Freq.	<b>Condition</b>	72.3 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Noise	<b>Condition</b>	0.8 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Flow	<b>Condition</b>	0.54 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Pressure	<b>Condition</b>	678.3 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell A Tmp.	<b>Condition</b>	33.7 C	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Freq.	<b>Condition</b>	66.5 kHz	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Noise	<b>Condition</b>	0.6 ppb	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Flow	<b>Condition</b>	0.53 lpm	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Pressure	<b>Condition</b>	678.3 mmHg	<b>Status</b>	pass
<b>Sensor Component</b>	Cell B Tmp.	<b>Condition</b>		<b>Status</b>	pass
<b>Sensor Component</b>	Line Loss	<b>Condition</b>	Not tested	<b>Status</b>	pass
<b>Sensor Component</b>	System Memo	<b>Condition</b>		<b>Status</b>	pass