#### NEBRASKA ADMINISTRATIVE CODE

- Title 129 DEPARTMENT OF ENVIRONMENTAL QUALITY
- Chapter 22 INCINERATORS; EMISSION STANDARDS
- $\underline{001}$  The provisions of this chapter shall apply to all new and existing incinerators except for those listed in sections  $\underline{001.01}$  through  $\underline{001.05}$  of this chapter. Incinerators not included in the exceptions listed in sections  $\underline{001.01}$  through  $\underline{001.05}$  must comply with construction permit requirements listed in Chapter 17, section  $\underline{001.03}$ .
  - <u>001.01</u> Incinerators located on residential premises containing five or less dwelling units and used exclusively for the disposal of waste originating on said premises.
  - 001.02 Incinerators used solely for space heating.
  - <u>001.03</u> Incinerators used to burn hazardous waste and subject to regulations under Nebraska Administrative Code Title 128, Chapter 7, section 008.
  - <u>001.04</u> Furnaces used for law enforcement purposes specified in definition of "incinerator" in Chapter 1.
  - 001.05 Air curtain incinerators subject to Chapter 18 sections 001.68 or 001.69 or which operate in compliance with Chapter 30, section 002.07G and combust only 100 percent wood waste; 100 percent clean lumber; 100 percent yard waste; or a 100 percent mixture of only wood waste, clean lumber, and/or yard waste.
    - <u>001.05A</u> Air curtain incinerators must meet additional requirements in section 007 of this chapter.
- $\underline{002}$  No person shall cause or permit particulate matter emissions from any incinerator to be discharged into the outdoor atmosphere to exceed 0.10 grains per dry standard cubic foot (gr/dscf) of exhaust gas, corrected to 7% oxygen.
- <u>003</u> The burning capacity of an incinerator shall be the manufacturer's or designer's guaranteed maximum rate or such other rate as may be determined by the Director in accordance with good engineering practice.

### Chapter 22

- <u>004</u> Waste burned during performance testing required by Chapter 34 shall be representative of the waste normally generated by the affected facility and shall be charged at a rate equal to the burning capacity of the incinerator. Copies of any additional operational data recorded during the test shall be submitted to the Department together with the completed test report forms.
- $\underline{005}$  Instructions for proper operation of each incinerator shall be posted on site and written certification that each operator has read these instructions, understands them and intends to comply, shall be kept on record by the owner.
- $\underline{006}$  Except as provided in sections  $\underline{006.01}$  and  $\underline{006.02}$  below, each incinerator shall consist of (a) refractory lined combustion furnace(s) employing adequate design parameters necessary for maximum combustion of the materials to be burned, and shall be designed to vent the products of combustion through an adequate stack, duct, or chimney.
  - $\underline{006.01}$  An alternate design for a new unit may be permitted provided it can be shown that the alternative design is at least as effective in controlling pollutant emissions as the design criteria of this section.
  - $\underline{006.02}$  An operating permit can be issued to an existing unit not meeting the design criteria set forth in section  $\underline{006}$  above, provided compliance with both section  $\underline{002}$  of this chapter and the visible emission standard in section  $\underline{005}$  of Chapter 20 can be demonstrated.
- <u>007</u> Air curtain incinerators which combust only clean lumber, wood waste, and/or yard waste shall meet the following requirements:
  - $\underline{007.01}$  Within 60 days after the air curtain incinerator reaches the charge rate at which it will operate, but no later than 180 days after its initial startup, the limitations in sections 007.01A and 007.01B must be met:
    - $\underline{007.01A}$  The opacity limitation is 10 percent (6-minute average), except as described in section  $\underline{007.01B}$ .
    - $\underline{007.01B}$  The opacity limitation is 35 percent (6-minute average) during the startup period that is within the first 30 minutes of operation.

- $\underline{007.02}$  Except during malfunctions, the requirements of section  $\underline{007.01}$  apply at all times, and each malfunction must not exceed 3 hours.
- <u>007.03</u> Opacity monitoring of the air curtain incinerator shall include:
  - $\underline{007.03A}$  Use of Method 9 of appendix A of New Source Performance Standards (40 CFR 60) to determine compliance with the opacity limitation.
  - 007.03B Conducting an initial test for opacity as specified in 40 CFR 60.8.
  - <u>007.03C</u> After the initial test for opacity, conducting annual opacity tests no more than 12 calendar months following the date of the previous test.
- $\underline{007.04}$  Prior to commencing construction on the air curtain incinerator, submit all items described in sections  $\underline{007.04A}$  through 007.04C:
  - <u>007.04A</u> Notification of intent to construct the air curtain incinerator.
  - 007.04B Planned initial startup date.
  - <u>007.04C</u> Types of materials to be burned in the air curtain incinerator.
- 007.05 Recordkeeping requirements for air curtain incinerators:
  - <u>007.05A</u> Keep records of results of all initial and annual opacity tests onsite (or readily available) in either paper copy or electronic format, unless the Director approves another format, for at least five years.
  - <u>007.05B</u> Make all records available for submittal to the Director or for an inspector's onsite review.
  - $\underline{007.05C}$  The results (each 6-minute average) of the initial opacity tests must be submitted no later than 60 days following the initial test. Submit annual opacity test results within 12 months following the previous report.

# Chapter 22

 $\underline{007.05D}$  Submit initial and annual opacity test reports in electronic or paper copy on or before the applicable submittal date.

<u>007.05E</u> Keep a copy of the initial and annual reports onsite (or readily available) for a period of five years

Enabling Legislation: Neb. Rev. Stat. §§81-1504(1)(2); 81-1505(1)(2)

Legal Citation: Title 129, Ch. 22, Nebraska Department of Environmental Quality

#### EPA Rulemakings

CFR: 40 C.F.R. 52.1420(c)
FRM: 81 FR 70023 (10/11/2016)
PRM: 81 FR 70065 (10/11/2016)
State Submission: 3/6/2014 and 7/14/14

State Final: Title 129, Chapters 4 (7/14/2014), 19, and 22 (3/6/2014)

APDB File: NE-90; EPA-R07-OAR-2016-0556 effective 12/12/16.

Description: This revision to Chapter 22 involves minor formatting and grammatical changes to the

text.

CFR: 40 C.F.R. 52.1420(c) FRM: 81 FR 69693 (10/7/2016) PRM: 81 FR 69752 (10/7/2016)

State Submission: 5/1/03

State Final: 11/8/11 Adopted 12/7/07 effective 7/3/10 APDB File: NE-84A, EPA-R07-OAR-2016-0555 effective 12/6/16

Description: This revision allows for the issuance of multiple operating permits to major sources; establishes requirements regarding opacity for air curtain incinerators; allows burning in an air curtain incinerator with a general or community open fire permit; and clarifies NDEQ's authority to order emission sources to make or have tests made to determine the rate of contaminant emissions from the source. Portions of the submittal had already been acted on previously.

CFR: 40 C.F.R. 52.1420(c) FRM: 65 FR 3130 (1/20/00) PRM: 65 FR 3168 (1/20/00)

State Submission: 2/5/99 State Final: 9/7/97 APDB File: NE-41

Description: Subsection  $\underline{001}$  was revised to clarify exempt incinerator provisions. Subsection  $\underline{002}$  was revised to correct the emission measurement method for particulate matter. Subsection  $\underline{006}$  was added to incorporate the incinerator design specifications formerly contained in 001.

CFR: 40 C.F.R. 1420(c)(41)
FRM: 60 FR 372 (01/04/95)
PRM: 60 FR 418 (01/04/95)

State Submission: 2/16/94 State Proposal: 9/16/93 State Final: 6/26/94 APDB File: NE-31

Description: The EPA approved the renumbering of this rule as part of the overall recodification of the Nebraska rules. The rule was previously Chapter 11.

# Note: All previous versions of the rule are obsolete; the record of prior rulemakings is shown below for historical purposes only.

CFR: 40 C.F.R. 52.1420(c)(39) FRM: 56 FR 50515 (10/7/91)

PRM: None
State Submission: 3/8/91
State Proposal: 12/7/90
State Final: 2/20/91
APDB File: NE-30

Description: The EPA approved a revision as part of an update of a number of regulations. This revision tightened the particulate emission limit for incinerators and added a requirement for operating instructions.

CFR: 40 C.F.R. 52.1420(c)(37) FRM: 54 FR 21059 (5/16/89)

PRM: None
State Submission: 6/15/88
State Proposal: 2/5/88
State Final: 6/5/88
APDB File: NE-21

Description: The EPA reapproved this rule as Chapter 11 as part of an action to update the entire set of regulations in the Nebraska SIP.

CFR: 40 C.F.R. 52.1420(c)(31) FRM: 50 FR 23003 (5/30/85) PRM: 49 FR 37427 (9/24/84)

State Submission: 10/6/83

# Chapter 22

State Proposal: 6/17/83 State Final: 9/30/83 APDB File:

Description: The EPA approved a change to the regulation revising the format for reporting incinerator emission compliance.

CFR: 40 C.F.R. 52.1420(c)(4) FRM: 41 FR 8962 (3/2/76)

PRM: None
State Submission: 6/9/72
State Proposal: Unknown
State Final: 6/6/72
APDB File: NE-00

Description: As part of an action to clarify the list of SIP submissions submitted by the state,

the EPA reapproved the rule. There were no apparent changes.

CFR: 40 C.F.R. 52.1420(a) FRM: 37 FR 10842 (5/31/72)

PRM: None
State Submission: 1/28/72
State Proposal: Unknown
State Final: 6/6/72
APDB File: NE-00

Description: EPA approved this as Rule 14 pertaining to incinerator emissions, in the original

SIP.

## Difference Between the State and EPA-Approved Regulation

None.