



# Leather Dyeing- Generic Scenario for Estimating Occupational Exposures and Environmental Releases

-Draft-

U.S. Environmental Protection Agency  
Office of Pollution Prevention and Toxics  
Chemical Engineering Branch  
1200 Pennsylvania Avenue  
Washington, D.C. 20460

---

29 September 2000

## TABLE OF CONTENTS

		<b>Page</b>
1.0	INTRODUCTION .....	1
	1.1 Background .....	1
	1.2 Purpose .....	1
	1.3 Methodology for Developing Estimation Techniques .....	1
	1.4 Hierarchy for Developing Release and Occupational Exposure Estimates .....	2
2.0	INDUSTRY PROFILE .....	4
3.0	PROCESS DESCRIPTION .....	5
4.0	SCREENING LEVEL ESTIMATION TECHNIQUES/METHODS .....	6
	4.1 General Facility Estimates .....	6
	4.2 Occupational Exposure .....	7
	4.3 Environmental Releases .....	9
5.0	ADDITIONAL INFORMATION .....	11
6.0	OTHER SOURCES .....	12
7.0	DATA GAPS AND UNCERTAINTIES .....	13
8.0	REFERENCES .....	14

## LIST OF TABLES

	<b>Page</b>
1	Release and Exposure Calculations for Leather Dyeing PMN Chemicals . . . . . iv

**-- REVISED DRAFT (DO NOT CITE OR QUOTE) --**

ABSTRACT AND RELEASE AND EXPOSURE  
CALCULATION SUMMARY TABLES

September 2000

The purpose of this report is to develop a standardized approach that EPA's Chemical Engineering Branch (CEB) can use to estimate potential occupational exposures and environmental releases from the use of leather dyeing chemicals. These estimation techniques may be used by CEB to future evaluate leather dyeing premanufacture notices (PMNs) and existing leather dyeing PMNs. The document also presents an industry profile, a discussion of typical processes in the industry, including release and exposure points, control technologies, and source reduction, pollution prevention, and material substitution alternatives (when applicable).

Information and data used to develop the estimation procedures were obtained from a review of the reference materials listed in Section 8.0. Based on this review, reasonable worst-case release and exposure estimates can be made using the methodology and calculations that are described in detail in Section 4.0. These calculations are summarized in the following table.

-- REVISED DRAFT (DO NOT CITE OR QUOTE) --

ABSTRACT AND RELEASE AND EXPOSURE  
CALCULATION SUMMARY TABLES

September 2000

**Table 1**

**Release and Exposure Calculations for Leather Dyeing PMN Chemicals**

<b>General Facility Estimates</b>	
Number of Sites:	$NS = \frac{PV}{1,000 \text{ kg/site-yr}}$
Chemical Use Rate per batch:	$DU = BS \times \% D \times PMN_c$
Days of Operation:	$OD = \frac{1,000 \text{ kg/site-yr}}{DU \times NB}$
<b>Occupational Exposure</b>	
Number of Workers Exposed:	$N_w = <7 \times NS$
Inhalation (mg/day):	
Weighing:	$I_w = 2.1 \text{ mg/m}^3 \times PMN_c \times 1.25 \text{ m}^3/\text{hr} \times 8 \text{ hr/day}$
Mixing:	$I_M = 0.009 \text{ mg/m}^3 \times PMN_c \times 1.25 \text{ m}^3/\text{hr} \times 8 \text{ hr/day}$
Dyeing and Drying:	Negligible
Buffing: Worst case	$I_B = 15 \text{ mg/m}^3 \times PMN_c \times 1.25 \text{ m}^3/\text{m} \times 8 \text{ hr/day}$
Typical case	$I_B = 1.1 \text{ mg/m}^3 \times PMN_c \times 1.25 \text{ m}^3/\text{m} \times 8 \text{ hr/day}$
Default PMN <sub>c</sub> :	50% for powder dyes 15% for liquid dyes
Dermal (mg/day):	
For solid PMN:	$D_{exp} = 3,100 \times PMN_c$
For liquid PMN:	$D_{exp} = 1,800 \times PMN_c$

**Table 1 (Continued)**

<b>Release Calculations</b>	
<b>Medium</b>	<b>Calculation</b>
Air	AR = negligible
Water	$WR = \frac{5 \text{ to } 40\% \times PV}{NS \times OD}$
Landfill	LR = 1.1% × PV
Incineration	IR = Not expected

Where:

%D	=	Percent weight of formulated dye on the leather (default 1.0% grain leather dyeing, 3.0% suede leather dyeing) <sup>7</sup>
AR	=	Amount of PMN chemical released to Air (kg/yr)
BS	=	Typical batch size, 450-900 kg (default = 680 kg)
D <sub>exp</sub>	=	Potential dermal exposure
DU	=	Use rate per batch of PMN chemical
I <sub>B</sub>	=	Inhalation exposure from buffing
I <sub>M</sub>	=	Inhalation exposure from mixing
IR	=	Amount of PMN chemical incinerated
I <sub>W</sub>	=	Inhalation exposure from weighing
LR	=	Amount of PMN chemical released to Land (kg/yr)
NB	=	Number of batches per day (default = 9)
NS	=	Number of Leather Dyeing Sites
N <sub>w</sub>	=	Total number of workers
OD	=	Days of operation
PMN <sub>c</sub>	=	Concentration of PMN (default 50% for powder dyes 15% for liquid dyes) <sup>7</sup>
PV	=	PMN chemical production volume
WR	=	Amount of PMN chemical released to Water (kg/day-site)

## **1.0 INTRODUCTION**

### **1.1 Background**

Under Section 5 of the Toxic Substances Control Act (TSCA), the U.S. Environmental Protection Agency's (EPA's) Office of Pollution Prevention and Toxics (OPPT) evaluates new chemicals (i.e., those chemicals not listed on the TSCA inventory), for potential risks associated with their stated and potential uses. Existing chemicals may also be evaluated under Sections 4 and 6 of TSCA for potential risks associated with their various uses. In these cases, EPA may develop regulatory controls and/or nonregulatory actions to protect human health and the environment from harm resulting from manufacturing, processing, transport, disposal, and current and potential new uses of existing and new chemical substances.

A new chemical, with certain exceptions, is any chemical that is not currently on the TSCA Inventory of Chemicals in Commerce. The new chemical review under Section 5 of TSCA requires an identification and mitigation of potential risks with the stated and potential uses of the new chemicals. Under Section 5 of TSCA, companies are required to submit a Premanufacture Notification (PMN) at least 90 days prior to commercial production (including importation). The Chemical Engineering Branch (CEB) is responsible for preparing the occupational exposure and release assessments of the new chemicals. These assessments are based on information provided by the PMN submitter, information from readily available databases and literature sources, and standard estimating techniques used by CEB.

CEB has developed a number of "generic scenarios" and modeling approaches for quantifying sources and control efficiencies in assessing exposures and releases for various industries and unit operations. These generic scenarios contain a compilation of information from readily available sources and from past CEB assessments. They have helped CEB to standardize its assessments.

### **1.2 Purpose**

The purpose of this document is to develop a generic scenario for the end use of leather dyeing chemicals. EPA/OPPT frequently receives leather dyeing PMNs and is seeking to improve its capabilities to assess the risks to human health and the environment for this particular type of application. This generic scenario is a compilation of information related to the assessment of occupational exposures and releases, it will serve as an aid to CEB in developing a standardized methodology for evaluating PMNs and leather dyeing chemicals.

### **1.3 Methodology for Developing Estimation Techniques**

The current generic scenario for leather dyeing was used as a guideline for the new generic scenario. Updated data for the leather dyeing industry has been included in this

generic scenario. References listed in the generic scenario were updated with the latest information available. The most recent Census information on the number of workers and sites for the leather dyeing industry was also obtained.

#### **1.4 Hierarchy for Developing Release and Occupational Exposure Estimates**

The goal of this generic scenario is to standardize CEB's approach and methodology to develop accurate release and occupational exposure estimates for leather dyeing chemicals. Actual data that are available and the need to make assumptions that are required for individual estimations may vary significantly between PMN reviews. Therefore, the following hierarchy in evaluating PMNs has been developed to provide consistent and accurate assessments.

1. Empirical data: Data obtained from the PMN submission or from contacts with the submitter should be considered first. It is assumed that data from testing will result in the most accurate release estimates. However, these data and the release and exposure estimates that result from their use should be compared to typical and historical release estimates.
2. Analogous data: It is possible that a facility may not have conducted testing on the PMN chemical, but did conduct tests on other similar chemicals. It may be appropriate to use the results of these tests to estimate releases and exposures. These data and corresponding estimates should also be compared to typical and historical estimates.
3. Generic scenario: In lieu of site-specific testing or analogous data, it may be appropriate to use the methodology described in this generic scenario to develop reasonable worst-case estimates for releases and occupational exposures. The CEB engineer should compare the site-specific information with the assumptions used in the generic scenario and make reasonable adjustments to the methodology based on engineering judgement. The resulting estimates should be compared to historical estimates for consistency.
4. Regulatory limits: If neither site-specific data nor the information needed to develop reasonable estimates using the generic scenario are available, regulatory limits should be considered. It is possible that local, state, or federal agencies may have imposed (or will impose in the future) restrictions on production volumes or PMN concentrations in facility air. If such limits exist, they may be used as reasonable worst-case estimates.

**-- REVISED DRAFT (DO NOT CITE OR QUOTE) --**

GENERIC SCENARIO: LEATHER DYEING

September 2000

5. Modeling: Other than the methodologies presented in this generic scenario, CEB has not developed modeling procedures to estimate releases or occupational exposures. If models are developed and verified through testing, CEB may consider adopting the modeling approach.

## 2.0 INDUSTRY PROFILE

There are approximately 315 tanneries<sup>6</sup> in the US and about 80% of the tanneries perform dyeing operations.<sup>7</sup> In the leather dyeing industry, the annual amount of PMN active colorant in the dyestuff solution used ranges from 200-2,500 kg/tannery, with an average use rate of 1,000 kg/tannery. The total number of hides dyed at each facility typically averages 1,000 sides/day. A batch consists of between 450 and 900 kg of leather with a typical value of 680 kg. This batch size corresponds to between 40 and 80 grain leather sides, and between 100 and 200 suede leather sides, based on a weight of 11kg/side of grain leather and 4.5 kg/side of suede leather.

Leather is not a homogenous product, but is derived from collagen and has been treated with one or more tanning agent(s). Almost all grain leather (i.e., glazed calf, glazed kid, and suede) have dye applied as the bottom color. The final shade is derived by application of a pigment finish. Pigments cover the imperfections in the leather.<sup>5</sup>

### **3.0 PROCESS DESCRIPTION**

Leather is generally dyed in wooden drums or rotating vessels. A dye bath is prepared by adding a dye stuff to the dyeing equipment; surfactants and other auxiliaries may also be added. The bath temperature may range from 0° to 60°C. The leather is brought into the drum or rotating vessel, and the leather is dyed by gentle agitation for approximately 10 minutes. There are also semicontinuous processes ((multimac) dyeing machine) for leather dyeing.<sup>5</sup>

The amount of formulated dyestuff used per batch is 6.8 kg for the grain leather sides, and 20 kg for the suede leather sides. The amount of active PMN in the formulated dyestuff (% active PMN) is typically 50% for powdered dyes and 15% for liquid dyes (most dyes used in leather dyeing are acid dyes).

#### 4.0 SCREENING LEVEL ESTIMATION TECHNIQUES/METHODS

##### 4.1 General Facility Estimates

Generally, facility estimates that are calculated in the following subsections are the number of sites (tanneries) that use the PMN chemical, the use rate of the PMN chemical, and the number of days of operation for each site. This information is determined based on the production volume of the PMN chemical, the amount PMN chemical in each batch, and the number of batches per year.

##### **Number of Sites:**

The average yearly use rate of PMN active colorant in the dye stuff solution is 1,000 kg/tannery. The number of tanneries can be calculated by dividing the PMN chemical production volume by the average use rate of active colorant for each tannery. There are approximately 315 tanneries in the US.<sup>6</sup> About 80% of the tanneries perform dyeing operations. Therefore, the number of sites should not exceed 252 tanneries.<sup>7</sup>

$$NS = \frac{PV}{UR}$$

Where:

NS	=	Number of sites (tanneries)
PV	=	Production volume of PMN chemical
UR	=	Average yearly use rate of PMN chemical per tannery (kg/site-yr) (default = 1,000 kg/site-yr)

##### **Use Rate:**

The average leather batch size is 680 kg. The amount of PMN chemical used for each batch depends on the amount of leather being dyed, the concentration of the PMN in the dyestuff, and the %D.

$$DU = BS \times \%D \times PMN_c$$

Where:

DU	=	Use rate per batch of the PMN chemical, kg/batch
PMN <sub>c</sub>	=	Concentration of the PMN chemical (default = 50% for powdered dyes and 15% for liquid dyes) <sup>7</sup>

-- REVISED DRAFT (DO NOT CITE OR QUOTE) --

GENERIC SCENARIO: LEATHER DYEING

September 2000

- %D = Percent weight of formulated dye on the leather (default = 1.0% for grain leather dyeing and 3.0% for suede leather dyeing)<sup>7</sup>
- BS = Average batch size (default = 680 kg leather)

**Days of Operation:**

The number of days of operation for each tannery depends on the amount of PMN each tannery uses per year (default 1,000 kg), the amount of PMN used in each batch, and number of batches dyed each day. The following equation should be used to calculate the number of operating days.

$$OD = \frac{UR}{DU \times NB}$$

Where:

- DU = Use rate per batch of PMN chemical
- OD = Days of operation
- NB = Number of batches per day at each site (default = 9)<sup>7</sup>
- UR = Average yearly use rate of the PMN chemical per tanning (kg/site-yr) (default = 1,000 kg/site-yr)

**4.2 Occupational Exposure**

**Number of workers and worker activities:<sup>7</sup>**

Worker Activity	Number of Workers per Activity	Duration of Exposure (hrs/day)
Weighing	1	1.5
Mixing	1	8
Dyeing	1	8
Drying	2	8
Buffing	1-2	8
<b>Total</b>	<7	1.5 - 8

$$NW = < 7 \times NS$$

-- REVISED DRAFT (DO NOT CITE OR QUOTE) --

GENERIC SCENARIO: LEATHER DYEING

September 2000

Where:

NW = Number of workers that may be exposed to the  
PMN chemical at each site  
NS = Number of sites (calculated previously)

**Dermal Exposure:**

$D_{exp}$  (mg/day) over OD days

For solid PMN,  $D_{exp} = 3,100 \times PMN_c$   
Basis: Routine, direct handling solids-2 hand<sup>8</sup> (weighing)

For liquid PMN,  $D_{exp} = 1,800 \times PMN_c$   
Basis: Routine, contact 2 hands-liquids<sup>8</sup> (mixing and filling)

Where:

$D_{exp}$  = Potential dermal exposure due to weighing.  
 $PMN_c$  = Concentration of  $PMN_c$  (solid, default = 50%;  
liquid, default = 15%)

**Inhalation Exposure**

**Weighting:** 0.001-3.2 mg/m<sup>3</sup> or an 8 hr geometric mean of 2.1 mg/m<sup>3</sup> total dust.<sup>7</sup>

$$I_W = 2.1 \text{ mg/m}^3 \times 1.25 \text{ m}^3/\text{hr} \times 8 \text{ hr/day} \times PMN_c$$

assume:  $PMN_c =$  50% for powdered dyes and  
15% for liquid dyes.

**Mixing:** 0.002-0.083 mg/m<sup>3</sup> or an 8 hr geometric mean of 0.009 mg/m<sup>3</sup> total dust.<sup>7</sup>

$$I_M = 0.009 \text{ mg/m}^3 \times 1.25 \text{ m}^3/\text{hr} \times 8 \text{ hr/day} \times PMN_c$$

assume:  $PMN_c =$  up to 50%

**Dyeing and Drying:** Inhalation is negligible

-- REVISED DRAFT (DO NOT CITE OR QUOTE) --

GENERIC SCENARIO: LEATHER DYEING

September 2000

**Buffing:** 15 mg/m<sup>3</sup> total dust assuming worst case when ventilation equipment is not working. Otherwise use a range of 0.14-3.3 mg/m<sup>3</sup> or an 8 hr geometric mean of 1.1 mg/m<sup>3</sup> total dust.<sup>7</sup>

Typical  $I_B = 1.1 \text{ mg/m}^3 \times 1.25 \text{ m}^3/\text{m} \times 8 \text{ hr/day} \times \text{PMN}_c$

Worst  $I_B = 15 \text{ mg/m}^3 \times 1.25 \text{ m}^3/\text{m} \times 8 \text{ hr/day} \times \text{PMN}_c$

assume:  $\text{PMN}_c =$  up to 1%

Where:

$I_W$  = Potential inhalation exposure due to weighing.  
 $I_M$  = Potential inhalation exposure due to mixing.  
 $I_B$  = Potential inhalation exposure due to sampling.

### 4.3 Environmental Releases

**Air:** Negligible

Basis: Solid PMN or Liquid PMN (VP < 0.01 torr)

**Water:** WR kg/site OD days

Source: Exhausted dyebath solution

To: POTW

Basis: Based on degree of exhaustion, ranges from 60-95%

Calculation: 
$$\text{WR} = \frac{(1 - \text{EXH}) \times \text{PV}}{\text{NS} \times \text{OD}}$$

Where:

WR = Amount of PMN chemical released to water per site.  
OD = Days of operation (calculated previously).  
PV = Production volume of PMN chemical.  
EXH = Degree of exhausting (default 60 - 95%)

**Landfill:** LR kg/yr

Source: Container residue, scrap and off spec material

-- REVISED DRAFT (DO NOT CITE OR QUOTE) --

GENERIC SCENARIO: LEATHER DYEING

September 2000

Basis: 0.1% of PV from container residue and 1% of PV from scrap and off-spec material.<sup>7</sup>

Calculation:  $LR = 1.1\% \times PV$

Where:

LR = Amount of PMN chemical released to land.  
PV = Production volume of PMN chemical.

**Incineration:** Not expected

All releases of PMN go to wastewater or landfill.

**-- REVISED DRAFT (DO NOT CITE OR QUOTE) --**

GENERIC SCENARIO: LEATHER DYEING

September 2000

**5.0 ADDITIONAL INFORMATION**

This section will be completed in future drafts of this generic scenario.

**-- REVISED DRAFT (DO NOT CITE OR QUOTE) --**

GENERIC SCENARIO: LEATHER DYEING

September 2000

**6.0 OTHER SOURCES**

This section will be completed in future drafts of this generic scenario.

**-- REVISED DRAFT (DO NOT CITE OR QUOTE) --**

GENERIC SCENARIO: LEATHER DYEING

September 2000

**7.0 DATA GAPS AND UNCERTAINTIES**

This section will be completed in future drafts of this generic scenario.

## 8.0 REFERENCES

1. CEB Research Project: Effluent Guidelines Information. Part C - Abstract of the Final Development Document for Effluent Limitations, Guidelines and Standards for the Leather Tanning and Finishing Point Source Category.
2. Kirk Othmer Encyclopedia of Chemical Technology, Vol 14. John Wiley & Sons. New York, 1981. pp 200-288
3. PEI Associates, Inc. CEB Engineering Branch Manual for the Preparation of Engineering Assessments. U.S. EPA OTS/ETD/CEB. February 28, 1991.
4. Vorbach, Jerry. Generic Engineering Assessment Leather Dyeing: Occupation Exposure and Environmental Releases. U.S. EPA OTS/ETD/CEB. July, 1986.
5. Leder, Ishikawa, Shariq; SRI Specialty Chemicals Strategies for Success, Synthetic dryers; December 1997.
6. 1998 County Business Patterns, NAICS 31611, Leather and Hide Tanning and Finishing.
7. CEB Leather Dyeing Generic Scenario.
8. Operations for Revising CEB's Method for Screening - Level Estimates of Dermal Exposure; Final Report June 2000.