Geologic Sequestration of CO₂ and Class VI Wells

Molly Bayer EPA HQ 202-564-1981

Brian Graves EPA Region 6 214-665-7193

UIC Inspector Training
July 2019



Presentation Overview

- Carbon Capture and Storage, Geologic Sequestration and Class VI Rule Background
- Class VI Requirements




Carbon Capture and Storage, Geologic Sequestration (GS) and Class VI Rule Background



... Putting Technology To Work


CO₂
Capture
and
Transport



Geologic Sequestration UIC Program Scope



Coordination on Carbon Capture and Storage (CCS) and Carbon Capture, Utilization and Storage (CCUS)







Friday, July 25, 2008

Part II

Environmental Protection Agency


40 CFR Parts 144 and 146
Federal Requirements Under the
Underground Injection Control (UIC)
Program for Carbon Dioxide (CO₂)
Geologic Sequestration (GS) Wells;
Proposed Rule

Class VI Rulemaking

- Proposed Rule for GS of CO₂
 - Announced by Administrator:
 October 11, 2007
 - Signed by Administrator:
 July 15, 2008
- NODA published in 2009
- Final Rule published on December 10, 2010, revises UIC Program to address Geologic Sequestration via Class VI wells




Geologic Sequestration Scenarios





CO₂ Storage Mechanisms, Monitoring & Potential Leakage Pathways





Class VI Primacy and Direct Implementation

- As of September 7, 2011
 - EPA directly implements the Class VI Program in all States,
 Tribes, and Territories except North Dakota
- States may apply for Class VI primacy at any time
 - States without Safe Drinking Water Act (SDWA) § 1422
 primacy must apply to implement a new § 1422 Program
 - States with § 1422 primacy for Classes I, II, III and V must submit a program revision to add Class VI
- State primacy applications
 - North Dakota application received June 2013
 - North Dakota Class VI Primacy was approved 4/24/18
 - Wyoming and Louisiana have expressed interest in applying for Class VI Primacy



Class VI Implementation


Implementation

- EPA has issued 6 permits
 - Archer Daniels Midland (ADM), Decatur, IL (2 active permits)
 - The FutureGen Alliance, Jacksonville, IL
 (4 permits DOE suspended funding in 2015 and the 4 permits have expired)


Limitations on CCS

- Limited policies to support or encourage climate change mitigation/carbon capture technology deployment (no carbon tax enacted by Congress)
- Resources/financing of projects
- There has been a strong emphasis on enhanced oil recovery (EOR) to store CO₂ (CCUS) due to economics but EOR alone can't achieve the largescale/long-term emissions reductions needed
- Recent changes to IRS § 45Q of the Internal Revenue Code increased the tax credits for CCS from \$10 to \$35/ton for EOR and \$25 to \$50/ ton for non EOR. This has increased interest in both EOR and non EOR projects














Final class VI permit



ADM - Project Photos (June 2013)



Four Compressor Train



Dehydration System



Compressor & Auxiliaries



8" High Pressure transmission Line





ADM - Project Monitoring Photos (June 2013)





Shallow Groundwater Sampling





Soil Gas and CO₂ Flux Networks







CCS #2 Wellhead Under Construction



CCS #2 Finished Wellhead Injecting

CCS #2 Photos courtesy of Andrew Greenhagen EPA Region 5



CCS #2 Annulus Tank









Temperature Logging Tool







Logging Truck

Lubricator for Temperature Logging











Flow Meter

Corrosion Monitor Coupon Loop



At 240 MW, Petra Nova is the world's largest post-combustion carbon capture facility installed on an existing coal-fueled power plant.



NRG's WA Parish Plant SW of Houston

The captured CO₂ will be used in EOR increasing production from 300 to 15,000 bopd In the West Ranch Field.




Net Power LLC - La Porte, Texas



This 50 MW demonstration plant is the world's largest attempt to use carbon dioxide as a working fluid to drive a turbine to generate electricity. Therefore, CO₂ emissions from natural gas combustion to generate electricity are zero. Combustion testing began 5/31/18.



The Net Power Plant Uses the Allam Cycle Shown Below





Class VI Requirements



Class VI Requirements: 40 CFR § 146.82 – 146.95

- 146.82: Required Class VI permit information
- 146.83: Minimum criteria for siting
- 146.84: Area of Review and corrective action
- 146.85: Financial Responsibility
- 146.86: Injection Well Construction
- 146.87: Logging, Sampling, and Testing (prior to operation)
- 146.88: Injection Well Operation
- 146.89: Mechanical Integrity
- 146.90: Testing and Monitoring
- 146.91: Reporting and Recordkeeping
- 146.92: Injection Well Plugging
- 146.93: Post-Injection Site Care and Site closure
- 146.94: Emergency and Remedial Response
- 146.95: Injection Depth Waiver requirements



Class VI Rule Background

Considerations for GS

- Large Volumes
- Buoyancy
- Viscosity (Mobility)
- Corrosivity

New well class established: Class VI

UIC Program Elements

- Site Characterization
- Area of Review (AoR)
- Well Construction
- Well Operation
- Site Monitoring
- Post-Injection Site Care
- Public Participation
- Financial Responsibility
- Site Closure



Class VI Requirements: Overview

- Wells used for injection of CO₂ for geologic sequestration
- Class VI wells <u>by permit</u> only
- Lifetime permit duration including the post-injection monitoring period
- Allow for transitioning from: Class I, II, or V wells or monitoring/stratigraphic wells
- Are flexible to accommodate project variability
 - In injection formation, volume and duration
 - Enable research and use of new, innovative technologies



Class VI Site Characterization Requirements


- Tailored, detailed geologic site characterization requirements (40 CFR § 146.82, 146.83 and 146.87)
 - Identification and characterization of injection and confining zone(s)
 - Establish baseline information and comprehensive project information prior to GS project construction and operation



Class VI Site Characterization Requirements

GS Rule Approach

- Director has discretion to require identification of additional confining zones
- Owners and Operators submit information on the following
 - Structure
 - Stratigraphy
 - Seismicity
 - Baseline geochemistry





Class VI Area of Review and Corrective Action Requirements

- Required at 40 CFR § 146.84
 - Initial delineation of the Area of Review (AoR)
 - Using computational modeling which accounts for the injected CO₂ plume and the area of elevated pressure
 - Relies upon site characterization data
 - Periodic re-evaluation of the AoR at a minimum of every 5 years
 - Relies upon operational and monitoring data
- Allows for phased corrective action of abandoned wells in the AoR at the UIC Director's discretion



Class VI Area of Review






Class VI Well Construction Requirements

GS Rule Approach

- Inject below USDWs (unless an injection depth waiver is issued)
- Long-string casing cemented in place for its entire length
- Surface casing through the base of the lowermost USDW and cemented to surface





Class VI Well Construction and Operation Requirements

- Establishes specific standards for Class VI well construction and operation (40 CFR § 146.81,146.86 and 146.88)
 - Construction materials must be compatible with the injectate and formation fluids
 - Owners or operators must establish site specific operational conditions
 - Use of automatic shut-off devices



Class VI Testing and Monitoring Requirements


- Requires tailored testing and monitoring at each GS project (40 CFR § 146.88,146.89 and 146.90)
 - Monitoring/sampling of the CO₂ (i.e., physical and chemical characteristics)
 - Mechanical integrity testing of injection wells
 - Ground water monitoring
 - Surface-air/soil-gas monitoring at the UIC Director's discretion



Class VI Testing and Monitoring Requirements

GS Rule Approach

- Determine extent of CO₂
 movement and associated area
 of elevated pressure (pressure
 front)
- Techniques, frequency, and spatial resolution of CO₂ plume and pressure front monitoring are not specified in the regulations



Seismic Monitoring Results at Sleipner



Class VI Project Plan Requirements

- Five project-specific plans must be developed, submitted and updated during the life of a GS project
 - Area of Review and Corrective Action (40 CFR § 146.84)
 - Testing and Monitoring (40 CFR § 146.90)
 - Injection Well Plugging (40 CFR § 146.92)
 - Post-Injection Site Care and Closure (40 CFR § 146.93)
 - Emergency and Remedial Response (40 CFR § 146.94)
- The final plans become enforceable permit conditions



Class VI Financial Responsibility (FR) Requirements

- Clarifies and expands FR requirements (40 CFR § 146.85) to ensure funds are available for all phases over the life of a GS project including
 - Project Operation
 - Corrective Action
 - Well Plugging
 - Emergency and Remedial Response
 - Post Injection Site Care (PISC) and Site Closure



Class VI Post-Injection Site Care Requirements

- Required, at 40 CFR § 146.93, appropriate monitoring and other actions (e.g., corrective action) needed following cessation of injection to ensure that USDWs are not endangered
- During the PISC period, the owner or operator will
 - Monitor the CO₂ plume and the associated area of elevated pressure
 - Update models and project plans, as appropriate
 - Perform corrective action, as appropriate
 - Ensure USDW protection
- The PISC period ends with a non-endangerment demonstration approved by the UIC Director



Class VI Post-Injection Site Care Requirements

- Determining the PISC timeframe
 - A 50 year <u>default</u> timeframe with associated modeling information
 - An alternative PISC timeframe determined during the permitting process based on modeling information
 - An updated, refined PISC timeframe may
 - Be informed by monitoring and operational information and modeling updates
 - Result in PISC plan updates and a permit modification



Class VI Injection Depth Waiver Requirements

- Injection depth waiver for Class VI wells (40 CFR § 146.95)
 - Available to owners or operators applying for a Class VI permit to inject above the lowermost USDW or between USDWs
 - Additional requirements to ensure protection of USDWs above and below the injection zone
 - Accommodates varied geologic settings and uses GS capacity at a range of depths