UNITED STATES ENVIRONMENTAL PROTECTION AGENCY REGION 9

75 Hawthorne Street San Francisco, CA 94105

AUTHORIZATION TO DISCHARGE UNDER THE NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM

NPDES PERMIT NO. GU0020389

In compliance with the provisions of the Clean Water Act ("CWA") (Public Law 92-500, as amended, 33 U.S.C. §§ 1251 et seq.), the following discharger is authorized to discharge from the identified facility at the outfall location(s) specified below, in accordance with the effluent limits, monitoring requirements, and other conditions set forth in this permit. This permit authorizes the discharge of only those pollutants resulting from facility processes, waste streams, and operations that have been clearly identified in the permit application process.

Permittee Name	United States Navy			
Permittee Address	U.S. Naval Base Guam			
	PSC 445 Box 152			
	FPO AP, GU 96540			
Facility Name	U.S. Navy Fena Water Treatment Plant			
Facility Location	Route 2A, Naval Magazine			
Address	Santa Rita, GU 96915			
Facility Rating	Minor			

Outfall	General Type of	Outfall	Outfall	Receiving
Number	Waste Discharged	Latitude	Longitude	Water
002	Emergency discharges of filter	13°22' 38" N	144°40' 51" E	Namo River
	backwash wastewater and/or clarifier			
	overflow			

This permit was issued on:	Date of signature below
This permit shall become effective on:	June 1, 2022
Permit reapplication due no later than:	December 2, 2026
This permit shall expire at midnight on:	May 31, 2027

In accordance with 40 CFR § 122.21(d), the permittee shall submit a new application for a permit at least 180 days before the expiration date of this permit, unless permission for a date no later than the permit expiration date has been granted by the Director.

Signed for the Regional Administrator:

Tomás Torres, Director	Date
Water Division	

TABLE OF CONTENTS

Part 1	I. EFFLUENT LIMITS AND MONITORING REQUIREMENTS	3
<i>A</i> .	Effluent Limits and Monitoring Requirements	3
В.	Effluent Limits and Monitoring Requirements – Outfall Number 002	5
C.	Sampling	5
D.	General Monitoring and Reporting	6
<i>E</i> .	Receiving Water Monitoring	9
Part 1	II. SPECIAL CONDITIONS	10
<i>A</i> .	Permit Reopener(s)	10
B.	Twenty-four Hour Reporting of Noncompliance	10
C.	Best Management Practices and Pollution Prevention	11
D.	Additional Special Conditions (CWA 401 Certification)	12
Part 1	III. STANDARD CONDITIONS	13
<i>A</i> .	All NPDES Permits	13
Attac	hment A: Definitions	27
Attac	hment B: Location Maps	29
	hment C: Wastewater Flow Schematic	
Attac	chment D: 401 Water Quality Certification (Order #2022-05)	31

Part I. EFFLUENT LIMITS AND MONITORING REQUIREMENTS

A. Effluent Limits and Monitoring Requirements

- 1. Effluent Limits Outfall Number 002
 - a. The permittee is authorized to discharge filter backwash wastewater and/or clarifier overflow in compliance with the effluent limits and monitoring requirements specified in Table 1.
- 2. The discharge of pollutants at any point other than the outfall number specifically authorized in this permit (Outfall 002) is prohibited.
- 3. The discharge from any point other than the backwash settling tank via Outfall 002 in the treatment process is prohibited.
- 4. The discharge of toxic substances in toxic amounts, including, but not limited to, pesticides, herbicides, heavy metals, and organic chemicals, is prohibited.
- 5. The discharge shall be free from substances, conditions, or combinations that:
 - a. Cause visible floating materials, debris, oil, grease, scum, foam, and other floating material which degrade water quality or use;
 - b. Produce visible turbidity, settle to form deposits, or otherwise adversely affect aquatic life;
 - c. Produce objectionable color, odor, or taste, directly, or by chemical or biological action;
 - d. Injure or are toxic or harmful to humans, animals, plants, or aquatic life; and
 - e. Induce the growth of undesirable aquatic life.
 - f. Form an oil deposit on the shores or bottom of the receiving body of water.
- 6. The discharge shall not cause the following conditions in the receiving water:
 - g. Concentrations of suspended matter at any point to be increased more than 25% from ambient at any time, and the total concentration should not exceed 40 mg/L, except when due to natural conditions,
 - h. Temperature to deviate more than 1.0 degree Centigrade from ambient conditions;
 - i. pH outside the range of 6.5 to 9.0 standard units,
 - j. Orthophosphate concentrations to exceed 0.10 mg/L,

NPDES Permit No. GU0020389 Page 4 of 33

- k. Nitrate-nitrogen concentration to exceed 0.50 mg/L and ammonia concentrations to exceed 0.02 mg/L,
- 1. Turbidity to exceed 1.0 NTU over ambient conditions, except when due to natural conditions;
- m. Concentration of dissolved oxygen to be less than 75% of saturation;
- n. Alterations of the marine environment that would alter the salinity of marine waters of Guam more than 10% of the ambient conditions, except when due to natural conditions; and
- o. Toxic substances in the receiving water that:
 - i. Produce detrimental physiological, acute, or chronic responses in human, plant, animal, or aquatic life, and
 - ii. Produce contamination in harvestable aquatic life to the extent that it causes detrimental physiological, acute, or chronic responses in humans or protected wildlife, when consumed.
 - iii. Result in the survival of aquatic life subject to the discharge to be less than that for the same water body in areas unaffected by the discharge.
- 7. The discharge of any radioactive wastes and contaminated radioactive materials is strictly prohibited.

B. Effluent Limits and Monitoring Requirements – Outfall Number 002

Table 1. Effluent Limits and Monitoring Requirements

Parameter ⁽²⁾	Maximum Allowable Discharge Concentration and Loadin	Monitoring Requirements		
Parameter	Maximum Daily	Units	Frequency	Sample Type
Flow rate	(1)	MGD	Continuous	Continuous
рН	Within 6.5 and 9.0 at all times.	S.U.	Continuous	Grab ⁽⁴⁾
Turbidity	1.0 greater than receiving water body	NTU	1x/discharge	Grab ⁽⁴⁾
Solids, settleable	45.0	mL/L	1x/discharge	Grab ⁽⁴⁾
Solids, total dissolved	1,000.0	mg/L	1x/discharge	Grab ⁽⁴⁾
Nitrate-nitrite (as N)	0.5	mg/L	1x/discharge	Grab ⁽⁴⁾
Total aluminium	1.0	mg/L	1x/discharge	Grab ⁽⁴⁾
Fluoride	0.8	mg/L	1x/discharge	_
Chlorine, Total Residual (TRC)	11.0	μg/L	1x/discharge	Grab ⁽⁴⁾
Copper	3.0	μg/L	1x/discharge	Grab ⁽⁴⁾
Mercury	0.051	μg/L	1x/discharge	Grab ⁽⁴⁾
Cadmium	3.9	μg/L	1x/discharge	Grab ⁽⁴⁾
Chromium (VI)	16.0	μg/L	1x/discharge	Grab ⁽⁴⁾
Selenium	20.0	μg/L	1x/discharge	Grab ⁽⁴⁾
Silver	4.1	μg/L	1x/discharge	Grab ⁽⁴⁾
Zinc	120	μg/L	1x/discharge	Grab ⁽⁴⁾
Chloroform	470.0	μg/L	1x/discharge	Grab ⁽⁴⁾
Dichlorobromomethane	46.0	μg/L	1x/discharge	Grab ⁽⁴⁾
Heptachlor	0.00021	μg/L	1x/discharge	Grab ⁽⁴⁾

- (1) No effluent limits are set at this time, but monitoring and reporting is required.
- (2) All metals shall be measured and reported in terms of total recoverable.
- (3) Continuous monitoring only required during discharge.
- (4) Sample type is grab because the discharge occurs in batches. Grab samples shall be taken when the concentration of pollutants are at their highest. If a peak concentration time is not determined, the sample shall be taken during the first thirty minutes of discharge. If the discharge time exceeds 3 hours, another discrete sample must be analyzed and reported.

C. Sampling

- 1. Samples shall be representative of the volume and quality of effluent discharged over the sampling and reporting period. All samples are to be taken during normal operating hours. The Permittee shall identify the effluent sampling location used for each discharge.
- 2. Samples shall be taken at the following locations:

- a. Effluent samples shall be taken after inplant return flows and the last treatment process and prior to mixing with the receiving water, where representative samples can be obtained. For Outfall 002, this means at the top of the backwash settling tank during a discharge event.
- 3. For intermittent discharges, the permittee shall monitor on the first day of discharge. The permittee is not required to monitor in excess of the minimum frequency required in Table 1. If there is no discharge, the permittee is not required to monitor the effluent.
- 4. For any unauthorized discharge, such as those that might occur from places other than Outfall 002 or from overflows from parts of the treatment process, the permittee shall:
 - a. Monitor for parameters specified in Table 2:

Table 2: Monitoring Requirements for Unauthorized Discharges

Parameter	Units	Frequency	Sample Type
Total Flow	MGD	1x/discharge	Estimate
pН	S.U.	(1)	Grab
Turbidity	μg/L	1x/discharge	Grab
Settleable Solids	μg/L	1x/discharge	Grab
TRC	μg/L	1x/discharge	Grab
Aluminum	μg/L	1x/discharge	Grab ⁽²⁾
Copper	μg/L	1x/discharge	Grab ⁽²⁾
Manganese	μg/L	1x/discharge	Grab ⁽²⁾
Mercury	μg/L	1x/discharge	Grab ⁽²⁾
Zinc	μg/L	1x/discharge	Grab ⁽²⁾
Chlorodibromomethane	μg/L	1x/discharge	Grab
Chloroform	μg/L	1x/discharge	Grab
Dichlorobromomethane	μg/L	1x/discharge	Grab
Heptachlor	μg/L	1x/discharge	Grab

- (1) One discrete pH sample shall be taken within 10 minutes of the discovery of the unauthorized discharge. One additional pH discrete sample shall be taken per additional hour of an unauthorized discharge.
- (2) All metals shall be measured and reported in terms of total recoverable.
- b. Report the authorized discharge, as specified in Part I.2.b Special Conditions, Twenty-Four Hour Reporting of Noncompliance.

D. General Monitoring and Reporting

1. All monitoring shall be conducted in accordance with 40 CFR § 136 test methods, unless otherwise specified in this permit. For influent and effluent analyses required in this permit, the permittee shall utilize 40 CFR § 136 test methods with MDLs and MLs that are lower than the effluent limits in this permit. For parameters without an effluent limit, the permittee must use an analytical method at or below the level of the applicable water quality criterion for the measured pollutant. If all MDLs or MLs are

higher than these effluent limits or criteria concentrations, then the permittee shall utilize the test method with the lowest MDL or ML. In this context, the permittee shall ensure that the laboratory utilizes a standard calibration where the lowest standard point is equal to or less than the ML. Influent and effluent analyses for metals shall measure "total recoverable metal", except as provided under 40 CFR § 122.45(c).

- 2. As an attachment to the first DMR, the permittee shall submit, for all parameters with monitoring requirements specified in this permit:
 - a. The test method number or title and published MDL or ML,
 - b. The preparation procedure used by the laboratory,
 - c. The laboratory's MDL for the test method computed in accordance with Appendix B of 40 CFR § 136,
 - d. The standard deviation (S) from the laboratory's MDL study,
 - e. The number of replicate analyses (n) used to compute the laboratory's MDL, and
 - f. The laboratory's lowest calibration standard.

As part of each DMR submittal, the permittee shall notify EPA of any changes to the laboratory's test methods, MDLs, MLs, or calibration standards. If there are any changes to the laboratory's test methods, MDLs, MLs, or calibration standards, these changes shall be summarized in an attachment to the subsequent DMR submittal.

- 3. The permittee shall develop a Quality Assurance ("QA") Manual for the field collection and laboratory analysis of samples. The purpose of the QA Manual is to assist in planning for the collection and analysis of samples and explaining data anomalies if they occur. The QA Manual shall be developed (or updated) within 90 days of permit issuance. At a minimum, the QA Manual shall include the following:
 - a. Identification of project management and a description of the roles and responsibilities of the participants; purpose of sample collection; matrix to be sampled; the analytes or compounds being measured; applicable technical, regulatory, or program-specific action criteria; personnel qualification requirements for collecting samples;
 - b. Description of sample collection procedures; equipment used; the type and number of samples to be collected including QA/Quality Control ("QC") samples; preservatives and holding times for the samples (see 40 CFR § 136.3); and chain of custody procedures;
 - c. Identification of the laboratory used to analyze the samples; provisions for any proficiency demonstration that will be required by the laboratory before or after contract award such as passing a performance evaluation sample; analytical method to be used; MDL and ML to be reported; required QC results to be reported (e.g., matrix spike recoveries, duplicate relative percent differences, blank contamination, laboratory control sample recoveries, surrogate spike

- recoveries, etc.) and acceptance criteria; and corrective actions to be taken in response to problems identified during QC checks; and
- d. Discussion of how the permittee will perform data review, report results, and resolve data quality issues and identify limits on the use of data.
- 4. Throughout all field collection and laboratory analyses of samples, the permittee shall use the QA/QC procedures documented in their QA Manual. If samples are tested by a contract laboratory, the permittee shall ensure that the laboratory has a QA Manual on file. A copy of the permittee's QA Manual shall be retained on the permittee's premises and available for review by regulatory authorities upon request. The permittee shall review its QA Manual annually and revise it, as appropriate.
- 5. Samples collected during each month of the reporting period must be reported on Discharge Monitoring Report forms, as follows:
 - a. For a *maximum daily* permit limit or monitoring requirement when one or more samples are collected during the month, report either:

The *maximum value*, if the maximum value of all analytical results is greater than or equal to the ML; or

NODI(Q), if the maximum value of all analytical results is greater than or equal to the laboratory's MDL, but less than the ML; or NODI(B), if the maximum value of all analytical results is less than the laboratory's MDL.

b. For an *average weekly* or *average monthly* permit limit or monitoring requirement when only one sample is collected during the week or month, report either:

The *maximum value*, if the maximum value of all analytical results is greater than or equal to the ML; or

NODI(Q), if the maximum value of all analytical results is greater than or equal to the laboratory's MDL, but less than the ML; or NODI(B), if the maximum value of all analytical results is less than the laboratory's MDL.

c. For an *average weekly* or *average monthly* permit limit or monitoring requirement when more than one sample is collected during the week or month, report:

The average value of all analytical results where 0 (zero) is substituted for NODI (B) and the laboratory's MDL is substituted for NODI (Q).

6. In addition to information requirements specified under 40 CFR § 122.41(j)(3), records of monitoring information shall include: the laboratory which performed the analyses and any comment, case narrative, or summary of results produced by the laboratory. The records should identify and discuss QA/QC analyses performed concurrently during sample analyses and whether project and 40 CFR § 136

requirements were met. The summary of results must include information on initial and continuing calibration, surrogate analyses, blanks, duplicates, laboratory control samples, matrix spike and matrix spike duplicate results, and sample condition upon receipt, holding time, and preservation.

- 7. The permittee shall electronically submit Discharge Monitoring Reports using NetDMR (http://www.epa.gov/netdmr).
- 8. Monthly DMRs shall be submitted quarterly, by the 28th day of the month following the previous calendar quarter. For example, the three DMR forms for January, February, and March are due on April 28th. Annual and quarterly monitoring must be conducted starting in the first complete quarter or calendar year following permit issuance. Reporting for annual monitoring is due on January 28th of the following year. A DMR must be submitted for the reporting period even if there was not any discharge. If there is no discharge from the facility during the reporting period, the permittee shall submit a DMR indicating no discharge as required.
- 9. The permittee shall submit an electronic and paper Discharge Monitoring Report, as well as any other report submittals required by this permit (i.e. receiving water monitoring results), to Guam EPA. The submittals shall be identified with WQC Order #2022-05 and the NPDES Permit Number and include the certifying representative's name, title, mailing address, and phone number. Electronic submissions shall be sent to jesse.cruz@epa.guam.gov and <a href="mailto:mai

Guam EPA

Attn: 401 Federal Permit Manager, NPS Program, EMAS Division 3304 Mariner Avenue, Bldg. 17-3304 Barrigada, Guam 96913

E. Receiving Water Monitoring

- 1. The permittee shall conduct the monitoring described in Table 1 for turbidity at a location upstream and downstream of the discharge during the duration of the discharge.
- 2. The permittee shall conduct receiving water monitoring for the pollutants at the locations identified in Table 3 and frequencies identified in Table 4, below. All samples shall be water column samples.
- 3. The receiving water must not exceed narrative water quality standards, as described in I.A, Effluent Limits, above.
- 4. The permittee shall retain and submit all monitoring data along with future applications, or at the request of EPA or Guam Environmental Protection Agency. The permittee shall submit receiving water monitoring result, along with effluent monitoring information, as part of their regular DMR submissions.

Table 3. Receiving Water Monitoring Locations

Station	Name	Description	
UR-1	Upstream	Single location immediately upstream of the outfall	
UR-2	Downstream	Single location at least 200 feet downstream of the outfall	

Table 4. Receiving Water Monitoring Requirements

Parameter	Units	Frequency	Depth	Sample Type			
	Station UR-1						
Turbidity	mg/L	1x/discharge	Profile	Grab			
Hardness, total (as CaCO3)	mg/L	1x/discharge	Profile	Grab			
Station UR-2							
Turbidity	mg/L	1x/discharge	Profile	Grab			

Part II. SPECIAL CONDITIONS

A. Permit Reopener(s)

1. In accordance with 40 CFR §§ 122 and 124, this permit may be modified by EPA to include effluent limits, monitoring, or other conditions to implement new regulations, including EPA-approved water quality standards; or to address new information indicating the presence of effluent toxicity or the reasonable potential for the discharge to cause or contribute to exceedances of water quality standards.

B. Twenty-four Hour Reporting of Noncompliance

1. The permittee shall report any noncompliance which may endanger human health or the environment. The permittee is required to provide an oral report by directly speaking with an EPA and Guam EPA staff person within 24 hours from the time the permittee becomes aware of the noncompliance. If the permittee is unsuccessful in reaching a staff person, the permittee shall provide notification by 9 a.m. on the first business day following the noncompliance to the EPA Wastewater Enforcement Section Manager at 415-947-4179 and to the Guam EPA Administrator at 671-475-1658.

The permittee shall follow up with a written submission within five days of the time the permittee becomes aware of the noncompliance. The written submission shall be emailed to R9NPDES@epa.gov and/or the EPA staff person initially notified. The submission shall contain a description of the noncompliance and its cause; the period of noncompliance, including exact dates and times; and if the noncompliance has not

been corrected, the anticipated time it is expected to continue; and steps taken or planned to reduce, eliminate, and prevent reoccurrence of the noncompliance.

- 2. The following shall be included as information which must be reported within 24 hours under this paragraph.
 - a. Any unanticipated bypass which exceeds any effluent limit in the permit (see 40 CFR § 122.44(g)).
 - b. Any upset which exceeds any effluent limit in the permit.
 - c. Violation of a maximum daily discharge limit for any of the pollutants listed by the director in the permit to be reported within 24 hours (see 40 CFR § 122.44(g)).
- 3. EPA may waive the written report on a case-by-case basis for reports required under paragraph B.2, if the oral report has been received within 24 hours.

C. Best Management Practices and Pollution Prevention

- 1. The permittee shall minimize the frequency and impacts of unauthorized discharges or spills.
- 2. The permittee shall contain and divert all discharges and upsets as to avoid or reduce the contamination of flow from potential sources of pollution.
- 3. The permittee shall clean all potential drainage areas that are possible sources of pollutants, using such measures as sweeping at regular intervals, keeping materials orderly and labeled, and storing materials in appropriate containers.

D. Additional Special Conditions (CWA 401 Certification)

Per the CWA 401 certification (see Attachment D), Guam EPA has stipulated the following specific conditions to be included in this permit in order to comply with all provisions of Guam Water Quality Standards:

- 1. The permittee shall submit the following monitoring documents to Guam EPA quarterly, consistent with I.D.9, above:
 - a. An electronic or paper Discharge Monitoring Report (DMR);
 - b. Receiving water monitoring results (Part I.E. Table 4: (Station URI and Station UR-2) Receiving Water Monitoring Requirements); and
 - c. Receiving water monitoring results at UR-I and UR-2 for narrative water quality standards described in Part I.A.5.
- 2. The permittee shall provide the coordinates of the upstream and downstream receiving water monitoring stations (UR-I and UR-2) to Guam EPA consistent with provision I.D.9 above.
- 3. Point source discharge(s) to waterbodies under the jurisdiction of Guam EPA must be consistent with the antidegradation policy in 22 GAR §5101(b).
- 4. The permittee shall develop and implement a Spill Prevention and Containment Plan.
- 5. The permittee shall have adequate and appropriate spill response materials on hand to respond to emergency release of oil, petroleum or any other material into waters of the territory.
- 6. Any unpermitted discharge into territorial waters or onto land with a potential for entry into territorial waters, is prohibited. If this occurs, the permittee shall immediately take the following actions:
 - a. Cease operations at the location of the violation or spill.
 - b. Assess the cause of the water quality problem and take appropriate measures to correct the problem and/or prevent further environmental damage.
 - c. Notify Guam EPA of the failure to comply. All petroleum spills shall be reported immediately to:
 - (1) Guam's Emergency 911 system
 - (2) Guam EPA's 24-Hour Spill Response Team at (671) 888-6488 or during working hours (671) 300-4751
 - (3) US Coast Guard Sector Guam (671) 355-4824
 - (4) National Response Center 1-800-424-8802
 - d. Submit a detailed written report to Guam EPA within five days of noncompliance that describes the nature of the event, corrective action taken and/or planned, steps to be taken to prevent a recurrence, results of any samples taken, and any other pertinent information.
- 7. Compliance with this condition does not relieve the permittee from responsibility to maintain continuous compliance with the terms and conditions of this Order or the resulting liability from failure to comply.

- 8. Submittal or reporting of any of this information does not provide relief from any subsequent enforcement actions for unpermitted discharges to waters of the United States.
- 9. The permittee shall provide notice to Guam EPA consistent with condition I.D.9: a. Immediately upon discovery of noncompliance with the provisions of this Order.
- 10. A Notice of Violation/Work Stop Order will be issued if certification conditions are not adhered to or when significant or sustained water quality degradation occurs. Work or discharge shall be suspended or halted until the permittee addresses environmental problems/concerns to Guam EPA's satisfaction. Guam EPA may also levy penalties and fines. Invalidity or enforceability of one or more provisions of this certification shall not affect any other provision of this certification.

Part III. STANDARD CONDITIONS

The permittee shall comply with all EPA Region 9 Standard Conditions below.

A. All NPDES Permits

In accordance with 40 CFR § 122.41, the following conditions apply to all NPDES permits and are expressly incorporated into this permit.

1. Duty to comply; at 40 CFR § 122.41(a).

The permittee must comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the CWA and is grounds for enforcement action; for permit termination, revocation and reissuance, or modification; or denial of a permit renewal application.

- a. The permittee shall comply with effluent standards or prohibitions established under section 307(a) of the CWA for toxic pollutants and with standards for sewage sludge use or disposal established under 405(d) of the CWA within the time provided in the regulations that established these standards or prohibitions or standards for sewage sludge use or disposal, even if the permit has not yet been modified to incorporate the requirement.
- b. The Clean Water Act provides that any person who violates section 301, 302, 306, 307, 308, 318 or 405 of the Act, or any permit condition or limitation implementing any such sections in a permit issued under section 402, or any requirement imposed in a pretreatment program approved under sections 402(a)(3) or 402(b)(8) of the Act, is subject to a civil penalty not to exceed \$25,000 per day for each violation. The Clean Water Act provides that any person who negligently violates sections 301, 302, 306, 307, 308, 318, or 405 of the Act, or any condition or limitation implementing any of such sections in a permit

issued under section 402 of the Act, or any requirement imposed in a pretreatment program approved under section 402(a)(3) or 402(b)(8) of the Act, is subject to criminal penalties of \$2,500 to \$25,000 per day of violation, or imprisonment of not more than 1 year, or both. In the case of a second or subsequent conviction for a negligent violation, a person shall be subject to criminal penalties of not more than \$50,000 per day of violation, or by imprisonment of not more than 2 years, or both. Any person who knowingly violates such sections, or such conditions or limitations is subject to criminal penalties of \$5,000 to \$50,000 per day of violation, or imprisonment for not more than 3 years, or both. In the case of a second or subsequent conviction for a knowing violation, a person shall be subject to criminal penalties of not more than \$100,000 per day of violation, or imprisonment of not more than 6 years, or both. Any person who knowingly violates section 301, 302, 303, 306, 307, 308, 318 or 405 of the Act, or any permit condition or limitation implementing any of such sections in a permit issued under section 402 of the Act, and who knows at that time that he thereby places another person in imminent danger of death or serious bodily injury, shall, upon conviction, be subject to a fine of not more than \$250,000 or imprisonment of not more than 15 years, or both. In the case of a second or subsequent conviction for a knowing endangerment violation, a person shall be subject to a fine of not more than \$500,000 or by imprisonment of not more than 30 years, or both. An organization, as defined in section 309(c)(3)(B)(iii) of the CWA, shall, upon conviction of violating the imminent danger provision, be subject to a fine of not more than \$1,000,000 and can be fined up to \$2,000,000 for second or subsequent convictions.1

c. Any person may be assessed an administrative penalty by the Administrator for violating section 301, 302, 306, 307, 308, 318 or 405 of this Act, or any permit condition or limitation implementing any of such sections in a permit issued under section 402 of this Act. Administrative penalties for Class I violations are not to exceed \$10,000 per violation, with the maximum amount of any Class I penalty assessed not to exceed \$25,000. Penalties for Class II violations are not to exceed \$10,000 per day for each day during which the violation continues, with the maximum amount of any Class II penalty not to exceed \$125,000.

2. Duty to reapply; at 40 CFR § 122.41(b).

If the permittee wishes to continue an activity regulated by this permit after the expiration date of this permit, the permittee must apply for and obtain a new permit. Any permittee with a currently effective permit shall submit a new application at least 180 days before the expiration date of the existing permit, unless permission for a later date has been granted by the Director.

3. Need to halt or reduce activity not a defense; at 40 CFR § 122.41(c).

¹ The civil and administrative penalty amounts are adjusted annually for inflation pursuant to the Federal Civil Penalties Inflation Adjustment Act Improvements Act of 2015, and the current penalty amounts are set forth in 40 CFR § 19.4.

It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

4. Duty to mitigate; at 40 CFR § 122.41(d).

The permittee shall take all reasonable steps to minimize or prevent any discharge or sludge use or disposal in violation of this permit which has a reasonable likelihood of adversely affecting human health or the environment.

5. Proper operation and maintenance; at 40 CFR § 122.41(e).

The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the conditions of this permit. Proper operation and maintenance also includes adequate laboratory controls and appropriate quality assurance procedures. This provision requires the operation of backup or auxiliary facilities or similar systems which are installed by a permittee only when the operation is necessary to achieve compliance with the conditions of the permit.

6. Permit actions; at 40 CFR § 122.41(f).

This permit may be modified, revoked and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition.

7. Property rights; at 40 CFR § 122.41(g).

This permit does not convey any property rights of any sort, or any exclusive privilege.

8. Duty to provide information; at 40 CFR § 122.41(h).

The permittee shall furnish to the Director, within a reasonable time, any information which the Director may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit or to determine compliance with this permit. The permittee shall also furnish to the Director upon request, copies of records required to be kept by this permit.

9. Inspection and entry; at 40 CFR § 122.41(i).

The permittee shall allow the Director, or an authorized representative (including an authorized contractor acting as a representative of the Administrator), upon presentation of credentials and other documents as may be required by law, to:

- a. Enter upon the permittee's premises where a regulated facility or activity is located or conducted, or where records must be kept under the conditions of this permit;
- b. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit; and
- d. Sample or monitor at reasonable times, for the purposes of assuring permit compliance or as otherwise authorized by the CWA, any substances or parameters at any location.
- 10. Monitoring and records; at 40 CFR § 122.41(j).
 - a. Samples and measurements taken for the purpose of monitoring shall be representative of the monitored activity.
 - b. Except for records of monitoring information required by this permit related to the permittee's sewage sludge use and disposal activities, which shall be retained for a period of at least five years (or longer as required by 40 CFR § 503), the permittee shall retain records of all monitoring information, including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this permit, and records of all data used to complete the application for this permit, for a period of at least 3 years from the date of the sample measurement, report or application. This period may be extended by request of the Director at any time.
 - c. Records of monitoring information shall include:
 - (1) The date, exact place, and time of sampling or measurements;
 - (2) The individual(s) who performed the sampling or measurements;
 - (3) The date(s) analyses were performed
 - (4) The individuals(s) who performed the analyses;
 - (5) The analytical techniques or methods used; and
 - (6) The results of such analyses.
 - d. Monitoring must be conducted according to test procedures approved under 40 CFR § 136 or, in the case of sludge use or disposal, approved under 40 CFR § 136 unless otherwise specified in 40 CFR § 503, unless other test procedures have been specified in the permit.

e. The CWA provides that any person who falsifies, tampers with, or knowingly renders inaccurate any monitoring device or method required to be maintained under this permit shall, upon conviction, be punished by a fine of not more than \$10,000, or by imprisonment for not more than 2 years, or both. If a conviction of a person is for a violation committed after a first conviction of such person under this paragraph, punishment is a fine of not more than \$20,000 per day of violation, or by imprisonment of not more than 4 years, or both.

11. Signatory requirement; at 40 CFR § 122.41(k).

- a. All applications, reports, or information submitted to the Director shall be signed and certified. (See 40 CFR § 122.22.) All permit applications shall be signed as follows:
 - (1) For a corporation. By a responsible corporate officer. For the purpose of this section, a responsible corporate officer means: (i) A president, secretary, treasurer, or vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy- or decision-making functions for the corporation, or (ii) the manager of one or more manufacturing, production, or operating facilities, provided, the manager is authorized to make management decisions which govern the operation of the regulated facility including having the explicit or implicit duty of making major capital investment recommendations, and initiating and directing other comprehensive measures to assure long term environmental compliance with environmental laws and regulations; the manager can ensure that the necessary systems are established or actions taken to gather complete and accurate information for permit application requirements; and where authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures.

Note: EPA does not require specific assignments or delegations of authority to responsible corporate officers identified in 40 CFR § 122.22(a)(1)(i). The Agency will presume that these responsible corporate officers have the requisite authority to sign permit applications unless the corporation has notified the Director to the contrary. Corporate procedures governing authority to sign permit applications may provide for assignment or delegation to applicable corporate positions under 40 CFR § 122.22(a)(1)(ii) rather than to specific individuals.

- (2) For a partnership or sole proprietorship. By a general partner or the proprietor, respectively; or
- (3) For a municipality, State, Federal, or other public agency. By either a principal executive officer or ranking elected official. For purposes of this section, a principal executive officer of a Federal agency includes: (i) The chief executive officer of the agency, or (ii) a senior executive officer

having responsibility for the overall operations of a principal geographic unit of the agency (e.g., Regional Administrators of EPA).

- b. All reports required by permits, and other information requested by the Director shall be signed by a person described in paragraph (a) of this section, or by a duly authorized representative of that person. A person is a duly authorized representative only if:
 - (1) The authorization is made in writing by a person described in paragraph (a) of this section;
 - (2) The authorization specifies either an individual or a position having responsibility for the overall operation of the regulated facility or activity such as the position of plant manager, operator of a well or well field, superintendent, position of equivalent responsibility, or an individual or position having overall responsibility for environmental matters of the company, (A duly authorized representative may thus be either a named individual or any individual occupying a named position.) and,
 - (3) The written authorization is submitted to the Director.
- c. Changes to authorization. If an authorization under paragraph (b) of this section is no longer accurate because a different individual or position has responsibility for the overall operation of the facility, a new authorization satisfying the requirements of paragraph (b) of this section must be submitted to the Director prior to or together with any reports, information, or applications to be signed by an authorized representative.
- d. Certification. Any person signing a document under paragraph (a) or (b) of this section shall make the following certification:
 - "I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."
- e. The CWA provides that any person who knowingly makes any false statement, representation, or certification in any record or other document submitted or required to be maintained under this permit, including monitoring reports or reports of compliance or non-compliance shall, upon conviction, be punished by a fine of not more than \$10,000 per violation, or by imprisonment for not more than 6 months per violation, or by both.

- 12. Reporting requirements; at 40 CFR § 122.41(1).
 - a. Planned changes. The permittee shall give notice to the Director as soon as possible of any planned physical alternations or additions to the permitted facility. Notice is required only when:
 - (1) The alteration or addition to a permitted facility may meet one of the criteria for determining whether a facility is a new source in 40 CFR § 122.29(b); or
 - (2) The alteration or addition could significantly change the nature or increase the quantity of pollutants discharged. This notification applies to pollutants which are subject neither to effluent limitations in the permit, nor to notification requirements under 40 CFR § 122.42(a)(1).
 - (3) The alteration or addition results in a significant change in the permittee's sludge use or disposal practices, an such alteration, addition, or change may justify the application of permit conditions that are different from or absent in the existing permit, including notification of additional use or disposal sites not reported during the permit application process or not reported pursuant to an approved land application plan;
 - b. Anticipated noncompliance. The permittee shall give advance notice to the Director of any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements.
 - c. Transfers. This permit is not transferable to any person except after notice to the Director. The Director may require modification or revocation and reissuance of the permit to change the name of the permittee and incorporate such other requirements as may be necessary under the CWA. (See 40 CFR § 122.61; in some cases, modification or revocation and reissuance is mandatory.)
 - (1) Transfers by modification. Except as provided in paragraph (b) of this section, a permit may be transferred by the permittee to a new owner or operator only if the permit has been modified or revoked and reissued (under 40 CFR § 122.62(b)(2)), or a minor modification made (under 40 CFR § 122.63(d)), to identify the new permittee and incorporate such other requirements as may be necessary under CWA.
 - (2) Automatic transfers. As an alternative to transfers under paragraph (a) of this section, any NPDES permit may be automatically transferred to a new permittee if:
 - (A) The current permittee notifies the Director at least 30 days in advance of the proposed transfer date in paragraph (b)(2) of this section;

- (B) The notice includes a written agreement between the existing and new permittees containing a specific date for transfer of permit responsibility, coverage, and liability between them; and
- (C) The Director does not notify the existing permittee and the proposed new permittee of his or her intent to modify or revoke and reissue the permit. A modification under this subparagraph may also be a minor modification under 40 CFR § 122.63. If this notice is not received, the transfer is effective on the date specified in the agreement mentioned in paragraph (b)(2) of this section.
- d. Monitoring reports. Monitoring results shall be reported at the intervals specified elsewhere in this permit.
 - (1) Monitoring results must be reported on a Discharge Monitoring Report (DMR) or forms provided or specified by the Director for reporting results of monitoring of sludge use or disposal practices. As of December 21, 2016 all reports and forms submitted in compliance with this section must be submitted electronically by the permittee to the Director or initial recipient, as defined in 40 CFR § 127.2(b), in compliance with this section and 40 CFR § 3 (including, in all cases, subpart D to part 3), 40 CFR § 122.22, and 40 CFR § 127.
 - (2) If the permittee monitors any pollutant more frequently than required by the permit using test procedures approved under 40 CFR § 136 or, in the case of sludge use or disposal, approved under 40 CFR § 503, or as specified in the permit, the results of such monitoring shall be included in the calculation and reporting of the data submitted in the DMR or sludge reporting form specified by the Director.
 - (3) Calculations for all limitations which require averaging of measurements shall utilize an arithmetic mean unless otherwise specified by the Director in the permit.
- e. Compliance schedules. Reports of compliance or noncompliance with, or any progress reports on, interim and final requirements contained in any compliance schedule of this permit shall be submitted no later than 14 days following each schedule date.
- f. Twenty-four hour reporting.
 - (1) The permittee shall report any noncompliance which may endanger health or the environment. Any information shall be provided orally within 24 hours from the time the permittee becomes aware of the circumstances. A report shall also be provided within 5 days of the time the permittee becomes aware of the circumstances. The report shall contain a description of the noncompliance and its cause; the period of

noncompliance, including exact dates and times), and if the noncompliance has not been corrected, the anticipated time it is expected to continue; and steps taken or planned to reduce, eliminate, and prevent reoccurrence of the noncompliance. For noncompliance events related to combined sewer overflows, sanitary sewer overflows, or bypass events, these reports must include the data described above (with the exception of time of discovery) as well as the type of event (combined sewer overflows, sanitary sewer overflows, or bypass events), type of sewer overflow structure (e.g., manhole, combine sewer overflow outfall), discharge volumes untreated by the treatment works treating domestic sewage, types of human health and environmental impacts of the sewer overflow event, and whether the noncompliance was related to wet weather. As of December 21, 2025 all reports related to combined sewer overflows, sanitary sewer overflows, or bypass events submitted in compliance with this section must be submitted electronically by the permittee to the Director or initial recipient, as defined in 40 CFR § 127.2(b), in compliance with this section and 40 CFR § 3 (including, in all cases, subpart D to part 3), 40 CFR § 122.22, and 40 CFR § 127. The permittee shall electronically submit all reports related to combined sewer overflows, sanitary sewer overflows, or bypass events using CDX (https://cdx.epa.gov/) in accordance with the reporting requirements specified in this permit. The permittee must also sign and certify all electronic submissions in accordance with the signatory requirements specified at 40 CFR § 122.41(k).

- (2) The following shall be included as information which must be reported within 24 hours under this paragraph.
 - (i) Any unanticipated bypass which exceeds any effluent limitation in the permit. (See 40 CFR § 122.41(g).)
 - (ii) Any upset which exceeds any effluent limitation in the permit.
 - (iii) Violation of a maximum daily discharge limitation for any of the pollutants listed by the Director in the permit to be reported within 24 hours. (See 40 CFR § 122.44(g).)
- (3) The Director may waive the written report on a case-by-case basis for reports under 40 CFR § 122.41(l)(6)(ii) of this section if the oral report has been received within 24 hours.
- g. Other noncompliance. The permittee shall report all instances of noncompliance not reported under 40 CFR § 122.41(l)(4), (5), and (6) of this section, at the time monitoring reports are submitted. The reports shall contain the information listed in paragraph (l)(6) of this section.

h. Other information. Where the permittee becomes aware that it failed to submit any relevant facts in a permit application, or submitted incorrect information in a permit application or in any report to the Director, it shall promptly submit such facts or information.

13. Bypass; at 40 CFR § 122.41(m).

- a. Definitions.
 - (1) "Bypass" means the intentional diversion of waste streams from any portion of a treatment facility.
 - (2) "Severe property damage" means substantial physical damage to property, damage to the treatment facilities which causes them to become inoperable, or substantial and permanent loss of natural resources which can reasonably be expected to occur in the absence of a bypass. Severe property damage does not mean economic loss caused by delays in production.
- b. Bypass not exceeding limitations. The permittee may allow any bypass to occur which does not cause effluent limitations to be exceeded, but only if it also is for essential maintenance to assure efficient operation. These bypasses are not subject to the provisions of paragraphs 40 CFR § 122.41(m)(3) and (m)(4) of this section.

c. Notice.

- (1) Anticipated bypass. If the permittee knows in advance of the need for a bypass, it shall submit prior notice, if possible at least ten days before the date of the bypass.
- (2) Unanticipated bypass. The permittee shall submit notice of an unanticipated bypass as required in paragraph (l)(6) of this section (24-hour notice).
- (3) As of December 21, 2025 all notices submitted in compliance with this section must be submitted electronically by the permittee to the Director or initial recipient, as defined in 40 CFR § 127.2(b), in compliance with this section and 40 CFR § 3 (including, in all cases, subpart D to part 3), 40 CFR § 122.22, and 40 CFR § 127. Part 127 is not intended to undo existing requirements for electronic reporting. Prior to this date, and independent of part 127, permittees may be required to report electronically if specified by a particular permit or if required to do so by state law.

d. Prohibition of bypass.

- (1) Bypass is prohibited, and the Director may take enforcement action against a permittee for bypass, unless:
 - (i) Bypass was unavoidable to prevent loss of life, personal injury, or severe property damage;
 - (ii) There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate back-up equipment should have been installed in the exercise of reasonable engineering judgment to prevent a bypass which occurred during normal periods of equipment downtime or preventative maintenance; and
 - (iii)The permittee submitted notices as required under paragraph (m)(3) of this section.
- (2) The Director may approve an anticipated bypass, after considering its adverse effects, if the Director determines that it will meet the three conditions listed above in paragraph (m)(4)(i) of this section.

14. Upset; at 40 CFR § 122.41(n).

- a. Definition. "Upset" means an exceptional incident in which there is unintentional and temporary noncompliance with technology-based permit effluent limitations because of factors beyond the reasonable control of the permittee. An upset does not include noncompliance to the extent cause by operational error, improperly designed treatment facilities, inadequate treatment facilities, lack of preventative maintenance, or careless or improper operation.
- b. Effect of an upset. An upset constitutes an affirmative defense to an action brought for noncompliance with such technology-based permit effluent limitations if the requirements of paragraph (n)(3) of this section are met. No determination made during administrative review of claims that noncompliance was caused by upset, and before an action for noncompliance, is final administrative action subject to judicial review.
- c. Conditions necessary for a demonstration of upset. A permittee who wishes to establish the affirmative defense of upset shall demonstrate, through properly signed, contemporaneous operating logs, or other relevant evidence that:
 - (1) An upset occurred and that the permittee can identify the cause(s) of the upset;
 - (2) The permitted facility was at the time being properly operated; and
 - (3) The permittee submitted notice of the upset as required in paragraph (l)(6)(ii)(B) of this section (24-hour notice).

- (4) The permittee complied with any remedial measures required under paragraph (d) of this section.
- d. Burden of proof. In any enforcement proceeding the permittee seeking to establish the occurrence of an upset has the burden of proof.
- 15. Reopener Clause; at 40 CFR § 122.44(c).

For any permit issued to a treatment works treating domestic sewage (including "sludge-only facilities"), the Director shall include a reopener clause to incorporate any applicable standard for sewage sludge use or disposal promulgated under section 405(d) of the CWA. The Director may promptly modify or revoke and reissue any permit containing the reopener clause required by this paragraph if the standard for sewage sludge use or disposal is more stringent than any requirements for sludge use or disposal in the permit, or controls a pollutant or practice not limited in the permit.

16. Minor modifications of permits; at 40 CFR § 122.63.

Upon the consent of the permittee, the Director may modify a permit to make the corrections or allowances for changes in the permitted activity listed in this section, without following the procedures of 40 CFR § 124. Any permit modification not processed as a minor modification under this section must be made for cause and with 40 CFR § 124 draft permit and public notice as required in 40 CFR § 122.62. Minor modifications may only:

- a. Correct typographical errors;
- b. Require more frequent monitoring or reporting by the permittee;
- c. Change an interim compliance date in a schedule of compliance, provided the new date is not more than 120 days after the date specified in the existing permit and does not interfere with attainment of the final compliance date requirement; or
- d. Allow for a change in ownership or operational control of a facility where the Director determines that no other change in the permit is necessary, provided that a written agreement containing a specific date for transfer of permit responsibility, coverage, and liability between the current and new permittees has been submitted to the Director.
- e. Change the construction schedule for a discharger which is a new source. No such change shall affect a discharger's obligation to have all pollution control equipment installed and in operation prior to discharge under 40 CFR § 122.29.
- f. Delete a point source outfall when the discharge from that outfall is terminated and does not result in discharge of pollutants from other outfalls except in accordance with permit limits.

g. Incorporate conditions of a POTW pretreatment program that has been approved in accordance with the procedures in 40 CFR § 403.11 (or a modification thereto that has been approved in accordance with the procedures in 40 CFR § 403.18) as enforceable conditions of the POTW's permits.

17. Termination of permits; at 40 CFR § 122.64.

- a. The following are causes for terminating a permit during its term, or for denying a permit renewal application:
 - (1) Noncompliance by the permittee with any conditions of the permit;
 - (2) The permittee's failure in the application or during the permit issuance process to disclose fully all relevant facts, or the permittee's misrepresentation of any relevant facts at any time;
 - (3) A determination that the permitted activity endangers human health or the environment and can only be regulated to acceptable levels by permit modification or termination; or
 - (4) A change in any condition that requires either a temporary or permanent reduction or elimination of any discharge or sludge use or disposal practice controlled by the permit (for example, plant closure or termination of discharge by connection to a POTW).

18. Availability of Reports; pursuant to CWA § 308

Except for data determined to be confidential under 40 CFR § 2, all reports prepared in accordance with the terms of this permit shall be available for public inspection at the offices of the Regional Administrator. As required by the CWA, permit applications, permits, and effluent data shall not be considered confidential.

19. Removed Substances; pursuant to CWA § 301

Solids, sludges, filter backwash, or other pollutants removed in the course of treatment or control of wastewaters shall be disposed of in a manner such as to prevent any pollutant from such materials entering waters of the U.S.

20. Severability; pursuant to CWA § 512

The provisions of this permit are severable, and if any provision of this permit, or the application of any provision of this permit to any circumstance, is held invalid, the application of such provision to other circumstances, and remainder of this permit, shall not be affected thereby.

21. Civil and Criminal Liability; pursuant to CWA § 309

Except as provided in permit conditions on "Bypass" and "Upset", nothing in this permit shall be construed to relieve the permittee from civil or criminal penalties for noncompliance.

22. Oil and Hazardous Substances Liability; pursuant to CWA § 311

Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties to which the permittee is or may be subject under Section 311 of the CWA.

23. State, Tribe, or Territory Law; pursuant to CWA § 510


Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the operator from any responsibilities, liabilities, or penalties established pursuant to any applicable State, Tribe, or Territory law or regulation under authorities preserved by CWA § 510.

Attachment A: Definitions


- 1. "Average monthly discharge limitation" means the highest allowable average of "daily discharges" over a calendar month, calculated as the sum of all "daily discharges" measured during a calendar month divided by the number of "daily discharges" measured during that month.
- 2. "Average weekly discharge limitation" means the highest allowable average of "daily discharges" over a calendar week, calculated as the sum of all "daily discharges" measured during a calendar week divided by the number of "daily discharges" measured during that week.
- 3. "Best Management Practices" or "BMPs" are schedules of activities, prohibitions of practices, maintenance procedures, and other physical, structural, and/or managerial practices to prevent or reduce the pollution of waters of the U.S. BMPs include treatment systems, operating procedures, and practices to control: plant site runoff, spillage or leaks, sludge or waste disposal, or drainage from raw material storage. BMPs may further be characterized as operational, source control, erosion and sediment control, and treatment BMPs.
- 4. A "composite" sample means a time-proportioned mixture of not less than eight discrete aliquots obtained at equal time intervals (e.g., 24-hour composite means a minimum of eight samples collected every three hours). The volume of each aliquot shall be directly proportional to the discharge flow rate at the time of sampling, but not less than 100 ml. Sample collection, preservation, and handling shall be performed as described in the most recent edition of 40 CFR § 136.3, Table II. Where collection, preservation, and handling procedures are not outlined in 40 CFR § 136.3, procedures outlined in the 18th edition of Standard Methods for the Examination of Water and Wastewater shall be used.
- 5. A "daily discharge" means the "discharge of a pollutant" measured during a calendar day or any 24-hour period that reasonably represents the calendar day for purposes of sampling. For pollutants with limitations expressed in units of mass, the "daily discharge" is calculated as the total mass of the pollutant discharged over the day. For pollutants with limitations expressed in other units of measurement, the "daily discharge" is calculated as the average measurement of the pollutant over the day.
- 6. A "daily maximum allowable effluent limitation" means the highest allowable "daily discharge."
- 7. A "DMR" is a "Discharge Monitoring Report" that is an EPA uniform national form, including any subsequent additions, revisions, or modifications for reporting of selfmonitoring results by the permittee.
- 8. A "grab" sample is a single sample collected at a particular time and place that represents the composition of the discharge only at that time and place. Sample collection, preservation, and handling shall be performed as described in the most recent edition of 40 CFR § 136.3, Table II. Where collection, preservation, and handling procedures are

- not outlined in 40 CFR § 136.3, procedures outlined in the 18th edition of Standard Methods for the Examination of Water and Wastewater shall be used.
- 9. The "method detection limit" or "MDL" is the minimum concentration of an analyte that can be detected with 99% confidence that the analyte concentration is distinguishable from the method blank results, as defined by a specific laboratory method in 40 CFR § 136. The procedure for determination of a laboratory MDL is in 40 CFR § 136, Appendix B.
- 10. The "minimum level" or "ML" is the concentration at which the entire analytical system must give a recognizable signal and acceptable calibration point. The ML is the concentration in a sample that is equivalent to the concentration of the lowest calibration standard analyzed in a specific analytical procedure, assuming that all the method-specific sample weights, volumes, and processing steps have been followed (as defined in EPA's draft National Guidance for the Permitting, Monitoring, and Enforcement of Water Quality-Based Effluent Limitations Set Below Analytical Detection/Quantitative Levels, March 22, 1994). If a published method-specific ML is not available, then an interim ML shall be calculated. The interim ML is equal to 3.18 times the published method-specific MDL rounded to the nearest multiple of 1, 2, 5, 10, 20, 50, etc. (When neither an ML nor MDL are available under 40 CFR § 136, an interim ML should be calculated by multiplying the best estimate of detection by a factor of 3.18; when a range of detection is given, the lower end value of the range of detection should be used to calculate the ML.) At this point in the calculation, a different procedure is used for metals, than non-metals:
 - a. For metals, due to laboratory calibration practices, calculated MLs may be rounded to the nearest whole number.
 - b. For non-metals, because analytical instruments are generally calibrated using the ML as the lowest calibration standard, the calculated ML is then rounded to the nearest multiple of (1, 2, or 5) x 10n, where n is zero or an integer. (For example, if an MDL is 2.5 μ g/l, then the calculated ML is: 2.5 μ g/l x 3.18 = 7.95 μ g/l. The multiple of (1, 2, or 5) x 10n nearest to 7.95 is 1 x 101 = 10 μ g/l, so the calculated ML, rounded to the nearest whole number, is 10 μ g/l.)
- 11. A "NODI(B)" means that the concentration of the pollutant in a sample is not detected. NODI(B) is reported when a sample result is less than the laboratory's MDL.
- 12. A "NODI(Q)" means that the concentration of the pollutant in a sample is detected but not quantified. NODI(Q) is reported when a sample result is greater than or equal to the laboratory's MDL, but less than the ML.

Attachment B: Location Maps



Attachment C: Wastewater Flow Schematic



Attachment D: 401 Water Quality Certification (Order #2022-05)

WATER QUALITY CERTIFICATION CONDITIONS

WQC Order No. **2022-05** ("Order") specifies conditions necessary to assuring that discharge(s) from the Navy Fena Water Treatment Plant to the Namo River will comply with water quality requirements. This water quality certification is subject to the conditions within this Order and is based on the terms and conditions contained in the final facility NPDES Permit.

This Order does not constitute authorization of the permitted activities by any other local or federal agency or private person or entity. This Order does not excuse the permit holder from the obligation to obtain any other necessary approvals, authorizations or permits.

The Guam EPA Administrator (Administrator) may, on the Administrator's own motion, or the application of any person, modify, suspend, or revoke the Order, if the Administrator determines that:

- 1. There is a violation of any condition of the Order;
- 2. The Order was obtained by misrepresentation, or failure to disclose fully all relevant facts; or
- 3. There is an unreasonable or significant change in the scope of the project and activity. 22 GAR 2 55106(1).

In accordance with 40 CFR 124.53(e)(3), Guam EPA has determined that no condition in the draft facility NPDES permit may be made less stringent without violating requirements in Guam territorial law, including water quality standards.

A. GENERAL CONDITIONS

- A1. For purposes of this Order, the term "applicant" shall mean U.S. Environmental Protection Agency, the entity seeking certification.
- A2. For purposes of this Order, the "permittee" or the United States Navy ("Navy") shall mean the applicant for an NPDES permit to authorize the discharge of treated effluent from the facility to the Namo River.
- A3. All submittals required by this Order shall be sent to the Guam Environmental Protection Agency Attn: 401 Federal Permit Manager, Non-Point Source Program, EMAS Division, 3304 Mariner Avenue, Bldg. 17-3304, Barrigada, Guam 96913, AND via email to jesse.cruz@epa.guam.gov and maricar.quezon@epa.guam.gov. The submittals shall be identified with WQC Order #2022-05 and include the NPDES

Permit Number, certifying representative's name, title, mailing address and phone number. 22 GAR 2 - \$5106(j)(4)

- A4. Discharges authorized by this Order are limited to the discharges described in draft NPDES Permit No. GU0020389.
- A5. As conditioned in the draft facility NPDES Permit, the Navy shall submit the following monitoring documents to Guam EPA quarterly, consistent with provision A3. above.
 - An electronic or paper Discharge Monitoring Report (DMR);
 - Receiving water monitoring results (NPDES Permit Part IE. Table 4: (Station URI and Station UR-2) Receiving Water Monitoring Requirements); and
 - Receiving water monitoring results at UR-I and UR-2 for narrative water quality standards described in Part I.A.5.

22 GAR 2 - \$5106(j)(4)

A6. The Navy shall provide the coordinates of the upstream and downstream receiving water monitoring stations (UR-I and UR-2) to Guam EPA consistent with provision A3. 22 GAR 2 – §5106(j)(4)

A7. U.S. EPA R-9 shall submit to Guam EPA a signed Statement of Understanding of Water Quality Certification Conditions. (see Attachment A for an example) per condition A3. 22 GAR 2 – §5106(j)(4)

B. WATER QUALITY CONDITIONS

B1. Point source discharge(s) to waterbodies under the jurisdiction of Guam EPA must be consistent with the antidegradation policy in 22 GAR 2 - §5101(b).

C. EMERGENCY/CONTINGENCY MEASURES:

40 CFR Part 1 10, 40 CFR Part 117, or 40 CFR Part 302

- C1. The Navy shall develop and implement a Spill Prevention and Containment Plan.
- C2. The Navy shall have adequate and appropriate spill response materials on hand to respond to emergency release of oil, petroleum or any other material into waters of the territory.
- C3. Any unpermitted discharge into territorial waters or onto land with a potential for entry into territorial waters, is prohibited. If this occurs, the permittee shall immediately take the following actions:

- Cease operations at the location of the violation or spill.
- Assess the cause of the water quality problem and take appropriate measures to correct the problem and/or prevent further environmental damage.
- Notify Guam EPA of the failure to comply. All petroleum spills shall be reported immediately to:
 - 1. Guam's Emergency 911 system
 - 2. Guam EPA's 24-Hour Spill Response Team at (671) 888-6488 or during working hours (671) 300-4751
 - 3. US Coast Guard Sector Guam (671) 355-4824
 - 4. National Response Center 1-800-424-8802
 - Submit a detailed written report to Guam EPA within five days of noncompliance that describes the nature of the event, corrective action taken and/or planned, steps to be taken to prevent a recurrence, results of any samples taken, and any other pertinent information.
- C4. Compliance with this condition does not relieve the Navy from responsibility to maintain continuous compliance with the terms and conditions of this Order or the resulting liability from failure to comply.
- C5. Submittal or reporting of any of this information does not provide relief from any subsequent enforcement actions for unpermitted discharges to waters of the United States.

D. Timing Requirements

D1. This Order is valid for five (5) Years from Date of Certification, unless otherwise approved by the Guam EPA Administrator.

E. Reporting and Notification Requirement Conditions

- E1. The Navy shall provide notice to Guam EPA consistent with Condition A3:
 - Immediately upon discovery of noncompliance with the provisions of this Order.
- E2. A Notice of Violation/Work Stop Order will be issued if certification conditions are not adhered to or when significant or sustained water quality degradation occurs. Work or discharge shall be suspended or halted until the permittee addresses environmental problems/concerns to Guam EPA's satisfaction. Guam EPA may also levy penalties and fines (10 GCA *471 I l). Invalidity or enforceability of one or more provisions of this certification shall not affect any other provision of this certification.