Inventory of U.S. Greenhouse Gas Emissions and Sinks 1990-2022: Updates Under Consideration for Underground Natural Gas Storage Well Emission Events

This memo discusses updates under consideration for the 2024 *Inventory of U.S. Greenhouse Gas Emissions and Sinks* (GHGI) to incorporate emissions for anomalous large emission events at underground natural gas storage wells.

The 2019 Refinement to the 2006 IPCC Guidelines for National Greenhouse Gas Inventories¹ included guidance on calculating emissions from "anomalous leak events" for national GHG Inventories. The 2019 IPCC Refinement provides examples of anomalous events, including emergency pressure relieving equipment and well blowouts, and specifies that these events should be evaluated and estimated on a case-by-case basis using the best available data.

The update under consideration would implement this guidance by incorporating additional estimates for anomalous leak events into the GHGI, focusing in this memo on the underground storage well source. The events considered include blowouts and other large emission release events occurring at wells.

1 Current GHGI Methodology

The current GHGI includes emissions from three large emission events for production wells, and one underground natural gas storage (UNGS) facility event.² EPA released a memo for the 2018 GHGI that presented methane emissions from the Aliso Canyon leak in 2015 and 2016.³ EPA used the California Air Resources Board's (CARB) method of estimating methane emitted from the leak.⁴

Using CARB's method, the methane emissions from the Aliso Canyon event were 78,350 metric tons (mt) of methane (CH₄) in 2015 and 21,288 mt CH₄ in 2016. EPA included both 2015 and 2016 emission estimates from the Aliso Canyon event in the 2018 GHGI.

The GHGI also includes equipment leak emissions (average annual emissions of around 13,000 mt CH₄) from UNGS wells but does not otherwise account for similar non-routine emissions events from these UNGS facilities.

2 Available Data

A recent article from Li et al.,⁵ "A national estimate of U.S. underground natural gas storage incident emissions," analyzed UNGS event emissions from 1984-2016. Li et al. 2022 used data from Folga et al. 2016,⁶ which contains incidents reported to the Pipeline and Hazardous Materials Safety Administration (PHMSA)⁷ for the years 1984-

https://www.arb.ca.gov/research/aliso_canyon/aliso_canyon_methane_emissions-arb_final.pdf.

¹ 2019 Refinement to the 2006 IPCC Guidelines for National Greenhouse Gas Inventories, Volume 2, Energy. Available online at: https://www.ipcc-nggip.iges.or.jp/public/2019rf/vol2.html.

² https://www.epa.gov/system/files/documents/2022-04/2022_ghgi_update_-_blowouts.pdf

³ <u>https://www.epa.gov/sites/default/files/2017-01/documents/memo_on_aliso_canyon_estimate_for_u.s._ghgi_1.10.17.pdf</u>

⁴ For more information on the leak measurements and calculations, please see California Air Resources Board. Determination of Total Methane Emission from the Aliso Canyon Natural Gas Leak Incident. October 21, 2016.

⁵ Li, H Z et al. 2022. A national estimate of U.S. underground natural gas storage incident emissions. *Environmental Research Letters*, 17: 084013. <u>https://doi.org/10.1088/1748-9326/ac8069</u>

⁶ Folga, S et al. 2016. U.S. Natural Gas Storage Risk-Based Ranking Methodology and Results. Technical Report. Office of Scientific and Technical Information, Department of Energy. <u>https://doi.org/10.2172/1337151</u>

⁷ <u>https://www.phmsa.dot.gov/data-and-statistics/pipeline/distribution-transmission-gathering-lng-and-liquid-accident-and-incident-data</u>

2016; and Evans and Chadwick 2009,⁸ which describes worldwide historical UNGS blowout events from 1953-2006.

PHMSA collects data for incidents at UNGS facilities. The available data is split into three distinct subgroups based on the reported PHMSA data.

The subgroups and reported data, as used in Li et al., are as follows:

- 1984-2001: Total property damage cost
- 2002-2009: Cost of gas lost
- 2010-2016: Gas release volume

Li et al. used different methods to estimate methane emissions for each subgroup due to the differences in data. The most recent time frame of incidents reported to PHMSA (i.e., 2010-2016) included the gas release volume, so the method was more straightforward than the methods used for the other two time frames. For reports with the cost of gas lost (i.e., 2002-2009), the gas volume was estimated using the monthly wellhead gas price from the U.S. Energy Information Administration (EIA). There was limited information available for events reported to PHMSA from 1984-2001. The leak size associated with events reported during this time frame was sometimes included in the narrative sections of PHMSA reports. For events without the cost of gas lost or gas release volumes, Li et al. used a formula based on fluid mechanics paired with the cross-section area of the leak and event duration, which was included in the 1984-2001 PHMSA reports, to estimate the methane leak volume.

3 Analysis of Available Data

The Li et al. 2022 data included 69 UNGS events between 1990 and 2016 with data available to estimate gas releases. EPA reviewed Li et al. to determine whether the events occurred at storage wells, or if the events were for other types of incidents at the UNGS facility. Of the 69 incidents, EPA identified 10 events that occurred at storage wells. Of these, five were blowouts EPA classified the events as blowouts based on the proposed definition of a "well blowout" in the recent subpart W proposed rule, which identified blowout events as having "a complete loss of well control for a long duration of time".⁹ Evidence of wellhead failure, casing failure, or a casing leak for these five events was also indicated in the narrative information. The other five well events not classified as blowouts were periods of shorter gas release due to well equipment damage. The records also noted evidence of well equipment damage for these events.

Li et al. presented an estimate of methane release from the large events without taking into account methane combustion. Combustion reduces methane release emissions from events and increases CO_2 emissions. EPA reviewed supporting information available for all 10 storage well events and identified 4 events where the gas ignited or there was an explosion.

The percentage of gas that was combusted was not available in Li et al. or the supporting information for each event. For the purposes of developing a preliminary estimate, EPA applied a combustion efficiency of 60 percent to events that were identified as including combustion. A study by Maasakkers et al. characterized emissions from a well blowout in Louisiana.¹⁰ In the study, Maasakkers et al. assume a combustion efficiency range of 60 to 99 percent when emissions are combusted using a flare. The 60 percent estimate is on the lower range of combustion efficiencies used for well blowout events with flared emissions. Combustion resulting from UNGS

⁸ Evans, DJ & Chadwick, RA. 2009. (eds) Underground Gas Storage: Worldwide Experiences and Future Development in the UK and Europe. *The Geological Society, London, Special Publications*, 313: 173–216. <u>https://doi.org/10.1144/SP313.12</u>

⁹ EPA. Greenhouse Gas Reporting Rule: Revisions and Confidentiality Determinations for Petroleum and Natural Gas Systems. EPA-HQ-OAR-2023-0234; FRL-10246-01- OAR https://www.govinfo.gov/content/pkg/FR-2023-08-01/pdf/2023-14338.pdf

¹⁰ Maasakkers, JD et al. 2022. Reconstructing and quantifying methane emissions from the full duration of a 38-day natural gas well blowout using space-based observations. *Remote Sensing of Environment*, 270: 112755. <u>https://doi.org/10.1016/j.rse.2021.112755</u>

November 2023

well events is assumed to not oxidize methane as efficiently as when flared, which is why the lowest estimate was applied.

EPA identified one high-emission storage well event, the Moss Bluff incident, that occurred in 2004 and released gas containing 107,933 mt CH₄. Based on supporting documentation, the fire resulting from the Moss Bluff explosion burned for six days until the fire self-extinguished, indicating a fraction of the released methane was combusted.¹¹ After applying a combustion efficiency of 60 percent, EPA calculated emissions from the Moss Bluff event to be 43,173 mt CH₄ and 203,310 mt CO₂. For the Moss Bluff incident, the description from Evans and Chadwick 2009 included information about how the escaping gas ignited and caused the wellhead to fail.

Another event with possible emissions combustion occurred at the Yaggy field in Kansas in 2001. The Yaggy event released gas containing 2,572 mt CH₄. According to Evans and Chadwick 2009, there was a fire and an explosion because of the event. Applying a 60 percent combustion efficiency factor, 1,092 mt CH₄ were calculated to be emitted.

Appendix A includes further information for each of the 10 storage well events identified by EPA in the Li et al. data.

EPA is also considering utilizing PHMSA data beyond what is presented in Li et al. 2022 to capture additional large emission events. To evaluate large emission events at UNGS wells from 2017 to the present, EPA would review data reported to PHMSA. PHMSA reports include a detailed narrative section describing each event. EPA would review the narrative sections to determine whether an event occurred at a storage well and if the event can be described as a well blowout. Once the UNGS well events are identified, EPA would use the quantity of gas released from the PHMSA report to calculate the amount of methane released. EPA would then investigate if there was ignition of gas or an explosion during the event to see if the combustion efficiency should be applied to the amount of methane released to account for combustion.

4 Time Series Considerations

Currently, Aliso Canyon is the only storage well blowout incident included in the overall time series. EPA is considering incorporating the 10 identified storage well events into the GHGI as one-off events and including emissions for each in the year the event occurred. UNGS events occurred in 10 inventory years with one event occurring each year.

5 Preliminary National Emissions Estimates

EPA analyzed the scope of incident emissions from 1990-2016, as presented in Li et al, coupled with considerations for the combustion efficiency of events with a fire or explosion. Table 1 and Table 2 below present the number of incidents, volume of gas lost, CH₄ released, CH₄ emissions, and CO₂ combusted emissions by year and by state, respectively.

¹¹ Djizanne, H et al. 2014. Blowout in Gas Storage Caverns. *Oil & Gas Science and Technology - Revue d'IFP Energies nouvelles*, 69: 1251-1267. <u>https://doi.org/10.2516/ogst/2013208ff</u>.

November 2023

Year	Number of Volume of Gas CH ₄ Release CH ₄ Emissions				
	Incidents	Lost (mcf)	(mt) ^a	(mt) ^b	CO₂ Emissions (mt) ^c
1990	0	0	0	0	0
1991	0	0	0	0	0
1992	1	14	0.3	0.1	0.5
1993	0	0	0	0	0
1994	0	0	0	0	0
1995	0	0	0	0	0
1996	0	0	0	0	0
1997	0	0	0	0	0
1998	1	8,500	153	153	0
1999	0	0	0	0	0
2000	0	0	0	0	0
2001	1	143,000	2,572	1,029	4,846
2002	1	10,185	183	183	0
2003	1	350,000	6,296	6,296	0
2004	1	6,000,000	107,933	43,173	203,310
2005	0	0	0	0	0
2006	1	675,000	12,142	12,142	0
2007	0	0	0	0	0
2008	0	0	0	0	0
2009	0	0	0	0	0
2010	1	1,970	35	14	69
2011	1	42,919	772	772	0
2012	0	0	0	0	0
2013	0	0	0	0	0
2014	0	0	0	0	0
2015 ^d	1	4,500,000	78,350	78,350	0
2016 ^d	1	1,200,000	21,288	21,288	0
Total	10	12,931,588	229,726	163,401	208,226

Table 1. Total Incident Emissions by Year from 1990-2016 (mt CH₄)

^a Methane released by the event, estimated using methane composition and density data from the inventory.

^b Methane emissions from the event, taking into account any combustion by applying a 60 percent combustion efficiency value to events indicated as including gas ignition or explosion.

^c Carbon dioxide emissions from events indicated as including gas ignition or explosion, calculated by applying a 60 percent combustion efficiency value. Methane and carbon dioxide composition data from the inventory was used to estimate carbon dioxide emissions.

^d The Aliso Canyon event is included for 2015 and 2016 in Table 1. These values are currently in the GHGI and would continue to be used in the updated under consideration.

UNGS well events occurred in 10 inventory years with one event occurring each year. Other than 2015, which includes emissions from Aliso Canyon, the year with the highest methane emission is the year 2004 with 43,173 mt of methane emissions. Incidents with emissions lower than 2,000 mt of methane took place in the years 1992, 1998, 2001, 2010, and 2011.

State	Number of Incidents	Volume of Gas Lost (mcf)	CH₄ Release (mt)ª	CH₄ Emissions (mt) ^b	CO₂ Emissions (mt) ^c
ТХ	1	6,000,000	107,933	43,173	203,310
CA ^d	1	5,700,000	99,638	99,638	-
CO	1	675,000	12,142	12,142	-
LA	1	350,000	6,296	6,296	-
KS	2	153,185	2,756	1,212	4,846
ОК	2	51,419	925	925	-
IA	1	1,970	35	14	69
КҮ	1	14	0.3	0.1	0.5
Total	10	12,931,588	229,726	163,401	208,226

Table 2. Total Incident emissions by State from 1990-2016 (mt of CH4)

^a Methane released by the event, estimated using methane composition and density data from the inventory.

^b Methane emissions from the event, taking into account any combustion by applying a 60 percent combustion efficiency value to events indicated as including gas ignition or explosion.

^c Carbon dioxide emissions from events indicated as including gas ignition or explosion, calculated by applying a 60 percent combustion efficiency value. Methane and carbon dioxide composition data from the inventory was used to estimate carbon dioxide emissions.

^d The Aliso Canyon event (already incorporated into the Inventory) is included with California in Table 2.

The state with the highest UNGS well incident emissions identified in this analysis, other than California, from 1990-2016 is Texas, which is due to the Moss Bluff incident. The most incidents at storage facilities occurred in Kansas and Oklahoma, with two events occurring in both states.

6 Requests for Stakeholder Feedback

EPA seeks stakeholder feedback on the updates under consideration discussed in this memo and the questions below.

- 1. EPA seeks feedback on including emissions resulting from UNGS well events to the time series.
- 2. EPA seeks feedback on the preliminary combustion efficiency value of 60 percent.
- 3. EPA seeks feedback on additional data sources or studies with information on anomalous leak events at storage wells.
- 4. EPA seeks feedback on whether and how events other than storage well events from Li et al. could be incorporated into the GHGI.

Appendix A

Field Name	State	Date	Leak Size (mcf)	CH₄ Release	CH ₄ Emissions	CO₂ Emissions	Reference/PHMSA Report Number ^a
				(mt)	(mt)	(mt)	
Aliso Canyon	CA	10/23/2015 – 2/18/2016	5,000,000	99,638	99,638	-	(See Li et al. 2015)
Moss Bluff Storage	ТΧ	8/19/2004-8/26/2004	6,000,000	115,560	46,224	203,310	(See Evans and Chadwick 2009)
Fort Morgan	CO	10/1/2006	675,000	13,001	13,001	-	(See Evans and Chadwick 2009)
Magnolia Gas Storage	LA	12/24/2003	350,000	6,741	6,741	-	(See Evans and Chadwick 2009)
Yaggy	KS	1/1/2001	143,000	2,754	1,102	4,846	(See Evans and Chadwick 2009)
Edmond	OK	5/24/2011	42,919	827	827	-	20110199
Cunningham	KS	10/1/2002	10,185	196	196	-	20020084
Stuart Storage	ОК	12/10/1998	8,500	164	164	-	19990009
Redfield	IA	1/10/2010	1,970	38	15	69	20100019
Hawesville N W	KY	6/1/1992	14	0.3	0.1	0.5	19920093

^a Additional information, including the event narrative, can be found for events with PHMSA numbers from the downloadable files at the following website: https://www.phmsa.dot.gov/data-and-statistics/pipeline/distribution-transmission-gathering-lng-and-liquid-accident-and-incident-data. For events without a PHMSA report number, the reference with narrative information is listed instead.